



FCC 47 CFR MPE REPORT

Music Tribe Commercial MY Sdn. Bhd

Portable Speaker

Model Number: MPA100BT

FCC ID: QWHMPA100BTV2

Applicant:	Music Tribe Commercial MY Sdn. Bhd
Address:	1-17-02,SUNTECH @ PENANG CYBERC1-12-01 SUNTECH @ PENANG
	CYBERCITY LINTANG MAYANG PASIR 3, BAYAN BARU PULAU
	PINANG, MALAYSIA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2308209
Date of Test:	Jul. 17 ~ Aug. 15, 2023
Date of Report:	Aug. 16, 2023

Maximum Permissible Exposure

1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

1.1. Limits for Maximum Permissible Exposure (MPE)

(a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	0.88	1.225
	2441	-0.05	0.989
	2480	-0.60	0.871
π /4-DQPSK	2402	0.71	1.178
	2441	-0.31	0.931
	2480	-0.68	0.855
8-DPSK	2402	0.99	1.256
	2441	-0.12	0.973
	2480	-0.58	0.875
BLE 1M	2402	0.76	1.191
	2440	-0.21	0.953
	2480	-0.73	0.845
BLE 2M	2402	0.97	1.250
	2440	0.00	1.000
	2480	-0.46	0.899

3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	0.88	0±1	1	1.5	1.413	0.0004	1	Complies
π /4-DQPSK	0.71	0±1	1	1.5	1.413	0.0004	1	Complies
8-DPSK	0.99	0±1	1	1.5	1.413	0.0004	1	Complies
BLE 1M	0.76	0±1	1	1.5	1.413	0.0004	1	Complies
BLE 2M	0.97	0±1	1	1.5	1.413	0.0004	1	Complies

End of Test Report

