

Date: 2003-02-28

TEST REPORT

Page 1 of 21

No.: HM109661

FCC PART 15 SUBPART C CERTIFICATION REPORT

FOR LOW POWER TRANSMITTER

TEST REPORT No.: HM109661

Equipment Under Test [EUT]:

Model Number:

Applicant:

FCC ID :

Radio Control Vehicle

TC49MHzP

Toy Century Industrial Co., Ltd.

QXATC49MHzP

Date: 2003-02-28

TEST REPORT

Page 2 of 21

No.: HM109661

CONTENT:

Cover
Content
Conclusion

Page 1 of 21
Page 2-3 of 21
Page 4 of 21

1.0 **General Details**

- 1.1 Test Laboratory
- 1.2 Applicant Details
Applicant
HKSTC Code Number for Applicant
Manufacturer
- 1.3 Equipment Under Test [EUT]
Description of EUT operation
- 1.4 Date of Order
- 1.5 Submitted Sample
- 1.6 Test Duration
- 1.7 Country of Origin
- 1.8 Additional Information of EUT

Page 5 of 21

Page 5 of 21

Page 6 of 21

Page 6 of 21

Page 6 of 21

Page 6 of 21

Page 6 of 21

Page 7 of 21

2.0 **Technical Details**

- 2.1 Investigations Requested
- 2.2 Test Standards and Results Summary

Page 8 of 21

Page 8 of 21

3.0 **Test Results**

- 3.1 Emission
- 3.2 Bandwidth Measurement

Page 9-13 of 21

Page 14-15 of 21

Date: 2003-02-28

TEST REPORT

Page 3 of 21

No.: HM109661

Appendix A

List of Measurement Equipment

Page 16 of 21

Appendix B

Duty Cycle Correction During 100 msec

Page 17-18 of 21

Appendix C

Modification Method

Page 19-21 of 21

Appendix D

Photographs

Page 19-21 of 21

Date: 2003-02-28

TEST REPORT

Page 4 of 21

No.: HM109661

CONCLUSION

The submitted product was deemed to have **COMPLIED** after modification with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

Verify by

Patrick Wong
for Chief Executive

Date: 2003-02-28

TEST REPORT

Page 5 of 21

No.: HM109661

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate
New Territories, Hong Kong

Telephone: 852 2666 1888
Fax: 852 2664 4353

1.2 Applicant Details **Applicant**

TOY CENTURY INDUSTRIAL CO., LTD.
Unit 1010-1015, 10/F., Tower B, New Mandarin Plaza,
No. 14 Science Museum Road, Tsim Sha Tsui East,
Kowloon, Hong Kong.

Telephone: 852 2790 3612
Fax: 852 2304 1863

HKSTC Code Number for Applicant

BVP001

Manufacturer

TOY CENTURY INDUSTRIAL CO., LTD.
Unit 1010-1015, 10/F., Tower B, New Mandarin Plaza,
No. 14 Science Museum Road, Tsim Sha Tsui East,
Kowloon, Hong Kong.

Telephone: 852 2790 3612
Fax: 852 2304 1863

Date: 2003-02-28

TEST REPORT

Page 6 of 21

No.: HM109661

1.3 Equipment Under Test [EUT] Description of Sample

Product: Radio Control Vehicle
Manufacturer: Toys Century Industrial Co., Ltd.
Brand Name: N/A
Model Number: TC49MHzP
Input Voltage: 9Vd.c ("6F22" size battery x 1)
Additional Model Number: K00001, 00040, 17448, 19511, 19522, 19523, 19527, 19528, 19529, 19532, 19533, 19536, 19539, 207, 230, 6661, 6680, 6700, 6705, 6682, 6601, 6800, 6801, 6805, 6683, 6684, 6688, 66881, 6689, 6690, 6691, 6695, 6697, 6698, 66902, 66952, 66982, 66984, 66985, 66986, 66992, 7629, 85928, 9800

1.3.1 Description of EUT Operation

The Equipment Under Test (EUT) is an Toys Century Industrial Co., Ltd., Radio Control Vehicle. The transmitter is a 2 button transmitter. The EUT continues to transmit while button is being pressed, Modulation by Q1 and Q2. and tape is pulse modulation.

1.4 Date of Order

2003-01-16

1.5 Submitted Sample(s):

2 Samples per model

1.6 Test Duration

2003-01-27

1.7 Country of Origin

China

Date: 2003-02-28

TEST REPORT

Page 7 of 21

No.: HM109661

1.8 Additional Information of EUT

	Submitted	Not Available
User Manual	☒	☐
Part List	☒	☐
Circuit Diagram	☒	☐
Printed Circuit Board [PCB] Layout	☒	☐
Block diagram	☒	☐
FCC ID Label	☒	☐

Date: 2003-02-28

TEST REPORT

Page 8 of 21

No.: HM109661

2.0 Technical Details

2.1 Investigations Requested

Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.4:2000 for FCC Certification.

2.2 Test Standards and Results Summary Tables

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental Emissions & Spurious Emissions	FCC 47CFR 15.235	ANSI C63.4:2000	N/A	☒	☐	☐
Radiated Emissions, 30MHz to 1GHz	FCC 47CFR 15.209	ANSI C63.4:2000	Class B	☒	☐	☐
Conducted Emissions on AC, 0.15MHz to 30MHz	FCC 47CFR 15.207	ANSI C63.4:2000	Class B	☐	☐	☒

Note: N/A - Not Applicable

Date: 2003-02-28

TEST REPORT

Page 9 of 21

No.: HM109661

3.0 Test Results

3.1 Emission

3.1.1 Radiated Emissions


Test Requirement:	FCC 47CFR 15.235
Test Method:	ANSI C63.4:2000
Test Date:	2003-01-27
Mode of Operation:	On mode

Test Method:

The sample was placed 0.8m above the ground plane on the OATS *. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigate all operating modes, rotated about all 3 axis (X, Y & Z) to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

*: OATS [Open Area Test Site] located at HKSTC with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 90657.

Test Setup:



Date: 2003-02-28

TEST REPORT

Page 10 of 21

No.: HM109661

Limits for Field Strength of Fundamental Emissions [FCC 47CFR 15.235]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Peak] [μV/m]	Field Strength of Fundamental Emission [Average] [μV/m]
49.82-49.90	100,000	10,000

Results:

Field Strength of Fundamental Emissions						
Peak Value						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	Antenna Polarity
49.86	41.3	10.0	51.3	367.3	100,000	Vertical

Field Strength of Fundamental Emissions						
Average						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	Antenna Polarity
49.86	37.5	10.0	47.5	237.1	100,00	Vertical

According to FCC 47CFR15.35, the limit on the radio frequency emissions as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Remarks:

*: Adjusted by Duty Cycle = -3.8dB

*: Linear interpolations

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ±3.7dB
300MHz to 1GHz +3.0dB / -2.7dB

Date: 2003-02-28

TEST REPORT

Page 11 of 21

No.: HM109661

Limited for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [μV/m]
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results :

Radiated Emissions Quasi-Peak						
Frequency MHz	Measured Level @3m dBμV/m	Correction Factor dBμV/m	Field Strength dBμV/m	Field Strength μV/m	Limit @3m μV/m	Antenna Polarity
99.72	28.1	10.8	38.9	88.1	150	Horizontal
149.58	19.8	11.1	30.9	35.1	150	Horizontal
199.44	18.6	12.4	31.0	35.5	150	Horizontal
249.30	< 1.0	15.9	< 16.9	< 7.0	200	Vertical
299.16	< 1.0	17.4	< 18.4	< 8.3	200	Vertical
349.02	< 1.0	17.2	< 18.2	< 8.1	200	Vertical
398.88	< 1.0	18.8	< 19.8	< 9.8	200	Vertical
448.74	< 1.0	19.7	< 20.7	< 10.8	200	Vertical
498.60	< 1.0	20.6	< 21.6	< 12.0	200	Vertical

Remarks:

*: Linear interpolations

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty = 30MHz to 300MHz ±3.7dB
300MHz to 1GHz +3.0dB / -2.7dB


3.1.1 Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.4:2000
Test Date:	2003-01-27
Mode of Operation:	On mode

Test Method:

The test was performed in accordance with ANSI C63.4:2000, with the following: an initial measurement was performed in peak and average detection mode on the live line. Any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Test Setup:



Date: 2003-02-28

TEST REPORT

Page 13 of 21

No.: HM109661

Limit for Conducted Emissions (FCC 47 CFR 15.107):

Frequency Range [MHz]	Quasi-Peak Limits [dBμV]	Average [dBμV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram labelled as (QP and AV).

Results: N/A

The EUT is operated by internal battery power only, therefore power line conducted emission was deemed unnecessary.

Remarks:

Calculated measurement uncertainty = $\pm 2.3\text{dB}$

Date: 2003-02-28

TEST REPORT

Page 14 of 21

No.: HM109661

3.2 26dB Bandwidth of Fundamental Emission

Test Requirement:	FCC 47 CFR 15.235
Test Method:	ANSI C63.4:2000 (Section 13.1.7)
Test Date:	2003-01-27
Mode of Operation:	On mode

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

Date: 2003-02-28

TEST REPORT


Page 15 of 21

No.: HM109661

Limits for 26 dB Bandwidth of Fundamental Emission:

Frequency Range [MHz]	26dB Bandwidth [KHz]	FCC Limits * [KHz]
49.86	48.8	within 49.82-49.90

26dB Bandwidth of Fundamental Emission



Date: 2003-02-28

TEST REPORT

Page 16 of 21

No.: HM109661

Appendix A

Test Equipment Audit

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	HEWLETT PACKARD	HP85660B	3144A21192	07/09/01
EM008	SPECTRUM ANALYZER DISPLAY	HEWLETT PACKARD	HP85662A	3144A20514	07/09/01
EM009	QUASI PEAK ADAPTOR	HEWLETT PACKARD	HP85650A	3303A01702	07/09/01
EM010	RF PRESELECTOR	HEWLETT PACKARD	HP85685A	3221A01410	07/09/01
EM011	ATTENUATOR/SWITCH	HEWLETT PACKARD	HP11713A	2508A10595	07/09/01
EM012	PRE-AMPLIFIER	HEWLETT PACKARD	HP8449B	3008A00262	07/09/01
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	HEWLETT PACKARD HEWLETT PACKARD HEWLETT PACKARD	HP9000 HP A1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM020	HORN ANTENNA	EMCO	3115	4032	19/07/00
EM022	LOOP ANTENNA	EMCO	6502	1189-2424	04/08/00
EM072	SIGNAL GENERATOR	HEWLETT PACKARD	8640B	1948A11892	N/A
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	21/03/02
EM131	PORTABLE SPECTRUM ANALYSER	HEWLETT PACKARD	8595EM	3710A00155	18/12/01
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	22/07/02
EM194	BICONILOG ANTENNA	EMCO	3142B	1795	14/05/02
EM195	ANTENNA POSITIONING MAST	EMCO	2075	2368	N/A
EM196	MULTI-DEVICE CONTROLLER	EMCO	2090	1662	N/A

Conducted Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM078	VARIAC	SHANGHAI VOLTAGE	TDGC-3/0.5	N/A	CM
EM081	SMALL SCREENED ROOM	MIKO INST HK	N/A	N/A	18/10/02
EM119	LISN	R & S	ESH3-Z5	0831.5518.5 2	01/10/02
EM127	ISOLATION TRANSFORMER 220 TO 300	WING SUN	N/A	N/A	CM
EM142	PULSES LIMITER	R & S	ESH3Z2	357.8810.52	03/07/02
EM181	EMI TEST RECEIVER	R & S	ESIB7	100072	28/11/01
EM154	SHIELDING ROOM	SIEMENA MATSUSHITA COMPONENTS	N/A	803-740-057- 99A	18/10/02
EM197	LISN	EMCO	4825/2	1193	28/03/02

Remarks:

CM Corrective Maintenance
N/A Not Applicable or Not Available
TBD To Be Determined

No.: HM109661

Appendix B**Duty Cycle Correction During 100msec**


Each function key sends a different series of characters, but each packet period (45.37msec) never exceeds a series of 39 long (750µsec) or short pules. Assuming any combination of short and long pules may be obtained due to encoding the worse case transmit duty cycle would be considered $39 \times 750 \mu\text{sec}$ per $45.37 \text{ msec} = 64.5\%$ duty cycle. Figure A through C show the characteristics of the pulse train for one of these function.

Remarks:

Duty Cycle Correction = $20\text{Log}(0.645) = -3.8\text{dB}$

The following figures [Figure A to Figure B] showed the characteristics of the pulse train for one of these functions.

Figure A [Pulse Train]




Date: 2003-02-28

TEST REPORT

Page 18 of 21

No.: HM109661

Figure B [Long Pulse or Short]




Appendix C**Modification Method**


1. Change the value of the following parts.

	<u>Original</u>	<u>Change to</u>
R4	8.2k	20k
R5	3.9k	3k
C5	33pF	20pF
L2	2.7 μ H	1.8 μ H

2. Added a capacitor C20pF between L1 and ground as shown in figure 1.

Figure 1

3. Added a capacitor C68pF between b pole of Q1 and the ground as shown in figure 2.

Figure 2

Date: 2003-02-28

TEST REPORT

Page 20 of 21

No.: HM109661

Appendix D

Photographs of EUT


Front View of the product




Rear View of the product



Inner Circuit Top View



Inner Circuit Bottom View



Date: 2003-02-28

TEST REPORT

Page 21 of 21

No.: HM109661

Photographs of EUT

Measurement of Radiated Emission Test Set Up



End of Document