



RADIO TEST REPORT

FCC ID : QXO-AP3060
Equipment : Access Point
Brand Name : Extreme Networks
Model Name : AP3060
Applicant : Extreme Networks, Inc.
2121 RDU Center Drive Morrisville North Carolina
United States 27560
Manufacturer : Extreme Networks, Inc.
2121 RDU Center Drive Morrisville North Carolina
United States 27560
Standard : 47 CFR FCC Part 15.247

The product was received on Apr. 27, 2026, and testing was started from May 05, 2026 and completed on Jul. 21, 2026. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2020 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.



Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory

No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Information.....	5
1.2 Applicable Standards	10
1.3 Testing Location Information	10
1.4 Measurement Uncertainty	10
2 Test Configuration of EUT.....	12
2.1 Test Channel Mode	12
2.2 The Worst Case Measurement Configuration.....	13
2.3 EUT Operation during Test	15
2.4 Accessories	15
2.5 Support Equipment.....	16
2.6 Test Setup Diagram	17
3 Transmitter Test Result	21
3.1 AC Power-line Conducted Emissions	21
3.2 DTS Bandwidth	23
3.3 Maximum Conducted Output Power	24
3.4 Power Spectral Density	27
3.5 Emissions in Non-restricted Frequency Bands	29
3.6 Emissions in Restricted Frequency Bands.....	30
4 Test Equipment and Calibration Data	35
Appendix A. Test Results of AC Power-line Conducted Emissions	
Appendix B. Test Results of DTS Bandwidth	
Appendix C. Test Results of Maximum Conducted Output Power	
Appendix D. Test Results of Power Spectral Density	
Appendix E. Test Results of Emissions in Non-restricted Frequency Bands	
Appendix F. Test Results of Emissions in Restricted Frequency Bands	
Appendix G. Test Results of Radiated Emission Co-location	
Appendix H. Test Photos	
Photographs of EUT v01	



TEL : 886-3-656-9065
FAX : 886-3-656-9085
Report Template No.: CB-A10_6 Ver1.3



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.247(a)	DTS Bandwidth	PASS	-
3.3	15.247(b)	Maximum Conducted Output Power	PASS	-
3.4	15.247(e)	Power Spectral Density	PASS	-
3.5	15.247(d)	Emissions in Non-restricted Frequency Bands	PASS	-
3.6	15.247(d)	Emissions in Restricted Frequency Bands	PASS	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the chapter "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sam Chen**Report Producer: Vicky Huang**



1 General Description

1.1 Information

1.1.1 RF General Information

Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number
2400-2483.5	LE	2402-2480	0-39 [40]

Band	Mode	BWch (MHz)	Nant
2.4G	BT-LE(1Mbps)	1	1
2.4G	BT-LE(500Kb/s)	1	1
2.4G	BT-LE(125Kb/s)	1	1
2.4G	BT-LE(2Mbps)	2	1

Note:

Bluetooth LE uses a GFSK modulation.
BWch is the nominal channel bandwidth.

1.1.2 Antenna Information

Ant.	RF Port					Brand Name	Model Name	Ant. Type	Connector	Modes of Operation	Gain (dBi)
	WLAN 2.4GHz	WLAN 5GHz	WLAN 6GHz	Bluetooth and IEEE 802.15.4	GPS						
1	1	1	1	-	-	WNC	95XPAM15.GAI	Dipole	I-PEX	WLAN 2.4GHz, WLAN 5GHz UNII 1~2A, WLAN 6GHz UNII 5~8 (Radio 1) WLAN 5GHz UNII 2C~3 or UNII 1~3 (Radio 2) Bluetooth, IEEE 802.15.4 (Radio 3) Bluetooth, IEEE 802.15.4 (Radio 3) GPS (Radio 4)	Note 1
2	2	2	2	-	-	WNC	95XPAM15.GAJ	PIFA	I-PEX		
3	-	1	-	1	-	WNC	95XPAM15.GAG	PIFA	I-PEX		
4	-	2	-	1	-	WNC	95XPAM15.GAH	Dipole	I-PEX		
5	-	-	-	1	-	WNC	95XPAM15.GAL	PIFA	I-PEX		
6	-	-	-	-	1	WNC	95XPAM15.GAK	PIFA	I-PEX		

Note 1:

Table 2.

Ant.	Antenna Gain (dBi)						
	WLAN 2.4GHz (Radio 1)	WLAN 5GHz UNII 1~2A (Radio 1)		WLAN 6GHz UNII 5~8 (Radio 1)			
	2.45GHz	5.2GHz	5.3GHz	6.175GHz	6.475GHz	6.695GHz	6.995GHz
1	6.98	5.87	4.98	5.23	5.52	5.33	5.50
2	3.54	3.52	3.51	4.99	3.94	4.00	4.34
Ant.	WLAN 5GHz UNII 1~3 (Radio 2)				Bluetooth, IEEE 802.15.4 (Radio 3)		
	5.2GHz	5.3GHz	5.6GHz	5.785GHz			
3	5.67	5.15	5.66	4.32	5.10		
4	5.18	5.04	4.77	4.66	6.20		
Ant.	Bluetooth, IEEE 802.15.4 (Radio 3)						
5	4.60						
Ant.	GPS (Radio 4)						
6	3.00						



Directional Gain (dBi)							
Item	WLAN 2.4GHz (Radio 1)	WLAN 5GHz UNII 1~2A (Radio 1)		WLAN 6GHz UNII 5~8 (Radio 1)			
	2.45GHz	5.2GHz	5.3GHz	6.175GHz	6.475GHz	6.695GHz	6.995GHz
2T1S	6.98	5.91	5.14	5.40	5.99	5.89	6.58
2T2S	6.98	5.87	4.98	5.23	5.52	5.33	5.50
Item	WLAN 5GHz UNII 1~3 (Radio 2)						
	5.2GHz		5.3GHz		5.6GHz		5.785GHz
2T1S	5.67		5.15		5.88		5.16
2T2S	5.67		5.15		5.66		4.66

Note 2: The above information (excepting Ant. 1-4 (WLAN) antenna gain and directional gain) was declared by Manufacturer.

Note 3: States antenna 6GHz transmission will be restricted per country's regulation.

For Radio 1:

2.4GHz IEEE 802.11b/g/n/VHT/ax/be mode (1, 2TX/2RX)

The EUT can support both 1TX and 2TX functions.

For 1TX

Only Port 1 can be use as transmitting antenna.

For 2TX/2RX

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

5GHz IEEE 802.11a/n/ac/ax/be mode (1, 2TX/2RX)

The EUT can support both 1TX and 2TX functions.

For 1TX

Only Port 1 can be use as transmitting antenna.

For 2TX/2RX

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

6GHz IEEE 802.11ax/be mode (1, 2TX/2RX)

The EUT can support both 1TX and 2TX functions.

For 1TX

Only Port 1 can be use as transmitting antenna.

For 2TX/2RX

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For Radio 2:

5GHz IEEE 802.11a/n/ac/ax/be mode (1, 2TX/2RX)

The EUT can support both 1TX and 2TX functions.

For 1TX

Only Port 1 can be use as transmitting antenna.

For 2TX/2RX

Port 1 and Port 2 can be used as transmitting/receiving antenna.

Port 1 and Port 2 could transmit/receive simultaneously.

For Radio 3:

Bluetooth, IEEE 802.15.4 mode (1TX/1RX)

The EUT supports all antennas with TX/RX diversity functions.

At once time there is only one antenna port can transmitting/receiving RF signal

For Radio 4:

GPS (1RX)

Only Port 1 can be used as receiving antenna.

**1.1.3 Mode Test Duty Cycle**

Mode	DC	DCF (dB)	T (s)	VBW (Hz)_1/T
BT-LE(1Mbps)	0.608	2.16	380u	3k
BT-LE(2Mbps)	0.316	5	197.5u	10k

Note:

DC is Duty Cycle.

DCF is Duty Cycle Factor.

1.1.4 EUT Operational Condition

EUT Power Type	From PoE			
Function	☒	Point-to-multipoint	☐	Point-to-point
Test Software Version	For Radiated Emission Co-location: Ping and nRF Connect For others: DOS[ver 10.0.19045.6466]			
Support Mode	☒	LE 1M PHY: 1 Mb/s		
	☒	LE Coded PHY (S=2): 500 Kb/s		
	☒	LE Coded PHY (S=8): 125 Kb/s		
	☒	LE 2M PHY: 2 Mb/s		

Note: The above information was declared by manufacturer.

1.1.5 Table for Radio Function

Function Radio (R)	WLAN 2.4GHz	WLAN 5GHz	WLAN 6GHz	Bluetooth	IEEE 802.15.4	GPS
1	V	V (UNII 1~2A)	V	-	-	-
2	-	V (UNII 1~3 or UNII 2C~3)	-	-	-	-
3	-	-	-	V	V	-
4	-	-	-	-	-	V

Note 1: For WLAN 5GHz: The Radio1 and Radio 2 can't operate at the same frequency simultaneously

Note 2: The above information was declared by manufacturer.

**1.1.6 Table for EUT Support Function**

Type of Function	WLAN 2.4GHz	WLAN 5GHz		WLAN 6GHz
		Radio 1	Radio 2	
AP	V	V (UNII 1~2A)	V (UNII 1~3)	V
Bridge	V	V (UNII 1)	V (UNII 1, 3)	-
Mesh	V	V (UNII 1)	V (UNII 1, 3)	-

Note1: For above table list, only AP mode was tested and recorded in this test.

Note2: The above information was declared by manufacturer.



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

47 CFR FCC Part 15.247

ANSI C63.10-2020

The following reference test guidance is not within the scope of accreditation of TAF.

FCC KDB 558074 D01 v05r02

FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location Information	
Test Lab. : Sporton International Inc. Hsinchu Laboratory	
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan (R.O.C.) TEL: 886-3-656-9065 FAX: 886-3-656-9085 Test site Designation No. TW3787 with FCC. Conformity Assessment Body Identifier (CABID) TW3787 with ISED.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted	TH03-CB	Gino Huang	22.3~23.1 / 61~65	May 27, 2026~ Jun. 29, 2026
Radiated below 1GHz	10CH01-CB	Stim Sung	21~22 / 61~62	Jul. 14, 2026
Radiated above 1GHz	03CH02-CB	Paul Hu	24.2~24.5 / 58~63	May 05, 2026~ Jul. 21, 2026
Radiated co-location	03CH04-CB	Stim Sung	23.8~23.9 / 61~62	May 05, 2026~ Jul. 21, 2026
	03CH06-CB	Jimmy Huang	23.6~24.1 / 60~67	
AC Conduction (Test Mode: Mode 1~5)	CO01-CB	Ryan Huang	21~22 / 56~57	Jun. 03, 2026
AC Conduction (Test Mode: Mode 6)	CO01-CB	Allen Chung	23~24 / 58~59	Jul. 04, 2026

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Test Date: Before Jul. 01, 2026

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.8 dB	Confidence levels of 95%

**Test Date: After Jun. 30, 2026**

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.7 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	3.9 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	5.5 dB	Confidence levels of 95%

Test Date: Before May 28, 2026

Test Items	Uncertainty	Remark
Radiated Emission (1GHz ~ 18GHz)	4.3 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.2 dB	Confidence levels of 95%
Conducted Emission	2.5 dB	Confidence levels of 95%
Output Power Measurement	1.3 dB	Confidence levels of 95%
Power Density Measurement	2.0 dB	Confidence levels of 95%
Bandwidth Measurement	1.0 %	Confidence levels of 95%

Test Date: After May 27, 2026

Test Items	Uncertainty	Remark
Radiated Emission (1GHz ~ 18GHz)	4.5 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.3 dB	Confidence levels of 95%
Conducted Emission	3.8 dB	Confidence levels of 95%
Output Power Measurement	1.5 dB	Confidence levels of 95%
Power Density Measurement	3.5 dB	Confidence levels of 95%
Bandwidth Measurement	1.6 %	Confidence levels of 95%



2 Test Configuration of EUT

2.1 Test Channel Mode

Mode
BT-LE(1Mbps)
2402MHz
2440MHz
2480MHz
BT-LE(2Mbps)
2402MHz
2440MHz
2480MHz

Note:

- ♦ 1Mbps, 500Kb/s, and 125Kb/s modes were the same bandwidth. The 1Mbps mode generated the worst case; thus it was selected to test.

2.2 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Normal Link
1	EUT_R1 (2.4GHz)+R2 (5GHz UNII 1~3)+R3 (BT_Ant. 5)+R4 (GPS)+Bracket 1+PoE
2	EUT_R1 (2.4GHz)+R2 (5GHz UNII 1~3)+R3 (BT_Ant. 4)+R4 (GPS)+Bracket 1+PoE
3	EUT_R1 (2.4GHz)+R2 (5GHz UNII 1~3)+R3 (BT_Ant. 3)+R4 (GPS)+Bracket 1+PoE
Mode 1 has been evaluated to be the worst case between Mode 1~3, thus measurement for Mode 4~5 will follow this same test mode.	
4	EUT_R1 (6GHz)+R2 (5GHz UNII 1~3)+R3 (BT_Ant. 5)+R4 (GPS)+Bracket 1+PoE
5	EUT_R1 (5GHz UNII 1~2A)+R2 (5GHz UNII 2C~3)+R3 (BT_Ant. 5)+R4 (GPS)+Bracket 1+PoE
Mode 1 has been evaluated to be the worst case between Mode 1~5, thus measurement for Mode 6 will follow this same test mode.	
6	EUT_R1 (2.4GHz)+R2 (5GHz UNII 1~3)+R3 (802.15.4_Ant. 5)+R4 (GPS)+Bracket 1+PoE
For operating mode 1 is the worst case and it was record in this test report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	DTS Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in Non-restricted Frequency Bands
Test Condition	Conducted measurement at transmit chains The EUT supports all antennas with TX/RX diversity functions. At once time there is only one antenna port can transmitting/receiving RF signal. The Ant. 4 generated the worst case, so it was selected for testing.
1	EUT_R3+Ant. 4

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emissions in Restricted Frequency Bands
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	CTX
	1. After evaluating, and the worst case was found as below for radiated above 1GHz test. So the measurement will follow this same test configuration. 2. The EUT supports all antennas with TX/RX diversity functions. At once time there is only one antenna port can transmitting/receiving RF signal. The Ant. 4 generated the worst case, so it was selected for testing.
1	EUT in Y axis_R1 (2.4GHz)+Bracket 1+PoE
2	EUT in Y axis_R1 (2.4GHz)+Bracket 2+PoE
Mode 1 has been evaluated to be the worst case among Mode 1~2, thus measurement for Mode 3~7 will follow this same test mode.	
3	EUT in Y axis_R1 (5GHz UNII 1~2A)+Bracket 1+PoE
4	EUT in Y axis_R1 (6GHz)+Bracket 1+PoE
5	EUT in Z axis_R2 (5GHz UNII 1~3)+Bracket 1+PoE
6	EUT in Y axis_R3+Ant. 4 (BT)+Bracket 1+PoE
7	EUT in Y axis_R3+Ant. 4 (802.15.4)+Bracket 1+PoE
For operating mode 5 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX
	1. After evaluating, the worst case was found at Y axis, so it was selected to perform test and its test result was written in the report. 2. The EUT supports all antennas with TX/RX diversity functions. At once time there is only one antenna port can transmitting/receiving RF signal. The Ant. 4 generated the worst case, so it was selected for testing.
1	EUT in Y axis_R3+Ant. 4

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Radiated Emission Co-location
Test Condition	Radiated measurement
	After evaluating, the worst case was found at Z axis, so it was selected to perform test and its test result was written in the report.
Operating Mode	Normal Link
1	EUT in Z axis_R2 (5GHz UNII 1~3)+R3_(BT_Ant. 3)
2	EUT in Z axis_R2 (5GHz UNII 1~3)+R3_(BT_Ant. 4)
3	EUT in Z axis_R2 (5GHz UNII 1~3)+R3_(IEEE 802.15.4_Ant. 3)
4	EUT in Z axis_R2 (5GHz UNII 1~3)+R3_(IEEE 802.15.4_Ant. 4)



For operating mode 3 is the worst case and it was record in this test report.

Refer to Appendix G for Radiated Emission Co-location.

The Worst Case Mode for Following Conformance Tests

Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	R1 (2.4GHz) + R2 (5GHz UNII 1~3) + R3 (BT)
2	R1 (6GHz) + R2 (5GHz UNII 1~3) + R3 (BT)
3	R1 (5GHz UNII 1~2A) + R2 (5GHz UNII 2C~3) + R3 (BT)
4	R1 (2.4GHz) + R2 (5GHz UNII 1~3) + R3 (802.15.4)
5	R1 (6GHz) + R2 (5GHz UNII 1~3) + R3 (802.15.4)
6	R1 (5GHz UNII 1~2A) + R2 (5GHz UNII 2C~3) + R3 (802.15.4)

Refer to Sporton Test Report No.: FA631803 for Co-location RF Exposure Evaluation.

Note1: R means Radio ; BT means Bluetooth.

Note2: The PoE is used for testing purpose; it will not be sold with the EUT

Power	Brand Name	Model Name
PoE 1	Microsemi	PD-9501-10GC/AC
PoE 2	PHIHONG	POE60U-BTA

2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link:

During the test, the EUT operation to normal function.

2.4 Accessories

Accessories
Bracket 1*1
Bracket 2*1
Sealing Collar 1*1
Sealing Collar 2*1



2.5 Support Equipment

For AC Conduction:

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	PoE 2	PHIHONG	POE60U-BTA	N/A
B	ETH0 PC	ASUS	S300TA	TX2-RTL8821CE
C	R1(2.4G) NB	Lenovo	X260	N/A
D	R2(5G full) NB	Lenovo	X260	N/A
E	Smart phone	Apple	A2403	BCG-E3544A
F	GPS Simulator	WELNAVIGATE	GS-100	N/A

For Radiated (below 1GHz):

Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	PoE 2	PHIHONG	POE60U-BTA	N/A
B	PC	ASUS	S300TA	TX2-RTL8821CE


For Radiated (above 1GHz) and RF Conducted:


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	NB	DELL	E4300	N/A
B	PoE 1	Microsemi	PD-9501-10GC/AC	N/A

For Radiated (Emission Co-location):


Support Equipment				
No.	Equipment	Brand Name	Model Name	FCC ID
A	PoE 1	Microsemi	PD-9501-10GC/AC	N/A
B	NB	DELL	E4300	N/A
C	iPhone 12	Apple	A2403	BCG-E3544A
D	GPS Simulator	WELNAVIGATE	GS-100	N/A
E	2.4G NB	DELL	E4300	N/A
F	5G full NB	DELL	E4300	N/A

2.6 Test Setup Diagram




Test Setup Diagram - Radiated Test < 1GHz


Item	Connection	Shielded	Length
1	RJ-45 cable	No	10m
2	RJ-45 cable	No	3m
3	GND cable	No	2m

Test Setup Diagram - Radiated Test > 1GHz


Item	Connection	Shielded	Length
1	RJ-45 cable	No	1.5m
2	RJ-45 cable	No	10m

Test Setup Diagram - Radiated Emission Co-location Test


Item	Connection	Shielded	Length
1	RJ-45 cable	No	1.5m
2	RJ-45 cable	No	1.5m
3	Console cable	Yes	1m
4	GND cable	No	1.5m



3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		


3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
▪ Refer as ANSI C63.10-2020, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup



1.1.1. Measurement Results Calculation

The measured Level is calculated using:

- a. Corrected Reading: LISN Factor (LISN) + Attenuator (AT/AUX) + Cable Loss (CL) + Read Level (Raw) = Level
- b. Margin = -Limit + Level

3.1.5 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 DTS Bandwidth

3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
Systems using digital modulation techniques:
6 dB bandwidth $\geq$ 500 kHz.


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method
For the emission bandwidth shall be measured using one of the options below:
☒ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.1 Option 1 for 6 dB bandwidth measurement.
☐ Refer as FCC KDB 558074, clause 8.2 & C63.10 clause 11.8.2 Option 2 for 6 dB bandwidth measurement.
☐ Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.

3.2.4 Test Setup



3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Conducted Output Power

3.3.1 Maximum Conducted Output Power Limit

Maximum Conducted Output Power Limit						
	▪ If $G_{TX} \leq 6$ dBi, then $P_{Out} \leq 30$ dBm (1 W)					
	▪ Point-to-multipoint systems (P2M): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)$ dBm					
	▪ Point-to-point systems (P2P): If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm					
	▪ Smart antenna system (SAS):					
	<table> <tr> <td>-</td><td>Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm</td></tr> <tr> <td>-</td><td>Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm</td></tr> <tr> <td>-</td><td>Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm</td></tr> </table>	-	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm	-	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm	-
-	Single beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm					
-	Overlap beam: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3$ dBm					
-	Aggregate power on all beams: If $G_{TX} > 6$ dBi, then $P_{Out} = 30 - (G_{TX} - 6)/3 + 8$ dB dBm					
P_{Out} = maximum peak conducted output power or maximum conducted output power in dBm, G_{TX} = the maximum transmitting antenna directional gain in dBi.						


3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
Maximum Peak Conducted Output Power	
☐	Refer as FCC KDB 558074, clause 8.3.1.1 & C63.10 clause 11.9.1.1 (RBW ≥ EBW method).
☐	Refer as FCC KDB 558074, clause 8.3.1.3 & C63.10 clause 11.9.1.3 (peak power meter).
Maximum Conducted Output Power	
[duty cycle ≥ 98% or external video / power trigger]	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.2 Method AVGSA-1.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.3 Method AVGSA-1A. (alternative)
duty cycle < 98% and average over on/off periods with duty factor	
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.4 Method AVGSA-2.
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.5 Method AVGSA-2A (alternative)
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.6 Method AVGSA-3
☐	Refer as FCC KDB 558074, clause 8.3.2.2 & C63.10 clause 11.9.2.2.7 Method AVGSA-3A (alternative)
Measurement using a power meter (PM)	
☐	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.1 Method AVGPM (using an RF average power meter).
☒	Refer as FCC KDB 558074, clause 8.3.2.3 & C63.10 clause 11.9.2.3.2 Method AVGPM-G (using an gate RF average power meter).
For conducted measurement.	
If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.	
If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$	

3.3.4 Test Setup





3.3.5 Test Result of Maximum Conducted Output Power

Refer as Appendix C



3.4 Power Spectral Density

3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
▪ Power Spectral Density (PSD) ≤ 8 dBm/3kHz


3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪ Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).	
☒	Refer as FCC KDB 558074, clause 8.4 & C63.10 clause 11.10 Method Max. PSD. [duty cycle $\geq 98\%$ or external video / power trigger]
▪ For conducted measurement.	
▪ If The EUT supports multiple transmit chains using options given below:	
☐	Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
☐	Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
☐	Option 3: Measure and add $10 \log(N)$ dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$. Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.

3.4.4 Test Setup



3.4.5 Test Result of Power Spectral Density

Refer as Appendix D

3.5 Emissions in Non-restricted Frequency Bands

3.5.1 Emissions in Non-restricted Frequency Bands Limit

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dBc)
Peak output power procedure	20
Average output power procedure	30
Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level. Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.	


3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.5.3 Test Procedures

Test Method
Refer as FCC KDB 558074, clause 8.5 for unwanted emissions into non-restricted bands.

3.5.4 Test Setup



3.5.5 Test Result of Emissions in Non-restricted Frequency Bands

Refer as Appendix E

3.6 Emissions in Restricted Frequency Bands

3.6.1 Emissions in Restricted Frequency Bands Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB / decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.





3.6.3 Test Procedures

Test Method	
▪ The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].	
▪ Refer as ANSI C63.10, clause 6.10.3 band-edge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.	
▪ For the transmitter unwanted emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074, clause 8.6 for unwanted emissions into restricted bands.
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.1(trace averaging for duty cycle $\geq 98\%$).
	☐ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.2(trace averaging + duty factor).
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.5.3(Reduced VBW $\geq 1/T$).
	☐ Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW $\geq 1/T$, where T is pulse time.
	☐ Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
	☒ Refer as FCC KDB 558074, clause 8.6 & C63.10 clause 11.12.2.4 measurement procedure peak limit.
▪ For the transmitter band-edge emissions shall be measured using following options below:	
	▪ Refer as FCC KDB 558074 clause 8.7 & c63.10 clause 11.13.1, When the performing peak or average radiated measurements, emissions within 2 MHz of the authorized band edge may be measured using the marker-delta method described below.
	▪ Refer as FCC KDB 558074, clause 8.7 (ANSI C63.10, clause 6.10.6) for marker-delta method for band-edge measurements.
	▪ Refer as FCC KDB 558074, clause 8.7 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
	▪ For conducted unwanted emissions into restricted bands (absolute emission limits). Devices with multiple transmit chains using options given below: (1) Measure and sum the spectra across the outputs or (2) Measure and add 10 log(N) dB
	▪ For FCC KDB 662911 The methodology described here may overestimate array gain, thereby resulting in apparent failures to satisfy the out-of-band limits even if the device is actually compliant. In such cases, compliance may be demonstrated by performing radiated tests around the frequencies at which the apparent failures occurred.

3.6.4 Test Setup







3.6.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level.

3.6.6 Emissions in Restricted Frequency Bands (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.

3.6.7 Test Result of Emissions in Restricted Frequency Bands

Refer as Appendix F



4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.4GHz	Mar. 12, 2026	Mar. 11, 2027	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Feb. 04, 2026	Feb. 03, 2027	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Apr. 10, 2026	Apr. 09, 2027	Conduction (CO01-CB)
Pulse Limiter	Rohde& Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Sep. 14, 2025	Sep. 13, 2026	Conduction (CO01-CB)
COND Cable	Woken	Cable	CO01	9kHz ~ 30MHz	Sep. 14, 2025	Sep. 13, 2026	Conduction (CO01-CB)
Test Software	SPORTON	SENSE-EMI	V5.11	150kHz-30MHz	N.C.R.	N.C.R.	Conduction (CO01-CB)
10m Semi Anechoic Chamber NSA	TDK	SAC-10M	10CH01-CB	30MHz~1GHz 10m,3m	Jan. 14, 2026	Jan. 13, 2027	Radiation (10CH01-CB)
Amplifier	Agilent	8447D	2944A10783	9kHz ~ 1.3GHz	Mar. 07, 2026	Mar. 06, 2027	Radiation (10CH01-CB)
Amplifier	Agilent	8447D	2944A10784	9kHz ~ 1.3GHz	Mar. 07, 2026	Mar. 06, 2027	Radiation (10CH01-CB)
Low Cable	Woken	SUCOFLEX 104	low cable-01	25MHz ~ 1GHz	Oct. 14, 2025	Oct. 13, 2026	Radiation (10CH01-CB)
Low Cable	Woken	SUCOFLEX 104	low cable-02	25MHz ~ 1GHz	Oct. 14, 2025	Oct. 13, 2026	Radiation (10CH01-CB)
Biconical Antenna	Schwarzbeck	VHBB 9124	324	30MHz ~ 200MHz	Sep. 10, 2025	Sep. 09, 2026	Radiation (10CH01-CB)
Log Antenna	Schwarzbeck	VUSLP 9111	247	200MHz ~ 1GHz	Sep. 30, 2025	Sep. 29, 2026	Radiation (10CH01-CB)
EMI Test Receiver	Rohde& Schwarz	ESR7	103076	9 kHz ~ 7GHz	Aug. 27, 2025	Aug. 26, 2026	Radiation (10CH01-CB)
Loop Antenna	Teseq	HLA 6121	65417	9kHz - 30MHz	Oct. 20, 2025	Oct. 19, 2026	Radiation (10CH01-CB)
Spectrum analyzer	R&S	FSV40	101027	9kHz~40GHz	Sep. 03, 2025	Sep. 02, 2026	Radiation (10CH01-CB)
Test Software	SPORTON	SENSE-EMI	V5.11	30MHz-40GHz	N.C.R.	N.C.R.	Radiation (10CH01-CB)
3m Semi Anechoic Chamber VSWR	RIKEN	SAC-3M	03CH02-CB	1GHz ~18GHz	Mar. 21, 2026	Mar. 20, 2027	Radiation (03CH02-CB)
Horn Antenna	EMCO	3115	9610-4976	1GHz ~ 18GHz	Apr. 24, 2026	Apr. 23, 2027	Radiation (03CH02-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 07, 2025	Oct. 06, 2026	Radiation (03CH02-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Pre-Amplifier	Agilent	83017A	MY39501305	1GHz ~ 26.5GHz	Jun. 28, 2025	Jun. 27, 2026	Radiation (03CH02-CB)
Pre-Amplifier	Agilent	83017A	MY39501305	1GHz ~ 26.5GHz	Jun. 27, 2026	Jun. 26, 2027	Radiation (03CH02-CB)
Pre-Amplifier	SGH	SGH184	20221107-3	18GHz ~ 40GHz	Nov. 21, 2025	Nov. 20, 2026	Radiation (03CH02-CB)
Signal Analyzer	R&S	FSV3044	101536	10kHz ~ 44GHz	Aug. 20, 2025	Aug. 19, 2026	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Jun. 19, 2025	Jun. 18, 2026	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Jun. 18, 2026	Jun. 17, 2027	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Jun. 19, 2025	Jun. 18, 2026	Radiation (03CH02-CB)
RF Cable-high	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Jun. 18, 2026	Jun. 17, 2027	Radiation (03CH02-CB)
High Cable	Woken	WCA0929M	40G#5+6	1GHz ~ 40 GHz	Feb. 11, 2026	Feb. 10, 2027	Radiation (03CH02-CB)
Test Software	SPORTON	SENSE-15247_FS	V5.11.27	2.4GHz-2.4835GHz	N.C.R.	N.C.R.	Radiation (03CH02-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH04-CB	1GHz ~18GHz 3m	Feb. 13, 2026	Feb. 12, 2027	Radiation (03CH04-CB)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	BBHA 9120D-01816	1GHz~18GHz	Dec. 31, 2025	Dec. 30, 2026	Radiation (03CH04-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 07, 2025	Oct. 06, 2026	Radiation (03CH04-CB)
Pre-Amplifier	SGH	SGH5265	20211115-1	1~ 26.5GHz	Jan. 13, 2026	Jan. 12, 2027	Radiation (03CH04-CB)
Pre-Amplifier	SGH	SGH184	20221107-3	18GHz ~ 40GHz	Nov. 21, 2025	Nov. 20, 2026	Radiation (03CH04-CB)
Spectrum Analyzer	R&S	FSP40	100142	9kHz~40GHz	Mar. 30, 2026	Mar. 29, 2027	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-21	1GHz - 18GHz	Apr. 24, 2026	Apr. 23, 2027	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-21+67	1GHz - 18GHz	Apr. 24, 2026	Apr. 23, 2027	Radiation (03CH04-CB)
High Cable	Woken	WCA0929M	40G#5+6	1GHz ~ 40 GHz	Feb. 11, 2026	Feb. 10, 2027	Radiation (03CH04-CB)
Test Software	SPORTON	SENSE-15247_FS	V5.11.27	2.4GHz-2.4835GHz	N.C.R.	N.C.R.	Radiation (03CH04-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH06-CB	1GHz ~18GHz 3m	Oct. 07, 2025	Oct. 06, 2026	Radiation (03CH06-CB)
Horn Antenna	SCHWARZBECK	BBHA9120D	BBHA 9120D-1292	1GHz~18GHz	Aug. 22, 2025	Aug. 21, 2026	Radiation (03CH06-CB)



Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Oct. 07, 2025	Oct. 06, 2026	Radiation (03CH06-CB)
Pre-Amplifier	EMCI	EMC12630SE	980383	1GHz ~ 18GHz	Jul. 30, 2025	Jul. 29, 2026	Radiation (03CH06-CB)
Pre-Amplifier	SGH	SGH184	20221107-3	18GHz ~ 40GHz	Nov. 21, 2025	Nov. 20, 2026	Radiation (03CH06-CB)
Signal analyzer	R&S	FSV3044	101667	9kHz~44GHz	Aug. 27, 2025	Aug. 26, 2026	Radiation (03CH06-CB)
RF Cable-high	Woken	RG402	High Cable-05+68	1GHz~18GHz	Sep. 25, 2025	Sep. 24, 2026	Radiation (03CH06-CB)
High Cable	Woken	WCA0929M	40G#5+6	1GHz ~ 40 GHz	Feb. 11, 2026	Feb. 10, 2027	Radiation (03CH06-CB)
Test Software	SPORTON	SENSE-15247_FS	V5.11.27	2.4GHz-2.4835GHz	N.C.R.	N.C.R.	Radiation (03CH06-CB)
Spectrum analyzer	R&S	FSV40	101028	9kHz~40GHz	Jan. 14, 2026	Jan. 13, 2027	Conducted (TH03-CB)
Power Sensor	Anritsu	MA2411B	1726195	300MHz~40GHz	Sep. 12, 2025	Sep. 11, 2026	Conducted (TH03-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Sep. 12, 2025	Sep. 11, 2026	Conducted (TH03-CB)
RF Cable	Woken	RG402	High Cable-11	30MHz ~18 GHz	Sep. 30, 2025	Sep. 29, 2026	Conducted (TH03-CB)
RF Cable	Woken	RG402	High Cable-12	30MHz ~18 GHz	Sep. 30, 2025	Sep. 29, 2026	Conducted (TH03-CB)
RF Cable	Woken	RG402	High Cable-13	30MHz ~18 GHz	Sep. 30, 2025	Sep. 29, 2026	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-14	1 GHz ~18 GHz	Sep. 30, 2025	Sep. 29, 2026	Conducted (TH03-CB)
RF Cable-high	Woken	RG402	High Cable-15	1 GHz ~18 GHz	Sep. 30, 2025	Sep. 29, 2026	Conducted (TH03-CB)
Switch	SPTCB	SP-SWI	SWI-03	1~18GHz	Sep. 20, 2025	Sep. 19, 2026	Conducted (TH03-CB)
Test Software	SPORTON	SENSE-15247_FS	V5.11.27	2.4GHz-2.4835GHz	N.C.R.	N.C.R.	Conducted (TH03-CB)

Note: Calibration Interval of instruments listed above is one year.

NCR means Non-Calibration required.




Conducted Emissions at Powerline

Appendix A

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 1	Pass	AV	24.954M	41.55	50.00	-8.45	Line

Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)						
QP	568.5k	42.03	56.00	-13.97	10.12	Line	-	31.91	0.09	0.13	9.90						
AV	568.5k	34.87	46.00	-11.13	10.12	Line	-	24.75	0.09	0.13	9.90						
QP	12.129M	49.64	60.00	-10.36	10.78	Line	-	38.86	0.25	0.31	10.22						
AV	12.129M	40.65	50.00	-9.35	10.78	Line	-	29.87	0.25	0.31	10.22						
QP	12.476M	48.21	60.00	-11.79	10.82	Line	-	37.39	0.26	0.32	10.24						
AV	12.476M	37.19	50.00	-12.81	10.82	Line	-	26.37	0.26	0.32	10.24						
QP	20.031M	45.83	60.00	-14.17	11.00	Line	-	34.83	0.29	0.34	10.37						
AV	20.031M	38.42	50.00	-11.58	11.00	Line	-	27.42	0.29	0.34	10.37						
QP	24.36M	45.75	60.00	-14.25	11.04	Line	-	34.71	0.31	0.42	10.31						
AV	24.36M	35.67	50.00	-14.33	11.04	Line	-	24.63	0.31	0.42	10.31						
QP	24.954M	51.24	60.00	-8.76	11.05	Line	-	40.19	0.32	0.43	10.30						
AV	24.954M	41.55	50.00	-8.45	11.05	Line	"Worst"	30.50	0.32	0.43	10.30						

Mode 1



Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Factor (dB)	Condition	Comment	Raw (dBuV)	LISN (dB)	CL (dB)	AT (dB)						
QP	154.5k	50.43	65.75	-15.32	10.01	Neutral	-	40.42	0.06	0.09	9.86						
AV	154.5k	33.76	55.75	-21.99	10.01	Neutral	-	23.75	0.06	0.09	9.86						
QP	577.5k	41.73	56.00	-14.27	10.09	Neutral	-	31.64	0.06	0.13	9.90						
AV	577.5k	35.17	46.00	-10.83	10.09	Neutral	-	25.08	0.06	0.13	9.90						
QP	12.08M	48.36	60.00	-11.64	10.75	Neutral	-	37.61	0.22	0.31	10.22						
AV	12.08M	39.52	50.00	-10.48	10.75	Neutral	"Worst"	28.77	0.22	0.31	10.22						
QP	12.431M	43.31	60.00	-16.69	10.78	Neutral	-	32.53	0.22	0.32	10.24						
AV	12.431M	32.81	50.00	-17.19	10.78	Neutral	-	22.03	0.22	0.32	10.24						
QP	24.158M	47.51	60.00	-12.49	11.04	Neutral	-	36.47	0.31	0.42	10.31						
AV	24.158M	38.68	50.00	-11.32	11.04	Neutral	-	27.64	0.31	0.42	10.31						
QP	25.053M	49.49	60.00	-10.51	11.05	Neutral	-	38.44	0.32	0.43	10.30						
AV	25.053M	39.25	50.00	-10.75	11.05	Neutral	-	28.20	0.32	0.43	10.30						

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-LE(1Mbps)	647.5k	1.039M	1M04F1D	635k	1.032M
BT-LE(2Mbps)	620k	2.072M	2M07F1D	617.5k	2.07M

Max-N dB = Maximum 6dB down bandwidth; Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth; Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	500k	647.5k	1.036M
2440MHz	Pass	500k	635k	1.032M
2480MHz	Pass	500k	646.25k	1.039M
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	500k	620k	2.072M
2440MHz	Pass	500k	620k	2.07M
2480MHz	Pass	500k	617.5k	2.07M



Port X-N dB = Port X 6dB down bandwidth;
Port X-OBW = Port X 99% occupied bandwidth

2.4-2.4835GHz_BT-LE(1Mbps)
EBW-DTS
2402MHz

01/06/2026




2.4-2.4835GHz_BT-LE(1Mbps)
EBW-DTS
2440MHz

01/06/2026





2.4-2.4835GHz_BT-LE(1Mbps)
EBW-DTS
2480MHz

01/06/2026


2.4-2.4835GHz_BT-LE(2Mbps)
EBW-DTS
2402MHz

01/06/2026





2.4-2.4835GHz_BT-LE(2Mbps)

EBW-DTS

2440MHz

01/06/2026




2.4-2.4835GHz_BT-LE(2Mbps)

EBW-DTS

2480MHz

01/06/2026





Summary

Mode	Total Power (dBm)	Total Power (W)
2.4-2.4835GHz	-	-
BT-LE(1Mbps)	7.78	0.00600
BT-LE(2Mbps)	7.59	0.00574

Result

Mode	Result	DG (dBi)	Total Power (dBm)	Power Limit (dBm)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	6.20	7.77	29.80
2440MHz	Pass	6.20	7.78	29.80
2480MHz	Pass	6.20	5.04	29.80
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	6.20	7.59	29.80
2440MHz	Pass	6.20	7.04	29.80
2480MHz	Pass	6.20	4.14	29.80

DG = Directional Gain; Port X = Port X output power;
Inf = There's no restriction for the limit.

Summary

Mode	PD (dBm/RBW)
2.4-2.4835GHz	-
BT-LE(1Mbps)	2.65
BT-LE(2Mbps)	-1.32

RBW = 3kHz;

Result

Mode	Result	DG (dBi)	PD (dBm/RBW)	PD Limit (dBm/RBW)
BT-LE(1Mbps)	-	-	-	-
2402MHz	Pass	6.20	1.49	7.80
2440MHz	Pass	6.20	2.65	7.80
2480MHz	Pass	6.20	-1.20	7.80
BT-LE(2Mbps)	-	-	-	-
2402MHz	Pass	6.20	-1.32	7.80
2440MHz	Pass	6.20	-1.70	7.80
2480MHz	Pass	6.20	-6.65	7.80


DG = Directional Gain; RBW = 3kHz;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;
Inf = There's no restriction for the limit.

2.4-2.4835GHz_BT-LE(1Mbps)

PSD

2402MHz

01/06/2026




2.4-2.4835GHz_BT-LE(1Mbps)

PSD

2440MHz

01/06/2026




2.4-2.4835GHz_BT-LE(1Mbps)

PSD

2480MHz

01/06/2026




2.4-2.4835GHz_BT-LE(2Mbps)

PSD

2402MHz

01/06/2026




2.4-2.4835GHz_BT-LE(2Mbps)

PSD

2440MHz

01/06/2026




2.4-2.4835GHz_BT-LE(2Mbps)

PSD

2480MHz

01/06/2026



Summary

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
BT-LE(1Mbps)	Pass	2.44008G	7.30	-22.70	2.13678G	-53.89	2.39976G	-52.93	2.4G	-51.15	2.50046G	-53.97	21.9461G	-45.99	1
BT-LE(2Mbps)	Pass	2.402G	7.28	-22.72	1.8724G	-53.64	2.4G	-25.91	2.4G	-25.53	2.50286G	-53.84	21.87299G	-46.17	1

Result

Mode	Result	Ref (Hz)	Ref (dBm)	Limit (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Freq (Hz)	Level (dBm)	Port
BT-LE(1Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.44008G	7.30	-22.70	2.13678G	-53.89	2.39976G	-52.93	2.4G	-51.15	2.50046G	-53.97	21.9461G	-45.99	1
2440MHz	Pass	2.44008G	7.30	-22.70	2.1027G	-53.94	2.39232G	-53.91	2.4G	-57.00	2.50234G	-53.95	21.79987G	-45.66	1
2480MHz	Pass	2.44008G	7.30	-22.70	2.04865G	-54.16	2.4G	-53.64	2.4G	-55.88	2.50146G	-53.86	21.80831G	-45.54	1
BT-LE(2Mbps)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2402MHz	Pass	2.402G	7.28	-22.72	1.8724G	-53.64	2.4G	-25.91	2.4G	-25.53	2.50286G	-53.84	21.87299G	-46.17	1
2440MHz	Pass	2.402G	7.28	-22.72	1.87945G	-53.86	2.39548G	-52.79	2.4G	-55.04	2.50014G	-53.51	21.95454G	-45.29	1
2480MHz	Pass	2.402G	7.28	-22.72	30M	-53.86	2.39396G	-53.87	2.4G	-55.35	2.50102G	-53.76	21.91798G	-46.16	1


2.4-2.4835GHz_BT-LE(1Mbps)

CSEndB-DTS

2402MHz

01/06/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.30	-22.70	2.13678G	-53.89	2.39976G	-52.93	2.4G	-51.15	2.50046G	-53.97	2.19461G	-45.99	1


2.4-2.4835GHz_BT-LE(1Mbps)

CSEndB-DTS

2440MHz

01/06/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.30	-22.70	2.1027G	-53.94	2.39232G	-53.91	2.4G	-57.00	2.50234G	-53.95	2.179987G	-45.66	1

2.4-2.4835GHz_BT-LE(1Mbps)


CSEndB-DTS

2480MHz

01/06/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Port 1



Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.44008G	7.30	-22.70	2.04865G	-54.16	2.4G	-53.64	2.4G	-55.88	2.50146G	-53.86	21.80831G	-45.54	1

2.4-2.4835GHz_BT-LE(2Mbps)


CSEndB-DTS

2402MHz

01/06/2026

RBW (Hz)
100k
VBW (Hz)
300k
Detector
Peak

Port 1




Ref(Hz)	Ref(dBm)	Limit(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Freq(Hz)	Level(dBm)	Port
2.402G	7.28	-22.72	1.8724G	-53.64	2.4G	-25.91	2.4G	-25.53	2.50286G	-53.84	21.87299G	-46.17	1

2.4-2.4835GHz_BT-LE(2Mbps)

CSEndB-DTS

2440MHz

01/06/2026




2.4-2.4835GHz_BT-LE(2Mbps)

CSEndB-DTS

2480MHz

01/06/2026






Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 5	Pass	PK	46.98M	35.41	40.00	-4.59	Vertical

Mode 5



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)		
QP	39.7M	35.22	40.00	-4.78	-34.48	3	Vertical	254	1.00	-	69.70	18.91	0.20	53.59		
PK	46.98M	35.41	40.00	-4.59	-34.20	3	Vertical	103	1.00	"Worst"	69.61	19.45	0.27	53.92		
QP	60.07M	32.35	40.00	-7.65	-34.55	3	Vertical	0	3.00	-	66.90	18.90	0.50	53.95		
PK	79.96M	23.30	40.00	-16.70	-38.78	3	Vertical	155	4.00	-	62.08	14.76	0.38	53.92		
PK	219.64M	27.31	46.00	-18.69	-36.58	3	Vertical	0	2.00	-	63.89	15.44	1.76	53.78		
PK	240.01M	28.83	46.00	-17.17	-34.48	3	Vertical	95	2.00	-	63.31	17.30	1.85	53.63		

Mode 5



Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Factor (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	Raw (dBuV)	AF (dB)	CL (dB)	PA (dB)		
PK	40.19M	26.06	40.00	-13.94	-34.32	3	Horizontal	332	1.00	-	60.38	18.99	0.20	53.51		
PK	49.89M	21.03	40.00	-18.97	-34.15	3	Horizontal	135	1.00	-	55.18	19.66	0.35	54.16		
PK	59.59M	20.85	40.00	-19.15	-34.56	3	Horizontal	96	2.00	-	55.41	18.91	0.49	53.96		
PK	156.59M	18.69	43.50	-24.81	-33.05	3	Horizontal	71	3.00	-	51.74	19.19	1.48	53.72		
PK	227.88M	29.31	46.00	-16.69	-36.13	3	Horizontal	250	2.00	-	65.44	15.79	1.80	53.72		
PK	239.04M	34.93	46.00	-11.07	-34.58	3	Horizontal	98	1.00	"Worst"	69.51	17.22	1.84	53.64		




Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
2.4-2.4835GHz	-	-	-	-	-	-	-	-	-	-	-
BT-LE(2Mbps)	Pass	AV	2.4835G	53.40	54.00	-0.60	3	Horizontal	350	1.74	-

2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	2.3608G	57.49	74.00	-16.51	24.75	3	Vertical	15	1.12	-	28.40	4.34	-				
AV	2.3866G	46.12	54.00	-7.88	13.26	3	Vertical	15	1.12	-	28.50	4.36	-				
PK	2.4022G	101.17	Inf	-Inf	68.40	3	Vertical	15	1.12	-	28.40	4.37	-				
AV	2.402G	99.70	Inf	-Inf	66.93	3	Vertical	15	1.12	-	28.40	4.37	-				

2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	2.373G	57.69	74.00	-16.31	24.91	3	Horizontal	334	2.18	-	28.43	4.35	-				
AV	2.3718G	46.22	54.00	-7.78	13.45	3	Horizontal	334	2.18	-	28.42	4.35	-				
PK	2.4022G	109.31	Inf	-Inf	76.54	3	Horizontal	334	2.18	-	28.40	4.37	-				
AV	2.402G	107.74	Inf	-Inf	74.97	3	Horizontal	334	2.18	-	28.40	4.37	-				

2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




EUT_V_1TX
Setting 0C 0C
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	4.777G	48.07	74.00	-25.93	37.89	3	Vertical	105	2.68	-	32.97	7.36	30.15			
AV	4.7748G	36.34	54.00	-17.66	26.18	3	Vertical	105	2.68	-	32.95	7.36	30.15			

2.4-2.4835GHz_BT-LE(1Mbps)

2402MHz_TX




EUT_V_1TX
Setting 0C 0C
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	4.7816G	48.86	74.00	-25.14	38.62	3	Horizontal	352	2.60	-	33.02	7.37	30.15			
AV	4.788G	36.32	54.00	-17.68	26.00	3	Horizontal	352	2.60	-	33.08	7.38	30.14			

2.4-2.4835GHz_BT-LE(1Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	2.382G	57.29	74.00	-16.71	24.43	3	Vertical	22	1.08	-	28.50	4.36	-				
AV	2.3892G	46.10	54.00	-7.90	13.24	3	Vertical	22	1.08	-	28.50	4.36	-				
PK	2.4396G	101.99	Inf	-Inf	69.17	3	Vertical	22	1.08	-	28.40	4.42	-				
AV	2.44G	100.42	Inf	-Inf	67.60	3	Vertical	22	1.08	-	28.40	4.42	-				
PK	2.4844G	56.96	74.00	-17.04	23.78	3	Vertical	22	1.08	-	28.70	4.48	-				
AV	2.4964G	46.36	54.00	-7.64	13.10	3	Vertical	22	1.08	-	28.76	4.50	-				

2.4-2.4835GHz_BT-LE(1Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	2.382G	57.06	74.00	-16.94	24.20	3	Horizontal	340	2.15	-	28.50	4.36	-			
AV	2.3768G	46.18	54.00	-7.82	13.36	3	Horizontal	340	2.15	-	28.47	4.35	-			
PK	2.4396G	110.27	Inf	-Inf	77.45	3	Horizontal	340	2.15	-	28.40	4.42	-			
AV	2.44G	108.36	Inf	-Inf	75.54	3	Horizontal	340	2.15	-	28.40	4.42	-			
PK	2.488G	58.55	74.00	-15.45	25.36	3	Horizontal	340	2.15	-	28.70	4.49	-			
AV	2.4912G	46.45	54.00	-7.55	13.25	3	Horizontal	340	2.15	-	28.71	4.49	-			

2.4-2.4835GHz_BT-LE(1Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	4.8942G	48.57	74.00	-25.43	38.10	3	Vertical	101	2.90	-	33.10	7.47	30.10			
AV	4.897G	36.52	54.00	-17.48	26.05	3	Vertical	101	2.90	-	33.10	7.47	30.10			
PK	7.3684G	53.47	74.00	-20.53	38.79	3	Vertical	94	2.61	-	36.54	9.03	30.89			
AV	7.3674G	41.93	54.00	-12.07	27.26	3	Vertical	94	2.61	-	36.53	9.03	30.89			

2.4-2.4835GHz_BT-LE(1Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA			
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)			
PK	4.8876G	49.67	74.00	-24.33	39.21	3	Horizontal	183	1.81	-	33.10	7.46	30.10			
AV	4.8922G	36.63	54.00	-17.37	26.17	3	Horizontal	183	1.81	-	33.10	7.46	30.10			
PK	7.2848G	53.46	74.00	-20.54	39.00	3	Horizontal	8	3.00	-	36.34	9.01	30.89			
AV	7.3688G	41.99	54.00	-12.01	27.31	3	Horizontal	8	3.00	-	36.54	9.03	30.89			

2.4-2.4835GHz_BT-LE(1Mbps)

2480MHz_TX




EUT Y_1TX
Setting 0A 0A
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA					
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)					
PK	2.4802G	100.64	Inf	-Inf	67.46	3	Vertical	18	1.13	-	28.70	4.48	-					
AV	2.48G	99.20	Inf	-Inf	66.02	3	Vertical	18	1.13	-	28.70	4.48	-					
PK	2.4906G	57.57	74.00	-16.43	24.37	3	Vertical	18	1.13	-	28.71	4.49	-					
AV	2.4835G	48.42	54.00	-5.58	15.24	3	Vertical	18	1.13	-	28.70	4.48	-					

2.4-2.4835GHz_BT-LE(1Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 0A 0A
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	2.4798G	107.87	Inf	-Inf	74.69	3	Horizontal	346	2.53	-	28.70	4.48	-				
AV	2.48G	106.37	Inf	-Inf	73.19	3	Horizontal	346	2.53	-	28.70	4.48	-				
PK	2.4835G	60.12	74.00	-13.88	26.94	3	Horizontal	346	2.53	-	28.70	4.48	-				
AV	2.4835G	53.38	54.00	-0.62	20.20	3	Horizontal	346	2.53	-	28.70	4.48	-				

2.4-2.4835GHz_BT-LE(1Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 0A 0A
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	4.9656G	48.92	74.00	-25.08	38.14	3	Vertical	167	2.65	-	33.33	7.52	30.07				
AV	5.0082G	37.08	54.00	-16.92	26.18	3	Vertical	167	2.65	-	33.40	7.55	30.05				
PK	7.4754G	53.99	74.00	-20.01	39.36	3	Vertical	132	2.86	-	36.45	9.07	30.89				
AV	7.3906G	42.20	54.00	-11.80	27.48	3	Vertical	132	2.86	-	36.58	9.03	30.89				

2.4-2.4835GHz_BT-LE(1Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 0A 0A
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	4.9268G	48.68	74.00	-25.32	38.06	3	Horizontal	353	1.51	-	33.21	7.49	30.08				
AV	5.01G	37.00	54.00	-17.00	26.11	3	Horizontal	353	1.51	-	33.40	7.55	30.06				
PK	7.4538G	54.56	74.00	-19.44	39.98	3	Horizontal	208	1.57	-	36.41	9.06	30.89				
AV	7.3938G	42.36	54.00	-11.64	27.63	3	Horizontal	208	1.57	-	36.59	9.03	30.89				

2.4-2.4835GHz_BT-LE(2Mbps)

2402MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	2.361G	57.44	74.00	-16.56	24.70	3	Vertical	19	1.33	-	28.40	4.34	-				
AV	2.3586G	47.26	54.00	-6.74	14.53	3	Vertical	19	1.33	-	28.39	4.34	-				
PK	2.4026G	100.73	Inf	-Inf	67.96	3	Vertical	19	1.33	-	28.40	4.37	-				
AV	2.402G	97.80	Inf	-Inf	65.03	3	Vertical	19	1.33	-	28.40	4.37	-				

2.4-2.4835GHz_BT-LE(2Mbps)

2402MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	2.3644G	57.36	74.00	-16.64	24.61	3	Horizontal	340	2.42	-	28.40	4.35	-			
AV	2.364G	47.80	54.00	-6.20	15.05	3	Horizontal	340	2.42	-	28.40	4.35	-			
PK	2.4026G	108.96	Inf	-Inf	76.19	3	Horizontal	340	2.42	-	28.40	4.37	-			
AV	2.402G	105.95	Inf	-Inf	73.18	3	Horizontal	340	2.42	-	28.40	4.37	-			

2.4-2.4835GHz_BT-LE(2Mbps)

2402MHz_TX




EUT_V_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	4.7802G	49.18	74.00	-24.82	38.96	3	Vertical	294	1.39	-	33.00	7.37	30.15			
AV	4.843G	37.79	54.00	-16.21	27.38	3	Vertical	294	1.39	-	33.11	7.42	30.12			

2.4-2.4835GHz_BT-LE(2Mbps)

2402MHz_TX




EUT_V_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	4.7922G	48.12	74.00	-25.88	37.76	3	Horizontal	190	2.93	-	33.12	7.38	30.14			
AV	4.783G	38.01	54.00	-15.99	27.76	3	Horizontal	190	2.93	-	33.03	7.37	30.15			

2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	2.368G	57.56	74.00	-16.44	24.81	3	Vertical	12	1.11	-	28.40	4.35	-				
AV	2.368G	47.06	54.00	-6.94	14.20	3	Vertical	12	1.11	-	28.50	4.36	-				
PK	2.440G	102.06	Inf	-Inf	69.24	3	Vertical	12	1.11	-	28.40	4.42	-				
AV	2.44G	99.09	Inf	-Inf	66.27	3	Vertical	12	1.11	-	28.40	4.42	-				
PK	2.4908G	56.96	74.00	-17.04	23.76	3	Vertical	12	1.11	-	28.71	4.49	-				
AV	2.4956G	47.30	54.00	-6.70	14.04	3	Vertical	12	1.11	-	28.76	4.50	-				

2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)			
PK	2.3832G	57.34	74.00	-16.66	24.48	3	Horizontal	343	1.94	-	28.50	4.36	-			
AV	2.364G	47.24	54.00	-6.76	14.49	3	Horizontal	343	1.94	-	28.40	4.35	-			
PK	2.4404G	109.79	Inf	-Inf	76.97	3	Horizontal	343	1.94	-	28.40	4.42	-			
AV	2.44G	106.92	Inf	-Inf	74.10	3	Horizontal	343	1.94	-	28.40	4.42	-			
PK	2.4988G	57.46	74.00	-16.54	24.17	3	Horizontal	343	1.94	-	28.79	4.50	-			
AV	2.4924G	47.18	54.00	-6.82	13.97	3	Horizontal	343	1.94	-	28.72	4.49	-			

2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	4.8646G	49.13	74.00	-24.87	38.70	3	Vertical	72	2.68	-	33.10	7.44	30.11				
AV	4.883G	37.83	54.00	-16.17	27.37	3	Vertical	72	2.68	-	33.10	7.46	30.10				
PK	7.277G	54.92	74.00	-19.08	40.49	3	Vertical	146	1.81	-	36.31	9.01	30.89				
AV	7.3528G	43.46	54.00	-10.54	28.82	3	Vertical	146	1.81	-	36.51	9.02	30.89				

2.4-2.4835GHz_BT-LE(2Mbps)

2440MHz_TX




EUT_Y_1TX
Setting 0C 0C
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	4.8854G	48.48	74.00	-25.52	38.02	3	Horizontal	128	2.87	-	33.10	7.46	30.10				
AV	4.873G	37.89	54.00	-16.11	27.45	3	Horizontal	128	2.87	-	33.10	7.45	30.11				
PK	7.3578G	53.64	74.00	-20.36	38.99	3	Horizontal	98	2.27	-	36.52	9.02	30.89				
AV	7.3494G	43.59	54.00	-10.41	28.96	3	Horizontal	98	2.27	-	36.50	9.02	30.89				

2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 09 09
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	2.4806G	99.88	Inf	-Inf	66.70	3	Vertical	18	1.26	-	28.70	4.48	-				
AV	2.48G	96.92	Inf	-Inf	63.74	3	Vertical	18	1.26	-	28.70	4.48	-				
PK	2.4835G	57.81	74.00	-16.19	24.63	3	Vertical	18	1.26	-	28.70	4.48	-				
AV	2.4835G	49.35	54.00	-4.65	16.17	3	Vertical	18	1.26	-	28.70	4.48	-				

2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 09 09
02-D-G-5

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA				
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)				
PK	2.4806G	106.03	Inf	-Inf	72.85	3	Horizontal	350	1.74	-	28.70	4.48	-				
AV	2.48G	103.10	Inf	-Inf	69.92	3	Horizontal	350	1.74	-	28.70	4.48	-				
PK	2.4835G	61.59	74.00	-12.41	28.41	3	Horizontal	350	1.74	-	28.70	4.48	-				
AV	2.4835G	53.40	54.00	-0.60	20.22	3	Horizontal	350	1.74	-	28.70	4.48	-				

2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX




EUT_Y_1TX
Setting 09 09
02-D-G-5

Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	5.0078G	48.70	74.00	-25.30	37.80	3	Vertical	61	1.15	-	33.40	7.55	30.05				
AV	4.9942G	38.58	54.00	-15.42	27.69	3	Vertical	61	1.15	-	33.39	7.55	30.05				
PK	7.4814G	54.30	74.00	-19.70	39.66	3	Vertical	202	1.42	-	36.46	9.07	30.89				
AV	7.4708G	43.89	54.00	-10.11	29.27	3	Vertical	202	1.42	-	36.44	9.07	30.89				

2.4-2.4835GHz_BT-LE(2Mbps)

2480MHz_TX



EUT_Y_1TX
Setting 09 09
02-D-G-5


Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Raw (dBuV)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comment	AF (dB)	CL (dB)	PA (dB)				
PK	4.9942G	50.19	74.00	-23.81	39.30	3	Horizontal	339	2.95	-	33.39	7.55	30.05				
AV	4.9942G	38.36	54.00	-15.64	27.47	3	Horizontal	339	2.95	-	33.39	7.55	30.05				
PK	7.458G	53.72	74.00	-20.28	39.13	3	Horizontal	196	1.75	-	36.42	9.06	30.89				
AV	7.432G	43.67	54.00	-10.33	29.04	3	Horizontal	196	1.75	-	36.47	9.05	30.89				



Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 3	Pass	AV	3.7861G	37.72	54.00	-16.28	Horizontal

Mode 3



Mode 3

