


FCC SAR Test Report

APPLICANT : Getac Technology Corporation.
EQUIPMENT : WLAN module
BRAND NAME : Getac
MODEL NAME : 7265NGW
FCC ID : QYL7265NG
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2003

The product was installed into Tablet (Brand Name: Getac, Model Name: RX10) during test.

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.



Reviewed by: Eric Huang / Deputy Manager



Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. Statement of Compliance	4
2. Administration Data	4
3. Guidance Standard	4
4. Equipment Under Test (EUT)	5
4.1 General Information	5
4.2 Maximum Tune-up Limit.....	5
5. RF Exposure Limits.....	10
5.1 Uncontrolled Environment.....	10
5.2 Controlled Environment.....	10
6. Specific Absorption Rate (SAR).....	11
6.1 Introduction	11
6.2 SAR Definition.....	11
7. System Description and Setup	12
8. Measurement Procedures	13
8.1 Spatial Peak SAR Evaluation.....	13
8.2 Power Reference Measurement.....	14
8.3 Area Scan	14
8.4 Zoom Scan.....	15
8.5 Volume Scan Procedures.....	15
8.6 Power Drift Monitoring.....	15
9. Test Equipment List	16
10. System Verification	17
10.1 Tissue Verification	17
10.2 System Performance Check Results.....	18
11. RF Exposure Positions	18
11.1 SAR Testing for Tablet	18
12. Conducted RF Output Power (Unit: dBm).....	19
13. Bluetooth Exclusions Applied	28
14. Antenna Location	29
15. SAR Test Results	31
15.1 Body SAR	31
16. Simultaneous Transmission Analysis	32
16.1 Body Exposure Conditions	32
17. Uncertainty Assessment	33
18. References.....	36
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

[illegible]

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Getac Technology Corporation., WLAN module, 7265NGW**, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary	
		Body 1g SAR (W/kg)	Simultaneous Transmission 1g SAR (W/kg)
DTS	2.4GHz WLAN	0.28	0.64
	5.8GHz WLNA	0.43	
NII	5.2GHz WLAN		0.75
	5.3GHz WLAN	0.54	
	5.5GHz WLAN	0.31	
Date of Testing:		2015/7/21	

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC KDB publications.

2. Administration Data

Testing Laboratory	
Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978

Applicant	
Company Name	Getac Technology Corporation.
Address	5F., Building A, No. 209, Sec.1, Nangang Rd.,Nangang Dist., Taipei City 11568, Taiwan, R.O.C.

Manufacturer	
Company Name	Intel Mobile Communications
Address	100 Center Point Circle, Suite 200, Columbia, South Carolina 29210 USA

3. Guidance Standard

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03
- FCC KDB 865664 D02 SAR Reporting v01r01
- FCC KDB 447498 D01 General RF Exposure Guidance v05r02
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r01
- FCC KDB 616217 D04 SAR for laptop and tablets v01r01

4. Equipment Under Test (EUT)

4.1 General Information

Product Feature & Specification	
Equipment Name	WLAN module
Brand Name	Getac
Model Name	7265NGW
FCC ID	QYL7265NG
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	· 802.11a/b/g/n/ac HT20/HT40/VHT20/VHT40/VHT80 · Bluetooth v3.0+EDR · Bluetooth v4.0-LE
EUT Stage	Production Unit

Host Information	
Host Name	Tablet
Brand Name	Getac
Model Name	RX10
Mode	· NFC

4.2 Maximum Tune-up Limit

Mode		Average Power (dBm)
Bluetooth v3.0+EDR	1Mbps	4
	2Mbps	4
	3Mbps	4
Bluetooth 4.0-LE		4

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain A					
		11b	11g	HT20	VHT20	HT40	VHT40
2.4GHz Band	2412	16.5	14	14			
	2422					13.5	
	2437	17.5	17.5	17.5		17.5	
	2452					12.5	
	2462	16.5	12.5	12.5			

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain B					
		11b	11g	HT20	VHT20	HT40	VHT40
2.4GHz Band	2412	16.5	14.5	14.5			
	2422					13.5	
	2437	17.5	17.5	17.5		17.5	
	2452					13	
	2462	16.5	12.5	12.5			

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) MIMO at both ports A and B					
		11b	11g	HT20	VHT20	HT40	VHT40
2.4GHz Band	2412			15			
	2422					12.5	
	2437			20.5		16.5	
	2452					12.5	
	2462			15			

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain A					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.2GHz Band	5180	14	14		14		
	5190			12		12	
	5200	14.5	14.5		14.5		
	5210						13.5
	5220	14.5	14.5		14.5		
	5230			16.5		16.5	
	5240	14.5	14.5		15		
5.3GHz Band	5260	15.5	15.5		15.5		
	5270			16.5		16.5	
	5280	15.5	15.5		15.5		
	5290						13.5
	5300	15.5	15.5		15.5		
	5310			13.5		13.5	
	5320	13.5	13.5		13.5		

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain A					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.5GHz Band	5500	13.5	13.5		13.5		
	5510			13.5		13.5	
	5530						13.5
	5550			16.5		16.5	
	5580	15.5	15.5		15.5		
	5610						16.5
	5620	15.5	15.5		15.5		
	5630			16.5		16.5	
	5660	15.5	15.5		15.5		
	5670			16.5		16.5	
	5690						16.5
	5700	13	13		13		
	5710			15.5		16.5	
	5720	15.5	15.5		15.5		
5.8GHz Band	5745	15.5	15.5		15.5		
	5755			16.5		16.5	
	5775						16.5
	5785	15.5	15.5		15.5		
	5795			16.5		16.5	
	5825	15.5	15.5		15.5		

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain B					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.2GHz Band	5180	14	14		14		
	5190			13.5		13.5	
	5200	14.5	14.5		15		
	5210						13.5
	5220	14.5	15		15		
	5230			16.5		16.5	
	5240	14.5	14.5		15		
5.3GHz Band	5260	16	16		16		
	5270			16.5		16.5	
	5280	16	16		16		
	5290						13.5
	5300	16	16		16		
	5310			13.5		13.5	
	5320	13.5	13.5		13.5		

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) SISO Chain B					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.5GHz Band	5500	13.5	13.5		13.5		
	5510			14		14	
	5530						13.5
	5550			16.5		16.5	
	5580	16	16		16		
	5610						16.5
	5620	16	16		16		
	5630			16.5		16.5	
	5660	13.5	16		16		
	5670			16.5		16.5	
	5690						16.5
	5700	13	13		13		
	5710			16.5		16.5	
	5720	16	16		16		
5.8GHz Band	5745	15	15		15		
	5755			16.5		16.5	
	5775						16.5
	5785	15	15		15		
	5795			16.5		16.5	
	5825	15	15		15		

Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) MIMO at both ports A and B					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.2GHz Band	5180		14.5		14.5		
	5190			13		13	
	5200		14.5		14.5		
	5210						14.5
	5220		14.5		14.5		
	5230			17.5		17.5	
	5240		14.5		14.5		
5.3GHz Band	5260		16.5		16.5		
	5270			19.5		19.5	
	5280		16.5		16.5		
	5290						14.5
	5300		16.5		16.5		
	5310			14.5		14.5	
	5320		14.5		14.5		



Band / Frequency (MHz)		IEEE 802.11 Average Power (dBm) MIMO at both ports A and B					
		11a	HT20	HT40	VHT20	VHT40	VHT80
5.5GHz Band	5500		13.5		13.5		
	5510			14.5		14.5	
	5530						14.5
	5550			19.5		19.5	
	5580		17.5		17.5		
	5610						19.5
	5620		17.5		17.5		
	5630			19.5		19.5	
	5660		17.5		17.5		
	5670			19.5		19.5	
	5690						19.5
	5700		14		14		
	5710			19.5		19.5	
	5720		16.5		16.5		
5.8GHz Band	5745		16.5		16.5		
	5755			19.5		19.5	
	5775						19.5
	5785		16.5		16.5		
	5795			19.5		19.5	
	5825		16.5		16.5		

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r03 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 21, 2014	Aug. 20, 2015
SPEAG	5GHz System Validation Kit	D5GHzV2	1040	Jun. 22, 2015	Jun. 21, 2016
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 13, 2014	Nov. 12, 2015
SPEAG	Dosimetric E-Field Probe	EX3DV4	3955	Nov. 21, 2014	Nov. 20, 2015
H.M.IRIS	Thermometer	TH-08	TM658	Oct. 21, 2014	Oct. 20, 2015
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Agilent	Signal Generator	N5181A	MY50145381	Dec. 11, 2014	Dec. 10, 2015
Agilent	ENA Network Analyzer	E5071C	MY46316648	Feb. 11, 2015	Feb. 10, 2016
SPEAG	Dielectric Probe Kit	DAK-3.5	1138	Nov. 18, 2014	Nov. 17, 2015
Anritsu	Power Meter	ML2495A	1349001	Dec. 03, 2014	Dec. 02, 2015
Anritsu	Power Sensor	MA2411B	1306099	Dec. 03, 2014	Dec. 02, 2015
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 17, 2015	Jun. 16, 2016
Agilent	Dual Directional Coupler	778D	50422	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	
AR	Power Amplifier	5S1G4M2	0328767	Note 1	
Mini-Circuits	Power Amplifier	ZVE-3W	162601250	Note 1	

General Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

10. System Verification

10.1 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
2450	MSL	22.6	1.996	52.711	1.95	52.70	2.36	0.02	±5	2015/7/21
5300	MSL	22.6	5.573	47.803	5.42	48.90	2.82	-2.24	±5	2015/7/21
5600	MSL	22.6	5.958	47.205	5.77	48.50	3.26	-2.67	±5	2015/7/21
5800	MSL	22.6	6.203	46.981	6.00	48.20	3.38	-2.53	±5	2015/7/21

10.2 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2015/7/21	2450	MSL	250	D2450V2-736	EX3DV4 - SN3955	DAE4 Sn1399	12.00	50.60	48.00	-5.14
2015/7/21	5300	MSL	100	D5GHzV2-1040	EX3DV4 - SN3955	DAE4 Sn1399	7.54	75.20	75.40	0.27
2015/7/21	5600	MSL	100	D5GHzV2-1040	EX3DV4 - SN3955	DAE4 Sn1399	8.20	79.00	82.00	3.80
2015/7/21	5800	MSL	100	D5GHzV2-1040	EX3DV4 - SN3955	DAE4 Sn1399	7.42	76.60	74.20	-3.13




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

11. RF Exposure Positions

11.1 SAR Testing for Tablet

This device can be used also in full sized tablet exposure conditions, due to its size. Per FCC KDB 616217, the back surface and edges of the tablet should be tested for SAR compliance with the tablet touching the phantom. The SAR exclusion threshold in KDB 447498 D01v05r02 can be applied to determine SAR test exclusion for adjacent edge configurations. The closest distance from the antenna to an adjacent tablet edge is used to determine if SAR testing is required for the adjacent edges, with the adjacent edge positioned against the phantom and the edge containing the antenna positioned perpendicular to the phantom.

12. Conducted RF Output Power (Unit: dBm)

<WLAN Conducted Power>

General Note:

1. For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
2. Per KDB 248227 D01v02r01, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is $< 1.6\text{W/kg}$ and SAR peak to location ratio < 0.04 , no additional SAR measurements for MIMO.
3. Per KDB 248227 D01v02r01, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
4. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
5. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
6. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is $\leq 0.4\text{ W/kg}$, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is $> 0.4\text{ W/kg}$, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is $\leq 0.8\text{ W/kg}$ or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is $> 0.8\text{ W/kg}$, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is $\leq 1.2\text{ W/kg}$ or all required channels are tested.

<2.4GHz WLAN Antenna A>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Antenna A	802.11b	CH 1	2412	1Mbps	15.90	98.96
		CH 6	2437		17.20	
		CH 11	2462		16.49	
	802.11g	CH 1	2412	6Mbps	13.82	98.57
		CH 6	2437		17.10	
		CH 11	2462		12.11	
	802.11n-HT20	CH 1	2412	MCS0	13.74	98.47
		CH 6	2437		17.17	
		CH 11	2462		12.11	
	802.11n-HT40	CH 3	2422	MCS0	13.07	97.53
		CH 6	2437		17.17	
		CH 9	2452		12.06	

<2.4GHz WLAN Antenna B>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Antenna B	802.11b	CH 1	2412	1Mbps	16.19	98.96
		CH 6	2437		17.16	
		CH 11	2462		16.05	
	802.11g	CH 1	2412	6Mbps	14.32	99.04
		CH 6	2437		17.49	
		CH 11	2462		12.41	
	802.11n-HT20	CH 1	2412	MCS0	14.23	98.46
		CH 6	2437		17.48	
		CH 11	2462		12.17	
	802.11n-HT40	CH 3	2422	MCS0	13.47	97.53
		CH 6	2437		17.29	
		CH 9	2452		11.27	

<2.4GHz WLAN Antenna A+B>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
2.4GHz WLAN Antenna A+B	802.11n-HT20	CH 1	2412	MCS0	14.81	96.82
		CH 6	2437		19.99	
		CH 11	2462		14.96	
	802.11n-HT40	CH 3	2422	MCS0	12.47	95.13
		CH 6	2437		16.44	
		CH 9	2452		12.28	

<5GHz WLAN Antenna A>

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
5.2GHz WLAN Antenna A	802.11a	CH 36	5180	6Mbps	13.83	98.47
		CH 40	5200		14.31	
		CH 44	5220		14.38	
		CH 48	5240		14.34	
	802.11n-HT20	CH 36	5180	MCS0	13.62	98.36
		CH 40	5200		13.63	
		CH 44	5220		14.25	
		CH 48	5240		14.20	
	802.11n-HT40	CH 38	5190	MCS0	11.49	96.94
		CH 46	5230		16.26	
	802.11ac-VHT20	CH 36	5180	MCS0	13.70	98.37
		CH 40	5200		13.99	
		CH 44	5220		14.03	
		CH 48	5240		14.50	
	802.11ac-VHT40	CH 38	5190	MCS0	11.42	96.97
		CH 46	5230		16.11	
	802.11ac-VHT80	CH 42	5210	MCS0	13.49	93.67

	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
5.3GHz WLAN Antenna A	802.11a	CH 52	5260	6Mbps	15.21	98.47
		CH 56	5280		15.14	
		CH 60	5300		15.17	
		CH 64	5320		12.95	
	802.11n-HT20	CH 52	5260	MCS0	15.18	98.36
		CH 56	5280		15.23	
		CH 60	5300		15.48	
		CH 64	5320		13.14	
	802.11n-HT40	CH 54	5270	MCS0	16.05	96.94
		CH 62	5310		13.14	
	802.11ac-VHT20	CH 52	5260	MCS0	15.08	98.37
		CH 56	5280		15.41	
		CH 60	5300		15.45	
		CH 64	5320		13.03	
	802.11ac-VHT40	CH 54	5270	MCS0	16.05	96.97
		CH 62	5310		13.04	
	802.11ac-VHT80	CH 58	5290	MCS0	13.00	93.67

5.5GHz WLAN Antenna A	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 100	5500	6Mbps	13.50	98.47
		CH 116	5580		15.25	
		CH 124	5620		15.12	
		CH 132	5660		15.19	
		CH 144	5720		15.14	
	802.11n-HT20	CH 100	5500	MCS0	13.01	98.36
		CH 116	5580		15.41	
		CH 124	5620		15.21	
		CH 132	5660		15.31	
		CH 144	5720		15.14	
	802.11n-HT40	CH 102	5510	MCS0	13.01	96.94
		CH 110	5550		15.94	
		CH 126	5630		15.93	
		CH 134	5670		15.94	
		CH 142	5710		15.48	
	802.11ac-VHT20	CH 100	5500	MCS0	13.24	98.37
		CH 116	5580		15.38	
		CH 124	5620		15.36	
		CH 132	5660		15.37	
		CH 144	5720		15.43	
	802.11ac-VHT40	CH 102	5510	MCS0	12.94	96.97
		CH 110	5550		15.84	
		CH 126	5630		15.75	
		CH 134	5670		15.95	
		CH 142	5710		15.92	
	802.11ac-VHT80	CH 106	5530	MCS0	13.21	93.67
		CH 122	5610		16.20	
		CH 138	5690		16.11	

5.8GHz WLAN Antenna A	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 149	5745	MCS0	15.18	98.47
		CH 157	5785		15.43	
		CH 165	5825		15.22	
	802.11n-HT20	CH 149	5745	MCS0	15.41	98.36
		CH 157	5785		15.16	
		CH 165	5825		15.08	
	802.11n-HT40	CH 151	5755	MCS0	16.24	96.94
		CH 159	5795		16.28	
	802.11ac-VHT20	CH 149	5745	MCS0	15.35	98.37
		CH 157	5785		15.00	
		CH 165	5825		14.98	
	802.11ac-VHT40	CH 151	5755	MCS0	16.07	96.97
		CH 159	5795		15.99	
	802.11ac-VHT80	CH 155	5775	MCS0	16.25	93.67

<5GHz WLAN Antenna B>

5.2GHz WLAN Antenna B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 36	5180	6Mbps	13.68	98.47
		CH 40	5200		14.09	
		CH 44	5220		14.22	
		CH 48	5240		14.40	
	802.11n-HT20	CH 36	5180	MCS0	13.83	98.36
		CH 40	5200		13.68	
		CH 44	5220		14.51	
		CH 48	5240		14.44	
	802.11n-HT40	CH 38	5190	MCS0	13.08	96.91
		CH 46	5230		15.93	
	802.11ac-VHT20	CH 36	5180	MCS0	13.60	98.37
		CH 40	5200		14.30	
		CH 44	5220		14.49	
		CH 48	5240		14.20	
	802.11ac-VHT40	CH 38	5190	MCS0	12.92	96.94
		CH 46	5230		16.08	
	802.11ac-VHT80	CH 42	5210	MCS0	13.48	93.67

5.3GHz WLAN Antenna B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 52	5260	6Mbps	15.79	98.47
		CH 56	5280		15.45	
		CH 60	5300		15.67	
		CH 64	5320		13.07	
	802.11n-HT20	CH 52	5260	MCS0	15.66	98.36
		CH 56	5280		15.73	
		CH 60	5300		15.74	
		CH 64	5320		12.95	
	802.11n-HT40	CH 54	5270	MCS0	15.90	96.91
		CH 62	5310		12.93	
	802.11ac-VHT20	CH 52	5260	MCS0	15.79	98.37
		CH 56	5280		15.78	
		CH 60	5300		15.77	
		CH 64	5320		12.99	
	802.11ac-VHT40	CH 54	5270	MCS0	15.92	96.94
		CH 62	5310		12.94	
	802.11ac-VHT80	CH 58	5290	MCS0	13.02	93.67

5.5GHz WLAN Antenna B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 100	5500	6Mbps	12.98	98.47
		CH 116	5580		15.65	
		CH 124	5620		15.61	
		CH 132	5660		12.98	
		CH 144	5720		15.60	
	802.11n-HT20	CH 100	5500	MCS0	12.93	98.36
		CH 116	5580		15.99	
		CH 124	5620		15.97	
		CH 132	5660		15.98	
		CH 144	5720		15.98	
	802.11n-HT40	CH 102	5510	MCS0	13.13	96.91
		CH 110	5550		15.92	
		CH 126	5630		15.80	
		CH 134	5670		16.49	
		CH 142	5710		16.13	
	802.11ac-VHT20	CH 100	5500	MCS0	13.26	98.37
		CH 116	5580		15.92	
		CH 124	5620		15.91	
		CH 132	5660		15.87	
		CH 144	5720		15.85	
	802.11ac-VHT40	CH 102	5510	MCS0	13.19	96.94
		CH 110	5550		15.91	
		CH 126	5630		15.80	
		CH 134	5670		16.49	
		CH 142	5710		16.20	
	802.11ac-VHT80	CH 106	5530	MCS0	13.48	93.67
		CH 122	5610		16.31	
		CH 138	5690		16.16	

5.8GHz WLAN Antenna B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11a	CH 149	5745	MCS0	14.85	98.47
		CH 157	5785		14.68	
		CH 165	5825		14.97	
	802.11n-HT20	CH 149	5745	MCS0	14.78	98.36
		CH 157	5785		14.59	
		CH 165	5825		14.55	
	802.11n-HT40	CH 151	5755	MCS0	16.17	96.91
		CH 159	5795		16.12	
	802.11ac-VHT20	CH 149	5745	MCS0	14.99	98.37
		CH 157	5785		14.53	
		CH 165	5825		14.83	
	802.11ac-VHT40	CH 151	5755	MCS0	16.18	96.94
		CH 159	5795		16.09	
	802.11ac-VHT80	CH 155	5775	MCS0	16.44	93.67

<5GHz WLAN Antenna A+B>

5.2GHz WLAN Antenna A+B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11n-HT20	CH 36	5180	MCS0	14.15	97.03
		CH 40	5200		14.26	
		CH 44	5220		14.33	
		CH 48	5240		14.29	
	802.11n-HT40	CH 38	5190	MCS0	12.76	94.32
		CH 46	5230		16.83	
	802.11ac-VHT20	CH 36	5180	MCS0	14.27	97.06
		CH 40	5200		14.32	
		CH 44	5220		14.30	
		CH 48	5240		14.37	
	802.11ac-VHT40	CH 38	5190	MCS0	12.59	94.38
		CH 46	5230		16.80	
	802.11ac-VHT80	CH 42	5210	MCS0	14.49	90.14

5.5GHz WLAN Antenna A+B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11n-HT20	CH 52	5260	MCS0	16.43	97.03
		CH 56	5280		16.45	
		CH 60	5300		16.49	
		CH 64	5320		14.38	
	802.11n-HT40	CH 54	5270	MCS0	19.42	94.32
		CH 62	5310		14.45	
	802.11ac-VHT20	CH 52	5260	MCS0	16.47	97.06
		CH 56	5280		16.48	
		CH 60	5300		16.28	
		CH 64	5320		14.45	
	802.11ac-VHT40	CH 54	5270	MCS0	19.46	94.38
		CH 62	5310		14.49	
	802.11ac-VHT80	CH 58	5290	MCS0	14.48	90.14

5.5GHz WLAN Antenna A+B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11n-HT20	CH 100	5500	MCS0	13.31	97.03
		CH 116	5580		17.40	
		CH 124	5620		17.28	
		CH 132	5660		17.25	
		CH 144	5720		16.01	
	802.11n-HT40	CH 102	5510	MCS0	14.15	94.32
		CH 110	5550		19.28	
		CH 126	5630		19.28	
		CH 134	5670		19.37	
		CH 142	5710		19.18	
	802.11ac-VHT20	CH 100	5500	MCS0	13.41	97.06
		CH 116	5580		17.44	
		CH 124	5620		17.41	
		CH 132	5660		17.36	
		CH 144	5720		16.34	
	802.11ac-VHT40	CH 102	5510	MCS0	14.36	94.38
		CH 110	5550		19.24	
		CH 126	5630		19.33	
		CH 134	5670		19.40	
		CH 142	5710		19.36	
	802.11ac-VHT80	CH 106	5530	MCS0	14.31	90.14
		CH 122	5610		19.47	
		CH 138	5690		19.35	

5.8GHz WLAN Antenna A+B	Mode	Channel	Frequency (MHz)	Data Rate	Average power (dBm)	Duty Cycle %
	802.11n-HT20	CH 149	5745	MCS0	16.20	97.03
		CH 157	5785		16.10	
		CH 165	5825		16.33	
	802.11n-HT40	CH 151	5755	MCS0	19.42	94.32
		CH 159	5795		19.15	
	802.11ac-VHT20	CH 149	5745	MCS0	16.17	97.06
		CH 157	5785		16.12	
		CH 165	5825		16.48	
	802.11ac-VHT40	CH 151	5755	MCS0	19.23	94.38
		CH 159	5795		19.14	
	802.11ac-VHT80	CH 155	5775	MCS0	19.43	90.14

13. Bluetooth Exclusions Applied

Mode Band	Average power(dBm)	
	v3.0+EDR	v4.0+LE
2.4GHz Bluetooth	4.0	4.0

Note:

- Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:


$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
for 1-g SAR and ≤ 7.5 for 10-g extremity SAR
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison

Bluetooth Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
4	< 5	2.48	0.94

Note:

Per KDB 447498 D01v05r02, when the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. The test exclusion threshold is 0.94 which is ≤ 3 , SAR testing is not required.

14. Antenna Location



<SAR test exclusion table>
General Note:

1. The below table, when the distance is < 50 mm exclusion threshold is "Ratio", when the distance is > 50 mm exclusion threshold is "mW"
2. Maximum power is the source-based time-average power and represents the maximum RF output power among production units
3. Per KDB 447498 D01v05r02, for larger devices, the test separation distance of adjacent edge configuration is determined by the closest separation between the antenna and the user.
4. Per KDB 447498 D01v05r02, standalone SAR test exclusion threshold is applied; If the test separation distance is < 5mm, 5mm is used to determine SAR exclusion threshold.
5. Per KDB 447498 D01v05r02, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation
 - The result is rounded to one decimal place for comparison
6. Per KDB 447498 D01v05r02, at 100 MHz to 6 GHz and for *test separation distances* > 50 mm, the SAR test exclusion threshold is determined according to the following
 - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · (f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm) · 10] mW at > 1500 MHz and ≤ 6 GHz

Exposure Position	Wireless Interface	2.4GHz WLAN Ant A	2.4GHz WLAN Ant B	5GHz WLAN Ant A	5GHz WLAN Ant B
	Calculated Frequency	2462MHz	2462MHz	5825MHz	5825MHz
	Maximum power (dBm)	17.5	17.5	16.5	16.5
	Maximum rated power(mW)	56.0	56.0	45.0	45.0
Bottom Face	Separation distance(mm)	5.0	5.0	5.0	5.0
	exclusion threshold	17.6	17.6	21.7	21.7
	Testing required?	Yes	Yes	Yes	Yes
Edge 1	Separation distance(mm)	55.4	5.0	55.4	5.0
	exclusion threshold	149.0	17.6	116.0	21.7
	Testing required?	No	Yes	No	Yes
Edge 2	Separation distance(mm)	133.8	150.2	133.8	150.2
	exclusion threshold	933.0	1097.0	900.0	1064.0
	Testing required?	No	No	No	No
Edge 3	Separation distance(mm)	182.1	230.5	182.1	230.5
	exclusion threshold	1417.0	1901.0	1383.0	1867.0
	Testing required?	No	No	No	No
Edge 4	Separation distance(mm)	99.7	94.7	99.7	94.7
	exclusion threshold	593.0	543.0	559.0	509.0
	Testing required?	No	No	No	No

15. SAR Test Results

General Note:

- Per KDB 447498 D01v05r02, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - For WLAN: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
- Per KDB 865664 D01v01r03, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
- Per KDB 248227 D01v02r01, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
- Per KDB 248227 D01v02r01, for U-NII-1 Body SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
- When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
- For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
- For WLAN SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
- Per KDB 248227 D01v02r01, the simultaneous SAR provisions in KDB publication 447498 should be applied to determine simultaneous transmission SAR test exclusion for WiFi MIMO. If the sum of 1g single transmission chain SAR measurements is < 1.6 W/kg and SAR peak to location ratio < 0.04 , no additional SAR measurements for MIMO.
- During SAR testing the WLAN transmission was verified using a spectrum analyzer.

15.1 Body SAR

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Main	6	2437	17.20	17.50	1.073	98.96	1.011	-0.14	0.042	0.046
	WLAN2.4GHz	802.11b 1Mbps	Bottom Face	0mm	Aux	6	2437	17.16	17.50	1.083	98.96	1.011	-0.04	0.117	0.128
	WLAN2.4GHz	802.11b 1Mbps	Edge 1	0mm	Aux	6	2437	17.16	17.50	1.083	98.96	1.011	-0.14	0.254	0.278
02	WLAN5GHz	802.11n-HT40 MCS0	Bottom Face	0mm	Main	54	5270	16.05	16.50	1.108	96.94	1.032	0.13	0.115	0.131
	WLAN5GHz	802.11n-HT40 MCS0	Bottom Face	0mm	Aux	54	5270	15.90	16.50	1.149	96.61	1.035	-0.11	0.457	0.544
	WLAN5GHz	802.11n-HT40 MCS0	Edge 1	0mm	Aux	54	5270	15.90	16.50	1.149	96.61	1.035	-0.16	0.179	0.213
03	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Main	122	5610	16.20	16.50	1.071	93.67	1.068	-0.03	0.184	0.210
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Aux	122	5610	16.31	16.50	1.044	93.67	1.068	-0.07	0.279	0.311
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Aux	122	5610	16.31	16.50	1.044	93.67	1.068	0.07	0.106	0.118
04	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Main	155	5775	16.25	16.50	1.059	93.67	1.068	-0.07	0.185	0.209
	WLAN5GHz	802.11ac-VHT80 MCS0	Bottom Face	0mm	Aux	155	5775	16.44	16.50	1.014	93.67	1.068	-0.05	0.395	0.428
	WLAN5GHz	802.11ac-VHT80 MCS0	Edge 1	0mm	Aux	155	5775	16.44	16.50	1.014	93.67	1.068	-0.06	0.144	0.156

16. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Support
1.	WLAN + Bluetooth	Yes
2.	WLAN Main Antenna A + WLAN Aux. Antenna B	Yes

General Note:

- For SAR testing was performed on single antenna RF power in SISO mode is larger or equal to the single antenna RF power in MIMO mode, and for RF exposure assessment of MIMO mode simultaneous transmission exclusion analysis was performed with SAR test results of each antenna in SISO mode.
- EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
- The Scaled SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v05r02, simultaneous transmission SAR is compliant if,
 - Scalar SAR summation $< 1.6 \text{ W/kg}$.
 - $\text{SPLSR} = (\text{SAR1} + \text{SAR2})^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where $(x1, y1, z1)$ and $(x2, y2, z2)$ are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $\text{SPLSR} \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band SAR $< 1.6 \text{ W/kg}$.
- For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01v05r02 based on the formula below.
 - $(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})} / x] \text{ W/kg}$ for test separation distances $\leq 50 \text{ mm}$; where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
 - When the minimum separation distance is $< 5 \text{ mm}$, the distance is used 5mm to determine SAR test exclusion.
 - 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distances is $> 50 \text{ mm}$.
 - Bluetooth estimated SAR is conservatively determined by 5mm separation, for all applicable exposure positions.

Bluetooth Max Power	Exposure Position	All Positions
4.0 dBm	Estimated SAR (W/kg)	0.126 W/kg

16.1 Body Exposure Conditions

Exposure Position	1	2	3	4	5	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	4+5 Summed 1g SAR (W/kg)
	2.4GHz / 5.8GHz WLAN Ant A	2.4GHz / 5.8GHz WLAN Ant B	2.4GHz Bluetooth	5.2GHz / 5.3GHz / 5.5GHz WLAN Ant A	5.2GHz / 5.3GHz / 5.5GHz WLAN Ant B			
	1g SAR (W/kg)	1g SAR (W/kg)	Estimated 1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
Bottom Face at 0mm	0.209	0.428	0.126	0.210	0.544	0.64	0.34	0.75
Edge 1 at 0mm		0.278	0.126		0.213	0.28	0.13	0.21

Test Engineer : Kurt Liu

17. Uncertainty Assessment

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience, and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in table below.

Uncertainty Distributions	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor ^(a)	$1/k^{(b)}$	$1/\sqrt{3}$	$1/\sqrt{6}$	$1/\sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Table 17.1. Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is shown in the following tables.

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.0	Normal	1	1	1	± 6.0 %	± 6.0 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.4	Rectangular	√3	1	1	± 0.2 %	± 0.2 %
Probe Positioning	2.9	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Max. SAR Eval.	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 11.0 %	± 10.8 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 22.0 %	± 21.5 %

Table 17.2. Uncertainty Budget for frequency range 300 MHz to 3 GHz

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Ci (10g)	Standard Uncertainty (1g)	Standard Uncertainty (10g)
Measurement System							
Probe Calibration	6.55	Normal	1	1	1	± 6.55 %	± 6.55 %
Axial Isotropy	4.7	Rectangular	√3	0.7	0.7	± 1.9 %	± 1.9 %
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	0.7	± 3.9 %	± 3.9 %
Boundary Effects	2.0	Rectangular	√3	1	1	± 1.2 %	± 1.2 %
Linearity	4.7	Rectangular	√3	1	1	± 2.7 %	± 2.7 %
System Detection Limits	1.0	Rectangular	√3	1	1	± 0.6 %	± 0.6 %
Readout Electronics	0.3	Normal	1	1	1	± 0.3 %	± 0.3 %
Response Time	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Integration Time	2.6	Rectangular	√3	1	1	± 1.5 %	± 1.5 %
RF Ambient Noise	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
RF Ambient Reflections	3.0	Rectangular	√3	1	1	± 1.7 %	± 1.7 %
Probe Positioner	0.8	Rectangular	√3	1	1	± 0.5 %	± 0.5 %
Probe Positioning	9.9	Rectangular	√3	1	1	± 5.7 %	± 5.7 %
Max. SAR Eval.	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Test Sample Related							
Device Positioning	2.9	Normal	1	1	1	± 2.9 %	± 2.9 %
Device Holder	3.6	Normal	1	1	1	± 3.6 %	± 3.6 %
Power Drift	5.0	Rectangular	√3	1	1	± 2.9 %	± 2.9 %
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	1	± 2.3 %	± 2.3 %
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	0.43	± 1.8 %	± 1.2 %
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	0.43	± 1.6 %	± 1.1 %
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	0.49	± 1.7 %	± 1.4 %
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	0.49	± 1.5 %	± 1.2 %
Combined Standard Uncertainty						± 12.8 %	± 12.6 %
Coverage Factor for 95 %						K=2	
Expanded Uncertainty						± 25.6 %	± 25.2 %

Table 17.3. Uncertainty Budget for frequency range 3 GHz to 6 GHz

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r01, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Jun 2015.
- [6] FCC KDB 447498 D01 v05r02, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Feb 2014
- [7] FCC KDB 616217 D04 v01r01, "SAR Evaluation Considerations for Laptop, Notebook, Netbook and Tablet Computers", May 2013
- [8] FCC KDB 865664 D01 v01r03, "SAR Measurement Requirements for 100 MHz to 6 GHz", Feb 2014.
- [9] FCC KDB 865664 D02 v01r01, "RF Exposure Compliance Reporting and Documentation Considerations" May 2013.