

Variant FCC Test Report

(PART 24)

Report No.: RF180227C27D-6

FCC ID: QYLEM7511K

Test Model: K120

Received Date: Mar. 25, 2019

Test Date: Apr. 16 ~ Apr. 23, 2019

Issued Date: May 14, 2019

Applicant: Getac Technology Corporation.

Address: 5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist., Taipei City
11568, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
(R.O.C)

Test Location (1): No. 19, Hwa Ya 2nd Rd, Wen Hwa Vil, Kwei Shan Dist., Taoyuan City
33383, Taiwan (R.O.C)

Test Location (2): B2F., No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231,
Taiwan, R.O.C

FCC Registration / 788550 / TW0003

Designation Number: 427177 / TW0011



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 Summary of Test Results.....	5
2.1 Measurement Uncertainty.....	5
2.2 Test Site and Instruments	6
3 General Information	8
3.1 General Description of EUT	8
3.2 Configuration of System under Test.....	10
3.3 Test Mode Applicability and Tested Channel Detail	11
3.4 EUT Operating Conditions	12
3.5 General Description of Applied Standards.....	12
4 Test Types and Results	13
4.1 Output Power Measurement.....	13
4.1.1 Limits of Output Power Measurement	13
4.1.2 Test Procedures.....	13
4.1.3 Test Setup.....	14
4.1.4 Test Results	15
4.2 Radiated Emission Measurement.....	21
4.2.1 Limits of Radiated Emission Measurement	21
4.2.2 Test Procedure	21
4.2.3 Deviation from Test Standard	21
4.2.4 Test Setup.....	22
4.2.5 Test Results	23
5 Pictures of Test Arrangements.....	47
Appendix – Information of the Testing Laboratories	48

Release Control Record

Issue No.	Description	Date Issued
RF180227C27D-6	Original Release	May 14, 2019

1 Certificate of Conformity

Product: Tablet

Brand: Getac

Test Model: K120

Sample Status: Identical Prototype

Applicant: Getac Technology Corporation.

Test Date: Apr. 16 ~ Apr. 23, 2019

Standards: FCC Part 24, Subpart E

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by :

Lena Wang

, **Date:** May 14, 2019

Lena Wang / Specialist

Approved by :

Dylan Chiou

, **Date:** May 14, 2019

Dylan Chiou / Project Engineer

2 Summary of Test Results

Applied Standard: FCC Part 24 & Part 2			
FCC Clause	Test Item	Result	Remarks
2.1046 24.232(c)	Effective Isotropic Radiated Power	N/A	Refer to Note
2.1047	Modulation Characteristics	N/A	Refer to Note
2.1046 24.232(d)	Peak to Average Ratio	N/A	Refer to Note
2.1055 24.235	Frequency Stability	N/A	Refer to Note
2.1049	Occupied Bandwidth	N/A	Refer to Note
24.238	Band Edge Measurements	N/A	Refer to Note
2.1051 24.238	Conducted Spurious Emissions	N/A	Refer to Note
2.1053 24.238	Radiated Spurious Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -32.78 dB at 223.59 MHz.

Note:

1. This report is a partial report, only test item of Radiated Emissions were performed for this report. Other testing data please refer to TTL report no.: FG791919B for module (Brand: Sierra, Model: EM7511).
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	9 kHz ~ 30 MHz	3.0400 dB
	30 MHz ~ 200 MHz	2.0153 dB
	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
	18 GHz ~ 40 GHz	1.1508 dB

2.2 Test Site and Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Aug. 20, 2018	Aug. 19, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSW26	102023	Oct. 11, 2018	Oct. 10, 2019
BILOG Antenna SCHWARZBECK	VULB9168	9168-616	Nov. 27, 2018	Nov. 26, 2019
HORN Antenna SCHWARZBECK	3117	00155510	Nov. 25, 2018	Nov. 24, 2019
HORN Antenna ETS-Lindgren	3117	00143293	Nov. 25, 2018	Nov. 24, 2019
HORN Antenna SCHWARZBECK	BBHA9170	9170-480	Nov. 25, 2018	Nov. 24, 2019
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-969	Nov. 25, 2018	Nov. 24, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020
MXG Vector signal generator Agilent	N5182B	MY53050430	Nov. 19, 2018	Nov. 18, 2019
Preamplifier Agilent	310N	187226	Jun. 19, 2018	Jun. 18, 2019
Preamplifier Agilent	83017A	MY39501357	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-400)	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RFC-SMS-100-SMS-24)	Jun. 19, 2018	Jun. 18, 2019
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower & Turn Table Controller MF	MF-7802	NA	NA	NA
Communications Tester- Wireless Agilent	8960 Series 10	MY53201073	Jun. 28, 2017	Jun. 27, 2019
Radio Communication Analyzer Anritsu	MT8820C	6201300640	Aug. 16, 2017	Aug. 15, 2019
Temperature & Humidity Chamber	GTH-120-40-CP-AR	MAA1306-019	Sep. 05, 2018	Sep. 04, 2019

- Note:
1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HsinTien Chamber 1.
 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.

3 General Information

3.1 General Description of EUT

Product	Tablet	
Brand	Getac	
Test Model	K120	
Status of EUT	Identical Prototype	
Power Supply Rating	11.1 Vdc / 14.4 Vdc (Battery) 19 Vdc (Adapter)	
Modulation Type	WCDMA	QPSK
	LTE	QPSK, 16QAM, 64QAM
Frequency Range	WCDMA	1852.4 ~ 1907.6 MHz
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	1850.7 ~ 1909.3 MHz
	LTE Band 2 (Channel Bandwidth: 3 MHz)	1851.5 ~ 1908.5 MHz
	LTE Band 2 (Channel Bandwidth: 5 MHz)	1852.5 ~ 1907.5 MHz
	LTE Band 2 (Channel Bandwidth: 10 MHz)	1855.0 ~ 1905.0 MHz
	LTE Band 2 (Channel Bandwidth: 15 MHz)	1857.5 ~ 1902.5 MHz
	LTE Band 2 (Channel Bandwidth: 20 MHz)	1860.0 ~ 1900.0 MHz
Max. EIRP Power	WCDMA	234.96 mW
	LTE Band 2 (Channel Bandwidth: 1.4 MHz)	140.93 mW
	LTE Band 2 (Channel Bandwidth: 3 MHz)	136.24 mW
	LTE Band 2 (Channel Bandwidth: 5 MHz)	140.06 mW
	LTE Band 2 (Channel Bandwidth: 10 MHz)	119.21 mW
	LTE Band 2 (Channel Bandwidth: 15 MHz)	120.31 mW
	LTE Band 2 (Channel Bandwidth: 20 MHz)	145.31 mW
Antenna Type	PIFA Antenna with 1.28 dBi gain	
Accessory Device	Refer to Note as below	
Data Cable Supplied	Refer to Note as below	

Note:

1. This report is issued as a supplementary report to BV CPS report no. RF180227C27-6. The difference compared with original report is adding WWAN Module (EM7511), therefore the EUT is re-tested in this report.


2. The EUT contains following accessory devices.

Product	Brand	Model	Description
Adapter	Chicony	A12-065N2A	I/P: 100-240 Vac, 50-60 Hz, 1.7 A O/P: 19 Vdc, 3.42 A 1.75 m shielded cable with 1 core
Battery 1	Getac	BP3S1P2100S-01	11.1 Vdc, 2100 mAh
Battery 2	Getac	BP4S1P3450P-01	14.4 Vdc, 3450 mAh
WWAN Module 1	Sierra	EM7455	--
WWAN Module 2	Sierra	EM7511	--
WiFi & BT Module	Intel	8265NGW	--
RFID Module	NXP	PN-7462	--
Bar code Reader	HONEYWELL	N6603	--
Fingerprint	IMD	SF1155	--


3. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Configuration of System under Test

<Radiated Emission Test>



<E.I.R.P. Test>



3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis, and antenna ports.

The worst case was found when positioned as the table below. Following channel(s) was (were) selected for the final test as listed below:

Band	EIRP	Radiated Emission
WCDMA	Z-plane	NB-axis
LTE Band 2	Z-plane	Y-axis

WCDMA

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Mode
-	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
-	Radiated Emission	9262 to 9538	9262, 9400, 9538	WCDMA

LTE Band 2

EUT Configure Mode	Test Item	Available Channel	Tested Channel	Channel Bandwidth	Modulation	Mode
-	EIRP	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK, 16QAM, 64QAM	1 RB / 0 RB Offset
-	Radiated Emission	18607 to 19193	18607, 18900, 19193	1.4 MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5 MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20 MHz	QPSK	1 RB / 0 RB Offset

Note:

1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.
2. For radiated emission above 1 GHz, according to 3GPP 36.521 Section 6.6.3.1.4, choose the lowest, 5 MHz & highest channel bandwidth for final test.

Test Condition:

Test Item	Environmental Conditions	Input Power	Tested By
EIRP	26 deg. C, 58 % RH	11.1 Vdc / 14.4 Vdc	Karl Lee
Radiated Emission	25 deg. C, 65 % RH	120 Vac, 60 Hz	Karl Lee

3.4 EUT Operating Conditions

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-E 2016

ANSI 63.26-2015

ANSI 63.2 -1996

NOTE: All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Output Power Measurement

4.1.1 Limits of Output Power Measurement

Mobile / Portable station are limited to 2 watts e.i.r.p.

4.1.2 Test Procedures

EIRP / ERP Measurement:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 5 MHz for WCDMA and 10 MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step b. Record the power level of S.G.
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $E.R.P \text{ power} = E.I.R.P \text{ power} - 2.15 \text{ dB}$.


Conducted Power Measurement:

The EUT was set up for the maximum power with WCDMA and LTE link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.


4.1.3 Test Setup

EIRP / ERP Measurement:

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.4 Test Results

EIRP Power (dBm)

WCDMA							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	9262	1852.4	-14.48	38.19	23.71	234.96	H
	9400	1880.0	-15.10	38.70	23.60	229.09	
	9538	1907.6	-15.71	39.35	23.64	231.21	
	9262	1852.4	-16.76	38.48	21.72	148.59	V
	9400	1880.0	-16.96	38.59	21.63	145.55	
	9538	1907.6	-17.20	38.87	21.67	146.89	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 1.4 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18607	1850.7	-23.32	44.70	21.38	137.40	H
	18900	1880.0	-23.21	44.70	21.49	140.93	
	19193	1909.3	-23.93	44.57	20.64	115.96	
	18607	1850.7	-24.92	44.27	19.35	86.10	V
	18900	1880.0	-25.27	44.87	19.60	91.20	
	19193	1909.3	-25.17	44.61	19.44	87.96	
Channel Bandwidth: 1.4 MHz / 16QAM							
Z	18607	1850.7	-24.27	44.70	20.43	110.41	H
	18900	1880.0	-24.90	44.70	19.80	95.50	
	19193	1909.3	-24.69	44.57	19.88	97.34	
	18607	1850.7	-25.94	44.27	18.33	68.08	V
	18900	1880.0	-26.97	44.87	17.90	61.66	
	19193	1909.3	-26.87	44.61	17.74	59.47	
Channel Bandwidth: 1.4 MHz / 64QAM							
Z	18607	1850.7	-25.25	44.70	19.45	88.10	H
	18900	1880.0	-25.56	44.70	19.14	82.04	
	19193	1909.3	-25.86	44.57	18.71	74.35	
	18607	1850.7	-27.21	44.27	17.06	50.82	V
	18900	1880.0	-27.27	44.87	17.60	57.54	
	19193	1909.3	-27.59	44.61	17.02	50.38	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 3 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18615	1851.5	-23.81	44.70	20.89	122.74	H
	18900	1880.0	-23.44	44.70	21.26	133.66	
	19185	1908.5	-23.23	44.57	21.34	136.24	
	18615	1851.5	-25.16	44.27	19.11	81.47	V
	18900	1880.0	-25.57	44.87	19.30	85.11	
	19185	1908.5	-25.61	44.61	19.00	79.49	
Channel Bandwidth: 3 MHz / 16QAM							
Z	18615	1851.5	-24.24	44.70	20.46	111.17	H
	18900	1880.0	-24.92	44.70	19.78	95.06	
	19185	1908.5	-24.09	44.57	20.48	111.76	
	18615	1851.5	-26.59	44.27	17.68	58.61	V
	18900	1880.0	-26.34	44.87	18.53	71.29	
	19185	1908.5	-26.11	44.61	18.50	70.84	
Channel Bandwidth: 3 MHz / 64QAM							
Z	18615	1851.5	-25.21	44.70	19.49	88.92	H
	18900	1880.0	-25.35	44.70	19.35	86.10	
	19185	1908.5	-25.51	44.57	19.06	80.59	
	18615	1851.5	-27.23	44.27	17.04	50.58	V
	18900	1880.0	-27.34	44.87	17.53	56.62	
	19185	1908.5	-27.17	44.61	17.44	55.50	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 5 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18625	1852.5	-23.50	44.70	21.20	131.83	H
	18900	1880.0	-23.25	44.70	21.45	139.64	
	19175	1907.5	-23.11	44.57	21.46	140.06	
	18625	1852.5	-25.46	44.27	18.81	76.03	V
	18900	1880.0	-25.25	44.87	19.62	91.62	
	19175	1907.5	-25.46	44.61	19.15	82.28	
Channel Bandwidth: 5 MHz / 16QAM							
Z	18625	1852.5	-24.36	44.70	20.34	108.19	H
	18900	1880.0	-24.21	44.70	20.49	111.94	
	19175	1907.5	-24.61	44.57	19.96	99.15	
	18625	1852.5	-26.59	44.27	17.68	58.61	V
	18900	1880.0	-26.91	44.87	17.96	62.52	
	19175	1907.5	-26.37	44.61	18.24	66.73	
Channel Bandwidth: 5 MHz / 64QAM							
Z	18625	1852.5	-25.87	44.70	18.83	76.38	H
	18900	1880.0	-25.50	44.70	19.20	83.18	
	19175	1907.5	-25.92	44.57	18.65	73.33	
	18625	1852.5	-27.21	44.27	17.06	50.82	V
	18900	1880.0	-27.27	44.87	17.60	57.54	
	19175	1907.5	-27.57	44.61	17.04	50.62	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 10 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18650	1855.0	-24.03	44.70	20.67	116.68	H
	18900	1880.0	-23.95	44.70	20.75	118.85	
	19150	1905.0	-23.81	44.57	20.76	119.21	
	18650	1855.0	-25.23	44.27	19.04	80.17	V
	18900	1880.0	-25.25	44.87	19.62	91.62	
	19150	1905.0	-25.51	44.61	19.10	81.34	
Channel Bandwidth: 10 MHz / 16QAM							
Z	18650	1855.0	-24.14	44.70	20.56	113.76	H
	18900	1880.0	-24.57	44.70	20.13	103.04	
	19150	1905.0	-24.87	44.57	19.70	93.39	
	18650	1855.0	-26.38	44.27	17.89	61.52	V
	18900	1880.0	-26.88	44.87	17.99	62.95	
	19150	1905.0	-26.60	44.61	18.01	63.27	
Channel Bandwidth: 10 MHz / 64QAM							
Z	18650	1855.0	-25.31	44.70	19.39	86.90	H
	18900	1880.0	-25.61	44.70	19.09	81.10	
	19150	1905.0	-25.46	44.57	19.11	81.53	
	18650	1855.0	-27.21	44.27	17.06	50.82	V
	18900	1880.0	-27.27	44.87	17.60	57.54	
	19150	1905.0	-27.17	44.61	17.44	55.50	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 15 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18675	1857.5	-24.05	44.70	20.65	116.14	H
	18900	1880.0	-23.91	44.70	20.79	119.95	
	19125	1902.5	-23.77	44.57	20.80	120.31	
	18675	1857.5	-25.61	44.27	18.66	73.45	V
	18900	1880.0	-25.37	44.87	19.50	89.13	
	19125	1902.5	-25.33	44.61	19.28	84.78	
Channel Bandwidth: 15 MHz / 16QAM							
Z	18675	1857.5	-24.81	44.70	19.89	97.50	H
	18900	1880.0	-24.35	44.70	20.35	108.39	
	19125	1902.5	-24.77	44.57	19.80	95.57	
	18675	1857.5	-26.37	44.27	17.90	61.66	V
	18900	1880.0	-26.91	44.87	17.96	62.52	
	19125	1902.5	-26.14	44.61	18.47	70.36	
Channel Bandwidth: 15 MHz / 64QAM							
Z	18675	1857.5	-25.94	44.70	18.76	75.16	H
	18900	1880.0	-25.98	44.70	18.72	74.47	
	19125	1902.5	-25.87	44.57	18.70	74.18	
	18675	1857.5	-27.01	44.27	17.26	53.21	V
	18900	1880.0	-27.25	44.87	17.62	57.81	
	19125	1902.5	-27.07	44.61	17.54	56.79	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

LTE Band 2							
Channel Bandwidth: 20 MHz / QPSK							
Plane	Channel	Frequency (MHz)	Reading (dBm)	Correction Factor (dB)	EIRP (dBm)	EIRP (mW)	Polarization (H/V)
Z	18700	1860.0	-24.01	44.70	20.69	117.22	H
	18900	1880.0	-23.81	44.70	20.89	122.74	
	19100	1900.0	-22.95	44.57	21.62	145.31	
	18700	1860.0	-25.37	44.27	18.90	77.62	V
	18900	1880.0	-25.98	44.87	18.89	77.45	
	19100	1900.0	-25.35	44.61	19.26	84.39	
Channel Bandwidth: 20 MHz / 16QAM							
Z	18700	1860.0	-24.37	44.70	20.33	107.89	H
	18900	1880.0	-24.07	44.70	20.63	115.61	
	19100	1900.0	-24.31	44.57	20.26	106.24	
	18700	1860.0	-26.61	44.27	17.66	58.34	V
	18900	1880.0	-26.50	44.87	18.37	68.71	
	19100	1900.0	-26.97	44.61	17.64	58.12	
Channel Bandwidth: 20 MHz / 64QAM							
Z	18700	1860.0	-25.86	44.70	18.84	76.56	H
	18900	1880.0	-25.08	44.70	19.62	91.62	
	19100	1900.0	-25.21	44.57	19.36	86.36	
	18700	1860.0	-27.37	44.27	16.90	48.98	V
	18900	1880.0	-27.25	44.87	17.62	57.81	
	19100	1900.0	-27.14	44.61	17.47	55.89	

Note: EIRP (dBm) = Reading (dBm) + Correction Factor (dB)

4.2 Radiated Emission Measurement

4.2.1 Limits of Radiated Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit is equal to -13 dBm.

4.2.2 Test Procedure

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) and/or 1.5 m (above 1 GHz) height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G.
- c. EIRP = Output power level of S.G – TX cable loss + Antenna gain of substitution horn.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, E.R.P power = E.I.R.P power - 2.15 dB.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz.

4.2.3 Deviation from Test Standard


No deviation.

4.2.4 Test Setup

<Radiated Emission below or equal 1 GHz>



<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.5 Test Results

WCDMA:

Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13

Date: 2019-04-17



Site : 966 chamber 1

Condition: PART 22/24 Horizontal

Remark : Band II_Link_CH9262

Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	168.78	-53.14	-46.34	-13.00	-40.14	-6.80	Peak
2 pp	223.59	-46.46	-40.60	-13.00	-33.46	-5.86	Peak
3	246.00	-50.91	-45.35	-13.00	-37.91	-5.56	Peak
4	304.20	-60.65	-54.75	-13.00	-47.65	-5.90	Peak
5	419.70	-66.06	-62.87	-13.00	-53.06	-3.19	Peak
6	657.70	-67.04	-66.87	-13.00	-54.04	-0.17	Peak
7	3704.80	-51.48	-67.36	-13.00	-38.48	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2019-04-17



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9262
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	141.78	-55.20	-47.46	-13.00	-42.20	-7.74	Peak
2	170.40	-55.82	-49.22	-13.00	-42.82	-6.60	Peak
3	223.05	-55.86	-49.99	-13.00	-42.86	-5.87	Peak
4	387.50	-60.99	-57.63	-13.00	-47.99	-3.36	Peak
5	714.40	-63.70	-63.05	-13.00	-50.70	-0.65	Peak
6	839.70	-61.94	-63.50	-13.00	-48.94	1.56	Peak
7 pp	3704.80	-50.50	-66.38	-13.00	-37.50	15.88	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : Band II_Link_CH9400
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.92	-68.06	-13.00	-38.92	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-17



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9400
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.41	-67.55	-13.00	-38.41	16.14	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : Band II_Link_CH9538
 Tested by: Karl Lee

Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-50.90	-67.31	-13.00	-37.90	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-17



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : Band II_Link_CH9538
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.20	-52.21	-68.62	-13.00	-39.21	16.41	Peak


LTE Band 2
Channel Bandwidth: 1.4 MHz / QPSK
Low Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3701.40	-52.81	-68.69	-13.00	-39.81	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2019-04-23



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18607
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3701.40	-52.63	-68.51	-13.00	-39.63	15.88	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.98	-68.12	-13.00	-38.98	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2019-04-23



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.08	-67.22	-13.00	-38.08	16.14	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 3



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : LTE_Band 2_Link_CH19193
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3818.60	-51.51	-68.01	-13.00	-38.51	16.50	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 4

Date: 2019-04-23



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19193
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3818.60	-51.24	-67.74	-13.00	-38.24	16.50	Peak

Channel Bandwidth: 5 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18625
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3705.00	-52.22	-68.10	-13.00	-39.22	15.88	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18625
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3705.00	-52.76	-68.64	-13.00	-39.76	15.88	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : LTE_Band 2_Link_CH18900
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-49.34	-65.48	-13.00	-36.34	16.14	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-51.43	-67.57	-13.00	-38.43	16.14	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : LTE_Band 2_Link_CH19175
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.00	-50.00	-66.41	-13.00	-37.00	16.41	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19175
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3815.00	-51.14	-67.55	-13.00	-38.14	16.41	Peak

Channel Bandwidth: 20 MHz / QPSK
Low Channel




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3720.00	-52.18	-68.15	-13.00	-39.18	15.97	Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 10

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18700
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3720.00	-49.72	-65.69	-13.00	-36.72	15.97	Peak


Middle Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 9



Site : 966 chamber 1
 Condition: PART 22/24 Horizontal
 Remark : LTE_Band 2_Link_CH18900
 Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-50.04	-66.18	-13.00	-37.04	16.14	Peak




Bureau Veritas Consumer Products Services Ltd.,Taoyuan Branch

A D T

Data: 10

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH18900
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1 pp 3760.00	-52.04	-68.18	-13.00	-39.04	16.14	Peak


High Channel



Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 13



Site : 966 chamber 1
Condition: PART 22/24 Horizontal
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

		Read	Limit	Over		
Freq	Level	Level	Line	Limit	Factor	Remark
MHz	dBm	dBm	dBm	dB	dB	
1	147.45	-54.62	-46.74	-13.00	-41.62	-7.88 Peak
2	223.59	-45.78	-39.92	-13.00	-32.78	-5.86 Peak
3	232.50	-48.47	-42.73	-13.00	-35.47	-5.74 Peak
4	304.90	-60.11	-54.21	-13.00	-47.11	-5.90 Peak
5	433.70	-58.34	-54.86	-13.00	-45.34	-3.48 Peak
6	667.50	-64.54	-64.32	-13.00	-51.54	-0.22 Peak
7	3800.00	-47.33	-63.74	-13.00	-34.33	16.41 Peak




Bureau Veritas Consumer Products Services Ltd., Taoyuan Branch

A D T

Data: 14

Date: 2019-04-16



Site : 966 chamber 1
Condition: PART 22/24 Vertical
Remark : LTE_Band 2_Link_CH19100
Tested by: Karl Lee

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark
	MHz	dBm	dBm	dBm	dB	dB	
1	142.59	-55.33	-47.57	-13.00	-42.33	-7.76	Peak
2	170.67	-55.95	-49.35	-13.00	-42.95	-6.60	Peak
3	222.24	-55.57	-49.69	-13.00	-42.57	-5.88	Peak
4	387.50	-60.32	-56.96	-13.00	-47.32	-3.36	Peak
5	575.80	-66.53	-65.95	-13.00	-53.53	-0.58	Peak
6	708.80	-61.35	-60.81	-13.00	-48.35	-0.54	Peak
7 pp	3800.00	-51.34	-67.75	-13.00	-38.34	16.41	Peak

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---