

Appendix A. Plots of System Verification

The plots for system verification are shown as follows.

Plots of System Verification

Measurement Report

S01 System Check_H1900_251110

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1900V2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1900.000, 0	7.73	1.45	40.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	1.85	1.90
psSAR10g [W/kg]	0.999	1.00
Power Drift [dB]	-0.00	-0.03



Plots of System Verification

Measurement Report

S02 System Check_H1750_251110

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1750V2,	10.0 x 10.0 x 302.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1750.000, 0	8.0	1.37	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	1.86	1.86
psSAR10g [W/kg]	0.993	1.00
Power Drift [dB]	0.01	0.01



Plots of System Verification

Measurement Report
S03 System Check_H835_251110
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D835V2,	10.0 x 10.0 x 340.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	835.000, 0	9.56	0.943	43.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.491	0.493
psSAR10g [W/kg]	0.323	0.324
Power Drift [dB]	0.01	0.02



Plots of System Verification

Measurement Report

S04 System Check_H1900_251110

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1900V2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1900.000, 0	7.73	1.45	40.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	1.85	1.90
psSAR10g [W/kg]	0.999	1.00
Power Drift [dB]	-0.00	-0.03



Plots of System Verification

Measurement Report

S05 System Check_H1750_251110

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1750V2,	10.0 x 10.0 x 302.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1750.000, 0	8.0	1.37	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	1.86	1.86
psSAR10g [W/kg]	0.993	1.00
Power Drift [dB]	0.01	0.01



Plots of System Verification

Measurement Report S06 System Check_H835_251110

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D835V2,	10.0 x 10.0 x 340.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	835.000, 0	9.56	0.943	43.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.491	0.493
psSAR10g [W/kg]	0.323	0.324
Power Drift [dB]	0.01	0.02



Plots of System Verification

Measurement Report

S07 System Check_H2600_251112

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2600V2,	50.0 x 10.0 x 290.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2600.000, 0	6.99	1.93	39.7

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	48.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	2.82	2.84
psSAR10g [W/kg]	1.23	1.25
Power Drift [dB]	-0.09	-0.11



Plots of System Verification

Measurement Report

S08 System Check_H750_251112

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D750V3,	10.0 x 10.0 x 330.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	750.000, 0	9.72	0.915	43.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.423	0.438
psSAR10g [W/kg]	0.281	0.287
Power Drift [dB]	-0.10	0.05



Plots of System Verification

Measurement Report

S09 System Check_H750_251112

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D750V3,	10.0 x 10.0 x 330.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	750.000, 0	9.72	0.915	43.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.423	0.438
psSAR10g [W/kg]	0.281	0.287
Power Drift [dB]	-0.10	0.05



Plots of System Verification

Measurement Report

S10 System Check_H750_251112

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D750V3,	10.0 x 10.0 x 330.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	750.000, 0	9.72	0.915	43.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.423	0.438
psSAR10g [W/kg]	0.281	0.287
Power Drift [dB]	-0.10	0.05



Plots of System Verification

Measurement Report

S11 System Check_H1900_251112

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1900V2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1900.000, 0	7.73	1.45	40.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	1.88	1.92
psSAR10g [W/kg]	0.979	1.01
Power Drift [dB]	-0.19	0.18



Plots of System Verification

Measurement Report S12 System Check_H835_251112 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D835V2,	10.0 x 10.0 x 340.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	835.000, 0	9.56	0.942	43.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.435	0.446
psSAR10g [W/kg]	0.273	0.282
Power Drift [dB]	-0.14	-0.15



Plots of System Verification

Measurement Report

S14 System Check_H2600_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2600V2,	10.0 x 10.0 x 290.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2600.000, 0	6.99	1.93	39.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	48.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	2.97	3.06
psSAR10g [W/kg]	1.34	1.41
Power Drift [dB]	-0.01	-0.02



Plots of System Verification

Measurement Report

S17a System Check_H3500_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D3500V2,	10.0 x 10.0 x 285.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	3500.000, 0	6.58	2.79	38.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H33T42N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	44.0 x 88.0	30.0 x 30.0 x 28.0
Grid Steps [mm]	11.0 x 11.0	5.0 x 5.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	3.30	3.54
psSAR10g [W/kg]	1.35	1.36
Power Drift [dB]	0.01	0.01



Plots of System Verification

Measurement Report

S17b System Check_H3700_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D3700V2,	10.0 x 10.0 x 285.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	3700.000, 0	6.51	2.97	38.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H33T42N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	44.0 x 88.0	30.0 x 30.0 x 28.0
Grid Steps [mm]	11.0 x 11.0	5.0 x 5.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	3.25	3.39
psSAR10g [W/kg]	1.21	1.29
Power Drift [dB]	0.12	-0.01



Plots of System Verification

Measurement Report

S18 System Check_H1750_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D1750V2,	10.0 x 10.0 x 302.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	1750.000, 0	8.0	1.38	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	1.88	1.86
psSAR10g [W/kg]	1.00	0.997
Power Drift [dB]	-0.01	-0.01



Plots of System Verification

Measurement Report S19 System Check_H750_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D750V3,	10.0 x 10.0 x 330.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	750.000, 0	9.72	0.903	43.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.440	0.444
psSAR10g [W/kg]	0.295	0.298
Power Drift [dB]	0.02	-0.02



Plots of System Verification

Measurement Report S20 System Check_H835_251113

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D835V2,	10.0 x 10.0 x 340.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	835.000, 0	9.56	0.944	43.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	36.0 x 36.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	6.0 x 6.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.467	0.475
psSAR10g [W/kg]	0.291	0.302
Power Drift [dB]	0.18	-0.02



Plots of System Verification

Measurement Report

S100 System Check H2450_251117

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2450V2,	10.0 x 10.0 x 290.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2450.000, 0	7.14	1.81	39.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	48.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	2.75	2.82
psSAR10g [W/kg]	1.32	1.33
Power Drift [dB]	-0.02	-0.14



Plots of System Verification

Measurement Report S101 System Check H5250_251117 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5250.000, 0	5.46	4.64	37.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	4.06	4.09
psSAR10g [W/kg]	1.14	1.18
Power Drift [dB]	0.12	0.06



Plots of System Verification

Measurement Report S102 System Check H5600_251117 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5600.000, 0	5.1	5.03	36.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	3.92	4.00
psSAR10g [W/kg]	1.13	1.14
Power Drift [dB]	0.10	-0.16



Plots of System Verification

Measurement Report S103 System Check H5800_251117 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5800.000, 0	4.93	5.27	36.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	3.59	3.69
psSAR10g [W/kg]	1.04	1.04
Power Drift [dB]	0.07	0.09



Plots of System Verification

Measurement Report S104 System Check H5800_251117 Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D5GHzV2,	10.0 x 10.0 x 300.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	5800.000, 0	4.93	5.27	36.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	40.0 x 80.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	3.59	3.69
psSAR10g [W/kg]	1.04	1.04
Power Drift [dB]	0.07	0.09



Plots of System Verification

Measurement Report

S105 System Check H2450_251118

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D2450V2,	10.0 x 10.0 x 290.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	2450.000, 0	7.14	1.82	39.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-18	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	48.0 x 96.0	35.0 x 35.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 1.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-18	2025-11-18
psSAR1g [W/kg]	2.71	2.80
psSAR10g [W/kg]	1.28	1.32
Power Drift [dB]	0.15	0.05



Plots of System Verification

Measurement Report

S106 System Check H6500_251117

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
D6.5GHzV2,	10.0 x 10.0 x 296.0		

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	,		CW, 0--	6500.000, 0	5.25	5.95	34.8

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H60T72N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	45.0 x 90.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	7.5 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	26.3	27.9
psSAR10g [W/kg]	5.04	5.20
psAPD (1.0cm2, sq) [W/m2]		294
psAPD (4.0cm2, sq) [W/m2]		125
Power Drift [dB]	0.05	0.14



Plots of System Verification

Measurement Report

S106 PD_System Check_10 GHz_251118

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
SPEAG, 5G Verification Source 10 GHz	100.0 x 100.0 x 170.0	SN: 1025	

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G Air	FRONT, 10.00	Validation band	CW, 0--	10000.0, 10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave- 1035	---Air	EUmmWV4 - SN9615_F1-55GHz, 2025-05-14	DAE4 Sn1585, 2025-05-19

Scan Setup

	5G Scan
Grid Extents [mm]	60.0 x 60.0
Grid Steps [lambda]	0.125 x 0.125
Sensor Surface [mm]	10.0

Measurement Results

	5G Scan
Date	2025-11-18
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	53.7
psPDtot+ [W/m ²]	53.9
psPDmod+ [W/m ²]	54.1
E _{max} [V/m]	149
Power Drift [dB]	-0.04



Appendix B. Plots of Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination are shown as follows.

Plots of Measurement

Measurement Report
P01 WCDMA II_RMC12.2K_Top Side_0mm_Ch9262_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 2	WCDMA, 10011-CAC	1852.400, 9262	7.73	1.42	40.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.646	0.707
psSAR10g [W/kg]	0.326	0.358
Power Drift [dB]	-0.05	-0.02
M2/M1 [%]		58.9
Dist 3dB Peak [mm]		9.4



Plots of Measurement

Measurement Report
P02 WCDMA IV_RMC12.2K_Top Side_0mm_Ch1513_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 4	WCDMA, 10011-CAC	1752.600, 1513	8.0	1.37	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.658	0.720
psSAR10g [W/kg]	0.338	0.373
Power Drift [dB]	0.01	-0.02
M2/M1 [%]		61.0
Dist 3dB Peak [mm]		9.4



Plots of Measurement

Measurement Report
P03 WCDMA V_RMC12.2K_Top Side_0mm_Ch4182_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 5	WCDMA, 10011-CAC	836.400, 4182	9.56	0.948	43.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.630	0.673
psSAR10g [W/kg]	0.380	0.365
Power Drift [dB]	-0.01	0.02
M2/M1 [%]		52.4
Dist 3dB Peak [mm]		8.1



Plots of Measurement

Measurement Report

P04 LTE 2_QPSK20M_Top Side_0mm_Ch18700_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 2	LTE-FDD, 10169-CAF	1860.000, 18700	7.73	1.43	40.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.619	0.669
psSAR10g [W/kg]	0.312	0.340
Power Drift [dB]	-0.05	-0.02
M2/M1 [%]		59.3
Dist 3dB Peak [mm]		9.8



Plots of Measurement

Measurement Report
P05 LTE 4_QPSK20M_Top Side_0mm_Ch20300_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 4	LTE-FDD, 10169-CAF	1745.000, 20300	8.0	1.37	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.644	0.708
psSAR10g [W/kg]	0.331	0.368
Power Drift [dB]	-0.02	0.01
M2/M1 [%]		61.2
Dist 3dB Peak [mm]		9.4



Plots of Measurement

Measurement Report

P06 LTE 5_QPSK10M_Top Side_0mm_Ch20450_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 5	LTE-FDD, 10175-CAH	829.000, 20450	9.56	0.945	43.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-10	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-10	2025-11-10
psSAR1g [W/kg]	0.658	0.698
psSAR10g [W/kg]	0.398	0.381
Power Drift [dB]	-0.03	0.01
M2/M1 [%]		52.9
Dist 3dB Peak [mm]		8.1



Plots of Measurement

Measurement Report

P07 LTE 7_QPSK20M_Top Side_0mm_Ch20850_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 7	LTE-FDD, 10169-CAF	2510.000, 20850	6.99	1.87	39.8

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	72.0 x 396.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.616	0.746
psSAR10g [W/kg]	0.288	0.314
Power Drift [dB]	-0.06	-0.05
M2/M1 [%]		52.2
Dist 3dB Peak [mm]		7.1



Plots of Measurement

Measurement Report

P08 LTE 12_QPSK10M_Top Side_0mm_Ch23130_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 12	LTE-FDD, 10175-CAH	711.000, 23130	9.72	0.900	43.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.601	0.724
psSAR10g [W/kg]	0.392	0.392
Power Drift [dB]	0.00	0.01
M2/M1 [%]		41.5
Dist 3dB Peak [mm]		8.1



Plots of Measurement

Measurement Report

P09 LTE 13_QPSK10M_Top Side_0mm_Ch23230_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 13	LTE-FDD, 10175-CAH	782.000, 23230	9.72	0.926	43.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.562	0.715
psSAR10g [W/kg]	0.359	0.378
Power Drift [dB]	-0.03	-0.01
M2/M1 [%]		43.4
Dist 3dB Peak [mm]		8.7



Plots of Measurement

Measurement Report

P10 LTE 14_QPSK10M_Top Side_0mm_Ch23330_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 14	LTE-FDD, 10175-CAH	793.000, 23330	9.72	0.931	43.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.604	0.770
psSAR10g [W/kg]	0.386	0.410
Power Drift [dB]	-0.05	0.01
M2/M1 [%]		43.8
Dist 3dB Peak [mm]		8.7



Plots of Measurement

Measurement Report

P11 LTE 25_QPSK20M_Top Side_0mm_Ch26140_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 25	LTE-FDD, 10169-CAF	1860.000, 26140	7.73	1.43	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.699	0.727
psSAR10g [W/kg]	0.342	0.377
Power Drift [dB]	-0.02	-0.01
M2/M1 [%]		60.1
Dist 3dB Peak [mm]		9.4



Plots of Measurement

Measurement Report
P12 LTE 26_QPSK15M_Top Side_0mm_Ch26965_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 26	LTE-FDD, 10181-CAF	841.500, 26965	9.56	0.951	43.1

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-12	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-12	2025-11-12
psSAR1g [W/kg]	0.529	0.641
psSAR10g [W/kg]	0.341	0.359
Power Drift [dB]	-0.01	-0.02
M2/M1 [%]		45.1
Dist 3dB Peak [mm]		9.4



Plots of Measurement

Measurement Report
P14 LTE 41_QPSK20M_Top Side_0mm_Ch39750_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 41	LTE-TDD, 10172-CAH	2506.000, 39750	6.99	1.86	39.9

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	72.0 x 384.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.621	0.761
psSAR10g [W/kg]	0.289	0.320
Power Drift [dB]	-0.03	0.02
M2/M1 [%]		52.0
Dist 3dB Peak [mm]		7.1



Plots of Measurement

Measurement Report
P17 LTE 48_QPSK20M_Top Side_0mm_Ch55340_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 48	LTE-TDD, 10172-CAH	3560.000, 55340	6.58	2.84	38.4

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H33T42N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	72.0 x 384.0	30.0 x 30.0 x 28.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 2.5
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.679	0.727
psSAR10g [W/kg]	0.271	0.280
Power Drift [dB]	-0.01	-0.03
M2/M1 [%]		59.2
Dist 3dB Peak [mm]		7.1



Plots of Measurement

Measurement Report

P18 LTE 66_QPSK20M_Top Side_0mm_Ch132572_1RB_OS0_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 66	LTE-FDD, 10169-CAF	1770.000, 132572	8.0	1.39	40.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H14T19N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.737	0.766
psSAR10g [W/kg]	0.367	0.405
Power Drift [dB]	-0.02	-0.01
M2/M1 [%]		62.3
Dist 3dB Peak [mm]		10.2



Plots of Measurement

Measurement Report
P19 LTE 71_QPSK20M_Top Side_0mm_Ch133222_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 71	LTE-FDD, 10169-CAF	673.000, 133222	9.72	0.873	43.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.604	0.761
psSAR10g [W/kg]	0.395	0.398
Power Drift [dB]	-0.03	-0.02
M2/M1 [%]		45.3
Dist 3dB Peak [mm]		9.6



Plots of Measurement

Measurement Report
P20 LTE 106_QPSK3M_Top Side_0mm_Ch134322_1RB_OS0_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Top Side, 0.00	Band 106	LTE-FDD, 10184-CAF	899.000, 134322	9.56	0.976	42.9

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H06T09N5 , 2025-Nov-13	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 390.0	32.0 x 32.0 x 30.0
Grid Steps [mm]	15.0 x 15.0	8.0 x 8.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-13	2025-11-13
psSAR1g [W/kg]	0.788	0.782
psSAR10g [W/kg]	0.469	0.429
Power Drift [dB]	-0.00	-0.02
M2/M1 [%]		50.5
Dist 3dB Peak [mm]		8.1



Plots of Measurement

Measurement Report

P100 WLAN 2.4G_802.11b_Left Side_0mm_Ch13_Ant1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	WLAN 2.4GHz	WLAN, 10012-CAB	2472.000, 13	7.14	1.83	39.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.344	0.346
psSAR10g [W/kg]	0.173	0.237
Power Drift [dB]	-0.04	0.02
M2/M1 [%]		53.2
Dist 3dB Peak [mm]		7.7



Plots of Measurement

Measurement Report

P101 WLAN 5.3G_802.11ac VHT160_Left Side_0mm_Ch50_Ant0+1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	WLAN 5GHz	WLAN, 10554-AAE	5250.000, 50	5.46	4.64	37.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.107	0.305
psSAR10g [W/kg]	0.041	0.066
Power Drift [dB]	-0.38	-0.13
M2/M1 [%]		63.7
Dist 3dB Peak [mm]		4.7



Plots of Measurement

Measurement Report

P102 WLAN 5.6G_802.11ac VHT160_Left Side_0mm_Ch114_Ant1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	WLAN 5GHz	WLAN, 10554-AAE	5570.000, 114	5.1	5.00	36.7

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.174	0.250
psSAR10g [W/kg]	0.064	0.068
Power Drift [dB]	-0.48	0.17
M2/M1 [%]		57.2
Dist 3dB Peak [mm]		4.8



Plots of Measurement

Measurement Report

P103 WLAN 5.8G_802.11ac VHT80_Left Side_0mm_Ch155_Ant0+1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	WLAN 5GHz	WLAN, 10544-AAD	5775.000, 155	4.93	5.24	36.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.055	0.303
psSAR10g [W/kg]	0.018	0.058
Power Drift [dB]	-1.43	-0.11
M2/M1 [%]		58.3
Dist 3dB Peak [mm]		4.1



Plots of Measurement

Measurement Report

P104 WLAN 5.9G_802.11ac VHT160_Left Side_0mm_Ch163_Ant1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	WLAN 5GHz	WLAN, 10554-AAE	5815.000, 163	4.93	5.30	36.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H50T60N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	24.0 x 24.0 x 22.0
Grid Steps [mm]	10.0 x 10.0	4.0 x 4.0 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.070	0.349
psSAR10g [W/kg]	0.023	0.082
Power Drift [dB]	0.47	-0.01
M2/M1 [%]		58.0
Dist 3dB Peak [mm]		4.1



Plots of Measurement

Measurement Report
P105 BT_BR_Left Side_0mm_Ch0_Ant1_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	ISM 2.4 GHz Band	Bluetooth, 10032-CAA	2402.000, 0	7.14	1.77	39.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H19T27N5 , 2025-Nov-18	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	60.0 x 300.0	30.0 x 30.0 x 30.0
Grid Steps [mm]	12.0 x 12.0	5.0 x 5.0 x 5.0
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-18	2025-11-18
psSAR1g [W/kg]	0.217	0.250
psSAR10g [W/kg]	0.101	0.128
Power Drift [dB]	0.01	-0.06
M2/M1 [%]		54.1
Dist 3dB Peak [mm]		7.3



Plots of Measurement

Measurement Report

P106 WLAN UNII-5_802.11ax HE160_Left Side_0mm_Ch47_Ant0+1_Battery 1

Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	240.0 x 338.0 x 30.0		Tablet

Exposure Conditions

Phantom Section, TSL	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat,	Left Side, 0.00	U-NII-5	WLAN, 10755-AAC	6185.000, 47	5.25	5.58	35.3

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
ELI V8.0 (20deg probe tilt) - 2118	H60T72N5 , 2025-Nov-17	EX3DV4 - SN7696, 2025-09-11	DAE4 Sn1590, 2025-08-13

Scan Setup

	Area Scan	Zoom Scan
Grid Extents [mm]	90.0 x 300.0	22.0 x 22.0 x 22.0
Grid Steps [mm]	7.5 x 7.5	3.4 x 3.4 x 1.4
Sensor Surface [mm]	3.0	1.4

Measurement Results

	Area Scan	Zoom Scan
Date	2025-11-17	2025-11-17
psSAR1g [W/kg]	0.094	0.206
psSAR10g [W/kg]	0.034	0.044
psAPD (1.0cm2, sq) [W/m2]		2.06
psAPD (4.0cm2, sq) [W/m2]		1.01
Power Drift [dB]	0.05	-0.07
M2/M1 [%]		54.6
Dist 3dB Peak [mm]		4.1



Plots of Measurement

Measurement Report
P106 UNII-5_802.11ax HE160_Left Side_0mm_Ch47_Ant 0+1_Battery 1
Device under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
CDVB-WTW-P25100255,	338.0 x 240.0 x 30.0		Tablet

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G Air	Left Side, 2.00	U-NII-5	WLAN, 10755-AAC	6185.0, 47	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave- 1035	---Air	EUmmWV4 - SN9615_F1-55GHz, 2025-05-14	DAE4 Sn1585, 2025-05-19

Scan Setup

	5G Scan
Grid Extents [mm]	97.0 x 97.0
Grid Steps [lambda]	0.0515 x 0.0515
Sensor Surface [mm]	2.0

Measurement Results

	5G Scan
Date	2025-11-18
Avg. Area [cm ²]	4.00
psPDn+ [W/m ²]	0.971
psPDtot+ [W/m ²]	1.72
psPDmod+ [W/m ²]	2.03
E _{max} [V/m]	33.7
Power Drift [dB]	-0.04



Appendix C. Tissue & System Verification

The measuring results for tissue simulating liquid and system check are shown as below.

Note:

1. For Section 4.3, the dielectric properties of the tissue simulating liquid have been measured within 24 hours before the SAR testing and within ± 10 % of the target values. Liquid temperature during the SAR testing has kept within ± 2 °C.
2. For Section 4.4, The SAR measurement system was validated according to procedures in FCC KDB 865664 D0. The validation status in tabulated summary is as below.
3. For Section 4.5, Comparing to the reference SAR value provided by SPEAG in dipole calibration certificate, the deviation of system check results is within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots please refer to Appendix A of this report.

Tissue Verification									Validation for CW			Validation for Modulation			System Check										System Validation				Note				
Plot No.	Frequency (MHz)	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (εr)	Targeted Conductivity (σ)	Targeted Permittivity (εr)	Deviation Conductivity (σ)	Deviation Permittivity (εr)	Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR	Date	Frequency (MHz)	Targeted 1g SAR (W/kg)	Measured 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)	Targeted APD 4 cm² (W/kg)	Measured APD 4 cm² (W/kg)	Normalized APD 4 cm² (W/kg)	Deviation (%)	Targeted APD 4 cm² (W/kg)	Measured APD 4 cm² (W/kg)	Normalized APD 4 cm² (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N	Output Power (dBm)	
S01	1900	21.5	1.45	40	1.4	40	3.57	0.00	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	1900	39.60	1.9	37.91	-4.27	-	-	-	-	-	-	-	-	5d036	7696	1590	17	
S02	1750	21.5	1.37	40.2	1.37	40.1	0.00	0.25	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	1750	36.40	1.86	37.11	1.96	-	-	-	-	-	-	-	-	-	1055	7696	1590	17
S03	835	21.3	0.943	43	0.9	41.5	4.78	3.61	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	835	9.51	0.493	9.84	3.43	-	-	-	-	-	-	-	-	-	4d121	7696	1590	17
S04	1900	21.5	1.45	40	1.4	40	3.57	0.00	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	1900	39.60	1.9	37.91	-4.27	-	-	-	-	-	-	-	-	-	5d036	7696	1590	17
S05	1750	21.5	1.37	40.2	1.37	40.1	0.00	0.25	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	1750	36.40	1.86	37.11	1.96	-	-	-	-	-	-	-	-	-	1055	7696	1590	17
S06	835	21.3	0.943	43	0.9	41.5	4.78	3.61	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 10, 2025	835	9.51	0.493	9.84	3.43	-	-	-	-	-	-	-	-	-	4d121	7696	1590	17
S07	2600	22.4	1.93	39.7	1.96	39	-1.53	1.79	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	2600	56.50	2.84	56.67	0.29	-	-	-	-	-	-	-	-	-	1020	7696	1590	17
S08	750	22.4	0.915	43.4	0.89	41.9	2.81	3.58	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	750	8.72	0.438	8.74	0.22	-	-	-	-	-	-	-	-	-	1013	7696	1590	17
S09	750	22.4	0.915	43.4	0.89	41.9	2.81	3.58	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	750	8.72	0.438	8.74	0.22	-	-	-	-	-	-	-	-	-	1013	7696	1590	17
S10	750	22.4	0.915	43.4	0.89	41.9	2.81	3.58	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	750	8.72	0.438	8.74	0.22	-	-	-	-	-	-	-	-	-	1013	7696	1590	17
S11	1900	22.4	1.45	40.1	1.4	40	3.57	0.25	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	1900	39.60	1.92	38.31	-3.26	-	-	-	-	-	-	-	-	-	5d036	7696	1590	17
S12	835	22.4	0.942	43.1	0.9	41.5	4.67	3.86	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 12, 2025	835	9.51	0.446	8.90	-6.43	-	-	-	-	-	-	-	-	-	4d121	7696	1590	17
S14	2600	21.3	1.93	39.6	1.96	39	-1.53	1.54	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	2600	56.50	3.06	61.06	8.06	-	-	-	-	-	-	-	-	-	1020	7696	1590	17
S17a	3500	21.3	2.79	38.5	2.91	37.9	-4.12	1.58	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	3500	66.00	3.54	70.63	7.02	-	-	-	-	-	-	-	-	-	1007	7696	1590	17
S17b	3700	21.3	2.97	38.2	3.12	37.7	-4.81	1.33	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	3700	68.00	3.39	67.64	-0.53	-	-	-	-	-	-	-	-	-	1017	7696	1590	17
S18	1750	21.2	1.38	40.2	1.37	40.1	0.73	0.25	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	1750	36.40	1.86	37.11	1.96	-	-	-	-	-	-	-	-	-	1055	7696	1590	17
S19	750	21.2	0.903	43.5	0.89	41.9	1.46	3.82	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	750	8.72	0.444	8.86	1.59	-	-	-	-	-	-	-	-	-	1013	7696	1590	17
S20	835	21.2	0.944	43.1	0.9	41.5	4.89	3.86	Pass	Pass	Pass	N/A	N/A	N/A	Nov. 13, 2025	835	9.51	0.475	9.48	-0.34	-	-	-	-	-	-	-	-	-	4d121	7696	1590	17
S100	2450	22.2	1.81	39.5	1.8	39.2	0.56	0.77	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	2450	52.90	2.82	56.27	6.36	-	-	-	-	-	-	-	-	-	737	7696	1590	17
S101	5250	22.2	4.64	37.2	4.71	35.9	-1.49	3.62	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	5250	78.30	4.09	81.61	4.22	-	-	-	-	-	-	-	-	-	1019	7696	1590	17
S102	5600	22.2	5.03	36.6	5.07	35.5	-0.79	3.10	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	5600	80.80	4	79.81	-1.22	-	-	-	-	-	-	-	-	-	1019	7696	1590	17
S103	5800	22.2	5.27	36.3	5.27	35.3	0.00	2.83	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	5800	78.80	3.69	73.63	-6.57	-	-	-	-	-	-	-	-	-	1019	7696	1590	17
S104	5800	22.2	5.27	36.3	5.27	35.3	0.00	2.83	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	5800	78.80	3.69	73.63	-6.57	-	-	-	-	-	-	-	-	-	1019	7696	1590	17
S105	2450	22.2	1.82	39.5	1.8	39.2	1.11	0.77	Pass	Pass	Pass	GFSK	N/A	Pass	Nov. 18, 2025	2450	52.90	2.8	55.87	5.61	-	-	-	-	-	-	-	-	-	737	7696	1590	17
S106	6500	22.2	5.95	34.8	6.07	34.5	-1.98	0.87	Pass	Pass	Pass	OFDM	N/A	Pass	Nov. 17, 2025	6500	296.00	27.9	279.00	-5.74	1320.00	125	1250.00	-5.30	1290.00	125	1250.00	-3.10	1008	7696	1590	20	

System Performance Check for Incident Power Density Measurement									
Plot No.	Test Date	Frequency [GHz]	mmWave Probe S/N	Verification Source S/N	Averaging Area [cm ²]	Distance [mm]	Target Power Density [W/m ²]	Measured Power Density [W/m ²]	Deviation [%]
S106	Nov. 18, 2025	10	9615	1025	4	10.0	55.9	53.9	-3.58%

Appendix D. Maximum Target Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

WCDMA Max. Tune-up Power (Full)		
Mode	RMC 12.2K	HSDPA DC-HSDPA HSUPA
	Maximum Target Power	Maximum Target Power
WCDMA Band II	24.0	23.0
WCDMA Band IV	24.0	23.0
WCDMA Band V	24.0	23.0

LTE Max. Tune-up Power (Full)			
Mode	QPSK	16QAM	64QAM
	Maximum Target Power	Maximum Target Power	Maximum Target Power
LTE 2	24.0	23.0	22.0
LTE 4	24.0	23.0	22.0
LTE 5	24.0	23.0	22.0
LTE 7	24.0	23.0	22.0
LTE 12	24.0	23.0	22.0
LTE 13	24.0	23.0	22.0
LTE 14	24.0	23.0	22.0
LTE 25	24.0	23.0	22.0
LTE 26	24.0	23.0	22.0
LTE 41	24.0	23.0	22.0
LTE 48	23.0	22.0	21.0
LTE 66	24.0	23.0	22.0
LTE 71	24.0	23.0	22.0
LTE 106	24.0	23.0	22.0

WCDMA Max. Tune-up Power (Reduction)		
Mode	RMC 12.2K	HSDPA DC-HSDPA HSUPA
	Maximum Target Power	Maximum Target Power
WCDMA Band II	17.5	16.5
WCDMA Band IV	17.5	16.5
WCDMA Band V	19.0	18.0

LTE Max. Tune-up Power (Reduction)			
Mode	QPSK	16QAM	64QAM
	Maximum Target Power	Maximum Target Power	Maximum Target Power
LTE 2	17.5	17.5	17.5
LTE 4	17.5	17.5	17.5
LTE 5	19.5	19.5	19.5
LTE 7	17.0	17.0	17.0
LTE 12	23.0	23.0	23.0
LTE 13	21.0	21.0	21.0
LTE 14	21.0	21.0	21.0
LTE 25	17.5	17.5	17.5
LTE 26	19.0	19.0	19.0
LTE 41	19.0	19.0	19.0
LTE 48	17.0	17.0	17.0
LTE 66	17.5	17.5	17.5
LTE 71	23.0	23.0	23.0
LTE 106	18.5	18.5	18.5

Appendix E. Measured Conducted Power Result

The measuring conducted power (Unit: dBm) are shown as below.

WCDMA Conducted Power (Full)

Band	WCDMA II			WCDMA IV			WCDMA V		
TX Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233
Rx Channel	9662	9800	9938	1537	1638	1738	4357	4407	4458
Frequency	1852.4	1880	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6
RMC 12.2K	23.18	23.08	23.11	23.58	23.51	23.46	23.17	23.23	23.19
HSDPA Subtest-1	22.43	22.35	22.31	22.56	22.52	22.47	22.62	22.71	22.65
HSDPA Subtest-2	22.41	22.33	22.28	22.53	22.51	22.41	22.61	22.68	22.63
HSDPA Subtest-3	21.92	21.81	21.79	22.08	22.06	21.85	22.13	22.18	22.15
HSDPA Subtest-4	21.97	21.89	21.83	22.05	22.01	21.83	22.09	22.16	22.13
DC-HSDPA Subtest-1	22.21	22.16	22.17	22.37	22.31	22.35	22.47	22.52	22.45
DC-HSDPA Subtest-2	22.22	22.21	22.13	22.38	22.31	22.23	22.47	22.51	22.48
DC-HSDPA Subtest-3	21.71	21.62	21.67	21.89	21.92	21.69	21.91	21.99	21.98
DC-HSDPA Subtest-4	21.81	21.68	21.65	21.90	21.86	21.61	21.92	22.04	21.98
HSUPA Subtest-1	22.36	22.23	22.15	22.53	22.46	22.38	22.56	22.65	22.63
HSUPA Subtest-2	20.27	20.35	20.28	20.49	20.37	20.35	20.55	20.63	20.62
HSUPA Subtest-3	21.35	21.41	21.22	21.51	21.28	21.27	21.53	21.62	21.57
HSUPA Subtest-4	20.32	20.37	20.25	20.48	20.43	20.25	20.63	20.69	20.65
HSUPA Subtest-5	22.25	22.32	22.21	22.47	22.41	22.35	22.51	22.62	22.61

LTE Conducted Power (Full)							
LTE Band 2							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100	
		Frequency (MHz)		1860	1880	1900	
20M	QPSK	1	0	22.32	22.34	22.20	0
		1	50	22.18	22.16	22.06	0
		1	99	22.14	22.21	22.05	0
		50	0	21.28	21.30	21.19	1
		50	25	21.26	21.23	21.13	1
		50	50	21.14	21.21	21.07	1
		100	0	21.22	21.25	21.09	1
20M	16QAM	1	0	21.30	21.55	21.08	1
		1	50	21.21	21.28	21.11	1
		1	99	21.22	21.16	21.08	1
		50	0	20.13	20.41	20.01	2
		50	25	20.29	20.30	20.15	2
		50	50	20.15	20.29	20.12	2
		100	0	20.25	20.39	20.01	2
20M	64QAM	1	0	20.16	21.39	20.08	2
		1	50	20.28	20.21	20.02	2
		1	99	20.14	20.20	20.15	2
		50	0	19.27	20.40	19.16	3
		50	25	19.18	19.32	19.09	3
		50	50	19.15	19.28	19.14	3
		100	0	19.23	20.38	19.03	3
BW	MCS Index	Channel		18675	18900	19125	3GPP MPR
		Frequency (MHz)		1857.5	1880	1902.5	
15M	QPSK	1	0	22.22	22.27	22.14	0
		1	37	22.17	22.17	22.02	0
		1	74	22.19	22.17	22.01	0
		36	0	21.26	21.29	21.16	1
		36	19	21.21	21.22	21.08	1
		36	39	21.14	21.16	21.01	1
		75	0	21.18	21.20	21.07	1
15M	16QAM	1	0	21.20	21.26	21.14	1
		1	37	21.23	21.17	21.02	1
		1	74	21.22	21.22	21.01	1
		36	0	20.18	20.20	20.16	2
		36	19	20.10	20.27	20.01	2
		36	39	20.26	20.27	20.08	2
		75	0	20.16	20.28	20.12	2
15M	64QAM	1	0	20.10	20.21	20.02	2
		1	37	20.11	20.24	20.13	2
		1	74	20.11	20.23	20.07	2
		36	0	19.26	19.29	19.02	3
		36	19	19.14	19.11	19.05	3
		36	39	19.21	19.12	19.15	3
		75	0	19.15	19.18	19.07	3

LTE Conducted Power (Full)							
LTE Band 2							
BW	MCS Index	Channel		18650	18900	19150	3GPP MPR
		Frequency (MHz)		1855	1880	1905	
10M	QPSK	1	0	22.22	22.24	22.12	0
		1	24	22.17	22.14	22.11	0
		1	49	22.11	22.15	22.06	0
		25	0	21.25	21.28	21.15	1
		25	12	21.19	21.18	21.11	1
		25	25	21.10	21.16	21.05	1
		50	0	21.21	21.22	21.06	1
10M	16QAM	1	0	21.14	21.28	21.07	1
		1	24	21.15	21.20	21.06	1
		1	49	21.25	21.25	21.06	1
		25	0	20.17	20.18	20.07	2
		25	12	20.12	20.18	20.01	2
		25	25	20.18	20.28	20.12	2
		50	0	20.18	20.11	20.15	2
10M	64QAM	1	0	20.12	20.23	20.05	2
		1	24	20.23	20.16	20.02	2
		1	49	20.18	20.13	20.06	2
		25	0	19.24	19.19	19.09	3
		25	12	19.22	19.19	19.14	3
		25	25	19.21	19.26	19.10	3
		50	0	19.20	19.22	19.09	3
BW	MCS Index	Channel		18625	18900	19175	3GPP MPR
		Frequency (MHz)		1852.5	1880	1907.5	
5M	QPSK	1	0	22.26	22.24	22.12	0
		1	12	22.08	22.13	22.04	0
		1	24	22.12	22.17	22.06	0
		12	0	21.24	21.29	21.14	1
		12	6	21.18	21.22	21.11	1
		12	13	21.13	21.16	21.01	1
		25	0	21.18	21.18	21.07	1
5M	16QAM	1	0	21.11	21.15	21.10	1
		1	12	21.21	21.24	21.11	1
		1	24	21.25	21.14	21.04	1
		12	0	20.10	20.26	20.01	2
		12	6	20.14	20.27	20.01	2
		12	13	20.11	20.11	20.03	2
		25	0	20.18	20.27	20.14	2
5M	64QAM	1	0	20.22	20.22	20.14	2
		1	12	20.13	20.24	20.09	2
		1	24	20.24	20.26	20.04	2
		12	0	19.10	19.14	19.03	3
		12	6	19.27	19.21	19.02	3
		12	13	19.23	19.23	19.01	3
		25	0	19.12	19.20	19.04	3

LTE Conducted Power (Full)							
LTE Band 2							
BW	MCS Index	Channel		18615	18900	19185	3GPP MPR
		Frequency (MHz)		1851.5	1880	1908.5	
3M	QPSK	1	0	22.25	22.26	22.14	0
		1	7	22.14	22.18	22.04	0
		1	14	22.13	22.14	22.08	0
		8	0	21.25	21.28	21.15	1
		8	3	21.18	21.18	21.11	1
		8	7	21.14	21.17	21.09	1
		15	0	21.18	21.24	21.09	1
3M	16QAM	1	0	21.25	21.12	21.02	1
		1	7	21.15	21.11	21.05	1
		1	14	21.21	21.26	21.16	1
		8	0	20.14	20.28	20.07	2
		8	3	20.24	20.27	20.04	2
		8	7	20.26	20.12	20.11	2
		15	0	20.09	20.11	20.05	2
3M	64QAM	1	0	20.13	20.24	20.16	2
		1	7	20.21	20.21	20.09	2
		1	14	20.19	20.24	20.16	2
		8	0	19.12	19.13	19.16	3
		8	3	19.13	19.28	19.14	3
		8	7	19.24	19.19	19.12	3
		15	0	19.13	19.29	19.02	3
BW	MCS Index	Channel		18607	18900	19193	3GPP MPR
		Frequency (MHz)		1850.7	1880	1909.3	
1.4M	QPSK	1	0	22.24	22.25	22.12	0
		1	2	22.09	22.19	22.01	0
		1	5	22.13	22.12	22.06	0
		3	0	22.15	22.19	22.07	0
		3	1	22.10	22.11	22.06	0
		3	3	22.10	22.14	22.03	0
		6	0	21.13	21.19	21.05	1
1.4M	16QAM	1	0	21.11	21.19	21.08	1
		1	2	21.15	21.17	21.04	1
		1	5	21.09	21.19	21.04	1
		3	0	21.10	21.13	21.05	1
		3	1	21.12	21.14	21.03	1
		3	3	21.17	21.17	21.05	1
		6	0	20.16	20.16	20.04	2
1.4M	64QAM	1	0	20.14	20.18	20.05	2
		1	2	20.13	20.15	20.02	2
		1	5	20.14	20.12	20.03	2
		3	0	20.16	20.18	20.03	2
		3	1	20.16	20.12	20.01	2
		3	3	20.09	20.11	20.07	2
		6	0	19.11	19.12	19.02	3

LTE Conducted Power (Full)							
LTE Band 4							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20050	20175	20300	
		Frequency (MHz)		1720	1732.5	1745	
20M	QPSK	1	0	22.58	22.65	22.63	0
		1	50	22.45	22.56	22.47	0
		1	99	22.47	22.49	22.49	0
		50	0	21.56	21.73	21.59	1
		50	25	21.50	21.54	21.53	1
		50	50	21.44	21.48	21.48	1
		100	0	21.47	21.69	21.51	1
20M	16QAM	1	0	21.39	22.11	21.54	1
		1	50	21.49	21.89	21.49	1
		1	99	21.49	21.59	21.52	1
		50	0	20.40	20.78	20.53	2
		50	25	20.45	20.59	20.48	2
		50	50	20.45	20.47	20.51	2
		100	0	20.43	20.73	20.49	2
20M	64QAM	1	0	20.53	21.84	20.52	2
		1	50	20.47	20.47	20.53	2
		1	99	20.53	20.54	20.59	2
		50	0	19.56	20.74	19.45	3
		50	25	19.55	19.47	19.47	3
		50	50	19.43	19.60	19.56	3
		100	0	19.46	20.70	19.49	3
BW	MCS Index	Channel		20025	20175	20325	3GPP MPR
		Frequency (MHz)		1717.5	1732.5	1747.5	
15M	QPSK	1	0	22.47	22.58	22.53	0
		1	37	22.43	22.49	22.43	0
		1	74	22.42	22.44	22.44	0
		36	0	21.49	21.58	21.55	1
		36	19	21.47	21.53	21.52	1
		36	39	21.36	21.44	21.40	1
		75	0	21.46	21.53	21.52	1
15M	16QAM	1	0	21.48	21.46	21.43	1
		1	37	21.44	21.56	21.47	1
		1	74	21.37	21.60	21.51	1
		36	0	20.42	20.49	20.56	2
		36	19	20.52	20.55	20.52	2
		36	39	20.47	20.43	20.45	2
		75	0	20.37	20.48	20.49	2
15M	64QAM	1	0	20.40	20.42	20.50	2
		1	37	20.41	20.46	20.42	2
		1	74	20.51	20.49	20.50	2
		36	0	19.51	19.42	19.45	3
		36	19	19.39	19.57	19.51	3
		36	39	19.41	19.51	19.40	3
		75	0	19.43	19.45	19.41	3

LTE Conducted Power (Full)							
LTE Band 4							
BW	MCS Index	Channel		20000	20175	20350	3GPP MPR
		Frequency (MHz)		1715	1732.5	1750	
10M	QPSK	1	0	22.46	22.56	22.54	0
		1	24	22.40	22.42	22.38	0
		1	49	22.44	22.50	22.40	0
		25	0	21.52	21.57	21.54	1
		25	12	21.48	21.53	21.48	1
		25	25	21.38	21.47	21.42	1
		50	0	21.46	21.54	21.49	1
10M	16QAM	1	0	21.52	21.53	21.46	1
		1	24	21.43	21.54	21.48	1
		1	49	21.51	21.46	21.53	1
		25	0	20.48	20.44	20.51	2
		25	12	20.41	20.47	20.50	2
		25	25	20.43	20.45	20.43	2
		50	0	20.51	20.50	20.43	2
10M	64QAM	1	0	20.43	20.59	20.49	2
		1	24	20.48	20.53	20.40	2
		1	49	20.38	20.50	20.41	2
		25	0	19.41	19.42	19.50	3
		25	12	19.35	19.59	19.46	3
		25	25	19.36	19.57	19.54	3
		50	0	19.35	19.46	19.47	3
BW	MCS Index	Channel		19975	20175	20375	3GPP MPR
		Frequency (MHz)		1712.5	1732.5	1752.5	
5M	QPSK	1	0	22.47	22.57	22.55	0
		1	12	22.34	22.49	22.46	0
		1	24	22.39	22.42	22.43	0
		12	0	21.52	21.56	21.55	1
		12	6	21.42	21.49	21.49	1
		12	13	21.39	21.47	21.39	1
		25	0	21.47	21.53	21.47	1
5M	16QAM	1	0	21.44	21.55	21.51	1
		1	12	21.43	21.52	21.44	1
		1	24	21.44	21.52	21.54	1
		12	0	20.40	20.46	20.44	2
		12	6	20.44	20.59	20.43	2
		12	13	20.48	20.44	20.46	2
		25	0	20.41	20.50	20.38	2
5M	64QAM	1	0	20.44	20.51	20.39	2
		1	12	20.39	20.55	20.52	2
		1	24	20.34	20.53	20.56	2
		12	0	19.43	19.59	19.55	3
		12	6	19.36	19.46	19.51	3
		12	13	19.49	19.55	19.51	3
		25	0	19.48	19.44	19.55	3

LTE Conducted Power (Full)							
LTE Band 4							
BW	MCS Index	Channel		19965	20175	20385	3GPP MPR
		Frequency (MHz)		1711.5	1732.5	1753.5	
3M	QPSK	1	0	22.47	22.54	22.49	0
		1	7	22.39	22.43	22.37	0
		1	14	22.40	22.46	22.43	0
		8	0	21.47	21.54	21.52	1
		8	3	21.40	21.53	21.47	1
		8	7	21.36	21.44	21.41	1
		15	0	21.44	21.52	21.49	1
3M	16QAM	1	0	21.39	21.43	21.42	1
		1	7	21.37	21.41	21.45	1
		1	14	21.38	21.48	21.50	1
		8	0	20.46	20.43	20.45	2
		8	3	20.43	20.47	20.48	2
		8	7	20.50	20.56	20.40	2
		15	0	20.44	20.48	20.49	2
3M	64QAM	1	0	20.47	20.45	20.42	2
		1	7	20.41	20.58	20.50	2
		1	14	20.50	20.41	20.44	2
		8	0	19.46	19.50	19.43	3
		8	3	19.39	19.48	19.37	3
		8	7	19.34	19.49	19.49	3
		15	0	19.36	19.45	19.37	3
BW	MCS Index	Channel		19957	20175	20393	3GPP MPR
		Frequency (MHz)		1710.7	1732.5	1754.3	
1.4M	QPSK	1	0	22.49	22.53	22.49	0
		1	2	22.37	22.42	22.44	0
		1	5	22.40	22.44	22.38	0
		3	0	22.39	22.41	22.42	0
		3	1	22.32	22.40	22.37	0
		3	3	22.34	22.38	22.39	0
		6	0	21.32	21.46	21.39	1
1.4M	16QAM	1	0	21.38	21.44	21.42	1
		1	2	21.35	21.45	21.44	1
		1	5	21.40	21.47	21.43	1
		3	0	21.41	21.41	21.37	1
		3	1	21.35	21.43	21.44	1
		3	3	21.41	21.45	21.43	1
		6	0	20.41	20.43	20.36	2
1.4M	64QAM	1	0	20.33	20.43	20.37	2
		1	2	20.41	20.43	20.36	2
		1	5	20.37	20.40	20.37	2
		3	0	20.35	20.40	20.37	2
		3	1	20.39	20.48	20.41	2
		3	3	20.35	20.41	20.41	2
		6	0	19.38	19.45	19.37	3

LTE Conducted Power (Full)							
LTE Band 5							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600	
		Frequency (MHz)		829	836.5	844	
10M	QPSK	1	0	23.05	23.16	23.18	0
		1	24	22.93	23.09	23.12	0
		1	49	22.89	23.06	23.08	0
		25	0	22.06	22.15	22.18	1
		25	12	22.02	22.12	22.11	1
		25	25	21.93	22.01	22.09	1
10M	16QAM	50	0	21.99	22.07	22.15	1
		1	0	21.90	22.03	22.09	1
		1	24	22.02	22.12	22.19	1
		1	49	21.91	22.12	22.07	1
		25	0	20.89	21.13	21.11	2
		25	12	20.94	21.06	21.16	2
10M	64QAM	25	25	21.00	21.01	21.13	2
		50	0	20.96	21.15	21.05	2
		1	0	20.97	21.03	21.11	2
		1	24	20.97	21.12	21.03	2
		1	49	20.89	21.13	21.13	2
		25	0	19.94	20.12	20.12	3
5M	QPSK	25	12	20.06	20.01	20.15	3
		25	25	20.01	20.06	20.13	3
		50	0	20.04	20.12	20.16	3
		1	0	23.04	23.14	23.17	0
		1	12	22.91	23.00	23.09	0
		1	24	22.90	22.97	23.07	0
5M	16QAM	12	0	22.03	22.11	22.16	1
		12	6	21.96	22.05	22.09	1
		12	13	21.91	21.97	22.02	1
		25	0	21.93	22.05	22.10	1
		1	0	22.02	22.06	22.12	1
		1	12	21.95	22.08	22.13	1
5M	64QAM	1	24	21.98	22.06	21.99	1
		12	0	20.86	21.01	21.15	2
		12	6	20.86	21.00	21.04	2
		12	13	20.92	20.99	21.02	2
		25	0	20.95	21.11	21.01	2
		1	0	20.86	21.01	21.08	2
5M	QPSK	1	12	21.02	21.05	21.11	2
		1	24	20.91	21.05	21.01	2
		12	0	19.97	20.00	20.01	3
		12	6	19.90	19.99	20.06	3
		12	13	19.91	20.01	19.99	3
		25	0	19.92	20.01	20.10	3

LTE Conducted Power (Full)							
LTE Band 5							
BW	MCS Index	Channel		20415	20525	20635	3GPP MPR
		Frequency (MHz)		825.5	836.5	847.5	
3M	QPSK	1	0	23.00	23.03	23.10	0
		1	7	22.87	22.92	23.04	0
		1	14	22.84	22.92	22.99	0
		8	0	21.99	22.08	22.13	1
		8	3	21.94	22.01	22.09	1
		8	7	21.85	21.96	22.02	1
		15	0	21.91	22.01	22.08	1
3M	16QAM	1	0	21.92	22.04	22.06	1
		1	7	21.85	22.09	21.97	1
		1	14	22.01	22.08	22.07	1
		8	0	21.02	20.94	20.98	2
		8	3	20.85	21.00	21.04	2
		8	7	20.98	20.96	21.06	2
		15	0	20.91	21.09	21.11	2
3M	64QAM	1	0	20.99	21.05	21.03	2
		1	7	20.99	20.94	20.98	2
		1	14	20.98	21.07	21.13	2
		8	0	19.85	20.00	19.97	3
		8	3	19.94	19.97	19.97	3
		8	7	19.90	19.96	20.11	3
		15	0	19.90	20.06	19.98	3
BW	MCS Index	Channel		20407	20525	20643	3GPP MPR
		Frequency (MHz)		824.7	836.5	848.3	
1.4M	QPSK	1	0	22.97	23.02	23.08	0
		1	2	22.92	22.97	23.04	0
		1	5	22.84	22.94	23.04	0
		3	0	22.91	22.98	23.00	0
		3	1	22.86	22.92	22.96	0
		3	3	22.85	22.93	22.99	0
		6	0	21.86	21.97	22.01	1
1.4M	16QAM	1	0	21.92	21.99	21.98	1
		1	2	21.86	21.96	22.01	1
		1	5	21.88	21.94	21.98	1
		3	0	21.87	21.98	22.00	1
		3	1	21.92	21.95	21.97	1
		3	3	21.90	21.93	21.98	1
		6	0	20.84	20.98	21.04	2
1.4M	64QAM	1	0	20.87	20.97	21.00	2
		1	2	20.90	20.96	21.03	2
		1	5	20.91	20.92	20.97	2
		3	0	20.84	20.92	20.98	2
		3	1	20.84	20.96	20.96	2
		3	3	20.86	20.98	20.96	2
		6	0	19.92	19.92	20.00	3

LTE Conducted Power (Full)							
LTE Band 7							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350	
		Frequency (MHz)		2510	2535	2560	
20M	QPSK	1	0	23.19	23.22	23.38	0
		1	50	22.78	22.83	23.16	0
		1	99	22.71	22.87	23.09	0
		50	0	21.85	21.96	22.22	1
		50	25	21.78	21.93	22.19	1
		50	50	21.75	21.86	22.15	1
		100	0	21.79	21.89	22.16	1
20M	16QAM	1	0	21.80	21.93	22.21	1
		1	50	21.71	21.83	22.18	1
		1	99	21.80	21.87	22.25	1
		50	0	20.84	20.85	21.15	2
		50	25	20.78	20.81	21.14	2
		50	50	20.85	20.81	21.15	2
		100	0	20.70	20.87	21.15	2
20M	64QAM	1	0	20.72	20.81	21.16	2
		1	50	20.72	20.82	21.23	2
		1	99	20.78	20.88	21.14	2
		50	0	19.85	19.82	20.12	3
		50	25	19.82	19.82	20.10	3
		50	50	19.80	19.82	20.12	3
		100	0	19.77	19.92	20.16	3
BW	MCS Index	Channel		20825	21100	21375	3GPP MPR
		Frequency (MHz)		2507.5	2535	2562.5	
15M	QPSK	1	0	22.84	22.94	23.20	0
		1	37	22.71	22.78	23.04	0
		1	74	22.67	22.75	23.06	0
		36	0	21.80	21.93	22.20	1
		36	19	21.73	21.89	22.13	1
		36	39	21.68	21.79	22.09	1
		75	0	21.75	21.85	22.14	1
15M	16QAM	1	0	21.65	21.87	22.09	1
		1	37	21.81	21.77	22.17	1
		1	74	21.65	21.93	22.10	1
		36	0	20.73	20.93	21.13	2
		36	19	20.78	20.87	21.08	2
		36	39	20.72	20.86	21.10	2
		75	0	20.75	20.86	21.13	2
15M	64QAM	1	0	20.70	20.87	21.12	2
		1	37	20.70	20.76	21.10	2
		1	74	20.70	20.81	21.11	2
		36	0	19.78	19.91	20.11	3
		36	19	19.73	19.93	20.17	3
		36	39	19.82	19.92	20.14	3
		75	0	19.77	19.78	20.15	3

LTE Conducted Power (Full)							
LTE Band 7							
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR
		Frequency (MHz)		2505	2535	2565	
10M	QPSK	1	0	22.78	22.88	23.15	0
		1	24	22.68	22.84	23.04	0
		1	49	22.64	22.75	23.06	0
		25	0	21.79	21.93	22.19	1
		25	12	21.73	21.84	22.16	1
		25	25	21.67	21.79	22.07	1
		50	0	21.77	21.87	22.11	1
10M	16QAM	1	0	21.73	21.92	22.03	1
		1	24	21.64	21.85	22.15	1
		1	49	21.66	21.81	22.04	1
		25	0	20.76	20.87	21.20	2
		25	12	20.70	20.90	21.10	2
		25	25	20.80	20.92	21.16	2
		50	0	20.74	20.90	21.05	2
10M	64QAM	1	0	20.77	20.80	21.14	2
		1	24	20.65	20.82	21.11	2
		1	49	20.72	20.85	21.12	2
		25	0	19.64	19.87	20.16	3
		25	12	19.71	19.92	20.04	3
		25	25	19.65	19.91	20.03	3
		50	0	19.72	19.77	20.05	3
BW	MCS Index	Channel		20775	21100	21425	3GPP MPR
		Frequency (MHz)		2502.5	2535	2567.5	
5M	QPSK	1	0	22.75	22.88	23.17	0
		1	12	22.71	22.77	23.01	0
		1	24	22.71	22.78	23.01	0
		12	0	21.79	21.89	22.18	1
		12	6	21.76	21.82	22.11	1
		12	13	21.64	21.76	22.04	1
		25	0	21.70	21.81	22.12	1
5M	16QAM	1	0	21.69	21.84	22.15	1
		1	12	21.73	21.81	22.07	1
		1	24	21.79	21.82	22.20	1
		12	0	20.75	20.77	21.19	2
		12	6	20.71	20.78	21.09	2
		12	13	20.73	20.91	21.05	2
		25	0	20.70	20.87	21.19	2
5M	64QAM	1	0	20.66	20.92	21.09	2
		1	12	20.81	20.77	21.06	2
		1	24	20.65	20.77	21.14	2
		12	0	19.71	19.84	20.05	3
		12	6	19.81	19.76	20.18	3
		12	13	19.80	19.90	20.03	3
		25	0	19.77	19.83	20.11	3

LTE Conducted Power (Full)							
LTE Band 12							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23060	23095	23130	
		Frequency (MHz)		704	707.5	711	
10M	QPSK	1	0	22.85	22.96	23.16	0
		1	24	22.65	22.79	23.07	0
		1	49	22.73	22.85	23.03	0
		25	0	21.82	21.91	22.17	1
		25	12	21.75	21.88	22.07	1
		25	25	21.67	21.80	21.98	1
10M	16QAM	50	0	21.75	21.84	22.16	1
		1	0	21.83	21.88	22.31	1
		1	24	21.77	21.77	22.13	1
		1	49	21.76	21.92	22.15	1
		25	0	20.79	20.95	21.20	2
		25	12	20.78	20.79	21.05	2
10M	64QAM	25	25	20.69	20.95	21.03	2
		50	0	20.75	20.95	21.15	2
		1	0	20.69	20.86	21.12	2
		1	24	20.66	20.79	21.12	2
		1	49	20.77	20.78	21.06	2
		25	0	19.75	19.95	20.09	3
5M	QPSK	25	12	19.83	19.87	19.98	3
		25	25	19.78	19.88	20.06	3
		50	0	19.71	19.89	20.05	3
		1	0	22.77	22.87	23.03	0
		1	12	22.68	22.79	22.97	0
		1	24	22.70	22.74	22.96	0
5M	16QAM	12	0	21.75	21.89	22.06	1
		12	6	21.69	21.84	22.00	1
		12	13	21.62	21.77	21.97	1
		25	0	21.73	21.80	22.04	1
		1	0	21.76	21.89	22.07	1
		1	12	21.64	21.90	22.07	1
5M	64QAM	1	24	21.64	21.81	22.10	1
		12	0	20.78	20.77	20.93	2
		12	6	20.63	20.76	21.05	2
		12	13	20.62	20.73	20.92	2
		25	0	20.71	20.75	21.07	2
		1	0	20.75	20.75	20.94	2
5M	QPSK	1	12	20.79	20.76	21.07	2
		1	24	20.64	20.75	21.04	2
		12	0	19.78	19.88	20.02	3
		12	6	19.71	19.76	20.05	3
		12	13	19.74	19.73	19.97	3
		25	0	19.67	19.73	19.98	3

LTE Conducted Power (Full)							
LTE Band 12							
BW	MCS Index	Channel		23025	23095	23165	3GPP MPR
		Frequency (MHz)		700.5	707.5	714.5	
3M	QPSK	1	0	22.80	22.83	23.05	0
		1	7	22.68	22.78	23.01	0
		1	14	22.60	22.71	22.99	0
		8	0	21.77	21.90	22.06	1
		8	3	21.72	21.84	21.99	1
		8	7	21.65	21.78	21.95	1
		15	0	21.69	21.85	22.02	1
3M	16QAM	1	0	21.79	21.83	21.96	1
		1	7	21.79	21.81	22.10	1
		1	14	21.68	21.79	21.99	1
		8	0	20.75	20.73	21.07	2
		8	3	20.69	20.78	21.10	2
		8	7	20.65	20.77	21.02	2
		15	0	20.76	20.81	21.10	2
3M	64QAM	1	0	20.63	20.74	21.04	2
		1	7	20.62	20.73	21.00	2
		1	14	20.75	20.90	21.08	2
		8	0	19.79	19.76	20.01	3
		8	3	19.76	19.72	19.98	3
		8	7	19.75	19.73	19.97	3
		15	0	19.76	19.79	19.97	3
BW	MCS Index	Channel		23017	23095	23173	3GPP MPR
		Frequency (MHz)		699.7	707.5	715.3	
1.4M	QPSK	1	0	22.75	22.82	23.03	0
		1	2	22.64	22.72	23.01	0
		1	5	22.62	22.76	23.00	0
		3	0	22.67	22.77	22.93	0
		3	1	22.60	22.72	22.92	0
		3	3	22.62	22.74	22.91	0
		6	0	21.67	21.78	21.94	1
1.4M	16QAM	1	0	21.61	21.77	21.94	1
		1	2	21.66	21.75	22.00	1
		1	5	21.68	21.74	21.94	1
		3	0	21.68	21.80	21.93	1
		3	1	21.69	21.76	21.95	1
		3	3	21.65	21.75	21.97	1
		6	0	20.68	20.78	20.96	2
1.4M	64QAM	1	0	20.64	20.75	21.00	2
		1	2	20.62	20.79	20.92	2
		1	5	20.68	20.80	20.96	2
		3	0	20.64	20.73	20.94	2
		3	1	20.66	20.73	20.92	2
		3	3	20.68	20.77	20.98	2
		6	0	19.64	19.76	19.93	3

LTE Conducted Power (Full)							
LTE Band 13							
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)
		Channel			23230		
		Frequency (MHz)			782		
10M	QPSK	1	0		22.98		0
		1	24		22.84		0
		1	49		22.8		0
		25	0		21.95		1
		25	12		21.87		1
		25	25		21.85		1
10M	16QAM	50	0		21.92		1
		1	0		21.80		1
		1	24		21.92		1
		1	49		21.88		1
		25	0		20.96		2
		25	12		20.91		2
10M	64QAM	25	25		20.83		2
		50	0		20.84		2
		1	0		20.83		2
		1	24		20.89		2
		1	49		20.84		2
		25	0		19.84		3
10M	64QAM	25	12		19.87		3
		25	25		19.97		3
		50	0		19.91		3
BW	MCS Index	Channel		23205	23230	23255	3GPP MPR
		Frequency (MHz)		779.5	782	784.5	
5M	QPSK	1	0	22.89	22.93	22.76	0
		1	12	22.79	22.83	22.64	0
		1	24	22.76	22.80	22.71	0
		12	0	21.87	21.91	21.79	1
		12	6	21.79	21.86	21.73	1
		12	13	21.71	21.77	21.69	1
5M	16QAM	25	0	21.78	21.86	21.71	1
		1	0	21.80	21.83	21.65	1
		1	12	21.79	21.83	21.68	1
		1	24	21.73	21.79	21.64	1
		12	0	20.87	20.82	20.66	2
		12	6	20.77	20.93	20.78	2
5M	64QAM	12	13	20.75	20.92	20.78	2
		25	0	20.74	20.90	20.68	2
		1	0	20.71	20.93	20.72	2
		1	12	20.81	20.87	20.79	2
		1	24	20.81	20.94	20.75	2
		12	0	19.82	19.78	19.78	3
5M	64QAM	12	6	19.87	19.89	19.74	3
		12	13	19.83	19.76	19.75	3
		25	0	19.81	19.89	19.69	3

LTE Conducted Power (Full)							
LTE Band 14							
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)
		Channel			23330		
		Frequency (MHz)			793		
10M	QPSK	1	0		22.89		0
		1	24		22.73		0
		1	49		22.76		0
		25	0		21.86		1
		25	12		21.77		1
		25	25		21.74		1
10M	16QAM	50	0		21.83		1
		1	0		21.70		1
		1	24		21.79		1
		1	49		21.72		1
		25	0		20.79		2
		25	12		20.81		2
10M	64QAM	25	25		20.75		2
		50	0		20.79		2
		1	0		20.71		2
		1	24		20.85		2
		1	49		20.70		2
		25	0		19.80		3
10M	64QAM	25	12		19.81		3
		25	25		19.79		3
		50	0		19.74		3
BW	MCS Index	Channel		23305	23330	23355	3GPP MPR
		Frequency (MHz)		790.5	793	795.5	
5M	QPSK	1	0	22.64	22.81	22.74	0
		1	12	22.49	22.68	22.55	0
		1	24	22.54	22.68	22.56	0
		12	0	21.64	21.82	21.69	1
		12	6	21.57	21.74	21.66	1
		12	13	21.51	21.71	21.60	1
5M	16QAM	25	0	21.59	21.77	21.67	1
		1	0	21.61	21.74	21.71	1
		1	12	21.56	21.83	21.70	1
		1	24	21.54	21.68	21.56	1
		12	0	20.56	20.78	20.68	2
		12	6	20.58	20.84	20.61	2
5M	64QAM	12	13	20.51	20.69	20.58	2
		25	0	20.54	20.73	20.55	2
		1	0	20.62	20.74	20.58	2
		1	12	20.56	20.76	20.68	2
		1	24	20.57	20.78	20.57	2
		12	0	19.64	19.84	19.66	3
5M	64QAM	12	6	19.60	19.74	19.55	3
		12	13	19.57	19.75	19.56	3
		25	0	19.61	19.67	19.58	3

LTE Conducted Power (Full)							
LTE Band 25							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26140	26365	26590	
		Frequency (MHz)		1860	1882.5	1905	
20M	QPSK	1	0	22.58	22.51	22.30	0
		1	50	22.40	22.34	22.17	0
		1	99	22.44	22.41	22.18	0
		50	0	21.55	21.46	21.28	1
		50	25	21.49	21.39	21.22	1
		50	50	21.42	21.36	21.16	1
		100	0	21.51	21.43	21.22	1
20M	16QAM	1	0	21.49	21.47	21.15	1
		1	50	21.40	21.47	21.17	1
		1	99	21.41	21.37	21.22	1
		50	0	20.44	20.42	20.18	2
		50	25	20.39	20.46	20.17	2
		50	50	20.44	20.49	20.13	2
		100	0	20.53	20.32	20.17	2
20M	64QAM	1	0	20.55	20.37	20.13	2
		1	50	20.54	20.46	20.22	2
		1	99	20.53	20.45	20.18	2
		50	0	19.41	19.34	19.11	3
		50	25	19.44	19.32	19.24	3
		50	50	19.53	19.36	19.27	3
		100	0	19.41	19.36	19.16	3
BW	MCS Index	Channel		26115	26365	26615	3GPP MPR
		Frequency (MHz)		1857.5	1882.5	1907.5	
15M	QPSK	1	0	22.49	22.46	22.21	0
		1	37	22.39	22.37	22.10	0
		1	74	22.37	22.35	22.12	0
		36	0	21.49	21.45	21.22	1
		36	19	21.46	21.39	21.19	1
		36	39	21.39	21.32	21.10	1
		75	0	21.46	21.37	21.20	1
15M	16QAM	1	0	21.44	21.28	21.21	1
		1	37	21.47	21.36	21.14	1
		1	74	21.50	21.28	21.12	1
		36	0	20.36	20.34	20.10	2
		36	19	20.38	20.33	20.19	2
		36	39	20.47	20.39	20.22	2
		75	0	20.38	20.42	20.22	2
15M	64QAM	1	0	20.41	20.41	20.22	2
		1	37	20.42	20.33	20.24	2
		1	74	20.38	20.28	20.08	2
		36	0	19.40	19.36	19.10	3
		36	19	19.49	19.33	19.07	3
		36	39	19.35	19.41	19.09	3
		75	0	19.35	19.39	19.09	3

LTE Conducted Power (Full)							
LTE Band 25							
BW	MCS Index	Channel		26090	26365	26640	3GPP MPR
		Frequency (MHz)		1855	1882.5	1910	
10M	QPSK	1	0	22.46	22.39	22.26	0
		1	24	22.43	22.33	22.12	0
		1	49	22.37	22.30	22.06	0
		25	0	21.52	21.42	21.25	1
		25	12	21.46	21.37	21.19	1
		25	25	21.41	21.30	21.12	1
		50	0	21.46	21.39	21.19	1
10M	16QAM	1	0	21.42	21.33	21.23	1
		1	24	21.52	21.43	21.11	1
		1	49	21.35	21.44	21.11	1
		25	0	20.45	20.39	20.14	2
		25	12	20.36	20.40	20.16	2
		25	25	20.40	20.29	20.08	2
		50	0	20.46	20.35	20.15	2
10M	64QAM	1	0	20.39	20.34	20.13	2
		1	24	20.47	20.41	20.12	2
		1	49	20.48	20.41	20.19	2
		25	0	19.37	19.32	19.21	3
		25	12	19.47	19.37	19.20	3
		25	25	19.37	19.38	19.14	3
		50	0	19.49	19.32	19.24	3
BW	MCS Index	Channel		26065	26365	26665	3GPP MPR
		Frequency (MHz)		1852.5	1882.5	1912.5	
5M	QPSK	1	0	22.51	22.41	22.26	0
		1	12	22.44	22.33	22.12	0
		1	24	22.43	22.32	22.07	0
		12	0	21.49	21.42	21.25	1
		12	6	21.47	21.41	21.17	1
		12	13	21.36	21.33	21.09	1
		25	0	21.45	21.40	21.16	1
5M	16QAM	1	0	21.44	21.31	21.24	1
		1	12	21.39	21.33	21.19	1
		1	24	21.42	21.37	21.11	1
		12	0	20.43	20.42	20.18	2
		12	6	20.51	20.34	20.17	2
		12	13	20.35	20.33	20.19	2
		25	0	20.38	20.35	20.16	2
5M	64QAM	1	0	20.40	20.30	20.07	2
		1	12	20.41	20.45	20.23	2
		1	24	20.39	20.30	20.16	2
		12	0	19.36	19.34	19.08	3
		12	6	19.48	19.40	19.21	3
		12	13	19.46	19.36	19.18	3
		25	0	19.40	19.30	19.15	3

LTE Conducted Power (Full)							
LTE Band 25							
BW	MCS Index	Channel		26055	26365	26675	3GPP MPR
		Frequency (MHz)		1851.5	1882.5	1913.5	
3M	QPSK	1	0	22.50	22.42	22.24	0
		1	7	22.39	22.30	22.12	0
		1	14	22.34	22.34	22.15	0
		8	0	21.50	21.42	21.24	1
		8	3	21.45	21.35	21.18	1
		8	7	21.38	21.30	21.09	1
		15	0	21.48	21.40	21.15	1
3M	16QAM	1	0	21.48	21.32	21.24	1
		1	7	21.47	21.29	21.23	1
		1	14	21.49	21.28	21.10	1
		8	0	20.35	20.31	20.07	2
		8	3	20.39	20.36	20.11	2
		8	7	20.48	20.43	20.15	2
		15	0	20.35	20.31	20.19	2
3M	64QAM	1	0	20.43	20.35	20.15	2
		1	7	20.39	20.41	20.18	2
		1	14	20.36	20.42	20.08	2
		8	0	19.44	19.39	19.11	3
		8	3	19.36	19.34	19.18	3
		8	7	19.52	19.36	19.10	3
		15	0	19.50	19.38	19.17	3
BW	MCS Index	Channel		26047	26365	26683	3GPP MPR
		Frequency (MHz)		1850.7	1882.5	1914.3	
1.4M	QPSK	1	0	22.49	22.44	22.20	0
		1	2	22.37	22.36	22.13	0
		1	5	22.37	22.36	22.15	0
		3	0	22.43	22.34	22.13	0
		3	1	22.38	22.32	22.11	0
		3	3	22.35	22.27	22.07	0
		6	0	21.36	21.29	21.06	1
1.4M	16QAM	1	0	21.39	21.35	21.07	1
		1	2	21.37	21.28	21.14	1
		1	5	21.40	21.32	21.12	1
		3	0	21.39	21.34	21.07	1
		3	1	21.35	21.31	21.07	1
		3	3	21.43	21.29	21.12	1
		6	0	20.38	20.35	20.08	2
1.4M	64QAM	1	0	20.42	20.33	20.09	2
		1	2	20.40	20.32	20.14	2
		1	5	20.40	20.29	20.14	2
		3	0	20.39	20.36	20.10	2
		3	1	20.41	20.34	20.13	2
		3	3	20.35	20.34	20.09	2
		6	0	19.42	19.29	19.12	3

LTE Conducted Power (Full)								
LTE Band 26								
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid-1	High	3GPP MPR (dB)
		Channel		26765	26865	26915	26965	
		Frequency (MHz)		821.5	831.5	836.5	841.5	
15M	QPSK	1	0	22.83	22.86	22.85	22.89	0
		1	37	22.67	22.67	22.65	22.73	0
		1	74	22.64	22.66	22.58	22.74	0
		36	0	21.81	21.82	21.74	21.86	1
		36	19	21.73	21.75	21.71	21.78	1
		36	39	21.67	21.68	21.59	21.71	1
15M	16QAM	75	0	21.73	21.78	21.78	21.83	1
		1	0	21.66	21.80	21.76	21.83	1
		1	37	21.66	21.70	21.70	21.80	1
		1	74	21.69	21.77	21.74	21.87	1
		36	0	20.70	20.76	20.70	20.79	2
		36	19	20.78	20.79	20.75	20.81	2
15M	64QAM	36	39	20.66	20.80	20.73	20.81	2
		75	0	20.66	20.74	20.69	20.73	2
		1	0	20.65	20.66	20.64	20.73	2
		1	37	20.68	20.70	20.62	20.79	2
		1	74	20.76	20.72	20.67	20.76	2
		36	0	19.70	19.74	19.68	19.73	3
15M	64QAM	36	19	19.72	19.72	19.64	19.72	3
		36	39	19.79	19.75	19.74	19.85	3
		75	0	19.64	19.82	19.82	19.81	3
BW	MCS Index	Channel		26740	26865	26915	26990	3GPP MPR
		Frequency (MHz)		819	831.5	836.5	844	
10M	QPSK	1	0	22.78	22.75	22.75	22.84	0
		1	24	22.65	22.62	22.61	22.72	0
		1	49	22.64	22.62	22.51	22.69	0
		25	0	21.77	21.78	21.67	21.81	1
		25	12	21.68	21.74	21.63	21.78	1
		25	25	21.65	21.64	21.56	21.68	1
10M	16QAM	50	0	21.66	21.71	21.78	21.73	1
		1	0	21.59	21.70	21.69	21.74	1
		1	24	21.70	21.66	21.70	21.81	1
		1	49	21.64	21.75	21.68	21.82	1
		25	0	20.75	20.77	20.67	20.73	2
		25	12	20.63	20.70	20.69	20.72	2
10M	64QAM	25	25	20.71	20.73	20.70	20.66	2
		50	0	20.68	20.67	20.63	20.69	2
		1	0	20.76	20.76	20.63	20.77	2
		1	24	20.61	20.76	20.61	20.73	2
		1	49	20.59	20.72	20.67	20.72	2
		25	0	19.73	19.66	19.68	19.79	3
10M	64QAM	25	12	19.66	19.70	19.59	19.77	3
		25	25	19.65	19.63	19.64	19.71	3
		50	0	19.64	19.62	19.80	19.72	3

LTE Conducted Power (Full)								
LTE Band 26								
BW	MCS Index	Channel		26715	26865	26915	27015	3GPP MPR
		Frequency (MHz)		816.5	831.5	836.5	846.5	
5M	QPSK	1	0	22.60	22.64	22.74	22.69	0
		1	12	22.54	22.54	22.54	22.65	0
		1	24	22.48	22.55	22.42	22.57	0
		12	0	21.65	21.65	21.60	21.72	1
		12	6	21.60	21.58	21.55	21.64	1
		12	13	21.50	21.57	21.46	21.58	1
		25	0	21.56	21.60	21.73	21.67	1
5M	16QAM	1	0	21.62	21.60	21.62	21.65	1
		1	12	21.58	21.57	21.60	21.72	1
		1	24	21.66	21.52	21.64	21.74	1
		12	0	20.56	20.54	20.63	20.66	2
		12	6	20.57	20.51	20.59	20.61	2
		12	13	20.59	20.51	20.62	20.74	2
		25	0	20.57	20.59	20.59	20.61	2
5M	64QAM	1	0	20.64	20.64	20.62	20.68	2
		1	12	20.66	20.65	20.57	20.72	2
		1	24	20.60	20.60	20.63	20.60	2
		12	0	19.51	19.68	19.68	19.67	3
		12	6	19.50	19.57	19.54	19.57	3
		12	13	19.62	19.67	19.62	19.61	3
		25	0	19.56	19.55	19.71	19.73	3
BW	MCS Index	Channel		26705	26865	26915	27025	3GPP MPR
		Frequency (MHz)		815.5	831.5	836.5	847.5	
3M	QPSK	1	0	22.63	22.61	22.77	22.72	0
		1	7	22.57	22.51	22.43	22.56	0
		1	14	22.50	22.50	22.42	22.64	0
		8	0	21.64	21.66	21.64	21.72	1
		8	3	21.59	21.59	21.53	21.68	1
		8	7	21.52	21.53	21.46	21.57	1
		15	0	21.61	21.62	21.54	21.65	1
3M	16QAM	1	0	21.56	21.56	21.63	21.73	1
		1	7	21.51	21.58	21.51	21.66	1
		1	14	21.67	21.64	21.57	21.60	1
		8	0	20.55	20.60	20.59	20.67	2
		8	3	20.52	20.51	20.55	20.61	2
		8	7	20.66	20.54	20.54	20.74	2
		15	0	20.67	20.54	20.55	20.59	2
3M	64QAM	1	0	20.64	20.68	20.55	20.56	2
		1	7	20.57	20.63	20.43	20.61	2
		1	14	20.57	20.66	20.44	20.68	2
		8	0	19.51	19.52	19.63	19.60	3
		8	3	19.64	19.66	19.57	19.64	3
		8	7	19.50	19.63	19.54	19.62	3
		15	0	19.54	19.68	19.69	19.69	3

LTE Conducted Power (Full)								
LTE Band 26								
BW	MCS Index	Channel		26697	26865	26915	27033	3GPP MPR
		Frequency (MHz)		814.7	831.5	836.5	848.3	
1.4M	QPSK	1	0	22.63	22.66	22.65	22.72	0
		1	2	22.56	22.54	22.63	22.64	0
		1	5	22.54	22.53	22.61	22.59	0
		3	0	22.58	22.61	22.63	22.65	0
		3	1	22.49	22.55	22.54	22.59	0
		3	3	22.49	22.53	22.56	22.60	0
1.4M	16QAM	6	0	21.49	21.51	21.59	21.58	1
		1	0	21.56	21.52	21.59	21.63	1
		1	2	21.53	21.54	21.59	21.56	1
		1	5	21.56	21.51	21.59	21.56	1
		3	0	21.56	21.55	21.59	21.64	1
		3	1	21.55	21.59	21.58	21.57	1
1.4M	64QAM	3	3	21.56	21.58	21.56	21.56	1
		6	0	20.52	20.52	20.58	20.61	2
		1	0	20.55	20.59	20.60	20.59	2
		1	2	20.52	20.51	20.59	20.60	2
		1	5	20.51	20.59	20.54	20.56	2
		3	0	20.57	20.59	20.61	20.56	2
		3	1	20.53	20.55	20.55	20.58	2
		3	3	20.55	20.54	20.61	20.61	2
		6	0	19.52	19.56	19.62	19.60	3

LTE Conducted Power (Full)									
LTE Band 41									
BW	MCS Index	RB Size	RB Offset	Low-2	Mid-1	Mid-2	Mid-3	High	3GPP MPR (dB)
		Channel		39750	40185	40620	41055	41490	
		Frequency (MHz)		2506	2549.5	2593	2636.5	2680	
20M	QPSK	1	0	23.00	23.11	23.14	23.21	23.26	0
		1	50	22.88	23.00	23.08	23.18	23.22	0
		1	99	22.87	22.97	23.07	23.17	23.21	0
		50	0	22.52	22.58	22.67	22.68	22.71	1
		50	25	22.45	22.55	22.57	22.65	22.68	1
		50	50	22.43	22.45	22.55	22.61	22.67	1
		100	0	22.49	22.56	22.61	22.63	22.69	1
20M	16QAM	1	0	22.42	22.43	22.46	22.56	22.81	1
		1	50	22.36	22.41	22.45	22.53	22.78	1
		1	99	22.35	22.37	22.43	22.51	22.69	1
		50	0	21.59	21.62	21.63	21.69	21.79	2
		50	25	21.52	21.59	21.51	21.61	21.76	2
		50	50	21.51	21.58	21.58	21.63	21.75	2
		100	0	21.53	21.56	21.61	21.65	21.78	2
20M	64QAM	1	0	21.46	21.49	21.51	21.56	21.48	2
		1	50	21.38	21.41	21.47	21.55	21.46	2
		1	99	21.31	21.35	21.39	21.49	21.38	2
		50	0	20.57	20.57	20.61	20.67	20.73	3
		50	25	20.39	20.47	20.56	20.61	20.72	3
		50	50	20.38	20.46	20.57	20.66	20.67	3
		100	0	20.53	20.56	20.58	20.59	20.75	3
BW	MCS Index	Channel		39725	40173	40620	41068	41515	3GPP MPR
		Frequency (MHz)		2503.5	2548.3	2593	2637.8	2682.5	
15M	QPSK	1	0	22.83	22.91	23.10	23.13	23.19	0
		1	37	22.84	22.94	23.02	23.13	23.14	0
		1	74	22.79	22.91	22.99	23.13	23.21	0
		36	0	22.48	22.49	22.62	22.60	22.63	1
		36	19	22.45	22.45	22.57	22.55	22.61	1
		36	39	22.40	22.37	22.55	22.58	22.64	1
		75	0	22.45	22.50	22.60	22.62	22.62	1
15M	16QAM	1	0	22.34	22.38	22.40	22.56	22.52	1
		1	37	22.33	22.38	22.38	22.50	22.54	1
		1	74	22.27	22.27	22.33	22.49	22.49	1
		36	0	21.55	21.61	21.62	21.63	21.62	2
		36	19	21.42	21.57	21.46	21.61	21.58	2
		36	39	21.51	21.50	21.53	21.56	21.67	2
		75	0	21.52	21.54	21.58	21.60	21.63	2
15M	64QAM	1	0	21.38	21.40	21.43	21.46	21.55	2
		1	37	21.31	21.31	21.46	21.55	21.51	2
		1	74	21.31	21.33	21.38	21.40	21.48	2
		36	0	20.49	20.57	20.61	20.65	20.64	3
		36	19	20.29	20.43	20.56	20.51	20.59	3
		36	39	20.37	20.40	20.49	20.62	20.66	3
		75	0	20.43	20.55	20.52	20.53	20.59	3

LTE Conducted Power (Full)									
LTE Band 41									
BW	MCS Index	Channel		39700	40160	40620	41080	41540	3GPP MPR
		Frequency (MHz)		2501	2547	2593	2639	2685	
10M	QPSK	1	0	22.77	22.90	22.96	23.14	23.13	0
		1	24	22.76	22.96	22.92	23.05	23.17	0
		1	49	22.84	22.82	22.97	23.07	23.08	0
		25	0	22.40	22.57	22.63	22.55	22.68	1
		25	12	22.39	22.48	22.52	22.47	22.60	1
		25	25	22.33	22.29	22.44	22.51	22.60	1
		50	0	22.39	22.45	22.44	22.54	22.53	1
10M	16QAM	1	0	22.13	22.26	22.31	22.50	22.50	1
		1	24	22.12	22.32	22.29	22.41	22.47	1
		1	49	22.12	22.26	22.37	22.37	22.44	1
		25	0	21.43	21.47	21.65	21.58	21.68	2
		25	12	21.30	21.51	21.46	21.48	21.63	2
		25	25	21.31	21.37	21.40	21.53	21.62	2
		50	0	21.47	21.49	21.44	21.50	21.50	2
10M	64QAM	1	0	21.11	21.31	21.33	21.43	21.45	2
		1	24	21.17	21.26	21.26	21.44	21.45	2
		1	49	21.20	21.27	21.35	21.34	21.48	2
		25	0	20.40	20.49	20.63	20.60	20.63	3
		25	12	20.30	20.54	20.45	20.51	20.59	3
		25	25	20.34	20.29	20.41	20.48	20.58	3
		50	0	20.39	20.46	20.49	20.47	20.58	3
BW	MCS Index	Channel		39675	40148	40620	41093	41565	3GPP MPR
		Frequency (MHz)		2498.5	2545.8	2593	2640.3	2687.5	
5M	QPSK	1	0	22.73	22.91	23.03	23.11	23.18	0
		1	12	22.82	22.87	22.90	23.10	23.13	0
		1	24	22.80	22.90	22.93	23.12	23.05	0
		12	0	22.46	22.41	22.54	22.57	22.66	1
		12	6	22.37	22.41	22.43	22.64	22.58	1
		12	13	22.32	22.26	22.42	22.46	22.53	1
		25	0	22.41	22.50	22.47	22.55	22.55	1
5M	16QAM	1	0	22.09	22.33	22.30	22.51	22.50	1
		1	12	22.08	22.28	22.34	22.50	22.44	1
		1	24	22.11	22.30	22.26	22.42	22.40	1
		12	0	21.52	21.39	21.50	21.57	21.60	2
		12	6	21.38	21.41	21.45	21.64	21.65	2
		12	13	21.36	21.27	21.48	21.45	21.59	2
		25	0	21.44	21.54	21.53	21.54	21.61	2
5M	64QAM	1	0	21.14	21.28	21.39	21.45	21.47	2
		1	12	21.08	21.20	21.31	21.43	21.43	2
		1	24	21.11	21.27	21.33	21.40	21.43	2
		12	0	20.46	20.40	20.60	20.66	20.62	3
		12	6	20.42	20.39	20.43	20.56	20.61	3
		12	13	20.31	20.32	20.52	20.52	20.59	3
		25	0	20.36	20.47	20.50	20.53	20.53	3

LTE Conducted Power (Full)								
LTE Band 48								
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	High	3GPP MPR (dB)
		Channel		55340	55780	56210	56640	
		Frequency (MHz)		3560	3604	3647	3690	
20M	QPSK	1	0	22.15	22.19	22.11	22.28	0
		1	50	22.03	22.17	21.99	22.26	0
		1	99	22.02	22.16	21.98	22.25	0
		50	0	21.11	21.25	21.07	21.27	1
		50	25	21.13	21.23	21.02	21.25	1
		50	50	21.05	21.15	21.01	21.21	1
		100	0	21.19	21.22	21.16	21.28	1
20M	16QAM	1	0	21.12	21.19	21.11	21.29	1
		1	50	21.09	21.17	21.08	21.26	1
		1	99	20.97	21.15	20.96	21.25	1
		50	0	20.05	20.18	19.97	20.27	2
		50	25	19.99	20.17	19.96	20.25	2
		50	50	19.97	20.15	19.95	20.23	2
		100	0	20.15	20.21	20.11	20.28	2
20M	64QAM	1	0	20.13	20.21	20.09	20.22	2
		1	50	20.11	20.18	20.07	20.21	2
		1	99	20.05	20.17	19.98	20.19	2
		50	0	19.13	19.22	19.11	19.28	3
		50	25	19.12	19.21	19.08	19.26	3
		50	50	19.05	19.17	19.01	19.25	3
		100	0	19.16	19.25	19.06	19.29	3
BW	MCS Index	Channel		55315	55765	56215	56665	3GPP MPR
		Frequency (MHz)		3557.5	3602.5	3647.5	3692.5	
15M	QPSK	1	0	22.10	22.14	22.09	22.18	0
		1	37	21.99	22.13	21.91	22.26	0
		1	74	21.99	22.15	21.92	22.19	0
		36	0	21.05	21.23	20.97	21.26	1
		36	19	21.03	21.16	21.02	21.18	1
		36	39	20.97	21.10	20.97	21.12	1
		75	0	21.15	21.20	21.14	21.21	1
15M	16QAM	1	0	21.03	21.15	21.03	21.20	1
		1	37	21.06	21.08	21.02	21.22	1
		1	74	20.91	21.06	20.94	21.18	1
		36	0	19.95	20.14	19.92	20.18	2
		36	19	19.97	20.14	19.94	20.21	2
		36	39	19.92	20.08	19.92	20.17	2
		75	0	20.06	20.12	20.11	20.19	2
15M	64QAM	1	0	20.03	20.11	20.04	20.24	2
		1	37	20.08	20.18	19.97	20.23	2
		1	74	19.97	20.17	19.92	20.18	2
		36	0	19.07	19.15	19.09	19.17	3
		36	19	19.07	19.20	19.08	19.23	3
		36	39	19.00	19.10	18.96	19.13	3
		75	0	19.12	19.24	18.97	19.26	3

LTE Conducted Power (Full)								
LTE Band 48								
BW	MCS Index	Channel		55290	55750	56220	56690	3GPP MPR
		Frequency (MHz)		3555	3601	3648	3695	
10M	QPSK	1	0	22.01	22.10	22.06	22.14	0
		1	24	21.95	22.11	21.95	22.16	0
		1	49	21.96	22.01	21.85	22.19	0
		25	0	20.99	21.10	20.94	21.14	1
		25	12	21.02	21.07	20.84	21.13	1
		25	25	20.95	21.09	20.87	21.14	1
		50	0	21.15	21.10	21.04	21.11	1
10M	16QAM	1	0	21.02	21.08	21.07	21.19	1
		1	24	20.99	21.06	20.95	21.24	1
		1	49	21.01	20.99	20.81	21.20	1
		25	0	19.97	20.16	19.96	20.15	2
		25	12	20.01	20.12	19.90	20.10	2
		25	25	19.88	20.12	19.85	20.17	2
		50	0	20.07	20.09	20.05	20.09	2
10M	64QAM	1	0	20.05	20.09	20.02	20.20	2
		1	24	20.03	20.03	19.91	20.26	2
		1	49	19.99	20.06	19.80	20.24	2
		25	0	19.02	19.12	18.93	19.15	3
		25	12	19.06	19.12	18.91	19.09	3
		25	25	18.92	19.07	18.91	19.18	3
		50	0	19.16	19.15	19.08	19.11	3
BW	MCS Index	Channel		55265	55745	56235	56715	3GPP MPR
		Frequency (MHz)		3552.5	3600.5	3649.5	3697.5	
5M	QPSK	1	0	22.08	22.08	21.98	22.22	0
		1	12	21.94	22.13	21.97	22.23	0
		1	24	21.92	22.12	21.80	22.25	0
		12	0	21.03	21.17	21.01	21.15	1
		12	6	21.08	21.15	20.90	21.11	1
		12	13	20.87	21.10	20.93	21.12	1
		25	0	21.06	21.13	21.00	21.17	1
5M	16QAM	1	0	21.12	21.03	21.02	21.19	1
		1	12	20.86	21.08	20.90	21.20	1
		1	24	20.85	21.13	20.79	21.22	1
		12	0	20.05	20.14	19.96	20.12	2
		12	6	20.03	20.14	19.90	20.09	2
		12	13	19.93	20.13	19.89	20.12	2
		25	0	20.06	20.17	20.01	20.24	2
5M	64QAM	1	0	20.06	20.05	19.98	20.16	2
		1	12	19.90	20.15	19.93	20.17	2
		1	24	19.84	20.15	19.85	20.22	2
		12	0	18.97	19.16	18.98	19.20	3
		12	6	19.03	19.13	18.94	19.19	3
		12	13	18.91	19.05	18.89	19.13	3
		25	0	19.01	19.12	19.00	19.19	3

LTE Conducted Power (Full)							
LTE Band 66							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		132072	132322	132572	
		Frequency (MHz)		1720	1745	1770	
20M	QPSK	1	0	23.05	23.11	23.02	0
		1	50	23.02	23.03	22.99	0
		1	99	22.97	23.01	22.95	0
		50	0	22.03	22.05	22.01	1
		50	25	22.02	22.03	21.98	1
		50	50	21.96	22.02	21.91	1
20M	16QAM	100	0	22.05	22.06	21.96	1
		1	0	22.31	22.38	22.23	1
		1	50	22.29	22.35	22.21	1
		1	99	22.28	22.31	22.25	1
		50	0	21.12	21.13	21.02	2
		50	25	21.09	21.11	21.06	2
20M	64QAM	50	50	20.99	21.07	20.93	2
		100	0	21.05	21.08	20.99	2
		1	0	21.27	21.32	21.21	2
		1	50	21.21	21.29	21.16	2
		1	99	21.18	21.27	21.13	2
		50	0	20.17	20.21	20.11	3
20M	64QAM	50	25	20.07	20.17	20.05	3
		50	50	20.03	20.12	19.95	3
		100	0	20.06	20.15	20.03	3
BW	MCS Index	Channel		132047	132322	132597	3GPP MPR
		Frequency (MHz)		1717.5	1745	1772.5	
15M	QPSK	1	0	22.99	23.10	22.93	0
		1	37	22.94	22.94	22.99	0
		1	74	22.93	22.98	22.91	0
		36	0	22.01	21.98	22.01	1
		36	19	21.97	22.02	21.90	1
		36	39	21.88	21.99	21.89	1
15M	16QAM	75	0	22.04	21.97	21.96	1
		1	0	22.27	22.31	22.20	1
		1	37	22.19	22.30	22.19	1
		1	74	22.25	22.26	22.17	1
		36	0	21.09	21.12	21.00	2
		36	19	21.09	21.10	21.06	2
15M	64QAM	36	39	20.91	20.97	20.84	2
		75	0	20.95	21.00	20.94	2
		1	0	21.20	21.23	21.11	2
		1	37	21.19	21.19	21.06	2
		1	74	21.12	21.22	21.08	2
		36	0	20.13	20.12	20.07	3
15M	64QAM	36	19	20.04	20.17	20.05	3
		36	39	20.03	20.08	19.92	3
		75	0	19.96	20.14	19.98	3

LTE Conducted Power (Full)							
LTE Band 66							
BW	MCS Index	Channel		132022	132322	132622	3GPP MPR
		Frequency (MHz)		1715	1745	1775	
10M	QPSK	1	0	22.90	23.02	22.87	0
		1	24	22.82	22.85	22.82	0
		1	49	22.87	22.90	22.82	0
		25	0	21.94	21.90	21.95	1
		25	12	21.95	21.97	21.89	1
		25	25	21.90	21.79	21.75	1
		50	0	21.94	21.99	21.82	1
10M	16QAM	1	0	22.20	22.23	22.04	1
		1	24	22.19	22.22	22.13	1
		1	49	22.14	22.12	22.12	1
		25	0	21.02	21.06	20.95	2
		25	12	21.00	20.97	20.96	2
		25	25	20.92	20.94	20.79	2
		50	0	21.02	21.03	20.86	2
10M	64QAM	1	0	21.08	21.27	21.08	2
		1	24	21.04	21.17	21.12	2
		1	49	21.03	21.19	21.05	2
		25	0	20.07	20.08	20.04	3
		25	12	19.98	20.09	19.91	3
		25	25	20.00	20.08	19.75	3
		50	0	19.95	20.13	19.88	3
BW	MCS Index	Channel		131997	132322	132647	3GPP MPR
		Frequency (MHz)		1712.5	1745	1777.5	
5M	QPSK	1	0	23.03	22.93	22.81	0
		1	12	22.91	22.99	22.97	0
		1	24	22.85	22.87	22.83	0
		12	0	21.90	21.90	21.80	1
		12	6	21.98	21.87	21.77	1
		12	13	21.87	21.95	21.80	1
		25	0	21.87	21.88	21.88	1
5M	16QAM	1	0	22.24	22.24	22.06	1
		1	12	22.05	22.23	22.13	1
		1	24	22.08	22.21	22.09	1
		12	0	20.99	21.02	20.87	2
		12	6	21.00	21.00	20.86	2
		12	13	20.79	20.92	20.78	2
		25	0	20.98	21.03	20.88	2
5M	64QAM	1	0	21.11	21.20	21.17	2
		1	12	21.09	21.17	20.98	2
		1	24	21.13	21.11	20.98	2
		12	0	20.02	20.09	20.04	3
		12	6	20.00	20.00	19.89	3
		12	13	19.82	19.92	19.79	3
		25	0	19.95	20.03	19.88	3

LTE Conducted Power (Full)							
LTE Band 66							
BW	MCS Index	Channel		131987	132322	132657	3GPP MPR
		Frequency (MHz)		1711.5	1745	1778.5	
3M	QPSK	1	0	22.96	22.96	22.88	0
		1	7	22.89	22.84	22.93	0
		1	14	22.75	22.93	22.86	0
		8	0	22.00	21.92	21.91	1
		8	3	21.92	21.89	21.86	1
		8	7	21.88	21.86	21.75	1
		15	0	21.85	22.01	21.77	1
3M	16QAM	1	0	22.13	22.27	22.14	1
		1	7	22.20	22.30	22.08	1
		1	14	22.10	22.12	22.19	1
		8	0	21.03	21.04	20.98	2
		8	3	21.08	21.10	21.03	2
		8	7	20.89	20.98	20.76	2
		15	0	21.03	20.94	20.85	2
3M	64QAM	1	0	21.14	21.15	21.09	2
		1	7	21.10	21.08	21.03	2
		1	14	21.00	21.10	21.01	2
		8	0	20.13	20.02	19.96	3
		8	3	19.99	19.98	19.98	3
		8	7	19.98	20.07	19.82	3
		15	0	19.82	19.92	19.88	3
BW	MCS Index	Channel		131979	132322	132665	3GPP MPR
		Frequency (MHz)		1710.7	1745	1779.3	
1.4M	QPSK	1	0	23.03	22.96	22.89	0
		1	2	22.88	22.90	22.91	0
		1	5	22.82	22.85	22.70	0
		3	0	22.95	22.96	22.93	0
		3	1	22.93	22.94	22.83	0
		3	3	22.79	22.87	22.79	0
		6	0	21.99	21.88	21.91	1
1.4M	16QAM	1	0	22.17	22.15	21.99	1
		1	2	22.20	22.32	22.12	1
		1	5	22.21	22.20	22.05	1
		3	0	22.03	22.03	21.83	1
		3	1	22.04	22.01	21.97	1
		3	3	21.82	21.94	21.87	1
		6	0	20.93	21.03	20.97	2
1.4M	64QAM	1	0	21.20	21.14	21.14	2
		1	2	21.13	21.25	20.94	2
		1	5	21.04	21.05	21.00	2
		3	0	21.16	21.16	20.86	2
		3	1	20.90	20.94	20.90	2
		3	3	20.80	21.06	20.92	2
		6	0	19.91	20.14	19.88	3

LTE Conducted Power (Full)							
LTE Band 71							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		133222	133297	133372	
		Frequency (MHz)		673	680.5	688	
20M	QPSK	1	0	23.06	23.13	23.18	0
		1	50	23.03	23.11	23.15	0
		1	99	22.95	23.02	23.06	0
		50	0	22.13	22.21	22.23	1
		50	25	22.02	22.13	22.21	1
		50	50	22.01	22.08	22.17	1
		100	0	22.09	22.17	22.26	1
20M	16QAM	1	0	22.41	22.45	22.47	1
		1	50	22.36	22.41	22.42	1
		1	99	22.29	22.32	22.35	1
		50	0	21.21	21.25	21.27	2
		50	25	21.15	21.22	21.26	2
		50	50	21.17	21.19	21.21	2
		100	0	21.19	21.21	21.23	2
20M	64QAM	1	0	21.29	21.37	21.38	2
		1	50	21.23	21.26	21.35	2
		1	99	21.21	21.25	21.33	2
		50	0	20.13	20.18	20.23	3
		50	25	20.09	20.12	20.22	3
		50	50	20.07	20.15	20.19	3
		100	0	20.16	20.22	20.25	3
BW	MCS Index	Channel		133197	133297	133397	3GPP MPR
		Frequency (MHz)		670.5	680.5	690.5	
15M	QPSK	1	0	23.04	23.03	23.16	0
		1	37	22.98	23.02	23.13	0
		1	74	22.90	23.01	23.05	0
		36	0	22.05	22.14	22.20	1
		36	19	21.98	22.05	22.15	1
		36	39	21.98	21.98	22.08	1
		75	0	22.00	22.16	22.21	1
15M	16QAM	1	0	22.33	22.39	22.37	1
		1	37	22.31	22.36	22.34	1
		1	74	22.29	22.32	22.27	1
		36	0	21.17	21.25	21.21	2
		36	19	21.11	21.21	21.17	2
		36	39	21.10	21.15	21.17	2
		75	0	21.15	21.11	21.18	2
15M	64QAM	1	0	21.22	21.36	21.31	2
		1	37	21.16	21.16	21.30	2
		1	74	21.20	21.23	21.24	2
		36	0	20.11	20.13	20.15	3
		36	19	20.07	20.12	20.19	3
		36	39	20.00	20.07	20.15	3
		75	0	20.14	20.19	20.19	3

LTE Conducted Power (Full)							
LTE Band 71							
BW	MCS Index	Channel		133172	133297	133422	3GPP MPR
		Frequency (MHz)		668	680.5	693	
10M	QPSK	1	0	22.97	23.00	23.01	0
		1	24	22.96	22.98	22.95	0
		1	49	22.86	23.01	23.02	0
		25	0	22.08	21.97	22.16	1
		25	12	21.95	22.08	22.04	1
		25	25	21.93	21.90	22.08	1
		50	0	21.98	21.99	22.22	1
10M	16QAM	1	0	22.29	22.36	22.26	1
		1	24	22.22	22.32	22.21	1
		1	49	22.24	22.18	22.23	1
		25	0	21.07	21.16	21.16	2
		25	12	20.98	21.13	21.18	2
		25	25	21.08	21.12	21.15	2
		50	0	21.10	21.07	21.10	2
10M	64QAM	1	0	21.08	21.18	21.23	2
		1	24	21.06	21.05	21.24	2
		1	49	21.11	21.12	21.26	2
		25	0	19.96	19.98	20.05	3
		25	12	19.98	20.01	20.04	3
		25	25	19.90	20.08	20.05	3
		50	0	20.05	20.01	20.01	3
BW	MCS Index	Channel		133147	133297	133447	3GPP MPR
		Frequency (MHz)		665.5	680.5	695.5	
5M	QPSK	1	0	22.90	23.01	23.03	0
		1	12	22.92	22.90	22.99	0
		1	24	22.72	23.01	22.86	0
		12	0	22.04	22.10	22.06	1
		12	6	21.93	21.96	22.13	1
		12	13	21.84	21.94	22.12	1
		25	0	21.96	22.13	22.10	1
5M	16QAM	1	0	22.26	22.37	22.36	1
		1	12	22.18	22.31	22.30	1
		1	24	22.26	22.23	22.19	1
		12	0	21.00	21.09	21.09	2
		12	6	21.03	21.12	21.14	2
		12	13	21.13	21.16	21.21	2
		25	0	21.00	20.97	21.22	2
5M	64QAM	1	0	21.28	21.24	21.31	2
		1	12	21.13	21.18	21.25	2
		1	24	21.11	21.11	21.17	2
		12	0	19.94	20.11	20.08	3
		12	6	19.97	20.08	19.99	3
		12	13	19.94	20.02	20.17	3
		25	0	20.01	20.05	20.20	3

LTE Conducted Power (Full)							
LTE Band 106							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel			134322		
		Frequency (MHz)			899		
3M	QPSK	1	0		22.77		0
		1	7		22.62		0
		1	14		22.63		0
		8	0		21.76		1
		8	3		21.70		1
		8	7		21.62		1
3M	16QAM	15	0		21.67		1
		1	0		21.90		1
		1	7		21.72		1
		1	14		21.60		1
		8	0		20.83		2
		8	3		20.68		2
3M	64QAM	8	7		20.65		2
		15	0		20.79		2
		1	0		21.82		2
		1	7		20.64		2
		1	14		20.70		2
		8	0		20.79		3
3M	64QAM	8	3		20.39		3
		8	7		20.26		3
		15	0		20.77		3
BW	MCS Index	Channel		134314	134322	134330	3GPP MPR
		Frequency (MHz)		898.2	899	889.8	
1.4M	QPSK	1	0	22.66	22.68	22.58	0
		1	2	22.56	22.59	22.52	0
		1	5	22.57	22.65	22.49	0
		3	0	22.63	22.65	22.55	0
		3	1	22.55	22.58	22.45	0
		3	3	22.56	22.62	22.49	0
1.4M	16QAM	6	0	21.53	21.59	21.49	1
		1	0	21.59	21.59	21.50	1
		1	2	21.59	21.66	21.51	1
		1	5	21.61	21.59	21.52	1
		3	0	21.60	21.59	21.54	1
		3	1	21.56	21.58	21.52	1
1.4M	64QAM	3	3	21.59	21.61	21.54	1
		6	0	20.55	20.59	20.49	2
		1	0	20.54	20.63	20.54	2
		1	2	20.53	20.58	20.50	2
		1	5	20.57	20.59	20.54	2
		3	0	20.58	20.61	20.54	2
1.4M	64QAM	3	1	20.57	20.58	20.49	2
		3	3	20.59	20.66	20.50	2
		6	0	19.57	19.60	19.48	3

WCDMA Conducted Power (Reduction)									
Band	WCDMA II			WCDMA IV			WCDMA V		
TX Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233
Rx Channel	9662	9800	9938	1537	1638	1738	4357	4407	4458
Frequency	1852.4	1880	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6
RMC 12.2K	17.47	17.45	17.46	17.48	17.47	17.43	18.88	18.93	18.85
HSDPA Subtest-1	15.83	15.78	15.81	16.46	16.45	16.41	17.62	17.65	17.59
HSDPA Subtest-2	15.86	15.75	15.77	16.47	16.43	16.39	17.52	17.59	17.51
HSDPA Subtest-3	15.35	15.27	15.29	15.99	15.98	15.83	17.08	17.16	17.07
HSDPA Subtest-4	15.38	15.32	15.33	15.96	15.91	15.76	17.02	17.13	17.01
DC-HSDPA Subtest-1	15.68	15.61	15.66	16.33	16.29	16.28	17.47	17.48	17.42
DC-HSDPA Subtest-2	15.62	15.52	15.55	16.35	16.29	16.15	17.42	17.51	17.39
DC-HSDPA Subtest-3	15.15	15.02	15.07	15.88	15.87	15.65	16.85	16.98	16.82
DC-HSDPA Subtest-4	15.31	15.08	15.06	15.83	15.78	15.51	16.95	17.02	16.83
HSUPA Subtest-1	15.83	15.73	15.75	16.49	16.42	16.31	17.58	17.63	17.56
HSUPA Subtest-2	13.81	13.75	13.78	14.43	14.36	14.25	15.52	15.55	15.51
HSUPA Subtest-3	14.82	14.81	14.67	15.48	15.21	15.21	16.46	16.53	16.43
HSUPA Subtest-4	13.79	13.77	13.75	14.38	14.35	14.29	15.62	15.63	15.58
HSUPA Subtest-5	15.76	15.72	15.73	16.41	16.33	16.31	17.59	17.61	17.53

LTE Conducted Power (Reduction)							
LTE Band 2							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		18700	18900	19100	
		Frequency (MHz)		1860	1880	1900	
20M	QPSK	1	0	17.35	17.38	17.31	0
		1	50	17.28	17.37	17.26	0
		1	99	17.27	17.33	17.25	0
		50	0	17.33	17.36	17.31	0
		50	25	17.31	17.33	17.26	0
		50	50	17.28	17.31	17.25	0
		100	0	17.25	17.32	17.21	0
20M	16QAM	1	0	17.34	17.37	17.28	0
		1	50	17.34	17.35	17.27	0
		1	99	17.27	17.33	17.17	0
		50	0	17.30	17.36	17.30	0
		50	25	17.23	17.32	17.19	0
		50	50	17.27	17.31	17.20	0
		100	0	17.24	17.32	17.15	0
20M	64QAM	1	0	17.35	17.35	17.31	0
		1	50	17.27	17.31	17.20	0
		1	99	17.26	17.28	17.18	0
		50	0	17.31	17.32	17.31	0
		50	25	17.17	17.26	17.14	0
		50	50	17.18	17.25	17.11	0
		100	0	17.25	17.29	17.18	0
BW	MCS Index	Channel		18675	18900	19125	3GPP MPR
		Frequency (MHz)		1857.5	1880	1902.5	
15M	QPSK	1	0	17.25	17.37	17.22	0
		1	37	17.21	17.28	17.17	0
		1	74	17.17	17.30	17.19	0
		36	0	17.32	17.31	17.29	0
		36	19	17.24	17.32	17.20	0
		36	39	17.22	17.30	17.15	0
		75	0	17.15	17.27	17.19	0
15M	16QAM	1	0	17.28	17.31	17.20	0
		1	37	17.27	17.34	17.18	0
		1	74	17.24	17.23	17.10	0
		36	0	17.22	17.36	17.22	0
		36	19	17.13	17.29	17.16	0
		36	39	17.26	17.23	17.14	0
		75	0	17.16	17.24	17.08	0
15M	64QAM	1	0	17.25	17.27	17.29	0
		1	37	17.18	17.29	17.11	0
		1	74	17.16	17.19	17.10	0
		36	0	17.26	17.29	17.21	0
		36	19	17.14	17.16	17.04	0
		36	39	17.17	17.19	17.11	0
		75	0	17.15	17.20	17.13	0
BW	MCS Index	Channel		18650	18900	19150	3GPP MPR
		Frequency (MHz)		1855	1880	1905	
10M	QPSK	1	0	17.18	17.29	17.17	0
		1	24	17.25	17.22	17.21	0
		1	49	17.11	17.16	17.06	0
		25	0	17.19	17.25	17.13	0
		25	12	17.18	17.18	17.22	0
		25	25	17.08	17.28	17.02	0
		50	0	17.09	17.09	17.09	0
10M	16QAM	1	0	17.25	17.27	17.24	0
		1	24	17.19	17.15	17.20	0
		1	49	17.26	17.21	17.12	0
		25	0	17.25	17.18	17.19	0
		25	12	17.06	17.28	17.14	0
		25	25	17.20	17.16	17.07	0
		50	0	17.19	17.21	17.02	0
10M	64QAM	1	0	17.28	17.20	17.19	0
		1	24	17.12	17.26	17.00	0
		1	49	17.10	17.13	16.99	0
		25	0	17.13	17.11	17.09	0
		25	12	17.07	17.15	17.06	0
		25	25	17.04	17.15	16.91	0
		50	0	17.19	17.22	17.11	0

LTE Conducted Power (Reduction)							
LTE Band 2							
BW	MCS Index	Channel		18625	18900	19175	3GPP MPR
		Frequency (MHz)		1852.5	1880	1907.5	
5M	QPSK	1	0	17.12	17.33	17.09	0
		1	12	17.17	17.17	17.12	0
		1	24	17.20	17.25	16.97	0
		12	0	17.18	17.31	17.10	0
		12	6	17.09	17.21	17.09	0
		12	13	17.05	17.20	16.96	0
		25	0	17.20	17.16	17.03	0
5M	16QAM	1	0	17.19	17.33	17.24	0
		1	12	17.22	17.30	17.11	0
		1	24	17.26	17.19	17.05	0
		12	0	17.14	17.27	17.13	0
		12	6	17.13	17.24	17.13	0
		12	13	17.19	17.12	16.98	0
		25	0	17.12	17.15	17.02	0
5M	64QAM	1	0	17.30	17.24	17.17	0
		1	12	17.08	17.21	16.98	0
		1	24	17.09	17.13	17.03	0
		12	0	17.16	17.19	17.09	0
		12	6	17.03	17.14	17.05	0
		12	13	17.02	17.03	16.90	0
		25	0	17.06	17.22	17.06	0
BW	MCS Index	Channel		18615	18900	19185	3GPP MPR
		Frequency (MHz)		1851.5	1880	1908.5	
3M	QPSK	1	0	17.25	17.25	17.12	0
		1	7	17.16	17.18	17.15	0
		1	14	17.23	17.13	17.17	0
		8	0	17.20	17.18	17.11	0
		8	3	17.06	17.14	17.15	0
		8	7	17.10	17.25	17.16	0
		15	0	17.13	17.19	17.15	0
3M	16QAM	1	0	17.19	17.30	17.13	0
		1	7	17.25	17.15	17.12	0
		1	14	17.18	17.26	17.16	0
		8	0	17.17	17.29	17.10	0
		8	3	17.04	17.15	17.18	0
		8	7	17.24	17.17	17.07	0
		15	0	17.14	17.14	17.01	0
3M	64QAM	1	0	17.28	17.16	17.19	0
		1	7	17.05	17.25	17.07	0
		1	14	17.23	17.05	17.02	0
		8	0	17.21	17.16	17.07	0
		8	3	17.09	17.13	17.01	0
		8	7	17.02	17.17	16.91	0
		15	0	17.08	17.14	17.03	0
BW	MCS Index	Channel		18607	18900	19193	3GPP MPR
		Frequency (MHz)		1850.7	1880	1909.3	
1.4M	QPSK	1	0	17.21	17.32	17.16	0
		1	2	17.13	17.21	17.12	0
		1	5	17.18	17.19	17.15	0
		3	0	17.26	17.25	17.11	0
		3	1	17.19	17.25	17.12	0
		3	3	17.16	17.21	17.07	0
		6	0	17.18	17.11	17.14	0
1.4M	16QAM	1	0	17.22	17.30	17.17	0
		1	2	17.26	17.28	17.09	0
		1	5	17.15	17.29	17.02	0
		3	0	17.20	17.22	17.14	0
		3	1	17.09	17.27	17.11	0
		3	3	17.15	17.09	16.98	0
		6	0	17.10	17.19	16.92	0
1.4M	64QAM	1	0	17.22	17.25	17.20	0
		1	2	17.12	17.27	16.99	0
		1	5	17.12	17.20	17.02	0
		3	0	17.23	17.19	17.07	0
		3	1	17.06	17.19	16.97	0
		3	3	17.01	17.15	17.04	0
		6	0	17.16	17.19	16.98	0

LTE Conducted Power (Reduction)							
LTE Band 4							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20050	20175	20300	
		Frequency (MHz)		1720	1732.5	1745	
20M	QPSK	1	0	17.39	17.46	17.41	0
		1	50	17.35	17.43	17.39	0
		1	99	17.32	17.38	17.38	0
		50	0	17.31	17.41	17.37	0
		50	25	17.29	17.39	17.33	0
		50	50	17.23	17.37	17.28	0
		100	0	17.31	17.38	17.35	0
20M	16QAM	1	0	17.33	17.45	17.35	0
		1	50	17.28	17.43	17.36	0
		1	99	17.31	17.42	17.32	0
		50	0	17.32	17.43	17.36	0
		50	25	17.37	17.41	17.41	0
		50	50	17.26	17.38	17.36	0
		100	0	17.31	17.39	17.39	0
20M	64QAM	1	0	17.36	17.42	17.37	0
		1	50	17.37	17.41	17.40	0
		1	99	17.22	17.39	17.30	0
		50	0	17.31	17.36	17.36	0
		50	25	17.30	17.37	17.34	0
		50	50	17.27	17.35	17.31	0
		100	0	17.32	17.39	17.38	0
BW	MCS Index	Channel		20025	20175	20325	3GPP MPR
		Frequency (MHz)		1717.5	1732.5	1747.5	
15M	QPSK	1	0	17.37	17.45	17.34	0
		1	37	17.29	17.35	17.35	0
		1	74	17.22	17.36	17.36	0
		36	0	17.25	17.32	17.34	0
		36	19	17.25	17.37	17.25	0
		36	39	17.20	17.34	17.25	0
		75	0	17.29	17.32	17.31	0
15M	16QAM	1	0	17.33	17.37	17.30	0
		1	37	17.24	17.35	17.35	0
		1	74	17.24	17.42	17.22	0
		36	0	17.30	17.37	17.29	0
		36	19	17.32	17.34	17.37	0
		36	39	17.19	17.28	17.33	0
		75	0	17.23	17.31	17.32	0
15M	64QAM	1	0	17.32	17.35	17.28	0
		1	37	17.34	17.41	17.37	0
		1	74	17.16	17.33	17.28	0
		36	0	17.24	17.27	17.28	0
		36	19	17.26	17.31	17.33	0
		36	39	17.18	17.26	17.29	0
		75	0	17.28	17.39	17.28	0
BW	MCS Index	Channel		20000	20175	20350	3GPP MPR
		Frequency (MHz)		1715	1732.5	1750	
10M	QPSK	1	0	17.25	17.30	17.19	0
		1	24	17.28	17.21	17.27	0
		1	49	17.17	17.22	17.30	0
		25	0	17.16	17.31	17.20	0
		25	12	17.21	17.33	17.16	0
		25	25	17.13	17.22	17.10	0
		50	0	17.15	17.18	17.16	0
10M	16QAM	1	0	17.30	17.35	17.16	0
		1	24	17.12	17.25	17.35	0
		1	49	17.19	17.27	17.20	0
		25	0	17.20	17.27	17.22	0
		25	12	17.29	17.27	17.34	0
		25	25	17.14	17.15	17.31	0
		50	0	17.23	17.31	17.20	0
10M	64QAM	1	0	17.18	17.34	17.27	0
		1	24	17.32	17.30	17.30	0
		1	49	17.08	17.19	17.26	0
		25	0	17.17	17.20	17.13	0
		25	12	17.11	17.31	17.32	0
		25	25	17.05	17.17	17.14	0
		50	0	17.17	17.39	17.25	0

LTE Conducted Power (Reduction)							
LTE Band 4							
BW	MCS Index	Channel		19975	20175	20375	3GPP MPR
		Frequency (MHz)		1712.5	1732.5	1752.5	
5M	QPSK	1	0	17.23	17.32	17.06	0
		1	12	17.26	17.35	17.26	0
		1	24	17.19	17.22	17.28	0
		12	0	17.25	17.30	17.08	0
		12	6	17.12	17.31	17.09	0
		12	13	17.11	17.19	17.03	0
		25	0	17.15	17.27	17.09	0
5M	16QAM	1	0	17.18	17.33	17.25	0
		1	12	17.10	17.22	17.21	0
		1	24	17.12	17.40	17.17	0
		12	0	17.25	17.28	17.19	0
		12	6	17.31	17.20	17.27	0
		12	13	17.16	17.14	17.30	0
		25	0	17.17	17.16	17.26	0
5M	64QAM	1	0	17.18	17.29	17.20	0
		1	12	17.25	17.31	17.35	0
		1	24	17.15	17.25	17.26	0
		12	0	17.20	17.15	17.13	0
		12	6	17.16	17.25	17.24	0
		12	13	17.12	17.12	17.25	0
		25	0	17.18	17.24	17.21	0
BW	MCS Index	Channel		19965	20175	20385	3GPP MPR
		Frequency (MHz)		1711.5	1732.5	1753.5	
3M	QPSK	1	0	17.28	17.40	17.27	0
		1	7	17.23	17.32	17.27	0
		1	14	17.12	17.25	17.35	0
		8	0	17.13	17.36	17.34	0
		8	3	17.18	17.28	17.23	0
		8	7	17.13	17.23	17.20	0
		15	0	17.24	17.32	17.23	0
3M	16QAM	1	0	17.24	17.27	17.28	0
		1	7	17.15	17.25	17.23	0
		1	14	17.10	17.32	17.07	0
		8	0	17.20	17.34	17.25	0
		8	3	17.26	17.26	17.32	0
		8	7	17.17	17.21	17.18	0
		15	0	17.17	17.23	17.17	0
3M	64QAM	1	0	17.21	17.26	17.28	0
		1	7	17.20	17.39	17.32	0
		1	14	17.12	17.25	17.18	0
		8	0	17.24	17.27	17.20	0
		8	3	17.24	17.27	17.29	0
		8	7	17.05	17.19	17.27	0
		15	0	17.13	17.28	17.19	0
BW	MCS Index	Channel		19957	20175	20393	3GPP MPR
		Frequency (MHz)		1710.7	1732.5	1754.3	
1.4M	QPSK	1	0	17.27	17.38	17.33	0
		1	2	17.21	17.27	17.21	0
		1	5	17.13	17.22	17.27	0
		3	0	17.12	17.31	17.23	0
		3	1	17.12	17.32	17.19	0
		3	3	17.19	17.27	17.21	0
		6	0	17.28	17.21	17.21	0
1.4M	16QAM	1	0	17.21	17.31	17.30	0
		1	2	17.24	17.31	17.25	0
		1	5	17.13	17.28	17.13	0
		3	0	17.26	17.25	17.27	0
		3	1	17.23	17.26	17.31	0
		3	3	17.17	17.13	17.29	0
		6	0	17.15	17.28	17.19	0
1.4M	64QAM	1	0	17.21	17.30	17.26	0
		1	2	17.28	17.30	17.32	0
		1	5	17.16	17.27	17.16	0
		3	0	17.19	17.15	17.26	0
		3	1	17.25	17.29	17.32	0
		3	3	17.10	17.16	17.25	0
		6	0	17.28	17.35	17.17	0

LTE Conducted Power (Reduction)							
LTE Band 5							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20450	20525	20600	
		Frequency (MHz)		829	836.5	844	
10M	QPSK	1	0	19.41	19.46	19.48	0
		1	24	19.39	19.45	19.47	0
		1	49	19.31	19.38	19.39	0
		25	0	19.33	19.41	19.46	0
		25	12	19.32	19.33	19.42	0
		25	25	19.31	19.36	19.41	0
		50	0	19.28	19.38	19.45	0
10M	16QAM	1	0	19.27	19.36	19.41	0
		1	24	19.27	19.32	19.37	0
		1	49	19.22	19.22	19.32	0
		25	0	19.32	19.37	19.39	0
		25	12	19.31	19.33	19.37	0
		25	25	19.30	19.30	19.36	0
		50	0	19.24	19.30	19.38	0
10M	64QAM	1	0	19.29	19.37	19.39	0
		1	24	19.22	19.25	19.31	0
		1	49	19.16	19.16	19.25	0
		25	0	19.29	19.37	19.37	0
		25	12	19.18	19.24	19.29	0
		25	25	19.22	19.31	19.33	0
		50	0	19.26	19.29	19.36	0
BW	MCS Index	Channel		20425	20525	20625	3GPP MPR
		Frequency (MHz)		826.5	836.5	846.5	
5M	QPSK	1	0	19.36	19.38	19.41	0
		1	12	19.37	19.40	19.37	0
		1	24	19.21	19.31	19.31	0
		12	0	19.23	19.36	19.45	0
		12	6	19.28	19.25	19.37	0
		12	13	19.31	19.35	19.35	0
		25	0	19.24	19.30	19.38	0
5M	16QAM	1	0	19.26	19.29	19.35	0
		1	12	19.18	19.28	19.27	0
		1	24	19.18	19.22	19.27	0
		12	0	19.25	19.32	19.32	0
		12	6	19.28	19.25	19.27	0
		12	13	19.20	19.22	19.27	0
		25	0	19.14	19.20	19.37	0
5M	64QAM	1	0	19.19	19.27	19.35	0
		1	12	19.16	19.18	19.28	0
		1	24	19.10	19.08	19.23	0
		12	0	19.26	19.34	19.37	0
		12	6	19.14	19.18	19.27	0
		12	13	19.15	19.31	19.25	0
		25	0	19.21	19.19	19.28	0
BW	MCS Index	Channel		20415	20525	20635	3GPP MPR
		Frequency (MHz)		825.5	836.5	847.5	
3M	QPSK	1	0	19.25	19.26	19.28	0
		1	7	19.19	19.22	19.37	0
		1	14	19.13	19.32	19.28	0
		8	0	19.26	19.31	19.28	0
		8	3	19.23	19.22	19.29	0
		8	7	19.14	19.27	19.29	0
		15	0	19.15	19.18	19.29	0
3M	16QAM	1	0	19.12	19.21	19.27	0
		1	7	19.22	19.17	19.19	0
		1	14	19.06	19.08	19.18	0
		8	0	19.19	19.14	19.27	0
		8	3	19.20	19.19	19.15	0
		8	7	19.14	19.22	19.31	0
		15	0	19.04	19.18	19.27	0
3M	64QAM	1	0	19.15	19.31	19.30	0
		1	7	19.12	19.05	19.09	0
		1	14	19.16	19.04	19.08	0
		8	0	19.14	19.34	19.28	0
		8	3	19.10	19.05	19.10	0
		8	7	19.08	19.15	19.23	0
		15	0	19.17	19.08	19.19	0

LTE Conducted Power (Reduction)							
LTE Band 5							
BW	MCS Index	Channel		20407	20525	20643	3GPP MPR
		Frequency (MHz)		824.7	836.5	848.3	
1.4M	QPSK	1	0	19.40	19.34	19.22	0
		1	2	19.23	19.29	19.28	0
		1	5	19.17	19.37	19.13	0
		3	0	19.33	19.29	19.28	0
		3	1	19.11	19.17	19.17	0
		3	3	19.14	19.24	19.25	0
		6	0	19.15	19.24	19.20	0
1.4M	16QAM	1	0	19.19	19.28	19.26	0
		1	2	19.18	19.18	19.27	0
		1	5	19.10	19.15	19.12	0
		3	0	19.30	19.23	19.29	0
		3	1	19.16	19.19	19.24	0
		3	3	19.17	19.21	19.29	0
		6	0	19.06	19.21	19.23	0
1.4M	64QAM	1	0	19.24	19.26	19.21	0
		1	2	19.16	19.10	19.20	0
		1	5	19.01	19.04	19.12	0
		3	0	19.22	19.33	19.34	0
		3	1	19.07	19.13	19.10	0
		3	3	19.01	19.07	19.24	0
		6	0	19.08	19.06	19.17	0

LTE Conducted Power (Reduction)							
LTE Band 7							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		20850	21100	21350	
		Frequency (MHz)		2510	2535	2560	
20M	QPSK	1	0	16.76	16.78	16.85	0
		1	50	16.71	16.76	16.83	0
		1	99	16.67	16.72	16.81	0
		50	0	16.73	16.81	16.82	0
		50	25	16.69	16.77	16.78	0
		50	50	16.67	16.69	16.76	0
		100	0	16.69	16.79	16.83	0
20M	16QAM	1	0	16.74	16.78	16.82	0
		1	50	16.70	16.73	16.81	0
		1	99	16.71	16.77	16.79	0
		50	0	16.68	16.72	16.72	0
		50	25	16.64	16.66	16.71	0
		50	50	16.51	16.59	16.66	0
		100	0	16.64	16.68	16.78	0
20M	64QAM	1	0	16.55	16.65	16.75	0
		1	50	16.60	16.69	16.73	0
		1	99	16.62	16.69	16.72	0
		50	0	16.53	16.62	16.68	0
		50	25	16.55	16.65	16.67	0
		50	50	16.52	16.61	16.66	0
		100	0	16.73	16.75	16.76	0
BW	MCS Index	Channel		20825	21100	21375	3GPP MPR
		Frequency (MHz)		2507.5	2535	2562.5	
15M	QPSK	1	0	16.76	16.69	16.83	0
		1	37	16.63	16.69	16.74	0
		1	74	16.57	16.63	16.77	0
		36	0	16.67	16.80	16.80	0
		36	19	16.69	16.67	16.78	0
		36	39	16.63	16.59	16.68	0
		75	0	16.69	16.73	16.81	0
15M	16QAM	1	0	16.72	16.77	16.75	0
		1	37	16.67	16.66	16.73	0
		1	74	16.61	16.77	16.76	0
		36	0	16.62	16.69	16.62	0
		36	19	16.61	16.63	16.63	0
		36	39	16.41	16.49	16.63	0
		75	0	16.54	16.68	16.73	0
15M	64QAM	1	0	16.54	16.64	16.66	0
		1	37	16.53	16.64	16.67	0
		1	74	16.56	16.62	16.69	0
		36	0	16.44	16.59	16.58	0
		36	19	16.50	16.55	16.65	0
		36	39	16.45	16.53	16.66	0
		75	0	16.66	16.69	16.69	0
BW	MCS Index	Channel		20800	21100	21400	3GPP MPR
		Frequency (MHz)		2505	2535	2565	
10M	QPSK	1	0	16.63	16.58	16.75	0
		1	24	16.54	16.68	16.73	0
		1	49	16.47	16.54	16.67	0
		25	0	16.55	16.65	16.65	0
		25	12	16.69	16.58	16.71	0
		25	25	16.48	16.56	16.67	0
		50	0	16.65	16.59	16.79	0
10M	16QAM	1	0	16.72	16.67	16.60	0
		1	24	16.55	16.51	16.60	0
		1	49	16.48	16.75	16.64	0
		25	0	16.60	16.57	16.50	0
		25	12	16.48	16.56	16.55	0
		25	25	16.32	16.35	16.52	0
		50	0	16.43	16.53	16.68	0
10M	64QAM	1	0	16.40	16.53	16.66	0
		1	24	16.43	16.56	16.59	0
		1	49	16.46	16.56	16.56	0
		25	0	16.29	16.44	16.45	0
		25	12	16.37	16.52	16.52	0
		25	25	16.43	16.38	16.59	0
		50	0	16.59	16.67	16.61	0

LTE Conducted Power (Reduction)							
LTE Band 7							
BW	MCS Index	Channel		20775	21100	21425	3GPP MPR
		Frequency (MHz)		2502.5	2535	2567.5	
5M	QPSK	1	0	16.72	16.59	16.62	0
		1	12	16.50	16.66	16.66	0
		1	24	16.42	16.56	16.58	0
		12	0	16.52	16.68	16.58	0
		12	6	16.58	16.59	16.66	0
		12	13	16.56	16.44	16.53	0
		25	0	16.69	16.64	16.77	0
5M	16QAM	1	0	16.68	16.66	16.67	0
		1	12	16.66	16.59	16.66	0
		1	24	16.47	16.64	16.75	0
		12	0	16.58	16.69	16.47	0
		12	6	16.54	16.55	16.61	0
		12	13	16.31	16.37	16.56	0
		25	0	16.40	16.53	16.62	0
5M	64QAM	1	0	16.40	16.63	16.57	0
		1	12	16.44	16.58	16.61	0
		1	24	16.52	16.62	16.66	0
		12	0	16.38	16.46	16.48	0
		12	6	16.41	16.44	16.63	0
		12	13	16.40	16.42	16.60	0
		25	0	16.57	16.56	16.69	0

LTE Conducted Power (Reduction)							
LTE Band 12							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		23060	23095	23130	
		Frequency (MHz)		704	707.5	711	
10M	QPSK	1	0	22.69	22.78	22.92	0
		1	24	22.66	22.76	22.83	0
		1	49	22.55	22.63	22.65	0
		25	0	22.73	22.79	22.89	0
		25	12	22.72	22.76	22.85	0
		25	25	22.71	22.78	22.81	0
		50	0	22.68	22.76	22.83	0
10M	16QAM	1	0	22.77	22.85	22.91	0
		1	24	22.72	22.76	22.81	0
		1	49	22.68	22.73	22.78	0
		25	0	21.87	21.87	21.89	0
		25	12	21.78	21.87	21.88	0
		25	25	21.68	21.78	21.85	0
		50	0	21.74	21.84	21.86	0
10M	64QAM	1	0	21.96	21.96	21.97	0
		1	24	21.78	21.88	21.95	0
		1	49	21.81	21.82	21.91	0
		25	0	21.07	21.09	21.11	0
		25	12	21.05	21.07	21.08	0
		25	25	21.02	21.06	21.06	0
		50	0	21.03	21.05	21.13	0
BW	MCS Index	Channel		23035	23095	23155	3GPP MPR
		Frequency (MHz)		701.5	707.5	713.5	
5M	QPSK	1	0	22.62	22.68	22.84	0
		1	12	22.60	22.71	22.74	0
		1	24	22.51	22.57	22.55	0
		12	0	22.63	22.69	22.80	0
		12	6	22.65	22.75	22.76	0
		12	13	22.70	22.70	22.76	0
		25	0	22.60	22.75	22.75	0
5M	16QAM	1	0	22.70	22.82	22.88	0
		1	12	22.66	22.69	22.80	0
		1	24	22.62	22.70	22.70	0
		12	0	21.84	21.84	21.80	0
		12	6	21.77	21.85	21.87	0
		12	13	21.59	21.70	21.83	0
		25	0	21.69	21.77	21.78	0
5M	64QAM	1	0	21.91	21.96	21.87	0
		1	12	21.71	21.81	21.86	0
		1	24	21.76	21.77	21.84	0
		12	0	21.06	21.03	21.05	0
		12	6	21.05	21.02	21.06	0
		12	13	21.03	21.02	21.01	0
		25	0	21.02	21.05	21.05	0
BW	MCS Index	Channel		23025	23095	23165	3GPP MPR
		Frequency (MHz)		700.5	707.5	714.5	
3M	QPSK	1	0	22.67	22.70	22.87	0
		1	7	22.65	22.69	22.73	0
		1	14	22.38	22.46	22.45	0
		8	0	22.55	22.68	22.86	0
		8	3	22.60	22.75	22.72	0
		8	7	22.59	22.62	22.64	0
		15	0	22.64	22.60	22.58	0
3M	16QAM	1	0	22.66	22.70	22.89	0
		1	7	22.56	22.65	22.67	0
		1	14	22.50	22.62	22.56	0
		8	0	21.71	21.82	21.70	0
		8	3	21.72	21.75	21.74	0
		8	7	21.55	21.59	21.78	0
		15	0	21.61	21.66	21.69	0
3M	64QAM	1	0	21.93	21.85	21.95	0
		1	7	21.67	21.78	21.80	0
		1	14	21.65	21.69	21.78	0
		8	0	21.09	21.05	21.01	0
		8	3	21.07	21.02	21.03	0
		8	7	21.05	21.07	21.01	0
		15	0	21.06	21.08	21.04	0

LTE Conducted Power (Reduction)							
LTE Band 12							
BW	MCS Index	Channel		23017	23095	23173	3GPP MPR
		Frequency (MHz)		699.7	707.5	715.3	
1.4M	QPSK	1	0	22.58	22.64	22.75	0
		1	2	22.64	22.61	22.66	0
		1	5	22.35	22.44	22.30	0
		3	0	22.57	22.58	22.78	0
		3	1	22.63	22.73	22.68	0
		3	3	22.60	22.76	22.59	0
		6	0	22.59	22.54	22.46	0
1.4M	16QAM	1	0	22.59	22.75	22.82	0
		1	2	22.61	22.74	22.80	0
		1	5	22.56	22.60	22.59	0
		3	0	21.74	21.82	21.80	0
		3	1	21.67	21.83	21.80	0
		3	3	21.53	21.54	21.76	0
		6	0	21.71	21.74	21.76	0
1.4M	64QAM	1	0	21.91	21.87	21.85	0
		1	2	21.65	21.81	21.83	0
		1	5	21.64	21.65	21.88	0
		3	0	21.11	21.07	21.06	0
		3	1	21.12	21.05	21.05	0
		3	3	21.07	21.06	21.03	0
		6	0	21.05	21.08	21.02	0

LTE Conducted Power (Reduction)							
LTE Band 13							
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)
		Channel			23230		
		Frequency (MHz)			782		
10M	QPSK	1	0		20.77		0
		1	24		20.75		0
		1	49		20.68		0
		25	0		20.76		0
		25	12		20.72		0
		25	25		20.71		0
		50	0		20.73		0
10M	16QAM	1	0		20.75		0
		1	24		20.73		0
		1	49		20.66		0
		25	0		20.71		0
		25	12		20.69		0
		25	25		20.63		0
		50	0		20.73		0
10M	64QAM	1	0		20.67		0
		1	24		20.65		0
		1	49		20.62		0
		25	0		20.66		0
		25	12		20.65		0
		25	25		20.62		0
		50	0		20.63		0
BW	MCS Index	Channel		23205	23230	23255	3GPP MPR
		Frequency (MHz)		779.5	782	784.5	
5M	QPSK	1	0	20.67	20.72	20.65	0
		1	12	20.66	20.71	20.62	0
		1	24	20.65	20.66	20.61	0
		12	0	20.63	20.67	20.61	0
		12	6	20.61	20.62	20.58	0
		12	13	20.58	20.63	20.57	0
		25	0	20.65	20.70	20.64	0
5M	16QAM	1	0	20.61	20.70	20.61	0
		1	12	20.60	20.68	20.57	0
		1	24	20.64	20.66	20.61	0
		12	0	20.59	20.63	20.53	0
		12	6	20.65	20.68	20.56	0
		12	13	20.48	20.55	20.48	0
		25	0	20.63	20.71	20.60	0
5M	64QAM	1	0	20.53	20.61	20.45	0
		1	12	20.59	20.62	20.58	0
		1	24	20.56	20.56	20.47	0
		12	0	20.58	20.63	20.50	0
		12	6	20.47	20.55	20.39	0
		12	13	20.45	20.55	20.41	0
		25	0	20.51	20.59	20.47	0

LTE Conducted Power (Reduction)							
LTE Band 14							
BW	MCS Index	RB Size	RB Offset		Mid		3GPP MPR (dB)
		Channel			23330		
		Frequency (MHz)			793		
10M	QPSK	1	0		20.87		0
		1	24		20.85		0
		1	49		20.82		0
		25	0		20.79		0
		25	12		20.77		0
		25	25		20.76		0
		50	0		20.78		0
10M	16QAM	1	0		20.86		0
		1	24		20.82		0
		1	49		20.81		0
		25	0		20.79		0
		25	12		20.68		0
		25	25		20.73		0
		50	0		20.75		0
10M	64QAM	1	0		20.79		0
		1	24		20.78		0
		1	49		20.76		0
		25	0		20.77		0
		25	12		20.76		0
		25	25		20.66		0
		50	0		20.75		0
BW	MCS Index	Channel		23305	23330	23355	3GPP MPR
		Frequency (MHz)		790.5	793	795.5	
5M	QPSK	1	0	20.77	20.79	20.68	0
		1	12	20.76	20.78	20.65	0
		1	24	20.71	20.75	20.63	0
		12	0	20.66	20.73	20.65	0
		12	6	20.65	20.72	20.61	0
		12	13	20.63	20.71	20.59	0
		25	0	20.68	20.75	20.62	0
5M	16QAM	1	0	20.73	20.78	20.73	0
		1	12	20.70	20.74	20.70	0
		1	24	20.70	20.79	20.64	0
		12	0	20.71	20.76	20.70	0
		12	6	20.59	20.61	20.52	0
		12	13	20.70	20.71	20.64	0
		25	0	20.64	20.68	20.60	0
5M	64QAM	1	0	20.68	20.77	20.64	0
		1	12	20.68	20.71	20.63	0
		1	24	20.64	20.67	20.64	0
		12	0	20.66	20.75	20.59	0
		12	6	20.72	20.76	20.68	0
		12	13	20.47	20.56	20.42	0
		25	0	20.63	20.71	20.56	0

LTE Conducted Power (Reduction)							
LTE Band 25							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		26140	26365	26590	
		Frequency (MHz)		1860	1882.5	1905	
20M	QPSK	1	0	17.41	17.38	17.37	0
		1	50	17.38	17.28	17.26	0
		1	99	17.36	17.27	17.25	0
		50	0	17.33	17.32	17.31	0
		50	25	17.32	17.29	17.21	0
		50	50	17.31	17.25	17.18	0
		100	0	17.35	17.31	17.23	0
20M	16QAM	1	0	17.38	17.30	17.20	0
		1	50	17.33	17.29	17.26	0
		1	99	17.32	17.27	17.25	0
		50	0	17.33	17.26	17.18	0
		50	25	17.31	17.28	17.25	0
		50	50	17.28	17.23	17.18	0
		100	0	17.32	17.22	17.17	0
20M	64QAM	1	0	17.37	17.32	17.31	0
		1	50	17.35	17.26	17.23	0
		1	99	17.26	17.16	17.13	0
		50	0	17.29	17.23	17.18	0
		50	25	17.25	17.15	17.12	0
		50	50	17.23	17.12	17.11	0
		100	0	17.31	17.23	17.15	0
BW	MCS Index	Channel		26115	26365	26615	3GPP MPR
		Frequency (MHz)		1857.5	1882.5	1907.5	
15M	QPSK	1	0	17.32	17.31	17.30	0
		1	37	17.35	17.22	17.23	0
		1	74	17.33	17.22	17.16	0
		36	0	17.29	17.31	17.31	0
		36	19	17.28	17.22	17.12	0
		36	39	17.29	17.25	17.08	0
		75	0	17.28	17.23	17.15	0
15M	16QAM	1	0	17.32	17.28	17.20	0
		1	37	17.29	17.19	17.23	0
		1	74	17.24	17.22	17.22	0
		36	0	17.28	17.16	17.16	0
		36	19	17.31	17.26	17.22	0
		36	39	17.24	17.22	17.13	0
		75	0	17.26	17.12	17.17	0
15M	64QAM	1	0	17.30	17.22	17.29	0
		1	37	17.33	17.16	17.21	0
		1	74	17.20	17.13	17.12	0
		36	0	17.20	17.23	17.13	0
		36	19	17.19	17.07	17.03	0
		36	39	17.14	17.07	17.01	0
		75	0	17.29	17.21	17.06	0
BW	MCS Index	Channel		26090	26365	26640	3GPP MPR
		Frequency (MHz)		1855	1882.5	1910	
10M	QPSK	1	0	17.26	17.30	17.22	0
		1	24	17.21	17.20	17.08	0
		1	49	17.24	17.17	17.15	0
		25	0	17.23	17.21	17.19	0
		25	12	17.20	17.21	17.12	0
		25	25	17.26	17.25	17.06	0
		50	0	17.27	17.18	17.02	0
10M	16QAM	1	0	17.17	17.14	17.18	0
		1	24	17.15	17.15	17.10	0
		1	49	17.21	17.10	17.21	0
		25	0	17.16	17.08	17.13	0
		25	12	17.26	17.11	17.17	0
		25	25	17.18	17.07	17.10	0
		50	0	17.23	17.06	17.02	0
10M	64QAM	1	0	17.22	17.17	17.21	0
		1	24	17.18	17.11	17.17	0
		1	49	17.10	17.02	17.01	0
		25	0	17.13	17.21	17.04	0
		25	12	17.05	17.04	17.02	0
		25	25	17.10	17.03	16.90	0
		50	0	17.24	17.06	16.99	0

LTE Conducted Power (Reduction)							
LTE Band 25							
BW	MCS Index	Channel		26065	26365	26665	3GPP MPR
		Frequency (MHz)		1852.5	1882.5	1912.5	
5M	QPSK	1	0	17.26	17.27	17.11	0
		1	12	17.24	17.18	16.97	0
		1	24	17.29	17.14	17.15	0
		12	0	17.18	17.24	17.19	0
		12	6	17.19	17.10	17.08	0
		12	13	17.26	17.18	16.95	0
		25	0	17.23	17.15	16.92	0
5M	16QAM	1	0	17.24	17.27	17.13	0
		1	12	17.17	17.14	17.13	0
		1	24	17.23	17.15	17.08	0
		12	0	17.24	17.10	17.01	0
		12	6	17.16	17.18	17.20	0
		12	13	17.22	17.16	17.05	0
		25	0	17.25	17.10	17.07	0
5M	64QAM	1	0	17.16	17.09	17.24	0
		1	12	17.28	17.07	17.10	0
		1	24	17.11	17.08	17.12	0
		12	0	17.15	17.23	17.13	0
		12	6	17.11	16.98	16.90	0
		12	13	17.11	17.00	17.01	0
		25	0	17.23	17.17	17.04	0
BW	MCS Index	Channel		26055	26365	26675	3GPP MPR
		Frequency (MHz)		1851.5	1882.5	1913.5	
3M	QPSK	1	0	17.18	17.29	17.27	0
		1	7	17.26	17.18	17.17	0
		1	14	17.30	17.18	17.16	0
		8	0	17.14	17.31	17.19	0
		8	3	17.13	17.08	17.02	0
		8	7	17.26	17.25	16.95	0
		15	0	17.28	17.15	17.03	0
3M	16QAM	1	0	17.24	17.22	17.16	0
		1	7	17.26	17.07	17.13	0
		1	14	17.14	17.11	17.08	0
		8	0	17.22	17.06	17.12	0
		8	3	17.30	17.15	17.12	0
		8	7	17.15	17.18	17.01	0
		15	0	17.19	16.98	17.17	0
3M	64QAM	1	0	17.25	17.19	17.15	0
		1	7	17.23	17.15	17.06	0
		1	14	17.13	17.12	17.11	0
		8	0	17.12	17.16	17.01	0
		8	3	17.14	16.97	16.88	0
		8	7	17.10	17.01	16.96	0
		15	0	17.15	17.17	17.00	0
BW	MCS Index	Channel		26047	26365	26683	3GPP MPR
		Frequency (MHz)		1850.7	1882.5	1914.3	
1.4M	QPSK	1	0	17.30	17.17	17.22	0
		1	2	17.29	17.11	17.19	0
		1	5	17.32	17.08	17.15	0
		3	0	17.27	17.26	17.17	0
		3	1	17.16	17.14	17.01	0
		3	3	17.16	17.25	16.93	0
		6	0	17.21	17.16	17.03	0
1.4M	16QAM	1	0	17.28	17.17	17.07	0
		1	2	17.27	17.10	17.14	0
		1	5	17.19	17.17	17.13	0
		3	0	17.26	17.06	17.11	0
		3	1	17.16	17.11	17.18	0
		3	3	17.09	17.13	17.04	0
		6	0	17.22	17.03	17.10	0
1.4M	64QAM	1	0	17.23	17.20	17.29	0
		1	2	17.31	17.11	17.06	0
		1	5	17.17	17.07	17.11	0
		3	0	17.06	17.13	17.01	0
		3	1	17.17	17.01	17.03	0
		3	3	17.09	17.06	16.88	0
		6	0	17.24	17.13	16.97	0

LTE Conducted Power (Reduction)

LTE Band 26

BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	High	3GPP MPR (dB)
		Channel		26765	26865	26915	26965	
		Frequency (MHz)		821.5	831.5	836.5	841.5	
15M	QPSK	1	0	18.73	18.76	18.70	18.78	0
		1	37	18.62	18.69	18.64	18.73	0
		1	74	18.51	18.55	18.48	18.65	0
		36	0	18.57	18.57	18.49	18.63	0
		36	19	18.45	18.53	18.49	18.62	0
		36	39	18.43	18.52	18.42	18.56	0
		75	0	18.49	18.55	18.48	18.59	0
15M	16QAM	1	0	18.64	18.65	18.64	18.71	0
		1	37	18.55	18.57	18.49	18.65	0
		1	74	18.53	18.56	18.46	18.62	0
		36	0	18.49	18.56	18.49	18.63	0
		36	19	18.47	18.57	18.51	18.62	0
		36	39	18.31	18.39	18.33	18.48	0
		75	0	18.47	18.47	18.39	18.57	0
15M	64QAM	1	0	18.65	18.66	18.61	18.69	0
		1	37	18.55	18.65	18.61	18.68	0
		1	74	18.45	18.49	18.49	18.59	0
		36	0	18.51	18.57	18.52	18.62	0
		36	19	18.53	18.56	18.50	18.61	0
		36	39	18.31	18.38	18.34	18.47	0
		75	0	18.48	18.52	18.50	18.55	0
BW	MCS Index	Channel		26740	26865	26915	26990	3GPP MPR
		Frequency (MHz)		819	831.5	836.5	844	
10M	QPSK	1	0	18.72	18.73	18.61	18.76	0
		1	24	18.59	18.59	18.55	18.68	0
		1	49	18.44	18.53	18.39	18.62	0
		25	0	18.51	18.55	18.40	18.61	0
		25	12	18.43	18.51	18.39	18.53	0
		25	25	18.41	18.50	18.41	18.56	0
		50	0	18.49	18.47	18.46	18.51	0
10M	16QAM	1	0	18.60	18.60	18.62	18.65	0
		1	24	18.49	18.49	18.43	18.62	0
		1	49	18.48	18.56	18.43	18.57	0
		25	0	18.43	18.53	18.40	18.54	0
		25	12	18.42	18.48	18.43	18.52	0
		25	25	18.23	18.34	18.31	18.45	0
		50	0	18.44	18.37	18.37	18.47	0
10M	64QAM	1	0	18.61	18.61	18.51	18.65	0
		1	24	18.47	18.56	18.55	18.63	0
		1	49	18.41	18.40	18.40	18.53	0
		25	0	18.50	18.49	18.43	18.59	0
		25	12	18.43	18.53	18.43	18.52	0
		25	25	18.28	18.30	18.29	18.40	0
		50	0	18.40	18.51	18.45	18.46	0
BW	MCS Index	Channel		26715	26865	26915	27015	3GPP MPR
		Frequency (MHz)		816.5	831.5	836.5	846.5	
5M	QPSK	1	0	18.69	18.65	18.59	18.70	0
		1	12	18.49	18.67	18.52	18.61	0
		1	24	18.37	18.53	18.39	18.44	0
		12	0	18.42	18.47	18.33	18.48	0
		12	6	18.44	18.45	18.39	18.60	0
		12	13	18.31	18.39	18.34	18.51	0
		25	0	18.47	18.35	18.41	18.50	0
5M	16QAM	1	0	18.54	18.64	18.53	18.46	0
		1	12	18.45	18.55	18.33	18.56	0
		1	24	18.38	18.38	18.41	18.45	0
		12	0	18.35	18.51	18.37	18.51	0
		12	6	18.34	18.52	18.43	18.52	0
		12	13	18.20	18.43	18.25	18.28	0
		25	0	18.28	18.54	18.34	18.44	0
5M	64QAM	1	0	18.46	18.63	18.43	18.52	0
		1	12	18.49	18.49	18.53	18.67	0
		1	24	18.32	18.43	18.40	18.42	0
		12	0	18.36	18.44	18.43	18.55	0
		12	6	18.37	18.51	18.35	18.47	0
		12	13	18.15	18.31	18.19	18.42	0
		25	0	18.26	18.52	18.42	18.42	0

LTE Conducted Power (Reduction)								
LTE Band 26								
BW	MCS Index	Channel		26705	26865	26915	27025	3GPP MPR
		Frequency (MHz)		815.5	831.5	836.5	847.5	
3M	QPSK	1	0	18.72	18.59	18.57	18.71	0
		1	7	18.53	18.40	18.48	18.49	0
		1	14	18.30	18.33	18.36	18.35	0
		8	0	18.48	18.52	18.23	18.33	0
		8	3	18.34	18.58	18.34	18.38	0
		8	7	18.41	18.31	18.29	18.34	0
3M	16QAM	15	0	18.44	18.37	18.38	18.42	0
		1	0	18.58	18.61	18.53	18.46	0
		1	7	18.49	18.54	18.29	18.40	0
		1	14	18.43	18.53	18.36	18.44	0
		8	0	18.36	18.52	18.36	18.33	0
		8	3	18.40	18.50	18.41	18.37	0
3M	64QAM	8	7	18.23	18.42	18.22	18.18	0
		15	0	18.38	18.52	18.29	18.27	0
		1	0	18.53	18.55	18.33	18.46	0
		1	7	18.38	18.47	18.46	18.48	0
		1	14	18.29	18.44	18.37	18.27	0
		8	0	18.36	18.59	18.36	18.33	0
3M	64QAM	8	3	18.35	18.55	18.35	18.49	0
		8	7	18.20	18.31	18.13	18.18	0
		15	0	18.28	18.40	18.37	18.35	0
BW	MCS Index	Channel		26697	26865	26915	27033	3GPP MPR
		Frequency (MHz)		814.7	831.5	836.5	848.3	
1.4M	QPSK	1	0	18.58	18.68	18.48	18.65	0
		1	2	18.51	18.52	18.43	18.58	0
		1	5	18.36	18.60	18.26	18.51	0
		3	0	18.41	18.43	18.67	18.53	0
		3	1	18.32	18.41	18.76	18.46	0
		3	3	18.36	18.49	18.77	18.45	0
1.4M	16QAM	6	0	18.46	18.42	18.29	18.45	0
		1	0	18.59	18.54	18.53	18.65	0
		1	2	18.39	18.58	18.22	18.58	0
		1	5	18.47	18.53	18.33	18.53	0
		3	0	18.36	18.46	18.34	18.48	0
		3	1	18.29	18.42	18.39	18.56	0
1.4M	64QAM	3	3	18.23	18.39	18.17	18.33	0
		6	0	18.37	18.37	18.24	18.44	0
		1	0	18.46	18.48	18.25	18.50	0
		1	2	18.39	18.52	18.42	18.56	0
		1	5	18.41	18.47	18.33	18.44	0
		3	0	18.48	18.49	18.28	18.51	0
1.4M	64QAM	3	1	18.31	18.52	18.29	18.46	0
		3	3	18.16	18.34	18.13	18.30	0
		6	0	18.35	18.48	18.29	18.47	0
		6	0	18.35	18.48	18.29	18.47	0

LTE Conducted Power (Reduction)									
LTE Band 41									
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	Mid	High	3GPP MPR (dB)
		Channel		39750	40185	40620	41055	41490	
		Frequency (MHz)		2506	2549.5	2593	2636.5	2680	
20M	QPSK	1	0	18.81	18.82	18.83	18.87	18.91	0
		1	50	18.61	18.67	18.73	18.83	18.88	0
		1	99	18.59	18.65	18.75	18.81	18.83	0
		50	0	18.63	18.67	18.72	18.78	18.87	0
		50	25	18.65	18.73	18.78	18.82	18.86	0
		50	50	18.61	18.63	18.71	18.76	18.83	0
20M	16QAM	100	0	18.66	18.68	18.72	18.82	18.85	0
		1	0	18.67	18.73	18.82	18.85	18.81	0
		1	50	18.66	18.75	18.77	18.79	18.78	0
		1	99	18.62	18.71	18.77	18.82	18.77	0
		50	0	18.72	18.75	18.81	18.83	18.79	0
		50	25	18.68	18.72	18.73	18.77	18.77	0
20M	64QAM	50	50	18.57	18.63	18.69	18.75	18.73	0
		100	0	18.65	18.66	18.75	18.76	18.83	0
		1	0	18.73	18.77	18.82	18.85	18.89	0
		1	50	18.72	18.79	18.81	18.82	18.88	0
		1	99	18.71	18.72	18.75	18.78	18.75	0
		50	0	18.72	18.72	18.76	18.77	18.77	0
20M	MCS Index	50	25	18.55	18.65	18.73	18.81	18.76	0
		50	50	18.61	18.68	18.72	18.81	18.73	0
		100	0	18.58	18.63	18.71	18.79	18.75	0
		Channel		39725	40173	40620	41068	41515	3GPP MPR
		Frequency (MHz)		2503.5	2548.3	2593	2637.8	2682.5	
15M	QPSK	1	0	18.80	18.76	18.76	18.85	18.89	0
		1	37	18.60	18.58	18.66	18.80	18.82	0
		1	74	18.50	18.64	18.74	18.80	18.80	0
		36	0	18.59	18.62	18.63	18.70	18.78	0
		36	19	18.60	18.68	18.76	18.80	18.84	0
		36	39	18.59	18.54	18.71	18.70	18.78	0
15M	16QAM	75	0	18.60	18.64	18.67	18.81	18.83	0
		1	0	18.60	18.64	18.79	18.81	18.83	0
		1	37	18.59	18.74	18.71	18.70	18.81	0
		1	74	18.55	18.67	18.68	18.78	18.73	0
		36	0	18.72	18.66	18.71	18.75	18.87	0
		36	19	18.67	18.69	18.70	18.77	18.77	0
15M	64QAM	36	39	18.55	18.54	18.67	18.66	18.83	0
		75	0	18.64	18.57	18.69	18.73	18.76	0
		1	0	18.67	18.75	18.82	18.84	18.88	0
		1	37	18.67	18.74	18.71	18.75	18.81	0
		1	74	18.62	18.68	18.72	18.68	18.80	0
		36	0	18.70	18.66	18.76	18.76	18.79	0
10M	QPSK	36	19	18.46	18.55	18.65	18.75	18.79	0
		36	39	18.53	18.64	18.72	18.74	18.77	0
		75	0	18.49	18.63	18.71	18.78	18.81	0
		Channel		39700	40160	40620	41080	41540	3GPP MPR
		Frequency (MHz)		2501	2547	2593	2639	2685	
10M	16QAM	1	0	18.77	18.70	18.71	18.78	18.88	0
		1	24	18.50	18.51	18.57	18.79	18.72	0
		1	49	18.46	18.64	18.73	18.74	18.78	0
		25	0	18.51	18.57	18.59	18.69	18.71	0
		25	12	18.52	18.62	18.69	18.73	18.76	0
		25	25	18.50	18.53	18.63	18.66	18.78	0
10M	64QAM	50	0	18.51	18.56	18.64	18.74	18.80	0
		1	0	18.77	18.73	18.67	18.84	18.81	0
		1	24	18.60	18.53	18.61	18.79	18.76	0
		1	49	18.49	18.55	18.66	18.71	18.76	0
		25	0	18.51	18.56	18.62	18.65	18.73	0
		25	12	18.50	18.66	18.73	18.76	18.74	0
10M	QPSK	25	25	18.53	18.49	18.67	18.60	18.75	0
		50	0	18.55	18.56	18.61	18.74	18.83	0
		1	0	18.78	18.75	18.70	18.85	18.84	0
		1	24	18.57	18.53	18.58	18.79	18.75	0
		1	49	18.48	18.58	18.71	18.71	18.79	0
		25	0	18.58	18.58	18.61	18.70	18.69	0
10M	16QAM	25	12	18.60	18.61	18.68	18.73	18.75	0
		25	25	18.52	18.53	18.71	18.61	18.69	0
		50	0	18.55	18.60	18.63	18.71	18.78	0
		50	0	18.55	18.60	18.63	18.71	18.78	0

LTE Conducted Power (Reduction)									
LTE Band 41									
BW	MCS Index	Channel		39675	40148	40620	41093	41565	3GPP MPR
		Frequency (MHz)		2498.5	2545.8	2593	2640.3	2687.5	
5M	QPSK	1	0	18.75	18.66	18.69	18.82	18.82	0
		1	12	18.52	18.52	18.65	18.71	18.80	0
		1	24	18.45	18.62	18.73	18.71	18.73	0
		12	0	18.57	18.53	18.62	18.60	18.68	0
		12	6	18.56	18.61	18.67	18.79	18.80	0
		12	13	18.55	18.44	18.67	18.68	18.77	0
		25	0	18.57	18.61	18.66	18.78	18.75	0
5M	16QAM	1	0	18.73	18.69	18.66	18.75	18.84	0
		1	12	18.56	18.53	18.65	18.73	18.82	0
		1	24	18.41	18.64	18.68	18.74	18.71	0
		12	0	18.49	18.54	18.53	18.60	18.70	0
		12	6	18.52	18.68	18.72	18.73	18.80	0
		12	13	18.49	18.53	18.62	18.63	18.72	0
		25	0	18.50	18.62	18.57	18.73	18.76	0
5M	64QAM	1	0	18.70	18.69	18.68	18.82	18.86	0
		1	12	18.58	18.58	18.64	18.76	18.73	0
		1	24	18.44	18.54	18.73	18.73	18.78	0
		12	0	18.49	18.57	18.56	18.64	18.73	0
		12	6	18.59	18.67	18.69	18.79	18.75	0
		12	13	18.59	18.51	18.69	18.64	18.70	0
		25	0	18.51	18.59	18.66	18.77	18.78	0

LTE Conducted Power (Reduction)								
LTE Band 48								
BW	MCS Index	RB Size	RB Offset	Low	Mid	Mid	High	3GPP MPR (dB)
		Channel		55340	55780	56210	56640	
		Frequency (MHz)		3560	3604	3647	3690	
20M	QPSK	1	0	16.86	16.89	16.93	16.98	0
		1	50	16.71	16.73	16.85	16.95	0
		1	99	16.59	16.68	16.91	16.92	0
		50	0	16.72	16.78	16.93	16.97	0
		50	25	16.71	16.76	16.92	16.96	0
		50	50	16.69	16.73	16.87	16.91	0
		100	0	16.75	16.81	16.91	16.95	0
20M	16QAM	1	0	16.77	16.82	16.92	16.93	0
		1	50	16.65	16.73	16.82	16.89	0
		1	99	16.52	16.58	16.76	16.86	0
		50	0	16.75	16.79	16.87	16.87	0
		50	25	16.57	16.59	16.73	16.83	0
		50	50	16.63	16.71	16.77	16.82	0
		100	0	16.62	16.67	16.78	16.86	0
20M	64QAM	1	0	16.68	16.71	16.85	16.88	0
		1	50	16.66	16.73	16.77	16.82	0
		1	99	16.67	16.68	16.71	16.81	0
		50	0	16.50	16.59	16.73	16.78	0
		50	25	16.62	16.63	16.72	16.75	0
		50	50	16.40	16.45	16.63	16.73	0
		100	0	16.56	16.63	16.72	16.79	0
BW	MCS Index	Channel		55315	55765	56215	56665	3GPP MPR
		Frequency (MHz)		3557.5	3602.5	3647.5	3692.5	
15M	QPSK	1	0	16.83	16.83	16.85	16.89	0
		1	37	16.66	16.73	16.78	16.94	0
		1	74	16.55	16.62	16.88	16.91	0
		36	0	16.72	16.71	16.89	16.87	0
		36	19	16.67	16.69	16.83	16.94	0
		36	39	16.65	16.63	16.85	16.90	0
		75	0	16.73	16.81	16.81	16.90	0
15M	16QAM	1	0	16.76	16.77	16.82	16.92	0
		1	37	16.62	16.72	16.81	16.84	0
		1	74	16.47	16.50	16.68	16.78	0
		36	0	16.75	16.79	16.80	16.85	0
		36	19	16.56	16.51	16.69	16.76	0
		36	39	16.61	16.71	16.71	16.81	0
		75	0	16.52	16.58	16.74	16.85	0
15M	64QAM	1	0	16.58	16.71	16.83	16.78	0
		1	37	16.61	16.67	16.76	16.77	0
		1	74	16.61	16.66	16.66	16.72	0
		36	0	16.48	16.49	16.64	16.69	0
		36	19	16.57	16.53	16.65	16.71	0
		36	39	16.30	16.45	16.60	16.69	0
		75	0	16.46	16.55	16.67	16.71	0
BW	MCS Index	Channel		55290	55750	56220	56690	3GPP MPR
		Frequency (MHz)		3555	3601	3648	3695	
10M	QPSK	1	0	16.81	16.82	16.85	16.83	0
		1	24	16.59	16.69	16.68	16.92	0
		1	49	16.51	16.57	16.88	16.88	0
		25	0	16.65	16.63	16.79	16.84	0
		25	12	16.64	16.68	16.78	16.89	0
		25	25	16.65	16.61	16.84	16.85	0
		50	0	16.66	16.78	16.81	16.84	0
10M	16QAM	1	0	16.79	16.83	16.80	16.79	0
		1	24	16.66	16.64	16.74	16.84	0
		1	49	16.46	16.52	16.83	16.91	0
		25	0	16.66	16.66	16.87	16.87	0
		25	12	16.63	16.65	16.82	16.89	0
		25	25	16.64	16.59	16.84	16.83	0
		50	0	16.64	16.76	16.80	16.81	0
10M	64QAM	1	0	16.76	16.77	16.79	16.85	0
		1	24	16.65	16.70	16.72	16.88	0
		1	49	16.48	16.55	16.86	16.90	0
		25	0	16.62	16.69	16.79	16.77	0
		25	12	16.61	16.65	16.79	16.94	0
		25	25	16.55	16.59	16.83	16.83	0
		50	0	16.68	16.76	16.81	16.86	0

LTE Conducted Power (Reduction)								
LTE Band 48								
BW	MCS Index	Channel		55265	55745	56235	56715	3GPP MPR
		Frequency (MHz)		3552.5	3600.5	3649.5	3697.5	
5M	QPSK	1	0	16.81	16.76	16.82	16.89	0
		1	12	16.63	16.63	16.74	16.94	0
		1	24	16.47	16.57	16.79	16.83	0
		12	0	16.65	16.70	16.81	16.79	0
		12	6	16.58	16.66	16.73	16.84	0
		12	13	16.65	16.54	16.81	16.85	0
		25	0	16.64	16.73	16.71	16.84	0
5M	16QAM	1	0	16.77	16.79	16.85	16.81	0
		1	12	16.64	16.70	16.76	16.87	0
		1	24	16.55	16.54	16.87	16.84	0
		12	0	16.62	16.67	16.85	16.87	0
		12	6	16.63	16.59	16.78	16.85	0
		12	13	16.60	16.53	16.75	16.82	0
		25	0	16.70	16.74	16.78	16.80	0
5M	64QAM	1	0	16.82	16.75	16.84	16.86	0
		1	12	16.64	16.72	16.75	16.92	0
		1	24	16.51	16.53	16.84	16.90	0
		12	0	16.68	16.64	16.80	16.82	0
		12	6	16.59	16.67	16.74	16.91	0
		12	13	16.56	16.57	16.81	16.82	0
		25	0	16.67	16.73	16.79	16.82	0

LTE Conducted Power (Reduction)							
LTE Band 66							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		132072	132322	132572	
		Frequency (MHz)		1720	1745	1770	
20M	QPSK	1	0	17.39	17.48	17.37	0
		1	50	17.39	17.41	17.31	0
		1	99	17.37	17.38	17.27	0
		50	0	17.35	17.39	17.28	0
		50	25	17.31	17.36	17.22	0
		50	50	17.26	17.35	17.18	0
		100	0	17.35	17.38	17.28	0
20M	16QAM	1	0	17.38	17.47	17.35	0
		1	50	17.31	17.33	17.27	0
		1	99	17.26	17.32	17.19	0
		50	0	17.32	17.35	17.31	0
		50	25	17.28	17.29	17.21	0
		50	50	17.21	17.28	17.17	0
		100	0	17.28	17.33	17.19	0
20M	64QAM	1	0	17.36	17.38	17.35	0
		1	50	17.26	17.35	17.16	0
		1	99	17.30	17.33	17.26	0
		50	0	17.33	17.37	17.27	0
		50	25	17.32	17.36	17.22	0
		50	50	17.22	17.26	17.13	0
		100	0	17.32	17.32	17.32	0
BW	MCS Index	Channel		132047	132322	132597	3GPP MPR
		Frequency (MHz)		1717.5	1745	1772.5	
15M	QPSK	1	0	17.38	17.44	17.34	0
		1	37	17.30	17.39	17.21	0
		1	74	17.37	17.29	17.21	0
		36	0	17.25	17.33	17.20	0
		36	19	17.25	17.31	17.15	0
		36	39	17.19	17.26	17.08	0
		75	0	17.26	17.36	17.21	0
15M	16QAM	1	0	17.33	17.47	17.31	0
		1	37	17.30	17.30	17.19	0
		1	74	17.19	17.28	17.18	0
		36	0	17.24	17.26	17.24	0
		36	19	17.27	17.27	17.18	0
		36	39	17.12	17.28	17.12	0
		75	0	17.20	17.29	17.17	0
15M	64QAM	1	0	17.27	17.35	17.26	0
		1	37	17.24	17.25	17.12	0
		1	74	17.22	17.33	17.24	0
		36	0	17.29	17.31	17.19	0
		36	19	17.28	17.36	17.22	0
		36	39	17.16	17.17	17.08	0
		75	0	17.24	17.23	17.23	0
BW	MCS Index	Channel		132022	132322	132622	3GPP MPR
		Frequency (MHz)		1715	1745	1775	
10M	QPSK	1	0	17.33	17.30	17.34	0
		1	24	17.30	17.33	17.16	0
		1	49	17.29	17.17	17.18	0
		25	0	17.15	17.20	17.05	0
		25	12	17.19	17.24	17.05	0
		25	25	17.15	17.18	17.08	0
		50	0	17.16	17.34	17.10	0
10M	16QAM	1	0	17.23	17.43	17.20	0
		1	24	17.19	17.28	17.15	0
		1	49	17.12	17.13	17.12	0
		25	0	17.23	17.20	17.17	0
		25	12	17.25	17.20	17.08	0
		25	25	16.98	17.24	16.99	0
		50	0	17.17	17.15	17.16	0
10M	64QAM	1	0	17.25	17.35	17.25	0
		1	24	17.22	17.10	17.11	0
		1	49	17.09	17.24	17.18	0
		25	0	17.16	17.26	17.18	0
		25	12	17.25	17.25	17.15	0
		25	25	17.06	17.11	16.99	0
		50	0	17.16	17.20	17.08	0

LTE Conducted Power (Reduction)							
LTE Band 66							
BW	MCS Index	Channel		131997	132322	132647	3GPP MPR
		Frequency (MHz)		1712.5	1745	1777.5	
5M	QPSK	1	0	17.33	17.35	17.30	0
		1	12	17.28	17.29	17.04	0
		1	24	17.36	17.15	17.18	0
		12	0	17.22	17.28	17.03	0
		12	6	17.12	17.17	16.96	0
		12	13	17.13	17.13	16.98	0
		25	0	17.13	17.22	17.01	0
5M	16QAM	1	0	17.33	17.41	17.18	0
		1	12	17.26	17.27	17.15	0
		1	24	17.12	17.19	17.13	0
		12	0	17.15	17.18	17.20	0
		12	6	17.25	17.14	17.05	0
		12	13	17.10	17.27	17.07	0
		25	0	17.05	17.21	17.07	0
5M	64QAM	1	0	17.24	17.24	17.18	0
		1	12	17.12	17.15	17.11	0
		1	24	17.15	17.33	17.20	0
		12	0	17.24	17.28	17.18	0
		12	6	17.27	17.27	17.07	0
		12	13	17.09	17.06	17.04	0
		25	0	17.24	17.21	17.18	0
BW	MCS Index	Channel		131987	132322	132657	3GPP MPR
		Frequency (MHz)		1711.5	1745	1778.5	
3M	QPSK	1	0	17.25	17.41	17.29	0
		1	7	17.16	17.39	17.09	0
		1	14	17.36	17.25	17.21	0
		8	0	17.23	17.18	17.20	0
		8	3	17.12	17.19	17.09	0
		8	7	17.14	17.19	16.96	0
		15	0	17.19	17.33	17.11	0
3M	16QAM	1	0	17.28	17.36	17.24	0
		1	7	17.29	17.22	17.16	0
		1	14	17.11	17.13	17.18	0
		8	0	17.17	17.20	17.24	0
		8	3	17.16	17.24	17.03	0
		8	7	17.10	17.20	17.11	0
		15	0	17.20	17.29	17.12	0
3M	64QAM	1	0	17.14	17.28	17.20	0
		1	7	17.12	17.17	17.10	0
		1	14	17.13	17.33	17.13	0
		8	0	17.19	17.31	17.14	0
		8	3	17.20	17.28	17.09	0
		8	7	17.04	17.14	17.02	0
		15	0	17.24	17.14	17.13	0
BW	MCS Index	Channel		131979	132322	132665	3GPP MPR
		Frequency (MHz)		1710.7	1745	1779.3	
1.4M	QPSK	1	0	17.27	17.36	17.33	0
		1	2	17.24	17.34	17.18	0
		1	5	17.23	17.24	17.09	0
		3	0	17.24	17.28	17.06	0
		3	1	17.16	17.24	17.02	0
		3	3	17.14	17.25	17.06	0
		6	0	17.13	17.36	17.14	0
1.4M	16QAM	1	0	17.22	17.39	17.16	0
		1	2	17.26	17.23	17.18	0
		1	5	17.04	17.18	17.10	0
		3	0	17.23	17.21	17.17	0
		3	1	17.19	17.19	17.18	0
		3	3	16.97	17.22	17.12	0
		6	0	17.09	17.19	17.10	0
1.4M	64QAM	1	0	17.27	17.35	17.20	0
		1	2	17.21	17.13	17.10	0
		1	5	17.18	17.21	17.19	0
		3	0	17.19	17.22	17.05	0
		3	1	17.24	17.31	17.11	0
		3	3	17.13	17.13	17.05	0
		6	0	17.15	17.18	17.23	0

LTE Conducted Power (Reduction)							
LTE Band 71							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel		133222	133297	133372	
		Frequency (MHz)		673	680.5	688	
20M	QPSK	1	0	22.81	22.83	22.86	0
		1	50	22.71	22.77	22.78	0
		1	99	22.69	22.76	22.76	0
		50	0	22.67	22.75	22.77	0
		50	25	22.63	22.71	22.75	0
		50	50	22.58	22.63	22.73	0
		100	0	22.71	22.72	22.76	0
20M	16QAM	1	0	22.66	22.67	22.76	0
		1	50	22.61	22.71	22.75	0
		1	99	22.71	22.73	22.73	0
		50	0	21.72	21.78	21.85	0
		50	25	21.81	21.81	21.83	0
		50	50	21.72	21.79	21.82	0
		100	0	21.77	21.81	21.86	0
20M	64QAM	1	0	21.82	21.85	21.86	0
		1	50	21.71	21.81	21.85	0
		1	99	21.77	21.78	21.83	0
		50	0	21.09	21.13	21.19	0
		50	25	21.02	21.09	21.17	0
		50	50	21.09	21.11	21.16	0
		100	0	21.16	21.18	21.18	0
BW	MCS Index	Channel		133197	133297	133397	3GPP MPR
		Frequency (MHz)		670.5	680.5	690.5	
15M	QPSK	1	0	22.77	22.79	22.76	0
		1	37	22.67	22.76	22.70	0
		1	74	22.65	22.66	22.72	0
		36	0	22.57	22.72	22.71	0
		36	19	22.60	22.62	22.74	0
		36	39	22.58	22.55	22.73	0
		75	0	22.68	22.71	22.72	0
15M	16QAM	1	0	22.57	22.63	22.73	0
		1	37	22.59	22.63	22.68	0
		1	74	22.64	22.64	22.68	0
		36	0	21.62	21.72	21.76	0
		36	19	21.75	21.72	21.75	0
		36	39	21.72	21.79	21.80	0
		75	0	21.74	21.71	21.79	0
15M	64QAM	1	0	21.75	21.76	21.80	0
		1	37	21.70	21.71	21.84	0
		1	74	21.68	21.77	21.73	0
		36	0	21.06	21.09	21.12	0
		36	19	21.03	21.08	21.08	0
		36	39	21.02	21.07	21.15	0
		75	0	21.11	21.16	21.16	0
BW	MCS Index	Channel		133172	133297	133422	3GPP MPR
		Frequency (MHz)		668	680.5	693	
10M	QPSK	1	0	22.77	22.70	22.70	0
		1	24	22.57	22.63	22.64	0
		1	49	22.57	22.61	22.58	0
		25	0	22.45	22.57	22.68	0
		25	12	22.57	22.59	22.69	0
		25	25	22.51	22.51	22.69	0
		50	0	22.58	22.60	22.70	0
10M	16QAM	1	0	22.51	22.60	22.64	0
		1	24	22.44	22.61	22.59	0
		1	49	22.56	22.63	22.68	0
		25	0	21.59	21.64	21.67	0
		25	12	21.73	21.65	21.67	0
		25	25	21.68	21.68	21.73	0
		50	0	21.68	21.67	21.76	0
10M	64QAM	1	0	21.74	21.66	21.76	0
		1	24	21.61	21.67	21.77	0
		1	49	21.58	21.72	21.66	0
		25	0	21.05	21.08	21.01	0
		25	12	21.03	21.07	21.02	0
		25	25	21.07	21.05	21.08	0
		50	0	21.08	21.16	21.15	0

LTE Conducted Power (Reduction)							
LTE Band 71							
BW	MCS Index	Channel		133147	133297	133447	3GPP MPR
		Frequency (MHz)		665.5	680.5	695.5	
5M	QPSK	1	0	22.69	22.69	22.60	0
		1	12	22.56	22.66	22.59	0
		1	24	22.58	22.66	22.44	0
		12	0	22.43	22.63	22.58	0
		12	6	22.45	22.53	22.64	0
		12	13	22.46	22.41	22.68	0
		25	0	22.54	22.65	22.60	0
5M	16QAM	1	0	22.52	22.54	22.62	0
		1	12	22.47	22.63	22.58	0
		1	24	22.60	22.50	22.60	0
		12	0	21.59	21.66	21.62	0
		12	6	21.75	21.58	21.69	0
		12	13	21.66	21.76	21.79	0
		25	0	21.73	21.64	21.75	0
5M	64QAM	1	0	21.68	21.76	21.79	0
		1	12	21.57	21.71	21.81	0
		1	24	21.65	21.75	21.64	0
		12	0	21.02	21.03	21.02	0
		12	6	21.05	21.02	21.07	0
		12	13	21.08	21.05	21.06	0
		25	0	21.06	21.03	21.08	0

LTE Conducted Power (Reduction)							
LTE Band 106							
BW	MCS Index	RB Size	RB Offset	Low	Mid	High	3GPP MPR (dB)
		Channel			134322		
		Frequency (MHz)			899		
3M	QPSK	1	0		18.46		0
		1	7		18.43		0
		1	14		18.42		0
		8	0		18.45		0
		8	3		18.42		0
		8	7		18.41		0
		15	0		18.43		0
3M	16QAM	1	0		18.41		0
		1	7		18.39		0
		1	14		18.36		0
		8	0		18.37		0
		8	3		18.35		0
		8	7		18.33		0
		15	0		18.38		0
3M	64QAM	1	0		18.38		0
		1	7		18.36		0
		1	14		18.35		0
		8	0		18.36		0
		8	3		18.33		0
		8	7		18.32		0
		15	0		18.39		0
BW	MCS Index	Channel		134314	134322	134330	3GPP MPR
		Frequency (MHz)		898.2	899	889.8	
1.4M	QPSK	1	0	18.38	18.43	18.32	0
		1	7	18.35	18.41	18.31	0
		1	14	18.32	18.36	18.22	0
		8	0	18.35	18.39	18.26	0
		8	3	18.32	18.36	18.23	0
		8	7	18.31	18.38	18.22	0
		15	0	18.41	18.42	18.33	0
1.4M	16QAM	1	0	18.30	18.31	18.21	0
		1	7	18.21	18.29	18.18	0
		1	14	18.32	18.32	18.30	0
		8	0	18.21	18.28	18.20	0
		8	3	18.29	18.31	18.22	0
		8	7	18.17	18.23	18.09	0
		15	0	18.23	18.32	18.15	0
1.4M	64QAM	1	0	18.21	18.28	18.21	0
		1	7	18.27	18.28	18.18	0
		1	14	18.29	18.29	18.19	0
		8	0	18.25	18.31	18.17	0
		8	3	18.23	18.32	18.23	0
		8	7	18.27	18.30	18.25	0
		15	0	18.33	18.37	18.30	0

Uplink Carrier Aggregation Scenarios Conducted Power_Full Power

Configure	Combination	PCC							SCC							Measurement Power		
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Maximum Tune-up Power	MPR Level (dB)	Tx Power with UL-CA Active (dBm)
																		Total
Intra Band Contiguous	5B	5	10	QPSK	1	0	20450	829	5	10	QPSK	1	49	20549	838.9	24	0-8.5	13.46
					1	49						1	0			24	0	22.83
		5	10	QPSK	1	0	20476	831.6	5	10	QPSK	1	49	20575	841.5	24	0-8.5	13.45
					1	49						1	0			24	0	23.02
		5	10	QPSK	1	0	20501	834.1	5	10	QPSK	1	49	20600	844	24	0-8.5	13.52
					1	49						1	0			24	0	23.07
	7C	7	20	QPSK	1	0	20850	2510	7	20	QPSK	1	99	21048	2529.8	24	0-8.5	15.31
					1	99						1	0			24	0	22.65
		7	20	QPSK	1	0	21001	2525.1	7	20	QPSK	1	99	21199	2544.9	24	0-8.5	15.33
					1	99						1	0			24	0	22.82
		7	20	QPSK	1	0	21152	2540.2	7	20	QPSK	1	99	21350	2560	24	0-8.5	15.35
					1	99						1	0			24	0	22.85
	41C	41	20	QPSK	1	0	39750	2506	41	20	QPSK	1	99	39948	2525.8	24	0-8.5	15.56
					1	99						1	0			24	0	22.95
		41	20	QPSK	1	0	40185	2549.5	41	20	QPSK	1	99	40383	2569.3	24	0-8.5	15.65
					1	99						1	0			24	0	23.01
		41	20	QPSK	1	0	40620	2593	41	20	QPSK	1	99	40818	2612.8	24	0-8.5	15.68
					1	99						1	0			24	0	23.03
		41	20	QPSK	1	0	41055	2636.5	41	20	QPSK	1	99	41253	2656.3	24	0-8.5	15.73
					1	99						1	0			24	0	23.18
		41	20	QPSK	1	0	41292	2660.2	41	20	QPSK	1	99	41490	2680	24	0-8.5	15.83
					1	99						1	0			24	0	23.25
	48C	48	20	QPSK	1	0	55340	3560	48	20	QPSK	1	99	55538	3579.8	23	0-8.5	14.35
					1	99						1	0			23	0	21.99
		48	20	QPSK	1	0	55891	3615.1	48	20	QPSK	1	99	56089	3634.9	23	0-8.5	14.31
					1	99						1	0			23	0	21.93
		48	20	QPSK	1	0	56442	3670.2	48	20	QPSK	1	99	56640	3690	23	0-8.5	14.50
					1	99						1	0			23	0	22.23

Uplink Carrier Aggregation Scenarios Conducted Power_Power Reduction

Confugure	Combination	PCC							SCC							Measurement Power		
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Maximum Tune-up Power	MPR Level (dB)	Tx Power with UL-CA Active (dBm)
																		Total
Intra Band Contiguous	5B	5	10	QPSK	1	0	20450	829	5	10	QPSK	1	49	20549	838.9	19.5	0-8.5	13.38
					1	49						1	0			19.5	0	19.14
		5	10	QPSK	1	0	20476	831.6	5	10	QPSK	1	49	20575	841.5	19.5	0-8.5	13.29
					1	49						1	0			19.5	0	19.10
		5	10	QPSK	1	0	20501	834.1	5	10	QPSK	1	49	20600	844	19.5	0-8.5	13.14
					1	49						1	0			19.5	0	19.08
	7C	7	20	QPSK	1	0	20850	2510	7	20	QPSK	1	99	21048	2529.8	17	0-8.5	15.02
					1	99						1	0			17	0	16.63
		7	20	QPSK	1	0	21001	2525.1	7	20	QPSK	1	99	21199	2544.9	17	0-8.5	14.88
					1	99						1	0			17	0	16.28
		7	20	QPSK	1	0	21152	2540.2	7	20	QPSK	1	99	21350	2560	17	0-8.5	14.81
					1	99						1	0			17	0	16.53
	41C	41	20	QPSK	1	0	39750	2506	41	20	QPSK	1	99	39948	2525.8	19	0-8.5	14.65
					1	99						1	0			19	0	18.45
		41	20	QPSK	1	0	40185	2549.5	41	20	QPSK	1	99	40383	2569.3	19	0-8.5	14.68
					1	99						1	0			19	0	18.37
		41	20	QPSK	1	0	40620	2593	41	20	QPSK	1	99	40818	2612.8	19	0-8.5	14.54
					1	99						1	0			19	0	18.48
		41	20	QPSK	1	0	41055	2636.5	41	20	QPSK	1	99	41253	2656.3	19	0-8.5	14.46
					1	99						1	0			19	0	18.61
		41	20	QPSK	1	0	41292	2660.2	41	20	QPSK	1	99	41490	2680	19	0-8.5	14.63
					1	99						1	0			19	0	18.21
	48C	48	20	QPSK	1	0	55340	3560	48	20	QPSK	1	99	55538	3579.8	17	0-8.5	13.35
					1	99						1	0			17	0	16.34
		48	20	QPSK	1	0	55891	3615.1	48	20	QPSK	1	99	56089	3634.9	17	0-8.5	13.21
					1	99						1	0			17	0	15.94
		48	20	QPSK	1	0	56442	3670.2	48	20	QPSK	1	99	56640	3690	17	0-8.5	13.43
					1	99						1	0			17	0	16.17

Appendix F. SAR and Incident Power Density Test Result

SAR Results for Body Exposure Condition.

Note:

1. SAR testing for WLAN / BT was performed on the maximum power mode.
2. SAR testing for LTE was performed on the maximum power mode.
3. The "< 0.001" means there is no SAR value or the SAR is too low to be measured.
4. Per KDB 388624 APPENDIX OVER6G, the minimum of 5 channels to perform IPD across U-NII 5,6,7 and 8. and measured results were scaled by factor 1.545 to reported power density when measurement uncertainty exceed 30%.
5. SAR testing for WLAN / BT was verified on the worst case of BV CPS report no.: SFCDVB-WTW-P25100254-2 to ensure compliance.

Body SAR Test Result

Body SAR Test Result																		
System & Position								DUT Configuration			SAR							
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	RB#	RB offset	Ant Status	Battery	Power Reduction	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	WCDMA II	RMC12.2K	Rear Face	7	9262			Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0.02	0.395	0.48
	WCDMA II	RMC12.2K	Left Side	0	9262			Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0	<0.001	0.00
	WCDMA II	RMC12.2K	Right Side	0	9262			Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	-0.01	0.364	0.44
	WCDMA II	RMC12.2K	Top Side	22	9262			Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0.07	0.354	0.43
	WCDMA II	RMC12.2K	Bottom Side	0	9262			Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0	<0.001	0.00
1	WCDMA II	RMC12.2K	Rear Face	0	9262			Ant 0	1	w/	-	1.00	17.50	17.47	1.01	0.12	0.357	0.36
	WCDMA II	RMC12.2K	Top Side	0	9262			Ant 0	1	w/	-	1.00	17.50	17.47	1.01	-0.02	0.707	0.71
	WCDMA II	RMC12.2K	Top Side	0	9400			Ant 0	1	w/	-	1.00	17.50	17.45	1.01	-0.19	0.691	0.70
	WCDMA II	RMC12.2K	Top Side	0	9538			Ant 0	1	w/	-	1.00	17.50	17.46	1.01	0.01	0.661	0.67
	WCDMA II	RMC12.2K	Top Side	0	9262			Ant 0	2	w/	-	1.00	17.50	17.47	1.01	-0.08	0.696	0.70
	WCDMA IV	RMC12.2K	Rear Face	7	1312			Ant 0	1	w/o	-	1.00	24.00	23.58	1.10	0.03	0.281	0.31
	WCDMA IV	RMC12.2K	Left Side	0	1312			Ant 0	1	w/o	-	1.00	24.00	23.58	1.10	0	<0.001	0.00
	WCDMA IV	RMC12.2K	Right Side	0	1312			Ant 0	1	w/o	-	1.00	24.00	23.58	1.10	-0.06	0.202	0.22
	WCDMA IV	RMC12.2K	Top Side	22	1312			Ant 0	1	w/o	-	1.00	24.00	23.58	1.10	-0.04	0.189	0.21
	WCDMA IV	RMC12.2K	Bottom Side	0	1312			Ant 0	1	w/o	-	1.00	24.00	23.58	1.10	0	<0.001	0.00
	WCDMA IV	RMC12.2K	Rear Face	0	1312			Ant 0	1	w/	-	1.00	17.50	17.48	1.00	-0.06	0.311	0.31
	WCDMA IV	RMC12.2K	Top Side	0	1312			Ant 0	1	w/	-	1.00	17.50	17.48	1.00	0.02	0.615	0.62
	WCDMA IV	RMC12.2K	Top Side	0	1413			Ant 0	1	w/	-	1.00	17.50	17.47	1.01	-0.15	0.699	0.71
2	WCDMA IV	RMC12.2K	Top Side	0	1513			Ant 0	1	w/	-	1.00	17.50	17.43	1.02	-0.02	0.72	0.73
	WCDMA IV	RMC12.2K	Top Side	0	1513			Ant 0	2	w/	-	1.00	17.50	17.43	1.02	0.12	0.713	0.73
	WCDMA V	RMC12.2K	Rear Face	7	4182			Ant 0	1	w/o	-	1.00	24.00	23.23	1.19	-0.04	0.202	0.24
	WCDMA V	RMC12.2K	Left Side	0	4182			Ant 0	1	w/o	-	1.00	24.00	23.23	1.19	0	<0.001	0.00
	WCDMA V	RMC12.2K	Right Side	0	4182			Ant 0	1	w/o	-	1.00	24.00	23.23	1.19	0.18	0.092	0.11
	WCDMA V	RMC12.2K	Top Side	22	4182			Ant 0	1	w/o	-	1.00	24.00	23.23	1.19	-0.13	0.107	0.13
	WCDMA V	RMC12.2K	Bottom Side	0	4182			Ant 0	1	w/o	-	1.00	24.00	23.23	1.19	0	<0.001	0.00
	WCDMA V	RMC12.2K	Rear Face	0	4182			Ant 0	1	w/	-	1.00	19.00	18.93	1.02	-0.07	0.273	0.28
3	WCDMA V	RMC12.2K	Top Side	0	4182			Ant 0	1	w/	-	1.00	19.00	18.93	1.02	0.02	0.673	0.69
	WCDMA V	RMC12.2K	Top Side	0	4132			Ant 0	1	w/	-	1.00	19.00	18.88	1.03	-0.11	0.607	0.63
	WCDMA V	RMC12.2K	Top Side	0	4233			Ant 0	1	w/	-	1.00	19.00	18.85	1.04	-0.07	0.549	0.57
	WCDMA V	RMC12.2K	Top Side	0	4182			Ant 0	2	w/	-	1.00	19.00	18.93	1.02	0.01	0.665	0.68
	LTE 2	QPSK20M	Rear Face	7	18900	1	0	Ant 0	1	w/o	-	1.00	24.00	22.34	1.47	-0.02	0.439	0.65
	LTE 2	QPSK20M	Left Side	0	18900	1	0	Ant 0	1	w/o	-	1.00	24.00	22.34	1.47	0	<0.001	0.00
	LTE 2	QPSK20M	Right Side	0	18900	1	0	Ant 0	1	w/o	-	1.00	24.00	22.34	1.47	0	0.391	0.57
	LTE 2	QPSK20M	Top Side	22	18900	1	0	Ant 0	1	w/o	-	1.00	24.00	22.34	1.47	-0.18	0.365	0.54
	LTE 2	QPSK20M	Bottom Side	0	18900	1	0	Ant 0	1	w/o	-	1.00	24.00	22.34	1.47	0	<0.001	0.00
	LTE 2	QPSK20M	Rear Face	7	18900	50	0	Ant 0	1	w/o	-	1.00	23.00	21.30	1.48	0.06	0.343	0.51
	LTE 2	QPSK20M	Left Side	0	18900	50	0	Ant 0	1	w/o	-	1.00	23.00	21.30	1.48	0	<0.001	0.00
	LTE 2	QPSK20M	Right Side	0	18900	50	0	Ant 0	1	w/o	-	1.00	23.00	21.30	1.48	0	0.329	0.49
	LTE 2	QPSK20M	Top Side	22	18900	50	0	Ant 0	1	w/o	-	1.00	23.00	21.30	1.48	0.17	0.291	0.43
	LTE 2	QPSK20M	Bottom Side	0	18900	50	0	Ant 0	1	w/o	-	1.00	23.00	21.30	1.48	0	<0.001	0.00
	LTE 2	QPSK20M	Rear Face	0	18900	1	0	Ant 0	1	w/	-	1.00	17.50	17.38	1.03	0.11	0.241	0.25
	LTE 2	QPSK20M	Top Side	0	18900	1	0	Ant 0	1	w/	-	1.00	17.50	17.38	1.03	0.14	0.627	0.65
	LTE 2	QPSK20M	Rear Face	0	18900	50	0	Ant 0	1	w/	-	1.00	17.50	17.36	1.03	-0.15	0.186	0.19
	LTE 2	QPSK20M	Top Side	0	18900	50	0	Ant 0	1	w/	-	1.00	17.50	17.36	1.03	0.05	0.508	0.52
4	LTE 2	QPSK20M	Top Side	0	18700	1	0	Ant 0	1	w/	-	1.00	17.50	17.35	1.04	-0.02	0.669	0.70
	LTE 2	QPSK20M	Top Side	0	19100	1	0	Ant 0	1	w/	-	1.00	17.50	17.31	1.04	0.19	0.595	0.62
	LTE 2	QPSK20M	Top Side	0	18700	1	0	Ant 0	2	w/	-	1.00	17.50	17.35	1.04	-0.16	0.663	0.69
	LTE 4	QPSK20M	Rear Face	7	20175	1	0	Ant 0	1	w/o	-	1.00	24.00	22.65	1.36	0.01	0.391	0.53
	LTE 4	QPSK20M	Left Side	0	20175	1	0	Ant 0	1	w/o	-	1.00	24.00	22.65	1.36	0	<0.001	0.00
	LTE 4	QPSK20M	Right Side	0	20175	1	0	Ant 0	1	w/o	-	1.00	24.00	22.65	1.36	0.18	0.345	0.47
	LTE 4	QPSK20M	Top Side	22	20175	1	0	Ant 0	1	w/o	-	1.00	24.00	22.65	1.36	-0.01	0.319	0.43
	LTE 4	QPSK20M	Bottom Side	0	20175	1	0	Ant 0	1	w/o	-	1.00	24.00	22.65	1.36	0	<0.001	0.00
	LTE 4	QPSK20M	Rear Face	7	20175	50	0	Ant 0	1	w/o	-	1.00	23.00	21.73	1.34	0	0.322	0.43
	LTE 4	QPSK20M	Left Side	0	20175	50	0	Ant 0	1	w/o	-	1.00	23.00	21.73	1.34	0	<0.001	0.00
	LTE 4	QPSK20M	Right Side	0	20175	50	0	Ant 0	1	w/o	-	1.00	23.00	21.73	1.34	0.11	0.295	0.40
	LTE 4	QPSK20M	Top Side	22	20175	50	0	Ant 0	1	w/o	-	1.00	23.00	21.73	1.34	0.02	0.253	0.34
	LTE 4	QPSK20M	Bottom Side	0	20175	50	0	Ant 0	1	w/o	-	1.00	23.00	21.73	1.34	0	<0.001	0.00
	LTE 4	QPSK20M	Rear Face	0	20175	1	0	Ant 0	1	w/	-	1.00	17.50	17.46	1.01	-0.05	0.241	0.24
	LTE 4	QPSK20M	Top Side	0	20175	1	0	Ant 0	1	w/	-	1.00	17.50	17.46	1.01	-0.15	0.701	0.71
	LTE 4	QPSK20M	Rear Face	0	20175	50	0	Ant 0	1	w/	-	1.00	17.50	17.41	1.02	-0.13	0.203	0.21
	LTE 4	QPSK20M	Top Side	0	20175	50	0	Ant 0	1	w/	-	1.00	17.50	17.41	1.02	-0.17	0.601	0.61
	LTE 4	QPSK20M	Top Side	0	20050	1	0	Ant 0	1	w/	-	1.00	17.50	17.39	1.03	0.14	0.619	0.64
5	LTE 4	QPSK20M	Top Side	0	20300	1	0	Ant 0	1	w/	-	1.00	17.50	17.41	1.02	0.01	0.708	0.72
	LTE 4	QPSK20M	Top Side	0	20300	1	0	Ant 0	2	w/	-	1.00	17.50	17.41	1.02	-0.03	0.6	



Body SAR Test Result

System & Position								DUT Configuration				SAR							
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	RB#	RB offset	Ant Status	Battery	Power Reduction	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	
	LTE 7	QPSK20M	Rear Face	7	21350	1	0	Ant 0	1	w/o	-	1.00	24.00	23.38	1.15	0.03	0.508	0.58	
	LTE 7	QPSK20M	Left Side	0	21350	1	0	Ant 0	1	w/o	-	1.00	24.00	23.38	1.15	0	<0.001	0.00	
	LTE 7	QPSK20M	Right Side	0	21350	1	0	Ant 0	1	w/o	-	1.00	24.00	23.38	1.15	-0.17	0.153	0.18	
	LTE 7	QPSK20M	Top Side	22	21350	1	0	Ant 0	1	w/o	-	1.00	24.00	23.38	1.15	-0.06	0.542	0.62	
	LTE 7	QPSK20M	Bottom Side	0	21350	1	0	Ant 0	1	w/o	-	1.00	24.00	23.38	1.15	0	<0.001	0.00	
	LTE 7	QPSK20M	Rear Face	7	21350	50	0	Ant 0	1	w/o	-	1.00	23.00	22.22	1.20	0.06	0.346	0.42	
	LTE 7	QPSK20M	Left Side	0	21350	50	0	Ant 0	1	w/o	-	1.00	23.00	22.22	1.20	0	<0.001	0.00	
	LTE 7	QPSK20M	Right Side	0	21350	50	0	Ant 0	1	w/o	-	1.00	23.00	22.22	1.20	-0.02	0.109	0.13	
	LTE 7	QPSK20M	Top Side	22	21350	50	0	Ant 0	1	w/o	-	1.00	23.00	22.22	1.20	0	0.396	0.48	
	LTE 7	QPSK20M	Bottom Side	0	21350	50	0	Ant 0	1	w/o	-	1.00	23.00	22.22	1.20	0	<0.001	0.00	
	LTE 7	QPSK20M	Rear Face	0	21350	1	0	Ant 0	1	w/	-	1.00	17.00	16.85	1.04	0.18	0.385	0.40	
	LTE 7	QPSK20M	Top Side	0	21350	1	0	Ant 0	1	w/	-	1.00	17.00	16.85	1.04	0.04	0.691	0.72	
	LTE 7	QPSK20M	Rear Face	0	21350	50	0	Ant 0	1	w/	-	1.00	17.00	16.82	1.04	0.09	0.33	0.34	
	LTE 7	QPSK20M	Top Side	0	21350	50	0	Ant 0	1	w/	-	1.00	17.00	16.82	1.04	0.19	0.575	0.60	
7	LTE 7	QPSK20M	Top Side	0	20850	1	0	Ant 0	1	w/	-	1.00	17.00	16.76	1.06	-0.05	0.746	0.79	
	LTE 7	QPSK20M	Top Side	0	21100	1	0	Ant 0	1	w/	-	1.00	17.00	16.78	1.05	-0.11	0.694	0.73	
	CA_7C	QPSK20M	Top Side	0	PCC: 20850 SCC: 21048	PCC: 1 SCC: 1	PCC: 99 SCC: 0	Ant 0	1	w/	-	1.00	17.00	16.63	1.09	0.1	0.673	0.73	
	LTE 7	QPSK20M	Top Side	0	20850	1	0	Ant 0	2	w/	-	1.00	17.00	16.76	1.06	-0.13	0.69	0.73	
	LTE 12	QPSK10M	Rear Face	7	23130	1	0	Ant 0	1	w/o	-	1.00	24.00	23.16	1.21	-0.06	0.172	0.21	
	LTE 12	QPSK10M	Left Side	0	23130	1	0	Ant 0	1	w/o	-	1.00	24.00	23.16	1.21	0	<0.001	0.00	
	LTE 12	QPSK10M	Right Side	0	23130	1	0	Ant 0	1	w/o	-	1.00	24.00	23.16	1.21	-0.08	0.071	0.09	
	LTE 12	QPSK10M	Top Side	22	23130	1	0	Ant 0	1	w/o	-	1.00	24.00	23.16	1.21	0.03	0.078	0.09	
	LTE 12	QPSK10M	Bottom Side	0	23130	1	0	Ant 0	1	w/o	-	1.00	24.00	23.16	1.21	0	<0.001	0.00	
	LTE 12	QPSK10M	Rear Face	7	23130	25	0	Ant 0	1	w/o	-	1.00	23.00	22.17	1.21	-0.11	0.135	0.16	
	LTE 12	QPSK10M	Left Side	0	23130	25	0	Ant 0	1	w/o	-	1.00	23.00	22.17	1.21	0	<0.001	0.00	
	LTE 12	QPSK10M	Right Side	0	23130	25	0	Ant 0	1	w/o	-	1.00	23.00	22.17	1.21	0.13	0.056	0.07	
	LTE 12	QPSK10M	Top Side	22	23130	25	0	Ant 0	1	w/o	-	1.00	23.00	22.17	1.21	0.18	0.061	0.07	
	LTE 12	QPSK10M	Bottom Side	0	23130	25	0	Ant 0	1	w/o	-	1.00	23.00	22.17	1.21	0	<0.001	0.00	
	LTE 12	QPSK10M	Rear Face	0	23130	1	0	Ant 0	1	w/	-	1.00	23.00	22.92	1.02	-0.1	0.242	0.25	
8	LTE 12	QPSK10M	Top Side	0	23130	1	0	Ant 0	1	w/	-	1.00	23.00	22.92	1.02	0.01	0.724	0.74	
	LTE 12	QPSK10M	Rear Face	0	23130	25	0	Ant 0	1	w/	-	1.00	23.00	22.89	1.03	0.18	0.201	0.21	
	LTE 12	QPSK10M	Top Side	0	23130	25	0	Ant 0	1	w/	-	1.00	23.00	22.89	1.03	0.12	0.48	0.49	
	LTE 12	QPSK10M	Top Side	0	23060	1	0	Ant 0	1	w/	-	1.00	23.00	22.69	1.07	-0.04	0.583	0.62	
	LTE 12	QPSK10M	Top Side	0	23095	1	0	Ant 0	1	w/	-	1.00	23.00	22.78	1.05	0.19	0.582	0.61	
	LTE 12	QPSK10M	Top Side	0	23130	1	0	Ant 0	2	w/	-	1.00	23.00	22.92	1.02	0	0.716	0.73	
	LTE 13	QPSK10M	Rear Face	7	23230	1	0	Ant 0	1	w/o	-	1.00	24.00	22.98	1.26	-0.05	0.201	0.25	
	LTE 13	QPSK10M	Left Side	0	23230	1	0	Ant 0	1	w/o	-	1.00	24.00	22.98	1.26	0	<0.001	0.00	
	LTE 13	QPSK10M	Right Side	0	23230	1	0	Ant 0	1	w/o	-	1.00	24.00	22.98	1.26	-0.16	0.086	0.11	
	LTE 13	QPSK10M	Top Side	22	23230	1	0	Ant 0	1	w/o	-	1.00	24.00	22.98	1.26	0.05	0.105	0.13	
	LTE 13	QPSK10M	Bottom Side	0	23230	1	0	Ant 0	1	w/o	-	1.00	24.00	22.98	1.26	0	<0.001	0.00	
	LTE 13	QPSK10M	Rear Face	7	23230	25	0	Ant 0	1	w/o	-	1.00	23.00	21.95	1.27	0	0.167	0.21	
	LTE 13	QPSK10M	Left Side	0	23230	25	0	Ant 0	1	w/o	-	1.00	23.00	21.95	1.27	0	<0.001	0.00	
	LTE 13	QPSK10M	Right Side	0	23230	25	0	Ant 0	1	w/o	-	1.00	23.00	21.95	1.27	0.15	0.079	0.10	
	LTE 13	QPSK10M	Top Side	22	23230	25	0	Ant 0	1	w/o	-	1.00	23.00	21.95	1.27	-0.18	0.081	0.10	
	LTE 13	QPSK10M	Bottom Side	0	23230	25	0	Ant 0	1	w/o	-	1.00	23.00	21.95	1.27	0	<0.001	0.00	
	LTE 13	QPSK10M	Rear Face	0	23230	1	0	Ant 0	1	w/	-	1.00	21.00	20.77	1.05	0.13	0.187	0.20	
9	LTE 13	QPSK10M	Top Side	0	23230	1	0	Ant 0	1	w/	-	1.00	21.00	20.77	1.05	-0.01	0.715	0.75	
	LTE 13	QPSK10M	Rear Face	0	23230	25	0	Ant 0	1	w/	-	1.00	21.00	20.76	1.06	0.18	0.155	0.16	
	LTE 13	QPSK10M	Top Side	0	23230	25	0	Ant 0	1	w/	-	1.00	21.00	20.76	1.06	-0.08	0.605	0.64	
	LTE 13	QPSK10M	Top Side	0	23230	1	0	Ant 0	2	w/	-	1.00	21.00	20.77	1.05	0.16	0.682	0.72	
	LTE 14	QPSK10M	Rear Face	7	23330	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	-0.01	0.216	0.28	
	LTE 14	QPSK10M	Left Side	0	23330	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	0	<0.001	0.00	
	LTE 14	QPSK10M	Right Side	0	23330	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	0.19	0.117	0.15	
	LTE 14	QPSK10M	Top Side	22	23330	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	-0.09	0.123	0.16	
	LTE 14	QPSK10M	Bottom Side	0	23330	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	0	<0.001	0.00	
	LTE 14	QPSK10M	Rear Face	7	23330	25	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	-0.05	0.185	0.24	
	LTE 14	QPSK10M	Left Side	0	23330	25	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0	<0.001	0.00	
	LTE 14	QPSK10M	Right Side	0	23330	25	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	-0.07	0.081	0.11	
	LTE 14	QPSK10M	Top Side	22	23330	25	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	-0.07	0.093	0.12	
	LTE 14	QPSK10M	Bottom Side	0	23330	25	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0	<0.001	0.00	
	LTE 14	QPSK10M	Rear Face	0	23330	1	0	Ant 0	1	w/	-	1.00	21.00	20.87	1.03	-0.14	0.197	0.20	
10	LTE 14	QPSK10M	Top Side	0	23330	1	0	Ant 0	1	w/	-	1.00	21.00	20.87	1.03	0.01	0.77	0.79	
	LTE 14	QPSK10M	Rear Face	0	23330	25	0	Ant 0	1	w/	-	1.00	21.00	20.79	1.05	-0.18	0.171	0.18	
	LTE 14	QPSK10M	Top Side	0	23330	25	0	Ant 0	1	w/	-	1.00	21.00	20.79	1.05	0.12	0.639	0.67	
	LTE 14	QPSK10M	Top Side	0	23330	1	0	Ant 0	2	w/	-	1.00	21.00	20.87	1.03	-0.03	0.748	0.77	
	LTE 25	QPSK20M	Rear Face	7	26140	1	0	Ant 0	1	w/o	-	1.00	24.00	22.58	1.39	0.01	0.463	0.64	
	LTE 25	QPSK20M	Left Side	0	26140	1	0	Ant 0	1	w/o	-	1.00	24.00	22.58	1.39	0	<0.001	0.00	



Body SAR Test Result

Body SAR Test Result																		
System & Position								DUT Configuration				SAR						
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	RB#	RB offset	Ant Status	Battery	Power Reduction	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
	LTE 26	QPSK15M	Rear Face	7	26965	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	-0.01	0.265	0.34
	LTE 26	QPSK15M	Left Side	0	26965	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	0	<0.001	0.00
	LTE 26	QPSK15M	Right Side	0	26965	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	-0.09	0.118	0.15
	LTE 26	QPSK15M	Top Side	22	26965	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	-0.17	0.155	0.20
	LTE 26	QPSK15M	Bottom Side	0	26965	1	0	Ant 0	1	w/o	-	1.00	24.00	22.89	1.29	0	<0.001	0.00
	LTE 26	QPSK15M	Rear Face	7	26965	36	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	-0.06	0.217	0.28
	LTE 26	QPSK15M	Left Side	0	26965	36	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0	<0.001	0.00
	LTE 26	QPSK15M	Right Side	0	26965	36	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0.16	0.096	0.12
	LTE 26	QPSK15M	Top Side	22	26965	36	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0.02	0.127	0.17
	LTE 26	QPSK15M	Bottom Side	0	26965	36	0	Ant 0	1	w/o	-	1.00	23.00	21.86	1.30	0	<0.001	0.00
	LTE 26	QPSK15M	Rear Face	0	26965	1	0	Ant 0	1	w/	-	1.00	19.00	18.78	1.05	0.06	0.146	0.15
12	LTE 26	QPSK15M	Top Side	0	26965	1	0	Ant 0	1	w/	-	1.00	19.00	18.78	1.05	-0.02	0.641	0.67
	LTE 26	QPSK15M	Rear Face	0	26965	36	0	Ant 0	1	w/	-	1.00	19.00	18.63	1.09	-0.06	0.119	0.13
	LTE 26	QPSK15M	Top Side	0	26965	36	0	Ant 0	1	w/	-	1.00	19.00	18.63	1.09	0.04	0.514	0.56
	LTE 26	QPSK15M	Top Side	0	26765	1	0	Ant 0	1	w/	-	1.00	19.00	18.73	1.06	0.19	0.53	0.56
	LTE 26	QPSK15M	Top Side	0	26865	1	0	Ant 0	1	w/	-	1.00	19.00	18.76	1.06	-0.19	0.594	0.63
	LTE 26	QPSK15M	Top Side	0	26965	1	0	Ant 0	2	w/	-	1.00	19.00	18.78	1.05	-0.06	0.617	0.65
																		-
	LTE 41	QPSK20M	Rear Face	7	41490	1	0	Ant 0	1	w/o	-	1.00	24.00	23.26	1.19	0.19	0.231	0.27
	LTE 41	QPSK20M	Left Side	0	41490	1	0	Ant 0	1	w/o	-	1.00	24.00	23.26	1.19	0	<0.001	0.00
	LTE 41	QPSK20M	Right Side	0	41490	1	0	Ant 0	1	w/o	-	1.00	24.00	23.26	1.19	0.15	0.125	0.15
	LTE 41	QPSK20M	Top Side	22	41490	1	0	Ant 0	1	w/o	-	1.00	24.00	23.26	1.19	-0.02	0.328	0.39
	LTE 41	QPSK20M	Bottom Side	0	41490	1	0	Ant 0	1	w/o	-	1.00	24.00	23.26	1.19	0	<0.001	0.00
	LTE 41	QPSK20M	Rear Face	7	41490	50	0	Ant 0	1	w/o	-	1.00	23.00	22.71	1.07	0.06	0.191	0.20
	LTE 41	QPSK20M	Left Side	0	41490	50	0	Ant 0	1	w/o	-	1.00	23.00	22.71	1.07	0	<0.001	0.00
	LTE 41	QPSK20M	Right Side	0	41490	50	0	Ant 0	1	w/o	-	1.00	23.00	22.71	1.07	-0.18	0.108	0.12
	LTE 41	QPSK20M	Top Side	22	41490	50	0	Ant 0	1	w/o	-	1.00	23.00	22.71	1.07	0.08	0.263	0.28
	LTE 41	QPSK20M	Bottom Side	0	41490	50	0	Ant 0	1	w/o	-	1.00	23.00	22.71	1.07	0	<0.001	0.00
	LTE 41	QPSK20M	Rear Face	0	41490	1	0	Ant 0	1	w/	-	1.00	19.00	18.91	1.02	-0.01	0.151	0.15
	LTE 41	QPSK20M	Top Side	0	41490	1	0	Ant 0	1	w/	-	1.00	19.00	18.91	1.02	0.15	0.519	0.53
	LTE 41	QPSK20M	Rear Face	0	41490	50	0	Ant 0	1	w/	-	1.00	19.00	18.87	1.03	0.01	0.126	0.13
	LTE 41	QPSK20M	Top Side	0	41490	50	0	Ant 0	1	w/	-	1.00	19.00	18.87	1.03	0.05	0.465	0.48
14	LTE 41	QPSK20M	Top Side	0	39750	1	0	Ant 0	1	w/	-	1.00	19.00	18.81	1.04	0.02	0.761	0.79
	LTE 41	QPSK20M	Top Side	0	40185	1	0	Ant 0	1	w/	-	1.00	19.00	18.82	1.04	-0.18	0.579	0.60
	LTE 41	QPSK20M	Top Side	0	40620	1	0	Ant 0	1	w/	-	1.00	19.00	18.83	1.04	-0.13	0.485	0.50
	LTE 41	QPSK20M	Top Side	0	41055	1	0	Ant 0	1	w/	-	1.00	19.00	18.87	1.03	-0.11	0.493	0.51
	CA_41C	QPSK20M	Top Side	0	PCC: 41055 SCC: 41253	PCC: 1 SCC: 1	PCC: 99 SCC: 0	Ant 0	1	w/	-	1.00	19.00	18.61	1.09	-0.01	0.431	0.47
	LTE 41	QPSK20M	Top Side	0	39750	1	0	Ant 0	2	w/	-	1.00	19.00	18.81	1.04	0.11	0.658	0.68
																		-



BUREAU
VERITAS

Body SAR Test Result

System & Position										DUT Configuration			SAR							
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	RB#	RB offset	Ant Status	Battery	Power Reduction	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)		
	LTE 48	QPSK20M	Rear Face	7	56640	1	0	Ant 0	1	w/o	-	1.00	23.00	22.28	1.18	0.04	0.214	0.25		
	LTE 48	QPSK20M	Left Side	0	56640	1	0	Ant 0	1	w/o	-	1.00	23.00	22.28	1.18	0	<0.001	0.00		
	LTE 48	QPSK20M	Right Side	0	56640	1	0	Ant 0	1	w/o	-	1.00	23.00	22.28	1.18	0.01	0.131	0.15		
	LTE 48	QPSK20M	Top Side	22	56640	1	0	Ant 0	1	w/o	-	1.00	23.00	22.28	1.18	0.11	0.193	0.23		
	LTE 48	QPSK20M	Bottom Side	0	56640	1	0	Ant 0	1	w/o	-	1.00	23.00	22.28	1.18	0	<0.001	0.00		
	LTE 48	QPSK20M	Rear Face	7	56640	50	0	Ant 0	1	w/o	-	1.00	22.00	21.27	1.18	-0.15	0.157	0.19		
	LTE 48	QPSK20M	Left Side	0	56640	50	0	Ant 0	1	w/o	-	1.00	22.00	21.27	1.18	0	<0.001	0.00		
	LTE 48	QPSK20M	Right Side	0	56640	50	0	Ant 0	1	w/o	-	1.00	22.00	21.27	1.18	0.04	0.11	0.13		
	LTE 48	QPSK20M	Top Side	22	56640	50	0	Ant 0	1	w/o	-	1.00	22.00	21.27	1.18	0.06	0.155	0.18		
	LTE 48	QPSK20M	Bottom Side	0	56640	50	0	Ant 0	1	w/o	-	1.00	22.00	21.27	1.18	0	<0.001	0.00		
	LTE 48	QPSK20M	Rear Face	0	56640	1	0	Ant 0	1	w/	-	1.00	17.00	16.98	1.00	0.06	0.129	0.13		
	LTE 48	QPSK20M	Top Side	0	56640	1	0	Ant 0	1	w/	-	1.00	17.00	16.98	1.00	0	0.403	0.40		
	LTE 48	QPSK20M	Rear Face	0	56640	50	0	Ant 0	1	w/	-	1.00	17.00	16.97	1.01	0.18	0.092	0.09		
	LTE 48	QPSK20M	Top Side	0	56640	50	0	Ant 0	1	w/	-	1.00	17.00	16.97	1.01	-0.15	0.335	0.34		
17	LTE 48	QPSK20M	Top Side	0	55340	1	0	Ant 0	1	w/	-	1.00	17.00	16.86	1.03	-0.03	0.727	0.75		
	LTE 48	QPSK20M	Top Side	0	55780	1	0	Ant 0	1	w/	-	1.00	17.00	16.89	1.03	-0.01	0.623	0.64		
	LTE 48	QPSK20M	Top Side	0	56210	1	0	Ant 0	1	w/	-	1.00	17.00	16.93	1.02	-0.11	0.481	0.49		
	CA 48C	QPSK20M	Top Side	0	PCC: 55340 SCC: 55538	PCC: 1 SCC: 1	PCC: 99 SCC: 0	Ant 0	1	w/	-	1.00	17.00	16.34	1.16	0.07	0.709	0.82		
	LTE 48	QPSK20M	Top Side	0	55340	1	0	Ant 0	2	w/	-	1.00	17.00	16.86	1.03	0.02	0.725	0.75		
	LTE 66	QPSK20M	Rear Face	7	132322	1	0	Ant 0	1	w/o	-	1.00	24.00	23.11	1.23	0	0.337	0.41		
	LTE 66	QPSK20M	Left Side	0	132322	1	0	Ant 0	1	w/o	-	1.00	24.00	23.11	1.23	0	<0.001	0.00		
	LTE 66	QPSK20M	Right Side	0	132322	1	0	Ant 0	1	w/o	-	1.00	24.00	23.11	1.23	0.07	0.26	0.32		
	LTE 66	QPSK20M	Top Side	22	132322	1	0	Ant 0	1	w/o	-	1.00	24.00	23.11	1.23	0.15	0.199	0.24		
	LTE 66	QPSK20M	Bottom Side	0	132322	1	0	Ant 0	1	w/o	-	1.00	24.00	23.11	1.23	0	<0.001	0.00		
	LTE 66	QPSK20M	Rear Face	7	132322	50	0	Ant 0	1	w/o	-	1.00	23.00	22.05	1.24	-0.11	0.283	0.35		
	LTE 66	QPSK20M	Left Side	0	132322	50	0	Ant 0	1	w/o	-	1.00	23.00	22.05	1.24	0	<0.001	0.00		
	LTE 66	QPSK20M	Right Side	0	132322	50	0	Ant 0	1	w/o	-	1.00	23.00	22.05	1.24	0.17	0.217	0.27		
	LTE 66	QPSK20M	Top Side	22	132322	50	0	Ant 0	1	w/o	-	1.00	23.00	22.05	1.24	-0.11	0.16	0.20		
	LTE 66	QPSK20M	Bottom Side	0	132322	50	0	Ant 0	1	w/o	-	1.00	23.00	22.05	1.24	0	<0.001	0.00		
	LTE 66	QPSK20M	Rear Face	0	132322	1	0	Ant 0	1	w/	-	1.00	17.50	17.48	1.00	-0.03	0.233	0.23		
	LTE 66	QPSK20M	Top Side	0	132322	1	0	Ant 0	1	w/	-	1.00	17.50	17.48	1.00	-0.02	0.691	0.69		
	LTE 66	QPSK20M	Rear Face	0	132322	50	0	Ant 0	1	w/	-	1.00	17.50	17.39	1.03	0.11	0.187	0.19		
	LTE 66	QPSK20M	Top Side	0	132322	50	0	Ant 0	1	w/	-	1.00	17.50	17.39	1.03	-0.18	0.602	0.62		
	LTE 66	QPSK20M	Top Side	0	132072	1	0	Ant 0	1	w/	-	1.00	17.50	17.39	1.03	-0.12	0.641	0.66		
18	LTE 66	QPSK20M	Top Side	0	132572	1	0	Ant 0	1	w/	-	1.00	17.50	17.37	1.03	-0.01	0.766	0.79		
	LTE 66	QPSK20M	Top Side	0	132572	1	0	Ant 0	2	w/	-	1.00	17.50	17.37	1.03	0.08	0.748	0.77		
	LTE 71	QPSK20M	Rear Face	7	133372	1	0	Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0	0.189	0.23		
	LTE 71	QPSK20M	Left Side	0	133372	1	0	Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0	<0.001	0.00		
	LTE 71	QPSK20M	Right Side	0	133372	1	0	Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	-0.01	0.068	0.08		
	LTE 71	QPSK20M	Top Side	22	133372	1	0	Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0.07	0.072	0.09		
	LTE 71	QPSK20M	Bottom Side	0	133372	1	0	Ant 0	1	w/o	-	1.00	24.00	23.18	1.21	0	<0.001	0.00		
	LTE 71	QPSK20M	Rear Face	7	133372	50	0	Ant 0	1	w/o	-	1.00	23.00	22.23	1.19	-0.13	0.148	0.18		
	LTE 71	QPSK20M	Left Side	0	133372	50	0	Ant 0	1	w/o	-	1.00	23.00	22.23	1.19	0	<0.001	0.00		
	LTE 71	QPSK20M	Right Side	0	133372	50	0	Ant 0	1	w/o	-	1.00	23.00	22.23	1.19	0	0.055	0.07		
	LTE 71	QPSK20M	Top Side	22	133372	50	0	Ant 0	1	w/o	-	1.00	23.00	22.23	1.19	-0.13	0.061	0.07		
	LTE 71	QPSK20M	Bottom Side	0	133372	50	0	Ant 0	1	w/o	-	1.00	23.00	22.23	1.19	0	<0.001	0.00		
	LTE 71	QPSK20M	Rear Face	0	133372	1	0	Ant 0	1	w/	-	1.00	23.00	22.86	1.03	0.07	0.323	0.33		
	LTE 71	QPSK20M	Top Side	0	133372	1	0	Ant 0	1	w/	-	1.00	23.00	22.86	1.03	-0.19	0.729	0.75		
	LTE 71	QPSK20M	Rear Face	0	133372	50	0	Ant 0	1	w/	-	1.00	23.00	22.77	1.05	-0.17	0.269	0.28		
	LTE 71	QPSK20M	Top Side	0	133372	50	0	Ant 0	1	w/	-	1.00	23.00	22.77	1.05	0.15	0.618	0.65		
19	LTE 71	QPSK20M	Top Side	0	133222	1	0	Ant 0	1	w/	-	1.00	23.00	22.81	1.04	-0.02	0.761	0.79		
	LTE 71	QPSK20M	Top Side	0	133297	1	0	Ant 0	1	w/	-	1.00	23.00	22.83	1.04	0.13	0.756	0.79		
	LTE 71	QPSK20M	Top Side	0	133222	1	0	Ant 0	2	w/	-	1.00	23.00	22.81	1.04	0.03	0.752	0.78		
																-	-			
	LTE 106	QPSK3M	Rear Face	7	134322	1	0	Ant 0	1	w/o	-	1.00	24.00	22.77	1.33	0	0.285	0.38		
	LTE 106	QPSK3M	Left Side	0	134322	1	0	Ant 0	1	w/o	-	1.00	24.00	22.77	1.33	0	<0.001	0.00		
	LTE 106	QPSK3M	Right Side	0	134322	1	0	Ant 0	1	w/o	-	1.00	24.00	22.77	1.33	0.02	0.152	0.20		
	LTE 106	QPSK3M	Top Side	22	134322	1	0	Ant 0	1	w/o	-	1.00	24.00	22.77	1.33	0.04	0.138	0.18		
	LTE 106	QPSK3M	Bottom Side	0	134322	1	0	Ant 0	1	w/o	-	1.00	24.00	22.77	1.33	0	<0.001	0.00		
	LTE 106	QPSK3M	Rear Face	7	134322	8	0	Ant 0	1	w/o	-	1.00	23.00	21.76	1.33	0.15	0.233	0.31		
	LTE 106	QPSK3M	Left Side	0	134322	8	0	Ant 0	1	w/o	-	1.00	23.00	21.76	1.33	0	<0.001	0.00		
	LTE 106	QPSK3M	Right Side	0	134322	8	0	Ant 0	1	w/o	-	1.00	23.00	21.76	1.33	-0.04	0.115	0.15		
	LTE 106	QPSK3M	Top Side	22	134322	8	0	Ant 0	1	w/o	-	1.00	23.00	21.76	1.33	0.07	0.111	0.15		
	LTE 106	QPSK3M	Bottom Side	0	134322	8	0	Ant 0	1	w/o	-	1.00	23.00	21.76	1.33	0	<0.001	0.00		
	LTE 106	QPSK3M	Rear Face	0	134322	1	0	Ant 0	1	w/	-	1.00	18.50	18.46	1.01	-0.19	0.178	0.18		
20	LTE 106	QPSK3M	Top Side	0	134322	1	0	Ant 0	1	w/	-	1.00	18.50	18.46	1.01	-0.02	0.782	0.79		
	LTE 106	QPSK3M	Rear Face	0	134322	8	0	Ant 0	1	w/	-	1.00	18.50	18.45	1.01	0.14	0.138	0.14		
	LTE 106	QPSK3M	Top Side	0	134322	8	0	Ant 0	1	w/	-	1.00	18.50	18.45	1.01	0.15	0.662	0.67		
	LTE 106	QPSK3M	Top Side	0	134322	1	0	Ant 0	2	w/	-	1.00	18.50	18.46	1.01	-0.01	0.764	0.77		



BUREAU
VERITAS

Body SAR Test Result

Body SAR Test Result																		
System & Position								DUT Configuration			SAR							
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	RB#	RB offset	Ant Status	Battery	Power Reduction	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)
100	WLAN2.4G	802.11b	Left Side	0	13			Ant 1	1		100.00	1.00	13.50	13.22	1.07	0.02	0.346	0.37
101	WLAN5.3G	802.11ac VHT160	Left Side	0	50			Ant 0+1	1		100.00	1.00	12.00	11.32	1.17	-0.13	0.305	0.36
102	WLAN5.6G	802.11ac VHT160	Left Side	0	114			Ant 1	1		0.00	1.00	10.50	10.25	1.06	0.17	0.25	0.27
103	WLAN5.8G	802.11ac VHT80	Left Side	0	155			Ant 0+1	1		0.00	1.00	12.00	11.58	1.10	-0.11	0.303	0.33
104	WLAN5.9G	802.11ac VHT160	Left Side	0	163			Ant 1	1		100.00	1.00	9.00	8.43	1.14	-0.01	0.349	0.40
105	BT	BR	Left Side	0	0			Ant 1	1		77.01	1.30	10.00	9.60	1.10	-0.06	0.25	0.36



BUREAU
VERITAS

SAR and Power Density Test Result																											
System & Position						DUT Configuration			SAR									Power Density									
Plot No.	Band	Mode	Test Position	Separation Distance (mm)	Channel	Sample	Ant Status	Battery	Duty Cycle	Crest Factor	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Scaling Factor	Power Drift (dB)	Measured SAR-1g (W/kg)	Scaled SAR-1g (W/kg)	Measured APD W/m ² (4cm ²)	Scaled APD W/m ² (4cm ²)	Grid Step [λ]	iPD [W/m2]	Scaling Factor for Measurement Uncertainty	Averagin g Area [cm2]	Power Drift [dB]	Normal psPD [W/m2]	Scaled Normal psPD [W/m2]	Total psPD [W/m2]	Scaled Total psPD [W/m2]
106	UNII-S	802.11ax HE160	Left Side	0	47	1	Ant 0+1	1	100.00	1.00	8.00	7.87	1.03	-0.07	0.206	0.21	1.01	1.04	0.0515	7.92	1.545	4.00	-0.04	0.971	1.5	1.72	2.74
									-	1.00	-	-	1	-	-	-	-	-									

Appendix H. Analysis of Simultaneous Transmission.

The analysis of simultaneous transmission SAR are shown as below.

<Possibilities of Simultaneous Transmission>

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Body Exposure Condition
A	WWAN + WLAN 5G MIMO + BT + NFC	Yes
B	WWAN + WLAN 6G MIMO + BT + NFC	Yes
C	WWAN + WLAN 2.4G SISO + WLAN 5G SISO + NFC	Yes
D	WWAN + WLAN 2.4G SISO + WLAN 6G SISO + NFC	Yes

Notes

1. The worst value of simultaneous transmission WLAN/BT/RFID SAR is the combined calculation of refer report No.: SFCDVB-WTW-P25100254-2

Simultaneous Transmission SAR Evaluation (Body)																	
Band	Position	0	1	2	3	4	5	4b	5b	6	7	A(0+3+6+7)	B(0+5+6+7)	C(0+1+2+7)	D(0+1+4+7)	B(0+5b+6+7)	D(0+1+4b+7)
		Max WWAN	Max WLAN 2.4GHz SISO	Max WLAN 5GHz SISO	Max WLAN 5GHz MIMO	Max WLAN 6GHz SISO	Max WLAN 6GHz MIMO	Max WLAN 6GHz SISO	Max WLAN 6GHz MIMO	Max BT Ant 1	NFC	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Total Exposure Ratio	Total Exposure Ratio
		1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	4cm ² W/m ²	4cm ² W/m ²	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg		
WCDMA II	Rear Face	0.48	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.67	0.67	0.70	0.63	0.37	0.35
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.44	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.44	0.44	0.44	0.44	0.28	0.28
	Top Side	0.71	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.35	1.23	1.21	1.03	0.68	0.54
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
WCDMA IV	Rear Face	0.31	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.50	0.50	0.53	0.46	0.26	0.24
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.22	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.22	0.22	0.22	0.22	0.14	0.14
	Top Side	0.73	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.37	1.25	1.23	1.05	0.69	0.55
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
WCDMA V	Rear Face	0.28	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.47	0.47	0.50	0.43	0.24	0.23
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.11	0.11	0.07	0.07
	Top Side	0.69	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.33	1.21	1.19	1.01	0.66	0.53
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 2	Rear Face	0.65	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.84	0.84	0.87	0.80	0.48	0.46
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.57	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.57	0.57	0.57	0.57	0.36	0.36
	Top Side	0.70	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.34	1.22	1.20	1.02	0.67	0.53
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 4	Rear Face	0.53	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.72	0.72	0.75	0.68	0.40	0.38
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.47	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.47	0.47	0.47	0.47	0.29	0.29
	Top Side	0.72	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.36	1.24	1.22	1.04	0.68	0.54
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 5	Rear Face	0.34	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.53	0.53	0.56	0.49	0.28	0.26
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.15	0.15	0.15	0.09	0.09
	Top Side	0.71	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.35	1.23	1.21	1.03	0.68	0.54
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 7	Rear Face	0.58	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.77	0.77	0.80	0.73	0.43	0.41
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.18	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.18	0.18	0.18	0.18	0.11	0.11
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 12	Rear Face	0.25	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.44	0.44	0.47	0.40	0.23	0.21
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.09	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.09	0.09	0.09	0.09	0.06	0.06
	Top Side	0.74	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.38	1.26	1.24	1.06	0.69	0.56
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 13	Rear Face	0.25	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.44	0.44	0.47	0.40	0.23	0.21
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.11	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.11	0.11	0.11	0.11	0.07	0.07
	Top Side	0.75	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.39	1.27	1.25	1.07	0.70	0.56
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 14	Rear Face	0.28	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.47	0.47	0.50	0.43	0.24	0.23
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.15	0.15	0.15	0.09	0.09
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Simultaneous Transmission SAR Evaluation (Body)																	
Band	Position	0	1	2	3	4	5	4b	5b	6	7	A(0+3+6+7)	B(0+5+6+7)	C(0+1+2+7)	D(0+1+4+7)	B(0+5b+6+7)	D(0+1+4b+7)
		Max WWAN	Max WLAN 2.4GHz SISO	Max WLAN 5GHz SISO	Max WLAN 5GHz MIMO	Max WLAN 6GHz SISO	Max WLAN 6GHz MIMO	Max WLAN 6GHz SISO	Max WLAN 6GHz MIMO	Max BT Ant 1	NFC	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Summing result 1g SAR W/kg	Total Exposure Ratio	Total Exposure Ratio
		1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	4cm ² W/m ²	4cm ² W/m ²	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg	1g SAR W/kg
LTE 25	Rear Face	0.64	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.83	0.83	0.86	0.79	0.47	0.45
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	0.50	0.50	0.50	0.31	0.31
	Top Side	0.74	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.38	1.26	1.24	1.06	0.69	0.56
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 26	Rear Face	0.34	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.53	0.53	0.56	0.49	0.28	0.26
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.15	0.15	0.15	0.09	0.09
	Top Side	0.67	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.31	1.19	1.17	0.99	0.65	0.51
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 41	Rear Face	0.27	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.46	0.46	0.49	0.42	0.24	0.22
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.15	0.15	0.15	0.09	0.09
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 48	Rear Face	0.25	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.44	0.44	0.47	0.40	0.23	0.21
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.15	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.15	0.15	0.15	0.15	0.09	0.09
	Top Side	0.75	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.39	1.27	1.25	1.07	0.70	0.56
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 66	Rear Face	0.41	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.60	0.60	0.63	0.56	0.33	0.31
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.32	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.32	0.32	0.32	0.32	0.20	0.20
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 71	Rear Face	0.33	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.52	0.52	0.55	0.48	0.28	0.26
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.08	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.08	0.08	0.08	0.08	0.05	0.05
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
LTE 106	Rear Face	0.38	0.07	0.14	0.08	0.07	0.08	0.00	0.00	0.10	0.01	0.57	0.57	0.60	0.53	0.31	0.29
	Left Side	0.00	0.39	0.40	0.40	0.27	0.33	2.35	2.94	0.37	0.00	0.77	0.70	0.79	0.66	0.53	0.48
	Right Side	0.20	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.20	0.20	0.20	0.20	0.13	0.13
	Top Side	0.79	0.12	0.35	0.27	0.17	0.15	0.00	0.00	0.34	0.03	1.43	1.31	1.29	1.11	0.73	0.59
	Bottom Side	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Appendix J. Calibration of Test Equipment List

Calibration of Test Equipment List are shown as below.

Equipment for SAR Test

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D750V3	1013	Aug. 14, 2025	1 Year
System Validation Dipole	SPEAG	D835V2	4d121	Aug. 14, 2025	1 Year
System Validation Dipole	SPEAG	D1750V2	1055	Sep. 11, 2025	1 Year
System Validation Dipole	SPEAG	D1900V2	5d036	Feb. 12, 2025	1 Year
System Validation Dipole	SPEAG	D2450V2	737	Feb. 12, 2025	1 Year
System Validation Dipole	SPEAG	D2600V2	1020	Aug. 14, 2025	1 Year
System Validation Dipole	SPEAG	D3500V2	1007	Jan. 15, 2025	1 Year
System Validation Dipole	SPEAG	D3700V2	1017	Feb. 14, 2025	1 Year
System Validation Dipole	SPEAG	D5GHzV2	1019	Feb. 11, 2025	1 Year
System Validation Dipole	SPEAG	D6.5GHzV2	1008	Sep. 10, 2025	1 Year
System Verification Source	SPEAG	5G Verification Source 10 GHz	1025	Jan. 14, 2025	1 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	7696	Sep. 11, 2025	1 Year
E-Field Probe	SPEAG	EUmmWV4	9615	May 14, 2025	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1585	May 19, 2025	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1590	Aug. 13, 2025	1 Year
Universal Radio Communication Tester	Anritsu	MT8821C	6201381727	Jul. 31, 2025	1 Year
Analog Signal Generator	R&S	SMA100B	104417	Oct. 20, 2025	1 Year
Mini-Circuits Wideband Amplifier	Mini-Circuits	ZVA-183-S+	434502031A	Jun. 11, 2025	1 Year
Power Meter	Anritsu	ML2495A	1218009	Nov. 22, 2024	1 Year
Power Sensor	Anritsu	MA2411B	1207252	Nov. 22, 2024	1 Year
Thermometer	YFE	YF-160A	120702365	Sep. 10, 2025	1 Year
Dielectric Assessment Kit	SPEAG	DAKS-3.5	1092	May 19, 2025	1 Year
Dielectric Assessment Kit	SPEAG	DAKS_VNA R140	0010917	May 19, 2025	1 Year
Powersource1	SPEAG	SE_UMS_160 BA	1052	Jul. 08, 2025	1 Year

Appendix K. Considerations Related to Bluetooth for Setup and Testing

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

The Bluetooth call box has been used during SAR measurement and the EUT was set to DH5 mode at the maximum output power. Its duty factor was calculated as below and the measured SAR for Bluetooth would be scaled to the 100% transmission duty factor to determine compliance.

The duty factor of Bluetooth signal are shown as below.

<Time-domain plot for Bluetooth transmission signal>



The duty factor of Bluetooth signal has been calculated as following.

$$\text{Duty Factor} = \text{Pulse Width} / \text{Total Period} = (7.63 - 4.75) / (8.49 - 4.75) = 77.01\%$$

Appendix Z. Calibration Certificate for Probe and Dipole

The SPEAG calibration certificates are shown as follows.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
Taoyuan City

Certificate No.

D750V3-1013_Aug25

CALIBRATION CERTIFICATE

Object **D750V3 - SN: 1013**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date **August 14, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
3.5mm mismatch combination	SN: 1152	24-Mar-25 (No. 217-04293)	Mar-26
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	17-Apr-25 (No. DAE4ip-1836_Apr25)	Apr-26

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Setup 1	SN: 1000	27-May-25 (No. 675-ACAD_Source_Box-250527)	May-26
Signal Generator R&S SMB100A	SN: 182081	27-May-25 (No. 675-CAL16-S4588-250527)	May-26
Mismatch; SMA	SN: 1102	24-Apr-25 (No. 675-Mismatch_SMA-250424)	Apr-26
OCP DAK-12	SN: 1029	27-Feb-25 (No. OCP-DAK12-1029_Feb25)	Feb-26
OCP DAK-3.5	SN: 1336	09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: August 14, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with spacer
Zoom Scan Resolution	dx, dy = 6mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	750MHz $\pm$ 1MHz	

HSL parameters at 750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal HSL parameters	22.0 °C	41.9	0.890 mho/m
Measured HSL parameters	(22.0 $\pm$ 0.2)°C	43.2 $\pm$ 6%	0.910 mho/m $\pm$ 6%
HSL temperature change during test	< 0.5 °C		

SAR result with HSL at 750 MHz

SAR averaged over 1 cm ³ (1 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	2.19 W/kg
SAR for nominal HSL parameters	normalized to 1W	8.72 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm ³ (10 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	1.43 W/kg
SAR for nominal HSL parameters	normalized to 1W	5.69 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with HSL at 750 MHz**

Impedance	51.0 Ω – 3.7 j Ω
Return Loss	-28.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.033 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D750V3 – SN1013	750	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	15		CW, 0--	750, 0	9.55	0.91	43.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
Flat V4.9 mod	HSL, 2025-08-14	EX3DV4 – SN7349, 2025-01-10	DAE4ip Sn1836, 2025-04-17

Scans Setup


	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	6.0 x 6.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	All points
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-08-14
psSAR1g [W/Kg]	2.19
psSAR10g [W/Kg]	1.43
Power Drift [dB]	0.00
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 3.36 W/Kg

Impedance Measurement Plot for HSL



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
 Taoyuan City

Certificate No.

D835V2-4d121_Aug25

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d121**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date **August 14, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
3.5mm mismatch combination	SN: 1152	24-Mar-25 (No. 217-04293)	Mar-26
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	17-Apr-25 (No. DAE4ip-1836_Apr25)	Apr-26

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Setup 1	SN: 1000	27-May-25 (No. 675-ACAD_Source_Box-250527)	May-26
Signal Generator R&S SMB100A	SN: 182081	27-May-25 (No. 675-CAL16-S4588-250527)	May-26
Mismatch; SMA	SN: 1102	24-Apr-25 (No. 675-Mismatch_SMA-250424)	Apr-26
OCP DAK-12	SN: 1029	27-Feb-25 (No. OCP-DAK12-1029_Feb25)	Feb-26
OCP DAK-3.5	SN: 1336	09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: August 14, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	15 mm	with spacer
Zoom Scan Resolution	dx, dy = 6mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	835MHz $\pm$ 1MHz	

HSL parameters at 835 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal HSL parameters	22.0 °C	41.5	0.900 mho/m
Measured HSL parameters	(22.0 $\pm$ 0.2) °C	43.0 $\pm$ 6%	0.940 mho/m $\pm$ 6%
HSL temperature change during test	< 0.5 °C		

SAR result with HSL at 835 MHz

SAR averaged over 1 cm ³ (1 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	2.39 W/kg
SAR for nominal HSL parameters	normalized to 1W	9.51 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm ³ (10 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	1.55 W/kg
SAR for nominal HSL parameters	normalized to 1W	6.17 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with HSL at 835 MHz**

Impedance	48.3 Ω – 8.0 j Ω
Return Loss	-21.6 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.394 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D835V2 – SN4d121	835	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	15		CW, 0--	835, 0	9.51	0.94	43.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
Flat V4.9 mod	HSL, 2025-08-14	EX3DV4 – SN7349, 2025-01-10	DAE4ip Sn1836, 2025-04-17

Scans Setup


	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	6.0 x 6.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	All points
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-08-14
psSAR1g [W/Kg]	2.39
psSAR10g [W/Kg]	1.55
Power Drift [dB]	0.02
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 3.74 W/Kg

Impedance Measurement Plot for HSL



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **B.V. ADT**
Taoyuan City

Certificate No. **D1750V2-1055_Sep25**

CALIBRATION CERTIFICATE

Object **D1750V2 - SN: 1055**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date **September 11, 2025**


This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
3.5mm mismatch combination	SN: 1152	24-Mar-25 (No. 217-04293)	Mar-26
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	04-Sep-25 (No. DAE4ip-1836_Sep25)	Sep-26

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Setup 1	SN: 1000	27-May-25 (No. 675-ACAD_Source_Box-250527)	May-26
Signal Generator R&S SMB100A	SN: 182081	27-May-25 (No. 675-CAL16-S4588-250527)	May-26
Mismatch; SMA	SN: 1102	24-Apr-25 (No. 675-Mismatch_SMA-250424)	Apr-26
OCP DAK-12	SN: 1029	27-Feb-25 (No. OCP-DAK12-1029_Feb25)	Feb-26
OCP DAK-3.5	SN: 1336	09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: September 12, 2025			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	17.0.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 6mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	1750MHz $\pm$ 1MHz	

HSL parameters at 1750 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal HSL parameters	22.0 °C	40.1	1.37 mho/m
Measured HSL parameters	(22.0 $\pm$ 0.2)°C	40.8 $\pm$ 6%	1.36 mho/m $\pm$ 6%
HSL temperature change during test	< 0.5 °C		

SAR result with HSL at 1750 MHz

SAR averaged over 1 cm³ (1 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	9.14 W/kg
SAR for nominal HSL parameters	normalized to 1W	36.4 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm³ (10 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	4.86 W/kg
SAR for nominal HSL parameters	normalized to 1W	19.3 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with HSL at 1750 MHz**

Impedance	48.5 Ω – 1.6 j Ω
Return Loss	-33.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.225 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D1750V2 - SN1055	1750	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0---	1750, 0	7.96	1.36	40.8

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-09-11	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2025-09-04

Scans Setup


	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	6.0 x 6.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-09-11
psSAR1g [W/Kg]	9.14
psSAR10g [W/Kg]	4.86
Power Drift [dB]	0.00
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 16.0 W/Kg

Impedance Measurement Plot for HSL



Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
 Taoyuan City

Certificate No.

D1900V2-5d036_Feb25

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d036**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date **February 12, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power Sensor R&S NRP18A	SN: 101859	22-Jul-24 (No. 4030A315008547)	Jul-25
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
Mismatch; Short [S4188] Attenuator [S4423]	SN: 1152	28-Mar-24 (No. 217-04050)	Mar-25
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	28-Oct-24 (No. DAE4ip-1836_Oct24)	Oct-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Source Box	SN: 1000	28-May-24 (No. 675-ACAD_Source_Box-240528)	May-25
Signal Generator R&S SMB100A	SN: 182081	28-May-24 (No. 675-CAL16-S4588-240528)	May-25
Mismatch; SMA	SN: 1102	22-May-24 (No. 675-Mismatch_SMA-240522)	May-25

	Name	Function	Signature
Calibrated by	Leif Klysner	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: February 12, 2025 This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 6mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	1900MHz $\pm$ 1MHz	

Head TSL parameters at 1900 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2)°C	39.2 $\pm$ 6%	1.40 mho/m $\pm$ 6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 1900 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	24 dBm input power	9.94 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	39.6 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	24 dBm input power	5.26 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	20.9 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with Head TSL at 1900 MHz**

Impedance	51.8 Ω + 5.3 j Ω
Return Loss	-25.2 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.195 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D1900V2 - SN5d036	1900	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	1900, 0	7.68	1.40	39.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-02-12	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup


	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	6.0 x 6.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-02-12
psSAR1g [W/Kg]	9.94
psSAR10g [W/Kg]	5.26
Power Drift [dB]	0.01
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 17.5 W/Kg

Impedance Measurement Plot for Head TSL



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
Taoyuan City

Certificate No.

D2450V2-737_Feb25

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 737**

Calibration procedure(s) **QA CAL-05.v12**
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date **February 12, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
Mismatch; Short [S4188] Attenuator [S4423]	SN: 1152	28-Mar-24 (No. 217-04050)	Mar-25
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	28-Oct-24 (No. DAE4ip-1836_Oct24)	Oct-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Source Box	SN: 1000	28-May-24 (No. 675-ACAD_Source_Box-240528)	May-25
Signal Generator R&S SMB100A	SN: 182081	28-May-24 (No. 675-CAL16-S4588-240528)	May-25
Mismatch; SMA	SN: 1102	22-May-24 (No. 675-Mismatch_SMA-240522)	May-25

	Name	Function	Signature
Calibrated by	Leif Klysner	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: February 12, 2025			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)

**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 5mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	2450MHz $\pm$ 1MHz	

Head TSL parameters at 2450 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2)°C	37.8 $\pm$ 6%	1.87 mho/m $\pm$ 6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 2450 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	24 dBm input power	13.3 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.9 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	24 dBm input power	6.24 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.8 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with Head TSL at 2450 MHz**

Impedance	53.4 Ω + 3.7 j Ω
Return Loss	-26.3 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.161 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D2450V2 - SN737	2450	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	2450, 0	7.06	1.87	37.8

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Right	HSL, 2025-02-12	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup

	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	5.0 x 5.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured


Measurement Results

	Zoom Scan
Date	2025-02-12
psSAR1g [W/Kg]	13.3
psSAR10g [W/Kg]	6.24
Power Drift [dB]	0.01
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 27.8 W/Kg

Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client
B.V. ADT
Taoyuan City

Certificate No. **D2600V2-1020_Aug25**

CALIBRATION CERTIFICATE

Object D2600V2 - SN: 1020

Calibration procedure(s) QA CAL-05.v12
Calibration Procedure for SAR Validation Sources between 0.7 - 3 GHz

Calibration date August 14, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
3.5mm mismatch combination	SN: 1152	24-Mar-25 (No. 217-04293)	Mar-26
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	17-Apr-25 (No. DAE4ip-1836_Apr25)	Apr-26

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Setup 1	SN: 1000	27-May-25 (No. 675-ACAD_Source_Box-250527)	May-26
Signal Generator R&S SMB100A	SN: 182081	27-May-25 (No. 675-CAL16-S4588-250527)	May-26
Mismatch; SMA	SN: 1102	24-Apr-25 (No. 675-Mismatch_SMA-250424)	Apr-26
OCP DAK-12	SN: 1029	27-Feb-25 (No. OCP-DAK12-1029_Feb25)	Feb-26
OCP DAK-3.5	SN: 1336	09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: August 14, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 5mm, dz = 1.5mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	2600MHz $\pm$ 1MHz	

HSL parameters at 2600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal HSL parameters	22.0 °C	39.0	1.96 mho/m
Measured HSL parameters	(22.0 $\pm$ 0.2)°C	38.2 $\pm$ 6%	1.99 mho/m $\pm$ 6%
HSL temperature change during test	< 0.5 °C		

SAR result with HSL at 2600 MHz

SAR averaged over 1 cm ³ (1 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	14.2 W/kg
SAR for nominal HSL parameters	normalized to 1W	56.5 W/kg $\pm$ 17.0% (k = 2)

SAR averaged over 10 cm ³ (10 g) of HSL	Condition	
SAR for nominal HSL parameters	24 dBm input power	6.43 W/kg
SAR for nominal HSL parameters	normalized to 1W	25.6 W/kg $\pm$ 16.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with HSL at 2600 MHz**

Impedance	48.3 Ω – 5.9 j Ω
Return Loss	-24.1 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.158 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D2600V2 ~ SN1020	2600	HSL	24

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10	CW, 0--		2600, 0	7.26	1.99	38.2

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-08-14	EX3DV4 ~ SN7349, 2025-01-10	DAE4ip Sn1836, 2025-04-17

Scans Setup


	Zoom Scan
Grid Extents [mm]	30 x 30 x 30
Grid Steps [mm]	5.0 x 5.0 x 1.5
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-08-14
psSAR1g [W/Kg]	14.2
psSAR10g [W/Kg]	6.43
Power Drift [dB]	0.00
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 29.5 W/Kg

Impedance Measurement Plot for HSL



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
Taoyuan City

Certificate No.

D3500V2-1007_Jan25

CALIBRATION CERTIFICATE

Object **D3500V2 - SN: 1007**

Calibration procedure(s) **QA CAL-22.v7**
Calibration Procedure for SAR Validation Sources between 3 - 10 GHz

Calibration date **January 15, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power Sensor R&S NRP18A	SN: 101859	22-Jul-24 (No. 4030A315008547)	Jul-25
Spectrum Analyzer R&S FSV40	SN: 101832	25-Jan-24 (No. 4030-315007551)	Jan-25
Mismatch; Short [S4188] Attenuator [S4423]	SN: 1152	28-Mar-24 (No. 217-04050)	Mar-25
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	28-Oct-24 (No. DAE4ip-1836_Oct24)	Oct-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Source Box	SN: 1000	28-May-24 (No. 675-ACAD_Source_Box-240528)	May-25
Signal Generator R&S SMB100A	SN: 182081	28-May-24 (No. 675-CAL16-S4588-240528)	May-25
Mismatch; SMA	SN: 1102	22-May-24 (No. 675-Mismatch_SMA-240522)	May-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: January 16, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of

Schmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 5mm, dz = 1.4mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	3500MHz $\pm$ 1MHz	

Head TSL parameters at 3500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	37.9	2.91 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2)°C	37.9 $\pm$ 6%	2.93 mho/m $\pm$ 6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 3500 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	6.60 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	66.0 W/kg $\pm$ 19.9% (k = 2)

SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	2.50 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	25.0 W/kg $\pm$ 19.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with Head TSL at 3500 MHz**

Impedance	54.3 Ω – 3.5 j Ω
Return Loss	-25.4 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.141 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D3500V2 - SN1007	3500	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	3500, 0	6.63	2.93	37.9

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-01-15	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup


	Zoom Scan
Grid Extents [mm]	28 x 28 x 28
Grid Steps [mm]	5.0 x 5.0 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-01-15
psSAR1g [W/Kg]	6.60
psSAR10g [W/Kg]	2.50
Power Drift [dB]	-0.08
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 17.3 W/Kg

Impedance Measurement Plot for Head TSL



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client

B.V. ADT
Taoyuan City

Certificate No.

D3700V2-1017_Feb25

CALIBRATION CERTIFICATE

Object D3700V2 - SN: 1017

Calibration procedure(s) QA CAL-22.v7
Calibration Procedure for SAR Validation Sources between 3 - 10 GHz

Calibration date February 14, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
Mismatch; Short [S4188] Attenuator [S4423]	SN: 1152	28-Mar-24 (No. 217-04050)	Mar-25
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	28-Oct-24 (No. DAE4ip-1836_Oct24)	Oct-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Source Box	SN: 1000	28-May-24 (No. 675-ACAD_Source_Box-240528)	May-25
Signal Generator R&S SMB100A	SN: 182081	28-May-24 (No. 675-CAL16-S4588-240528)	May-25
Mismatch; SMA	SN: 1102	22-May-24 (No. 675-Mismatch_SMA-240522)	May-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: February 14, 2025			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

TSL tissue simulating liquid
ConvF sensitivity in TSL / NORM x,y,z
N/A not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 5mm, dz = 1.4mm	Graded Ratio = 1.5 mm (Z direction)
Frequency	3700MHz $\pm$ 1MHz	

Head TSL parameters at 3700 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	37.7	3.12 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2)°C	37.5 $\pm$ 6%	3.08 mho/m $\pm$ 6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 3700 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	6.80 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	68.0 W/kg $\pm$ 19.9% (k = 2)

SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	2.51 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	25.1 W/kg $\pm$ 19.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with Head TSL at 3700 MHz**

Impedance	53.0 Ω – 7.1 j Ω
Return Loss	-22.5 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.139 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D3700V2 - SN1017	3700	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	3700, 0	6.45	3.08	37.5

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-02-14	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup

	Zoom Scan
Grid Extents [mm]	28 x 28 x 28
Grid Steps [mm]	5.0 x 5.0 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.5
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured


Measurement Results

	Zoom Scan
Date	2025-02-14
psSAR1g [W/Kg]	6.80
psSAR10g [W/Kg]	2.51
Power Drift [dB]	-0.08
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 18.4 W/Kg

Impedance Measurement Plot for Head TSL



Calibration Laboratory ofSchmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland

**S** Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**Accreditation No.: **SCS 0108**

Client

B.V. ADT
Taoyuan City

Certificate No.

D5GHzV2-1019_Feb25**CALIBRATION CERTIFICATE**

Object

D5GHzV2 - SN: 1019

Calibration procedure(s)

QA CAL-22.v7**Calibration Procedure for SAR Validation Sources between 3 - 10 GHz**

Calibration date

February 11, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	28-Mar-24 (No. 217-04038)	Mar-25
Power Sensor R&S NRP18A	SN: 101859	22-Jul-24 (No. 4030A315008547)	Jul-25
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
Mismatch; Short [S4188] Attenuator [S4423]	SN: 1152	28-Mar-24 (No. 217-04050)	Mar-25
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	28-Oct-24 (No. DAE4ip-1836_Oct24)	Oct-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Source Box	SN: 1000	28-May-24 (No. 675-ACAD_Source_Box-240528)	May-25
Signal Generator R&S SMB100A	SN: 182081	28-May-24 (No. 675-CAL16-S4588-240528)	May-25
Mismatch; SMA	SN: 1102	22-May-24 (No. 675-Mismatch_SMA-240522)	May-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: February 11, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	16.4.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	10 mm	with spacer
Zoom Scan Resolution	dx, dy = 4mm, dz = 1.4mm	Graded Ratio = 1.4 mm (Z direction)
Frequency	5250MHz $\pm$ 1MHz 5600MHz $\pm$ 1MHz 5800MHz $\pm$ 1MHz	

Head TSL parameters at 5250 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.9	4.71 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2)°C	35.6 $\pm$ 6%	4.53 mho/m $\pm$ 6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 5250 MHz

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	7.83 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	78.3 W/kg $\pm$ 19.9% (k = 2)

SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	2.24 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.4 W/kg $\pm$ 19.5% (k = 2)

Head TSL parameters at 5600 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.5	5.07 mho/m
Measured Head TSL parameters	(22.0 ±0.2)°C	34.9 ±6%	4.90 mho/m ±6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 5600 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	8.08 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	80.8 W/kg ±19.9% (k = 2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	2.32 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	23.2 W/kg ±19.5% (k = 2)

Head TSL parameters at 5800 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	35.3	5.27 mho/m
Measured Head TSL parameters	(22.0 ±0.2)°C	34.7 ±6%	5.11 mho/m ±6%
Head TSL temperature change during test	< 0.5 °C		

SAR result with Head TSL at 5800 MHz

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	7.88 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	78.8 W/kg ±19.9% (k = 2)

SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR for nominal Head TSL parameters	20 dBm input power	2.25 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	22.5 W/kg ±19.5% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with Head TSL at 5250 MHz**

Impedance	51.9 Ω – 2.7 j Ω
Return Loss	-29.9 dB

Antenna Parameters with Head TSL at 5600 MHz

Impedance	57.8 Ω – 0.7 j Ω
Return Loss	-22.7 dB

Antenna Parameters with Head TSL at 5800 MHz

Impedance	56.1 Ω + 3.1 j Ω
Return Loss	-23.8 dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.203 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D5GHzV2 - SN1019	5250	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0---	5250, 0	5.68	4.53	35.6

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-02-11	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup

	Zoom Scan
Grid Extents [mm]	22 x 22 x 22
Grid Steps [mm]	4.0 x 4.0 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.4
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-02-11
psSAR1g [W/Kg]	7.83
psSAR10g [W/Kg]	2.24
Power Drift [dB]	-0.06
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 31.5 W/Kg

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D5GHzV2 - SN1019	5600	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	5600, 0	5.21	4.90	34.9

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-02-11	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup

	Zoom Scan
Grid Extents [mm]	22 x 22 x 22
Grid Steps [mm]	4.0 x 4.0 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.4
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-02-11
psSAR1g [W/Kg]	8.08
psSAR10g [W/Kg]	2.32
Power Drift [dB]	0.00
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 35.0 W/Kg

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D5GHzV2 - SN1019	5800	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	10		CW, 0--	5800, 0	5.17	5.11	34.7

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-02-11	EX3DV4 - SN7349, 2025-01-10	DAE4ip Sn1836, 2024-10-28

Scans Setup

	Zoom Scan
Grid Extents [mm]	22 x 22 x 22
Grid Steps [mm]	4.0 x 4.0 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.4
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured


Measurement Results

	Zoom Scan
Date	2025-02-11
psSAR1g [W/Kg]	7.88
psSAR10g [W/Kg]	2.25
Power Drift [dB]	-0.01
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 35.7 W/Kg

Impedance Measurement Plot for Head TSL





Accredited by the Swiss Accreditation Service (SAS)
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **B.V. ADT**
Taoyuan City

Certificate No. **D6.5GHzV2-1008_Sep25**

CALIBRATION CERTIFICATE

Object **D6.5GHzV2 - SN: 1008**

Calibration procedure(s) **QA CAL-22.v7**
Calibration Procedure for SAR Validation Sources between 3 - 10 GHz

Calibration date **September 10, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
Power Sensor R&S NRP18A	SN: 101859	06-Feb-25 (No. 4030A315009541)	Feb-26
Spectrum Analyzer R&S FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
3.5mm mismatch combination	SN: 1152	24-Mar-25 (No. 217-04293)	Mar-26
OCF DAK-12	SN: 1016	24-Sept-24 (No. OCF-DAK12-1016_Sep24)	Sep-25
OCF DAK-3.5	SN: 1249	23-Sept-24 (No. OCF-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4ip	SN: 1836	04-Sep-25 (No. DAE4ip-1836_Sep25)	Sep-26

Secondary Standards	ID	Check Date (in house)	Scheduled Check
ACAD Setup 1	SN: 1000	27-May-25 (No. 675-ACAD_Source_Box-250527)	May-26
Signal Generator R&S SMB100A	SN: 182081	27-May-25 (No. 675-CAL16-S4588-250527)	May-26
Mismatch; SMA	SN: 1102	24-Apr-25 (No. 675-Mismatch_SMA-250424)	Apr-26
OCF DAK-12	SN: 1029	27-Feb-25 (No. OCF-DAK12-1029_Feb25)	Feb-26
OCF DAK-3.5	SN: 1336	09-Dec-24 (No. OCF-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Paulo Pina	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: September 11, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM x,y,z
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices - Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Additional Documentation

- DASY System Handbook

Methods Applied and Interpretation of Parameters

- *Measurement Conditions*: Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL*: The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss*: These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay*: One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured*: SAR measured at the stated antenna input power.
- *SAR normalized*: SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters*: The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module SAR	17.0.0
Extrapolation	Advanced Extrapolation	
Phantom	Modular Flat Phantom	
Distance Dipole Center - TSL	5 mm	with spacer
Zoom Scan Resolution	dx, dy = 3.4mm, dz = 1.4mm	Graded Ratio = 1.4 mm (Z direction)
Frequency	6500MHz $\pm$ 1MHz	

HSL parameters at 6500 MHz

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal HSL parameters	22.0 °C	34.5	6.07 mho/m
Measured HSL parameters	(22.0 $\pm$ 0.2)°C	35.0 $\pm$ 6%	6.22 mho/m $\pm$ 6%
HSL temperature change during test	< 0.5 °C		

SAR result with HSL at 6500 MHz

SAR averaged over 1 cm³ (1 g) of HSL	Condition	
SAR for nominal HSL parameters	20 dBm input power	29.6 W/kg
SAR for nominal HSL parameters	normalized to 1W	296 W/kg $\pm$ 24.7% (k = 2)

SAR averaged over 8 cm³ (8 g) of HSL	Condition	
SAR for nominal HSL parameters	20 dBm input power	6.62 W/kg
SAR for nominal HSL parameters	normalized to 1W	66.2 W/kg $\pm$ 24.4% (k = 2)

SAR averaged over 10 cm³ (10 g) of HSL	Condition	
SAR for nominal HSL parameters	20 dBm input power	5.44 W/kg
SAR for nominal HSL parameters	normalized to 1W	54.4 W/kg $\pm$ 24.4% (k = 2)

Appendix (Additional assessments outside the scope of SCS 0108)**Antenna Parameters with HSL at 6500 MHz**

Impedance	49.2 Ω – 6.1 j Ω
Return Loss	-24.2 dB

APD (Absorbed Power Density)

APD averaged over 1 cm ³	Condition	
APD measured	20 dBm input power	296 W/kg
APD measured	normalized to 1W	2960 W/kg $\pm$ 29.2% (k = 2)

APD averaged over 4 cm ³	Condition	
APD measured	20 dBm input power	132 W/kg
APD measured	normalized to 1W	1320 W/kg $\pm$ 28.9% (k = 2)

*The reported APD values have been derived using the psSAR1g and psSAR8g.

General Antenna Parameters and Design

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured. The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard. No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------

System Performance Check Report

Summary

Dipole	Frequency [MHz]	TSL	Power [dBm]
D6.5GHzV2 - SN1008	6500	HSL	20

Exposure Conditions

Phantom Section, TSL	Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor	TSL Conductivity [S/m]	TSL Permittivity
Flat	5	CW, 0--		6500, 0	5.49	6.22	35.0

Hardware Setup


Phantom	TSL, Measured Date	Probe, Calibration Date	DAE, Calibration Date
MFP V8.0 Center	HSL, 2025-09-10	EX3DV4 - 5N7349, 2025-01-10	DAE4ip Sn1836, 2025-09-04

Scans Setup


	Zoom Scan
Grid Extents [mm]	22 x 22 x 22
Grid Steps [mm]	3.4 x 3.4 x 1.4
Sensor Surface [mm]	1.4
Graded Grid	Yes
Grading Ratio	1.4
MAIA	N/A
Surface Detection	VMS + 6p
Scan Method	Measured

Measurement Results

	Zoom Scan
Date	2025-09-10
psSAR1g [W/Kg]	29.6
psSAR10g [W/Kg]	5.44
Power Drift [dB]	0.02
Power Scaling	Disabled
Scaling Factor [dB]	
TSL Correction	Positive / Negative



0 dB = 185 W/Kg

Impedance Measurement Plot for HSL



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **B.V. ADT**
Taoyuan City

Certificate No. **5G-Veri10-1025_Jan25**

CALIBRATION CERTIFICATE

Object **5G Verification Source 10 GHz - SN: 1025**

Calibration procedure(s) **QA CAL-45.v5**
Calibration procedure for sources in air > 6 GHz

Calibration date **January 14, 2025**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Cal
Reference Probe SPEAG EUmmWV3	SN: 9374	28-Aug-24 (No. Eumm_9374_Aug24)	Aug-25
DAE4ip	SN: 1602	06-Nov-24 (No. DAE4ip-1602_Nov24)	Nov-25

Secondary Standards	ID	Check Date (in house)	Scheduled Check
Signal Generator R&S SMF100A	SN: 100184	26-Nov-24 (No. 5G-Source-Cal-IHC-202411)	Nov-25
Power Sensor R&S NRP18S-10	SN: 101258	26-Nov-24 (No. 5G-Source-Cal-IHC-202411)	Nov-25
Network Analyzer Keysight E5063A	SN: MY54504221	30-Sept-24 (No. 675-CAL18-S4489-Sep24)	Sep-26

	Name	Function	Signature
Calibrated by	Leif Klysner	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Issued: January 19, 2025



Accredited by the Swiss Accreditation Service (SAS)
**The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates**

Accreditation No.: SCS 0108

Glossary

CW Continuous wave

Calibration is Performed According to the Following Standards

- Internal procedure QA CAL-45, Calibration procedure for sources in air above 6 GHz.
- IEC/IEEE 63195-1, "Assessment of power density of human exposure to radio frequency fields from wireless devices in close proximity to the head and body (frequency range of 6 GHz to 300 GHz)", May 2022

Methods Applied and Interpretation of Parameters

- *Coordinate System*: z-axis in the waveguide horn boresight, x-axis is in the direction of the E-field, y-axis normal to the others in the field scanning plane parallel to the horn flare and horn flange.
- *Measurement Conditions*: (1) 10 GHz: The radiated power is the forward power to the horn antenna minus ohmic and mismatch loss. The forward power is measured prior and after the measurement with a power sensor. During the measurements, the horn is directly connected to the cable and the antenna ohmic and mismatch losses are determined by far-field measurements. (2) 30, 45, 60 and 90 GHz: The verification sources are switched on for at least 30 minutes. Absorbers are used around the probe cub and at the ceiling to minimize reflections.
- *Horn Positioning*: The waveguide horn is mounted vertically on the flange of the waveguide source to allow vertical positioning of the EUmmW probe during the scan. The plane is parallel to the phantom surface. Probe distance is verified using mechanical gauges positioned on the flare of the horn.
- *E-field distribution*: The E-field is measured in two x-y-planes (10mm, 10mm + $\lambda/4$) with a vectorial E-field probe. The E-field value stated as calibration value represents the E-field-maxima and the averaged (1cm² and 4cm²) power density values at 10mm in front of the horn.
- *Field polarization*: Above the open horn, linear polarization of the field is expected. This is verified graphically in the field representation.

Calibrated Quantity

- Local peak E-field (V/m) and average of peak spatial components of the poynting vector (W/m²) averaged over the surface area of 1 cm² and 4cm² at the nominal operational frequency of the verification source. Both square and circular averaging results are listed.

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY8 Module mmWave	V3.2
Phantom	5G Phantom	
Distance Horn Aperture - plane	10 mm	
Number of measured planes	2 (10mm, 10mm + $\lambda/4$)	
Frequency	10.0 GHz $\pm$ 10 MHz	

Calibration Parameters, 10 GHz

Circular Averaging

Distance Horn Aperture to Measurement Plane	Prad ¹ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1cm ²	4cm ²	
10 mm	93.3	152	1.27 dB	60.2	55.9	1.28 dB

Distance Horn Aperture to Measurement Plane	Prad ¹ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1cm ²	4cm ²	
10 mm	93.3	152	1.27 dB	60.0, 60.2, 60.4	55.6, 56.0, 56.2	1.28 dB

Square Averaging

Distance Horn Aperture to Measurement Plane	Prad ¹ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Avg Power Density Avg (psPDn+, psPDtot+, psPDmod+) (W/m ²)		Uncertainty (k = 2)
				1cm ²	4cm ²	
10 mm	93.3	152	1.27 dB	60.2	55.8	1.28 dB

Distance Horn Aperture to Measurement Plane	Prad ¹ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Power Density psPDn+, psPDtot+, psPDmod+ (W/m ²)		Uncertainty (k = 2)
				1cm ²	4cm ²	
10 mm	93.3	152	1.27 dB	60.0, 60.2, 60.4	55.5, 55.9, 56.1	1.28 dB

Max Power Density

Distance Horn Aperture to Measurement Plane	Prad ¹ (mW)	Max E-field (V/m)	Uncertainty (k = 2)	Max Power Density Sn, Stot, Stot (W/m ²)	Uncertainty (k = 2)
10 mm	93.3	152	1.27 dB	61.6, 61.7, 61.9	1.28 dB


¹ Assessed ohmic and mismatch loss plus numerical offset: 0.30 dB

Appendix (Additional assessments outside the scope of SCS 0108)

Antenna Parameters

Impedance, transformed to feed point	51.7 Ω + 0.8 jΩ
Return Loss	-34.9 dB

Impedance Measurement Plot



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 -, Channel 10000.0 (10000.0 MHz)

Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW, 0--	10000.0,10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom -	Air -	EUmmWV3 - SN9374_F1-55GHz, 2024-08-28	DAE4ip - SN1602, 2024-11-06

Scans Setup

Sensor Surface [mm]	10.0
MAIA	MAIA not used

Measurement Results

Scan Type	5G Scan
Date	2025-01-14
Avg. Area [cm ²]	1.00
Avg. Type	Circular Averaging
psPDn+ [W/m ²]	60.0
psPDtot+ [W/m ²]	60.2
psPDmod+ [W/m ²]	60.4
Max(Sn) [W/m ²]	61.6
Max(Stot) [W/m ²]	61.7
Max(Stot) [W/m ²]	61.9
E _{max} [V/m]	152
Power Drift [dB]	0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 --, Channel 10000.0 (10000.0 MHz)

Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	-

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G -	10.0 mm	Validation band	CW, 0--	10000.0,10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom -	Air -	EUmmWV3 - SN9374_F1-55GHz, 2024-08-28	DAE4ip - SN1602, 2024-11-06

Scans Setup

Sensor Surface [mm]	10.0
MAIA	MAIA not used

Measurement Results

Scan Type	5G Scan
Date	2025-01-14
Avg. Area [cm ²]	4.00
Avg. Type	Circular Averaging
psPDn+ [W/m ²]	55.6
psPDtot+ [W/m ²]	56.0
psPDmod+ [W/m ²]	56.2
Max(Sn) [W/m ²]	61.6
Max(Stot) [W/m ²]	61.7
Max(IStotI) [W/m ²]	61.9
E _{max} [V/m]	152
Power Drift [dB]	0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 --, Channel 10000.0 (10000.0 MHz)

Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	--

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G --	10.0 mm	Validation band	CW, 0--	10000.0,10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom --	Air --	EUmmWV3 -- SN9374_F1--55GHz, 2024-08-28	DAE4ip -- SN1602, 2024-11-06

Scans Setup

Sensor Surface [mm]	10.0
MAIA	MAIA not used

Measurement Results

Scan Type	5G Scan
Date	2025-01-14
Avg. Area [cm ²]	1.00
Avg. Type	Square Averaging
psPDn+ [W/m ²]	60.0
psPDtot+ [W/m ²]	60.2
psPDmod+ [W/m ²]	60.4
Max(Sn) [W/m ²]	61.6
Max(Stot) [W/m ²]	61.7
Max(Stot) [W/m ²]	61.9
E _{max} [V/m]	152
Power Drift [dB]	0.01



DASY Report

Measurement Report for 5G Verification Source 10 GHz, UID 0 --, Channel 10000.0 (10000.0 MHz)

Device Under Test Properties

Model, Manufacturer	Dimensions [mm]	IMEI	DUT Type
5G Verification Source 10 GHz	100.0 x 100.0 x 172.0	SN: 1025	--

Exposure Conditions

Phantom Section	Position, Test Distance [mm]	Band	Group, UID	Frequency [MHz], Channel Number	Conversion Factor
5G --	10.0 mm	Validation band	CW, 0--	10000.0,10000	1.0

Hardware Setup


Phantom	Medium	Probe, Calibration Date	DAE, Calibration Date
mmWave Phantom --	Air --	EUmmWV3 - SN9374_F1-55GHz, 2024-08-28	DAE4ip - SN1602, 2024-11-06

Scans Setup

Sensor Surface [mm]	10.0
MAIA	MAIA not used

Measurement Results

Scan Type	5G Scan
Date	2025-01-14
Avg. Area [cm ²]	4.00
Avg. Type	Square Averaging
psPDn+ [W/m ²]	55.5
psPDtot+ [W/m ²]	55.9
psPDmod+ [W/m ²]	56.1
Max(Sn) [W/m ²]	61.6
Max(Stot) [W/m ²]	61.7
Max(Stot) [W/m ²]	61.9
E _{max} [V/m]	152
Power Drift [dB]	0.01





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client

B.V. ADT
Taoyuan City

Certificate No.

EX-7696_Sep25

CALIBRATION CERTIFICATE

Object EX3DV4 - SN:7696

Calibration procedure(s) QA CAL-01.v10, QA CAL-12.v10, QA CAL-14.v7, QA CAL-23.v6,
QA CAL-25.v8
Calibration procedure for dosimetric E-field probes

Calibration date September 11, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^\circ\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Calibration Date (Certificate No.)	Sched. Cal.
Power Sensor R&S NRP-33T	SN: 100967	30-Apr-25 (No. 1020-300791789)	Apr-26
N-type mismatch combination	SN: L1119	26-Mar-25 (No. 217-04292)	Mar-26
OCP DAK-12	SN: 1016	24-Sept-24 (No. OCP-DAK12-1016_Sep24)	Sep-25
OCP DAK-3.5	SN: 1249	23-Sept-24 (No. OCP-DAK3.5-1249_Sep24)	Sep-25
Reference Probe EX3DV4	SN: 7349	10-Jan-25 (No. EX3-7349_Jan25)	Jan-26
DAE4	SN: 1301	07-Nov-24 (No. DAE4-1301_Nov24)	Nov-25

Secondary Standards	ID	Check Date (in house)	Sched. Check
ACAP 2020 Setup 1	SN: L1404	30-Sept-24 (No. Report_ACAP2020E-Cave_20240930s)	Sep-25
OCP DAK-12	SN: 1029	27-Feb-25 (No. OCP-DAK12-1029_Feb25)	Feb-26
OCP DAK-3.5	SN: 1336	09-Dec-24 (No. OCP-DAK3.5-1336_Dec24)	Dec-25

	Name	Function	Signature
Calibrated by	Jeffrey Katzman	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	

Issued: September 11, 2025

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Calibration Laboratory of

Schmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEC/IEEE 62209-1528, "Measurement Procedure For The Assessment Of Specific Absorption Rate Of Human Exposure To Radio Frequency Fields From Hand-Held And Body-Worn Wireless Communication Devices – Part 1528: Human Models, Instrumentation And Procedures (Frequency Range of 4 MHz to 10 GHz)", October 2020.
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

Parameters of Probe: EX3DV4 - SN:7696

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc ($k = 2$)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	0.63	0.63	0.67	$\pm 10.1\%$
DCP (mV) ^B	105.6	105.7	108.1	$\pm 4.7\%$

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B $\text{dB}\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Max Unc ^E $k = 2$
0	Continuous Wave	X	0.00	0.00	1.00	0.00	143.9	$\pm 0.9\%$	$\pm 4.7\%$
		Y	0.00	0.00	1.00		122.3		
		Z	0.00	0.00	1.00		149.3		
10352	Pulse (D=10%, T=5 ms)	X	0.20	70.00	19.52	10.00	23.0	$\pm 2.2\%$	$\pm 9.6\%$
		Y	0.47	70.00	18.56		24.0		
		Z	0.28	70.00	19.11		24.0		
10353	Pulse (D=20%, T=5 ms)	X	0.18	73.01	19.55	6.99	47.0	$\pm 1.7\%$	$\pm 9.6\%$
		Y	0.44	73.01	18.61		48.0		
		Z	0.26	73.01	19.16		47.0		
10354	Pulse (D=40%, T=5 ms)	X	0.17	76.02	19.58	3.98	93.0	$\pm 1.4\%$	$\pm 9.6\%$
		Y	0.41	76.02	18.66		95.0		
		Z	0.24	76.02	19.21		94.0		
10355	Pulse (D=60%, T=5 ms)	X	0.17	77.78	19.60	2.22	140.0	$\pm 1.3\%$	$\pm 9.6\%$
		Y	0.39	77.78	18.69		143.0		
		Z	0.23	77.78	19.23		141.0		
10387	Random (BW=1 MHz, MOD=QPSK)	X	0.00	74.90	20.63	0.13	110.0	$\pm 1.4\%$	$\pm 9.6\%$
		Y	0.00	74.90	19.67		112.0		
		Z	0.00	74.90	20.34		111.0		
10388	Random (BW=10 MHz, MOD=QPSK)	X	1.72	74.78	17.43	0.00	116.0	$\pm 2.4\%$	$\pm 9.6\%$
		Y	1.81	74.78	17.57		119.0		
		Z	1.72	74.78	17.38		117.0		
10396	Random (BW=100 kHz, MOD=64QAM)	X	0.00	73.73	22.80	1.88	81.0	$\pm 5.3\%$	$\pm 9.6\%$
		Y	0.30	80.92	21.30		83.0		
		Z	0.00	73.73	22.39		82.0		
10399	Random (BW=40 MHz, MOD=64QAM)	X	3.97	73.73	17.26	0.00	108.0	$\pm 3.7\%$	$\pm 9.6\%$
		Y	3.94	73.73	17.47		111.0		
		Z	3.92	73.73	17.21		109.0		
10414	Random (BW=40 MHz, HIGH PAR)	X	5.02	71.46	17.26	0.00	80.0	$\pm 1.7\%$	$\pm 9.6\%$
		Y	4.94	71.46	17.47		82.0		
		Z	4.94	71.46	17.21		81.0		

Note: For details on UID parameters see Appendix

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor $k=2$, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E^2 -field uncertainty inside TSL (see Pages 5 and 6).

^B Linearization parameter uncertainty for maximum specified field strength.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Parameters of Probe: EX3DV4 - SN:7696

Sensor Model Parameters

	C1 fF	C2 fF	α V^{-1}	T1 msV^{-2}	T2 msV^{-1}	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
x	12.4	91.72	35.05	4.02	0.00	4.90	0.58	0.00	1.00
y	12.0	88.38	34.67	2.69	0.00	4.90	0.00	0.03	1.01
z	11.6	85.13	34.14	4.41	0.00	4.90	0.46	0.00	1.00

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle	-63.3°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	12 mm
Tip Length	9 mm
Tip Diameter	2.5 mm
Probe Tip to Sensor X Calibration Point	1 mm
Probe Tip to Sensor Y Calibration Point	1 mm
Probe Tip to Sensor Z Calibration Point	1 mm
Recommended Measurement Distance from Surface	1.4 mm

Note: Measurement distance from surface can be increased to 3–4 mm for an *Area Scan* job.

Parameters of Probe: EX3DV4 - SN:7696

Calibration Parameter Determined in HSL

f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc ^H (k = 2)
750	41.9	0.89	9.72	10.36	9.90	0.36	1.27	±11.0%
835	41.5	0.90	9.56	10.19	9.73	0.35	1.27	±11.0%
1750	40.1	1.37	8.00	8.52	8.14	0.35	1.27	±11.0%
1900	40.0	1.40	7.73	8.24	7.87	0.35	1.27	±11.0%
2000	40.0	1.40	7.64	8.14	7.78	0.35	1.27	±11.0%
2300	39.5	1.67	7.34	7.82	7.47	0.35	1.27	±11.0%
2450	39.2	1.80	7.14	7.61	7.27	0.35	1.27	±11.0%
2600	39.0	1.96	6.99	7.44	7.11	0.35	1.27	±11.0%
3300	38.2	2.71	6.68	7.12	6.80	0.35	1.27	±13.1%
3500	37.9	2.91	6.58	7.01	6.70	0.35	1.27	±13.1%
3700	37.7	3.12	6.51	6.94	6.63	0.35	1.27	±13.1%
4800	36.4	4.25	5.90	6.29	6.01	0.35	1.27	±13.1%
4950	36.3	4.40	5.79	6.17	5.89	0.33	1.27	±13.1%
5250	35.9	4.71	5.46	5.81	5.55	0.31	1.27	±13.1%
5600	35.5	5.07	5.10	5.44	5.19	0.28	1.27	±13.1%
5800	35.3	5.27	4.93	5.25	5.02	0.26	1.27	±13.1%

^C Frequency validity above 300 MHz of ±100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ±50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ±10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4–9 MHz, and ConvF assessed at 13 MHz is 9–19 MHz. Above 5 GHz frequency validity can be extended to ±110 MHz.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±5% from the target values (typically better than ±3%) and are valid for TSL with deviations of up to ±10% if SAR correction is applied.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz and below ±2% for frequencies between 3–6 GHz at any distance larger than half the probe tip diameter from the boundary.

^H The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.

Parameters of Probe: EX3DV4 - SN:7696

Calibration Parameter Determined in HSL


f (MHz) ^C	Relative Permittivity ^F	Conductivity ^F (S/m)	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^G (mm)	Unc ^H (k = 2)
6500	34.5	6.07	5.25	5.59	5.34	0.20	1.27	±18.6%

^C Frequency validity is -600/+700 MHz at 6.5 GHz, ±700 MHz at or above 7 GHz, and ±150 MHz at 9.85 GHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

^F The probes are calibrated using tissue simulating liquids (TSL) that deviate for ϵ and σ by less than ±10% from the target values (typically better than ±6%) and are valid for TSL with deviations of up to ±10%.


^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ±1% for frequencies below 3 GHz; below ±2% for frequencies between 3–6 GHz; and below ±4% for frequencies between 6–10 GHz at any distance larger than half the probe tip diameter from the boundary.

^H The stated uncertainty is the total calibration uncertainty (k = 2) of Norm-ConvF. This is equivalent to the uncertainty component with the symbol CF in Table 9 of IEC/IEEE 62209-1528:2020.




Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ (k=2)

Receiving Pattern (ϕ), $\vartheta = 0^\circ$




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{HSL})
(TEM cell, f_{eval} = 1900 MHz)




Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment



Deviation from Isotropy in Liquid



Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
0		Continuous Wave	CW	0.00	±4.7
10010	CAB	Pulse (D=10%, T=100 ms)	Test	10.00	±9.6
10011	CAC	Rel. 99, RMC, QPSK, 5.0 MHz	WCDMA	2.91	±9.6
10012	CAB	DSSS, DBPSK, 1.0 Mbps, 92.5% DC	WLAN	1.87	±9.6
10013	CAB	OFDM, BPSK, 6.0 Mbps, 72.1% DC	WLAN	9.46	±9.6
10021	DAC	Voice, GSMK, 1 slot(s)	GSM	9.39	±9.6
10023	DAC	Data, GSMK, 1 slot(s)	GSM	9.57	±9.6
10024	DAC	Data, GSMK, 2 slot(s)	GSM	6.56	±9.6
10025	DAC	Data, 8PSK, 1 slot(s)	GSM	12.62	±9.6
10026	DAC	Data, 8PSK, 2 slot(s)	GSM	9.55	±9.6
10027	DAC	Data, GSMK, 3 slot(s)	GSM	4.80	±9.6
10028	DAC	Data, GSMK, 4 slot(s)	GSM	3.55	±9.6
10029	DAC	Data, 8PSK, 3 slot(s)	GSM	7.78	±9.6
10030	CAA	BR, DH1, GFSK	Bluetooth	5.30	±9.6
10031	CAA	BR, DH3, GFSK	Bluetooth	1.87	±9.6
10032	CAA	BR, DH5, GFSK	Bluetooth	1.16	±9.6
10033	CAA	EDR, DH1, pi/4-DQPSK	Bluetooth	7.74	±9.6
10034	CAA	EDR, DH3, pi/4-DQPSK	Bluetooth	4.53	±9.6
10035	CAA	EDR, DH5, pi/4-DQPSK	Bluetooth	3.83	±9.6
10036	CAA	EDR, DH1, 8-DPSK	Bluetooth	8.01	±9.6
10037	CAA	EDR, DH3, 8-DPSK	Bluetooth	4.77	±9.6
10038	CAA	EDR, DH5, 8-DPSK	Bluetooth	4.10	±9.6
10039	CAB	RC1, 1xRTT	CDMA2000	4.57	±9.6
10048	CAA	Full Slot, GFSK, 1 slot(s)	DECT	13.80	±9.6
10049	CAA	Double Slot, GFSK, 2 slot(s)	DECT	10.79	±9.6
10056	CAA	TD-SCDMA, QPSK, 1.6 MHz	TD-SCDMA	11.01	±9.6
10058	DAC	Data, 8PSK, 4 slot(s)	GSM	6.52	±9.6
10059	CAB	DSSS, DQPSK, 2.0 Mbps, 87.4% DC	WLAN	2.12	±9.6
10060	CAB	HR-DSSS, DQPSK, 5.5 Mbps, 72.7% DC	WLAN	2.83	±9.6
10061	CAB	HR-DSSS, DQPSK, 11.0 Mbps, 57.5% DC	WLAN	3.60	±9.6
10062	CAE	OFDM, BPSK, 6.0 Mbps, 89.1% DC	WLAN	8.68	±9.6
10063	CAE	OFDM, BPSK, 9.0 Mbps, 85.3% DC	WLAN	8.63	±9.6
10064	CAE	OFDM, QPSK, 12.0 Mbps, 82.0% DC	WLAN	9.09	±9.6
10065	CAE	OFDM, QPSK, 18.0 Mbps, 76.0% DC	WLAN	9.00	±9.6
10066	CAE	OFDM, 16QAM, 24.0 Mbps, 70.6% DC	WLAN	9.38	±9.6
10067	CAE	OFDM, 16QAM, 36.0 Mbps, 62.9% DC	WLAN	10.12	±9.6
10068	CAE	OFDM, 64QAM, 48.0 Mbps, 56.6% DC	WLAN	10.24	±9.6
10069	CAE	OFDM, 64QAM, 54.0 Mbps, 54.4% DC	WLAN	10.56	±9.6
10071	CAB	OFDM, BPSK, 9.0 Mbps, 65.1% DC	WLAN	9.83	±9.6
10072	CAB	OFDM, QPSK, 12.0 Mbps, 60.1% DC	WLAN	9.62	±9.6
10073	CAB	OFDM, QPSK, 18.0 Mbps, 53.1% DC	WLAN	9.94	±9.6
10074	CAB	OFDM, 16QAM, 24.0 Mbps, 48.5% DC	WLAN	10.30	±9.6
10075	CAB	OFDM, 16QAM, 36.0 Mbps, 42.9% DC	WLAN	10.77	±9.6
10076	CAB	OFDM, 64QAM, 48.0 Mbps, 39.5% DC	WLAN	10.94	±9.6
10077	CAB	OFDM, 64QAM, 54.0 Mbps, 38.5% DC	WLAN	11.00	±9.6
10081	CAB	RC3, 1xRTT	CDMA2000	3.97	±9.6
10097	CAC	Rel. 5 HSDPA, QPSK, 5.0 MHz	WCDMA	3.98	±9.6
10098	CAC	Rel. 6 HSUPA, Subset 2, QPSK, 5.0 MHz	WCDMA	3.98	±9.6
10100	CAF	20.0 MHz, QPSK, 100% RB	LTE-FDD	5.67	±9.6
10101	CAF	20.0 MHz, 16QAM, 100% RB	LTE-FDD	6.42	±9.6
10102	CAF	20.0 MHz, 64QAM, 100% RB	LTE-FDD	6.60	±9.6
10103	CAH	20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.29	±9.6
10104	CAH	20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.97	±9.6
10105	CAH	20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.01	±9.6
10108	CAH	10.0 MHz, QPSK, 100% RB	LTE-FDD	5.80	±9.6
10109	CAH	10.0 MHz, 16QAM, 100% RB	LTE-FDD	6.43	±9.6
10110	CAH	5.0 MHz, QPSK, 100% RB	LTE-FDD	5.75	±9.6
10111	CAH	5.0 MHz, 16QAM, 100% RB	LTE-FDD	6.44	±9.6
10112	CAH	10.0 MHz, 64QAM, 100% RB	LTE-FDD	6.59	±9.6
10113	CAH	5.0 MHz, 64QAM, 100% RB	LTE-FDD	6.62	±9.6
10114	CAE	HT40 Greenfield, MCS0 (13.5 Mbps), 99.7% DC	WLAN	8.10	±9.6
10115	CAE	HT40 Greenfield, MCS4 (81.0 Mbps), 99.7% DC	WLAN	8.46	±9.6
10116	CAE	HT40 Greenfield, MCS7 (135.0 Mbps), 99.7% DC	WLAN	8.15	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10117	CAE	HT40 Mixed, MCS0 (13.5 Mbps), 99.7% DC	WLAN	8.07	±9.6
10118	CAE	HT40 Mixed, MCS4 (81.0 Mbps), 99.7% DC	WLAN	8.59	±9.6
10119	CAE	HT40 Mixed, MCS7 (135.0 Mbps), 99.7% DC	WLAN	8.13	±9.6
10140	CAF	15.0 MHz, 16QAM, 100% RB	LTE-FDD	6.49	±9.6
10141	CAF	15.0 MHz, 64QAM, 100% RB	LTE-FDD	6.53	±9.6
10142	CAF	3.0 MHz, QPSK, 100% RB	LTE-FDD	5.73	±9.6
10143	CAF	3.0 MHz, 16QAM, 100% RB	LTE-FDD	6.35	±9.6
10144	CAF	3.0 MHz, 64QAM, 100% RB	LTE-FDD	6.65	±9.6
10145	CAG	1.4 MHz, QPSK, 100% RB	LTE-FDD	5.76	±9.6
10146	CAG	1.4 MHz, 16QAM, 100% RB	LTE-FDD	6.41	±9.6
10147	CAG	1.4 MHz, 64QAM, 100% RB	LTE-FDD	6.72	±9.6
10149	CAF	20.0 MHz, 16QAM, 50% RB	LTE-FDD	6.42	±9.6
10150	CAF	20.0 MHz, 64QAM, 50% RB	LTE-FDD	6.60	±9.6
10151	CAH	20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.28	±9.6
10152	CAH	20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.92	±9.6
10153	CAH	20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.05	±9.6
10154	CAH	10.0 MHz, QPSK, 50% RB	LTE-FDD	5.75	±9.6
10155	CAH	10.0 MHz, 16QAM, 50% RB	LTE-FDD	6.43	±9.6
10156	CAH	5.0 MHz, QPSK, 50% RB	LTE-FDD	5.79	±9.6
10157	CAH	5.0 MHz, 16QAM, 50% RB	LTE-FDD	6.49	±9.6
10158	CAH	10.0 MHz, 64QAM, 50% RB	LTE-FDD	6.62	±9.6
10159	CAH	5.0 MHz, 64QAM, 50% RB	LTE-FDD	6.56	±9.6
10160	CAF	15.0 MHz, QPSK, 50% RB	LTE-FDD	5.82	±9.6
10161	CAF	15.0 MHz, 16QAM, 50% RB	LTE-FDD	6.43	±9.6
10162	CAF	15.0 MHz, 64QAM, 50% RB	LTE-FDD	6.58	±9.6
10166	CAG	1.4 MHz, QPSK, 50% RB	LTE-FDD	5.46	±9.6
10167	CAG	1.4 MHz, 16QAM, 50% RB	LTE-FDD	6.21	±9.6
10168	CAG	1.4 MHz, 64QAM, 50% RB	LTE-FDD	6.79	±9.6
10169	CAF	20.0 MHz, QPSK, 1 RB	LTE-FDD	5.73	±9.6
10170	CAF	20.0 MHz, 16QAM, 1 RB	LTE-FDD	6.52	±9.6
10171	AAF	20.0 MHz, 64QAM, 1 RB	LTE-FDD	6.49	±9.6
10172	CAH	20.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.21	±9.6
10173	CAH	20.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.48	±9.6
10174	CAH	20.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.25	±9.6
10175	CAH	10.0 MHz, QPSK, 1 RB	LTE-FDD	5.72	±9.6
10176	CAH	10.0 MHz, 16QAM, 1 RB	LTE-FDD	6.52	±9.6
10177	CAJ	5.0 MHz, QPSK, 1 RB	LTE-FDD	5.73	±9.6
10178	CAH	5.0 MHz, 16QAM, 1 RB	LTE-FDD	6.52	±9.6
10179	CAH	10.0 MHz, 64QAM, 1 RB	LTE-FDD	6.50	±9.6
10180	CAH	5.0 MHz, 64QAM, 1 RB	LTE-FDD	6.50	±9.6
10181	CAF	15.0 MHz, QPSK, 1 RB	LTE-FDD	5.72	±9.6
10182	CAF	15.0 MHz, 16QAM, 1 RB	LTE-FDD	6.52	±9.6
10183	AAE	15.0 MHz, 64QAM, 1 RB	LTE-FDD	6.50	±9.6
10184	CAF	3.0 MHz, QPSK, 1 RB	LTE-FDD	5.73	±9.6
10185	CAF	3.0 MHz, 16QAM, 1 RB	LTE-FDD	6.51	±9.6
10186	AAF	3.0 MHz, 64QAM, 1 RB	LTE-FDD	6.50	±9.6
10187	CAG	1.4 MHz, QPSK, 1 RB	LTE-FDD	5.73	±9.6
10188	CAG	1.4 MHz, 16QAM, 1 RB	LTE-FDD	6.52	±9.6
10189	AAG	1.4 MHz, 64QAM, 1 RB	LTE-FDD	6.50	±9.6
10193	CAE	HT20 Greenfield, MCS0 (6.5 Mbps), 99.4% DC	WLAN	8.09	±9.6
10194	CAE	HT20 Greenfield, MCS4 (39.0 Mbps), 99.5% DC	WLAN	8.12	±9.6
10195	CAE	HT20 Greenfield, MCS7 (65.0 Mbps), 99.5% DC	WLAN	8.21	±9.6
10196	CAE	HT20 Mixed, MCS0 (6.5 Mbps), 99.4% DC	WLAN	8.10	±9.6
10197	CAE	HT20 Mixed, MCS4 (39.0 Mbps), 99.5% DC	WLAN	8.13	±9.6
10198	CAE	HT20 Mixed, MCS7 (65.0 Mbps), 99.5% DC	WLAN	8.27	±9.6
10219	CAE	HT20 Mixed, MCS0 (7.2 Mbps), 99.3% DC	WLAN	8.03	±9.6
10220	CAE	HT20 Mixed, MCS4 (43.3 Mbps), 99.4% DC	WLAN	8.13	±9.6
10221	CAE	HT20 Mixed, MCS7 (72.2 Mbps), 99.4% DC	WLAN	8.27	±9.6
10222	CAE	HT40 Mixed, MCS0 (15.0 Mbps), 99.7% DC	WLAN	8.06	±9.6
10223	CAE	HT40 Mixed, MCS4 (90.0 Mbps), 99.7% DC	WLAN	8.48	±9.6
10224	CAE	HT40 Mixed, MCS7 (150.0 Mbps), 99.7% DC	WLAN	8.08	±9.6
10225	CAC	Rel. 7 HSPA+, 16QAM, 5.0 MHz	WCDMA	5.97	±9.6
10226	CAC	1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.49	±9.6
10227	CAC	1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.26	±9.6
10228	CAC	1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.22	±9.6
10229	CAE	3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.48	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10230	CAE	3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.25	±9.6
10231	CAE	3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.19	±9.6
10232	CAH	5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.48	±9.6
10233	CAH	5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.25	±9.6
10234	CAH	5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.21	±9.6
10235	CAH	10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.48	±9.6
10236	CAH	10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.25	±9.6
10237	CAH	10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.21	±9.6
10238	CAG	15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.48	±9.6
10239	CAG	15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	10.25	±9.6
10240	CAG	15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 1 RB	LTE-TDD	9.21	±9.6
10241	CAC	1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.82	±9.6
10242	CAC	1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.86	±9.6
10243	CAC	1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.46	±9.6
10244	CAE	3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.06	±9.6
10245	CAE	3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.06	±9.6
10246	CAE	3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.30	±9.6
10247	CAH	5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.91	±9.6
10248	CAH	5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.09	±9.6
10249	CAH	5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.29	±9.6
10250	CAH	10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.81	±9.6
10251	CAH	10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.17	±9.6
10252	CAH	10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.24	±9.6
10253	CAG	15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.90	±9.6
10254	CAG	15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	10.14	±9.6
10255	CAG	15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 50% RB	LTE-TDD	9.20	±9.6
10256	CAC	1.4 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.96	±9.6
10257	CAC	1.4 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.08	±9.6
10258	CAC	1.4 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.34	±9.6
10259	CAE	3.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.98	±9.6
10260	CAE	3.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.97	±9.6
10261	CAE	3.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.24	±9.6
10262	CAH	5.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.83	±9.6
10263	CAH	5.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.16	±9.6
10264	CAH	5.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.23	±9.6
10265	CAH	10.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.92	±9.6
10266	CAH	10.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.07	±9.6
10267	CAH	10.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.30	±9.6
10268	CAG	15.0 MHz, 16QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.06	±9.6
10269	CAG	15.0 MHz, 64QAM, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	10.13	±9.6
10270	CAG	15.0 MHz, QPSK, UL/DL CFG: 1, SSC: 4, 100% RB	LTE-TDD	9.58	±9.6
10274	CAC	Rel. 6 HSUPA Subset 2, beta_d 0, QPSK, 5.0 MHz	WCDMA	4.87	±9.6
10275	CAC	Rel. 6 HSUPA Subset 2, beta_d 15, QPSK, 5.0 MHz	WCDMA	3.96	±9.6
10290	AAB	RC1, SO55, Full frame rate, 1xRTT	CDMA2000	3.91	±9.6
10291	AAB	RC3, SO55, Full frame rate, 1xRTT	CDMA2000	3.46	±9.6
10292	AAB	RC3, SO32, Full frame rate, SCH0 disabled, 1xRTT	CDMA2000	3.39	±9.6
10293	AAB	RC3, SO3, Full frame rate, 1xRTT	CDMA2000	3.50	±9.6
10295	AAB	RC3, SO3, 1/8 frame rate, 1xRTT	CDMA2000	12.49	±9.6
10297	AAE	20.0 MHz, QPSK, 50% RB	LTE-FDD	5.81	±9.6
10298	AAE	3.0 MHz, QPSK, 50% RB	LTE-FDD	5.72	±9.6
10299	AAE	3.0 MHz, 16QAM, 50% RB	LTE-FDD	6.39	±9.6
10300	AAE	3.0 MHz, 64QAM, 50% RB	LTE-FDD	6.60	±9.6
10301	AAA	PUSC, 29:18, QPSK, 5.0 ms, 18 TRAF SYM	WiMAX	12.03	±9.6
10302	AAA	PUSC, 29:18, QPSK, 5.0 ms, 15 TRAF SYM	WiMAX	12.57	±9.6
10303	AAA	PUSC, 31:15, 64QAM, 5.0 ms, 15 TRAF SYM	WiMAX	12.52	±9.6
10304	AAA	PUSC, 29:18, 64QAM, 5.0 ms, 18 TRAF SYM	WiMAX	11.86	±9.6
10305	AAA	PUSC, 31:15, 64QAM, 10.0 ms, 15 TRAF SYM	WiMAX	15.24	±9.6
10306	AAA	PUSC, 29:18, 64QAM, 10.0 ms, 18 TRAF SYM	WiMAX	14.67	±9.6
10307	AAA	PUSC, 29:18, QPSK, 10.0 ms, 18 TRAF SYM	WiMAX	14.49	±9.6
10308	AAA	PUSC, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM	WiMAX	14.46	±9.6
10309	AAA	AMC 2x3, 29:18, 16QAM, 10.0 ms, 18 TRAF SYM	WiMAX	14.58	±9.6
10310	AAA	AMC 2x3, 29:18, QPSK, 10.0 ms, 18 TRAF SYM	WiMAX	14.57	±9.6
10311	AAE	15.0 MHz, QPSK, 100% RB	LTE-FDD	6.06	±9.6
10315	AAB	DSSS, DBPSK, 1.0 Mbps, 96.0% DC	WLAN	1.71	±9.6
10316	AAB	OFDM, BPSK, 6.0 Mbps, 95.9% DC	WLAN	8.36	±9.6
10317	AAE	OFDM, BPSK, 6.0 Mbps, 95.9% DC	WLAN	8.36	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10352	AAA	Pulse (D=10%, T=5 ms)	Generic	10.00	±9.6
10353	AAA	Pulse (D=20%, T=5 ms)	Generic	6.99	±9.6
10354	AAA	Pulse (D=40%, T=5 ms)	Generic	3.98	±9.6
10355	AAA	Pulse (D=60%, T=5 ms)	Generic	2.22	±9.6
10356	AAA	Pulse (D=80%, T=5 ms)	Generic	0.97	±9.6
10387	AAA	Random (BW=1 MHz, MOD=QPSK)	Generic	5.10	±9.6
10388	AAA	Random (BW=10 MHz, MOD=QPSK)	Generic	5.22	±9.6
10396	AAA	Random (BW=100 kHz, MOD=64QAM)	Generic	6.27	±9.6
10399	AAA	Random (BW=40 MHz, MOD=64QAM)	Generic	6.27	±9.6
10400	AAF	VHT20, MCS5 (52.0 Mbps), 99.0% DC	WLAN	8.37	±9.6
10401	AAF	VHT40, MCS5 (108.0 Mbps), 96.7% DC	WLAN	8.60	±9.6
10402	AAF	VHT80, MCS5 (234.0 Mbps), 99.0% DC	WLAN	8.53	±9.6
10403	AAB	Rev. 0, 1xEV-DO	CDMA2000	3.76	±9.6
10404	AAB	Rev. A, 1xEV-DO	CDMA2000	3.77	±9.6
10406	AAB	RC3, SO32, Full frame rate, SCH0 enabled, 1xRTT	CDMA2000	5.22	±9.6
10410	AAH	10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 4, 1 RB	LTE-TDD	7.82	±9.6
10414	AAA	Random (BW=40 MHz, HIGH PAR)	Generic	8.54	±9.6
10415	AAA	DSSS, DBPSK, 1.0 Mbps, 99.9% DC	WLAN	1.54	±9.6
10416	AAA	OFDM, BPSK, 6.0 Mbps, 99.9% DC	WLAN	8.23	±9.6
10417	AAD	OFDM, BPSK, 6.0 Mbps, 99.9% DC	WLAN	8.23	±9.6
10418	AAA	OFDM (LTF), BPSK, 6.0 Mbps, 99.8% DC	WLAN	8.14	±9.6
10419	AAA	OFDM (STF), BPSK, 6.0 Mbps, 99.8% DC	WLAN	8.19	±9.6
10422	AAD	HT20 Greenfield, MCS0 (7.2 Mbps), 99.3% DC	WLAN	8.32	±9.6
10423	AAD	HT20 Greenfield, MCS4 (43.3 Mbps), 99.3% DC	WLAN	8.47	±9.6
10424	AAD	HT20 Greenfield, MCS7 (72.2 Mbps), 99.3% DC	WLAN	8.40	±9.6
10425	AAD	HT40 Greenfield, MCS0 (15.0 Mbps), 99.2% DC	WLAN	8.41	±9.6
10426	AAD	HT40 Greenfield, MCS4 (90.0 Mbps), 99.2% DC	WLAN	8.45	±9.6
10427	AAD	HT40 Greenfield, MCS7 (150.0 Mbps), 99.2% DC	WLAN	8.41	±9.6
10430	AAE	5.0 MHz, 64-QAM, 100% RB	LTE-FDD	8.28	±9.6
10431	AAE	10.0 MHz, 64-QAM, 100% RB	LTE-FDD	8.38	±9.6
10432	AAD	15.0 MHz, 64-QAM, 100% RB	LTE-FDD	8.34	±9.6
10433	AAD	20.0 MHz, 64-QAM, 100% RB	LTE-FDD	8.34	±9.6
10434	AAB	BS Test Model 1, 64 DPCH, 64QAM, 5.0 MHz (DL)	WCDMA	8.60	±9.6
10435	AAG	20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10447	AAE	5.0 MHz, 64-QAM, 100% RB	LTE-FDD	7.56	±9.6
10448	AAE	10.0 MHz, 64-QAM, 100% RB	LTE-FDD	7.53	±9.6
10449	AAD	15.0 MHz, 64-QAM, 100% RB	LTE-FDD	7.51	±9.6
10450	AAD	20.0 MHz, 64-QAM, 100% RB	LTE-FDD	7.48	±9.6
10451	AAB	BS Test Model 1, 64 DPCH, Clipping 44%, 64QAM, 5.0 MHz (DL)	WCDMA	7.59	±9.6
10456	AAD	VHT160, MCS5 (58.5 Mbps), 99.0% DC	WLAN	8.63	±9.6
10457	AAB	Rel. 5 DC-HSDPA, QPSK, 10.0 MHz	WCDMA	6.62	±9.6
10458	AAA	Rev. B, 2 carriers, 1xEV-DO	CDMA2000	6.55	±9.6
10459	AAA	Rev. B, 3 carriers, 1xEV-DO	CDMA2000	8.25	±9.6
10460	AAB	Rel. 99, AMR, QPSK, 5.0 MHz	WCDMA	2.39	±9.6
10461	AAC	1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10462	AAC	1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.30	±9.6
10463	AAC	1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.56	±9.6
10464	AAD	3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10465	AAD	3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.32	±9.6
10466	AAD	3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.57	±9.6
10467	AAG	5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10468	AAG	5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.32	±9.6
10469	AAG	5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.56	±9.6
10470	AAG	10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10471	AAG	10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.32	±9.6
10472	AAG	10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.57	±9.6
10473	AAF	15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	7.82	±9.6
10474	AAF	15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.32	±9.6
10475	AAF	15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.57	±9.6
10477	AAG	20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.32	±9.6
10478	AAG	20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 1 RB	LTE-TDD	8.57	±9.6
10479	AAC	1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.74	±9.6
10480	AAC	1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.18	±9.6
10481	AAC	1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.45	±9.6
10482	AAD	3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.71	±9.6
10483	AAD	3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.39	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10484	AAD	3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.47	±9.6
10485	AAG	5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.59	±9.6
10486	AAG	5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.38	±9.6
10487	AAG	5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.60	±9.6
10488	AAG	10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.70	±9.6
10489	AAG	10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.31	±9.6
10490	AAG	10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.54	±9.6
10491	AAF	15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.74	±9.6
10492	AAF	15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.41	±9.6
10493	AAF	15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.55	±9.6
10494	AAG	20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	7.74	±9.6
10495	AAG	20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.37	±9.6
10496	AAG	20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 50% RB	LTE-TDD	8.54	±9.6
10497	AAC	1.4 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.67	±9.6
10498	AAC	1.4 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.40	±9.6
10499	AAC	1.4 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.68	±9.6
10500	AAD	3.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.67	±9.6
10501	AAD	3.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.44	±9.6
10502	AAD	3.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.52	±9.6
10503	AAG	5.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.72	±9.6
10504	AAG	5.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.31	±9.6
10505	AAG	5.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.54	±9.6
10506	AAG	10.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.74	±9.6
10507	AAG	10.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.36	±9.6
10508	AAG	10.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.55	±9.6
10509	AAF	15.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.99	±9.6
10510	AAF	15.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.49	±9.6
10511	AAF	15.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.51	±9.6
10512	AAG	20.0 MHz, QPSK, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	7.74	±9.6
10513	AAG	20.0 MHz, 16QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.42	±9.6
10514	AAG	20.0 MHz, 64QAM, UL/DL CFG: 0, SSC: 7, 100% RB	LTE-TDD	8.45	±9.6
10515	AAA	DSSS, DQPSK, 2.0 Mbps, 99.0% DC	WLAN	1.58	±9.6
10516	AAA	HR-DSSS, DQPSK, 5.5 Mbps, 99.2% DC	WLAN	1.57	±9.6
10517	AAA	HR-DSSS, DQPSK, 11.0 Mbps, 99.0% DC	WLAN	1.58	±9.6
10518	AAD	OFDM, BPSK, 9.0 Mbps, 98.9% DC	WLAN	8.23	±9.6
10519	AAD	OFDM, QPSK, 12.0 Mbps, 99.0% DC	WLAN	8.39	±9.6
10520	AAD	OFDM, QPSK, 18.0 Mbps, 99.0% DC	WLAN	8.12	±9.6
10521	AAD	OFDM, 16QAM, 24.0 Mbps, 99.0% DC	WLAN	7.97	±9.6
10522	AAD	OFDM, 16QAM, 36.0 Mbps, 99.0% DC	WLAN	8.45	±9.6
10523	AAD	OFDM, 64QAM, 48.0 Mbps, 99.0% DC	WLAN	8.08	±9.6
10524	AAD	OFDM, 64QAM, 54.0 Mbps, 99.0% DC	WLAN	8.27	±9.6
10525	AAD	VHT20, MCS0 (6.5 Mbps), 98.9% DC	WLAN	8.36	±9.6
10526	AAD	VHT20, MCS1 (13.0 Mbps), 99.0% DC	WLAN	8.42	±9.6
10527	AAD	VHT20, MCS2 (19.5 Mbps), 99.0% DC	WLAN	8.21	±9.6
10528	AAD	VHT20, MCS3 (26.0 Mbps), 99.0% DC	WLAN	8.36	±9.6
10529	AAD	VHT20, MCS4 (39.0 Mbps), 99.0% DC	WLAN	8.36	±9.6
10531	AAD	VHT20, MCS6 (58.5 Mbps), 99.0% DC	WLAN	8.43	±9.6
10532	AAD	VHT20, MCS7 (65.0 Mbps), 99.0% DC	WLAN	8.29	±9.6
10533	AAD	VHT20, MCS8 (78.0 Mbps), 99.0% DC	WLAN	8.38	±9.6
10534	AAD	VHT40, MCS0 (13.5 Mbps), 98.9% DC	WLAN	8.45	±9.6
10535	AAD	VHT40, MCS1 (27.0 Mbps), 98.8% DC	WLAN	8.45	±9.6
10536	AAD	VHT40, MCS2 (40.5 Mbps), 98.8% DC	WLAN	8.32	±9.6
10537	AAD	VHT40, MCS3 (54.0 Mbps), 98.7% DC	WLAN	8.44	±9.6
10538	AAD	VHT40, MCS4 (81.0 Mbps), 98.5% DC	WLAN	8.54	±9.6
10540	AAD	VHT40, MCS6 (121.5 Mbps), 98.3% DC	WLAN	8.39	±9.6
10541	AAD	VHT40, MCS7 (135.0 Mbps), 98.3% DC	WLAN	8.46	±9.6
10542	AAD	VHT40, MCS8 (162.0 Mbps), 98.1% DC	WLAN	8.65	±9.6
10543	AAD	VHT40, MCS9 (180.0 Mbps), 98.0% DC	WLAN	8.65	±9.6
10544	AAD	VHT80, MCS0 (29.3 Mbps), 99.0% DC	WLAN	8.47	±9.6
10545	AAD	VHT80, MCS1 (58.5 Mbps), 99.0% DC	WLAN	8.55	±9.6
10546	AAD	VHT80, MCS2 (87.8 Mbps), 99.0% DC	WLAN	8.35	±9.6
10547	AAD	VHT80, MCS3 (117.0 Mbps), 99.0% DC	WLAN	8.49	±9.6
10548	AAD	VHT80, MCS4 (175.5 Mbps), 99.0% DC	WLAN	8.37	±9.6
10550	AAD	VHT80, MCS6 (263.3 Mbps), 99.0% DC	WLAN	8.38	±9.6
10551	AAD	VHT80, MCS7 (292.5 Mbps), 99.0% DC	WLAN	8.50	±9.6
10552	AAD	VHT80, MCS8 (351.0 Mbps), 99.0% DC	WLAN	8.42	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10553	AAD	VHT80, MCS9 (390.0 Mbps), 99.0% DC	WLAN	8.45	±9.6
10554	AAE	VHT160, MCS0 (58.5 Mbps), 99.0% DC	WLAN	8.48	±9.6
10555	AAE	VHT160, MCS1 (117.0 Mbps), 99.0% DC	WLAN	8.47	±9.6
10556	AAE	VHT160, MCS2 (175.5 Mbps), 99.0% DC	WLAN	8.50	±9.6
10557	AAE	VHT160, MCS3 (234.0 Mbps), 99.0% DC	WLAN	8.52	±9.6
10558	AAE	VHT160, MCS4 (351.0 Mbps), 99.0% DC	WLAN	8.61	±9.6
10560	AAE	VHT160, MCS6 (526.5 Mbps), 99.0% DC	WLAN	8.73	±9.6
10561	AAE	VHT160, MCS7 (585.0 Mbps), 99.0% DC	WLAN	8.56	±9.6
10562	AAE	VHT160, MCS8 (702.0 Mbps), 99.0% DC	WLAN	8.69	±9.6
10563	AAE	VHT160, MCS9 (780.0 Mbps), 99.0% DC	WLAN	8.77	±9.6
10564	AAA	OFDM, BPSK, 9.0 Mbps, 98.9% DC	WLAN	8.25	±9.6
10565	AAA	OFDM, QPSK, 12.0 Mbps, 99.0% DC	WLAN	8.45	±9.6
10566	AAA	OFDM, QPSK, 18.0 Mbps, 99.0% DC	WLAN	8.13	±9.6
10567	AAA	OFDM, 16QAM, 24.0 Mbps, 99.0% DC	WLAN	8.00	±9.6
10568	AAA	OFDM, 16QAM, 36.0 Mbps, 99.0% DC	WLAN	8.37	±9.6
10569	AAA	OFDM, 64QAM, 48.0 Mbps, 99.0% DC	WLAN	8.10	±9.6
10570	AAA	OFDM, 64QAM, 54.0 Mbps, 99.0% DC	WLAN	8.30	±9.6
10571	AAA	DSSS, DQPSK, 1.0 Mbps, 90.0% DC	WLAN	1.99	±9.6
10572	AAA	DSSS, DQPSK, 2.0 Mbps, 90.0% DC	WLAN	1.99	±9.6
10573	AAA	HR-DSSS, DQPSK, 5.5 Mbps, 90.1% DC	WLAN	1.98	±9.6
10574	AAA	HR-DSSS, DQPSK, 11.0 Mbps, 90.3% DC	WLAN	1.98	±9.6
10575	AAA	OFDM, BPSK, 6.0 Mbps, 89.9% DC	WLAN	8.59	±9.6
10576	AAA	OFDM, BPSK, 9.0 Mbps, 89.9% DC	WLAN	8.60	±9.6
10577	AAA	OFDM, QPSK, 12.0 Mbps, 90.0% DC	WLAN	8.70	±9.6
10578	AAA	OFDM, QPSK, 18.0 Mbps, 90.0% DC	WLAN	8.49	±9.6
10579	AAA	OFDM, 16QAM, 24.0 Mbps, 90.0% DC	WLAN	8.36	±9.6
10580	AAA	OFDM, 16QAM, 36.0 Mbps, 90.0% DC	WLAN	8.76	±9.6
10581	AAA	OFDM, 64QAM, 48.0 Mbps, 90.0% DC	WLAN	8.35	±9.6
10582	AAA	OFDM, 64QAM, 54.0 Mbps, 90.0% DC	WLAN	8.67	±9.6
10583	AAD	OFDM, BPSK, 6.0 Mbps, 89.9% DC	WLAN	8.59	±9.6
10584	AAD	OFDM, BPSK, 9.0 Mbps, 89.9% DC	WLAN	8.60	±9.6
10585	AAD	OFDM, QPSK, 12.0 Mbps, 90.0% DC	WLAN	8.70	±9.6
10586	AAD	OFDM, QPSK, 18.0 Mbps, 90.0% DC	WLAN	8.49	±9.6
10587	AAD	OFDM, 16QAM, 24.0 Mbps, 90.0% DC	WLAN	8.36	±9.6
10588	AAD	OFDM, 16QAM, 36.0 Mbps, 90.0% DC	WLAN	8.76	±9.6
10589	AAD	OFDM, 64QAM, 48.0 Mbps, 90.0% DC	WLAN	8.35	±9.6
10590	AAD	OFDM, 64QAM, 54.0 Mbps, 90.0% DC	WLAN	8.67	±9.6
10591	AAD	HT20 Mixed, MCS0 (6.5 Mbps), 89.9% DC	WLAN	8.63	±9.6
10592	AAD	HT20 Mixed, MCS1 (13.0 Mbps), 90.0% DC	WLAN	8.79	±9.6
10593	AAD	HT20 Mixed, MCS2 (19.5 Mbps), 90.0% DC	WLAN	8.64	±9.6
10594	AAD	HT20 Mixed, MCS3 (26.0 Mbps), 90.0% DC	WLAN	8.74	±9.6
10595	AAD	HT20 Mixed, MCS4 (39.0 Mbps), 90.0% DC	WLAN	8.74	±9.6
10596	AAD	HT20 Mixed, MCS5 (52.0 Mbps), 90.0% DC	WLAN	8.71	±9.6
10597	AAD	HT20 Mixed, MCS6 (58.5 Mbps), 90.0% DC	WLAN	8.72	±9.6
10598	AAD	HT20 Mixed, MCS7 (65.0 Mbps), 90.0% DC	WLAN	8.50	±9.6
10599	AAD	HT40 Mixed, MCS0 (13.5 Mbps), 89.9% DC	WLAN	8.79	±9.6
10600	AAD	HT40 Mixed, MCS1 (27.0 Mbps), 89.7% DC	WLAN	8.88	±9.6
10601	AAD	HT40 Mixed, MCS2 (40.5 Mbps), 89.6% DC	WLAN	8.82	±9.6
10602	AAD	HT40 Mixed, MCS3 (54.0 Mbps), 89.4% DC	WLAN	8.94	±9.6
10603	AAD	HT40 Mixed, MCS4 (81.0 Mbps), 89.2% DC	WLAN	9.03	±9.6
10604	AAD	HT40 Mixed, MCS5 (108.0 Mbps), 88.9% DC	WLAN	8.76	±9.6
10605	AAD	HT40 Mixed, MCS6 (121.5 Mbps), 88.8% DC	WLAN	8.97	±9.6
10606	AAD	HT40 Mixed, MCS7 (135.0 Mbps), 88.7% DC	WLAN	8.82	±9.6
10607	AAD	VHT20, MCS0 (6.5 Mbps), 89.9% DC	WLAN	8.64	±9.6
10608	AAD	VHT20, MCS1 (13.0 Mbps), 90.0% DC	WLAN	8.77	±9.6
10609	AAD	VHT20, MCS2 (19.5 Mbps), 90.0% DC	WLAN	8.57	±9.6
10610	AAD	VHT20, MCS3 (26.0 Mbps), 90.0% DC	WLAN	8.78	±9.6
10611	AAD	VHT20, MCS4 (39.0 Mbps), 90.0% DC	WLAN	8.70	±9.6
10612	AAD	VHT20, MCS5 (52.0 Mbps), 90.0% DC	WLAN	8.77	±9.6
10613	AAD	VHT20, MCS6 (58.5 Mbps), 90.0% DC	WLAN	8.94	±9.6
10614	AAD	VHT20, MCS7 (65.0 Mbps), 90.0% DC	WLAN	8.59	±9.6
10615	AAD	VHT20, MCS8 (78.0 Mbps), 90.0% DC	WLAN	8.82	±9.6
10616	AAD	VHT40, MCS0 (13.5 Mbps), 89.9% DC	WLAN	8.82	±9.6
10617	AAD	VHT40, MCS1 (27.0 Mbps), 89.7% DC	WLAN	8.81	±9.6
10618	AAD	VHT40, MCS2 (40.5 Mbps), 89.6% DC	WLAN	8.58	±9.6
10619	AAD	VHT40, MCS3 (54.0 Mbps), 89.4% DC	WLAN	8.86	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10620	AAD	VHT40, MCS4 (81.0 Mbps), 89.2% DC	WLAN	8.87	±9.6
10621	AAD	VHT40, MCS5 (108.0 Mbps), 88.9% DC	WLAN	8.77	±9.6
10622	AAD	VHT40, MCS6 (121.5 Mbps), 88.8% DC	WLAN	8.68	±9.6
10623	AAD	VHT40, MCS7 (135.0 Mbps), 88.6% DC	WLAN	8.82	±9.6
10624	AAD	VHT40, MCS8 (162.0 Mbps), 88.4% DC	WLAN	8.96	±9.6
10625	AAD	VHT40, MCS9 (180.0 Mbps), 88.2% DC	WLAN	8.96	±9.6
10626	AAD	VHT80, MCS0 (29.3 Mbps), 90.0% DC	WLAN	8.83	±9.6
10627	AAD	VHT80, MCS1 (58.5 Mbps), 90.0% DC	WLAN	8.88	±9.6
10628	AAD	VHT80, MCS2 (87.8 Mbps), 90.0% DC	WLAN	8.71	±9.6
10629	AAD	VHT80, MCS3 (117.0 Mbps), 90.0% DC	WLAN	8.85	±9.6
10630	AAD	VHT80, MCS4 (175.5 Mbps), 90.0% DC	WLAN	8.72	±9.6
10631	AAD	VHT80, MCS5 (234.0 Mbps), 90.0% DC	WLAN	8.81	±9.6
10632	AAD	VHT80, MCS6 (263.3 Mbps), 90.0% DC	WLAN	8.74	±9.6
10633	AAD	VHT80, MCS7 (292.5 Mbps), 90.0% DC	WLAN	8.83	±9.6
10634	AAD	VHT80, MCS8 (351.0 Mbps), 90.0% DC	WLAN	8.80	±9.6
10635	AAD	VHT80, MCS9 (390.0 Mbps), 90.0% DC	WLAN	8.81	±9.6
10636	AAE	VHT160, MCS0 (58.5 Mbps), 90.0% DC	WLAN	8.83	±9.6
10637	AAE	VHT160, MCS1 (117.0 Mbps), 90.0% DC	WLAN	8.79	±9.6
10638	AAE	VHT160, MCS2 (175.5 Mbps), 90.0% DC	WLAN	8.86	±9.6
10639	AAE	VHT160, MCS3 (234.0 Mbps), 90.0% DC	WLAN	8.85	±9.6
10640	AAE	VHT160, MCS4 (351.0 Mbps), 90.0% DC	WLAN	8.98	±9.6
10641	AAE	VHT160, MCS5 (468.0 Mbps), 90.0% DC	WLAN	9.06	±9.6
10642	AAE	VHT160, MCS6 (526.5 Mbps), 90.0% DC	WLAN	9.06	±9.6
10643	AAE	VHT160, MCS7 (585.0 Mbps), 90.0% DC	WLAN	8.89	±9.6
10644	AAE	VHT160, MCS8 (702.0 Mbps), 90.0% DC	WLAN	9.05	±9.6
10645	AAE	VHT160, MCS9 (780.0 Mbps), 90.0% DC	WLAN	9.11	±9.6
10646	AAH	5.0 MHz, QPSK, UL/DL CFG: 2, SSC: 4, 1 RB	LTE-TDD	11.96	±9.6
10647	AAG	20.0 MHz, QPSK, UL/DL CFG: 2, SSC: 7, 1 RB	LTE-TDD	11.96	±9.6
10648	AAA	RC8, SO75, 1xAdvanced	CDMA2000	3.45	±9.6
10670	AAA	LE, Test, GFSK	Bluetooth	2.19	±9.6
10671	AAC	ET20, MCS0 (8.6 Mbps), 90.0% DC	WLAN	9.09	±9.6
10672	AAC	ET20, MCS1 (17.0 Mbps), 90.0% DC	WLAN	8.57	±9.6
10673	AAC	ET20, MCS2 (26.0 Mbps), 90.0% DC	WLAN	8.78	±9.6
10674	AAC	ET20, MCS3 (34.0 Mbps), 90.0% DC	WLAN	8.74	±9.6
10675	AAC	ET20, MCS4 (52.0 Mbps), 90.0% DC	WLAN	8.90	±9.6
10676	AAC	ET20, MCS5 (69.0 Mbps), 90.0% DC	WLAN	8.77	±9.6
10677	AAC	ET20, MCS6 (77.0 Mbps), 90.0% DC	WLAN	8.73	±9.6
10678	AAC	ET20, MCS7 (86.0 Mbps), 90.0% DC	WLAN	8.78	±9.6
10679	AAC	ET20, MCS8 (103.0 Mbps), 90.0% DC	WLAN	8.89	±9.6
10680	AAC	ET20, MCS9 (115.0 Mbps), 90.0% DC	WLAN	8.80	±9.6
10681	AAC	ET20, MCS10 (122.0 Mbps), 90.0% DC	WLAN	8.62	±9.6
10682	AAC	ET20, MCS11 (135.0 Mbps), 90.0% DC	WLAN	8.83	±9.6
10683	AAC	ET20, MCS0 (8.6 Mbps), 100.0% DC	WLAN	8.42	±9.6
10684	AAC	ET20, MCS1 (17.0 Mbps), 100.0% DC	WLAN	8.26	±9.6
10685	AAC	ET20, MCS2 (26.0 Mbps), 100.0% DC	WLAN	8.33	±9.6
10686	AAC	ET20, MCS3 (34.0 Mbps), 100.0% DC	WLAN	8.28	±9.6
10687	AAC	ET20, MCS4 (52.0 Mbps), 100.0% DC	WLAN	8.45	±9.6
10688	AAC	ET20, MCS5 (69.0 Mbps), 100.0% DC	WLAN	8.29	±9.6
10689	AAC	ET20, MCS6 (77.0 Mbps), 100.0% DC	WLAN	8.55	±9.6
10690	AAC	ET20, MCS7 (86.0 Mbps), 100.0% DC	WLAN	8.29	±9.6
10691	AAC	ET20, MCS8 (103.0 Mbps), 100.0% DC	WLAN	8.25	±9.6
10692	AAC	ET20, MCS9 (115.0 Mbps), 100.0% DC	WLAN	8.29	±9.6
10693	AAC	ET20, MCS10 (122.0 Mbps), 100.0% DC	WLAN	8.25	±9.6
10694	AAC	ET20, MCS11 (135.0 Mbps), 100.0% DC	WLAN	8.57	±9.6
10695	AAC	ET40, MCS0 (17.2 Mbps), 89.8% DC	WLAN	8.78	±9.6
10696	AAC	ET40, MCS1 (34.0 Mbps), 89.8% DC	WLAN	8.91	±9.6
10697	AAC	ET40, MCS2 (52.0 Mbps), 89.7% DC	WLAN	8.61	±9.6
10698	AAC	ET40, MCS3 (69.0 Mbps), 89.7% DC	WLAN	8.89	±9.6
10699	AAC	ET40, MCS4 (103.0 Mbps), 89.9% DC	WLAN	8.82	±9.6
10700	AAC	ET40, MCS5 (138.0 Mbps), 89.8% DC	WLAN	8.73	±9.6
10701	AAC	ET40, MCS6 (155.0 Mbps), 89.8% DC	WLAN	8.86	±9.6
10702	AAC	ET40, MCS7 (172.0 Mbps), 89.8% DC	WLAN	8.70	±9.6
10703	AAC	ET40, MCS8 (207.0 Mbps), 89.8% DC	WLAN	8.82	±9.6
10704	AAC	ET40, MCS9 (229.0 Mbps), 89.8% DC	WLAN	8.56	±9.6
10705	AAC	ET40, MCS10 (258.0 Mbps), 89.8% DC	WLAN	8.69	±9.6
10706	AAC	ET40, MCS11 (267.0 Mbps), 89.8% DC	WLAN	8.66	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10707	AAC	ET40, MCS0 (17.2 Mbps), 99.8% DC	WLAN	8.32	±9.6
10708	AAC	ET40, MCS1 (34.0 Mbps), 99.7% DC	WLAN	8.55	±9.6
10709	AAC	ET40, MCS2 (52.0 Mbps), 99.7% DC	WLAN	8.33	±9.6
10710	AAC	ET40, MCS3 (69.0 Mbps), 99.7% DC	WLAN	8.29	±9.6
10711	AAC	ET40, MCS4 (103.0 Mbps), 99.8% DC	WLAN	8.39	±9.6
10712	AAC	ET40, MCS5 (138.0 Mbps), 99.8% DC	WLAN	8.67	±9.6
10713	AAC	ET40, MCS6 (155.0 Mbps), 99.8% DC	WLAN	8.33	±9.6
10714	AAC	ET40, MCS7 (172.0 Mbps), 99.8% DC	WLAN	8.26	±9.6
10715	AAC	ET40, MCS8 (207.0 Mbps), 99.8% DC	WLAN	8.45	±9.6
10716	AAC	ET40, MCS9 (229.0 Mbps), 99.8% DC	WLAN	8.30	±9.6
10717	AAC	ET40, MCS10 (258.0 Mbps), 99.8% DC	WLAN	8.48	±9.6
10718	AAC	ET40, MCS11 (267.0 Mbps), 99.8% DC	WLAN	8.24	±9.6
10719	AAC	ET80, MCS0 (36.0 Mbps), 90.0% DC	WLAN	8.81	±9.6
10720	AAC	ET80, MCS1 (72.1 Mbps), 90.0% DC	WLAN	8.87	±9.6
10721	AAC	ET80, MCS2 (108.1 Mbps), 90.0% DC	WLAN	8.76	±9.6
10722	AAC	ET80, MCS3 (144.1 Mbps), 90.0% DC	WLAN	8.55	±9.6
10723	AAC	ET80, MCS4 (216.2 Mbps), 90.0% DC	WLAN	8.70	±9.6
10724	AAC	ET80, MCS5 (288.2 Mbps), 90.0% DC	WLAN	8.90	±9.6
10725	AAC	ET80, MCS6 (324.4 Mbps), 90.0% DC	WLAN	8.74	±9.6
10726	AAC	ET80, MCS7 (360.3 Mbps), 90.0% DC	WLAN	8.72	±9.6
10727	AAC	ET80, MCS8 (432.4 Mbps), 90.0% DC	WLAN	8.66	±9.6
10728	AAC	ET80, MCS9 (480.4 Mbps), 90.0% DC	WLAN	8.65	±9.6
10729	AAC	ET80, MCS10 (540.4 Mbps), 90.0% DC	WLAN	8.64	±9.6
10730	AAC	ET80, MCS11 (72.0 Mbps), 90.0% DC	WLAN	8.67	±9.6
10731	AAC	ET80, MCS0 (36.0 Mbps), 100.0% DC	WLAN	8.42	±9.6
10732	AAC	ET80, MCS1 (72.1 Mbps), 100.0% DC	WLAN	8.46	±9.6
10733	AAC	ET80, MCS2 (108.1 Mbps), 100.0% DC	WLAN	8.40	±9.6
10734	AAC	ET80, MCS3 (144.1 Mbps), 100.0% DC	WLAN	8.25	±9.6
10735	AAC	ET80, MCS4 (216.2 Mbps), 100.0% DC	WLAN	8.33	±9.6
10736	AAC	ET80, MCS5 (288.2 Mbps), 100.0% DC	WLAN	8.27	±9.6
10737	AAC	ET80, MCS6 (324.4 Mbps), 100.0% DC	WLAN	8.36	±9.6
10738	AAC	ET80, MCS7 (360.3 Mbps), 100.0% DC	WLAN	8.42	±9.6
10739	AAC	ET80, MCS8 (432.4 Mbps), 100.0% DC	WLAN	8.29	±9.6
10740	AAC	ET80, MCS9 (480.4 Mbps), 100.0% DC	WLAN	8.48	±9.6
10741	AAC	ET80, MCS10 (540.4 Mbps), 100.0% DC	WLAN	8.40	±9.6
10742	AAC	ET80, MCS11 (600.5 Mbps), 100.0% DC	WLAN	8.43	±9.6
10743	AAC	ET160, MCS0 (72.0 Mbps), 88.2% DC	WLAN	8.94	±9.6
10744	AAC	ET160, MCS1 (144.0 Mbps), 87.1% DC	WLAN	9.16	±9.6
10745	AAC	ET160, MCS2 (216.0 Mbps), 87.4% DC	WLAN	8.93	±9.6
10746	AAC	ET160, MCS3 (282.0 Mbps), 87.1% DC	WLAN	9.11	±9.6
10747	AAC	ET160, MCS4 (432.0 Mbps), 87.4% DC	WLAN	9.04	±9.6
10748	AAC	ET160, MCS5 (576.0 Mbps), 86.8% DC	WLAN	8.93	±9.6
10749	AAC	ET160, MCS6 (649.0 Mbps), 86.7% DC	WLAN	8.90	±9.6
10750	AAC	ET160, MCS7 (721.0 Mbps), 86.7% DC	WLAN	8.79	±9.6
10751	AAC	ET160, MCS8 (865.0 Mbps), 86.3% DC	WLAN	8.82	±9.6
10752	AAC	ET160, MCS9 (961.0 Mbps), 86.3% DC	WLAN	8.81	±9.6
10753	AAC	ET160, MCS10 (1081.0 Mbps), 86.7% DC	WLAN	9.00	±9.6
10754	AAC	ET160, MCS11 (1201.0 Mbps), 86.7% DC	WLAN	8.94	±9.6
10755	AAC	ET160, MCS0 (72.0 Mbps), 98.0% DC	WLAN	8.64	±9.6
10756	AAC	ET160, MCS1 (144.0 Mbps), 96.8% DC	WLAN	8.77	±9.6
10757	AAC	ET160, MCS2 (216.0 Mbps), 97.1% DC	WLAN	8.77	±9.6
10758	AAC	ET160, MCS3 (282.0 Mbps), 96.8% DC	WLAN	8.69	±9.6
10759	AAC	ET160, MCS4 (432.0 Mbps), 97.1% DC	WLAN	8.58	±9.6
10760	AAC	ET160, MCS5 (576.0 Mbps), 96.5% DC	WLAN	8.49	±9.6
10761	AAC	ET160, MCS6 (649.0 Mbps), 96.3% DC	WLAN	8.58	±9.6
10762	AAC	ET160, MCS7 (721.0 Mbps), 96.3% DC	WLAN	8.49	±9.6
10763	AAC	ET160, MCS8 (865.0 Mbps), 95.9% DC	WLAN	8.53	±9.6
10764	AAC	ET160, MCS9 (961.0 Mbps), 95.9% DC	WLAN	8.54	±9.6
10765	AAC	ET160, MCS10 (1081.0 Mbps), 96.3% DC	WLAN	8.54	±9.6
10766	AAC	ET160, MCS11 (1201.0 Mbps), 96.3% DC	WLAN	8.51	±9.6
10767	AAG	CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.99	±9.6
10768	AAE	CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.01	±9.6
10769	AAD	CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.01	±9.6
10770	AAE	CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.02	±9.6
10771	AAD	CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.02	±9.6
10772	AAE	CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.23	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10773	AAF	CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.03	±9.6
10774	AAE	CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.02	±9.6
10775	AAF	CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.31	±9.6
10776	AAE	CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.30	±9.6
10777	AAC	CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.30	±9.6
10778	AAE	CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.34	±9.6
10779	AAC	CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.42	±9.6
10780	AAE	CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.38	±9.6
10781	AAF	CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.38	±9.6
10782	AAE	CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.43	±9.6
10783	AAG	CP-OFDM, 5.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.31	±9.6
10784	AAE	CP-OFDM, 10.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.29	±9.6
10785	AAD	CP-OFDM, 15.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.40	±9.6
10786	AAE	CP-OFDM, 20.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.35	±9.6
10787	AAD	CP-OFDM, 25.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.44	±9.6
10788	AAE	CP-OFDM, 30.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.39	±9.6
10789	AAF	CP-OFDM, 40.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.37	±9.6
10790	AAE	CP-OFDM, 50.0 MHz, QPSK, 15 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.39	±9.6
10791	AAG	CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.83	±9.6
10792	AAE	CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.92	±9.6
10793	AAD	CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.95	±9.6
10794	AAE	CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.82	±9.6
10795	AAD	CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.84	±9.6
10796	AAE	CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.82	±9.6
10797	AAF	CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	8.01	±9.6
10798	AAE	CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.89	±9.6
10799	AAF	CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.93	±9.6
10801	AAF	CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.89	±9.6
10802	AAE	CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.87	±9.6
10803	AAF	CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.93	±9.6
10805	AAE	CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.34	±9.6
10806	AAD	CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.37	±9.6
10809	AAE	CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.34	±9.6
10810	AAF	CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.34	±9.6
10812	AAF	CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.35	±9.6
10817	AAG	CP-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.35	±9.6
10818	AAE	CP-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.34	±9.6
10819	AAD	CP-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.33	±9.6
10820	AAE	CP-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.30	±9.6
10821	AAD	CP-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10822	AAE	CP-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10823	AAF	CP-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.36	±9.6
10824	AAE	CP-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.39	±9.6
10825	AAF	CP-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10827	AAF	CP-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.42	±9.6
10828	AAE	CP-OFDM, 90.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.43	±9.6
10829	AAF	CP-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.40	±9.6
10830	AAE	CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.63	±9.6
10831	AAD	CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.73	±9.6
10832	AAE	CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.74	±9.6
10833	AAD	CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	7.70	±9.6
10834	AAE	CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.75	±9.6
10835	AAF	CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.70	±9.6
10836	AAE	CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.66	±9.6
10837	AAF	CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.68	±9.6
10839	AAF	CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.70	±9.6
10840	AAE	CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.67	±9.6
10841	AAF	CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	7.71	±9.6
10843	AAD	CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.49	±9.6
10844	AAE	CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.34	±9.6
10846	AAE	CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	8.41	±9.6
10854	AAE	CP-OFDM, 10.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.34	±9.6
10855	AAD	CP-OFDM, 15.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.36	±9.6
10856	AAE	CP-OFDM, 20.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.37	±9.6
10857	AAD	CP-OFDM, 25.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.35	±9.6
10858	AAE	CP-OFDM, 30.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.36	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10859	AAF	CP-OFDM, 40.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.34	±9.6
10860	AAE	CP-OFDM, 50.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10861	AAF	CP-OFDM, 60.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.40	±9.6
10863	AAF	CP-OFDM, 80.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10864	AAE	CP-OFDM, 90.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.37	±9.6
10865	AAF	CP-OFDM, 100.0 MHz, QPSK, 60 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	8.41	±9.6
10866	AAF	DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10868	AAF	DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.89	±9.6
10869	AAE	DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	5.75	±9.6
10870	AAE	DFT-s-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	5.86	±9.6
10871	AAE	DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	5.75	±9.6
10872	AAE	DFT-s-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	6.52	±9.6
10873	AAE	DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	6.61	±9.6
10874	AAE	DFT-s-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	6.65	±9.6
10875	AAE	CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	7.78	±9.6
10876	AAE	CP-OFDM, 100.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.39	±9.6
10877	AAE	CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	7.95	±9.6
10878	AAE	CP-OFDM, 100.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.41	±9.6
10879	AAE	CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	8.12	±9.6
10880	AAE	CP-OFDM, 100.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.38	±9.6
10881	AAE	DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	5.75	±9.6
10882	AAE	DFT-s-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	5.96	±9.6
10883	AAE	DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	6.57	±9.6
10884	AAE	DFT-s-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	6.53	±9.6
10885	AAE	DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	6.61	±9.6
10886	AAE	DFT-s-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	6.65	±9.6
10887	AAE	CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 99.9% DC, 1 RB	5G NR FR2 TDD	7.78	±9.6
10888	AAE	CP-OFDM, 50.0 MHz, QPSK, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.35	±9.6
10889	AAE	CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	8.02	±9.6
10890	AAE	CP-OFDM, 50.0 MHz, 16QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.40	±9.6
10891	AAE	CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 1 RB	5G NR FR2 TDD	8.13	±9.6
10892	AAE	CP-OFDM, 50.0 MHz, 64QAM, 120 kHz, 100.0% DC, 100% RB	5G NR FR2 TDD	8.41	±9.6
10897	AAE	DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 99.9% DC, 1 RB	5G NR FR1 TDD	5.66	±9.6
10898	AAC	DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.67	±9.6
10899	AAB	DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.67	±9.6
10900	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10901	AAB	DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10902	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10903	AAD	DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10904	AAC	DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10905	AAD	DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10906	AAD	DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 1 RB	5G NR FR1 TDD	5.68	±9.6
10907	AAE	DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.78	±9.6
10908	AAC	DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.93	±9.6
10909	AAB	DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.96	±9.6
10910	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.83	±9.6
10911	AAB	DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.93	±9.6
10912	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.84	±9.6
10913	AAD	DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.84	±9.6
10914	AAC	DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.85	±9.6
10915	AAD	DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.83	±9.6
10916	AAD	DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.87	±9.6
10917	AAD	DFT-s-OFDM, 100.0 MHz, QPSK, 30 kHz, 100.0% DC, 50% RB	5G NR FR1 TDD	5.94	±9.6
10918	AAE	DFT-s-OFDM, 5.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.86	±9.6
10919	AAC	DFT-s-OFDM, 10.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.86	±9.6
10920	AAB	DFT-s-OFDM, 15.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.87	±9.6
10921	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.84	±9.6
10922	AAB	DFT-s-OFDM, 25.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.82	±9.6
10923	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.84	±9.6
10924	AAD	DFT-s-OFDM, 40.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.84	±9.6
10925	AAC	DFT-s-OFDM, 50.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.95	±9.6
10926	AAD	DFT-s-OFDM, 60.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.84	±9.6
10927	AAD	DFT-s-OFDM, 80.0 MHz, QPSK, 30 kHz, 100.0% DC, 100% RB	5G NR FR1 TDD	5.94	±9.6
10928	AAD	DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.52	±9.6
10929	AAD	DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.52	±9.6
10930	AAC	DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.52	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10931	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.51	±9.6
10932	AAC	DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.51	±9.6
10933	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.51	±9.6
10934	AAC	DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.51	±9.6
10935	AAD	DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 1 RB	5G NR FR1 FDD	5.51	±9.6
10936	AAD	DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.90	±9.6
10937	AAD	DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.77	±9.6
10938	AAC	DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.90	±9.6
10939	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.82	±9.6
10940	AAC	DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.89	±9.6
10941	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.83	±9.6
10942	AAC	DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.85	±9.6
10943	AAD	DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 50% RB	5G NR FR1 FDD	5.95	±9.6
10944	AAD	DFT-s-OFDM, 5.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.81	±9.6
10945	AAD	DFT-s-OFDM, 10.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.85	±9.6
10946	AAC	DFT-s-OFDM, 15.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.83	±9.6
10947	AAC	DFT-s-OFDM, 20.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.87	±9.6
10948	AAC	DFT-s-OFDM, 25.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.94	±9.6
10949	AAC	DFT-s-OFDM, 30.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.87	±9.6
10950	AAC	DFT-s-OFDM, 40.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.94	±9.6
10951	AAD	DFT-s-OFDM, 50.0 MHz, QPSK, 15 kHz, 100% RB	5G NR FR1 FDD	5.92	±9.6
10978	AAA	BDR, 1.0 MHz, 76.7% DC	ULLA	1.16	±9.6
10979	AAA	HDR4, 2.0 MHz, 25.1% DC	ULLA	8.58	±9.6
10980	AAA	HDR8, 4.0 MHz, 16.5% DC	ULLA	10.32	±9.6
10981	AAA	HDRp4, 2.0 MHz, 89.0% DC	ULLA	3.19	±9.6
10982	AAA	HDRp8, 4.0 MHz, 90.3% DC	ULLA	3.43	±9.6
11013	AAB	EHT320, MCS1 (272.0 Mbps), 100.0% DC	WLAN	8.47	±9.6
11014	AAB	EHT320, MCS2 (408.0 Mbps), 100.0% DC	WLAN	8.45	±9.6
11015	AAB	EHT320, MCS3 (544.0 Mbps), 100.0% DC	WLAN	8.44	±9.6
11016	AAB	EHT320, MCS4 (817.0 Mbps), 100.0% DC	WLAN	8.44	±9.6
11017	AAB	EHT320, MCS5 (1089.0 Mbps), 100.0% DC	WLAN	8.41	±9.6
11018	AAB	EHT320, MCS6 (1225.0 Mbps), 100.0% DC	WLAN	8.40	±9.6
11019	AAB	EHT320, MCS7 (1361.0 Mbps), 100.0% DC	WLAN	8.29	±9.6
11020	AAB	EHT320, MCS8 (1633.0 Mbps), 100.0% DC	WLAN	8.27	±9.6
11021	AAB	EHT320, MCS9 (1815.0 Mbps), 100.0% DC	WLAN	8.46	±9.6
11022	AAB	EHT320, MCS10 (2042.0 Mbps), 100.0% DC	WLAN	8.36	±9.6
11023	AAB	EHT320, MCS11 (2269.0 Mbps), 100.0% DC	WLAN	8.09	±9.6
11024	AAB	EHT320, MCS12 (2450.0 Mbps), 100.0% DC	WLAN	8.42	±9.6
11025	AAB	EHT320, MCS13 (2722.0 Mbps), 100.0% DC	WLAN	8.37	±9.6
11026	AAB	EHT320, MCS0 (136.0 Mbps), 100.0% DC	WLAN	8.39	±9.6

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client

B.V. ADT
Taoyuan City

Certificate No.

EUmm-9615_May25

CALIBRATION CERTIFICATE

Object

EUmmWV4 - SN:9615

Calibration procedure(s)

QA CAL-02.v9, QA CAL-25.v8, QA CAL-42.v3
Calibration procedure for E-field probes optimized for close near field
evaluations in air

Calibration date

May 14, 2025

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3) °C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Calibration Date (Certificate No.)	Sched. Cal.
Power sensor R&S NRP-33T	SN: 100967	26-Mar-25 (No. 217-04290)	Mar-26
Power sensor R&S NRP110T	SN: 101244	24-Mar-25 (No. 1020A300786765)	Mar-26
Spectrum analyzer FSV40	SN: 101832	29-Jan-25 (No. 4030A315009658)	Jan-26
Harmonic Mixer R&S FS-Z75	SN: 101566	20-Mar-25 (No. 1020A300786766)	Mar-26
Harmonic Mixer R&S FS-Z110	SN: 101633	21-Mar-25 (No. 1020A300786769)	Mar-26
Ref. Probe EUmmWV3	SN: 9374	28-Aug-24 (No. EUmm-9374_Aug24)	Aug-25
DAE4ip	SN: 1662	05-Nov-24 (No. DAE4ip-1662_Nov24)	Nov-25

Secondary Standards	ID	Check Date (in house)	Sched. Check
Signal Generator Anapico APSIN26G	SN: 2023	30-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power sensor R&S NRP40T	SN: 101439	08-Nov-21 (in house check Jun-24)	In house check: Jun-25
Power sensor R&S NRP110T	SN: 101226	15-Nov-21 (in house check Jun-24)	In house check: Jun-25

	Name	Function	Signature
Calibrated by	Leif Klysner	Laboratory Technician	
Approved by	Sven Kühn	Technical Manager	
Issued: May 15, 2025			
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			

Calibration Laboratory of

Schmid & Partner
Engineering AG

Zeughausstrasse 43, 8004 Zurich, Switzerland



S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary

NORM _{x,y}	sensitivity in free space
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system
Sensor Angles	sensor deviation from the probe axis, used to calculate the field orientation and polarization
$\vec{k}$	is the wave propagation direction

Calibration is Performed According to the Following Standards:

- a) IEEE Std 1309-2005, "IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", December 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y}*: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). For frequencies > 6 GHz, the far field in front of waveguide horn antennas is measured for a set of frequencies in various waveguide bands up to 110 GHz.
- DCP_{x,y}*: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal. DCP does not depend on frequency nor media.
Note: As the field is measured with a diode detector sensor, it is warranted that the probe response is linear (E^2) below the documented lowest calibrated value.
- PAR*: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- The frequency sensor model parameters are determined prior to calibration based on a frequency sweep (sensor model involving resistors R , R_p , inductance L and capacitors C , C_p).
- A_{x,y}; B_{x,y}; C_{x,y}; D_{x,y}; VR_{x,y}*: *A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle*: The angle is assessed using the information gained by determining the *NORM_x* (no uncertainty required).
- Equivalent Sensor Angle*: The two probe sensors are mounted in the same plane at different angles. The angles are assessed using the information gained by determining the *NORM_x* (no uncertainty required).
- Spherical isotropy (3D deviation from isotropy)*: in a locally homogeneous field realized using an open waveguide / horn setup.

Parameters of Probe: EUmmWV4 - SN:9615

Basic Calibration Parameters

	Sensor X	Sensor Y	Unc (k = 2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$)	0.01898	0.02029	$\pm 10.1\%$
DCP (mV) ^B	107.0	105.0	$\pm 4.7\%$
Equivalent Sensor Angle	-60.2	35.7	

Calibration Results for Frequency Response (750 MHz – 110 GHz)

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc (k = 2) dB
0.75	77.2	-0.31	-0.25	± 0.43
1.8	140.4	-0.03	-0.01	± 0.43
2.0	133.0	0.12	0.16	± 0.43
2.2	124.8	-0.07	-0.02	± 0.43
2.5	123.0	0.10	0.15	± 0.43
3.5	256.2	-0.07	-0.09	± 0.43
3.7	249.8	0.05	0.01	± 0.43
6.6	63.4	0.02	-0.27	± 0.98
8.0	58.4	-0.01	-0.11	± 0.98
10.0	57.8	-0.03	0.03	± 0.98
15.0	45.5	0.14	0.20	± 0.98
26.6	115.1	0.25	0.19	± 0.98
30.0	125.1	0.03	0.01	± 0.98
35.0	123.5	-0.22	-0.17	± 0.98
40.0	101.8	-0.35	-0.28	± 0.98
50.0	60.8	0.04	0.00	± 0.98
55.0	73.7	-0.06	-0.08	± 0.98
60.0	76.4	0.02	0.04	± 0.98
65.0	72.0	0.14	0.20	± 0.98
70.0	68.5	0.11	0.10	± 0.98
75.0	67.9	-0.03	-0.09	± 0.98
75.0	89.9	-0.08	-0.08	± 0.98
80.0	88.2	-0.16	-0.16	± 0.98
85.0	54.3	-0.04	-0.07	± 0.98
90.0	80.6	0.02	0.02	± 0.98
92.0	80.8	0.01	0.04	± 0.98
95.0	73.2	-0.03	-0.04	± 0.98
97.0	65.9	-0.02	-0.01	± 0.98
100.0	63.4	0.03	0.06	± 0.98
105.0	63.2	-0.18	-0.14	± 0.98
110.0	72.1	0.12	0.03	± 0.98

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^B Linearization parameter uncertainty for maximum specified field strength.

Parameters of Probe: EUmmWV4 - SN:9615

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu V}$	C	D dB	VR mV	Max dev.	Max Unc ^E k = 2
0	CW	X	0.00	0.00	1.00	0.00	135.1	±3.3%	±4.7%
		Y	0.00	0.00	1.00		68.9		
10352	Pulse Waveform (200Hz, 10%)	X	2.91	60.00	14.70	10.00	6.0	±0.5%	±9.6%
		Y	2.17	60.00	16.17		6.0		
10353	Pulse Waveform (200Hz, 20%)	X	2.04	60.00	13.48	6.99	12.0	±0.6%	±9.6%
		Y	1.50	60.00	15.19		12.0		
10354	Pulse Waveform (200Hz, 40%)	X	1.27	60.26	12.31	3.98	23.0	±0.6%	±9.6%
		Y	0.93	60.00	13.99		23.0		
10355	Pulse Waveform (200Hz, 60%)	X	0.73	60.00	11.57	2.22	27.0	±0.6%	±9.6%
		Y	0.62	60.00	13.04		27.0		
10387	QPSK Waveform, 1 MHz	X	1.21	60.00	12.24	1.00	22.0	±0.7%	±9.6%
		Y	1.19	60.00	12.33		22.0		
10388	QPSK Waveform, 10 MHz	X	1.27	60.00	12.01	0.00	22.0	±0.6%	±9.6%
		Y	1.33	60.00	12.17		22.0		
10396	64-QAM Waveform, 100 kHz	X	2.86	63.57	15.12	3.01	17.0	±0.5%	±9.6%
		Y	5.54	70.60	17.72		17.0		
10399	64-QAM Waveform, 40 MHz	X	2.08	60.00	12.45	0.00	19.0	±0.5%	±9.6%
		Y	2.05	60.00	12.69		19.0		
10414	WLAN CCDF, 64-QAM, 40 MHz	X	3.21	60.00	12.86	0.00	12.0	±0.8%	±9.6%
		Y	3.05	60.00	13.13		12.0		

Note: For details on UID parameters see Appendix

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

Parameters of Probe: EUmmWV4 - SN:9615

Calibration Results for Linearity Response

Frequency GHz	Target E-Field V/m	Deviation Sensor X dB	Deviation Sensor Y dB	Unc (k = 2) dB
0.9	50.0	-0.04	0.09	±0.2
0.9	100.0	-0.05	0.00	±0.2
0.9	500.0	0.03	-0.01	±0.2
0.9	1000.0	0.06	0.01	±0.2
0.9	1500.0	0.04	0.01	±0.2
0.9	2100.0	0.02	0.01	±0.2

Sensor Frequency Model Parameters (750 MHz – 55 GHz)

	Sensor X	Sensor Y
R (Ω)	89.41	45.84
R _p (Ω)	112.52	60.17
L (nH)	0.07934	0.03623
C (pF)	0.2099	0.5921
C _p (pF)	0.0752	0.1572

Sensor Frequency Model Parameters (55 GHz – 110 GHz)

	Sensor X	Sensor Y
R (Ω)	29.93	40.67
R _p (Ω)	157.37	220.40
L (nH)	0.09104	0.12510
C (pF)	0.0463	0.0348
C _p (pF)	0.0569	0.0422

Sensor Model Parameters


	C1 fF	C2 fF	α V^{-1}	T1 $ms V^{-2}$	T2 $ms V^{-1}$	T3 ms	T4 V^{-2}	T5 V^{-1}	T6
x	54.5	390.59	32.94	2.66	7.39	4.99	0.00	1.64	1.01
y	47.0	336.04	32.91	0.92	6.42	5.04	2.00	2.00	1.01

Other Probe Parameters


Sensor Arrangement	Rectangular
Connector Angle	56.8°
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	320 mm
Probe Body Diameter	8 mm
Tip Length	23 mm
Tip Diameter	8.0 mm
Probe Tip to Sensor X Calibration Point	1.5 mm
Probe Tip to Sensor Y Calibration Point	1.5 mm

Deviation from Isotropy in Air

30GHz: 3D isotropy, E-field parallel to probe axis



60GHz: 3D isotropy, E-field parallel to probe axis



Probe isotropy for E_{tot} : probe rotated $\phi = 0^\circ$ to 360° , tilted from field propagation direction $\vec{k}$
 Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 30 GHz: deviation within ± 0.36 dB
 Parallel to the field propagation ($\psi = 0^\circ - 90^\circ$) at 60 GHz: deviation within ± 0.38 dB

Appendix: Modulation Calibration Parameters

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
0		CW	CW	0.00	±4.7
10010	CAB	SAR Validation (Square, 100 ms, 10 ms)	Test	10.00	±9.6
10011	CAC	UMTS-FDD (WCDMA)	WCDMA	2.91	±9.6
10012	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)	WLAN	1.87	±9.6
10013	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps)	WLAN	9.46	±9.6
10021	DAC	GSM-FDD (TDMA, GMSK)	GSM	9.39	±9.6
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	GSM	9.57	±9.6
10024	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1)	GSM	6.56	±9.6
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	GSM	12.62	±9.6
10026	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1)	GSM	9.55	±9.6
10027	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2)	GSM	4.80	±9.6
10028	DAC	GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)	GSM	3.55	±9.6
10029	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2)	GSM	7.78	±9.6
10030	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH1)	Bluetooth	5.30	±9.6
10031	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH3)	Bluetooth	1.87	±9.6
10032	CAA	IEEE 802.15.1 Bluetooth (GFSK, DH5)	Bluetooth	1.16	±9.6
10033	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)	Bluetooth	7.74	±9.6
10034	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)	Bluetooth	4.53	±9.6
10035	CAA	IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)	Bluetooth	3.83	±9.6
10036	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH1)	Bluetooth	8.01	±9.6
10037	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH3)	Bluetooth	4.77	±9.6
10038	CAA	IEEE 802.15.1 Bluetooth (8-DPSK, DH5)	Bluetooth	4.10	±9.6
10039	CAB	CDMA2000 (1xRTT, RC1)	CDMA2000	4.57	±9.6
10042	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate)	AMPS	7.78	±9.6
10044	CAA	IS-91/EIA/TIA-553 FDD (FDMA, FM)	AMPS	0.00	±9.6
10048	CAA	DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)	DECT	13.80	±9.6
10049	CAA	DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)	DECT	10.79	±9.6
10056	CAA	UMTS-TDD (TD-SCDMA, 1.28 Mcps)	TD-SCDMA	11.01	±9.6
10058	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)	GSM	6.52	±9.6
10059	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)	WLAN	2.12	±9.6
10060	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)	WLAN	2.83	±9.6
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	WLAN	3.60	±9.6
10062	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)	WLAN	8.68	±9.6
10063	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)	WLAN	8.63	±9.6
10064	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)	WLAN	9.09	±9.6
10065	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)	WLAN	9.00	±9.6
10066	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)	WLAN	9.38	±9.6
10067	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)	WLAN	10.12	±9.6
10068	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)	WLAN	10.24	±9.6
10069	CAE	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)	WLAN	10.56	±9.6
10071	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)	WLAN	9.83	±9.6
10072	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps)	WLAN	9.62	±9.6
10073	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps)	WLAN	9.94	±9.6
10074	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps)	WLAN	10.30	±9.6
10075	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps)	WLAN	10.77	±9.6
10076	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps)	WLAN	10.94	±9.6
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	WLAN	11.00	±9.6
10081	CAB	CDMA2000 (1xRTT, RC3)	CDMA2000	3.97	±9.6
10082	CAB	IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate)	AMPS	4.77	±9.6
10090	DAC	GPRS-FDD (TDMA, GMSK, TN 0-4)	GSM	6.56	±9.6
10097	CAC	UMTS-FDD (HSDPA)	WCDMA	3.98	±9.6
10098	CAC	UMTS-FDD (HSUPA, Subtest 2)	WCDMA	3.98	±9.6
10099	DAC	EDGE-FDD (TDMA, 8PSK, TN 0-4)	GSM	9.55	±9.6
10100	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-FDD	5.67	±9.6
10101	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10102	CAF	LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10103	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)	LTE-TDD	9.29	±9.6
10104	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)	LTE-TDD	9.97	±9.6
10105	CAH	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)	LTE-TDD	10.01	±9.6
10108	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-FDD	5.80	±9.6
10109	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10110	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-FDD	5.75	±9.6
10111	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-FDD	6.44	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10112	CAH	LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-FDD	6.59	±9.6
10113	CAH	LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10114	CAE	IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)	WLAN	8.10	±9.6
10115	CAE	IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)	WLAN	8.46	±9.6
10116	CAE	IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM)	WLAN	8.15	±9.6
10117	CAE	IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)	WLAN	8.07	±9.6
10118	CAE	IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)	WLAN	8.59	±9.6
10119	CAE	IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)	WLAN	8.13	±9.6
10140	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10141	CAF	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-FDD	6.53	±9.6
10142	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10143	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-FDD	6.35	±9.6
10144	CAF	LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-FDD	6.65	±9.6
10145	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-FDD	5.76	±9.6
10146	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.41	±9.6
10147	CAG	LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.72	±9.6
10149	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-FDD	6.42	±9.6
10150	CAF	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10151	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-TDD	9.28	±9.6
10152	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10153	CAH	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)	LTE-TDD	10.05	±9.6
10154	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-FDD	5.75	±9.6
10155	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10156	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-FDD	5.79	±9.6
10157	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-FDD	6.49	±9.6
10158	CAH	LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-FDD	6.62	±9.6
10159	CAH	LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-FDD	6.56	±9.6
10160	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-FDD	5.82	±9.6
10161	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-FDD	6.43	±9.6
10162	CAF	LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-FDD	6.58	±9.6
10166	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-FDD	5.46	±9.6
10167	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.21	±9.6
10168	CAG	LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.79	±9.6
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-FDD	5.73	±9.6
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10171	AAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-FDD	6.49	±9.6
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	LTE-TDD	9.21	±9.6
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10175	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-FDD	5.72	±9.6
10176	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10177	CAJ	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-FDD	5.73	±9.6
10178	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10179	CAH	LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10180	CAH	LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10181	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-FDD	5.72	±9.6
10182	CAF	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10183	AAE	LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10184	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-FDD	5.73	±9.6
10185	CAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-FDD	6.51	±9.6
10186	AAF	LTE-FDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10187	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-FDD	5.73	±9.6
10188	CAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-FDD	6.52	±9.6
10189	AAG	LTE-FDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-FDD	6.50	±9.6
10193	CAE	IEEE 802.11n (HT Greenfield, 6.5 Mbps, BPSK)	WLAN	8.09	±9.6
10194	CAE	IEEE 802.11n (HT Greenfield, 39 Mbps, 16-QAM)	WLAN	8.12	±9.6
10195	CAE	IEEE 802.11n (HT Greenfield, 65 Mbps, 64-QAM)	WLAN	8.21	±9.6
10196	CAE	IEEE 802.11n (HT Mixed, 6.5 Mbps, BPSK)	WLAN	8.10	±9.6
10197	CAE	IEEE 802.11n (HT Mixed, 39 Mbps, 16-QAM)	WLAN	8.13	±9.6
10198	CAE	IEEE 802.11n (HT Mixed, 65 Mbps, 64-QAM)	WLAN	8.27	±9.6
10219	CAE	IEEE 802.11n (HT Mixed, 7.2 Mbps, BPSK)	WLAN	8.03	±9.6
10220	CAE	IEEE 802.11n (HT Mixed, 43.3 Mbps, 16-QAM)	WLAN	8.13	±9.6
10221	CAE	IEEE 802.11n (HT Mixed, 72.2 Mbps, 64-QAM)	WLAN	8.27	±9.6
10222	CAE	IEEE 802.11n (HT Mixed, 15 Mbps, BPSK)	WLAN	8.06	±9.6
10223	CAE	IEEE 802.11n (HT Mixed, 90 Mbps, 16-QAM)	WLAN	8.48	±9.6
10224	CAE	IEEE 802.11n (HT Mixed, 150 Mbps, 64-QAM)	WLAN	8.08	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k=2$
10225	CAC	UMTS-FDD (HSPA+)	WCDMA	5.97	±9.6
10226	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.49	±9.6
10227	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.26	±9.6
10228	CAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK)	LTE-TDD	9.22	±9.6
10229	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10230	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10231	CAE	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK)	LTE-TDD	9.19	±9.6
10232	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10233	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10234	CAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK)	LTE-TDD	9.21	±9.6
10235	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10236	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10237	CAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK)	LTE-TDD	9.21	±9.6
10238	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)	LTE-TDD	9.48	±9.6
10239	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)	LTE-TDD	10.25	±9.6
10240	CAG	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK)	LTE-TDD	9.21	±9.6
10241	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.82	±9.6
10242	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM)	LTE-TDD	9.86	±9.6
10243	CAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)	LTE-TDD	9.46	±9.6
10244	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10245	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-TDD	10.06	±9.6
10246	CAE	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-TDD	9.30	±9.6
10247	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)	LTE-TDD	9.91	±9.6
10248	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)	LTE-TDD	10.09	±9.6
10249	CAH	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK)	LTE-TDD	9.29	±9.6
10250	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)	LTE-TDD	9.81	±9.6
10251	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)	LTE-TDD	10.17	±9.6
10252	CAH	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK)	LTE-TDD	9.24	±9.6
10253	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)	LTE-TDD	9.90	±9.6
10254	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)	LTE-TDD	10.14	±9.6
10255	CAG	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK)	LTE-TDD	9.20	±9.6
10256	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)	LTE-TDD	9.96	±9.6
10257	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)	LTE-TDD	10.08	±9.6
10258	CAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)	LTE-TDD	9.34	±9.6
10259	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)	LTE-TDD	9.98	±9.6
10260	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)	LTE-TDD	9.97	±9.6
10261	CAE	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK)	LTE-TDD	9.24	±9.6
10262	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)	LTE-TDD	9.83	±9.6
10263	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)	LTE-TDD	10.16	±9.6
10264	CAH	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK)	LTE-TDD	9.23	±9.6
10265	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)	LTE-TDD	9.92	±9.6
10266	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)	LTE-TDD	10.07	±9.6
10267	CAH	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK)	LTE-TDD	9.30	±9.6
10268	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)	LTE-TDD	10.06	±9.6
10269	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)	LTE-TDD	10.13	±9.6
10270	CAG	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-TDD	9.58	±9.6
10274	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.10)	WCDMA	4.87	±9.6
10275	CAC	UMTS-FDD (HSUPA, Subtest 5, 3GPP Rel8.4)	WCDMA	3.96	±9.6
10277	CAA	PHS (QPSK)	PHS	11.81	±9.6
10278	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.5)	PHS	11.81	±9.6
10279	CAA	PHS (QPSK, BW 884 MHz, Rolloff 0.38)	PHS	12.18	±9.6
10290	AAB	CDMA2000, RC1, SO55, Full Rate	CDMA2000	3.91	±9.6
10291	AAB	CDMA2000, RC3, SO55, Full Rate	CDMA2000	3.46	±9.6
10292	AAB	CDMA2000, RC3, SO32, Full Rate	CDMA2000	3.39	±9.6
10293	AAB	CDMA2000, RC3, SO3, Full Rate	CDMA2000	3.50	±9.6
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	CDMA2000	12.49	±9.6
10297	AAE	LTE-FDD (SC-FDMA, 50% RB, 20 MHz, QPSK)	LTE-FDD	5.81	±9.6
10298	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, QPSK)	LTE-FDD	5.72	±9.6
10299	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM)	LTE-FDD	6.39	±9.6
10300	AAE	LTE-FDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM)	LTE-FDD	6.60	±9.6
10301	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC)	WiMAX	12.03	±9.6
10302	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, QPSK, PUSC, 3 CTRL symbols)	WiMAX	12.57	±9.6
10303	AAA	IEEE 802.16e WiMAX (31:15, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	12.52	±9.6
10304	AAA	IEEE 802.16e WiMAX (29:18, 5 ms, 10 MHz, 64QAM, PUSC)	WiMAX	11.86	±9.6
10305	AAA	IEEE 802.16e WiMAX (31:15, 10 ms, 10 MHz, 64QAM, PUSC, 15 symbols)	WiMAX	15.24	±9.6
10306	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 64QAM, PUSC, 18 symbols)	WiMAX	14.67	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10307	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, PUSC, 18 symbols)	WiMAX	14.49	±9.6
10308	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, PUSC)	WiMAX	14.46	±9.6
10309	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, 16QAM, AMC 2x3, 18 symbols)	WiMAX	14.58	±9.6
10310	AAA	IEEE 802.16e WiMAX (29:18, 10 ms, 10 MHz, QPSK, AMC 2x3, 18 symbols)	WiMAX	14.57	±9.6
10311	AAE	LTE-FDD (SC-FDMA, 100% RB, 15 MHz, QPSK)	LTE-FDD	6.06	±9.6
10313	AAA	iDEN 1:3	iDEN	10.51	±9.6
10314	AAA	iDEN 1:6	iDEN	13.48	±9.6
10315	AAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 96pc duty cycle)	WLAN	1.71	±9.6
10316	AAB	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10317	AAE	IEEE 802.11a WiFi 5 GHz (OFDM, 6 Mbps, 96pc duty cycle)	WLAN	8.36	±9.6
10352	AAA	Pulse Waveform (200Hz, 10%)	Generic	10.00	±9.6
10353	AAA	Pulse Waveform (200Hz, 20%)	Generic	6.99	±9.6
10354	AAA	Pulse Waveform (200Hz, 40%)	Generic	3.98	±9.6
10355	AAA	Pulse Waveform (200Hz, 60%)	Generic	2.22	±9.6
10356	AAA	Pulse Waveform (200Hz, 80%)	Generic	0.97	±9.6
10387	AAA	QPSK Waveform, 1 MHz	Generic	5.10	±9.6
10388	AAA	QPSK Waveform, 10 MHz	Generic	5.22	±9.6
10396	AAA	64-QAM Waveform, 100 kHz	Generic	6.27	±9.6
10399	AAA	64-QAM Waveform, 40 MHz	Generic	6.27	±9.6
10400	AAF	IEEE 802.11ac WiFi (20 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.37	±9.6
10401	AAF	IEEE 802.11ac WiFi (40 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.60	±9.6
10402	AAF	IEEE 802.11ac WiFi (80 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.53	±9.6
10403	AAB	CDMA2000 (1xEV-DO, Rev. 0)	CDMA2000	3.76	±9.6
10404	AAB	CDMA2000 (1xEV-DO, Rev. A)	CDMA2000	3.77	±9.6
10406	AAB	CDMA2000, RC3, SO32, SCH0, Full Rate	CDMA2000	5.22	±9.6
10410	AAH	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9, Subframe Conf=4)	LTE-TDD	7.82	±9.6
10414	AAA	WLAN CCDF, 64-QAM, 40 MHz	Generic	8.54	±9.6
10415	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 99pc duty cycle)	WLAN	1.54	±9.6
10416	AAA	IEEE 802.11g WiFi 2.4 GHz (ERP-OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10417	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10418	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Long preamble)	WLAN	8.14	±9.6
10419	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 99pc duty cycle, Short preamble)	WLAN	8.19	±9.6
10422	AAD	IEEE 802.11n (HT Greenfield, 7.2 Mbps, BPSK)	WLAN	8.32	±9.6
10423	AAD	IEEE 802.11n (HT Greenfield, 43.3 Mbps, 16-QAM)	WLAN	8.47	±9.6
10424	AAD	IEEE 802.11n (HT Greenfield, 72.2 Mbps, 64-QAM)	WLAN	8.40	±9.6
10425	AAD	IEEE 802.11n (HT Greenfield, 15 Mbps, BPSK)	WLAN	8.41	±9.6
10426	AAD	IEEE 802.11n (HT Greenfield, 90 Mbps, 16-QAM)	WLAN	8.45	±9.6
10427	AAD	IEEE 802.11n (HT Greenfield, 150 Mbps, 64-QAM)	WLAN	8.41	±9.6
10430	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1)	LTE-FDD	8.28	±9.6
10431	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1)	LTE-FDD	8.38	±9.6
10432	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10433	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1)	LTE-FDD	8.34	±9.6
10434	AAB	W-CDMA (BS Test Model 1, 64 DPCH)	WCDMA	8.60	±9.6
10435	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10447	AAE	LTE-FDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.56	±9.6
10448	AAE	LTE-FDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.53	±9.6
10449	AAD	LTE-FDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.51	±9.6
10450	AAD	LTE-FDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-FDD	7.48	±9.6
10451	AAB	W-CDMA (BS Test Model 1, 64 DPCH, Clipping 44%)	WCDMA	7.59	±9.6
10453	AAE	Validation (Square, 10 ms, 1 ms)	Test	10.00	±9.6
10456	AAD	IEEE 802.11ac WiFi (160 MHz, 64-QAM, 99pc duty cycle)	WLAN	8.63	±9.6
10457	AAB	UMTS-FDD (DC-HSDPA)	WCDMA	6.62	±9.6
10458	AAA	CDMA2000 (1xEV-DO, Rev. B, 2 carriers)	CDMA2000	6.55	±9.6
10459	AAA	CDMA2000 (1xEV-DO, Rev. B, 3 carriers)	CDMA2000	8.25	±9.6
10460	AAB	UMTS-FDD (WCDMA, AMR)	WCDMA	2.39	±9.6
10461	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10462	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.30	±9.6
10463	AAC	LTE-TDD (SC-FDMA, 1 RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10464	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10465	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10466	AAD	LTE-TDD (SC-FDMA, 1 RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10467	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10468	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10469	AAG	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.56	±9.6
10470	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10471	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10472	AAG	LTE-TDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10473	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.82	±9.6
10474	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10475	AAF	LTE-TDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10477	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.32	±9.6
10478	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.57	±9.6
10479	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10480	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.18	±9.6
10481	AAC	LTE-TDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10482	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.71	±9.6
10483	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.39	±9.6
10484	AAD	LTE-TDD (SC-FDMA, 50% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.47	±9.6
10485	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.59	±9.6
10486	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.38	±9.6
10487	AAG	LTE-TDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.60	±9.6
10488	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.70	±9.6
10489	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10490	AAG	LTE-TDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10491	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10492	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.41	±9.6
10493	AAF	LTE-TDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10494	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10495	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.37	±9.6
10496	AAG	LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10497	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10498	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.40	±9.6
10499	AAC	LTE-TDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.68	±9.6
10500	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.67	±9.6
10501	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.44	±9.6
10502	AAD	LTE-TDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.52	±9.6
10503	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.72	±9.6
10504	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.31	±9.6
10505	AAG	LTE-TDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.54	±9.6
10506	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10507	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.36	±9.6
10508	AAG	LTE-TDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.55	±9.6
10509	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.99	±9.6
10510	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.49	±9.6
10511	AAF	LTE-TDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.51	±9.6
10512	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK, UL Subframe=2,3,4,7,8,9)	LTE-TDD	7.74	±9.6
10513	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.42	±9.6
10514	AAG	LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM, UL Subframe=2,3,4,7,8,9)	LTE-TDD	8.45	±9.6
10515	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10516	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 99pc duty cycle)	WLAN	1.57	±9.6
10517	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 99pc duty cycle)	WLAN	1.58	±9.6
10518	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.23	±9.6
10519	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.39	±9.6
10520	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.12	±9.6
10521	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 99pc duty cycle)	WLAN	7.97	±9.6
10522	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10523	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.08	±9.6
10524	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.27	±9.6
10525	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.36	±9.6
10526	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.42	±9.6
10527	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.21	±9.6
10528	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.36	±9.6
10529	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.36	±9.6
10531	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.43	±9.6
10532	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10533	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.38	±9.6
10534	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.45	±9.6
10535	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.45	±9.6
10536	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.32	±9.6
10537	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
10538	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.54	±9.6
10540	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.39	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10541	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.46	±9.6
10542	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.65	±9.6
10543	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.65	±9.6
10544	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.47	±9.6
10545	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10546	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.35	±9.6
10547	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.49	±9.6
10548	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.37	±9.6
10550	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.38	±9.6
10551	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.50	±9.6
10552	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.42	±9.6
10553	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.45	±9.6
10554	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.48	±9.6
10555	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
10556	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.50	±9.6
10557	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.52	±9.6
10558	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.61	±9.6
10560	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.73	±9.6
10561	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.56	±9.6
10562	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.69	±9.6
10563	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.77	±9.6
10564	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 99pc duty cycle)	WLAN	8.25	±9.6
10565	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 99pc duty cycle)	WLAN	8.45	±9.6
10566	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 99pc duty cycle)	WLAN	8.13	±9.6
10567	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 99pc duty cycle)	WLAN	8.00	±9.6
10568	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 99pc duty cycle)	WLAN	8.37	±9.6
10569	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 99pc duty cycle)	WLAN	8.10	±9.6
10570	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 99pc duty cycle)	WLAN	8.30	±9.6
10571	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10572	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps, 90pc duty cycle)	WLAN	1.99	±9.6
10573	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10574	AAA	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps, 90pc duty cycle)	WLAN	1.98	±9.6
10575	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10576	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10577	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10578	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10579	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10580	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10581	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10582	AAA	IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10583	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps, 90pc duty cycle)	WLAN	8.59	±9.6
10584	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps, 90pc duty cycle)	WLAN	8.60	±9.6
10585	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps, 90pc duty cycle)	WLAN	8.70	±9.6
10586	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps, 90pc duty cycle)	WLAN	8.49	±9.6
10587	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps, 90pc duty cycle)	WLAN	8.36	±9.6
10588	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps, 90pc duty cycle)	WLAN	8.76	±9.6
10589	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps, 90pc duty cycle)	WLAN	8.35	±9.6
10590	AAD	IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps, 90pc duty cycle)	WLAN	8.67	±9.6
10591	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS0, 90pc duty cycle)	WLAN	8.63	±9.6
10592	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10593	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS2, 90pc duty cycle)	WLAN	8.64	±9.6
10594	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10595	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS4, 90pc duty cycle)	WLAN	8.74	±9.6
10596	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS5, 90pc duty cycle)	WLAN	8.71	±9.6
10597	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS6, 90pc duty cycle)	WLAN	8.72	±9.6
10598	AAD	IEEE 802.11n (HT Mixed, 20 MHz, MCS7, 90pc duty cycle)	WLAN	8.50	±9.6
10599	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS0, 90pc duty cycle)	WLAN	8.79	±9.6
10600	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10601	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS2, 90pc duty cycle)	WLAN	8.82	±9.6
10602	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS3, 90pc duty cycle)	WLAN	8.94	±9.6
10603	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS4, 90pc duty cycle)	WLAN	9.03	±9.6
10604	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS5, 90pc duty cycle)	WLAN	8.76	±9.6
10605	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS6, 90pc duty cycle)	WLAN	8.97	±9.6
10606	AAD	IEEE 802.11n (HT Mixed, 40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10607	AAD	IEEE 802.11ac WiFi (20 MHz, MCS0, 90pc duty cycle)	WLAN	8.64	±9.6
10608	AAD	IEEE 802.11ac WiFi (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.77	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10609	AAD	IEEE 802.11ac WiFi (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.57	±9.6
10610	AAD	IEEE 802.11ac WiFi (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.78	±9.6
10611	AAD	IEEE 802.11ac WiFi (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10612	AAD	IEEE 802.11ac WiFi (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10613	AAD	IEEE 802.11ac WiFi (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.94	±9.6
10614	AAD	IEEE 802.11ac WiFi (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.59	±9.6
10615	AAD	IEEE 802.11ac WiFi (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10616	AAD	IEEE 802.11ac WiFi (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.82	±9.6
10617	AAD	IEEE 802.11ac WiFi (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.81	±9.6
10618	AAD	IEEE 802.11ac WiFi (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.58	±9.6
10619	AAD	IEEE 802.11ac WiFi (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.86	±9.6
10620	AAD	IEEE 802.11ac WiFi (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.87	±9.6
10621	AAD	IEEE 802.11ac WiFi (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10622	AAD	IEEE 802.11ac WiFi (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.68	±9.6
10623	AAD	IEEE 802.11ac WiFi (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.82	±9.6
10624	AAD	IEEE 802.11ac WiFi (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.96	±9.6
10625	AAD	IEEE 802.11ac WiFi (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.96	±9.6
10626	AAD	IEEE 802.11ac WiFi (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10627	AAD	IEEE 802.11ac WiFi (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.88	±9.6
10628	AAD	IEEE 802.11ac WiFi (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.71	±9.6
10629	AAD	IEEE 802.11ac WiFi (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10630	AAD	IEEE 802.11ac WiFi (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.72	±9.6
10631	AAD	IEEE 802.11ac WiFi (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.81	±9.6
10632	AAD	IEEE 802.11ac WiFi (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10633	AAD	IEEE 802.11ac WiFi (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.83	±9.6
10634	AAD	IEEE 802.11ac WiFi (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.80	±9.6
10635	AAD	IEEE 802.11ac WiFi (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6
10636	AAE	IEEE 802.11ac WiFi (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.83	±9.6
10637	AAE	IEEE 802.11ac WiFi (160 MHz, MCS1, 90pc duty cycle)	WLAN	8.79	±9.6
10638	AAE	IEEE 802.11ac WiFi (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.86	±9.6
10639	AAE	IEEE 802.11ac WiFi (160 MHz, MCS3, 90pc duty cycle)	WLAN	8.85	±9.6
10640	AAE	IEEE 802.11ac WiFi (160 MHz, MCS4, 90pc duty cycle)	WLAN	8.98	±9.6
10641	AAE	IEEE 802.11ac WiFi (160 MHz, MCS5, 90pc duty cycle)	WLAN	9.06	±9.6
10642	AAE	IEEE 802.11ac WiFi (160 MHz, MCS6, 90pc duty cycle)	WLAN	9.06	±9.6
10643	AAE	IEEE 802.11ac WiFi (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.89	±9.6
10644	AAE	IEEE 802.11ac WiFi (160 MHz, MCS8, 90pc duty cycle)	WLAN	9.05	±9.6
10645	AAE	IEEE 802.11ac WiFi (160 MHz, MCS9, 90pc duty cycle)	WLAN	9.11	±9.6
10646	AAH	LTE-TDD (SC-FDMA, 1 RB, 5 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	LTE-TDD	11.96	±9.6
10648	AAA	CDMA2000 (1x Advanced)	CDMA2000	3.45	±9.6
10652	AAF	LTE-TDD (OFDMA, 5 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.91	±9.6
10653	AAF	LTE-TDD (OFDMA, 10 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.42	±9.6
10654	AAE	LTE-TDD (OFDMA, 15 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	6.96	±9.6
10655	AAF	LTE-TDD (OFDMA, 20 MHz, E-TM 3.1, Clipping 44%)	LTE-TDD	7.21	±9.6
10658	AAB	Pulse Waveform (200Hz, 10%)	Test	10.00	±9.6
10659	AAB	Pulse Waveform (200Hz, 20%)	Test	6.99	±9.6
10660	AAB	Pulse Waveform (200Hz, 40%)	Test	3.98	±9.6
10661	AAB	Pulse Waveform (200Hz, 60%)	Test	2.22	±9.6
10662	AAB	Pulse Waveform (200Hz, 80%)	Test	0.97	±9.6
10670	AAA	Bluetooth Low Energy	Bluetooth	2.19	±9.6
10671	AAC	IEEE 802.11ax (20 MHz, MCS0, 90pc duty cycle)	WLAN	9.09	±9.6
10672	AAC	IEEE 802.11ax (20 MHz, MCS1, 90pc duty cycle)	WLAN	8.57	±9.6
10673	AAC	IEEE 802.11ax (20 MHz, MCS2, 90pc duty cycle)	WLAN	8.78	±9.6
10674	AAC	IEEE 802.11ax (20 MHz, MCS3, 90pc duty cycle)	WLAN	8.74	±9.6
10675	AAC	IEEE 802.11ax (20 MHz, MCS4, 90pc duty cycle)	WLAN	8.90	±9.6
10676	AAC	IEEE 802.11ax (20 MHz, MCS5, 90pc duty cycle)	WLAN	8.77	±9.6
10677	AAC	IEEE 802.11ax (20 MHz, MCS6, 90pc duty cycle)	WLAN	8.73	±9.6
10678	AAC	IEEE 802.11ax (20 MHz, MCS7, 90pc duty cycle)	WLAN	8.78	±9.6
10679	AAC	IEEE 802.11ax (20 MHz, MCS8, 90pc duty cycle)	WLAN	8.89	±9.6
10680	AAC	IEEE 802.11ax (20 MHz, MCS9, 90pc duty cycle)	WLAN	8.80	±9.6
10681	AAC	IEEE 802.11ax (20 MHz, MCS10, 90pc duty cycle)	WLAN	8.62	±9.6
10682	AAC	IEEE 802.11ax (20 MHz, MCS11, 90pc duty cycle)	WLAN	8.83	±9.6
10683	AAC	IEEE 802.11ax (20 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10684	AAC	IEEE 802.11ax (20 MHz, MCS1, 99pc duty cycle)	WLAN	8.26	±9.6
10685	AAC	IEEE 802.11ax (20 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10686	AAC	IEEE 802.11ax (20 MHz, MCS3, 99pc duty cycle)	WLAN	8.28	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10687	AAC	IEEE 802.11ax (20 MHz, MCS4, 99pc duty cycle)	WLAN	8.45	±9.6
10688	AAC	IEEE 802.11ax (20 MHz, MCS5, 99pc duty cycle)	WLAN	8.29	±9.6
10689	AAC	IEEE 802.11ax (20 MHz, MCS6, 99pc duty cycle)	WLAN	8.55	±9.6
10690	AAC	IEEE 802.11ax (20 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
10691	AAC	IEEE 802.11ax (20 MHz, MCS8, 99pc duty cycle)	WLAN	8.25	±9.6
10692	AAC	IEEE 802.11ax (20 MHz, MCS9, 99pc duty cycle)	WLAN	8.29	±9.6
10693	AAC	IEEE 802.11ax (20 MHz, MCS10, 99pc duty cycle)	WLAN	8.25	±9.6
10694	AAC	IEEE 802.11ax (20 MHz, MCS11, 99pc duty cycle)	WLAN	8.57	±9.6
10695	AAC	IEEE 802.11ax (40 MHz, MCS0, 90pc duty cycle)	WLAN	8.78	±9.6
10696	AAC	IEEE 802.11ax (40 MHz, MCS1, 90pc duty cycle)	WLAN	8.91	±9.6
10697	AAC	IEEE 802.11ax (40 MHz, MCS2, 90pc duty cycle)	WLAN	8.61	±9.6
10698	AAC	IEEE 802.11ax (40 MHz, MCS3, 90pc duty cycle)	WLAN	8.89	±9.6
10699	AAC	IEEE 802.11ax (40 MHz, MCS4, 90pc duty cycle)	WLAN	8.82	±9.6
10700	AAC	IEEE 802.11ax (40 MHz, MCS5, 90pc duty cycle)	WLAN	8.73	±9.6
10701	AAC	IEEE 802.11ax (40 MHz, MCS6, 90pc duty cycle)	WLAN	8.86	±9.6
10702	AAC	IEEE 802.11ax (40 MHz, MCS7, 90pc duty cycle)	WLAN	8.70	±9.6
10703	AAC	IEEE 802.11ax (40 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10704	AAC	IEEE 802.11ax (40 MHz, MCS9, 90pc duty cycle)	WLAN	8.56	±9.6
10705	AAC	IEEE 802.11ax (40 MHz, MCS10, 90pc duty cycle)	WLAN	8.69	±9.6
10706	AAC	IEEE 802.11ax (40 MHz, MCS11, 90pc duty cycle)	WLAN	8.66	±9.6
10707	AAC	IEEE 802.11ax (40 MHz, MCS0, 99pc duty cycle)	WLAN	8.32	±9.6
10708	AAC	IEEE 802.11ax (40 MHz, MCS1, 99pc duty cycle)	WLAN	8.55	±9.6
10709	AAC	IEEE 802.11ax (40 MHz, MCS2, 99pc duty cycle)	WLAN	8.33	±9.6
10710	AAC	IEEE 802.11ax (40 MHz, MCS3, 99pc duty cycle)	WLAN	8.29	±9.6
10711	AAC	IEEE 802.11ax (40 MHz, MCS4, 99pc duty cycle)	WLAN	8.39	±9.6
10712	AAC	IEEE 802.11ax (40 MHz, MCS5, 99pc duty cycle)	WLAN	8.67	±9.6
10713	AAC	IEEE 802.11ax (40 MHz, MCS6, 99pc duty cycle)	WLAN	8.33	±9.6
10714	AAC	IEEE 802.11ax (40 MHz, MCS7, 99pc duty cycle)	WLAN	8.26	±9.6
10715	AAC	IEEE 802.11ax (40 MHz, MCS8, 99pc duty cycle)	WLAN	8.45	±9.6
10716	AAC	IEEE 802.11ax (40 MHz, MCS9, 99pc duty cycle)	WLAN	8.30	±9.6
10717	AAC	IEEE 802.11ax (40 MHz, MCS10, 99pc duty cycle)	WLAN	8.48	±9.6
10718	AAC	IEEE 802.11ax (40 MHz, MCS11, 99pc duty cycle)	WLAN	8.24	±9.6
10719	AAC	IEEE 802.11ax (80 MHz, MCS0, 90pc duty cycle)	WLAN	8.81	±9.6
10720	AAC	IEEE 802.11ax (80 MHz, MCS1, 90pc duty cycle)	WLAN	8.87	±9.6
10721	AAC	IEEE 802.11ax (80 MHz, MCS2, 90pc duty cycle)	WLAN	8.76	±9.6
10722	AAC	IEEE 802.11ax (80 MHz, MCS3, 90pc duty cycle)	WLAN	8.55	±9.6
10723	AAC	IEEE 802.11ax (80 MHz, MCS4, 90pc duty cycle)	WLAN	8.70	±9.6
10724	AAC	IEEE 802.11ax (80 MHz, MCS5, 90pc duty cycle)	WLAN	8.90	±9.6
10725	AAC	IEEE 802.11ax (80 MHz, MCS6, 90pc duty cycle)	WLAN	8.74	±9.6
10726	AAC	IEEE 802.11ax (80 MHz, MCS7, 90pc duty cycle)	WLAN	8.72	±9.6
10727	AAC	IEEE 802.11ax (80 MHz, MCS8, 90pc duty cycle)	WLAN	8.66	±9.6
10728	AAC	IEEE 802.11ax (80 MHz, MCS9, 90pc duty cycle)	WLAN	8.65	±9.6
10729	AAC	IEEE 802.11ax (80 MHz, MCS10, 90pc duty cycle)	WLAN	8.64	±9.6
10730	AAC	IEEE 802.11ax (80 MHz, MCS11, 90pc duty cycle)	WLAN	8.67	±9.6
10731	AAC	IEEE 802.11ax (80 MHz, MCS0, 99pc duty cycle)	WLAN	8.42	±9.6
10732	AAC	IEEE 802.11ax (80 MHz, MCS1, 99pc duty cycle)	WLAN	8.46	±9.6
10733	AAC	IEEE 802.11ax (80 MHz, MCS2, 99pc duty cycle)	WLAN	8.40	±9.6
10734	AAC	IEEE 802.11ax (80 MHz, MCS3, 99pc duty cycle)	WLAN	8.25	±9.6
10735	AAC	IEEE 802.11ax (80 MHz, MCS4, 99pc duty cycle)	WLAN	8.33	±9.6
10736	AAC	IEEE 802.11ax (80 MHz, MCS5, 99pc duty cycle)	WLAN	8.27	±9.6
10737	AAC	IEEE 802.11ax (80 MHz, MCS6, 99pc duty cycle)	WLAN	8.36	±9.6
10738	AAC	IEEE 802.11ax (80 MHz, MCS7, 99pc duty cycle)	WLAN	8.42	±9.6
10739	AAC	IEEE 802.11ax (80 MHz, MCS8, 99pc duty cycle)	WLAN	8.29	±9.6
10740	AAC	IEEE 802.11ax (80 MHz, MCS9, 99pc duty cycle)	WLAN	8.48	±9.6
10741	AAC	IEEE 802.11ax (80 MHz, MCS10, 99pc duty cycle)	WLAN	8.40	±9.6
10742	AAC	IEEE 802.11ax (80 MHz, MCS11, 99pc duty cycle)	WLAN	8.43	±9.6
10743	AAC	IEEE 802.11ax (160 MHz, MCS0, 90pc duty cycle)	WLAN	8.94	±9.6
10744	AAC	IEEE 802.11ax (160 MHz, MCS1, 90pc duty cycle)	WLAN	9.16	±9.6
10745	AAC	IEEE 802.11ax (160 MHz, MCS2, 90pc duty cycle)	WLAN	8.93	±9.6
10746	AAC	IEEE 802.11ax (160 MHz, MCS3, 90pc duty cycle)	WLAN	9.11	±9.6
10747	AAC	IEEE 802.11ax (160 MHz, MCS4, 90pc duty cycle)	WLAN	9.04	±9.6
10748	AAC	IEEE 802.11ax (160 MHz, MCS5, 90pc duty cycle)	WLAN	8.93	±9.6
10749	AAC	IEEE 802.11ax (160 MHz, MCS6, 90pc duty cycle)	WLAN	8.90	±9.6
10750	AAC	IEEE 802.11ax (160 MHz, MCS7, 90pc duty cycle)	WLAN	8.79	±9.6
10751	AAC	IEEE 802.11ax (160 MHz, MCS8, 90pc duty cycle)	WLAN	8.82	±9.6
10752	AAC	IEEE 802.11ax (160 MHz, MCS9, 90pc duty cycle)	WLAN	8.81	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10753	AAC	IEEE 802.11ax (160 MHz, MCS10, 90pc duty cycle)	WLAN	9.00	±9.6
10754	AAC	IEEE 802.11ax (160 MHz, MCS11, 90pc duty cycle)	WLAN	8.94	±9.6
10755	AAC	IEEE 802.11ax (160 MHz, MCS0, 99pc duty cycle)	WLAN	8.64	±9.6
10756	AAC	IEEE 802.11ax (160 MHz, MCS1, 99pc duty cycle)	WLAN	8.77	±9.6
10757	AAC	IEEE 802.11ax (160 MHz, MCS2, 99pc duty cycle)	WLAN	8.77	±9.6
10758	AAC	IEEE 802.11ax (160 MHz, MCS3, 99pc duty cycle)	WLAN	8.69	±9.6
10759	AAC	IEEE 802.11ax (160 MHz, MCS4, 99pc duty cycle)	WLAN	8.58	±9.6
10760	AAC	IEEE 802.11ax (160 MHz, MCS5, 99pc duty cycle)	WLAN	8.49	±9.6
10761	AAC	IEEE 802.11ax (160 MHz, MCS6, 99pc duty cycle)	WLAN	8.58	±9.6
10762	AAC	IEEE 802.11ax (160 MHz, MCS7, 99pc duty cycle)	WLAN	8.49	±9.6
10763	AAC	IEEE 802.11ax (160 MHz, MCS8, 99pc duty cycle)	WLAN	8.53	±9.6
10764	AAC	IEEE 802.11ax (160 MHz, MCS9, 99pc duty cycle)	WLAN	8.54	±9.6
10765	AAC	IEEE 802.11ax (160 MHz, MCS10, 99pc duty cycle)	WLAN	8.54	±9.6
10766	AAC	IEEE 802.11ax (160 MHz, MCS11, 99pc duty cycle)	WLAN	8.51	±9.6
10767	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	7.99	±9.6
10768	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10769	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.01	±9.6
10770	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10771	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10772	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.23	±9.6
10773	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.03	±9.6
10774	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.02	±9.6
10775	AAF	5G NR (CP-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10776	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10777	AAC	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.30	±9.6
10778	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.34	±9.6
10779	AAC	5G NR (CP-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.42	±9.6
10780	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10781	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.38	±9.6
10782	AAE	5G NR (CP-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.43	±9.6
10783	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.31	±9.6
10784	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.29	±9.6
10785	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.40	±9.6
10786	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.35	±9.6
10787	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.44	±9.6
10788	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10789	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.37	±9.6
10790	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	8.39	±9.6
10791	AAG	5G NR (CP-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.83	±9.6
10792	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.92	±9.6
10793	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.95	±9.6
10794	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10795	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.84	±9.6
10796	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.82	±9.6
10797	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.01	±9.6
10798	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10799	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10801	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.89	±9.6
10802	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.87	±9.6
10803	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	7.93	±9.6
10805	AAE	5G NR (CP-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10806	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.37	±9.6
10809	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10810	AAF	5G NR (CP-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10812	AAF	5G NR (CP-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10817	AAG	5G NR (CP-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.35	±9.6
10818	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.34	±9.6
10819	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.33	±9.6
10820	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.30	±9.6
10821	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10822	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10823	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.36	±9.6
10824	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.39	±9.6
10825	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.41	±9.6
10827	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.42	±9.6
10828	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10829	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	8.40	±9.6
10830	AAE	5G NR (CP-OFDM, 1 RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.63	±9.6
10831	AAD	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.73	±9.6
10832	AAE	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.74	±9.6
10833	AAD	5G NR (CP-OFDM, 1 RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10834	AAE	5G NR (CP-OFDM, 1 RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.75	±9.6
10835	AAF	5G NR (CP-OFDM, 1 RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10836	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.66	±9.6
10837	AAF	5G NR (CP-OFDM, 1 RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.68	±9.6
10839	AAF	5G NR (CP-OFDM, 1 RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.70	±9.6
10840	AAE	5G NR (CP-OFDM, 1 RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.67	±9.6
10841	AAF	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	7.71	±9.6
10843	AAD	5G NR (CP-OFDM, 50% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.49	±9.6
10844	AAE	5G NR (CP-OFDM, 50% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10846	AAE	5G NR (CP-OFDM, 50% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10854	AAE	5G NR (CP-OFDM, 100% RB, 10 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10855	AAD	5G NR (CP-OFDM, 100% RB, 15 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10856	AAE	5G NR (CP-OFDM, 100% RB, 20 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10857	AAD	5G NR (CP-OFDM, 100% RB, 25 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.35	±9.6
10858	AAE	5G NR (CP-OFDM, 100% RB, 30 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.36	±9.6
10859	AAF	5G NR (CP-OFDM, 100% RB, 40 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.34	±9.6
10860	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10861	AAF	5G NR (CP-OFDM, 100% RB, 60 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.40	±9.6
10863	AAF	5G NR (CP-OFDM, 100% RB, 80 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10864	AAE	5G NR (CP-OFDM, 100% RB, 90 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.37	±9.6
10865	AAF	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 60 kHz)	5G NR FR1 TDD	8.41	±9.6
10866	AAF	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10868	AAF	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.89	±9.6
10869	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10870	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.86	±9.6
10871	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10872	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.52	±9.6
10873	AAE	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10874	AAE	5G NR (DFT-s-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10875	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10876	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.39	±9.6
10877	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	7.95	±9.6
10878	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10879	AAE	5G NR (CP-OFDM, 1 RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.12	±9.6
10880	AAE	5G NR (CP-OFDM, 100% RB, 100 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.38	±9.6
10881	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.75	±9.6
10882	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	5.96	±9.6
10883	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.57	±9.6
10884	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	6.53	±9.6
10885	AAE	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.61	±9.6
10886	AAE	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	6.65	±9.6
10887	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	7.78	±9.6
10888	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, QPSK, 120 kHz)	5G NR FR2 TDD	8.35	±9.6
10889	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.02	±9.6
10890	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 16QAM, 120 kHz)	5G NR FR2 TDD	8.40	±9.6
10891	AAE	5G NR (CP-OFDM, 1 RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.13	±9.6
10892	AAE	5G NR (CP-OFDM, 100% RB, 50 MHz, 64QAM, 120 kHz)	5G NR FR2 TDD	8.41	±9.6
10897	AAE	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.66	±9.6
10898	AAC	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10899	AAB	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.67	±9.6
10900	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10901	AAB	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10902	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10903	AAD	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10904	AAC	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10905	AAD	5G NR (DFT-s-OFDM, 1 RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10906	AAD	5G NR (DFT-s-OFDM, 1 RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.68	±9.6
10907	AAE	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.78	±9.6
10908	AAC	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10909	AAB	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.96	±9.6
10910	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E k = 2
10911	AAB	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.93	±9.6
10912	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10913	AAD	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10914	AAC	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.85	±9.6
10915	AAD	5G NR (DFT-s-OFDM, 50% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.83	±9.6
10916	AAD	5G NR (DFT-s-OFDM, 50% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10917	AAD	5G NR (DFT-s-OFDM, 50% RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10918	AAE	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10919	AAC	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.86	±9.6
10920	AAB	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.87	±9.6
10921	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10922	AAB	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.82	±9.6
10923	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10924	AAD	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10925	AAC	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.95	±9.6
10926	AAD	5G NR (DFT-s-OFDM, 100% RB, 60 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.84	±9.6
10927	AAD	5G NR (DFT-s-OFDM, 100% RB, 80 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	5.94	±9.6
10928	AAD	5G NR (DFT-s-OFDM, 1 RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10929	AAD	5G NR (DFT-s-OFDM, 1 RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10930	AAC	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.52	±9.6
10931	AAC	5G NR (DFT-s-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10932	AAC	5G NR (DFT-s-OFDM, 1 RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10933	AAC	5G NR (DFT-s-OFDM, 1 RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10934	AAC	5G NR (DFT-s-OFDM, 1 RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10935	AAD	5G NR (DFT-s-OFDM, 1 RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.51	±9.6
10936	AAD	5G NR (DFT-s-OFDM, 50% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10937	AAD	5G NR (DFT-s-OFDM, 50% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.77	±9.6
10938	AAC	5G NR (DFT-s-OFDM, 50% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.90	±9.6
10939	AAC	5G NR (DFT-s-OFDM, 50% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.82	±9.6
10940	AAC	5G NR (DFT-s-OFDM, 50% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.89	±9.6
10941	AAC	5G NR (DFT-s-OFDM, 50% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10942	AAC	5G NR (DFT-s-OFDM, 50% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10943	AAD	5G NR (DFT-s-OFDM, 50% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.95	±9.6
10944	AAD	5G NR (DFT-s-OFDM, 100% RB, 5 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.81	±9.6
10945	AAD	5G NR (DFT-s-OFDM, 100% RB, 10 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.85	±9.6
10946	AAC	5G NR (DFT-s-OFDM, 100% RB, 15 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.83	±9.6
10947	AAC	5G NR (DFT-s-OFDM, 100% RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10948	AAC	5G NR (DFT-s-OFDM, 100% RB, 25 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10949	AAC	5G NR (DFT-s-OFDM, 100% RB, 30 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.87	±9.6
10950	AAC	5G NR (DFT-s-OFDM, 100% RB, 40 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.94	±9.6
10951	AAD	5G NR (DFT-s-OFDM, 100% RB, 50 MHz, QPSK, 15 kHz)	5G NR FR1 FDD	5.92	±9.6
10952	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.25	±9.6
10953	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.15	±9.6
10954	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.23	±9.6
10955	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.42	±9.6
10956	AAA	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.14	±9.6
10957	AAA	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.31	±9.6
10958	AAA	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.61	±9.6
10959	AAA	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.33	±9.6
10960	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.32	±9.6
10961	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.36	±9.6
10962	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.40	±9.6
10963	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.55	±9.6
10964	AAE	5G NR DL (CP-OFDM, TM 3.1, 5 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.29	±9.6
10965	AAC	5G NR DL (CP-OFDM, TM 3.1, 10 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.37	±9.6
10966	AAB	5G NR DL (CP-OFDM, TM 3.1, 15 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.55	±9.6
10967	AAC	5G NR DL (CP-OFDM, TM 3.1, 20 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.42	±9.6
10968	AAD	5G NR DL (CP-OFDM, TM 3.1, 100 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.49	±9.6
10972	AAC	5G NR (CP-OFDM, 1 RB, 20 MHz, QPSK, 15 kHz)	5G NR FR1 TDD	11.59	±9.6
10973	AAD	5G NR (DFT-s-OFDM, 1 RB, 100 MHz, QPSK, 30 kHz)	5G NR FR1 TDD	9.06	±9.6
10974	AAD	5G NR (CP-OFDM, 100% RB, 100 MHz, 256-QAM, 30 kHz)	5G NR FR1 TDD	10.28	±9.6
10978	AAA	ULLA BDR	ULLA	1.16	±9.6
10979	AAA	ULLA HDR4	ULLA	8.58	±9.6
10980	AAA	ULLA HDR8	ULLA	10.32	±9.6
10981	AAA	ULLA HDRp4	ULLA	3.19	±9.6
10982	AAA	ULLA HDRp8	ULLA	3.43	±9.6

UID	Rev	Communication System Name	Group	PAR (dB)	Unc ^E $k = 2$
10983	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.31	±9.6
10984	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	9.42	±9.6
10985	AAC	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.54	±9.6
10986	AAB	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.50	±9.6
10987	AAC	5G NR DL (CP-OFDM, TM 3.1, 60 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.53	±9.6
10988	AAB	5G NR DL (CP-OFDM, TM 3.1, 70 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.38	±9.6
10989	AAC	5G NR DL (CP-OFDM, TM 3.1, 80 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.33	±9.6
10990	AAB	5G NR DL (CP-OFDM, TM 3.1, 90 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	9.52	±9.6
11003	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 TDD	10.24	±9.6
11004	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 TDD	10.73	±9.6
11005	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.70	±9.6
11006	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.55	±9.6
11007	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.46	±9.6
11008	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 15 kHz)	5G NR FR1 FDD	8.51	±9.6
11009	AAA	5G NR DL (CP-OFDM, TM 3.1, 25 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.76	±9.6
11010	AAA	5G NR DL (CP-OFDM, TM 3.1, 30 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.95	±9.6
11011	AAA	5G NR DL (CP-OFDM, TM 3.1, 40 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.96	±9.6
11012	AAA	5G NR DL (CP-OFDM, TM 3.1, 50 MHz, 64-QAM, 30 kHz)	5G NR FR1 FDD	8.68	±9.6
11013	AAB	IEEE 802.11be (320 MHz, MCS1, 99pc duty cycle)	WLAN	8.47	±9.6
11014	AAB	IEEE 802.11be (320 MHz, MCS2, 99pc duty cycle)	WLAN	8.45	±9.6
11015	AAB	IEEE 802.11be (320 MHz, MCS3, 99pc duty cycle)	WLAN	8.44	±9.6
11016	AAB	IEEE 802.11be (320 MHz, MCS4, 99pc duty cycle)	WLAN	8.44	±9.6
11017	AAB	IEEE 802.11be (320 MHz, MCS5, 99pc duty cycle)	WLAN	8.41	±9.6
11018	AAB	IEEE 802.11be (320 MHz, MCS6, 99pc duty cycle)	WLAN	8.40	±9.6
11019	AAB	IEEE 802.11be (320 MHz, MCS7, 99pc duty cycle)	WLAN	8.29	±9.6
11020	AAB	IEEE 802.11be (320 MHz, MCS8, 99pc duty cycle)	WLAN	8.27	±9.6
11021	AAB	IEEE 802.11be (320 MHz, MCS9, 99pc duty cycle)	WLAN	8.46	±9.6
11022	AAB	IEEE 802.11be (320 MHz, MCS10, 99pc duty cycle)	WLAN	8.36	±9.6
11023	AAB	IEEE 802.11be (320 MHz, MCS11, 99pc duty cycle)	WLAN	8.09	±9.6
11024	AAB	IEEE 802.11be (320 MHz, MCS12, 99pc duty cycle)	WLAN	8.42	±9.6
11025	AAB	IEEE 802.11be (320 MHz, MCS13, 99pc duty cycle)	WLAN	8.37	±9.6
11026	AAB	IEEE 802.11be (320 MHz, MCS0, 99pc duty cycle)	WLAN	8.39	±9.6

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.