

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Report No.: RFCDVB-WTW-P22080669G-1

FCC ID: QYLFN990K12

Product: 5G NR Module

Brand: Getac

Model No.: FN990A28

Received Date: 2025/11/14

Test Date: 2025/12/2 ~ 2026/1/8

Issued Date: 2026/1/12

Applicant: Getac Technology Corporation.

Address: 5F., Building A, No. 209, Sec.1, Nangang Rd., Nangang Dist., Taipei City 115018, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan

FCC Registration / 788550 / TW0003

Designation Number:

Approved by: Jeremy Lin, **Date:** 2026/1/12

This test report consists of 55 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Polly Chien / Specialist



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Supplementary Information	5
3 General Information	6
3.1 General Description of EUT	6
3.2 Antenna Description of EUT	9
3.3 Test Mode Applicability and Tested Channel Detail.....	10
3.3.1 LTE Band 48	10
3.4 Test Program Used and Operation Descriptions	12
3.5 Connection Diagram of EUT and Peripheral Devices	12
3.6 Configuration of Peripheral Devices and Cable Connections	14
4 Test Instruments	15
4.1 Maximum EIRP	15
4.2 Radiated Spurious Emissions below 1GHz	15
4.3 Radiated Spurious Emissions above 1GHz	16
5 Limits of Test Items.....	17
5.1 Maximum EIRP	17
5.2 Radiated Spurious Emissions below 1GHz	17
5.3 Radiated Spurious Emissions above 1GHz	17
6 Test Arrangements	18
6.1 Maximum EIRP	18
6.1.1 Test Setup	18
6.1.2 Test Procedure	18
6.2 Radiated Spurious Emissions below 1GHz	20
6.2.1 Test Setup	20
6.2.2 Test Procedure	21
6.3 Radiated Spurious Emissions above 1GHz	22
6.3.1 Test Setup	22
6.3.2 Test Procedure	22
7 Test Results of Test Item	23
7.1 Maximum EIRP	23
7.1.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)	23
7.1.2 LTE Band 48C (3.55 GHz ~ 3.7 GHz).....	35
7.2 Radiated Spurious Emissions below 1GHz	41
7.2.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)	41
7.3 Radiated Spurious Emissions above 1GHz	45
7.3.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)	45
7.3.2 LTE Band 48C (3.55 GHz ~ 3.7 GHz).....	51
8 Pictures of Test Arrangements	54
9 Information of the Testing Laboratories	55

Release Control Record

Issue No.	Description	Date Issued
RFCDVB-WTW-P22080669G-1	Original release.	2026/1/12

1 Certificate

Product: 5G NR Module

Brand: Getac

Test Model: FN990A28

Sample Status: Engineering sample

Applicant: Getac Technology Corporation.

Test Date: 2025/12/2 ~ 2026/1/8

Standard: 47 CFR FCC Part 96
47 CFR FCC Part 2

Measurement ANSI/TIA/EIA-603-E 2016

procedure: ANSI C63.26-2015

KDB 971168 D01 Power Meas License Digital Systems v03r01

KDB 940660 D01 Part 96 CBRS Eqpt v03

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

Standard / Clause	Test Item	Result	Remark
Part 2.1046 Part 96.41(b)	Maximum EIRP	Pass	Meet the requirement of limit.
Part 2.1047	Modulation Characteristics	N/A	Refer to Note
Part 2.1046 Part 96.41(b)	Maximum Power Spectral Density	N/A	This device is End User Device.
Part 96.41(g)	Peak to Average Ratio	N/A	Refer to Note
Part 2.1049	Bandwidth	N/A	Refer to Note
Part 2.1051 Part 96.41(e)	Conducted Spurious Emissions	N/A	Refer to Note
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions below 1GHz	Pass	Minimum passing margin is -5.08 dB at 88.20 MHz
Part 2.1053 Part 96.41(e)	Radiated Spurious Emissions above 1GHz	Pass	Minimum passing margin is -0.28 dB at 7380.00 MHz
Part 2.1055	Frequency Stability	N/A	Refer to Note

Note:

1. Only test item of Equivalent Isotropically Radiated Power and Radiated Spurious Emissions were performed for this report. Other testing data please refer to WWAN module (FCC ID: RI7FN990A28) certified report.
2. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
Equivalent Isotropically Radiated Power	-	1.371 dB
Radiated Spurious Emissions below 1GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.6 dB
Radiated Spurious Emissions above 1GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	5G NR Module
Brand	Getac
Test Model	FN990A28
Status of EUT	Engineering sample
Power Supply Rating	3.3Vdc from host equipment
Modulation Type	QPSK, 16QAM, 64QAM, 256QAM
LTE support band	B43, B48
LTE band support CA mode	43C, 48C
Band Covered Information	B48 cover B43

Note:

1. The EUT is authorized for use in specific End-product. Please refer to below for more details.

Product	Brand	Model	Difference
Tablet	Getac	K120G3	For marketing purpose
		K120Y (Y= 10 characters, Y can be 0-9, a-z, A-Z, "-", "_" or blank for marketing purpose and no impact safety related critical components and constructions.)	

2. The End-product uses following accessories.

1. This End Product uses following accessories:

Adapter 1		
Brand	Model	Specification
Chicony	A20-065N3A	I/P: 100-240Vac, 50-60Hz, 1.6A O/P: 5.0V, 3.0A, 15.0W / 9V, 3A / 12V, 3A / 15V, 3A / 20.0V, 3.25A, 65.0W 1.45m non-shielded DC cable no core
Adapter 2		
Brand	Model	Specification
FSP	FSP065-RBBN3	I/P: 100-240Vac, 50-60Hz, 1.5A O/P: 19.0Vdc, 3.42A, 65.0W 1.5m non-shielded DC cable no core
Battery 1		
Brand	Model	Specification
Getac	BP3S1P2100S-01	Rating: 11.1Vdc 2040mAh, 23Wh Typical Capacity: 2100mAh, 24Wh
Battery 2		
Brand	Model	Specification
Getac	BP4S1P3450P-01	Rating: 14.4Vdc 3300mAh, 48Wh Typical Capacity: 3450mAh, 50Wh
Touch Pen		
Brand	Model	Description
Getac	340142000064	2.8mm + 1500g Spring
K120 Keyboard Dock (Support Unit)		
Brand	Model	Description
Getac	K120-KeyBoard Dock 3.0	-

3. EUT Overview

LTE Band 48 (3.55 GHz ~ 3.7 GHz)

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
5 MHz	3552.5 ~ 3697.5	QPSK	0.036	15.58
		16QAM	0.029	14.62
		64QAM	0.024	13.79
		256QAM	0.012	10.74
10 MHz	3555 ~ 3695	QPSK	0.035	15.44
		16QAM	0.028	14.47
		64QAM	0.023	13.63
		256QAM	0.012	10.64
15 MHz	3557.5 ~ 3692.5	QPSK	0.035	15.45
		16QAM	0.028	14.42
		64QAM	0.023	13.59
		256QAM	0.012	10.64
20 MHz	3560 ~ 3690	QPSK	0.036	15.59
		16QAM	0.029	14.64
		64QAM	0.024	13.76
		256QAM	0.012	10.76

LTE Band 48C (3.55 GHz ~ 3.7 GHz)

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
20 MHz + 20 MHz	3560 ~ 3690	QPSK	0.003	4.77
		16QAM	0.002	3.44
		64QAM	0.002	2.89
		256QAM	0.001	1.31
20 MHz + 15 MHz	3560 ~ 3692.2	QPSK	0.003	4.66
		16QAM	0.002	3.38
		64QAM	0.002	2.79
		256QAM	0.001	1.23
15 MHz + 20 MHz	3557.8 ~ 3690	QPSK	0.003	4.73
		16QAM	0.002	3.34
		64QAM	0.002	2.83
		256QAM	0.001	1.20
20 MHz + 10 MHz	3560 ~ 3694.5	QPSK	0.003	4.73
		16QAM	0.002	3.37
		64QAM	0.002	2.78
		256QAM	0.001	1.24
10 MHz + 20 MHz	3555.5 ~ 3690	QPSK	0.003	4.67
		16QAM	0.002	3.36
		64QAM	0.002	2.81
		256QAM	0.001	1.26

Bandwidth	TX Frequency Range (MHz)	Modulation	Max. EIRP (W)	Max. EIRP (dBm)
20 MHz + 5 MHz	3560 ~ 3696.7	QPSK	0.003	4.73
		16QAM	0.002	3.36
		64QAM	0.002	2.87
		256QAM	0.001	1.25
5 MHz + 20 MHz	3553.3 ~ 3565	QPSK	0.003	4.71
		16QAM	0.002	3.42
		64QAM	0.002	2.79
		256QAM	0.001	1.19

4. The EUT support the following CA Configuration.

Band Configuration
48C

5. E-UTRA CA configuration / Bandwidth combination set.

E-UTRA CA configuration / Bandwidth combination set		
E-UTRA CA Configuration	Component carriers in order of increasing carrier frequency Channel bandwidth for PCC and SCC [MHz]	Maximum aggregated bandwidth [MHz]
CA_48C	20+5 / 5+20	25
	20+10 / 10+20	30
	20+15 / 15+20	35
	20+20	40

* For CA mode configuration, please consult the manufacturer to declare the test mode.

* 48C is continuous CA and maximum combination is 20M+20M.

6. For detailed information about each WWAN bands frequency range, bandwidth mode of the product, please refer to section 3.3 of the report.

7. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Ant. 0		Ant. 1	
Antenna Type	PIFA	Antenna Type	PIFA
Connector Type	I-PEX	Connector Type	I-PEX
Brand	AWAN	Brand	AWAN
Model	422144600011	Model	422144600028

Band		Freq. Range (MHz)	Ant. 0 Gain (dBi)	Ant. 1 Gain (dBi)
LTE Band 42	1TX (Ant. 0)	3400 ~ 3600	-5.20	-7.14
LTE Band 43	1TX (Ant. 0)	3600 ~ 3800	-5.43	-6.65
LTE Band 48	1TX (Ant. 0)	3550 ~ 3700	-5.61	-7.14

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

3.3 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. The EUT has the following Battery: Battery 1 / Battery 2. Pre-scan these batteries and find the worst case as a representative test condition. 2. The EUT has the following Adapter: Adapter 1 / Adapter 2. Pre-scan these batteries and find the worst case as a representative test condition. 3. EUT can be used in the following ways: X-axis / Y-axis / Z-axis. Pre-scan these ways and find the worst case as a representative test condition.
Worst Case:	1. Battery Worst Condition: Battery 2 2. Adapter Worst Condition: Adapter 1 3. X-axis/ Y-axis/ Z-axis Worst Condition: X-axis (Tablet Mode)

3.3.1 LTE Band 48

Test Item	EUT Configure Mode	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum EIRP	A	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55290(3555.00 MHz) 55990(3625.00 MHz) 56690(3695.00 MHz)	10 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55315(3557.50 MHz) 55990(3625.00 MHz) 56665(3692.50 MHz)	15 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
	A	55340(3560.00 MHz) + 55538(3579.80 MHz) 55891(3615.10 MHz) + 56089(3634.90 MHz) 56442(3670.20 MHz) + 56640(3690.00 MHz)	20 MHz + 20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55340(3560.00 MHz) + 55511(3577.10 MHz) 55916(3617.60 MHz) + 56087(3634.70 MHz) 56491(3675.10 MHz) + 56662(3692.20 MHz)	20 MHz + 15 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55318(3557.80 MHz) + 55489(3574.90 MHz) 55893(3615.30 MHz) + 56064(3632.40 MHz) 56469(3672.90 MHz) + 56640(3690.00 MHz)	15 MHz + 20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55340(3560.00 MHz) + 55484(3574.40 MHz) 55941(3620.10 MHz) + 56085(3634.50 MHz) 56541(3680.10 MHz) + 56685(3694.50 MHz)	20 MHz + 10 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB


Test Item	EUT Configure Mode	Tested Channel	Channel Bandwidth	Modulation	Mode
Maximum EIRP	A	55295(3555.50 MHz) + 55439(3569.90 MHz) 55896(3615.60 MHz) + 56040(3630.00 MHz) 56496(3675.60 MHz) + 56640(3690.00 MHz)	10 MHz + 20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55340(3560.00 MHz) + 55457(3571.70 MHz) 55965(3622.50 MHz) + 56082(3634.20 MHz) 56590(3685.00 MHz) + 56707(3696.70 MHz)	20 MHz + 5 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
		55273(3553.30 MHz) + 55390(3565.00 MHz) 55898(3615.80 MHz) + 56015(3627.50 MHz) 56523(3678.30 MHz) + 56640(3690.00 MHz)	5 MHz + 20 MHz	QPSK / 16QAM / 64QAM / 256QAM	1 RB Half RB Full RB
Radiated Spurious Emissions below 1GHz	A, B	56640(3690.00 MHz)	20 MHz	QPSK	1 RB
Radiated Spurious Emissions above 1GHz	A	55265(3552.50 MHz) 55990(3625.00 MHz) 56715(3697.50 MHz)	5 MHz	QPSK	1 RB
		55340(3560.00 MHz) 55990(3625.00 MHz) 56640(3690.00 MHz)	20 MHz	QPSK	1 RB
	A	55340(3560.00 MHz) + 55538(3579.80 MHz) 55891(3615.10 MHz) + 56089(3634.90 MHz) 56442(3670.20 MHz) + 56640(3690.00 MHz)	20 MHz + 20 MHz	QPSK	1 RB
EUT Configure Mode:	A	Tablet Mode			
	B	NB Mode			
Note: LTE Band 42 and Band 43 is already covered by the current test results of LTE Band 48.					

3.4 Test Program Used and Operation Descriptions


There is no need to controlling software during the test, and the EUT can be paired with the Radio Communication Analyzer to test the connection when it is powered on.

3.5 Connection Diagram of EUT and Peripheral Devices

Mode A



Mode B



3.6 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	Chicony	A20-065N3A	N/A	N/A	Supplied by applicant
B	USB Flash	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab
C	USB Flash	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab
D	USB Flash	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab
E	Earphone	APPLE	MB77PFEB	N/A	N/A	Provided by Lab
F	Load	N/A	N/A	N/A	N/A	Provided by Lab
G	Radio Communication Analyzer	Anritsu	MT8821C	6201462755	N/A	Provided by Lab
H	Tablet	Getac	K120G3	N/A	N/A	Supplied by applicant
I	USB Flash	SanDisk	SDDDC3-032G	NA	NA	Provided by Lab
J	USB Flash	SanDisk	SDDDC3-032G	NA	NA	Provided by Lab
K	USB Flash	SanDisk	SDDDC3-032G	NA	NA	Provided by Lab
L	USB Flash	SanDisk	SDDDC3-032G	NA	NA	Provided by Lab
M	Monitor	DELL	A14S2421HSXmTW	CN-01KFWF-WSL00-24C-714B	NA	Provided by Lab
N	Monitor	DELL	A14S2421HSXmTW	CN-01KFWF-WSL00-24C-711B	NA	Provided by Lab
O	K120 Keyboard Dock	Getac	K120-Detachable Keyboard 3.0	NA	NA	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	RJ-45 Cable	1	1.5	N	0	Provided by Lab
2	RJ-45 Cable	1	1.5	N	0	Provided by Lab
3	Console Cable	1	1.5	N	0	Provided by Lab
4	HDMI Cable	1	1.5	N	0	Provided by Lab
5	DP Cable	1	1.5	N	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Maximum EIRP

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030B	MY57140938	2025/3/24	2026/3/23
Radio Communication Analyzer Anritsu	MT8821C	6201462755	2025/4/8	2026/4/7
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/12/3 ~ 2025/12/5

4.2 Radiated Spurious Emissions below 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-160	2025/9/16	2026/9/15
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
Preamplifier Agilent	8447D	2944A10638	2025/4/27	2026/4/26
Preamplifier EMCI	EMC001340	980201	2025/9/21	2026/9/20
RF Coaxial Cable Woken	8D-FB	Cable-CH9-01	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSW43	101866	2025/3/25	2026/3/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/12/3 ~ 2026/1/8

4.3 Radiated Spurious Emissions above 1GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower & Turn BV ADT	AT100	AT93021705	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1169	2025/11/9	2026/11/8
	BBHA 9170	9170-480	2025/11/9	2026/11/8
		BBHA9170243	2025/11/9	2026/11/8
Preamplifier Agilent	8449B	3008A02367	2025/1/5	2026/1/4
Preamplifier EMCI	EMC 184045	980116	2025/9/21	2026/9/20
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2025/6/30	2026/6/29
	EMC102-KM-KM-3000	150929	2025/6/30	2026/6/29
RF Coaxial Cable HUBER+SUHNER	SUCOFLEX 104	CABLE-CH9-(250795/4)	2025/1/5	2026/1/4
RF Coaxial Cable HUBER+SUHNER&EMCI	SUCOFLEX 104& EMC104-SM-SM8000	CABLE-CH9-02 (248780+171006)	2025/1/5	2026/1/4
Signal & Spectrum Analyzer R&S	FSW43	101866	2025/3/25	2026/3/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 4.
2. Tested Date: 2025/12/2

5 Limits of Test Items

5.1 Maximum EIRP

For LTE Band 48 / LTE Band 48C (3.55 GHz ~ 3.7 GHz):

Device Category	Maximum EIRP (dBm/10 MHz)
End User Device	23
Category A CBSD	30
Category B CBSD	47

5.2 Radiated Spurious Emissions below 1GHz

For LTE Band 48 / LTE Band 48C (3.55 GHz ~ 3.7 GHz):

The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40 dBm/MHz.

5.3 Radiated Spurious Emissions above 1GHz

For LTE Band 48 / LTE Band 48C (3.55 GHz ~ 3.7 GHz):


The power of any emissions below 3530 MHz or above 3720 MHz shall not exceed -40dBm/MHz.

6 Test Arrangements


6.1 Maximum EIRP

6.1.1 Test Setup

Conducted Power Measurement:



For measuring output power using spectrum



6.1.2 Test Procedure

Conducted Power Measurement:

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology. The average (rms) power measurement was performed on emulator and power value was measured from power function on emulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

For measuring output power using spectrum

The EUT is configured by emulator to set data modulation and maximum power using WWAN technology and link to spectrum analyzer measurements. Set the EUT to transmit under low, middle and high channel and record the power level shown on spectrum analyzer. Power measurements use detector average (rms).

For measuring output power using spectrum

Measurement method refers to ANSI C63.26 section 5.2.4.4.

- Set span to $2 \times$ to $3 \times$ the OBW.
- Set RBW = 1% to 5% of the OBW.
- Set VBW $\geq 3 \times$ RBW.
- Set number of measurement points in sweep $\geq 2 \times$ span / RBW.
- Set Sweep time = auto-couple.
- Detector = power averaging (rms).
- Set sweep trigger to "free run."
- Trace average at least 100 traces in power averaging (rms) mode.
- Use the Band/Channel Power function to determine the integrated power per 10 MHz bandwidth and full bandwidth, according to the 47 CFR FCC Part 96 standard.
- If Duty cycle < 98%, Add $10 \log (1/\text{duty cycle})$ to the measured power level to compute the average power during continuous transmission.

Maximum EIRP / ERP

The relevant equation for determining the maximum ERP or EIRP from the measured RF output power is given in Equation as follows:

$$\text{EIRP} = P_{\text{Meas}} + G_T$$

$$\text{ERP} = P_{\text{Meas}} + G_T - 2.15$$

where

ERP or EIRP effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , e.g., dBm or dBW)


P_{Meas} measured transmitter output power or PSD, in dBm or dBW

G_T gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP)


6.2 Radiated Spurious Emissions below 1GHz

6.2.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.2.2 Test Procedure

The EUT is configured to set data modulation and maximum power using WWAN technology.

- a. In the semi-anechoic chamber, EUT placed on the 0.8 m (below or equal 1 GHz) height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- c. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- d. Following ANSI C63.26 section 5.5 and 5.2.7
- e. $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- f. $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.


Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.
2. The amplitude of spurious emissions in the range 9 kHz to 30 MHz which are attenuated more than 20 dB below the permissible value need not be reported.

6.3 Radiated Spurious Emissions above 1GHz

6.3.1 Test Setup

For radiated emission above 1 GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.3.2 Test Procedure

The EUT is configured to set data modulation and maximum power using WWAN technology.

- In the semi-anechoic chamber, EUT placed on the 1.5 m height of turn table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1 m to 4 m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP/ERP level.
- Following ANSI C63.26 section 5.5 and 5.2.7
- $EIRP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8$; where D is the measurement distance (in the far field region) in m.
- $ERP (dBm) = E (dB\mu V/m) + 20\log(D) - 104.8 - 2.15$; where D is the measurement distance (in the far field region) in m.

Note: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz/3 MHz. Set detector = average.

7 Test Results of Test Item

7.1 Maximum EIRP

Environmental Conditions:	23°C, 62% RH	Tested By:	Charles Hsiao
---------------------------	--------------	------------	---------------

7.1.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 5 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55265	CH 55990	CH 56715
			3552.5 MHz	3625 MHz	3697.5 MHz
QPSK	1	0	21.15	21.01	21.19
	1	12	21.11	21.09	21.03
	1	24	21.09	21.09	21.08
	12	0	20.43	20.27	20.34
	12	6	20.3	20.2	20.34
	12	13	20.21	20.19	20.34
	25	0	20.31	20.19	20.3
16QAM	1	0	20.23	20.17	20.17
	1	12	20.11	20.07	20.05
	1	24	20.08	20.06	20.12
	12	0	19.3	19.25	19.29
	12	6	19.26	19.27	19.27
	12	13	19.21	19.17	19.25
	25	0	19.37	19.29	19.29
64QAM	1	0	19.38	19.29	19.4
	1	12	19.23	19.15	19.13
	1	24	19.13	19.03	19.08
	12	0	18.33	18.44	18.31
	12	6	18.21	18.19	18.21
	12	13	18.18	18.14	18.18
	25	0	18.38	18.3	18.39
256QAM	1	0	16.26	16.18	16.22
	1	12	16.13	16.11	16.08
	1	24	16.11	15.94	16.06
	12	0	16.31	16.28	16.29
	12	6	16.29	16.24	16.3
	12	13	16.18	16.23	16.3
	25	0	16.35	16.2	16.27

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	20.19	21.19	14.58	15.58	23
16QAM	19.17	20.23	13.56	14.62	23
64QAM	18.14	19.4	12.53	13.79	23
256QAM	15.94	16.35	10.33	10.74	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55290	CH 55990	CH 56690
			3555 MHz	3625 MHz	3695 MHz
QPSK	1	0	21.05	20.98	21.02
	1	24	21.03	20.82	21.02
	1	49	21.01	20.86	21.01
	25	0	20.13	20.06	20.15
	25	12	20.22	20.01	20.11
	25	25	20.02	19.97	20.12
	50	0	20.26	20.11	20.12
16QAM	1	0	20.05	20.01	20.08
	1	24	20.04	19.86	20.06
	1	49	20.01	19.83	20.04
	25	0	19.24	19.08	19.15
	25	12	19.07	19.13	19.11
	25	25	19.03	19.02	19.04
	50	0	19.1	19.03	19.17
64QAM	1	0	19.12	19.24	19.13
	1	24	19.08	19.05	19.11
	1	49	19.01	18.87	19.01
	25	0	18.16	18.17	18.31
	25	12	18.11	18.07	18.08
	25	25	18.08	17.9	18.03
	50	0	18.19	18.1	18.21
256QAM	1	0	16.14	15.98	16.14
	1	24	16.01	15.97	16.08
	1	49	16.01	15.85	16.02
	25	0	16.25	16.02	16.15
	25	12	16.08	16.08	16.11
	25	25	16.02	16.06	16.08
	50	0	16.04	16.03	16.11

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	19.97	21.05	14.36	15.44	23
16QAM	19.02	20.08	13.41	14.47	23
64QAM	17.9	19.24	12.29	13.63	23
256QAM	15.85	16.25	10.24	10.64	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 15 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55315	CH 55990	CH 56665
			3557.5 MHz	3625 MHz	3692.5 MHz
QPSK	1	0	21.01	21	21.06
	1	37	21.01	20.79	21.04
	1	74	21.01	20.9	21.02
	36	0	20.17	20.05	20.13
	36	19	20.09	20.02	20.11
	36	39	20.11	20.06	20.1
	75	0	20.19	20.06	20.09
16QAM	1	0	20.03	20	20.01
	1	37	20.02	19.96	20.01
	1	74	20.01	19.9	20.01
	36	0	19.26	19.03	19.03
	36	19	19.24	18.98	19.07
	36	39	19.18	18.86	19.08
	75	0	19.09	19.04	19.11
64QAM	1	0	19.12	19.2	19.12
	1	37	19.01	18.92	19.08
	1	74	19.01	18.9	19.06
	36	0	18.17	18.14	18.3
	36	19	18.16	18.11	18.03
	36	39	18.02	18	18.08
	75	0	18.24	18.13	18.17
256QAM	1	0	16.05	16.01	16.07
	1	37	16.04	16.01	16.05
	1	74	16.02	15.81	16.02
	36	0	16.25	16.03	16.2
	36	19	16.16	16.01	16.03
	36	39	16.14	16.03	16.01
	75	0	16.18	16.06	16.2

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	20.02	21.06	14.41	15.45	23
16QAM	18.86	20.03	13.25	14.42	23
64QAM	18	19.2	12.39	13.59	23
256QAM	15.81	16.25	10.2	10.64	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 20 MHz, Output Power: Full Power

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55340	CH 55990	CH 56640
			3560 MHz	3625 MHz	3690 MHz
QPSK	1	0	21.12	21.13	21.2
	1	50	21.08	21.04	21.11
	1	99	21.06	20.99	21.08
	50	0	20.35	20.29	20.3
	50	25	20.34	20.37	20.27
	50	50	20.24	20.26	20.23
	100	0	20.36	20.35	20.25
16QAM	1	0	20.17	20.1	20.25
	1	50	20.13	20.08	20.09
	1	99	20.07	20.07	20.06
	50	0	19.38	19.19	19.27
	50	25	19.2	19.14	19.25
	50	50	19.16	19.16	19.23
	100	0	19.29	19.29	19.34
64QAM	1	0	19.3	19.37	19.36
	1	50	19.2	19.21	19.11
	1	99	19.18	19.06	19.08
	50	0	18.41	18.33	18.45
	50	25	18.28	18.2	18.27
	50	50	18.21	18.13	18.26
	100	0	18.41	18.34	18.36
256QAM	1	0	16.3	16.19	16.31
	1	50	16.14	16.1	16.16
	1	99	16.11	15.87	16.01
	50	0	16.37	16.24	16.3
	50	25	16.2	16.19	16.21
	50	50	16.16	16.21	16.08
	100	0	16.28	16.3	16.32

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	20.23	21.2	14.62	15.59	23
16QAM	19.14	20.25	13.53	14.64	23
64QAM	18.13	19.37	12.52	13.76	23
256QAM	15.87	16.37	10.26	10.76	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 15 MHz, Output Power: dBm/10 MHz

Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55315	CH 55990	CH 56665
			3557.5 MHz	3625 MHz	3692.5 MHz
QPSK	1	0	20.94	20.93	20.98
	1	37	20.97	20.74	20.99
	1	74	20.92	20.82	20.95
	36	0	20.1	20.04	20.1
	36	19	20.05	19.95	20.06
	36	39	20.05	20.05	20.04
	75	0	18.76	18.6	18.63
16QAM	1	0	20	19.94	20
	1	37	19.92	19.92	19.94
	1	74	19.94	19.88	19.98
	36	0	19.23	19.02	18.96
	36	19	19.16	18.9	19.04
	36	39	19.13	18.78	19.07
	75	0	17.63	17.64	17.71
64QAM	1	0	19.1	19.16	19.02
	1	37	18.93	18.85	19.05
	1	74	18.95	18.87	18.97
	36	0	18.11	18.1	18.25
	36	19	18.06	18.03	18.02
	36	39	18.01	17.91	18.06
	75	0	16.76	16.65	16.74
256QAM	1	0	15.97	15.91	16
	1	37	16	15.92	16.03
	1	74	15.93	15.75	16.01
	36	0	16.21	15.99	16.12
	36	19	16.09	15.94	15.98
	36	39	16.05	15.93	15.95
	75	0	14.7	14.59	14.77

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	18.6	20.99	12.99	15.38	23
16QAM	17.63	20	12.02	14.39	23
64QAM	16.65	19.16	11.04	13.55	23
256QAM	14.59	16.21	8.98	10.6	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48 (3.55 GHz ~ 3.7 GHz), Channel Bandwidth: 20 MHz, Output Power: dBm/10 MHz


Modulation	RB Size	RB Offset	Measurement Conducted Power (dBm)		
			CH 55340	CH 55990	CH 56640
			3560 MHz	3625 MHz	3690 MHz
QPSK	1	0	21.09	21.11	21.2
	1	50	21	20.98	21.06
	1	99	21.01	20.98	21.07
	50	0	20.33	20.23	20.2
	50	25	20.27	20.27	20.19
	50	50	20.15	20.16	20.13
	100	0	17.95	17.88	17.79
16QAM	1	0	20.13	20.04	20.21
	1	50	20.03	20.01	20.04
	1	99	20.05	19.99	20
	50	0	19.34	19.15	19.26
	50	25	19.12	19.13	19.22
	50	50	19.13	19.13	19.21
	100	0	16.86	16.85	16.85
64QAM	1	0	19.25	19.34	19.33
	1	50	19.14	19.11	19.05
	1	99	19.1	19.05	18.99
	50	0	18.4	18.25	18.43
	50	25	18.18	18.1	18.24
	50	50	18.19	18.06	18.2
	100	0	16	15.86	15.87
256QAM	1	0	16.25	16.12	16.29
	1	50	16.05	16.08	16.12
	1	99	16.1	15.79	15.96
	50	0	16.27	16.14	16.24
	50	25	16.12	16.14	16.13
	50	50	16.15	16.18	16.07
	100	0	13.84	13.84	13.83

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	17.79	21.2	12.18	15.59	23
16QAM	16.85	20.21	11.24	14.6	23
64QAM	15.86	19.34	10.25	13.73	23
256QAM	13.83	16.29	8.22	10.68	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

Spectrum Plot of Worst Value



Note: For the channel bandwidth is less than or equal to 10 MHz, the full power test data please refer to the power per 10 MHz corresponding to the channel bandwidth.

7.1.2 LTE Band 48C (3.55 GHz ~ 3.7 GHz)

LTE Band 48C (3.55 GHz ~ 3.7 GHz), Output Power: Full Power

Configure	Combination	PCC							SCC							Measurement Power Tx Power with UL-CA Active (dBm) Total
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	
Intra Band Contiguous	48C	48	20	QPSK20M	100	0	55340	3560	48	20	QPSK20M	100	0	55538	3579.8	10.21
		48	20	QPSK20M	100	0	55891	3615.1	48	20	QPSK20M	100	0	56089	3634.9	10.38
		48	20	QPSK20M	100	0	56442	3670.2	48	20	QPSK20M	100	0	56640	3690	10.07
	48C	48	20	QPSK20M	100	0	55340	3560	48	15	QPSK15M	75	0	55511	3577.1	10.20
		48	20	QPSK20M	100	0	55916	3617.6	48	15	QPSK15M	75	0	56087	3634.7	10.27
		48	20	QPSK20M	100	0	56491	3675.1	48	15	QPSK15M	75	0	56662	3692.2	9.97
	48C	48	15	QPSK15M	75	0	55318	3557.8	48	20	QPSK20M	100	0	55489	3574.9	10.11
		48	15	QPSK15M	75	0	55893	3615.3	48	20	QPSK20M	100	0	56064	3632.4	10.34
		48	15	QPSK15M	75	0	56469	3672.9	48	20	QPSK20M	100	0	56640	3690	9.93
	48C	48	20	QPSK20M	100	0	55340	3560	48	10	QPSK10M	50	0	55484	3574.4	10.13
		48	20	QPSK20M	100	0	55941	3620.1	48	10	QPSK10M	50	0	56085	3634.5	10.24
		48	20	QPSK20M	100	0	56541	3680.1	48	10	QPSK10M	50	0	56685	3694.5	9.99
	48C	48	10	QPSK10M	50	0	55295	3555.5	48	20	QPSK20M	100	0	55439	3569.9	10.11
		48	10	QPSK10M	50	0	55896	3615.6	48	20	QPSK20M	100	0	56040	3630	10.28
		48	10	QPSK10M	50	0	56496	3675.6	48	20	QPSK20M	100	0	56640	3690	10.00
	48C	48	20	QPSK20M	100	0	55340	3560	48	5	QPSK5M	25	0	55457	3571.7	10.14
		48	20	QPSK20M	100	0	55965	3622.5	48	5	QPSK5M	25	0	56082	3634.2	10.34
		48	20	QPSK20M	100	0	56590	3685	48	5	QPSK5M	25	0	56707	3696.7	9.93
	48C	48	5	QPSK5M	25	0	55273	3553.3	48	20	QPSK20M	100	0	55390	3565	10.13
		48	5	QPSK5M	25	0	55898	3615.8	48	20	QPSK20M	100	0	56015	3627.5	10.32
		48	5	QPSK5M	25	0	56523	3678.3	48	20	QPSK20M	100	0	56640	3690	10.00
	48C	48	20	16QAM20M	100	0	55340	3560	48	20	16QAM20M	100	0	55538	3579.8	8.86
		48	20	16QAM20M	100	0	55891	3615.1	48	20	16QAM20M	100	0	56089	3634.9	9.05
		48	20	16QAM20M	100	0	56442	3670.2	48	20	16QAM20M	100	0	56640	3690	8.73
	48C	48	20	16QAM20M	100	0	55340	3560	48	15	16QAM15M	75	0	55511	3577.1	8.76
		48	20	16QAM20M	100	0	55916	3617.6	48	15	16QAM15M	75	0	56087	3634.7	8.99
		48	20	16QAM20M	100	0	56491	3675.1	48	15	16QAM15M	75	0	56662	3692.2	8.66
	48C	48	15	16QAM15M	75	0	55318	3557.8	48	20	16QAM20M	100	0	55489	3574.9	8.75
		48	15	16QAM15M	75	0	55893	3615.3	48	20	16QAM20M	100	0	56064	3632.4	8.95
		48	15	16QAM15M	75	0	56469	3672.9	48	20	16QAM20M	100	0	56640	3690	8.64
	48C	48	20	16QAM20M	100	0	55340	3560	48	10	16QAM10M	50	0	55484	3574.4	8.77
		48	20	16QAM20M	100	0	55941	3620.1	48	10	16QAM10M	50	0	56085	3634.5	8.98
		48	20	16QAM20M	100	0	56541	3680.1	48	10	16QAM10M	50	0	56685	3694.5	8.66
	48C	48	10	16QAM10M	50	0	55295	3555.5	48	20	16QAM20M	100	0	55439	3569.9	8.83
		48	10	16QAM10M	50	0	55896	3615.6	48	20	16QAM20M	100	0	56040	3630	8.97
		48	10	16QAM10M	50	0	56496	3675.6	48	20	16QAM20M	100	0	56640	3690	8.65
	48C	48	20	16QAM20M	100	0	55340	3560	48	5	16QAM5M	25	0	55457	3571.7	8.80
		48	20	16QAM20M	100	0	55965	3622.5	48	5	16QAM5M	25	0	56082	3634.2	8.97
		48	20	16QAM20M	100	0	56590	3685	48	5	16QAM5M	25	0	56707	3696.7	8.70
	48C	48	5	16QAM5M	25	0	55273	3553.3	48	20	16QAM20M	100	0	55390	3565	8.74
		48	5	16QAM5M	25	0	55898	3615.8	48	20	16QAM20M	100	0	56015	3627.5	9.03
		48	5	16QAM5M	25	0	56523	3678.3	48	20	16QAM20M	100	0	56640	3690	8.68

Configure	Combination	PCC							SCC							Measurement Power
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Tx Power with UL-CA Active (dBm)
		Total														
Intra Band Contiguous	48C	48	20	64QAM20M	100	0	55340	3560	48	20	64QAM20M	100	0	55538	3579.8	8.28
		48	20	64QAM20M	100	0	55891	3615.1	48	20	64QAM20M	100	0	56089	3634.9	8.50
		48	20	64QAM20M	100	0	56442	3670.2	48	20	64QAM20M	100	0	56640	3690	8.18
	48C	48	20	64QAM20M	100	0	55340	3560	48	15	64QAM15M	75	0	55511	3577.1	8.15
		48	20	64QAM20M	100	0	55916	3617.6	48	15	64QAM15M	75	0	56087	3634.7	8.40
		48	20	64QAM20M	100	0	56491	3675.1	48	15	64QAM15M	75	0	56662	3692.2	8.11
	48C	48	15	64QAM15M	75	0	55318	3557.8	48	20	64QAM20M	100	0	55489	3574.9	8.14
		48	15	64QAM15M	75	0	55893	3615.3	48	20	64QAM20M	100	0	56064	3632.4	8.44
		48	15	64QAM15M	75	0	56469	3672.9	48	20	64QAM20M	100	0	56640	3690	8.13
	48C	48	20	64QAM20M	100	0	55340	3560	48	10	64QAM10M	50	0	55484	3574.4	8.19
		48	20	64QAM20M	100	0	55941	3620.1	48	10	64QAM10M	50	0	56085	3634.5	8.39
		48	20	64QAM20M	100	0	56541	3680.1	48	10	64QAM10M	50	0	56685	3694.5	8.08
	48C	48	10	64QAM10M	50	0	55295	3555.5	48	20	64QAM20M	100	0	55439	3569.9	8.24
		48	10	64QAM10M	50	0	55896	3615.6	48	20	64QAM20M	100	0	56040	3630	8.42
		48	10	64QAM10M	50	0	56496	3675.6	48	20	64QAM20M	100	0	56640	3690	8.04
	48C	48	20	64QAM20M	100	0	55340	3560	48	5	64QAM5M	25	0	55457	3571.7	8.21
		48	20	64QAM20M	100	0	55965	3622.5	48	5	64QAM5M	25	0	56082	3634.2	8.48
		48	20	64QAM20M	100	0	56590	3685	48	5	64QAM5M	25	0	56707	3696.7	8.07
	48C	48	5	64QAM5M	25	0	55273	3553.3	48	20	64QAM20M	100	0	55390	3565	8.21
		48	5	64QAM5M	25	0	55898	3615.8	48	20	64QAM20M	100	0	56015	3627.5	8.40
		48	5	64QAM5M	25	0	56523	3678.3	48	20	64QAM20M	100	0	56640	3690	8.07
	48C	48	20	256QAM20M	100	0	55340	3560	48	20	256QAM20M	100	0	55538	3579.8	6.73
		48	20	256QAM20M	100	0	55891	3615.1	48	20	256QAM20M	100	0	56089	3634.9	6.92
		48	20	256QAM20M	100	0	56442	3670.2	48	20	256QAM20M	100	0	56640	3690	6.59
	48C	48	20	256QAM20M	100	0	55340	3560	48	15	256QAM15M	75	0	55511	3577.1	6.66
		48	20	256QAM20M	100	0	55916	3617.6	48	15	256QAM15M	75	0	56087	3634.7	6.84
		48	20	256QAM20M	100	0	56491	3675.1	48	15	256QAM15M	75	0	56662	3692.2	6.47
	48C	48	15	256QAM15M	75	0	55318	3557.8	48	20	256QAM20M	100	0	55489	3574.9	6.65
		48	15	256QAM15M	75	0	55893	3615.3	48	20	256QAM20M	100	0	56064	3632.4	6.81
		48	15	256QAM15M	75	0	56469	3672.9	48	20	256QAM20M	100	0	56640	3690	6.51
	48C	48	20	256QAM20M	100	0	55340	3560	48	10	256QAM10M	50	0	55484	3574.4	6.66
		48	20	256QAM20M	100	0	55941	3620.1	48	10	256QAM10M	50	0	56085	3634.5	6.85
		48	20	256QAM20M	100	0	56541	3680.1	48	10	256QAM10M	50	0	56685	3694.5	6.49
	48C	48	10	256QAM10M	50	0	55295	3555.5	48	20	256QAM20M	100	0	55439	3569.9	6.66
		48	10	256QAM10M	50	0	55896	3615.6	48	20	256QAM20M	100	0	56040	3630	6.87
		48	10	256QAM10M	50	0	56496	3675.6	48	20	256QAM20M	100	0	56640	3690	6.47
	48C	48	20	256QAM20M	100	0	55340	3560	48	5	256QAM5M	25	0	55457	3571.7	6.65
		48	20	256QAM20M	100	0	55965	3622.5	48	5	256QAM5M	25	0	56082	3634.2	6.86
		48	20	256QAM20M	100	0	56590	3685	48	5	256QAM5M	25	0	56707	3696.7	6.54
	48C	48	5	256QAM5M	25	0	55273	3553.3	48	20	256QAM20M	100	0	55390	3565	6.65
		48	5	256QAM5M	25	0	55898	3615.8	48	20	256QAM20M	100	0	56015	3627.5	6.80
		48	5	256QAM5M	25	0	56523	3678.3	48	20	256QAM20M	100	0	56640	3690	6.47

Output Power					
Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	9.93	10.38	4.32	4.77	23
16QAM	8.64	9.05	3.03	3.44	23
64QAM	8.04	8.50	2.43	2.89	23
256QAM	6.47	6.92	0.86	1.31	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

LTE Band 48C (3.55 GHz ~ 3.7 GHz), Output Power: dBm/10 MHz

Configure	Combination	PCC							SCC							Measurement Power
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Tx Power with UL-CA Active (dBm)
																Total
Intra Band Contiguous	48C	48	20	QPSK20M	100	0	55340	3560	48	20	QPSK20M	100	0	55538	3579.8	8.32
		48	20	QPSK20M	100	0	55891	3615.1	48	20	QPSK20M	100	0	56089	3634.9	8.51
		48	20	QPSK20M	100	0	56442	3670.2	48	20	QPSK20M	100	0	56640	3690	8.17
	48C	48	20	QPSK20M	100	0	55340	3560	48	15	QPSK15M	75	0	55511	3577.1	8.32
		48	20	QPSK20M	100	0	55916	3617.6	48	15	QPSK15M	75	0	56087	3634.7	8.38
		48	20	QPSK20M	100	0	56491	3675.1	48	15	QPSK15M	75	0	56662	3692.2	8.00
	48C	48	15	QPSK15M	75	0	55318	3557.8	48	20	QPSK20M	100	0	55489	3574.9	8.15
		48	15	QPSK15M	75	0	55893	3615.3	48	20	QPSK20M	100	0	56064	3632.4	8.39
		48	15	QPSK15M	75	0	56469	3672.9	48	20	QPSK20M	100	0	56640	3690	8.03
	48C	48	20	QPSK20M	100	0	55340	3560	48	10	QPSK10M	50	0	55484	3574.4	8.24
		48	20	QPSK20M	100	0	55941	3620.1	48	10	QPSK10M	50	0	56085	3634.5	8.32
		48	20	QPSK20M	100	0	56541	3680.1	48	10	QPSK10M	50	0	56685	3694.5	8.10
	48C	48	10	QPSK10M	50	0	55295	3555.5	48	20	QPSK20M	100	0	55439	3569.9	8.17
		48	10	QPSK10M	50	0	55896	3615.6	48	20	QPSK20M	100	0	56040	3630	8.31
		48	10	QPSK10M	50	0	56496	3675.6	48	20	QPSK20M	100	0	56640	3690	8.07
	48C	48	20	QPSK20M	100	0	55340	3560	48	5	QPSK5M	25	0	55457	3571.7	8.22
		48	20	QPSK20M	100	0	55965	3622.5	48	5	QPSK5M	25	0	56082	3634.2	8.36
		48	20	QPSK20M	100	0	56590	3685	48	5	QPSK5M	25	0	56707	3696.7	8.04
	48C	48	5	QPSK5M	25	0	55273	3553.3	48	20	QPSK20M	100	0	55390	3565	8.19
		48	5	QPSK5M	25	0	55898	3615.8	48	20	QPSK20M	100	0	56015	3627.5	8.37
		48	5	QPSK5M	25	0	56523	3678.3	48	20	QPSK20M	100	0	56640	3690	8.08
	48C	48	20	16QAM20M	100	0	55340	3560	48	20	16QAM20M	100	0	55538	3579.8	6.98
		48	20	16QAM20M	100	0	55891	3615.1	48	20	16QAM20M	100	0	56089	3634.9	7.11
		48	20	16QAM20M	100	0	56442	3670.2	48	20	16QAM20M	100	0	56640	3690	6.76
	48C	48	20	16QAM20M	100	0	55340	3560	48	15	16QAM15M	75	0	55511	3577.1	6.77
		48	20	16QAM20M	100	0	55916	3617.6	48	15	16QAM15M	75	0	56087	3634.7	7.04
		48	20	16QAM20M	100	0	56491	3675.1	48	15	16QAM15M	75	0	56662	3692.2	6.72
	48C	48	15	16QAM15M	75	0	55318	3557.8	48	20	16QAM20M	100	0	55489	3574.9	6.81
		48	15	16QAM15M	75	0	55893	3615.3	48	20	16QAM20M	100	0	56064	3632.4	6.97
		48	15	16QAM15M	75	0	56469	3672.9	48	20	16QAM20M	100	0	56640	3690	6.67
	48C	48	20	16QAM20M	100	0	55340	3560	48	10	16QAM10M	50	0	55484	3574.4	6.85
		48	20	16QAM20M	100	0	55941	3620.1	48	10	16QAM10M	50	0	56085	3634.5	7.08
		48	20	16QAM20M	100	0	56541	3680.1	48	10	16QAM10M	50	0	56685	3694.5	6.71
	48C	48	10	16QAM10M	50	0	55295	3555.5	48	20	16QAM20M	100	0	55439	3569.9	6.86
		48	10	16QAM10M	50	0	55896	3615.6	48	20	16QAM20M	100	0	56040	3630	7.07
		48	10	16QAM10M	50	0	56496	3675.6	48	20	16QAM20M	100	0	56640	3690	6.73
	48C	48	20	16QAM20M	100	0	55340	3560	48	5	16QAM5M	25	0	55457	3571.7	6.86
		48	20	16QAM20M	100	0	55965	3622.5	48	5	16QAM5M	25	0	56082	3634.2	7.03
		48	20	16QAM20M	100	0	56590	3685	48	5	16QAM5M	25	0	56707	3696.7	6.74
	48C	48	5	16QAM5M	25	0	55273	3553.3	48	20	16QAM20M	100	0	55390	3565	6.87
		48	5	16QAM5M	25	0	55898	3615.8	48	20	16QAM20M	100	0	56015	3627.5	7.07
		48	5	16QAM5M	25	0	56523	3678.3	48	20	16QAM20M	100	0	56640	3690	6.72

Configure	Combination	PCC							SCC							Measurement Power
		Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Band	BW (MHz)	Modulation	RB Size	RB Offset	UL Channel	UL Frequency (MHz)	Tx Power with UL-CA Active (dBm)
		Total														
Intra Band Contiguous	48C	48	20	64QAM20M	100	0	55340	3560	48	20	64QAM20M	100	0	55538	3579.8	6.36
		48	20	64QAM20M	100	0	55891	3615.1	48	20	64QAM20M	100	0	56089	3634.9	6.57
		48	20	64QAM20M	100	0	56442	3670.2	48	20	64QAM20M	100	0	56640	3690	6.27
	48C	48	20	64QAM20M	100	0	55340	3560	48	15	64QAM15M	75	0	55511	3577.1	6.18
		48	20	64QAM20M	100	0	55916	3617.6	48	15	64QAM15M	75	0	56087	3634.7	6.46
		48	20	64QAM20M	100	0	56491	3675.1	48	15	64QAM15M	75	0	56662	3692.2	6.19
	48C	48	15	64QAM15M	75	0	55318	3557.8	48	20	64QAM20M	100	0	55489	3574.9	6.20
		48	15	64QAM15M	75	0	55893	3615.3	48	20	64QAM20M	100	0	56064	3632.4	6.56
		48	15	64QAM15M	75	0	56469	3672.9	48	20	64QAM20M	100	0	56640	3690	6.24
	48C	48	20	64QAM20M	100	0	55340	3560	48	10	64QAM10M	50	0	55484	3574.4	6.28
		48	20	64QAM20M	100	0	55941	3620.1	48	10	64QAM10M	50	0	56085	3634.5	6.49
		48	20	64QAM20M	100	0	56541	3680.1	48	10	64QAM10M	50	0	56685	3694.5	6.14
	48C	48	10	64QAM10M	50	0	55295	3555.5	48	20	64QAM20M	100	0	55439	3569.9	6.32
		48	10	64QAM10M	50	0	55896	3615.6	48	20	64QAM20M	100	0	56040	3630	6.53
		48	10	64QAM10M	50	0	56496	3675.6	48	20	64QAM20M	100	0	56640	3690	6.09
	48C	48	20	64QAM20M	100	0	55340	3560	48	5	64QAM5M	25	0	55457	3571.7	6.26
		48	20	64QAM20M	100	0	55965	3622.5	48	5	64QAM5M	25	0	56082	3634.2	6.59
		48	20	64QAM20M	100	0	56590	3685	48	5	64QAM5M	25	0	56707	3696.7	6.14
	48C	48	5	64QAM5M	25	0	55273	3553.3	48	20	64QAM20M	100	0	55390	3565	6.30
		48	5	64QAM5M	25	0	55898	3615.8	48	20	64QAM20M	100	0	56015	3627.5	6.48
		48	5	64QAM5M	25	0	56523	3678.3	48	20	64QAM20M	100	0	56640	3690	6.15
	48C	48	20	256QAM20M	100	0	55340	3560	48	20	256QAM20M	100	0	55538	3579.8	5.30
		48	20	256QAM20M	100	0	55891	3615.1	48	20	256QAM20M	100	0	56089	3634.9	5.68
		48	20	256QAM20M	100	0	56442	3670.2	48	20	256QAM20M	100	0	56640	3690	5.24
	48C	48	20	256QAM20M	100	0	55340	3560	48	15	256QAM15M	75	0	55511	3577.1	5.25
		48	20	256QAM20M	100	0	55916	3617.6	48	15	256QAM15M	75	0	56087	3634.7	5.39
		48	20	256QAM20M	100	0	56491	3675.1	48	15	256QAM15M	75	0	56662	3692.2	5.05
	48C	48	15	256QAM15M	75	0	55318	3557.8	48	20	256QAM20M	100	0	55489	3574.9	5.27
		48	15	256QAM15M	75	0	55893	3615.3	48	20	256QAM20M	100	0	56064	3632.4	5.46
		48	15	256QAM15M	75	0	56469	3672.9	48	20	256QAM20M	100	0	56640	3690	5.08
	48C	48	20	256QAM20M	100	0	55340	3560	48	10	256QAM10M	50	0	55484	3574.4	5.23
		48	20	256QAM20M	100	0	55941	3620.1	48	10	256QAM10M	50	0	56085	3634.5	5.38
		48	20	256QAM20M	100	0	56541	3680.1	48	10	256QAM10M	50	0	56685	3694.5	5.07
	48C	48	10	256QAM10M	50	0	55295	3555.5	48	20	256QAM20M	100	0	55439	3569.9	5.17
		48	10	256QAM10M	50	0	55896	3615.6	48	20	256QAM20M	100	0	56040	3630	5.39
		48	10	256QAM10M	50	0	56496	3675.6	48	20	256QAM20M	100	0	56640	3690	5.09
	48C	48	20	256QAM20M	100	0	55340	3560	48	5	256QAM5M	25	0	55457	3571.7	5.25
		48	20	256QAM20M	100	0	55965	3622.5	48	5	256QAM5M	25	0	56082	3634.2	5.45
		48	20	256QAM20M	100	0	56590	3685	48	5	256QAM5M	25	0	56707	3696.7	5.15
	48C	48	5	256QAM5M	25	0	55273	3553.3	48	20	256QAM20M	100	0	55390	3565	5.22
		48	5	256QAM5M	25	0	55898	3615.8	48	20	256QAM20M	100	0	56015	3627.5	5.33
		48	5	256QAM5M	25	0	56523	3678.3	48	20	256QAM20M	100	0	56640	3690	5.11

Output Power

Modulation	Minimum Cond. Power (dBm)	Maximum Cond. Power (dBm)	Minimum EIRP (dBm)	Maximum EIRP (dBm)	EIRP Limit (dBm)
QPSK	8.00	8.51	2.39	2.90	23
16QAM	6.67	7.11	1.06	1.50	23
64QAM	6.09	6.59	0.48	0.98	23
256QAM	5.05	5.68	-0.56	0.07	23

Note: EIRP (dBm) = Cond. Power (dBm) + Antenna Gain (dBi) + Array Gain (if applicable)

Spectrum Plot of Worst Value



QPSK CH 55891 (3615.1 MHz) + CH 56089 (3634.9 MHz)

Note: For the channel bandwidth is less than or equal to 10 MHz, the full power test data please refer to the power per 10 MHz corresponding to the channel bandwidth.

7.2 Radiated Spurious Emissions below 1GHz

7.2.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)


Mode A

RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 56640 : 3690 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	30.00	-49.99	-40.00	-9.99	1.50 H	73	55.55	-105.54
2	71.71	-55.12	-40.00	-15.12	1.00 H	244	51.21	-106.33
3	144.46	-51.98	-40.00	-11.98	1.00 H	281	51.78	-103.76
4	211.39	-46.19	-40.00	-6.19	1.00 H	158	59.81	-106.00
5	318.09	-48.77	-40.00	-8.77	1.00 H	212	52.34	-101.11
6	347.19	-50.21	-40.00	-10.21	1.50 H	215	50.60	-100.81

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 56640 : 3690 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	49.40	-47.24	-40.00	-7.24	1.50 V	343	56.88	-104.12
2	88.20	-45.08	-40.00	-5.08	1.00 V	182	64.46	-109.54
3	128.94	-46.29	-40.00	-6.29	1.50 V	43	58.81	-105.10
4	213.33	-48.89	-40.00	-8.89	1.00 V	13	57.04	-105.93
5	288.99	-45.78	-40.00	-5.78	1.00 V	118	56.25	-102.03
6	322.94	-47.64	-40.00	-7.64	1.00 V	105	53.34	-100.98

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




Mode B

RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 56640 : 3690 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	34.85	-48.89	-40.00	-8.89	1.00 H	120	56.41	-105.30
2	159.98	-48.47	-40.00	-8.47	2.00 H	299	54.82	-103.29
3	206.54	-46.09	-40.00	-6.09	1.00 H	180	60.07	-106.16
4	339.43	-46.14	-40.00	-6.14	1.50 H	9	54.70	-100.84
5	521.79	-58.34	-40.00	-18.34	1.50 H	257	39.18	-97.52
6	712.88	-55.29	-40.00	-15.29	1.00 H	222	38.67	-93.96

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 56640 : 3690 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Rex Wang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	32.91	-47.25	-40.00	-7.25	1.50 V	268	58.31	-105.56
2	113.42	-49.79	-40.00	-9.79	1.50 V	210	56.75	-106.54
3	206.54	-46.73	-40.00	-6.73	1.00 V	144	59.43	-106.16
4	339.43	-50.57	-40.00	-10.57	1.50 V	287	50.27	-100.84
5	530.52	-58.05	-40.00	-18.05	1.00 V	165	39.32	-97.37
6	696.39	-56.01	-40.00	-16.01	1.00 V	250	38.23	-94.24

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.3 Radiated Spurious Emissions above 1GHz

7.3.1 LTE Band 48 (3.55 GHz ~ 3.7 GHz)

RF Mode	LTE Band 48 Channel Bandwidth: 5MHz	Channel	CH 55265 : 3552.5 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7105.00	-42.01	-40.00	-2.01	2.05 H	23	43.58	-85.59
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7105.00	-40.77	-40.00	-0.77	1.83 V	237	44.82	-85.59

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. $Margin\ value = EIRP - Limit\ value$
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48 Channel Bandwidth: 5MHz	Channel	CH 55990 : 3625 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7250.00	-42.14	-40.00	-2.14	2.10 H	19	43.24	-85.38
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7250.00	-41.61	-40.00	-1.61	1.78 V	240	43.77	-85.38

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48 Channel Bandwidth: 5MHz	Channel	CH 56715 : 3697.5 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7395.00	-41.21	-40.00	-1.21	2.06 H	25	43.54	-84.75
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7395.00	-40.79	-40.00	-0.79	1.82 V	238	43.96	-84.75

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 55340 : 3560 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7120.00	-41.64	-40.00	-1.64	2.12 H	23	43.94	-85.58
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7120.00	-41.39	-40.00	-1.39	1.84 V	242	44.19	-85.58

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 55990 : 3625 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7250.00	-41.72	-40.00	-1.72	2.10 H	25	43.66	-85.38
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7250.00	-41.50	-40.00	-1.50	1.78 V	240	43.88	-85.38

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48 Channel Bandwidth: 20MHz	Channel	CH 56640 : 3690 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7380.00	-40.57	-40.00	-0.57	2.06 H	23	44.23	-84.80
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7380.00	-40.28	-40.00	-0.28	1.86 V	245	44.52	-84.80

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

7.3.2 LTE Band 48C (3.55 GHz ~ 3.7 GHz)

RF Mode	LTE Band 48C Channel Bandwidth: 20MHz+ 20MHz	Channel	CH 55340 : 3560 MHz + CH 55538 : 3579.8 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7120.00	-42.25	-40.00	-2.25	2.54 H	55	43.33	-85.58
2	7159.60	-42.29	-40.00	-2.29	2.58 H	61	43.22	-85.51
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7120.00	-41.91	-40.00	-1.91	2.04 V	266	43.67	-85.58
2	7159.60	-41.90	-40.00	-1.90	2.10 V	271	43.61	-85.51

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48C Channel Bandwidth: 20MHz+ 20MHz	Channel	CH 55891 : 3615.1 MHz + CH 56089 : 3634.9 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7230.20	-42.10	-40.00	-2.10	2.34 H	49	43.22	-85.32
2	7269.80	-42.19	-40.00	-2.19	2.33 H	57	43.16	-85.35
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7230.20	-41.77	-40.00	-1.77	2.02 V	269	43.55	-85.32
2	7269.80	-41.82	-40.00	-1.82	1.98 V	264	43.53	-85.35

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

RF Mode	LTE Band 48C Channel Bandwidth: 20MHz+ 20MHz	Channel	CH 56442 : 3670.2MHz + CH 56640 : 3690 MHz
Frequency Range	1 GHz ~ 40 GHz	Detector Function & Bandwidth	1 MHz/3 MHz (RMS)
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Adair Peng		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7340.40	-41.76	-40.00	-1.76	2.38 H	46	43.23	-84.99
2	7380.00	-41.61	-40.00	-1.61	2.42 H	55	43.19	-84.80
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	7340.40	-41.41	-40.00	-1.41	2.13 V	272	43.58	-84.99
2	7380.00	-41.28	-40.00	-1.28	2.10 V	275	43.52	-84.80

Remarks:

1. $EIRP(dBm) = Raw\ Value(dBuV) + Correction\ Factor(dB/m)$
2. $Correction\ Factor(dB/m) = Antenna\ Factor(dB/m) + Cable\ Factor(dB) - Pre-Amplifier\ Factor(dB) + 20\log(D) - 104.8$
3. Margin value = EIRP – Limit value
4. The other EIRP levels were very low against the limit.

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---