7. Measurement Data (continued)

7.12. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN, ISSUE 4 5.5, RSS 102)

7.12.1. 15.247(i) (1.1307 (b)(1) Requirements

Requirement: Portable devices are subject to radio frequency radiation exposure requirements.

For a 1-g head or body SAR, the test exclusion result must be ≤ 3.0.
For a 10-g extremity SAR, the test exclusion result must be ≤ 7.5.

Test Notes: The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by the following formula:

$$\text{SAR Test Exclusion} = \frac{P_{MAX}}{d_{MIN}} \times \sqrt{f_{(GHz)}} \quad (1)$$

P_{MAX}	mW	Maximum power of channel, including tune-up tolerance
d_{MIN}	mm	Minimum test separation distance, mm (≤ 50 mm)
$f_{(GHz)}$	GHz	$f_{(GHz)}$ is the RF channel transmit frequency in GHz (>100 MHz and <6 GHz)

(1) FCC OET 447498 - Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies.

Results: Compliant - The device under test meets the exclusion requirement detailed in FCC OET 447498.

Channel:		**37**	**38**	**39**	
Input[1]:	P_{MAX}	0.064	0.074	0.062	**mW**
	d_{MIN}[2]	5.00	5.00	5.00	**mm**
	$f_{(GHz)}$	2.402	2.426	2.480	**GHz**
Test Exclusion:		**0.02**	**0.02**	**0.02**	
Limit Exemption:		**3.0**	**3.0**	**3.0**	
Measurement Result:		**Compliant**	**Compliant**	**Compliant**	

[1] Taken from column 3 of the table in Section 7.3 of this test report.

[2] When the minimum test separation distance is < 5 mm, a distance of 5 mm according to KDB 447498, 4.1 f) is applied to determine SAR test exclusion.

Compliance Worldwide, Inc. - 357 Main Street - Sandown, NH 03873
(603) 887 3903 Fax (603) 887 6445
www.complainceworldwide.com

7. Measurement Data (continued)

7.12. Public Exposure to Radio Frequency Energy Levels (15.247(i) (1.1307 (b)(1)) RSS-GEN, ISSUE 4 5.5, RSS 102) (continued)

7.12.2. RSS-102 Issue 5 Requirements

Requirement: SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. Portable devices are subject to radio frequency radiation exposure requirements.

Test Notes: The limit was taken from Table 1 of RSS-102 Issue 5. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation in Table 1 are multiplied by a factor of 2.5.

Results: Compliant

Bluetooth Radio

Frequency	Separation Distance	Maximum Power	RSS-102 Limit	Result
MHz	mm	mW	mW	
2402	≤5	0.06	10.65	Compliant
2426	≤5	0.07	10.33	Compliant
2480	≤5	0.06	9.86	Compliant

Compliance Worldwide, Inc. - 357 Main Street - Sandown, NH 03873
(603) 887 3903 Fax (603) 887 6445
www.complainceworldwide.com