

TEST REPORT

Test Report No.: 1-1845/21-01-11

BNNetzA-CAB-02/21-102

Testing Laboratory

CTC advanced GmbH

Untertürkheimer Straße 6 – 10
66117 Saarbrücken/GERMANY
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: <https://ctcadvanced.com/>
e-mail: mail@ctcadvanced.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2018-03) by the Deutsche Akkreditierungsstelle GmbH (DAkkS). The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate starting with the registration number: D-PL-12076-01.

Applicant

BURY SP. z o.o.
Wojska Polskiego 4
39-300 Mielec, Poland

Manufacturer

Same as Applicant

Test Standard/s

FCC - Title 47 CFR
Part 18: 2017-01


FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 18 - Industrial, scientific and medical equipment

MP-5: 1986

FCC Methods of measurements of radio noise emissions from industrial, scientific and medical equipment


Test Item

Kind of test item: Wireless charger with NFC
Model name: WCA CS NFC LCI
FCC-ID: QZ9 - WCACS
IC: 5927A - WCACS
detailed information see chapter 6.1 and 6.2 of this test report



This test report is electronically signed and valid without handwritten signature. The public keys can be requested at the test laboratory to verify the electronic signatures.

Test report authorised:



cn=Uli Kraus, o=CTC advanced GmbH,
ou=KRA-211122,
email=uli.kraus@ctcadvanced.com, c=DE
2022.01.13 08:21:47 +01'00'

Uli Kraus
Head of Department
Electromagnetic Compatibility & Acoustics

Test performed:

p.o. 

cn=Jens Hennemann, o=CTC
advanced GmbH, ou=HMN_211123,
email=jens.hennemann@ctcadvanced.com, c=DE
2022.01.13 08:17:56 +01'00'

Holger Medrow
Testing Manager
Electromagnetic Compatibility & Acoustics

1 Table of contents

1	Table of contents	2
2	General information	3
2.1	Notes and disclaimer	3
2.2	Application details	4
3	Test standard/s:	4
4	Test Environment	4
5	Test Laboratories sub-contracted	4
6	Information about Test Conditions	5
6.1	Test Item	5
6.2	Additional information	5
6.3	EUT: Type, S/N etc. and Short Descriptions Used in this Test Report	5
6.4	Auxiliary Equipment (AE): Type, S/N etc. and Short Descriptions	6
6.5	EUT Set-up(s)	6
6.6	EUT Operating Modes	6
7	Summary of Test Results	7
7.1	Emission	7
7.2	Measurement and Test Set-up	8
7.3	Measurement uncertainty	8
7.4	Limits	8
8	Detailed test results - Emission	9
8.1	Electromagnetic Radiated Emissions (Distance 3 m)	9
8.2	Electromagnetic Radiated Emissions (Distance 10 m)	16
9	Test equipment and ancillaries used for tests	22
10	Observations	23
Annex A	Document history	24
Annex B	Further information	24

2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CTC advanced GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CTC advanced GmbH.

The testing service provided by CTC advanced GmbH has been rendered under the current "General Terms and Conditions for CTC advanced GmbH".

CTC advanced GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CTC advanced GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CTC advanced GmbH test report include or imply any product or service warranties from CTC advanced GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CTC advanced GmbH.

All rights and remedies regarding vendor's products and services for which CTC advanced GmbH has prepared this test report shall be provided by the party offering such products or services and not by CTC advanced GmbH. In no case this test report can be considered as a Letter of Approval.

The present test report can only be used for the sDOC procedure in the USA if the „Responsible Party“ (located in USA) or an official of the responsible party confirms the report in writing, as designated in FCC§2.938.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order: 2021-03-05
Date of receipt of test item: 2021-03-08
Start of test¹⁾: 2021-04-20
End of test¹⁾: 2021-04-20
Person(s) present during the test: - / -

¹⁾ Date of each measurement, if not shown in the plot, can be requested. Dates are stored in the measurement software.

3 Test standard/s:

Test Standard	Test Standard Description
FCC - Title 47 CFR Part 18	FCC - Title 47 of the Code of Federal Regulations; Chapter I; Part 18 - Industrial, scientific and medical equipment
MP-5	FCC Methods of measurements of radio noise emissions from industrial, scientific and medical equipment

4 Test Environment

Temperature: 20°C – 25°C
Relative humidity content: 30 % - 50 %
Air pressure: 1020 hPa
Power supply of measurement equipment: 230 V / 50 Hz

5 Test Laboratories sub-contracted

6 Information about Test Conditions

6.1 Test Item

Kind of test item :	Wireless charger with NFC		
Type identification :	WCA CS NFC LCI		
Equipment classification:	Equipment for vehicular use		
Environment classification:	Residential, commercial and light industry		
Supply voltage :	12V DC		
Ports : (maximum cable lengths declared by manufacturer)	Description	Direction	Length
	CAN/DC power port	Input/Output	< 3m
Is mounting position / usual operating position defined?			No
Additional information:			
- / -			

6.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup and EUT photos are included in test report: 1-1845/21-01-01_AnnexA
 1-1845/21-01-01_AnnexB
 1-1845/21-01-01_AnnexE

6.3 EUT: Type, S/N etc. and Short Descriptions Used in this Test Report

short description*)	EUT	Type	S/N serial number	HW hardware status	SW software status
EUT A	Wireless charger with NFC	BMW 5 A14 5E3	012100560008 6419163010	070	0061

*) EUT short description is used to simplify the identification of the EUT in this test report.

6.4 Auxiliary Equipment (AE): Type, S/N etc. and Short Descriptions

AE description*)	Auxiliary equipment	Type	S/N serial number	HW hardware status	SW software status
AE A	load	- / -	- / -	- / -	- / -

*) AE short description is used to simplify the identification of the auxiliary equipment in this test report.

6.5 EUT Set-up(s)

EUT set-up no.*)	Combination of EUT and AE	Remarks
set. 1	EUT A + AE A	- / -

*) EUT set-up no. is used to simplify the identification of the EUT set-up in this test report.

6.6 EUT Operating Modes

EUT operating mode no.*)	Description of operating modes	Additional information
op. 1	wireless charging	- / -

*) EUT operating mode no. is used to simplify the test report.

7 Summary of Test Results

- ☒ No deviations from the technical specifications were ascertained
☐ There were deviations from the technical specifications ascertained

7.1 Emission

7.1.1 Enclosure

EMI Phenomenon	Frequency range	Basic standard	Result
Radiated Interference Field Strength	9KHz - 30MHz	FCC Part 18	passed
Radiated Interference Field Strength	30MHz - 1GHz	FCC Part 18	passed

7.1.2 DC Mains Power Input/Output Ports

EMI Phenomenon	Frequency range	Basic standard	Result
Conducted interference voltage	0,15– 30 MHz	FCC Part 18	NA7

Remarks:

NA1	Not tested because not required by used standard
NA2	Test not applicable because port does not exists
NA3	Test not applicable because port only for services
NA4	Test not applicable because port lengths not longer than 3m
NA5	Not tested because not required by customer
NA6	Not tested because used frequency < 108 MHz
NA7	Not tested because the device is for vehicular use

7.2 Measurement and Test Set-up

Note: The test configuration is in accordance with the requirements given in the standards in point 3

7.3 Measurement uncertainty

The uncertainty of the measurement equipment fulfils CISPR 16 and the related European and national standards.

The semi anechoic chamber fulfils the requirements of CISPR 16-1 (ANSI C63.4) for a test volume of 4m Ø.

The table below shows the measurement uncertainties for each measurement method. The expended uncertainty (k=2 or 95%) was calculated with worst case values.

Measurement Method	Frequency area Impulse duration time	Description	Expanded uncertainty (k=2 or 95%)
Radiated Emission MP 5	9kHz – 18 GHz	- / -	± 4.28 dB
Conducted Emission ANSI C63.4	9 kHz – 30 MHz	- / -	± 3.49 dB

7.4 Limits

Equipment	operating frequency	RF power generated by equipment (watts)	field strength limit (µV/m)	distance (meters)
any type unless otherwise specified	any ISM frequency	below 500 500 or more	25 25xSQRT(power/500)	300 ¹ 300
	any non ISM frequency	below 500 500 or more	15 15xSQRT(power/500)	300 ¹ 300
industrial heaters and RF stabilized arc welders	on or below 5,725MHz above 5,725MHz	any any	10 (²)	1600 (²)
medical diathermy	any ISM frequency any non ISM frequency	any any	25 15	300 300
ultrasonic	below 490kHz	below 500 500 and more	2,400/F(kHz) 2,400/F(kHz)x SQRT(power/500)	300 ³ 300
	490 to 1,600kHz above 1,600kHz	any any	24,000/F(kHz) 15	30 30
induction cooking ranges	below 90kHz on or above 90kHz	any any	1,500 300	⁴ 30 ⁴ 30

1 Field strength may not exceed 10 µV/m at 1600 meters. Consumer equipment operating below 1000 MHz is not permitted the increase in field strength otherwise permitted here for power over 500 watts.

2 Reduced to the greatest extent possible.

3 Field strength may not exceed 10 µV/m at 1600 meters. Consumer equipment is not permitted the increase in field strength otherwise permitted here for over 500 watts.

4 Induction cooking ranges manufactured prior to February 1, 1980, shall be subject to the field strength limits for miscellaneous ISM equipment.

8 Detailed test results - Emission

8.1 Electromagnetic Radiated Emissions (Distance 3 m)

8.1.1 Instrumentation for Test (see equipment list)

F 1	F 5	F 6	F 7	F 8	F 28	F 34					
-----	-----	-----	-----	-----	------	------	--	--	--	--	--

8.1.2 Test Plan

EUT set-up	set 1		
Operating mode	Application	Limit	Result
op 1	Enclosure	FCC part 18	passed

Remarks: Powered by external power supply (12V DC)

8.1.3 Radiated Limits


	FCC part 18
9KHz - 30 MHz	23,52dBµV/m@300m or 103,52dBµV/m@3m

Remarks: - the measurements have been performed @3m distance, therefore the limit line was recalculated accordingly (distance correction for 300m: $40\log(300/3)=80\text{dB}$)

8.1.4 Test Results

Common Information

EUT: Wireless Charger with NFC
 Serial number: 0121005600086419163010
 Test description: FCC part 18@3m - x-axis
 Operating condition: wireless charging
 Operator name: FSD
 Comment: DC 12V




Final Result

Frequency (MHz)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)
0.011	52.11	103.5	51.4	1000	0.2	V	355
0.051	39.63	103.5	63.9	1000	0.2	V	189
0.111	80.05	103.5	23.5	1000	0.2	V	150
0.130	65.16	103.5	38.4	1000	0.2	V	0
0.373	41.79	103.5	61.7	1000	9.0	V	19
5.726	22.52	103.5	81.0	1000	9.0	V	84

Common Information

EUT: Wireless Charger with NFC
 Serial number: 0121005600086419163010
 Test description: FCC part 18@3m - y axis
 Operating condition: wireless charging
 Operator name: FSD
 Comment: DC 12V




Final Result

Frequency (MHz)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)
0.011	51.36	103.5	52.2	1000	0.2	V	90
0.035	58.34	103.5	45.2	1000	0.2	V	343
0.111	78.08	103.5	25.4	1000	0.2	V	163
0.130	79.65	103.5	23.9	1000	0.2	V	355
0.259	60.63	103.5	42.9	1000	9.0	V	325
5.781	28.68	103.5	74.8	1000	9.0	V	163

Common Information

EUT: Wireless Charger with NFC
 Serial number: 0121005600086419163010
 Test description: FCC part 18@3m - z axis
 Operating condition: wireless charging
 Operator name: FSD
 Comment: DC 12V




Final Result

Frequency (MHz)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Pol	Azimuth (deg)
0.010	51.95	103.5	51.6	1000	0.2	V	63
0.020	47.02	103.5	56.5	1000	0.2	V	55
0.111	79.53	103.5	24.0	1000	0.2	V	78
0.130	75.71	103.5	27.8	1000	0.2	V	355
0.260	55.81	103.5	47.7	1000	9.0	V	139
5.731	24.20	103.5	79.3	1000	9.0	V	201

8.1.5 Hardware Set-up

Frequency Range:	9 kHz - 30 MHz
Receiver:	ESR 3 [ESR 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.42
Signal Path:	LOOP-Ant FW 1.0
Antenna:	EMCO6502
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12
Software version:	V10.59.0

8.1.6 Test set-up



8.1.7 Sequence of testing

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a nonconducting table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC or DC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized successively in x, y and z axis
- The antenna height is 2 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$
- The final measurement is done with average detector (as described in FCC/OET MP-5).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna position, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.1.8 Signal strength calculation

Calculation formula:

$$SS = U_R + CL + AF$$

List of abbreviations:

SS	▶	signal strength
U_R	▶	voltage at the receiver
CL	▶	loss of the cable
AF	▶	antenna factor

List with correction factors:

Frequency [MHz]	CL [dB]	AF [1/m]
0,009	0,20	17,60
0,015	0,20	11,17
1,000	0,30	10,96
10,000	0,40	9,90
22,000	0,40	6,56
30,000	0,40	3,40

Example calculation:

For example at 1,000 MHz the measured Voltage (U_R) is 12,35 dB μ V, the loss of the cable (CL) is 0,30 dB and the antenna factor (AF) is 10,96 dB (m^{-1}) the final result will be calculated:

$$SS [dB\mu V/m] = 12,35 [dB\mu V] + 0,30 [dB] + 10,96 [dB (m^{-1})] = \underline{23,61 [dB\mu V/m]} \quad (15,1 \mu V/m)$$

8.2 Electromagnetic Radiated Emissions (Distance 10 m)

8.2.1 Instrumentation for Test (see equipment list)

F 1	F 2	F 4b	F 5	F 6	F 7	F 8	F 28				
-----	-----	------	-----	-----	-----	-----	------	--	--	--	--

8.2.2 Test Plan

EUT set-up	set 1		
Operating mode	Application	Limit	Result
op 1	Enclosure	FCC part 18 Class B	passed

Remarks: Powered by external power supply (12V DC)

8.2.3 Radiated Limits

Frequency- range	FCC part 18
30 MHz – 1000 MHz	23,52dBµV/m@300m or 53 dBµV/m@10m
	* This values are recalculated from the limits at 300m antenna distance in §18.305 of the FCC rules


8.2.4 Calibration Information

Device	Serial number	Internal Number	Calibration valid until	Calibration interval
ESR 3	1316.3003K03-102587-ct	300005771	12 / 2021	12 month
Trilog Antenna	9163-295	300003696	09 / 2021	24 month

Remarks:
System check of all relevant devices and the chamber (weekly)

8.2.5 Test Results

EUT: Wireless Charger with NFC
 Serial number: 0121005600086419163010
 Test description: FCC part 18 class B @ 10 m
 Operating condition: wireless charging
 Operator name: FSD
 Comment: DC 12V



Final Result

Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
55.719	9.62	82.6	73.0	1000	120.0	249.0	H	256	15
99.548	10.68	82.6	71.9	1000	120.0	200.0	V	255	12
242.200	8.47	82.6	74.1	1000	120.0	281.0	H	90	13
509.939	14.29	82.6	68.3	1000	120.0	150.0	V	225	18
687.088	17.01	82.6	65.6	1000	120.0	200.0	V	217	21
943.733	20.30	82.6	62.3	1000	120.0	191.0	H	196	24

8.2.6 Hardware Set-up

Subrange 1	
Frequency Range:	30 MHz - 2 GHz
Receiver:	ESR 3 [ESR 3] @ GPIB0 (ADR 20), SN 1316.3003K03/102587, FW 3.46 SP1
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12
Software version:	EMC32 V10.59.0

8.2.7 Sequence of testing

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a nonconducting table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) – see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

Final measurement

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position $\pm 45^\circ$ and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.

8.2.8 Signal strength calculation

Calculation formula:

$$SS = U_R + CL + AF$$

List of abbreviations:

SS	▶	signal strength
U_R	▶	voltage at the receiver
CL	▶	loss of the cable
AF	▶	antenna factor

List with correction factors:


Frequency [MHz]	CL [dB]	AF [1/m]
30,000	0,20	12,30
100,000	0,60	11,30
200,000	1,10	10,60
300,000	1,30	13,20
400,000	1,60	15,30
500,000	1,90	16,80
600,000	2,00	18,80
700,000	2,20	20,30
800,000	2,30	21,50
900,000	2,40	22,80
1000,000	2,50	23,30

Example calculation:

For example at 500,000 000 MHz the measured Voltage (U_R) is 12,35 dB μ V, the loss of the cable (CL) is 1,90 dB and the antenna factor (AF) is 16,80 dB (m^{-1}) the final result will be calculated:

$$SS [dB\mu V/m] = 12,35 [dB\mu V] + 1,90 [dB] + 16,80 [dB (m^{-1})] = \underline{31,05 [dB\mu V/m]} \quad (35,69 \mu V/m)$$

8.2.9 Test Set-up



9 Test equipment and ancillaries used for tests

To simplify the identification of the test equipment and/or ancillaries which were used, the reporting of the relevant test cases only refer to the test item number as specified in the table below.

No.	Instrument/Ancillary	Manufacturer	Type	Serial-No.	Internal identification
Radiated emission in chamber F					
F-1	Control Computer	F+W		2934939v001	300005258
F-2	Trilog-Antenna	Schwarzbeck	VULB 9163	9163-295	300003787
F-3a	Amplifier	Veritech Microwave Inc.	0518C-138	- / -	- / -
F-4b	Switch	Netgear	GS108P	26V12A3H50336	300000368
F-5	EMI Test receiver	R&S	ESR	1316.3003K03-102587-ct	300005771
F-6	Turntable Interface-Box	EMCO / ETS-LINDGREN	Model 105637	44583	300003747
F-7	Tower/Turntable Controller	EMCO / ETS-LINDGREN	Model 2090	64672	300003746
F-8	Tower	EMCO / ETS-LINDGREN	Model 2175	64762	300003745
F-9	Ultra Notch-Filter Rejected band Ch. 62	WRCD		9	
Radiated immunity in chamber F					
F-10	Control Computer	F+W		FW0502032	300003303
F-11	Signal Generator	R&S	SMB 100A	1406.6000k02-113856	300005266
F-13	RF-Amplifier	Bonn	BLWA 0860-250/100D	035491	300003210
F-14	Stacked Logper Antenna	Schwarzbeck	STLP9128 E	9128 E 013	300003408
F-14a	Bicon-Antenna	EMCO	3109	8906-2309	300000575
F-14b	Bicon-Antenna	Schwarzbeck	Balun VHBD 9134 elements BBFA 9146	3011 0057	300005385
F-15	RF-Amplifier	ar	1000LM20	20562	-/-
F-16	Directional Coupler	ar	DC7144A	312786	300003411
F-16a	Directional coupler	emv	DC 2000	9401-1677	300000592
F-18	Power Meter	R&S	NRP2	104973	300005114
F-19	Power sensor	R&S	NRP-Z91	103332	300005114-1
F-20	Power sensor	R&S	NRP-Z91	103333	300005114-2
F-35	RF- Amplifier	Bonn	BLMA 2060-5	097392A	300003908
F-36	Stacked Microwave Log.-Per. Antenna	Schwarzbeck	STLP9149	9149-044	300003919
Harmonics and flicker in front of chamber F					
F-21	Flicker and Harmonics Test System	Spitzenberger & Spies	PHE4500/B I PHE4500/B II	B5983 B5984	300003314
F-28	Power Supply	Hewlett Packard	6032 A	2920 A 04466	300000580
Radiated emission in chamber F > 1GHz					
F-29	Horn antenna	Schwarzbeck	BBHA 9120 B	188	300003896
F-30	Amplifier	ProNova	0518C-138	005	F 024
F-31	Amplifier	Miteq	42-00502650-28-5A	1103782	300003379
F-32	Horn antenna	Emco	3115	8812-3088	300001032
F-33	Spectrum Analyzer	R&S	FSU26	200809	300003874
F-34	Loop antenna	EMCO	6502	8905-2342	300000256

10 Observations

No observations, exceeding those reported with the single test cases, have been made.

Annex A Document history

Version	Applied changes	Date of release
- / -	Initial release	2022-01-13

Annex B Further information**Glossary**

DUT	-	Device under Test
EMC	-	Electromagnetic Compatibility
EUT	-	Equipment under Test
FCC	-	Federal Communication Commission
FCC ID	-	Company Identifier at FCC
HW	-	Hardware
IC	-	Industry Canada
Inv. No.	-	Inventory number
N/A	-	not applicable
S/N	-	Serial Number
SW	-	Software