



PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA

Tel. 410.290.6652 / Fax 410.290.6654

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 15.247 ZIGBEE

Applicant Name:
Elster Solutions, LLC
208 S. Rogers Lane
Raleigh, NC 27610
United States

Date of Testing:
7/28 - 8/25/2014
Test Site/Location:
PCTEST Lab, Columbia, MD, USA
Test Report Serial No.:
0Y1408131724.QZC-R1

FCC ID:	QZC-RXUEV
APPLICANT:	Elster Solutions, LLC

Application Type:	Certification
Model(s):	RXUEVV, RXUEVDCV
EUT Type:	Wireless Power Meter
Max. RF Output Power:	97.499 mW (19.89 dBm) Peak Conducted
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15.247
Test Procedure(s):	KDB 558074 v03r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in KDB 558074 v03r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

This revised Test Report (S/N: 0Y1408131724.QZC-R1) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.


Randy Ortanez
President



FCC ID: QZC-RXUEV		 FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 1 of 40		

TABLE OF CONTENTS

FCC PART 15.247 MEASUREMENT REPORT	3
1.0 INTRODUCTION.....	4
1.1 SCOPE.....	4
1.2 PCTEST TEST LOCATION.....	4
2.0 PRODUCT INFORMATION	5
2.1 EQUIPMENT DESCRIPTION.....	5
2.2 DEVICE CAPABILITIES	5
2.3 TEST CONFIGURATION	5
2.4 EMI SUPPRESSION DEVICE(S)/MODIFICATIONS.....	5
2.5 LABELING REQUIREMENTS	5
3.0 DESCRIPTION OF TEST	6
3.1 EVALUATION PROCEDURE.....	6
3.2 AC LINE CONDUCTED EMISSIONS.....	6
3.3 RADIATED EMISSIONS	7
4.0 ANTENNA REQUIREMENTS	8
5.0 TEST EQUIPMENT CALIBRATION DATA.....	9
6.0 TEST RESULTS	10
6.1 SUMMARY	10
6.2 6DB BANDWIDTH MEASUREMENT	11
6.3 OUTPUT POWER MEASUREMENT	14
6.4 POWER SPECTRAL DENSITY	17
6.5 CONDUCTED EMISSIONS AT THE BAND EDGE.....	20
6.6 CONDUCTED SPURIOUS EMISSIONS.....	22
6.7 RADIATED SPURIOUS EMISSION MEASUREMENTS.....	27
6.8 RADIATED RESTRICTED BAND EDGE MEASUREMENTS	34
6.9 LINE-CONDUCTED TEST DATA.....	38
7.0 CONCLUSION	40

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 2 of 40



MEASUREMENT REPORT

FCC Part 15.247



§ 2.1033 General Information

APPLICANT: Elster Solutions, LLC

APPLICANT ADDRESS: 208 S. Rogers Lane
Raleigh, NC 27610, United States

TEST SITE: PCTEST ENGINEERING LABORATORY, INC.

TEST SITE ADDRESS: 7185 Oakland Mills Road, Columbia, MD 21046 USA

FCC RULE PART(S): Part 15.247

BASE MODEL: RXUEVV, RXUEVDCV

FCC ID: QZC-RXUEV

FCC CLASSIFICATION: Digital Transmission System (DTS)

Test Device Serial No.: 17477433/17477378 ☐ Production ☒ Pre-Production ☐ Engineering

DATE(S) OF TEST: 7/28 - 8/25/2014

TEST REPORT S/N: 0Y1408131724.QZC-R1

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 159966) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451B-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451B-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EvDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 3 of 40

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Elster Wireless Power Meter FCC ID: QZC-RXUEV**. The test data contained in this report pertains only to the emissions due to the EUT's 2.4-2.48 GHz ZigBee transmitter.

This device can be outfitted with a 200amp disconnect board and thus radiated spurious emissions were provided with and without the board in place.

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 CDMA/EvDO, 900MHz ISM, 2.4GHz Zigbee

2.3 Test Configuration

The Elster Wireless Power Meter FCC ID: QZC-RXUEV was tested per the guidance of KDB 558074 v03r02. ANSI C63.10-2009 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 6.2, 6.3, 6.4, 6.5, and 6.6 for antenna port conducted emissions test setups.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

2.5 Labeling Requirements

Per 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

FCC ID: QZC-RXUEV		 FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter			Page 5 of 40

3.0 DESCRIPTION OF TEST

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2009), and the guidance provided in KDB 558074 v03r02 were used in the measurement of the **Elster Wireless Power Meter FCC ID: QZC-RXUEV**.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 10'x16'x9' shielded enclosure. The shielded enclosure is manufactured by ETS Lindgren RF Enclosures. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-5. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is an ETS Lindgren Model LPRX-4X30 (100dB Attenuation, 14kHz-18GHz) and the two EMI/RFI filters are ETS Lindgren Model LRW-2030-S1 (100dB Minimum Insertion Loss, 14kHz – 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or resolution, clock or data exchange speed, scrolling H pattern to the EUT and/or support equipment whichever determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 6.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 8.51.0.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 6 of 40

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Clause 5, Figure 5.7 of ANSI C63.4-2009. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. An ETS Lindgren Model 2188 raised turntable is used for radiated measurement. It is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. A 78cm high PVC support structure is placed on top of the turntable. A ¾" (~1.9cm) sheet of high density polyethylene is used as the table top and is placed on top of the PVC supports to bring the total height of the table to 80cm.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 0.8 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions. For the EUT positioning, "H" is defined with the EUT lying flat on the test surface, "H2" is defined with the EUT standing up on its side, and "V" is defined with the EUT standing upright.

FCC ID: QZC-RXUEV		 FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		 Reviewed by: Quality Manager	
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 7 of 40	

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the Wireless Power Meter are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:

The **Elster Wireless Power Meter FCC ID: QZC-RXUEV** unit complies with the requirement of §15.203.

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
11	2405	19	2445
12	2410	20	2450
13	2415	21	2455
14	2420	22	2460
15	2425	23	2460
16	2430	24	2470
17	2435	25	2475
18	2440		

Table 4-1. Frequency/ Channel Operations

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 8 of 40

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	RE1	Radiated Emissions Cable Set (UHF/EHF)	5/29/2014	Annual	5/29/2015	N/A
-	WL25-1	Conducted Cable Set (25GHz)	1/29/2014	Annual	1/29/2015	N/A
Agilent	8447D	Broadband Amplifier	5/30/2014	Annual	5/30/2015	2443A01900
Agilent	N9020A	MXA Signal Analyzer	10/29/2013	Annual	10/29/2014	US46470561
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	6/26/2013	Biennial	6/26/2015	121034
Emco	3115	Horn Antenna (1-18GHz)	1/30/2014	Biennial	1/30/2016	9704-5182
Emco	3816/2	Line Impedance Stabilization Network	2/12/2013	Biennial	2/12/2015	9707-1079
K & L	13SH10-1000/U1000	N Type High Pass Filter	5/22/2014	Annual	5/22/2015	1
Pasternack	NMLC-1	Line Conducted Emissions Cable (NM)	1/28/2014	Annual	1/28/2015	N/A
Rohde & Schwarz	TS-PR18	1-18 GHz Pre-Amplifier	3/5/2014	Annual	3/5/2015	100071
Rohde & Schwarz	ESU26	EMI Test Receiver (26.5GHz)	1/27/2014	Annual	1/27/2015	100342
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	1/28/2014	Biennial	1/28/2016	A051107

Table 5-1. Annual Test Equipment Calibration Schedule

Note:

For equipment listed above that has a calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 9 of 40	

6.0 TEST RESULTS

6.1 Summary

Company Name: Elster Solutions, LLC
 FCC ID: QZC-RXUEV
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)					
15.247(a)(2)	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 6.2
15.247(b)(3)	Transmitter Output Power	< 1 Watt		PASS	Sections 6.3
15.247(e)	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 6.4
15.247(d)	Band Edge / Out-of-Band Emissions	Conducted $\geq$ 20dBc		PASS	Sections 6.5, 6.6
15.205 15.209	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209	RADIATED	PASS	Sections 6.7, 0
15.207	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits	LINE CONDUCTED	PASS	Section 6.9

Table 6-1. Summary of Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 10 of 40	

6.2 6dB Bandwidth Measurement

§15.247(a.2)

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

KDB 558074 v03r02 – Section 8.2 Option 2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-1. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 11 of 40	


Frequency [MHz]	Channel No.	Measured Bandwidth [MHz]	Minimum Bandwidth [MHz]	Pass / Fail
2405	11	1.576	0.500	PASS
2440	18	1.633	0.500	PASS
2475	25	1.596	0.500	PASS

Table 6-2. Conducted Bandwidth Measurements




Plot 6-1. 6dB Bandwidth Plot (ZigBee- Ch. 11)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 12 of 40



Plot 6-2. 6dB Bandwidth Plot (ZigBee – Ch. 18)



Plot 6-3. 6dB Bandwidth Plot (Zigbee – Ch. 25)

FCC ID: QZC-RXUEV	 FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)			Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 13 of 40	

6.3 Output Power Measurement

§15.247(b.3)

Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making peak and average measurements while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The maximum permissible conducted output power is 1 Watt.

Test Procedure Used

KDB 558074 v03r02 – Section 9.1.1 RBW $\geq$ DTS bandwidth

Test Settings

1. Set the RBW $\geq$ DTS bandwidth.
2. Set VBW $\geq 3 \times$ RBW.
3. Set span $\geq 3 \times$ RBW
4. Sweep time = auto couple.
5. Detector = peak.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use peak marker function to determine the peak amplitude level.

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.





Figure 6-2. Test Instrument & Measurement Setup

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 14 of 40


Frequency [MHz]	Channel No.	Peak Conducted Power	
		[dBm]	[mW]
2405	11	18.55	71.614
2440	18	19.89	97.499
2475	25	17.26	53.211

Table 6-3. Conducted Power Measurements




Plot 6-4. ZigBee – Ch.11 - Conducted Output Power

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)	elster	Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 15 of 40



Plot 6-5. ZigBee – Ch.18 - Conducted Output Power



Plot 6-6. ZigBee – Ch.25 - Conducted Output Power

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 16 of 40

6.4 Power Spectral Density

§15.247(e)

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

KDB 558074 v03r02 – Section 10.2 Method PKPSD

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span = 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW = 1MHz
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-3. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 17 of 40	


Frequency [MHz]	Channel No.	Measured Power Spectral Density [dBm]	Maximum Permissible Power Density [dBm / 3kHz]	Margin [dB]	Pass / Fail
2405	11	4.73	8.00	-3.27	Pass
2440	18	5.58	8.00	-2.42	Pass
2475	25	0.20	8.00	-7.80	Pass

Table 6-4. Conducted Power Density Measurements




Plot 6-7. Power Spectral Density Plot (ZigBee – Ch. 11)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 18 of 40



Plot 6-8. Power Spectral Density Plot (ZigBee – Ch. 18)



Plot 6-9. Power Spectral Density Plot (ZigBee – Ch. 25)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 19 of 40

6.5 Conducted Emissions at the Band Edge

§15.247(d)

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 9.1).

Test Procedure Used

KDB 558074 v03r02 – Section 11.3

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW = 1MHz
5. Detector = Peak
6. Number of sweep points $\geq 2 \times \text{Span/RBW}$
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-4. Test Instrument & Measurement Setup


Test Notes

None

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 20 of 40



Plot 6-10. Band Edge Plot (ZigBee – Ch. 11)



Plot 6-11. Band Edge Plot (ZigBee – Ch. 25)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 21 of 40

6.6 Conducted Spurious Emissions

§15.247(d)

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.1 of KDB 558074 v03r02.

Test Procedure Used

KDB 558074 v03r02 – Section 11.3

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 6-5. Test Instrument & Measurement Setup

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 22 of 40


Test Notes

1. RBW was set to 1MHz rather than 100kHz in order to increase the measurement speed.
2. The display line shown in the following plots denotes the limit at 20dB below the fundamental emission level measured in a 100kHz bandwidth. However, since the traces in the following plots are measured with a 1MHz RBW, the display line may not necessarily appear to be 20dB below the level of the fundamental in a 1MHz bandwidth.
3. For plots showing conducted spurious emissions near the limit, the frequencies were investigated with a reduced RBW to ensure that no emissions were present.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 23 of 40	




Plot 6-12. Conducted Spurious Plot (ZigBee – Ch. 11)




Plot 6-13. Conducted Spurious Plot (ZigBee – Ch. 11)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)	elster	Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 24 of 40




Plot 6-14. Conducted Spurious Plot (ZigBee – Ch. 18)




Plot 6-15. Conducted Spurious Plot (ZigBee – Ch. 18)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 25 of 40



Plot 6-16. Conducted Spurious Plot (ZigBee – Ch. 25)



Plot 6-17. Conducted Spurious Plot (ZigBee – Ch. 25)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)	elster	Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 26 of 40

6.7 Radiated Spurious Emission Measurements

§15.247(d) §15.205 & §15.209

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle (>98%), at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table 6-5 per Section 15.209.

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 6-5. Radiated Limits

Test Procedures Used

KDB 558074 v03r02 – Section 12.1, 12.2.7

Test Settings

Average Field Strength Measurements per Section 12.2.5.1 of KDB 558074 v03r02

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 27 of 40

Peak Field Strength Measurements per Section 12.2.4 of KDB 558074 v03r02

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 6-6. Test Instrument & Measurement Setup

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 28 of 40

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 v03r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 are below the limit shown in Table 6-10.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes. The H polarity represents the unit laying flat on its back, H2 represents the unit laying down on its side and V represents the unit sitting up right.
4. This unit was tested while powered by an AC power source.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas. The worst-case emissions are reported however emissions whose levels were not within 20dB of the respective limits were not reported.
6. Emissions below 18GHz were measured at a 3 meter test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.

Sample Calculations

Determining Spurious Emissions Levels

- o Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- o $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]}$
- o $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

Radiated Band Edge Measurement Offset

- o The amplitude offset shown in the radiated restricted band edge plots in Section 6.8 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + 10 \text{ dB Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 29 of 40

Radiated Spurious Emission Measurements (with 200amp disconnect)

§15.247(d) §15.205 & §15.209

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2405MHz
 Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4810.00	-103.51	Avg	V	V	40.99	44.48	53.98	-9.50
4810.00	-97.41	Peak	V	V	40.99	50.58	73.98	-23.40
12025.00	-115.72	Avg	V	V	45.80	37.08	53.98	-16.90
12025.00	-103.24	Peak	V	V	45.80	49.56	73.98	-24.42

Table 6-6. Radiated Measurements (with 200amp disconnect)

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 18

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	-103.00	Avg	V	V	41.01	45.01	53.98	-8.97
4880.00	-95.98	Peak	V	V	41.01	52.03	73.98	-21.95
7320.00	-104.86	Avg	V	V	41.20	43.34	53.98	-10.64
7320.00	-97.31	Peak	V	V	41.20	50.89	73.98	-23.09
12200.00	-115.51	Avg	V	V	46.08	37.57	53.98	-16.41
12200.00	-103.44	Peak	V	V	46.08	49.64	73.98	-24.34

Table 6-7. Radiated Measurements (with 200amp disconnect)

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 30 of 40

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2475MHz
 Channel: 25

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4950.00	-105.17	Avg	V	V	41.01	42.84	53.98	-11.14
4950.00	-97.29	Peak	V	V	41.01	50.72	73.98	-23.26
7425.00	-111.99	Avg	V	V	41.04	36.06	53.98	-17.92
7425.00	-102.27	Peak	V	V	41.04	45.78	73.98	-28.20
12375.00	-114.14	Avg	V	V	46.18	39.04	53.98	-14.94
12375.00	-103.32	Peak	V	V	46.18	49.86	73.98	-24.12

Table 6-8. Radiated Measurements (with 200amp disconnect)

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 31 of 40

Radiated Spurious Emission Measurements (without 200amp disconnect)

§15.247(d) §15.205 & §15.209

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2405MHz
 Channel: 11

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4810.00	-105.27	Avg	V	V	40.98	42.71	53.98	-11.27
4810.00	-97.21	Peak	V	V	40.98	50.77	73.98	-23.21
12025.00	-116.35	Avg	V	V	45.80	36.45	53.98	-17.53
12025.00	-104.60	Peak	V	V	45.80	48.20	73.98	-25.78

Table 6-9. Radiated Measurements (without 200amp disconnect)

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2440MHz
 Channel: 18

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4880.00	-106.53	Avg	V	V	41.01	41.48	53.98	-12.50
4880.00	-98.86	Peak	V	V	41.01	49.15	73.98	-24.83
7320.00	-107.92	Avg	V	V	41.19	40.27	53.98	-13.71
7320.00	-99.54	Peak	V	V	41.19	48.65	73.98	-25.33
12200.00	-113.40	Avg	V	V	46.07	39.67	53.98	-14.31
12200.00	-102.70	Peak	V	V	46.07	50.37	73.98	-23.61

Table 6-10. Radiated Measurements (without 200amp disconnect)

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 32 of 40

Worst Case Mode: ZigBee
 Distance of Measurements: 3 Meters
 Operating Frequency: 2475MHz
 Channel: 25

Frequency [MHz]	Analyzer Level [dBm]	Detector	Ant. Pol. [H/V]	EUT Pol. [H/H2/V]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4950.00	-107.45	Avg	V	V	41.01	40.56	53.98	-13.42
4950.00	-98.43	Peak	V	V	41.01	49.58	73.98	-24.40
7425.00	-113.62	Avg	V	V	41.04	34.43	53.98	-19.55
7425.00	-102.83	Peak	V	V	41.04	45.22	73.98	-28.76
12375.00	-117.34	Avg	V	V	46.18	35.84	53.98	-18.14
12375.00	-105.36	Peak	V	V	46.18	47.82	73.98	-26.16

Table 6-11. Radiated Measurements (without 200amp disconnect)

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 33 of 40

6.8 Radiated Restricted Band Edge Measurements

\$15.205 \$15.209


The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting.

Worst Case Mode: ZigBee

Distance of Measurements: 3 Meters

Operating Frequency: 2405MHz

Channel: 11




Plot 6-18. Radiated Restricted Lower Band Edge Measurement (Average)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter	Page 34 of 40

Radiated Restricted Band Edge Measurements

\$15.205 \$15.209



Plot 6-19. Radiated Restricted Lower Band Edge Measurement (Peak)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 35 of 40

Radiated Restricted Band Edge Measurements


§15.205 §15.209

Worst Case Mode: ZigBee

Distance of Measurements: 3 Meters

Operating Frequency: 2475MHz

Channel: 25




Plot 6-20. Radiated Restricted Upper Band Edge Measurement (Average)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 36 of 40

Radiated Restricted Band Edge Measurements

\$15.205 \$15.209




Plot 6-21. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 37 of 40

6.9 Line-Conducted Test Data

\$15.207



Plot 6-22. Line Conducted Plot with ZigBee (L1)


Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in ZigBee mode using Channel 18. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Factor (dB)
5. Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 38 of 40

Line-Conducted Test Data

§15.207



Plot 6-23. Line Conducted Plot with ZigBee (N)

Notes:

1. All modes of operation, data rates, and test channels were investigated and the worst-case emissions are reported in ZigBee mode using Channel 18. The emissions found were not affected by the choice of channel used during testing.
2. The limit for Class B device(s) from 150kHz to 30MHz are specified in Section 15.207 of the Title 47 CFR.
3. Factor (dB) = Cable loss (dB) + LISN insertion factor (dB)
4. QP/AV Level (dBμV) = QP/AV Analyzer/Receiver Level (dBμV) + Factor (dB)
5. Margin (dB) = QP/AV Limit (dBμV) – QP/AV Level (dBμV)
6. Traces shown in plot are made using a peak detector.
7. Deviations to the Specifications: None.

FCC ID: QZC-RXUEV	PCTEST ENGINEERING LABORATORY, INC.	FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 39 of 40

7.0 CONCLUSION

The data collected relate only the item(s) tested and show that the **Elster Wireless Power Meter** **FCC ID: QZC-RXUEV** is in compliance with Part 15C of the FCC Rules.

FCC ID: QZC-RXUEV		FCC Pt. 15.247 ZIGBEE MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1408131724.QZC-R1	Test Dates: 7/28 - 8/25/2014	EUT Type: Wireless Power Meter		Page 40 of 40