



Elster Solutions
208 S Rogers Lane
Raleigh, NC 27610-2144
United States

T +1 919 212 4800
F +1 919 212 4801

www.elster.com

21 April 2022

Federal Communications Commission
Equipment and Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Modular Approval Request

FCC ID: QZC-SNRGK4

The following attestation addresses the requirements to support modular approval:

	Single modular transmitters Checklist Item	Honeywell Response	Remarks
1	The radio elements of the modular transmitter must have their own shielding. The physical crystal and tuning capacitors may be located external to the shielded radio elements.	Yes	
2	The modular transmitter must have buffered modulation/data inputs (if such inputs are provided) to ensure that the module will comply with part 15 requirements under conditions of excessive data rates or over-modulation.	Yes	All the modulation is handled inside the comms processor module
3	The modular transmitter must have its own power supply regulation.	Yes	all supply voltages are regulated on the PCB.
4	The modular transmitter must comply with the antenna and transmission system requirements of §§ 15.203, 15.204(b) and 15.204(c). The antenna must either be permanently attached or employ a "unique" antenna coupler (at all connections between the module and the antenna, including the cable). The "professional installation" provision of § 15.203 is not applicable to modules but can apply to limited modular approvals under paragraph (b) of this section.	Yes	Professional installation, protected by sealing enclosure

5	The modular transmitter must be tested in a stand-alone configuration, i.e., the module must not be inside another device during testing for compliance with part 15 requirements. Unless the transmitter module will be battery powered, it must comply with the AC line conducted requirements found in § 15.207. AC or DC power lines and data input/output lines connected to the module must not contain ferrites, unless they will be marketed with the module (see § 15.27(a)). The length of these lines shall be the length typical of actual use or, if that length is unknown, at least 10 centimeters to insure that there is no coupling between the case of the module and supporting equipment. Any accessories, peripherals, or support equipment connected to the module during testing shall be unmodified and commercially available (see § 15.31(i)).	Yes	the module can be tested as a standalone board run from a 12V supply.
6	The modular transmitter must be equipped with either a permanently affixed label or must be capable of electronically displaying its FCC identification number	Yes	
7	The modular transmitter must comply with any specific rules or operating requirements that ordinarily apply to a complete transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization.	Yes	
8	Radio frequency devices operating under the provisions of this part are subject to the radio frequency radiation exposure requirements specified in §§ 1.1307(b), 1.1310, 2.1091, and 2.1093 of this chapter, as appropriate. Applications for equipment authorization of modular transmitters under this section must contain a statement confirming compliance with these requirements. The modular transmitter must comply with any	Yes	Scope of the FCC testing being performed at element

	applicable RF exposure requirements in its final configuration. Technical information showing the basis for this statement must be submitted to the Commission upon request.		
--	--	--	--

Respectfully,

Charles Greene Digitally signed by Charles
Greene
Date: 2022.04.21 15:19:24 -04'00'

Charles Greene
Advanced Wireless/RF Engineer
Telephone: 919-212-5018
e-mail: charles.greene@honeywell.com