FCC Test Report

Report No.: AGC00070150704FE03

FCC ID	:	R2MAE01
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Bluetooth headset
BRAND NAME	:	N/A
MODEL NAME	:	AE01, AE02, AE03, AE05, AE06, AE07, AEXX
CLIENT	:	AVLink Industrial Co., Ltd.
DATE OF ISSUE	:	Aug.10, 2015
STANDARD(S) **TEST PROCEDURE(S)**	:	FCC Part 15 Rules
REPORT VERSION	:	V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	Aug.10, 2015	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 4
2. GENERAL INFORMATION 5
2.1. PRODUCT DESCRIPTION 5
2.2. TABLE OF CARRIER FREQUENCYS 5
3. MEASUREMENT UNCERTAINTY 7
4. DESCRIPTION OF TEST MODES 7
5. SYSTEM TEST CONFIGURATION 8
5.1. CONFIGURATION OF EUT SYSTEM 8
5.2. EQUIPMENT USED IN EUT SYSTEM 8
5.3. SUMMARY OF TEST RESULTS 8
6. TEST FACILITY 9
7 ALL TEST EQUIPMENT LIST 9
8. RADIATED EMISSION 11
8.1TEST LIMIT 11
8.2. MEASUREMENT PROCEDURE 12
8.3. TEST SETUP 14
8.4. TEST RESULT(Worst modulation:GFSK) 16
9. BAND EDGE EMISSION 42
9.1. MEASUREMENT PROCEDURE 42
9.2 TEST SETUP 42
9.3 RADIATED TEST RESULT(Worst modulation:GFSK) 43
10. 20DB BANDWIDTH 51
10.1. MEASUREMENT PROCEDURE 51
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 51
10.3. LIMITS AND MEASUREMENT RESULTS 51
11. FCC LINE CONDUCTED EMISSION TEST 60
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST 60
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 60
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 61
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 61
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 62
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 66
APPENDIX B: PHOTOGRAPHS OF EUT 68

1. VERIFICATION OF CONFORMITY

Applicant	AVLink Industrial Co., Ltd.
Address	7/F, A1 Bldg, Shuichanjingwan Industrial 1st Area, Nanchang, Gushu, Xixiang, Bao'an, Shenzhen, China 518126
Manufacturer	AVLink Industrial Co., Ltd.
Address	7/F, A1 Bldg, Shuichanjingwan Industrial 1st Area, Nanchang, Gushu, Xixiang, Bao'an, Shenzhen, China 518126
Product Designation	Bluetooth headset
Brand Name	N/A
Test Model	AE01
Series Model	AE02, AE03, AE05, AE06, AE07, AEXX
Different Description	All the same except for the model name.
Date of test	Aug.06,, 2015 to Aug.06, 2015
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Dongguan Precise Testing Service Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Tested By	Matt Zhang	
	Matt Zhang(Zhang Liang)	Aug.10, 2015
Reviewed By	Bart Xie	
	Bart Xie(Xie Xiaobin)	Aug.10, 2015
Approved By	Solger Zhang	
	Solger Zhang(Zhang Hongyi) Authorized Officer	Aug.10, 2015

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	1.04dBm(Max)
Bluetooth Version	V4.1
Modulation	GFSK, π /4-DQPSK, 8-DPSK (For Traditional Bluetooth and BLE)
Number of channels	79 for traditional BT 40 for BLE
Hardware Version	V1.2
Software Version	V1.0
Antenna Designation	Ceramic Antenna (Met 15.203 Antenna requirement)
Antenna Gain	0dBi
Power Supply	DC 3.7V by battery
Note: The USB port only used for charging and can't be used to transfer data with PC.	

2.2. TABLE OF CARRIER FREQUENCYS

Traditional Bluetooth channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

BLE Channel List

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Normal operation (BT)

Note:
1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Bluetooth headset	AE01	R2MAE01	EUT
2	PC	N/A	ASUS	A.E
3	Control box	N/A	N/A	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWIDTH	Compliant

6. TEST FACILITY

Site	Dongguan Precise Testing Service Co., Ltd.
Location	Building D,Baoding Technology Park, Guangming Road2,Dongcheng District, Dongguan, Guangdong, China,
FCC Registration No.	371540
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7 ALL TEST EQUIPMENT LIST

FOR RADIATED EMISSION TEST (BELOW 1GHZ)

Radiated Emission Test Site					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Trilog Broadband Antenna (25M-1GHz)	SCHWARZBECK	VULB9160	9160-3355	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9475	9745-0013	July 4, 2015	July 3, 2016
RF Cable	SCHWARZBECK	AK9515E	96221	July 4, 2015	July 3, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Active loop antenna (9K-30MHz)	Schwarzbeck	FMZB1519	1519-038	June 6, 2015	June 5, 2016
Spectrum analyzer	Agilent	E4407B	MY46185649	June 6, 2015	June 5, 2016

FOR RADIATED EMISSION TEST (1GHZ ABOVE)

Radiated Emission Test Site					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Horn Antenna (1G-18GHz)	SCHWARZBECK	BBHA9120D	9120D-1246	July 11, 2015	July 10, 2016
Spectrum Analyzer	Agilent	E4411B	MY4511453	July 4, 2015	July 3, 2016
Signal Amplifier	SCHWARZBECK	BBV 9718	9718-269	July 7, 2015	July 6, 2016
RF Cable	SCHWARZBECK	AK9515H	96220	July 8, 2015	July 7, 2016
3m Anechoic Chamber	CHENGYU	966	PTS-001	June 6, 2015	June 5, 2016
MULTI-DEVICE Positioning Controller	Max-Full	MF-7802	MF780208339	N/A	N/A
Horn Ant (18G-40GHz)	Schwarzbeck	BBHA 9170	9170-181	June 6, 2015	June 5, 2016

Conducted Emission Test Site					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
EMI Test Receiver	Rohde & Schwarz	ESCI	101417	July 4, 2015	July 3, 2016
Artificial Mains Network	Narda	L2-16B	000WX31025	July 8, 2015	July 7, 2016
Artificial Mains Network (AUX)	Narda	L2-16B	000WX31026	July 8, 2015	July 7, 2016
RF Cable	SCHWARZBECK	AK9515E	96222	July 4, 2015	July 3, 2016
Shielded Room	CHENGYU	843	PTS-002	June 6,2015	June 5,2016

8. RADIATED EMISSION

8.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark: (1) Emission level dBμ V = 20 log Emission level μ V/m
(2) The smaller limit shall apply at the cross point between two frequency bands.
(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.4. TEST RESULT(Worst modulation:GFSK)

FOR TRADITIONAL BLUETOOTH

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Low channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7333	11.87	9.73	21.60	40.00	-18.40	peak			
2		256.3333	18.82	14.09	32.91	46.00	-13.09	peak			
3	*	288.6666	18.71	15.07	33.78	46.00	-12.22	peak			
4		599.0667	8.03	23.71	31.74	46.00	-14.26	peak			
5		697.6833	5.47	25.13	30.60	46.00	-15.40	peak			
6		982.2167	3.43	29.69	33.12	54.00	-20.88	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Low channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	81.7333	24.64	2.42	27.06	40.00	-12.94	peak			
2		170.6500	15.86	14.66	30.52	43.50	-12.98	peak			
3		298.3667	16.66	15.36	32.02	46.00	-13.98	peak			
4		398.6000	10.80	19.06	29.86	46.00	-16.14	peak			
5		731.6332	6.29	26.10	32.39	46.00	-13.61	peak			
6		943.4167	2.13	29.82	31.95	46.00	-14.05	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Middle channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7333	13.56	9.73	23.29	40.00	-16.71	peak			
2		160.9500	12.86	15.13	27.99	43.50	-15.51	peak			
3	*	232.0833	20.17	13.22	33.39	46.00	-12.61	peak			
4		338.7833	14.25	17.99	32.24	46.00	-13.76	peak			
5		697.6833	4.67	25.13	29.80	46.00	-16.20	peak			
6		799.5333	4.37	27.31	31.68	46.00	-14.32	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Middle channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	88.2000	27.44	4.74	32.18	43.50	-11.32	peak			
2		181.9667	17.06	13.57	30.63	43.50	-12.87	peak			
3		299.9833	16.38	15.41	31.79	46.00	-14.21	peak			
4		498.8333	7.54	21.12	28.66	46.00	-17.34	peak			
5		731.6332	3.90	26.10	30.00	46.00	-16.00	peak			
6		983.8333	3.20	29.68	32.88	54.00	-21.12	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: High channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		59.1000	12.34	11.16	23.50	40.00	-16.50	peak			
2		159.3333	12.45	15.33	27.78	43.50	-15.72	peak			
3	*	259.5667	19.43	14.19	33.62	46.00	-12.38	peak			
4		291.9000	16.88	15.17	32.05	46.00	-13.95	peak			
5		797.9167	1.74	27.29	29.03	46.00	-16.97	peak			
6		945.0333	1.80	29.86	31.66	46.00	-14.34	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: High channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	86.5833	25.61	4.16	29.77	40.00	-10.23	peak			
2		181.9667	16.93	13.57	30.50	43.50	-13.00	peak			
3		338.7833	15.07	17.99	33.06	46.00	-12.94	peak			
4		398.6000	15.87	19.06	34.93	46.00	-11.07	peak			
5		796.3000	6.61	27.27	33.88	46.00	-12.12	peak			
6		983.8333	4.88	29.68	34.56	54.00	-19.44	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

FOR BLE

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Low channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7332	12.87	9.73	22.60	40.00	-17.40	peak			
2	*	288.6666	18.21	15.07	33.28	46.00	-12.72	peak			
3		400.2167	6.60	19.08	25.68	46.00	-20.32	peak			
4		582.8999	4.50	23.30	27.80	46.00	-18.20	peak			
5		697.6833	5.47	25.13	30.60	46.00	-15.40	peak			
6		982.2166	2.93	29.69	32.62	54.00	-21.38	peak			

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL –VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Low channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7332	25.64	2.42	28.06	40.00	-11.94	peak			
2	*	170.6500	17.36	14.66	32.02	43.50	-11.48	peak			
3		298.3666	16.66	15.36	32.02	46.00	-13.98	peak			
4		398.6000	12.30	19.06	31.36	46.00	-14.64	peak			
5		506.9166	6.77	21.32	28.09	46.00	-17.91	peak			
6		731.6332	5.29	26.10	31.39	46.00	-14.61	peak			

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Middle channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		81.7332	13.56	9.73	23.29	40.00	-16.71	peak			
2	*	202.9833	18.71	12.11	30.82	43.50	-12.68	peak			
3		232.0833	19.17	13.22	32.39	46.00	-13.61	peak			
4		338.7832	13.75	17.99	31.74	46.00	-14.26	peak			
5		799.5333	1.87	27.31	29.18	46.00	-16.82	peak			
6		930.4832	1.81	29.46	31.27	46.00	-14.73	peak			

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL –VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: Middle channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	88.2000	28.44	4.74	33.18	43.50	-10.32	peak			
2		181.9667	17.06	13.57	30.63	43.50	-12.87	peak			
3		299.9832	16.38	15.41	31.79	46.00	-14.21	peak			
4		400.2167	11.28	19.08	30.36	46.00	-15.64	peak			
5		498.8333	8.04	21.12	29.16	46.00	-16.84	peak			
6		797.9166	3.62	27.29	30.91	46.00	-15.09	peak			

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: High channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		59.1000	10.34	11.16	21.50	40.00	-18.50	peak			
2		159.3333	12.95	15.33	28.28	43.50	-15.22	peak			
3	*	259.5667	20.93	14.19	35.12	46.00	-10.88	peak			
4		498.8333	2.66	21.12	23.78	46.00	-22.22	peak			
5		699.2998	3.33	25.17	28.50	46.00	-17.50	peak			
6		974.1331	1.77	29.77	31.54	54.00	-22.46	peak			

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Bluetooth headset
M/N: AE01
Mode: High channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 23.7
Humidity: 56.5 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	86.5832	26.11	4.16	30.27	40.00	-9.73	peak			
2		181.9667	18.43	13.57	32.00	43.50	-11.50	peak			
3		283.8167	18.19	14.92	33.11	46.00	-12.89	peak			
4		531.1666	10.38	21.97	32.35	46.00	-13.65	peak			
5		796.2999	7.11	27.27	34.38	46.00	-11.62	peak			
6		896.5333	5.10	28.52	33.62	46.00	-12.38	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ

FOR TRADITIONAL BLUETOOTH

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1575.000	59.32	-14.59	44.73	74.00	-29.27	peak			
2		2402.000	104.73	-9.68	95.05	114.00	-18.95	peak			
3	*	2402.000	94.85	-9.68	85.17	94.00	-8.83	AVG	150	77	
4		4450.000	47.34	-3.28	44.06	74.00	-29.94	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1600.000	58.48	-14.33	44.15	74.00	-29.85	peak			
2		2402.000	104.73	-9.68	95.05	114.00	-18.95	peak			
3	*	2402.000	94.82	-9.68	85.14	94.00	-8.86	AVG	150	92	
4		4300.000	49.09	-3.79	45.30	74.00	-28.70	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Middle Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1766.667	57.33	-12.57	44.76	74.00	-29.24	peak			
2		2441.000	104.79	-9.63	95.16	114.00	-18.84	peak			
3	*	2441.000	94.60	-9.63	84.97	94.00	-9.03	AVG	150	66	
4		4333.333	47.84	-3.68	44.16	74.00	-29.84	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: Bluetooth headset Distance: 3m
M/N: AE01
Mode: Middle Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1650.000	58.72	-13.80	44.92	74.00	-29.08	peak			
2		2441.000	105.23	-9.63	95.60	114.00	-18.40	peak			
3	*	2441.000	94.80	-9.63	85.17	94.00	-8.83	AVG	150	81	
4		5008.333	45.69	-1.80	43.89	74.00	-30.11	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: High Channel TX
Note:

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1758.333	58.36	-12.66	45.70	74.00	-28.30	peak			
2		2480.000	105.37	-9.59	95.78	114.00	-18.22	peak			
3	*	2480.000	94.90	-9.59	85.31	94.00	-8.69	AVG	150	50	
4		4000.000	49.34	-4.81	44.53	74.00	-29.47	peak			

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: Bluetooth headset Distance: 3m
M/N: AE01
Mode: High Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1641.667	59.14	-13.89	45.25	74.00	-28.75	peak			
2		2480.000	105.87	-9.59	96.28	114.00	-17.72	peak			
3	*	2480.000	94.86	-9.59	85.27	94.00	-8.73	AVG	150	36	
4		4583.333	47.89	-2.89	45.00	74.00	-29.00	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.73	-9.68	95.05	114	-18.95	Horizontal
2402	104.73	-9.68	95.05	114	-18.95	Vertical
2441	104.79	-9.63	95.16	114	-18.84	Horizontal
2441	105.23	-9.63	95.60	114	-18.40	Vertical
2480	105.37	-9.59	95.78	114	-18.22	Horizontal
2480	105.87	-9.59	96.28	114	-17.72	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	94.85	-9.68	85.17	94	-8.83	Horizontal
2402	94.82	-9.68	85.14	94	-8.86	Vertical
2441	94.60	-9.63	84.97	94	-9.03	Horizontal
2441	94.80	-9.63	85.17	94	-8.83	Vertical
2480	94.90	-9.59	85.31	94	-8.69	Horizontal
2480	94.86	-9.59	85.27	94	-8.73	Vertical

FOR BLE

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 | Polarization: *Horizontal* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- | Power: | Humidity: 60 %
EUT: Bluetooth headset | Distance: 3m
M/N: AE01
Mode: Low Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1958.333	55.72	-10.56	45.16	74.00	-28.84	peak			
2		2402.000	104.23	-9.68	94.55	114.00	-19.45	peak			
3	*	2402.000	94.20	-9.68	84.52	94.00	-9.48	AVG	150	21	
4		4875.000	46.85	-2.13	44.72	74.00	-29.28	peak			

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1750.000	57.59	-12.75	44.84	74.00	-29.16	peak			
2		2402.000	104.23	-9.68	94.55	114.00	-19.45	peak			
3	*	2402.000	94.35	-9.68	84.67	94.00	-9.33	AVG	150	10	
4		4883.333	46.46	-2.11	44.35	74.00	-29.65	peak			

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Middle Channel TX
Note:

Polarization: ***Horizontal***
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1891.667	54.93	-11.26	43.67	74.00	-30.33	peak			
2		2440.000	104.30	-9.64	94.66	114.00	-19.34	peak			
3	*	2440.000	93.97	-9.64	84.33	94.00	-9.67	AVG	150	11	
4		4333.333	47.84	-3.68	44.16	74.00	-29.84	peak			

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: Middle Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1825.000	56.92	-11.96	44.96	74.00	-29.04	peak			
2		2440.000	104.74	-9.64	95.10	114.00	-18.90	peak			
3	*	2440.000	93.38	-9.64	83.74	94.00	-10.26	AVG	150	0	
4		4291.667	49.14	-3.82	45.32	74.00	-28.68	peak			

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Bluetooth headset
M/N: AE01
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2041.667	55.05	-10.07	44.98	74.00	-29.02	peak			
2		2480.000	104.37	-9.59	94.78	114.00	-19.22	peak			
3	*	2480.000	93.84	-9.59	84.25	94.00	-9.75	AVG	150	24	
4		3966.667	49.91	-5.02	44.89	74.00	-29.11	peak			

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- Power: Humidity: 60 %
EUT: Bluetooth headset Distance: 3m
M/N: AE01
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		1733.333	57.56	-12.93	44.63	74.00	-29.37	peak			
2		2480.000	104.87	-9.59	95.28	114.00	-18.72	peak			
3	*	2480.000	93.10	-9.59	83.51	94.00	-10.49	AVG	150	11	
4		3816.667	50.38	-5.94	44.44	74.00	-29.56	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	104.23	-9.68	94.55	114	-19.45	Horizontal
2402	104.23	-9.68	94.55	114	-19.45	Vertical
2440	104.30	-9.64	94.66	114	-19.34	Horizontal
2440	104.74	-9.64	95.10	114	-18.90	Vertical
2480	104.37	-9.59	94.78	114	-19.22	Horizontal
2480	104.87	-9.59	95.28	114	-18.72	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	94.20	-9.68	84.52	94	-9.48	Horizontal
2402	94.35	-9.68	84.67	94	-9.33	Vertical
2440	93.97	-9.63	84.33	94	-9.67	Horizontal
2440	93.38	-9.64	83.74	94	-10.26	Vertical
2480	93.84	-9.59	84.25	94	-9.75	Horizontal
2480	93.10	-9.59	83.51	94	-10.49	Vertical

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP



CONDUCTED TEST SETUP



9.3 RADIATED TEST RESULT(Worst modulation:GFSK)

FOR TRADITIONAL BLEUTOOTH

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1	Polarization: *Horizontal*	Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)	Power:	Humidity: 60 %
EUT: Bluetooth headset	Distance:	
M/N: AE01		
Mode: Low Channel TX		
Note:		

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2316.167	33.04	10.23	43.27	74.00	-30.73	peak			
2		2390.000	33.00	10.31	43.31	74.00	-30.69	peak			
3	*	2402.000	85.72	10.32	96.04	74.00	22.04	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Bluetooth headset
M/N: AE01
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2320.608	32.52	10.23	42.75	74.00	-31.25	peak			
2		2390.000	32.21	10.31	42.52	74.00	-31.48	peak			
3	*	2402.000	85.59	10.32	95.91	74.00	21.91	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Bluetooth headset
M/N: AE01
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.55	10.41	95.96	74.00	21.96	peak			
2		2483.500	33.19	10.41	43.60	74.00	-30.40	peak			
3		2490.943	33.85	10.42	44.27	74.00	-29.73	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth headset Distance:
M/N: AE01
Mode: High Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.32	10.41	95.73	74.00	21.73	peak			
2		2483.500	31.76	10.41	42.17	74.00	-31.83	peak			
3		2490.283	32.95	10.42	43.37	74.00	-30.63	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

FOR BLE

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1 | Polarization: *Horizontal* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) | Power: | Humidity: 60 %
EUT: Bluetooth headset | Distance:
M/N: AE01
Mode: Low Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2337.008	32.92	10.25	43.17	74.00	-30.83	peak			
2		2390.000	34.00	10.31	44.31	74.00	-29.69	peak			
3	*	2402.000	85.22	10.32	95.54	74.00	21.54	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Bluetooth headset
M/N: AE01
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2317.533	32.19	10.23	42.42	74.00	-31.58	peak			
2		2390.000	31.71	10.31	42.02	74.00	-31.98	peak			
3	*	2402.000	85.09	10.32	95.41	74.00	21.41	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Bluetooth headset
M/N: AE01
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	85.05	10.41	95.46	74.00	21.46	peak			
2		2483.500	33.69	10.41	44.10	74.00	-29.90	peak			
3		2493.070	32.66	10.42	43.08	74.00	-30.92	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 Polarization: *Vertical* Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Bluetooth headset Distance:
M/N: AE01
Mode: High Channel TX
Note:

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	84.82	10.41	95.23	74.00	21.23	peak			
2		2483.500	31.76	10.41	42.17	74.00	-31.83	peak			
3		2490.283	32.95	10.42	43.37	74.00	-30.63	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel
   RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



10.3. LIMITS AND MEASUREMENT RESULTS

FOR TRADITIONAL BLUETOOTH

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	0.891	PASS
	Middle Channel	0.812	PASS
	High Channel	0.766	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.233	PASS
	Middle Channel	1.214	PASS
	High Channel	1.186	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.280	PASS
	Middle Channel	1.264	PASS
	High Channel	1.260	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



FOR BLE

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	**Measurement Result**		
	Test Data (MHz)		**Criteria**
N/A	Low Channel	1.200	PASS
	Middle Channel	1.197	PASS
	High Channel	1.200	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST

11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by PC which received 120V/60Hzpower by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.

2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

FOR TRADITIONAL BLUETOOTH

Line Conducted Emission Test Line 1-L



Site: Conduction
Phase: *L1*
Temperature: 23.6
Limit: FCC Class B Conduction(QP)
Power:
Humidity: 51.5 %
EUT: Bluetooth headset
M/N: AE01
Mode: Normal operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1580	45.79		26.61	10.17	55.96		36.78	65.56	55.56	-9.60	-18.78	P	
2	0.1780	42.34		22.40	10.19	52.53		32.59	64.57	54.57	-12.04	-21.98	P	
3	0.6740	29.12		19.31	10.34	39.46		29.65	56.00	46.00	-16.54	-16.35	P	
4	0.9100	32.07		12.96	10.41	42.48		23.37	56.00	46.00	-13.52	-22.63	P	
5	1.5660	26.76		15.04	10.36	37.12		25.40	56.00	46.00	-18.88	-20.60	P	
6	4.1220	26.02		11.01	10.38	36.40		21.39	56.00	46.00	-19.60	-24.61	P	

Line Conducted Emission Test Line 2-N



Site: Conduction
Phase: N
Temperature: 23.6
Limit: FCC Class B Conduction(QP)
Power:
Humidity: 51.5 %
EUT: Bluetooth headset
M/N: AE01
Mode: Normal operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1539	45.93		25.18	10.16	56.09		35.34	65.78	55.78	-9.69	-20.44	P	
2	0.4940	27.33		18.07	10.40	37.73		28.47	56.10	46.10	-18.37	-17.63	P	
3	0.6780	28.44		16.91	10.34	38.78		27.25	56.00	46.00	-17.22	-18.75	P	
4	0.8980	31.32		19.23	10.41	41.73		29.64	56.00	46.00	-14.27	-16.36	P	
5	4.2020	25.67		11.12	10.34	36.01		21.46	56.00	46.00	-19.99	-24.54	P	
6	25.4340	19.54		7.54	10.12	29.66		17.66	60.00	50.00	-30.34	-32.34	P	

FOR BLE

Line Conducted Emission Test Line 1-L



Site: Conduction | Phase: *L1* | Temperature: 23.6
Limit: FCC Class B Conduction(QP) | Power: | Humidity: 51.5 %
EUT: Bluetooth headset
M/N: AE01
Mode: Normal operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.1500	46.77		29.43	10.16	56.93		39.59	65.99	55.99	-9.06	-16.40	P	
2	0.6740	28.42		18.33	10.34	38.76		28.67	56.00	46.00	-17.24	-17.33	P	
3	0.9020	32.14		21.19	10.41	42.55		31.60	56.00	46.00	-13.45	-14.40	P	
4	1.7860	28.71		15.42	10.29	39.00		25.71	56.00	46.00	-17.00	-20.29	P	
5	4.4899	22.19		10.94	10.21	32.40		21.15	56.00	46.00	-23.60	-24.85	P	
6	17.2820	20.32		5.48	10.13	30.45		15.61	60.00	50.00	-29.55	-34.39	P	

Line Conducted Emission Test Line 2-N



Site: Conduction | Phase: *N* | Temperature: 23.6
Limit: FCC Class B Conduction(QP) | Power: | Humidity: 51.5 %
EUT: Bluetooth headset
M/N: AE01
Mode: Normal operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.2220	44.48		24.46	10.24	54.72		34.70	62.74	52.74	-8.02	-18.04	P	
2	0.3060	41.06		15.13	10.29	51.35		25.42	60.08	50.08	-8.73	-24.66	P	
3	0.7820	33.59		10.14	10.29	43.88		20.43	56.00	46.00	-12.12	-25.57	P	
4	2.3460	28.44		17.74	10.37	38.81		28.11	56.00	46.00	-17.19	-17.89	P	
5	4.1220	30.04		13.99	10.38	40.42		24.37	56.00	46.00	-15.58	-21.63	P	
6	24.5380	17.98		5.89	10.12	28.10		16.01	60.00	50.00	-31.90	-33.99	P	

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP

FCC RADIATED EMISSION TEST SETUP





APPENDIX B: PHOTOGRAPHS OF EUT

All VIEW OF EUT

TOP VIEW OF EUT

BOTTOM VIEW OF EUT

FRONT VIEW OF EUT



BACK VIEW OF EUT

LEFT VIEW OF EUT

RIGHT VIEW OF EUT

Port VIEW OF EUT



OPEN VIEW OF EUT-1



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



----END OF REPORT----