

Max Conducted Output PWR of various operation modes of SXP-1080

Protocol Reversion Number: 6

Radio Configuration	Service Option		Conducted Output Power(dBm)		
			Low Channel(1013) 824.70MHz	Mid Channel(384) 836.52MHz	High Channel(777) 848.31MHz
F1R1	SO2		23.6	24.0	23.3
	SO3		23.7	24.0	23.4
F2R2	SO9		23.6	24.0	23.3
	SO17		23.8	24.1	23.3
	SO32768		23.7	24.1	23.5
F3R3	SO2	9.6 Kbps	23.6	24.1	23.1
		19.2 Kbps	23.6	24.1	23.2
		38.4 Kbps	23.5	24.0	23.0
		76.8 Kbps	23.5	24.0	23.0
		153.6 Kbps	23.5	24.0	23.0
	SO3	9.6 Kbps	23.7	24.1	23.3
		19.2 Kbps	23.6	24.0	23.3
		38.4 Kbps	23.6	24.0	23.4
		76.8 Kbps	23.7	24.1	23.3
		153.6 Kbps	23.6	24.1	23.3
	SO32	9.6 Kbps	23.4	24.0	23.0
		19.2 Kbps	23.4	24.0	23.0
		38.4 Kbps	23.5	24.1	23.1
		76.8 Kbps	23.5	24.1	23.0
		153.6 Kbps	23.5	24.0	23.0

Protocol Reversion Number: 6

Max Conducted Output PWR of various operation modes of SXP-1080

(Continued..)

Radio Configuration	Service Option		Conducted Output Power(dBm)		
			Low Channel(1013) 824.70MHz	Mid Channel(384) 836.52MHz	High Channel(777) 848.31MHz
F4R3	SO3	9.6 Kbps	23.9	24.1	23.4
		19.2 Kbps	23.8	24.0	23.3
		38.4 Kbps	23.9	24.0	23.5
		76.8 Kbps	23.9	24.0	23.5
		153.6 Kbps	23.9	24.1	23.4
	SO32	9.6 Kbps	23.7	24.0	23.3
		19.2 Kbps	23.8	24.0	23.3
		38.4 Kbps	23.9	24.1	23.5
		76.8 Kbps	23.9	24.1	23.4
		153.6 Kbps	23.9	24.1	23.4
F5R4	SO17	14.4 Kbps	23.9	24.1	23.4
		28.8 Kbps	23.8	24.1	23.5
		57.6 Kbps	23.8	24.1	23.4
		115.2 Kbps	23.8	24.1	23.4
		230.4 Kbps	23.8	24.0	23.4
	SO32768	14.4 Kbps	23.8	24.0	23.2
		28.8 Kbps	23.8	24.0	23.2
		57.6 Kbps	23.8	24.1	23.3
		115.2 Kbps	23.8	24.1	23.4
		230.4 Kbps	23.9	24.1	23.4
SAR TEST MODE			24.1	24.3	24.0

Note : SAR tests were performed using test mode program and conducted output power of each channel was set equal or greater than the largest power of each channel of above table.