



ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR PCS PRIVATE LAND MOBILE LICENSED DATA TRANSCEIVER

Test report file number : E044R-040

Applicant : Hoseo Telnet Co., Ltd.

Address : 157-033, 680 Deungcheon3-Dong, Kangseo-Gu, Seoul Korea

Manufacturer : Hoseo Telnet Co., Ltd.

Address : 157-033, 680 Deungcheon3-Dong, Kangseo-Gu, Seoul Korea

Type of Equipment : ReFELX Two Way Data Device

FCC ID. : R2SHSD8000

Model Name : HSD8000

Serial number : None

Total page of Report : 29 pages (including this page)

Date of Incoming : March 10, 2004

Date of issue : April 20, 2004

SUMMARY

The equipment complies with the regulation; **FCC Part 24D and 90.**

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Prepared by: G. W. Lee
G. W. Lee/ Chief Engineer
EMC & Telecom Div.
ONETECH Corp.

Reviewed by: Y. K. Kwon
Y. K. Kwon/ Director
EMC & Telecom Div.
ONETECH Corp.



CONTENTS

	PAGE
1. VERIFICATION OF COMPLIANCE	4
2. TEST SUMMARY	5
2.1 TEST ITEMS AND RESULTS	5
2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS	5
2.3 RELATED SUBMITTAL(S) / GRANT(S)	5
2.4 PURPOSE OF THE TEST	5
2.5 TEST METHODOLOGY	5
2.6 TEST FACILITY	5
3. GENERAL INFORMATION	6
3.1 PRODUCT DESCRIPTION	6
3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.	6
4. EUT MODIFICATIONS	6
5. SYSTEM TEST CONFIGURATION	7
5.1 JUSTIFICATION	7
5.3 PERIPHERAL EQUIPMENT	7
5.4 MODE OF OPERATION DURING THE TEST	7
6. RF POWER OUTPUT AT ANTENNA TERMINAL	8
6.1 OPERATING ENVIRONMENT	8
6.2 TEST SET-UP	8
6.3 TEST EQUIPMENT USED	8
6.4 TEST DATA	9
8. OCCUPIED BANDWIDTH, BANDWIDTH LIMITATION, EMISSION MASKS	11
8.1 OPERATING ENVIRONMENT	11
8.2 TEST SET-UP	11
8.3 TEST EQUIPMENT USED	11
8.4 TEST DATA	12
9. SPURIOUS EMISSION AT ANTENNA TERMINAL	15
9.1 OPERATING ENVIRONMENT	15



9.2 TEST SET-UP FOR CONDUCTED MEASUREMENT	15
9.3 TEST EQUIPMENT USED	15
9.5. TEST DATA	16
11. FIELD STRENGTH OF SPURIOUS RADIATION	19
11.1 OPERATING ENVIRONMENT	19
11.2 TEST SET-UP	19
11.3 TEST EQUIPMENT USED	19
9.5.2. TEST DATA FOR RADIATED EMISSION	20
9.5.2.1. SPURIOUS & HARMONIC RADIATED EMISSION.....	20
12. FREQUENCY STABILITY WITH TEMPERATURE VARIATION	21
12.1 OPERATING ENVIRONMENT	21
12.2 TEST SET-UP	21
12.3 TEST EQUIPMENT USED	21
12.5 TEST DATA	22
13. FREQUENCY STABILITY WITH VOLTAGE VARIATION	23
13.1 OPERATING ENVIRONMENT	23
13.2 TEST SET-UP	23
13.3 TEST EQUIPMENT USED	23
13.5 TEST DATA	24
12. FIELD STRENGTH OF SPURIOUS RADIATED EMISSION IN RECEIVING MODE	25
12.1 OPERATING ENVIRONMENT	25
12.2 TEST SET-UP	25
12.3 TEST EQUIPMENT USED	25
12.5 TEST DATA	26
13. CONDUCTED EMISSION TEST	27
13.1 OPERATING ENVIRONMENT	27
13.2 TEST SET-UP	27
13.3 TEST EQUIPMENT USED	27
13.5 TEST DATA	28

**1. VERIFICATION OF COMPLIANCE**

APPLICANT : Hoseo Telnet Co., Ltd.
ADDRESS : 157-033, 680 Deungcheon3-Dong, Kangseo-Gu, Seoul Korea
CONTACT PERSON : C. H. Kim / Marketing & Sales Director
TELEPHONE NO : +82-2-2659-7345
FCC ID : R2SHSD8000
MODEL NO/NAME : HSD8000
SERIAL NUMBER : N/A
DATE : April 20, 2004

DEVICE TYPE	PCS Private Land Mobile Data Transceiver ReFELX Two Way Data Device
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	ANSI C63.4/2001
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	PART 24D and 90
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER(S) OPEN AREA TEST SITE

- This device has shown compliance with the conducted emissions limits in 15.207 adopted under FCC 02-107 (ET Docket 98-80). The device may be marketed after July 11, 2005 and is not affected by the 15.37(j) transition provisions.
- The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.



2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
2.1046, 24.132, 90.635	RF Power Output at Antenna Terminals	Met the Limit / PASS
2.1049, 24.131, 90.209(b), 90.210(j)	Occupied Bandwidth, Bandwidth Limitation, Emission Masks	Met the Limit / PASS
2.1051, 24.133, 90.210(j)	Spurious Emissions at Antenna Terminals	Met the Limit / PASS
2.1053, 24.133, 90.210(j)	Field strength of Spurious Radiation	Met the Limit / PASS
2.1055(a)(1), 24.135, 90.213	Frequency Stability with Temperature variation	Met the Limit / PASS
2.1055(d), 24.135, 90.213	Frequency stability with primary voltage variation	Met the Limit / PASS
15.109(b)	Field strength of Spurious Radiation in Receiving Mode	Met the Limit / PASS
15.207 and 15.107	Conducted Limits	Met the Limit / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in section 2.1.

2.5 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4/2001. Radiated testing was performed at a distance of 3 meters from EUT to the antenna.

2.6 Test Facility

The Electromagnetic compatibility measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Myeon, Gwangju-Si, Gyeonggi-Do 464-080 Korea. Description details of test facilities were submitted to the Federal Communications Commission on January 18, 2002 (Registration Number: 92819 and 340658), accredited by KOLAS (Korea Laboratory Accreditation Scheme, No: 85) and approved by TUV, DNV, SEMKO and MIC (Ministry of Information and Communications in Korea) according to the requirement of ISO17025.



3. GENERAL INFORMATION

3.1 Product Description

The Hoseo Telnet Co., Ltd., Model HSD800 (referred to as the EUT in this report) is a ReFELX Two Way Data Device, which is designed for user's convenient in sending or receiving a message through device or internet. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE		PCS Private Land Mobile Data Transceiver
TYPE OF EMISSION		10K0F1D
OPERATING FREQUENCY	Transmitting Frequency	896~902 MHz
	Receiving Frequency.	929MHz~942MHz
APPLICABLE FREQUENCY	PART 24	901~902 MHz
	PART 90	896~901 MHz
OUTPUT POWER		1 Watt
MODULATION		4 Level FSK
DATA TRANSFER RATE	Transmitter	800, 1600, 6800, 9400
	Receiver	1600, 6800, 9400
CHANNEL SPACING		12.5 kHz
USED CPU		32bit RISC Processor (14MIPS)
USED MEMORY	Flash Memory	512Kbytes
	Data Memory	256Kbytes
	Program Memory	256 Kbytes(Mask ROM or Flash Memory)
ANTENNA	Transmitter	Fixed Helical Antenna, Model No: HW-899-S
	Receiver	Loop Antenna
ANTENNA GAIN		-3dBi
LIST OF EACH OSC. ORCRY. FREQ.(FREQ.>=1MHz)		14.7456, 16.8, 20.945 MHz
NUMBER OF LAYER		Main Board: 6 Layers, Key Board: LCD Board:
POWER REQUIREMENT		DC 3.7V, 680mA from Li-Ion Battery or 4.2V, 450mA from AC/DC Adapter
EXTERNAL CONNECTOR		Battery Charger Port for AC/DC Adapter

3.2 Alternative type(s)/model(s); also covered by this test report.

No other model differences have been mentioned.

4. EUT MODIFICATIONS

None

It should not be reproduced except in full, without the written approval of ONETECH.

EMC-007(Rev.0)

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea
(TEL: 82-31-746-8500 FAX: 82-31-746-8700)

EMC Testing Dept : 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-860 Korea. (TEL: 82-31-765-8289 FAX: 82-31-766-2904)



5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	Hoseo Telnet Co., Ltd.	HSRMD40001	N/A
Key Board	Hoseo Telnet Co., Ltd.	HSRKD040101	N/A
LCD Board	Hoseo Telnet Co., Ltd.	HSRLM040201	N/A
RF MODULE	Hoseo Telnet Co., Ltd.	HSRM040301	N/A

5.3 Peripheral equipment

Defined as equipment needed for correct operation of the EUT, but not considered as tested:

Model	Manufacturer	FCC ID	Description	Connected to
HSD8000	Hoseo Telnet Co., Ltd.	R2SHSD8000	ReFELX Two Way Data Device (EUT)	Adapter
NC-P780A	AriTech Co., Ltd.	N/A	AC/DC Adapter	EUT

5.4 Mode of operation during the test

The EUT was continuously transmitted with max power at 800, 1600, 6800 and 9600 bps and the worst data was recorded in this test report.

6. RF POWER OUTPUT at ANTENNA TERMINAL


6.1 Operating environment

Temperature : 20°C

Relative humidity : 35 %

6.2 Test set-up

The RF output port of the EUT was connected to the input of the spectrum analyzer through sufficient attenuation. The resolution bandwidth was set to 2 MHz and video bandwidth of the spectrum analyzer was set at 3 MHz and the spectrum as recorded in the frequency band ± 5 MHz from the carrier frequency.



6.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number
■ -	8564E	HP	Spectrum Analyzer	3650A00756
■ -	N/A	HP	30dB Attenuator Assembly	2350A3133
■ -	3033B	B&J TMI	DC Power Supply	2056036

All test equipment used is calibrated on a regular basis.



6.4 Test data

- Test Date : April 15, 2004
- Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LOSS (dB)	TOTAL (dBm)	RESULT (W)
Low	896	31.67	0.1	31.77	1.50
High	902	31.67	0.1	31.77	1.50

Remark: See next page for an overview sweep performed with peak detector and spectrum analyzer offset function was used for attenuator.

Tested by: Dan-Gi Lee / Project Engineer



Low Channel



High Channel

8. OCCUPIED BANDWIDTH, BANDWIDTH LIMITATION, EMISSION MASKS


8.1 Operating environment

Temperature : 20°C

Relative humidity : 35 %

8.2 Test set-up

The RF output port of the EUT was connected to the input of the spectrum analyzer through sufficient attenuation. The resolution bandwidth and video bandwidth of the spectrum analyzer was set at 300 Hz for emission mask, 1 kHz for 99% occupied bandwidth and the spectrum was recorded in the frequency band ± 25 kHz from the carrier frequency.



8.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number
■ - 8564E	HP	Spectrum Analyzer	3650A00756
■ - N/A	HP	30dB Attenuator Assembly	2350A3133
■ - 3033B	B&J TMI	DC Power Supply	2056036

All test equipment used is calibrated on a regular basis.





8.4 Test data

- Test Date : April 15, 2004
- Test Result : Pass


CHANNEL	FREQUENCY(MHz)	MEASURED VLAUE (kHz)	LIMIT (kHz)	MARGIN (kHz)
Low	896	7.583	10.0 kHz for Part 24	-2.417
High	902	7.583	13.6 kHz for Part 90	

Tested by: Dan-Gi Lee / Project Engineer





Low Channel according to Part 90



High Channel according to Part 24D



9. SPURIOUS EMISSION AT ANTENNA TERMINAL


9.1 Operating environment

Temperature : 19°C

Relative humidity : 35 %

9.2 Test set-up for conducted measurement

The RF output port of the EUT was connected to the input of the spectrum analyzer through sufficient attenuation. The resolution bandwidth and video bandwidth of the spectrum analyzer was set at 100 kHz and sufficient scans were taken to show any out of band emissions up to 10 GHz.



9.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number
■ -	8564E	HP	Spectrum Analyzer	3650A00756
■ -	N/A	HP	30dB Attenuator Assembly	2350A3133
■ -	3033B	B&J TMI	DC Power Supply	2056036

All test equipment used is calibrated on a regular basis.


**9.5. Test data**

- Test Date : April 15, 2004
- Frequency range : 30 MHz ~ 10 GHz
- Result : PASSED BY -9.00 dB at High Channel


Carrier Freq. (MHz)	Harmonic Freq. (MHz)	Measured Value (dBm)	Cable Loss (dB)	TOTAL (dBm)	Limit (dBm)	Margin (dB)
896.0	1792	-21.70	0.2	-21.50	-12.0	-9.50
	2688	-34.30	0.3	-34.30		-22.30
	3580	-37.30	0.7	-36.60		-24.60
	4472	-30.80	1.2	-29.60		-17.60
	5364	-39.50	1.8	-37.70		-25.70
902.0	1804	-21.20	0.2	-21.00	-12.0	-9.00
	2706	-32.80	0.3	-32.50		-20.50
	3608	-37.00	0.7	-36.30		-24.30
	4510	-30.80	1.3	-29.50		-17.50
	5412	-38.80	1.8	-37.00		-25.00

According to Part 24D, out of band emission shall be attenuated by $43 + 10 \log (P)$ dBc, equates to -12.0dBm.


Tested by: Dan-Gi Lee / Project Engineer



Low Channel



Low Channel



High Channel



High Channel



11. FIELD STRENGTH OF SPURIOUS RADIATION

11.1 Operating environment

Temperature : 26°C

Relative humidity : 43 %

11.2 Test set-up

The radiated emissions measurements were on the 3 meters, open-field test site. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30MHz to up to 10th harmonic of the fundamental frequency was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 and 4.0 meters in order to determine the maximum emission levels. The test was performed by placing the EUT on 3-orthogonal axis. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

11.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number
■ - ESVS10	Rohde & Schwarz	EMI Test Receiver	827864/005
■ - 85650A	Hewlett Packard	Quasi-Peak Adapter	3107A01542
■ - 8568B	Hewlett-Packard	Spectrum Analyzer	3109A05456
■ - 85685A	Hewlett-Packard	RF Preselector	3107A01264
■ - 8564E	Hewlett-Packard	Spectrum Analyzer	3650A00756
■ - 8449B	Hewlett-Packard	Preamplifier	3008A00833
□ - 83051A	Agilent	Preamplifier	3950M00201
■ - BBHA9170	Schwarzbeck	Horn Antenna	BBHA9170178
□ - 8449B	Hewlett-Packard	RF Amplifier	3008A00833
□ - 8447F	HP	RF Amplifier	3113A04554
■ - 1070-1	EMCO	Antenna Master	9109-1624
■ - MA220	HD	Turn Table	N/A
■ - HD240	HD	Antenna Mast	N/A
■ - 3104C	EMCO	Biconical Antenna	9109-4441
■ - 3146	EMCO	Log Periodic Antenna	9109-3214
■ - YSE 500B	YoungShin Eng.	Frequency Converter	950413001
■ - ETCR-10	DaeHa	Automatic Voltage Com.	N/A

All test equipment used is calibrated on a regular basis.

**9.5.2. Test data for radiated emission****9.5.2.1. Spurious & Harmonic Radiated Emission**

- Test Date : April 16, 2004
- Resolution bandwidth : 1 MHz for Peak and Average Mode
- Video bandwidth : 1 MHz for Peak Mode, 10Hz for Average Mode
- Frequency range : 1 GHz ~ 10 GHz
- Measurement distance : 3m
- Result : PASSED BY -5.67 dB at Low Channel

Frequency (MHz)	Spectrum Reading (dBuV)	Generator Reading (dBm)	Ant. Gain (dBi)	Ant. Pol. (H/V)	Dipole Gain (dB)	Cable Loss (dB)	Total (dBm)	Limit (dBm)	Margin (dB)
Test Data for Low Channel, 896.0 MHz									
896.0	99.30	26.20		H	0	0.2	26.00		
896.0	92.70	19.80		V	0	0.2	19.60		
1792.0	50.50	-23.20	8.18	H	2.15	0.5	-17.67	-12.0	-5.67
1792.0	46.80	-26.40	8.18	V	2.15	0.5	-20.87	-12.0	-7.13
2688.0	41.20	-30.30	8.78	H	2.15	0.8	-24.47	-12.0	-12.47
2688.0	34.70	-40.50	8.78	V	2.15	0.8	-34.67	-12.0	-22.67
Test Data for High Channel, 902 MHz									
902.0	99.00	25.60		H	0	0.2	25.40		
902.0	92.30	19.30		V	0	0.2	19.10		
1804.0	50.70	-24.10	8.20	H	2.15	0.5	-18.55	-12.0	-6.55
1804.0	46.70	-28.30	8.20	V	2.15	0.5	-22.75	-12.0	-10.75
2706.0	41.10	-29.10	8.82	H	2.15	0.8	-23.23	-12.0	-11.23
2706.0	34.50	-40.90	8.82	V	2.15	0.8	-35.03	-12.0	-23.03

Tabulated test data for Restricted Band

Remark: "H": Horizontal, "V": Vertical,

Tested by: Dan-Gi Lee / Project Engineer

12. FREQUENCY STABILITY WITH TEMPERATURE VARIATION

12.1 Operating environment

Temperature : 14°C

Relative humidity : 39 %

12.2 Test set-up

The EUT was connected to an external DC power supply and the RF output port of the EUT was connected to a frequency counter via feed-through attenuators. The EUT was placed inside of the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

Turn EUT off and set chamber temperature to -30°C and then allow sufficient time (approximately 20 to 30 minutes after chamber reach the assigned temperature) for EUT to stabilize. Turn ON EUT and measure the EUT operating frequency and then turn off the EUT after the measurement.

Repeat above method emission measurements at +50°C and then record all measured frequencies on each temperature step.

12.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number
■ -	8564E	HP	Spectrum Analyzer	3650A00756
■ -	53152A	HP	Frequency Counter	US39270295
■ -	N/A	HP	30 dB Attenuator Assembly	2350A03133
■ -	3033B	B&J TMI	DC Power Supply	2056036
■ -	EY-101	Tabai ESPEC Corp.	Chamber	5104390

All test equipment used is calibrated on a regular basis.

**12.5 Test data**

- Test Date : April 15, 2004
- Operating Condition : 800/1600/6400/9200 bps was transmitted.
- Result : PASSED BY -0.64PPM at 20°C on 896MHz

Temperature (°C)	Center Freq. (Hz)	Measured Freq.(Hz)	Result (PPM)	Limit
-30	896000000	896000277	0.30915179	1 PPM
-20		896000296	0.33035714	
-10		896000537	0.59933036	
0		896000326	0.36383929	
10		896000338	0.37723214	
20		896000571	0.63727679	
30		896000158	0.17633929	
40		896000036	0.04017857	
50		896000033	0.03683036	
-30	902000000	902000148	0.16407982	1 PPM
-20		902000440	0.48780488	
-10		902000207	0.22949002	
0		902000248	0.27494457	
10		902000250	0.27716186	
20		902000391	0.43348115	
30		902000086	0.09534368	
40		901999936	-0.0709534	
50		902000056	0.06208426	

Tested by: Dan-Gi Lee / Project Engineer



13. FREQUENCY STABILITY WITH VOLTAGE VARIATION

13.1 Operating environment

Temperature : 20°C

Relative humidity : 34 %

13.2 Test set-up

An external variable DC power supply was connected to the battery terminals of the EUT. The voltage of EUT set to 115% of the nominal value and was then decreased until the EUT light no longer illuminated; i.e., the battery end point. The output frequency was recorded for each battery voltage.

13.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number
■ - 8564E	HP	Spectrum Analyzer	3650A00756
■ - 53152A	HP	Frequency Counter	US39270295
■ - N/A	HP	30 dB Attenuator Assembly	2350A03133
■ - 3033B	B&J TMI	DC Power Supply	2056036

All test equipment used is calibrated on a regular basis.



13.5 Test data

- Test Date : April 15, 2004
- Rated Supply Voltage : 3.7 Vdc
- Result : PASSED BY 0.3 PPM at 3.15Vdc on 902 MHz

Voltage (Vdc)	Carrier Freq. (Hz)	Measured Freq. (Hz)	Result (PPM)	Limit
3.15	896000000	896000071	0.07924107	1 PPM
4.23		896000045	0.05022321	
3.15	902000000	902000272	0.30155211	1 PPM
4.23		902000200	0.22172949	

Tested by: Dan-Gi Lee / Project Engineer

12. FIELD STRENGTH OF SPURIOUS RADIATED EMISSION IN RECEIVING MODE

12.1 Operating environment

Temperature : 14°C

Relative humidity : 39 %

12.2 Test set-up

The radiated emissions measurements were on the 3 meters, open-field test site. The EUT and other support equipment were placed on a non-conductive turntable above the ground plane. The interconnecting cables from outside test site were inserted into ferrite clamps at the point where the cables reach the turntable.

The frequency spectrum from 30MHz to 1000MHz was scanned and emission levels maximized at each frequency recorded. The system was rotated 360°, and the antenna was varied in height between 1.0 and 4.0 meters in order to determine the maximum emission levels. This procedure was performed for both horizontal and vertical polarization of the receiving antenna.

12.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number
■ - ESVS10	Rohde & Schwarz	EMI Test Receiver	827864/005
■ - 85650A	Hewlett Packard	Quasi-Peak Adapter	3107A01542
■ - 8568B	Hewlett-Packard	Spectrum Analyzer	3109A05456
■ - 85685A	Hewlett-Packard	RF Preselector	3107A01264
□ - 8449B	Hewlett-Packard	RF Amplifier	3008A00833
□ - 8447F	HP	RF Amplifier	3113A04554
■ - 1070-1	EMCO	Antenna Master	9109-1624
■ - MA220	HD	Turn Table	N/A
■ - HD240	HD	Antenna Mast	N/A
■ - 3104C	EMCO	Biconical Antenna	9109-4441
■ - 3146	EMCO	Log Periodic Antenna	9109-3214
■ - YSE 500B	YoungShin Eng.	Frequency Converter	950413001
■ - ETCR-10	DaeHa	Automatic Voltage Com.	N/A

All test equipment used is calibrated on a regular basis.

**12.5 Test data**

- Test Date : April 16, 2004
- Resolution bandwidth : 120 kHz
- Frequency range : 30MHz ~ 2.0GHz
- Measurement distance : 3m
- Operating Condition : Receiving mode at Low and High Channel

Frequency (MHz)	Reading (dBuV)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Emission Level(dBuV/m)	Limits (dBuV/m)	Margin (dB)
It was not observed any emission from the EUT up to 2.0GHz.							

Tabulated test data for Radiated Electromagnetic Field

Remark: "H": Horizontal, "V": Vertical

Tested by: Dan-Gi Lee / Project Engineer



13. CONDUCTED EMISSION TEST

13.1 Operating environment

Temperature : 20°C

Relative humidity : 34 %

13.2 Test set-up

The conducted emission measurements of power line were performed in a shielded room. The EUT was placed on a wooden table, 0.8 meters height above the floor. Power was fed to the EUT through a 50 ohm/ 50 microhenry Line Impedance Stabilization Network (LISN). The ground plane was electrically bonded to the shield room ground system and all power lines entering the shield room were filtered.

13.3 Test equipment used

Model Number	Manufacturer	Description	Serial Number
■ - ESHS10	Rohde & Schwarz	EMI Test Receiver	834467/007
■ - 3825/2	EMCO	AMN	9109-1869
■ - N/A	HanKook Shield room	Shield Room	N/A
■ - YSE 500B	YoungShin Eng.	Frequency Converter	950413001
■ - ETCR-10	DaeHa	Automatic Voltage Com.	N/A

All test equipment used is calibrated on a regular basis.

**13.5 Test data**

- Test Date : April 16, 2004
- Resolution bandwidth : 9 kHz
- Frequency range : 0.15MHz ~ 30MHz
- Result : PASSED BY -11.94 dB at 2.12 MHz with Peak Detector

Frequency (MHz)	Line	Quasi-Peak (dBuV)			Margin (dB)	Average (dBuV)		Margin (dB)
		Emission level	Detector Mode	Limits		Emission level	Limits	
0.46	H	41.48	P	56.78	-15.30			
0.86	H	41.97	P	56.00	-14.03			
1.15	H	42.54	P	56.00	-13.46			
1.43	H	41.53	P	56.00	-14.47			
1.89	N	41.57	P	56.00	-14.43			
2.12	H	44.06	P	56.00	-11.94			

Line Conducted Emissions Tabulated Data

Remark : "H": Hot Line, "N": Neutral line, "P": Peak detect.

Average mode was not recorded, because peak values were under the average limit.

See next page for an overview sweep performed with peak and average detector.

Tested by: Dan-Gi Lee / Project Engineer

