TEST REPORT

No.I19N00846-HAC RF

For

Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd

Smartphone

Model Name: cp3648A

With

Hardware Version: P1

Software Version: 9.0.002.P1.190609.cp3648A

FCC ID: R38YLCP3648A

Results Summary: M Category = M4

Issued Date: 2019-07-05

Designation Number: CN1210

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of SAICT.

Test Laboratory:

Shenzhen Academy of Information and Communications Technology

Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China 518026.

Tel: +86(0)755-33322000, Fax: +86(0)755-33322001

Email: yewu@caict.ac.cn, website: www.cszit.com

©Copyright. All rights reserved by SAICT.

REPORT HISTORY

Report Number	Revision	Issue Date	Description
I19N00846-HAC RF	Rev.0	2019-07-05	Initial creation of test report

©Copyright. All rights reserved by SAICT.

TABLE OF CONTENT

1 TEST LABORATORY 4

1.1 TESTING LOCATION 4
1.2 TESTING ENVIRONMENT 4
1.3 PROJECT DATA 4
1.4 SIGNATURE 4

2 CLIENT INFORMATION 5

2.1 APPLICANT INFORMATION 5
2.2 MANUFACTURER INFORMATION 5

3 EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE) 6

3.1 ABOUT EUT 6
3.2 INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST 6
3.3 INTERNAL IDENTIFICATION OF AE USED DURING THE TEST 6
3.4 AIR INTERFACES / BANDS INDICATING OPERATING MODES 6

4. REFERENCE DOCUMENTS 7

5 OPERATIONAL CONDITIONS DURING TEST 8

5.1 HAC MEASUREMENT SET-UP 8
5.2 PROBE SPECIFICATION 9
5.3 TEST ARCH PHANTOM & PHONE POSITIONER 10
4.4 ROBOTIC SYSTEM SPECIFICATIONS 10

6 EUT ARRANGEMENT 11

6.1 WD RF EMISSION MEASUREMENTS REFERENCE AND PLANE 11

7 SYSTEM VALIDATION 12

7.1 VALIDATION PROCEDURE 12
7.2 VALIDATION RESULT 12

8 MODULATION INTERFERENCE FACTOR (MIF) 13

9 EVALUATION FOR LOW-POWER EXEMPTION 15

9.1 PRODUCT TESTING THRESHOLD 15
9.2 CONDUCTED POWER 16

10 RF TEST PROCEDURES 17

11 MEASUREMENT RESULTS (E-FIELD) 18

12 ANSI C 63.19-2011 LIMITS 19

13 MEASUREMENT UNCERTAINTY 20

14 MAIN TEST INSTRUMENTS 21

ANNEX A RF EMISSION TEST PLOT 22

ANNEX B SYSTEM VALIDATION RESULT 42

ANNEX C PROBE CALIBRATION CERTIFICATE 45

ANNEX D DIPOLE CALIBRATION CERTIFICATE 55

ANNEX E UID SPECIFICATION 70

©Copyright. All rights reserved by SAICT.

1 Test Laboratory

1.1 Testing Location

Company Name:	Shenzhen Academy of Information and Communications Technology
Address:	Building G, Shenzhen International Innovation Center, No.1006 Shennan Road, Futian District, Shenzhen, Guangdong, P. R. China
Postal Code:	518026
Telephone:	+86-755-33322000
Fax:	+86-755-33322001

1.2 Testing Environment

Temperature:	18°C ~ 25°C
Relative humidity:	30% ~ 70%
Ground system resistance:	<4Ω
Ambient noise & Reflection:	< 0.012 W/kg

1.3 Project Data

Testing Start Date:	June 09, 2019
Testing End Date:	June 10, 2019

1.4 Signature

李勇富

Li Yongfu

(Prepared this test report)

张运转

Zhang Yunzhuan

(Reviewed this test report)

曹俊飞

Cao Junfei

Deputy Director of the laboratory

(Approved this test report)

©Copyright. All rights reserved by SAICT.

2 Client Information

2.1 Applicant Information

Company Name:	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address /Post:	Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
Contact:	Yentl Chen
Email:	chenyanting@yulong.com
Telephone:	+86 15927320221
Fax:	/

2.2 Manufacturer Information

Company Name:	Yulong Computer Telecommunication Scientific (Shenzhen) Co., Ltd
Address /Post:	Building B, Boton Science Park, Chaguang Road, Xili Town, Nanshan District, Shenzhen
Contact:	Yentl Chen
Email:	chenyanting@yulong.com
Telephone:	+86 15927320221
Fax:	/

©Copyright. All rights reserved by SAICT.

3 Equipment under Test (EUT) and Ancillary Equipment (AE)

3.1 About EUT

Description:	Smartphone
Model name:	cp3648A
Operating mode(s):	GSM 850/1900, CDMA BC0/BC1/BC10, WCDMA Band 2/4/5 LTE Band 2/4/5/12/13/25/26/41/66/71, BT, Wi-Fi 2.4G

3.2 Internal Identification of EUT used during the test

EUT ID*	IMEI	HW Version	SW Version
EUT1	990013500004564	P1	9.0.002.P1.190609.cp3648A
EUT2	990013500004549	P1	9.0.002.P1.190609.cp3648A

*EUT ID: is used to identify the test sample in the lab internally.

Note: It is performed to test HAC with the EUT 1 & 2.

3.3 Internal Identification of AE used during the test

AE ID*	Description	Type	Manufacturer
AE1	Battery	Li-ion Polymer	Tianjin Lishen
AE2	Battery	Li-ion Polymer	Zhuhai Coslight

*AE ID: is used to identify the test sample in the lab internally.

3.4 Air Interfaces / Bands Indicating Operating Modes

Air-interface	Band(MHz)	Type	C63.19 / tested	Simultaneous Transmissions	Name of Voice Service	Power Reduction
GSM	850 /1900	VO	Yes	BT,WLAN	CMRS Voice	No
EDGE	850 /1900	DT	Yes	BT,WLAN	Google Duo	
WCDMA	B2 / B4/ B5	VO	Yes	BT,WLAN	CMRS Voice	No
	HSPA	DT	Yes	BT,WLAN	Google Duo	
CDMA	BC0 / BC1 / BC10	VO	Yes	BT,WLAN	CMRS Voice	No
	1XRTT / EVDO	DT	Yes	BT,WLAN	Google Duo	
LTE (FDD)	2/4/5/12/13/ 25/26/66/71	DT	Yes	BT,WLAN	Google Duo	No
LTE (TDD)	41	DT	Yes	BT,WLAN	Google Duo	
WLAN	2.4G	DT	Yes	WWAN	Google Duo	No
BT	2.4G	DT	No	WWAN	NA	No

VO: Voice CMRS/PSTN Service Only

VD: Voice CMRS/PSTN and Data Service

DT: Digital Transport

* HAC Rating was not based on concurrent voice and data modes; Non-current mode was found to represent worst case rating for both M and T rating

©Copyright. All rights reserved by SAICT.

4. Reference Documents

The following document listed in this section is referred for testing.

Reference	Title	Version
ANSI C63.19-2011	American National Standard for Methods of Measurement of Compatibility between Wireless Communication Devices and Hearing Aids	2011
KDB 285076 D01	Equipment Authorization Guidance for Hearing Aid Compatibility	v05

©Copyright. All rights reserved by SAICT.

5 Operational Conditions During Test

5.1 HAC Measurement Set-up

These measurements are performed using the DASY5 NEO automated dosimetric assessment system. It is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland. It consists of high precision robotics system (Stäubli), robot controller, Intel Core2 computer, near-field probe, probe alignment sensor. The robot is a six-axis industrial robot performing precise movements. A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and remote control, is used to drive the robot motors. The PC consists of the HP Intel Core2 1.86 GHz computer with Windows XP system and HAC Measurement Software DASY5 NEO, A/D interface card, monitor, mouse, and keyboard. The Stäubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.



Fig. 1 HAC Test Measurement Set-up

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

©Copyright. All rights reserved by SAICT.

5.2 Probe Specification

E-Field Probe Description



[ER3DV6]

Construction	One dipole parallel, two dipoles normal to probe axis Built-in shielding against static charges PEEK enclosure material
Calibration	In air from 100 MHz to 3.0 GHz (absolute accuracy ±6.0%, k=2)
Frequency	40 MHz to > 6 GHz (can be extended to < 20 MHz) Linearity: ± 0.2 dB (100 MHz to 3 GHz)
Directivity	± 0.2 dB in air (rotation around probe axis) ± 0.4 dB in air (rotation normal to probe axis)
Dynamic Range	2 V/m to > 1000 V/m; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm (Tip: 16 mm) Tip diameter: 8 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.5 mm
Application	General near-field measurements up to 6 GHz Field component measurements Fast automatic scanning in phantoms

©Copyright. All rights reserved by SAICT.

5.3 Test Arch Phantom & Phone Positioner

The Test Arch phantom should be positioned horizontally on a stable surface. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. It enables easy and well defined positioning of the phone and validation dipoles as well as simple teaching of the robot (Dimensions: 370 x 370 x 370 mm).

The Phone Positioner supports accurate and reliable positioning of any phone with effect on near field <±0.5 dB.



Fig. 2 HAC Phantom & Device Holder

4.4 Robotic System Specifications

Specifications

Positioner: Stäubli Unimation Corp. Robot Model: RX160XL
Repeatability: ±0.02 mm
No. of Axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller
Processor: Intel Core2
Clock Speed: 1.86 GHz
Operating System: Windows XP
Data Converter
Features: Signal Amplifier, multiplexer, A/D converter, and control logic
Software: DASY5 software
Connecting Lines: Optical downlink for data and status info.
Optical uplink for commands and clock

©Copyright. All rights reserved by SAICT.

6 EUT Arrangement

6.1 WD RF Emission Measurements Reference and Plane

Figure 4 illustrates the references and reference plane that shall be used in the WD emissions measurement.

• The grid is 5 cm by 5 cm area that is divided into 9 evenly sized blocks or sub-grids.

• The grid is centered on the audio frequency output transducer of the WD (speaker or T-coil).

• The grid is located by reference to a reference plane. This reference plane is the planar area that contains the highest point in the area of the WD that normally rests against the user's ear

• The measurement plane is located parallel to the reference plane and 15 mm from it, out from the phone. The grid is located in the measurement plane.



Fig. 3 WD reference and plane for RF emission measurements

©Copyright. All rights reserved by SAICT.

7 System Validation

7.1 Validation Procedure

Place a dipole antenna meeting the requirements given in ANSI C63.19 in the position normally occupied by the WD. The dipole antenna serves as a known source for an electrical output. Position the E-field probes so that:

• The probes and their cables are parallel to the coaxial feed of the dipole antenna

• The probe cables and the coaxial feed of the dipole antenna approach the measurement area from opposite directions

• The center point of the probe element(s) are 15 mm from the closest surface of the dipole elements.



Fig. 4 Dipole Validation Setup

7.2 Validation Result

E-Field Scan						
Mode	**Frequency (MHz)**	**Input Power (mW)**	**Measured[1] Value(dBV/m)**	**Target[2] Value(dBV/m)**	**Deviation[3] (%)**	**Limit[4] (%)**
CW	835	100	42.28	40.72	3.8	±25
CW	1880	100	39.64	39.06	1.5	±25
CW	2600	100	39.53	38.71	2.1	±25

Notes:

1. Please refer to the attachment for detailed measurement data and plot.
2. Target value is provided by SPEAD in the calibration certificate of specific dipoles.
3. Deviation (%) = 100 * (Measured value minus Target value) divided by Target value.
4. ANSI C63.19 requires values within ± 25% are acceptable, of which 12% is deviation and 13% is measurement uncertainty. Values independently validated for the dipole actually used in the measurements should be used, when available.

©Copyright. All rights reserved by SAICT.

8 Modulation Interference Factor (MIF)

The HAC Standard ANSI C63.19-2011 defines a new scaling using the Modulation Interference Factor (MIF) which replaces the need for the Articulation Weighting Factor (AWF) during the evaluation and is applicable to any modulation scheme.

The Modulation Interference factor (MIF, in dB) is added to the measured average E-field (in dBV/m) and converts it to the RF Audio Interference level (in dBV/m). This level considers the audible amplitude modulation components in the RF E-field. CW fields without amplitude modulation are assumed to not interfere with the hearing aid electronics. Modulations without time slots and low fluctuations at low frequencies have low MIF values, TDMA modulations with narrow transmission and repetition rates of few 100 Hz have high MIF values and give similar classifications as ANSI C63-2007.

Definitions

ER3D, E-field probes have a bandwidth <10 kHz and can therefore not evaluate the RF envelope in the full audio band. DASY52 is therefore using the “indirect” measurement method according to ANSI C63.19-2011 which is the primary method. These near field probes read the averaged E-field measurement. Especially for the new high peak-to-average (PAR) signal types, the probes shall be linearized by probe modulation response (PMR) calibration in order to not overestimate the field reading.

The evaluation method or the MIF is defined in ANSI C63.19-2011 section D.7. An RMS demodulated RF signal is fed to a spectral filter (similar to an A weighting filter) and forwarded to a temporal filter acting as a quasi-peak detector. The averaged output of these filtering is called to a 1 kHz 80% AM signal as reference. MIF measurement requires additional instrumentation and is not well suited for evaluation by the end user with reasonable uncertainty It may alternatively be determined through analysis and simulation, because it is constraint and characteristic for a communication signal. DASY52 uses well defined signals for PMR calibration. The MIF of these signals has been determined by simulation and is automatically applied.

MIF values were not tested by a probe or as specified in the standards but are based on analysis provided by SPEAG for all the air interfaces (GSM, WCDMA, CDMA, LTE). The data included in this report are for the worst case operating modes. The UIDs used are listed below:

©Copyright. All rights reserved by SAICT.

UID	Communication System Name	MIF (dB)
10021	GSM-FDD (TDMA, GMSK)	3.63
10025	EDGE-FDD (TDMA, 8PSK, TN 0)	3.75
10011	UMTS-FDD (WCDMA)	-27.23
10225	UMTS-FDD (HSPA+)	-20.39
10295	CDMA2000 (RC1, SO3, 1/8th Rate 25 fr.)	3.26
10403	CDMA2000 (1xEV-DO, Rev. 0)	-17.67
10170	LTE-FDD(SC-FDMA, 1RB, 20MHz, 16-QAM)	-9.76
10176	LTE-FDD(SC-FDMA, 1RB, 10MHz, 16-QAM)	-9.76
10173	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16QAM)	-1.44
10061	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02

A PMR calibrated probe is linearized for the selected waveform over the full dynamic range within the uncertainty specified in its calibration certificate. ER3D, EF3D and EU2D E-field probes have a bandwidth <10 kHz and can therefore not evaluate the RF envelope in the full audio band. DASY52 is therefore using the \indirect" measurement method according to ANSI C63.19-2011 which is the primary method. These near field probes read the averaged E-field measurement. Especially for the new high peak-to-average (PAR) signal types, the probes shall be linearized by PMR calibration in order to not overestimate the field reading.

The MIF measurement uncertainty is estimated as follows, for modulation frequencies from slotted waveforms with fundamental frequency and at least 2 harmonics within 10 kHz:

0.2 dB for MIF -7 to +5 dB,
0.5 dB for MIF -13 to +11 dB
1 dB for MIF > -20 dB

©Copyright. All rights reserved by SAICT.

9 Evaluation for low-power exemption

9.1 Product testing threshold

There are two methods for exempting an RF air interface technology from testing. The first method requires evaluation of the MIF for the worst-case operating mode. An RF air interface technology of a device is exempt from testing when its average antenna input power plus its MIF is ≤17 dBm for any of its operating modes. The second method does not require determination of the MIF. The RF emissions testing exemption shall be applied to an RF air interface technology in a device whose peak antenna input power, averaged over intervals ≤50 μs20, is ≤23 dBm. An RF air interface technology that is exempted from testing by either method shall be rated as M4.
The first method is used to be exempt from testing for the RF air interface technology in this report.

©Copyright. All rights reserved by SAICT.

9.2 Conducted power

Band	power (dBm)	MIF (dB)	Sum (dBm)	HAC Test
GSM 850	34.5	3.63	38.13	Yes
EGPRS 850	27.5	3.75	31.25	Yes
GSM 1900	32.0	3.63	35.63	Yes
EGPRS 1900	26.5	3.75	30.25	Yes
CDMA BC0	24.5	3.26	27.76	Yes
CDMA BC0 -EVDO	24.5	-17.67	6.83	No
CDMA BC1	24.0	3.26	27.26	Yes
CDMA BC1 -EVDO	24.0	-17.67	6.33	No
CDMA BC10	24.5	3.26	27.76	Yes
CDMA BC10 -EVDO	24.5	-17.67	6.83	No
WCDMA B2	24.5	-27.23	-2.73	No
WCDMA B2 -HSPA	23.5	-20.39	3.11	No
WCDMA B4	24.5	-27.23	-2.73	No
WCDMA B4 -HSPA	23.5	-20.39	3.11	No
WCDMA B5	24.5	-27.23	-2.73	No
WCDMA B5 -HSPA	23.5	-20.39	3.11	No
LTE Band 2	23.5	-9.76	13.74	No
LTE Band 4	24.5	-9.76	14.74	No
LTE Band 5	24.0	-9.76	14.24	No
LTE Band 12	24.0	-9.76	14.24	No
LTE Band 13	24.0	-9.76	14.24	No
LTE Band 25	23.5	-9.76	13.74	No
LTE Band 26	24.0	-9.76	14.24	No
LTE Band 41	24.0	-1.44	22.56	Yes
LTE Band 66	24.5	-9.76	14.74	No
LTE Band 71	24.0	-9.76	14.24	No
WIFI 2.4G	16.0	-2.02	13.98	No

Note:

1. Power = Max turn-up limit.
2. EGPRS data modes are not necessary due the GSM Voice mode is the worst case.

©Copyright. All rights reserved by SAICT.

10 RF Test Procedures

The evaluation was performed with the following procedure:

1) Confirm proper operation of the field probe, probe measurement system and other instrumentation and the positioning system.

2) Position the WD in its intended test position. The gauge block can simplify this positioning.

3) Configure the WD normal operation for maximum rated RF output power, at the desired channel and other operating parameters (e.g., test mode), as intended for the test.

4) The center sub-grid shall centered on the center of the T-Coil mode axial measurement point or the acoustic output, as appropriate. Locate the field probe at the initial test position in the 50 mm by 50 mm grid, which is contained in the measurement plane. If the field alignment method is used, align the probe for maximum field reception.

5) Record the reading.

6) Scan the entire 50 mm by 50 mm region in equally spaced increments and record the reading at each measurement point. The distance between measurement points shall be sufficient to assure the identification of the maximum reading.

7) Identify the five contiguous sub-grids around the center sub-grid whose maximum reading is the lowest of all available choices. This eliminates the three sub-grids with the maximum readings. Thus, the six areas to be used to determine the WD's highest emissions are identified.

8) Identify the maximum field reading within the non-excluded sub-grids identified in Step 7)

9) Evaluate the MIF and add to the maximum steady-state rms field-strength reading to obtain the RF audio interference level..

10) Compare this RF audio interference level with the categories and record the resulting WD category rating.

©Copyright. All rights reserved by SAICT.

11 Measurement Results (E-Field)

Frequency		Measured Value	Power Drift	Category
MHz	Channel	(dBV/m)	(dB)	
GSM 850				
848.8	251	27.48	-0.03	**M4** (see Fig A.1)
836.6	190	27.96	-0.06	**M4** (see Fig A.2)
824.2	128	27.75	-0.04	**M4** (see Fig A.3)
GSM 1900				
1909.8	810	18.71	0.02	**M4** (see Fig A.4)
1880	661	18.93	0.08	**M4** (see Fig A.5)
1850.2	512	19.48	0.03	**M4** (see Fig A.6)
CDMA BC0				
848.31	777	26.02	-0.01	**M4** (see Fig A.7)
836.52	384	26.24	-0.03	**M4** (see Fig A.8)
824.70	1013	26.37	-0.07	**M4** (see Fig A.9)
CDMA BC1				
1908.75	1175	18.34	0.01	**M4** (see Fig A.10)
1880	600	19.78	0.04	**M4** (see Fig A.11)
1851.25	25	21.54	0.02	**M4** (see Fig A.12)
CDMA BC10				
823.1	684	26.47	-0.08	**M4** (see Fig A.13)
820.5	580	28.34	-0.03	**M4** (see Fig A.14)
817.9	476	30.39	-0.09	**M4** (see Fig A.15)
LTE Band 41				
2680	41490	20.02	0.06	**M4** (see Fig A.16)
2636.5	41055	19.99	0.08	**M4** (see Fig A.17)
2593	40620	19.91	0.10	**M4** (see Fig A.18)
2549.5	40185	19.80	0.05	**M4** (see Fig A.19)
2506	39750	19.04	0.08	**M4** (see Fig A.20)

©Copyright. All rights reserved by SAICT.

12 ANSI C 63.19-2011 Limits

WD RF audio interference level categories in logarithmic units

Emission categories	**< 960 MHz**	
	E-field emissions	
Category M1	50 to 55	dB (V/m)
Category M2	45 to 50	dB (V/m)
Category M3	40 to 45	dB (V/m)
Category M4	< 40	dB (V/m)
Emission categories	**> 960 MHz**	
	E-field emissions	
Category M1	40 to 45	dB (V/m)
Category M2	35 to 40	dB (V/m)
Category M3	30 to 35	dB (V/m)
Category M4	< 30	dB (V/m)

©Copyright. All rights reserved by SAICT.

13 Measurement Uncertainty

No.	Error source	Type	Uncertainty Value (%)	Prob. Dist.	k	c_i E	Standard Uncertainty (%) u_i' (%) E	Degree of freedom V_{eff} or v_i	source
1	System repeatability	A	0.24	N	1	1	0.24	9	Measurement
Measurement System									
2	Probe Calibration	B	10.1	N	1	1	10.1	∞	Manufacturer
3	Axial Isotropy	B	0.5	R	$\sqrt{3}$	1	0.5	∞	Cal report
4	Sensor Displacement	B	16.5	R	$\sqrt{3}$	1	9.5	∞	Manufacturer
5	Boundary Effects	B	2.4	R	$\sqrt{3}$	1	1.4	∞	Manufacturer
6	Linearity	B	0.6	R	$\sqrt{3}$	1	0.35	∞	Cal report
7	Scaling to Peak Envolope Power	B	2.0	R	$\sqrt{3}$	1	1.2	∞	Standard
8	System Detection Limit	B	1.0	R	$\sqrt{3}$	1	0.6	∞	Manufacturer
9	Readout Electronics	B	0.3	N	1	1	0.3	∞	Manufacturer
10	Response Time	B	0.8	R	$\sqrt{3}$	1	0.5	∞	Manufacturer
11	Integration Time	B	2.6	R	$\sqrt{3}$	1	1.5	∞	Manufacturer
12	RF Ambient Conditions	B	3.0	R	$\sqrt{3}$	1	1.7	∞	Measurement
13	RF Reflections	B	12.0	R	$\sqrt{3}$	1	6.9	∞	Measurement
14	Probe Positioner	A	1.2	R	$\sqrt{3}$	1	0.7	∞	Manufacturer
15	Probe Positioning	A	4.7	R	$\sqrt{3}$	1	2.7	∞	Manufacturer
16	Extra. And Interpolation	B	1.0	R	$\sqrt{3}$	1	0.6	∞	Manufacturer
Test Sample Related									
17	Device Positioning Vertical	B	4.7	R	$\sqrt{3}$	1	2.7	∞	Manufacturer
18	Device Positioning Lateral	B	1.0	R	$\sqrt{3}$	1	0.6	∞	Manufacturer
19	Device Holder and Phantom	B	2.4	R	$\sqrt{3}$	1	1.4	∞	Manufacturer
20	Power Drift	B	5.0	R	$\sqrt{3}$	1	2.9	∞	Measurement
Phantom and Setup related									
21	Phantom Thickness	B	2.4	R	$\sqrt{3}$	1	1.4	∞	Manufacturer
PMF related									
22	Monitor amplitude	B	3.5	R	$\sqrt{3}$	1	2.02	∞	Manufacturer
23	Setup repeatability	A	2.3	N	1	1	2.3	9	Manufacturer
24	Sensor amplitude	B	12	R	$\sqrt{3}$	1	6.93	∞	Manufacturer
	Combined standard uncertainty(%)						18.3		
	Expanded uncertainty (confidence interval of 95 %)	$u_e = 2u_c$		N	k=2		36.6		

©Copyright. All rights reserved by SAICT.

14 Main Test Instruments

Table 14-1: List of Main Instruments

No.	Name	Type	Serial Number	Calibration Date	Valid Period
01	Signal Generator	E8257D	MY47461211	2019-06-03	One year
02	Power meter	E4418B	MY50000366	2018-12-14	One year
03	Power sensor	E9304A	MY50000188		
04	Amplifier	VTL5400	0404	/	
05	HAC Test Arch	N/A	1150	/	
06	DAE	DAE4	1527	2018-11-08	One year
07	E-Field Probe	ER3DV6	2424	2018-02-23	Three year
08	HAC Dipole	CD835V3	1165	2018-07-19	Three year
09	HAC Dipole	CD1880V3	1149	2018-07-19	Three year
10	HAC Dipole	CD2600V3	1020	2018-10-23	Three year
11	BTS	CMU200	114544	2018-09-03	One year
12	BTS	CMU500	152499	2018-07-19	One year

©Copyright. All rights reserved by SAICT.

ANNEX A RF Emission Test Plot

HAC RF E-Field GSM 850 High

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 848.8 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 18.52 V/m; Power Drift = -0.03 dB

Applied MIF = 3.63 dB

RF audio interference level = 27.48 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **25.52 dBV/m**	Grid 2 **M4** **27.23 dBV/m**	Grid 3 **M4** **27.23 dBV/m**
Grid 4 **M4** **25.89 dBV/m**	Grid 5 **M4** **27.48 dBV/m**	Grid 6 **M4** **27.39 dBV/m**
Grid 7 **M4** **26.65 dBV/m**	Grid 8 **M4** **27.42 dBV/m**	Grid 9 **M4** **27.39 dBV/m**



0 dB = 23.66 V/m = 27.48 dBV/m

Fig A.1 HAC RF E-Field GSM850

©Copyright. All rights reserved by SAICT.

HAC RF E-Field GSM 850 Middle

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 836.6 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 19.76 V/m; Power Drift = -0.06 dB

Applied MIF = 3.63 dB

RF audio interference level = 27.96 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **26.17 dBV/m**	Grid 2 **M4** **27.7 dBV/m**	Grid 3 **M4** **27.7 dBV/m**
Grid 4 **M4** **26.47 dBV/m**	Grid 5 **M4** **27.96 dBV/m**	Grid 6 **M4** **27.89 dBV/m**
Grid 7 **M4** **27.18 dBV/m**	Grid 8 **M4** **27.96 dBV/m**	Grid 9 **M4** **27.89 dBV/m**



0 dB = 24.50 V/m = 27.96 dBV/m

Fig A.2 HAC RF E-Field GSM850

©Copyright. All rights reserved by SAICT.

HAC RF E-Field GSM 850 Low

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 824.2 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 19.26 V/m; Power Drift = -0.04 dB

Applied MIF = 3.63 dB

RF audio interference level = 27.75 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **25.94 dBV/m**	Grid 2 **M4** **27.58 dBV/m**	Grid 3 **M4** **27.58 dBV/m**
Grid 4 **M4** **26.27 dBV/m**	Grid 5 **M4** **27.75 dBV/m**	Grid 6 **M4** **27.71 dBV/m**
Grid 7 **M4** **26.9 dBV/m**	Grid 8 **M4** **27.7 dBV/m**	Grid 9 **M4** **27.68 dBV/m**



0 dB = 23.84 V/m = 27.75 dBV/m

Fig A.3 HAC RF E-Field GSM850

©Copyright. All rights reserved by SAICT.

HAC RF E-Field GSM 1900 High

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 1910 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 4.559 V/m; Power Drift = 0.02 dB

Applied MIF = 3.63 dB

RF audio interference level = 18.71 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **18.59 dBV/m**	Grid 2 **M4** **20.84 dBV/m**	Grid 3 **M4** **20.73 dBV/m**
Grid 4 **M4** **16.37 dBV/m**	Grid 5 **M4** **18.71 dBV/m**	Grid 6 **M4** **18.44 dBV/m**
Grid 7 **M4** **16.7 dBV/m**	Grid 8 **M4** **17.21 dBV/m**	Grid 9 **M4** **16.73 dBV/m**



0 dB = 10.77 V/m = 20.84 dBV/m

Fig A.4 HAC RF E-Field GSM1900

©Copyright. All rights reserved by SAICT.

HAC RF E-Field GSM 1900 Middle

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 4.836 V/m; Power Drift = 0.08 dB

Applied MIF = 3.63 dB

RF audio interference level = 18.93 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **20.31 dBV/m**	Grid 2 **M4** **21.86 dBV/m**	Grid 3 **M4** **21.75 dBV/m**
Grid 4 **M4** **17.34 dBV/m**	Grid 5 **M4** **18.93 dBV/m**	Grid 6 **M4** **18.92 dBV/m**
Grid 7 **M4** **17.55 dBV/m**	Grid 8 **M4** **17.79 dBV/m**	Grid 9 **M4** **17.48 dBV/m**



0 dB = 12.11 V/m = 21.86 dBV/m

Fig A.5 HAC RF E-Field GSM1900

©Copyright. All rights reserved by SAICT.

HAC RF E-Field GSM 1900 Low

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, GSM Frequency: 1850.2 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 5.445 V/m; Power Drift = 0.03 dB

Applied MIF = 3.63 dB

RF audio interference level = 19.48 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **20.46 dBV/m**	Grid 2 **M4** **22.23 dBV/m**	Grid 3 **M4** **22.12 dBV/m**
Grid 4 **M4** **17.3 dBV/m**	Grid 5 **M4** **19.48 dBV/m**	Grid 6 **M4** **19.48 dBV/m**
Grid 7 **M4** **18.01 dBV/m**	Grid 8 **M4** **18.28 dBV/m**	Grid 9 **M4** **17.87 dBV/m**



0 dB = 12.63 V/m = 22.23 dBV/m

Fig A.6 HAC RF E-Field GSM1900

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC0 High

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 848.31 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 14.86 V/m; Power Drift = -0.01 dB

Applied MIF = 3.26 dB

RF audio interference level = 26.02 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **23.48 dBV/m**	Grid 2 **M4** **25.83 dBV/m**	Grid 3 **M4** **25.93 dBV/m**
Grid 4 **M4** **24.66 dBV/m**	Grid 5 **M4** **26.02 dBV/m**	Grid 6 **M4** **26.1 dBV/m**
Grid 7 **M4** **24.34 dBV/m**	Grid 8 **M4** **26.11 dBV/m**	Grid 9 **M4** **26.12 dBV/m**



0 dB = 20.24 V/m = 26.12 dBV/m

Fig A.7 HAC RF E-Field CDMA BC0

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC0 Middle

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 836.52 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 17.41 V/m; Power Drift = -0.03 dB

Applied MIF = 3.26 dB

RF audio interference level = 26.24 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **24.59 dBV/m**	Grid 2 **M4** **26.19 dBV/m**	Grid 3 **M4** **26.24 dBV/m**
Grid 4 **M4** **24.8 dBV/m**	Grid 5 **M4** **26.12 dBV/m**	Grid 6 **M4** **26.19 dBV/m**
Grid 7 **M4** **24.72 dBV/m**	Grid 8 **M4** **26.48 dBV/m**	Grid 9 **M4** **26.42 dBV/m**



0 dB = 21.08 V/m = 26.48 dBV/m

Fig A.8 HAC RF E-Field CDMA BC0

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC0 Low

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 824.7 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 15.47 V/m; Power Drift = -0.07 dB

Applied MIF = 3.26 dB

RF audio interference level = 26.37 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **24.74 dBV/m**	Grid 2 **M4** **26.35 dBV/m**	Grid 3 **M4** **26.22 dBV/m**
Grid 4 **M4** **24.68 dBV/m**	Grid 5 **M4** **26.34 dBV/m**	Grid 6 **M4** **26.47 dBV/m**
Grid 7 **M4** **25.34 dBV/m**	Grid 8 **M4** **26.37 dBV/m**	Grid 9 **M4** **25.71 dBV/m**



0 dB = 21.07 V/m = 26.47 dBV/m

Fig A.9 HAC RF E-Field CDMA BC0

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC1 High

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 1908.75 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 2.739 V/m; Power Drift = 0.11 dB

Applied MIF = 3.26 dB

RF audio interference level = 15.23 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **14.35 dBV/m**	Grid 2 **M4** **14.54 dBV/m**	Grid 3 **M4** **13.06 dBV/m**
Grid 4 **M4** **14.44 dBV/m**	Grid 5 **M4** **15.23 dBV/m**	Grid 6 **M4** **13.77 dBV/m**
Grid 7 **M4** **15.72 dBV/m**	Grid 8 **M4** **15.13 dBV/m**	Grid 9 **M4** **15.15 dBV/m**



0 dB = 6.106 V/m = 15.72 dBV/m

Fig A.10 HAC RF E-Field CDMA BC1

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC1 Middle

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 1880 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 2.742 V/m; Power Drift = 0.07 dB

Applied MIF = 3.26 dB

RF audio interference level = 14.78 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **14.59 dBV/m**	Grid 2 **M4** **13.85 dBV/m**	Grid 3 **M4** **13.13 dBV/m**
Grid 4 **M4** **14.52 dBV/m**	Grid 5 **M4** **14.78 dBV/m**	Grid 6 **M4** **13.19 dBV/m**
Grid 7 **M4** **15.65 dBV/m**	Grid 8 **M4** **15.04 dBV/m**	Grid 9 **M4** **14.65 dBV/m**



0 dB = 6.062 V/m = 15.65 dBV/m

Fig A.11 HAC RF E-Field CDMA BC1

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC1 Low

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 1851.25 MHz Duty Cycle: 1:8.3

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 2.873 V/m; Power Drift = 0.01 dB

Applied MIF = 3.26 dB

RF audio interference level = 15.25 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **14.78 dBV/m**	Grid 2 **M4** **14.23 dBV/m**	Grid 3 **M4** **13.08 dBV/m**
Grid 4 **M4** **14.85 dBV/m**	Grid 5 **M4** **15.25 dBV/m**	Grid 6 **M4** **14.37 dBV/m**
Grid 7 **M4** **15.64 dBV/m**	Grid 8 **M4** **15.65 dBV/m**	Grid 9 **M4** **15.61 dBV/m**



0 dB = 6.058 V/m = 15.65 dBV/m

Fig A.12 HAC RF E-Field CDMA BC1

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC10 High

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 823.1 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 17.28 V/m; Power Drift = -0.08 dB

Applied MIF = 3.26 dB

RF audio interference level = 26.47 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **26.14 dBV/m**	Grid 2 **M4** **26.09 dBV/m**	Grid 3 **M4** **26.3 dBV/m**
Grid 4 **M4** **26.24 dBV/m**	Grid 5 **M4** **26.47 dBV/m**	Grid 6 **M4** **26.33 dBV/m**
Grid 7 **M4** **26.34 dBV/m**	Grid 8 **M4** **26.11 dBV/m**	Grid 9 **M4** **26.09 dBV/m**



0 dB = 21.06 V/m = 26.47 dBV/m

Fig A.13 HAC RF E-Field CDMA BC10

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC10 Middle

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 820.5 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 15.33 V/m; Power Drift = -0.03 dB

Applied MIF = 3.26 dB

RF audio interference level = 28.34 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **28.81 dBV/m**	Grid 2 **M4** **28.7 dBV/m**	Grid 3 **M4** **26.39 dBV/m**
Grid 4 **M4** **28.38 dBV/m**	Grid 5 **M4** **28.34 dBV/m**	Grid 6 **M4** **26.51 dBV/m**
Grid 7 **M4** **25.38 dBV/m**	Grid 8 **M4** **26.02 dBV/m**	Grid 9 **M4** **26.1 dBV/m**



0 dB = 27.56 V/m = 28.81 dBV/m

Fig A.14 HAC RF E-Field CDMA BC10

©Copyright. All rights reserved by SAICT.

HAC RF E-Field CDMA BC10 Low

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, CDMA Frequency: 817.9 MHz Duty Cycle: 1:1

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 17.90 V/m; Power Drift = -0.09 dB

Applied MIF = 3.26 dB

RF audio interference level = 30.39 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **23.96 dBV/m**	Grid 2 **M4** **30.16 dBV/m**	Grid 3 **M4** **26.32 dBV/m**
Grid 4 **M4** **25.09 dBV/m**	Grid 5 **M4** **30.39 dBV/m**	Grid 6 **M4** **26.67 dBV/m**
Grid 7 **M4** **24.71 dBV/m**	Grid 8 **M4** **26.52 dBV/m**	Grid 9 **M4** **25.8 dBV/m**



0 dB = 33.08 V/m = 30.39 dBV/m

Fig A.15 HAC RF E-Field CDMA BC10

©Copyright. All rights reserved by SAICT.

HAC RF E-Field LTE-Band 41 High

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, LTE_TDD Frequency: 2680 MHz Duty Cycle: 1:1.58

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 5.935 V/m; Power Drift = 0.06 dB

Applied MIF = -1.44 dB

RF audio interference level = 20.02 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **21.63 dBV/m**	Grid 2 **M4** **18.78 dBV/m**	Grid 3 **M4** **20.1 dBV/m**
Grid 4 **M4** **18.99 dBV/m**	Grid 5 **M4** **18.22 dBV/m**	Grid 6 **M4** **20.02 dBV/m**
Grid 7 **M4** **17.96 dBV/m**	Grid 8 **M4** **17.19 dBV/m**	Grid 9 **M4** **18.81 dBV/m**



0 dB = 12.06 V/m = 21.63 dBV/m

Fig A.7 HAC RF E-Field LTE-Band 41 High

©Copyright. All rights reserved by SAICT.

HAC RF E-Field LTE-Band 41 High-2

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, LTE_TDD Frequency: 2636.5 MHz Duty Cycle: 1:1.58

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 7.832 V/m; Power Drift = 0.08 dB

Applied MIF = -1.44 dB

RF audio interference level = 19.99 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **19.99 dBV/m**	Grid 2 **M4** **21.10 dBV/m**	Grid 3 **M4** **21.16 dBV/m**
Grid 4 **M4** **16.29 dBV/m**	Grid 5 **M4** **19.37 dBV/m**	Grid 6 **M4** **19.99 dBV/m**
Grid 7 **M4** **14.7 dBV/m**	Grid 8 **M4** **16.7 dBV/m**	Grid 9 **M4** **17.99 dBV/m**



0 dB = 11.43 V/m = 21.16 dBV/m

Fig A.7 HAC RF E-Field LTE-Band 41 High-2

©Copyright. All rights reserved by SAICT.

HAC RF E-Field LTE-Band 41 Middle

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, LTE_TDD Frequency: 2593 MHz Duty Cycle: 1:1.58

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 5.935 V/m; Power Drift = 0.10 dB

Applied MIF = -1.44 dB

RF audio interference level = 19.91 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **21.60 dBV/m**	Grid 2 **M4** **18.67 dBV/m**	Grid 3 **M4** **19.99 dBV/m**
Grid 4 **M4** **18.88 dBV/m**	Grid 5 **M4** **18.11 dBV/m**	Grid 6 **M4** **19.91 dBV/m**
Grid 7 **M4** **17.85 dBV/m**	Grid 8 **M4** **17.08 dBV/m**	Grid 9 **M4** **18.7 dBV/m**



0 dB = 12.06 V/m = 21.60 dBV/m

Fig A.8 HAC RF E-Field LTE-Band 41 Middle

©Copyright. All rights reserved by SAICT.

HAC RF E-Field LTE-Band 41 Low-2

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, LTE_TDD Frequency: 2549.5 MHz Duty Cycle: 1:1.58

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 7.832 V/m; Power Drift = 0.05 dB

Applied MIF = -1.44 dB

RF audio interference level = 19.80 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **19.8 dBV/m**	Grid 2 **M4** **20.98 dBV/m**	Grid 3 **M4** **21.12 dBV/m**
Grid 4 **M4** **16.1 dBV/m**	Grid 5 **M4** **19.18 dBV/m**	Grid 6 **M4** **19.8 dBV/m**
Grid 7 **M4** **14.51 dBV/m**	Grid 8 **M4** **16.51 dBV/m**	Grid 9 **M4** **17.8 dBV/m**



0 dB = 11.43 V/m = 21.12 dBV/m

Fig A.9 HAC RF E-Field LTE-Band 41 Low-2

©Copyright. All rights reserved by SAICT.

HAC RF E-Field LTE-Band 41 Low

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 S/m, ε_r = 1; ρ = 1000 kg/m^3

Ambient Temperature: 22.0ºC Liquid Temperature: 21.5ºC

Communication System: UID 0, LTE_TDD Frequency: 2506 MHz Duty Cycle: 1:1.58

Probe: ER3DV6 - SN2424 ConvF (1, 1, 1);

E Scan - ER3DV6 - 2011: 15 mm from Probe Center to the Device /Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 6.080 V/m; Power Drift = 0.08 dB

Applied MIF = -1.44 dB

RF audio interference level = 19.04 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 **M4** **20.14 dBV/m**	Grid 2 **M4** **20.03 dBV/m**	Grid 3 **M4** **20.24 dBV/m**
Grid 4 **M4** **18.17 dBV/m**	Grid 5 **M4** **17.98 dBV/m**	Grid 6 **M4** **19.04 dBV/m**
Grid 7 **M4** **17.83 dBV/m**	Grid 8 **M4** **16.3 dBV/m**	Grid 9 **M4** **16.96 dBV/m**



0 dB = 10.28 V/m = 20.24 dBV/m

Fig A.9 HAC RF E-Field LTE-Band 41 Low

©Copyright. All rights reserved by SAICT.

ANNEX B System Validation Result

835 MHz

Date: 2019-6-10
Electronics: DAE4 Sn1527
Medium: Air
Medium parameters used: σ = 0 mho/m, εr = 1; ρ = 1000 kg/m3
Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1
Probe: ER3DV6 - SN2424; ConvF (1, 1, 1)

E Scan - measurement distance from the probe sensor center to CD835 Dipole = 15mm /Hearing Aid Compatibility Test (41x361x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm
Device Reference Point: 0, 0, -6.3 mm
Reference Value = 110.9 V/m; Power Drift = 0.08 dB
Applied MIF = 0.00 dB
RF audio interference level = 42.28 dBV/m
Emission category: M3

MIF scaled E-field

Grid 1 **M3** **41.62 dBV/m**	Grid 2 **M3** **42.18 dBV/m**	Grid 3 **M3** **42.02 dBV/m**
Grid 4 **M4** **37.11 dBV/m**	Grid 5 **M4** **37.44 dBV/m**	Grid 6 **M4** **37.38 dBV/m**
Grid 7 **M3** **41.74 dBV/m**	Grid 8 **M3** **42.28 dBV/m**	Grid 9 **M3** **42.09 dBV/m**



0 dB = 42.28 dBV/m

©Copyright. All rights reserved by SAICT.

1880 MHz

Date: 2019-6-10

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 mho/m, ε_r = 1; ρ = 1000 kg/m^3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: ER3DV6 - SN2424; ConvF (1, 1, 1)

E Scan - measurement distance from the probe sensor center to CD1880 Dipole = 15mm /Hearing Aid Compatibility Test (41x181x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 106.4 V/m; Power Drift = 0.02 dB

Applied MIF = 0.00 dB

RF audio interference level = 39.64 dBV/m

Emission category: M2

MIF scaled E-field

Grid 1 **M2** **39.18 dBV/m**	Grid 2 **M2** **39.64 dBV/m**	Grid 3 **M2** **39.56 dBV/m**
Grid 4 **M2** **37.39 dBV/m**	Grid 5 **M2** **37.73 dBV/m**	Grid 6 **M2** **37.68 dBV/m**
Grid 7 **M2** **39.15 dBV/m**	Grid 8 **M2** **39.60 dB V/m**	Grid 9 **M2** **39.51 dBV/m**



0 dB = 39.64 dBV/m

©Copyright. All rights reserved by SAICT.

2600 MHz

Date: 2019-6-9

Electronics: DAE4 Sn1527

Medium: Air

Medium parameters used: σ = 0 mho/m, ε_r = 1; ρ = 1000 kg/m^3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1

Probe: ER3DV6 - SN2424; ConvF (1, 1, 1)

E Scan - measurement distance from the probe sensor center to CD2600 Dipole = 15mm /Hearing Aid Compatibility Test (41x181x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 70.68 V/m; Power Drift = -0.09 dB

Applied MIF = 0.00 dB

RF audio interference level = 39.53 dBV/m

Emission category: M2

MIF scaled E-field

Grid 1 **M2** **39.08 dBV/m**	Grid 2 **M2** **39.35 dBV/m**	Grid 3 **M2** **39.29 dBV/m**
Grid 4 **M2** **38.72 dBV/m**	Grid 5 **M2** **38.88 dBV/m**	Grid 6 **M2** **38.86 dBV/m**
Grid 7 **M2** **39.36 dBV/m**	Grid 8 **M2** **39.53 dB V/m**	Grid 9 **M2** **39.44 dBV/m**



0 dB = 39.53 dBV/m

©Copyright. All rights reserved by SAICT.

ANNEX C Probe Calibration Certificate

E_Probe ER3DV6

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client CTTL-SZ (Auden)

Certificate No: ER3-2424_Feb18

CALIBRATION CERTIFICATE

Object	ER3DV6 - SN:2424
Calibration procedure(s)	QA CAL-02.v8, QA CAL-25.v6 Calibration procedure for E-field probes optimized for close near field evaluations in air
Calibration date:	February 23, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-17 (No. 217-02521/02522)	Apr-18
Power sensor NRP-Z91	SN: 103244	04-Apr-17 (No. 217-02521)	Apr-18
Power sensor NRP-Z91	SN: 103245	04-Apr-17 (No. 217-02525)	Apr-18
Reference 20 dB Attenuator	SN: S5277 (20x)	07-Apr-17 (No. 217-02528)	Apr-18
Reference Probe ER3DV6	SN: 2328	10-Oct-17 (No. ER3-2328_Oct17)	Oct-18
DAE4	SN: 789	2-Aug-17 (No. DAE4-789_Aug17)	Aug-18
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-16)	In house check: Jun-18
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-16)	In house check: Jun-18
Network Analyzer HP 8753E	SN: US37390585	18-Oct-01 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Jeton Kastrati	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: February 23, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

©Copyright. All rights reserved by SAICT.

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S C S Schweizerischer Kalibrierdienst
Service suisse d'étalonnage
Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Glossary:

NORMx,y,z	sensitivity in free space
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., ϑ = 0 is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

a) IEEE Std 1309-2005, " IEEE Standard for calibration of electromagnetic field sensors and probes, excluding antennas, from 9 kHz to 40 GHz", December 2005
b) CTIA Test Plan for Hearing Aid Compatibility, Rev 3.0, November 2013

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization ϑ = 0 for XY sensors and ϑ = 90 for Z sensor (f ≤ 900 MHz in TEM-cell; f > 1800 MHz: R22 waveguide).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart).
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *PAR:* PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- *Ax,y,z; Bx,y,z; Cx,y,z; Dx,y,z; VRx,y,z: A, B, C, D* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. *VR* is the maximum calibration range expressed in RMS voltage across the diode.
- *Spherical isotropy (3D deviation from isotropy)*: in a locally homogeneous field realized using an open waveguide setup.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- *Connector Angle*: The angle is assessed using the information gained by determining the *NORMx* (no uncertainty required).

©Copyright. All rights reserved by SAICT.

Probe ER3DV6

SN:2424

Manufactured: November 12, 2007
Calibrated: February 23, 2018

Calibrated for DASY/EASY Systems
(Note: non-compatible with DASY2 system!)

©Copyright. All rights reserved by SAICT.

DASY/EASY - Parameters of Probe: ER3DV6 - SN:2424

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu V/(V/m)^2$)	1.46	1.51	1.82	± 10.1 %
DCP (mV)[B]	100.0	98.3	100.6	

Modulation Calibration Parameters

UID	Communication System Name		A dB	B dB√μV	C	D dB	VR mV	Unc[E] (k=2)
0	CW	X	0.0	0.0	1.0	0.00	189.6	±3.5 %
		Y	0.0	0.0	1.0		204.8	
		Z	0.0	0.0	1.0		200.6	
10021-DAC	GSM-FDD (TDMA, GMSK)	X	21.68	99.9	28.7	9.39	106.2	±2.2 %
		Y	19.41	99.7	28.8		111.3	
		Z	24.71	99.5	28.2		119.2	
10061-CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	X	8.35	84.6	25.4	3.60	146.9	±1.9 %
		Y	4.81	74.8	21.7		112.9	
		Z	6.43	78.8	22.9		111.9	
10077-CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	X	13.28	77.7	29.3	11.00	139.0	±3.8 %
		Y	11.65	73.4	26.9		100.8	
		Z	11.41	72.1	25.6		99.2	
10172-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	X	9.48	80.8	29.7	9.21	125.2	±3.8 %
		Y	9.49	81.9	30.6		134.1	
		Z	10.82	83.6	30.5		136.8	
10173-CAD	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	X	9.87	81.2	29.9	9.48	125.1	±2.5 %
		Y	10.11	83.1	31.3		134.2	
		Z	11.30	84.2	30.8		136.9	
10295-AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 fr.	X	16.69	99.5	40.3	12.49	96.6	±2.5 %
		Y	15.42	99.3	41.1		100.6	
		Z	17.91	99.9	39.8		104.3	

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[B] Numerical linearization parameter: uncertainty not required.
[E] Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

©Copyright. All rights reserved by SAICT.

ER3DV6 – SN:2424

February 23, 2018

Frequency Response of E-Field
(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

©Copyright. All rights reserved by SAICT.

Receiving Pattern (ϕ), ϑ = 0°

f=600 MHz,TEM,0°



f=2500 MHz,R22,0°



Receiving Pattern (ϕ), ϑ = 90°

f=600 MHz,TEM,90°



f=2500 MHz,R22,90°



©Copyright. All rights reserved by SAICT.

ER3DV6 – SN:2424

February 23, 2018

Receiving Pattern (ϕ), ϑ = 0°



Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Receiving Pattern (ϕ), ϑ = 90°



Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

©Copyright. All rights reserved by SAICT.

Dynamic Range f(E-field)
(TEM cell , f = 900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

©Copyright. All rights reserved by SAICT.

ER3DV6 – SN:2424

February 23, 2018

Deviation from Isotropy in Air

Error (ϕ, ϑ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

©Copyright. All rights reserved by SAICT.

DASY/EASY - Parameters of Probe: ER3DV6 - SN:2424

Other Probe Parameters

Sensor Arrangement	Rectangular
Connector Angle (°)	-11.2
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	8 mm
Probe Tip to Sensor X Calibration Point	2.5 mm
Probe Tip to Sensor Y Calibration Point	2.5 mm
Probe Tip to Sensor Z Calibration Point	2.5 mm

©Copyright. All rights reserved by SAICT.

ANNEX D Dipole Calibration Certificate

Dipole 835 MHz

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
S Servizio svizzero di taratura
Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client CTTL (Auden)

Certificate No: CD835V3-1165_Jul18

CALIBRATION CERTIFICATE

Object	CD835V3 - SN: 1165
Calibration procedure(s)	QA CAL-20.v6 Calibration procedure for dipoles in air
Calibration date:	July 19, 2018

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	04-Apr-18 (No. 217-02672/02673)	Apr-19
Power sensor NRP-Z91	SN: 103244	04-Apr-18 (No. 217-02672)	Apr-19
Power sensor NRP-Z91	SN: 103245	04-Apr-18 (No. 217-02673)	Apr-19
Reference 20 dB Attenuator	SN: 5058 (20k)	04-Apr-18 (No. 217-02682)	Apr-19
Type-N mismatch combination	SN: 5047.2 / 06327	04-Apr-18 (No. 217-02683)	Apr-19
Probe EF3DV3	SN: 4013	05-Mar-18 (No. EF3-4013_Mar18)	Mar-19
Probe H3DV6	SN: 6065	30-Dec-17 (No. H3-6065_Dec17)	Dec-18
DAE4	SN: 781	17-Jan-18 (No. DAE4-781_Jan18)	Jan-19

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power meter Agilent 4419B	SN: GB42420191	09-Oct-09 (in house check Oct-17)	In house check: Oct-20
Power sensor HP E4412A	SN: US38485102	05-Jan-10 (in house check Oct-17)	In house check: Oct-20
Power sensor HP 8482A	SN: US37295597	09-Oct-09 (in house check Oct-17)	In house check: Oct-20
RF generator R&S SMT-06	SN: 832283/011	27-Aug-12 (in house check Oct-17)	In house check: Oct-20
Network Analyzer Agilent E8358A	SN: US41080477	31-Mar-14 (in house check Oct-17)	In house check: Oct-18

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: July 19, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

©Copyright. All rights reserved by SAICT.