

FCC TEST REPORT

for

Meiloon Industrial Co., Ltd.

active Loudspeaker

Model Number: PW600, PW800

FCC ID: R48TT025

IC ID:7190A-TT205

Prepared for : Meiloon Industrial Co., Ltd.

Address : No.99, Xingfu Road, Taoyuan Dist, Taoyuan City, Taiwan

Prepared by : Keyway Testing Technology Co., Ltd.

Address : Baishun Industrial Zone, Zhangmutou Town,
Dongguan, Guangdong, China

Tel: 86-769-8718 2258

Fax: 86-769-8718 1058

Report No. : 15KWE062682F



Date of Test : Jun. 9~Jun. 16, 2015

Date of Report : Jun. 17, 2015

TABLE OF CONTENTS

Test Report Declaration	Page
1. TEST SUMMARY.....	4
2. GENERAL PRODUCT INFORMATION.....	4
2.1. Product Function.....	4
2.2. Description of Device (EUT).....	4
2.3. Independent Operation Modes.....	5
2.4. Test Supporting System.....	5
2.5. Product Version.....	5
2.6. TEST SITES.....	5
2.7. List of Test and Measurement Instruments.....	6
3. TEST SET-UP AND OPERATION MODES.....	7
3.1. Principle of Configuration Selection.....	7
3.2. Block Diagram of Test Set-up.....	7
3.3. Test Operation Mode and Test Software.....	7
3.4. Special Accessories and Auxiliary Equipment.....	7
3.5. Countermeasures to Achieve EMC Compliance.....	7
4. EMISSION TEST RESULTS.....	8
4.1. Conducted Emission at the Mains Terminals Test.....	8
4.2. Radiated Emission Test.....	13
5. BAND EDGE COMPLIANCE TEST.....	38
5.1. Limits.....	38
5.2. Test setup.....	38
6. 6DB OCCUPY BANDWIDTH.....	40
6.1. Limits.....	40
7. OUTPUT POWER TEST.....	45
7.1. Limits.....	45
7.2. Test setup.....	45
7.3. Test result.....	45
8. POWER SPECTRAL DENSITY TEST.....	46
8.1. Limits.....	46
8.2. Test setup.....	46
8.3. Test result.....	46
9. ANTENNA REQUIREMENTS.....	53
9.1. Limits.....	53
9.2. Result.....	53
10. PHOTOGRAPHS OF TEST SET-UP.....	54
11. PHOTOGRAPHS OF THE EUT.....	56

Keyway Testing Technology Co., Ltd.

Applicant:	Meiloon Industrial Co., Ltd.		
Address:	No.99, Xingfu Road, Taoyuan Dist, Taoyuan City, Taiwan		
Manufacturer:	Paradigm Electronics		
Address:	205 Annagem Blvd., Mississauga ON L5T 2V1, CANADA		
Factory:	Dongguan Meiloon Acoustic Equipments Co., Ltd.		
Address:	77, Yuanlin Road Fenghuanggang Ind, Estate, Tangxia Town, 523727 Dongguan City, Guangdong Province, PEOPLE'S REPUBLIC OF CHINA.		
E.U.T:	active Loudspeaker		
Model Number:	PW600, PW800		
Trade Name:		Serial No.:	-----
Date of Receipt:	Jun. 8 , 2015	Date of Test:	Jun. 9~16, 2015
Test Specification:	FCC Part 15, Subpart 15.247: Oct. 1, 2014 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r02 RSS-247 Issue 1 May 2015 RSS-Gen Issue 4 November 2014		
Test Result:	The equipment under test was found to be compliance with the requirements of the standards applied.		
Issue Date: Jun. 17, 2015			
Tested by:	Reviewed by:	Approved by:	
			
Keven Wu / Engineer	Andy Gao / Supervisor	Jade Yang / Supervisor	
Other Aspects:	None.		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Keyway Testing Technology Co., Ltd.			

1.TEST SUMMARY

Test Items	Test Requirement	Result
Conducted Emissions	15.207 &RSS-Gen §8.8	PASS
Radiated Emissions	15.205(a)/15.209/15.247(d) &RSS-Gen §6.13	PASS
6dB&99% Bandwidth	15.247(a)(2)& RSS-247 §5.2(1) &RSS-Gen§6.6	PASS
Power density	15.247(e) &RSS-247 §5.2 (2)	PASS
Maximum Peak Output Power	15.247(b)(3)& RSS-247 §5.4&RSS-Gen§6.12	PASS
Emissions from out of band	15.247(d) & RSS-247 §5.5	PASS
Antenna Requirement	15.203&RSS-Gen§8.3	PASS

2.GENERAL PRODUCT INFORMATION

2.1. Product Function

Refer to Technical Construction Form and User Manual.

2.2. Description of Device (EUT)

Product Name:	Active Loudspeaker
Model No.:	PW600, PW800
Operation Frequency:	2412MHz~2462MHz (802.11b/802.11g/802.11n(H20)) 2422MHz~2452MHz (802.11n(H40)) 5180-5240 MHz; 5745-5805 MHz(5G 802.11a/n(HT20)) 5190-5230 MHz; 5755-5795 MHz(802.11n(HT40))
Channel numbers:	11 for 802.11b/802.11g/802.11n(H20) ,7 for 802.11n(H40) 5channels for 5G 802.11a/n(HT20) 4channels for 802.11n(HT40)
Modulation technology:	Direct Sequence Spread Spectrum (DSSS) for (IEEE 802.11b) Orthogonal Frequency Division Multiplexing(OFDM) for (IEEE 802.11g/802.11n)
Data speed (IEEE 802.11b):	1Mbps, 2Mbps, 5.5Mbps, 11Mbps
Data speed (IEEE 802.11g):	6Mbps, 9Mbps, 12Mbps, 18Mbps, 24Mbps, 36Mbps, 48Mbps,54Mbps
Data speed (IEEE 802.11n):	Up to 150Mbps
Antenna Type:	Internal
Antenna gain:	3.3dBi for 2.4GWIFI(declare by Applicant) 3.25 dBi for 5G WIFI
Power supply:	AC 120V/60Hz

2.3. Independent Operation Modes

The basic operation modes are:

2.3.1. EUT work WFI TX mode, and frequency as below:

	Channel	Frequency
802.11b	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11g	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11n(HT20)	Low	2412MHz
	Middle	2437MHz
	High	2462MHz
802.11 n(HT40)	Low	2422MHz
	Middle	2437MHz
	High	2452MHz

Remark: According to ANSI C63.10 standards, the test results are both the “worst case” and “worst setup” 11MHz for 802.11b, 54MHz for 802.11g, 6.5Mbps for 802.11n(H20), 13Mbps for 802.11n(H40).

2.4. Test Supporting System

None.

2.5. Product Version

Product SW version	3.10.20
Product HW version	Anzhen4_mrd8_w_64-userdebug
Radio SW version	4.4
Radio HW version	VT2.1
Test SW Version	T1.2
RF power setting in TEST SW	2.4G:11b 15 dBm;11g 14 dBm;11n(HT20) 13 dBm; 11n(HT40) 11 dBm 5G:11n 14 dBm; 11a 13 dBm

Note: SW means software, HW means hardware.

2.6. TEST SITES

2.6.1. Test Facilities

Lab Qualifications : Certificated by Industry Canada
Registration No.: 9868A
Date of registration: December 8, 2011

Certificated by FCC, USA
Registration No.: 370994
Date of registration: February 21, 2012

Certificated by CNAS China
Registration No.: CNAS L5783
Date of registration: August 8, 2012

2.7. List of Test and Measurement Instruments

2.7.1. For conducted emission at the mains terminals test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 27,15	Apr. 27,16
Artificial Mains Network	Rohde&Schwarz	ENV216	101315	Apr. 27,15	Apr. 27,16
Artificial Mains Network (AUX)	Rohde&Schwarz	ENV216	101314	Apr. 27,15	Apr. 27,16
RF Cable	FUJIKURA	3D-2W	944 Cable	Apr. 27,15	Apr. 27,16

2.7.2. For radiated emission test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	101156	Apr. 27,15	Apr. 27,16
System Simulator	Agilent	E5515C	GB43130245	Apr. 27,15	Apr. 27,16
Power Splitter	Weinschel	1506A	NW425	Apr. 27,15	Apr. 27,16
Bilog Antenna	ETS-LINDGREEN	3142D	135452	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	E4411B	MY4511304	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	R&S	FSV40	132.1.3008K39-100967	Apr. 27,15	Apr. 27,16
3m Semi-anechoic Chamber	ETS-LINDGREEN	966	KW01	Apr. 27,15	Apr. 27,16
Signal Amplifier	SONOMA	310	187016	Apr. 27,15	Apr. 27,16
Signal Amplifier	Agilent	8449B	3008A00251	Apr. 27,15	Apr. 27,16
RF Cable	IMRO	IMRO-400	966 Cable 1#	N/A	N/A
MULTI-DEVICE Controller	ETS-LINDGREEN	2090	126913	N/A	N/A
Horn Antenna	DAZE	ZN30701	11003	Apr. 27,15	Apr. 27,16
Horn Antenna	SCHWARZBECK	BBHA9170	9170-068	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	8593E	3911A04271	Apr. 27,15	Apr. 27,16
Spectrum Analyzer	Agilent	E4408B	MY44211125	Apr. 27,15	Apr. 27,16
Signal Amplifier	DAZE	ZN3380C	11001	Apr. 27,15	Apr. 27,16
High Pass filter	Micro	HPM50111	324216	Apr. 27,15	Apr. 27,16
Filter	COM-MW	ZBSF-C836.5-25-X	KW032	Apr. 27,15	Apr. 27,16
Filter	COM-MW	ZBSF-C1747.5-75-X2	KW035	Apr. 27,15	Apr. 27,16
Filter	COM-MW	ZBSF-C1880-60-X2	KW037	Apr. 27,15	Apr. 27,16
DC Power Supply	LongWei	PS-305D	010964729	Apr. 27,15	Apr. 27,16
Constant temperature and humidity box	GF	GTH-800-40-1P	MAA9906-005	Apr. 27,15	Apr. 27,16
Universal radio communication tester	Rohde&Schwarz	CMU200	3215420	Apr. 27,15	Apr. 27,16
Splitter	Agilent	11636B	0025164	Apr. 27,15	Apr. 27,16


3. TEST SET-UP AND OPERATION MODES

3.1. Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the Operating Instructions.

3.2. Block Diagram of Test Set-up

System Diagram of Connections between EUT and Simulators



(EUT: active Loudspeaker)

3.3. Test Operation Mode and Test Software

None.

3.4. Special Accessories and Auxiliary Equipment

None.

3.5. Countermeasures to Achieve EMC Compliance

None.

4. EMISSION TEST RESULTS

4.1. Conducted Emission at the Mains Terminals Test

4.1.1. Limit 15.209 limits

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

4.1.2. Test Setup


The EUT was put on a wooden table which was 0.8 m high above the ground and connected to the AC mains through the Artificial Mains Network (AMN). Where the mains cable supplied by the manufacture was longer than 0.8 m, the excess was folded back and forth parallel to the cable at the centre so as to form a bundle no longer than 0.4 m.

The EUT was kept 0.4 m from any other earthed conducting surface. Both sides of AC line were checked to find out the maximum conducted emission levels according to the test procedure during the conducted emission test.

The frequency range from 150 kHz to 30 MHz was investigated.


The bandwidth of the test receiver was set at 9 kHz.

Pretest for all mode, The test data of the worst case condition(s) was reported on the following page.




Remark:
E.U.T: Equipment Under Test
LISN: Line Impedance Stabilization Network
Test table height=0.8m

Line (PW800)




	Freq	Level	Limit	Over	
	MHz	dB	Line	Limit	Remark
1	0.151	47.15	55.96	-8.81	Average
2	0.151	53.30	65.96	-12.66	QP
3	0.171	46.26	54.90	-8.64	Average
4	0.171	53.26	64.90	-11.64	QP
5	0.813	34.31	46.00	-11.69	Average
6	0.813	42.18	56.00	-13.82	QP
7	1.352	30.80	46.00	-15.20	Average
8	1.352	36.59	56.00	-19.41	QP
9	7.368	34.94	50.00	-15.06	Average
10	7.368	42.57	60.00	-17.43	QP
11	10.963	39.70	50.00	-10.30	Average
12	10.963	48.52	60.00	-11.48	QP

Neutral (PW800)




	Freq	Level	Limit	Over	
	MHz	dB	Line	Limit	Remark
1	0.151	46.26	55.96	-9.70	Average
2	0.151	55.30	65.96	-10.66	QP
3	0.171	44.81	54.90	-10.09	Average
4	0.171	51.32	64.90	-13.58	QP
5	0.830	33.89	46.00	-12.11	Average
6	0.830	41.57	56.00	-14.43	QP
7	1.010	32.27	46.00	-13.73	Average
8	1.010	37.69	56.00	-18.31	QP
9	2.033	30.25	46.00	-15.75	Average
10	2.033	36.21	56.00	-19.79	QP
11	7.290	35.30	50.00	-14.70	Average
12	7.290	43.25	60.00	-16.75	QP

Line (PW600)



			Limit	Over	
	Freq	Level	Line	Limit	Remark
	MHz	dB	dB	dB	
1	0.154	43.85	55.78	-11.93	Average
2	0.154	50.30	65.78	-15.48	QP

Neutral (PW600)



	Freq	Level	Limit	Over	
	MHz	dB	Line	Limit	Remark
1	0.156	43.64	55.69	-12.05	Average
2	0.156	51.36	65.69	-14.33	QP

4.2. Radiated Emission Test

4.2.1. Limit 15.209 limits

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 $\text{dB}(\mu\text{V})/\text{m}$ (Peak) 54.0 $\text{dB}(\mu\text{V})/\text{m}$ (Average)	

4.2.2. Restricted bands of operation

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

4.2.3. Test setup

The EUT was placed on a turn table which was 0.8 m (above 1GHz, the high was 1.5m) above the ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was set 3 m away from the receiving antenna which was mounted on an antenna tower. The measuring antenna moved up and down to find out the maximum emission level. It moved from 1 m to 4 m for both horizontal and vertical polarizations.

The EUT was tested in the Chamber Site. It was pre-scanned with a Peak detector from the spectrum, and all the final readings from the test receiver were measured with the Quasi-Peak detector.

The bandwidth of the EMI test receiver is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's VBW is set at 3MHz and RBW is set at 1MHz for peak emissions measurement above 1GHz and 1MHz RBW, 10Hz VBW for average emissions measure above 1GHz, Both PK and AV measure, PK detector is used.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.

Notes: 1. Emission Level = Antenna Factor + Cable Loss + Meter Reading-Preamp Factor.


2. Measurement Uncertainty: ± 3.2 dB at a level of confidence of 95%.

3. For emissions above 1GHz, if peak level comply with average limit, then the average level is deemed to comply with average limit.


4. For emissions below 1GHz, pretest for all mode, The test data of the worst case condition(s) was reported on the following pages.

5. For Both PK and AV value above 1GHz, PK detector is used.

Below 1GHz




Above 1GHz




Below 1GHz

Horizontal (PW800)




	Preamp Freq	Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	97.90	31.35	53.18	0.94	32.27	43.50	-11.23	QP
2	163.86	31.21	59.10	1.30	38.74	43.50	-4.76	QP
3	352.04	30.66	49.39	2.10	36.50	46.00	-9.50	QP
4	451.95	30.61	48.09	2.62	37.75	46.00	-8.25	QP
5	641.10	30.77	42.20	3.58	36.37	46.00	-9.63	QP
6	798.24	30.57	42.70	4.29	39.40	46.00	-6.60	QP

Vertical (PW800)




		Preamp	Read	Cable		Limit	Over	
	Freq	Factor	Level	Loss	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	!	41.64	31.38	54.01	0.56	35.42	40.00	-4.58 QP
2	!	97.90	31.35	60.62	0.94	39.71	43.50	-3.79 QP
3	!	163.86	31.21	60.80	1.30	40.44	43.50	-3.06 QP
4	!	481.05	30.59	52.12	2.77	42.70	46.00	-3.30 QP
5	!	561.56	30.88	50.89	3.12	42.77	46.00	-3.23 QP
6	!	720.64	30.65	46.50	3.96	42.29	46.00	-3.71 QP

Horizontal (PW600)



	Preamp	Read	Cable		Limit	Over	
	Freq	Factor	Level	Loss	Level	Line	Limit
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB
1	97.90	31.35	53.18	0.94	32.27	43.50	-11.23
2	163.86	31.21	59.10	1.30	38.74	43.50	-4.76
3	352.04	30.66	49.39	2.10	36.50	46.00	-9.50
4	451.95	30.61	48.09	2.62	37.75	46.00	-8.25
5	641.10	30.77	42.20	3.58	36.37	46.00	-9.63
6	798.24	30.57	42.70	4.29	39.40	46.00	-6.60
							QP

Vertical (PW600)



		Preamp	Read	Cable		Limit	Over	
	Freq	Factor	Level	Loss	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	!	41.64	31.38	54.01	0.56	35.42	40.00	-4.58 QP
2	!	97.90	31.35	60.62	0.94	39.71	43.50	-3.79 QP
3	!	163.86	31.21	60.80	1.30	40.44	43.50	-3.06 QP
4	!	481.05	30.59	52.12	2.77	42.70	46.00	-3.30 QP
5	!	561.56	30.88	50.89	3.12	42.77	46.00	-3.23 QP
6	!	720.64	30.65	46.50	3.96	42.29	46.00	-3.71 QP

Above 1GHz (PW800)

802.11b 2412MHz Horizontal polarizations

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	33.87	12.01	32.99	51.37	74.00	-22.63	Peak
2	7236.00	27.95	23.11	16.61	37.30	49.07	74.00	-24.93	Peak
3	8089.00	28.13	21.14	16.68	36.47	46.16	74.00	-27.84	Peak
4	10180.00	28.82	21.42	17.00	38.69	48.29	74.00	-25.71	Peak
5	13053.00	29.21	16.72	18.28	40.94	46.73	74.00	-27.27	Peak
6	14702.00	29.51	16.97	19.81	39.76	47.03	74.00	-26.97	Peak

802.11b 2412MHz Vertical polarizations

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	33.91	12.01	32.99	51.41	74.00	-22.59	Peak
2	7236.00	27.95	23.67	16.61	37.30	49.63	74.00	-24.37	Peak
3	8548.00	28.26	23.01	16.78	36.86	48.39	74.00	-25.61	Peak
4	10639.00	28.86	20.77	17.09	39.28	48.28	74.00	-25.72	Peak
5	12509.00	29.10	20.81	17.81	39.54	49.06	74.00	-24.94	Peak
6	14719.00	29.51	18.34	19.83	39.69	48.35	74.00	-25.65	Peak

802.11b 2437MHz Vertical polarizations

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.61	12.14	33.11	51.33	74.00	-22.67	Peak
2	7311.00	27.96	22.99	16.62	37.32	48.97	74.00	-25.03	Peak
3	9194.00	28.48	18.68	16.89	37.63	44.72	74.00	-29.28	Peak
4	10775.00	28.88	15.86	17.12	39.37	43.47	74.00	-30.53	Peak
5	12713.00	29.14	13.89	17.97	40.02	42.74	74.00	-31.26	Peak
6	14906.00	29.54	16.84	19.94	38.92	46.16	74.00	-27.84	Peak

802.11b 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.37	12.14	33.11	51.09	74.00	-22.91	Peak
2	7311.00	27.96	23.09	16.62	37.32	49.07	74.00	-24.93	Peak
3	8956.00	28.38	20.80	16.87	37.34	46.63	74.00	-27.37	Peak
4	10146.00	28.82	19.45	16.99	38.64	46.26	74.00	-27.74	Peak
5	12220.00	29.04	20.70	17.56	39.44	48.66	74.00	-25.34	Peak
6	14005.00	29.40	15.85	19.37	43.50	49.32	74.00	-24.68	Peak

802.11b 2462MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.32	12.28	33.23	50.27	74.00	-23.73	Peak
2	7386.00	27.98	23.33	16.62	37.36	49.33	74.00	-24.67	Peak
3	9347.00	28.54	19.56	16.91	37.81	45.74	74.00	-28.26	Peak
4	11132.00	28.91	19.20	17.19	39.61	47.09	74.00	-26.91	Peak
5	12254.00	29.05	19.19	17.58	39.45	47.17	74.00	-26.83	Peak
6	13461.00	29.29	16.08	18.75	42.84	48.38	74.00	-25.62	Peak

802.11b 2462MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.67	12.28	33.23	50.62	74.00	-23.38	Peak
2	7386.00	27.98	23.54	16.62	37.36	49.54	74.00	-24.46	Peak
3	9840.00	28.74	18.56	16.95	38.28	45.05	74.00	-28.95	Peak
4	10928.00	28.89	17.10	17.15	39.46	44.82	74.00	-29.18	Peak
5	12254.00	29.05	15.87	17.58	39.45	43.85	74.00	-30.15	Peak
6	13835.00	29.37	12.87	19.16	43.33	45.99	74.00	-28.01	Peak

802.11g 2412MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable&Antenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.58	12.01	32.99	50.08	74.00	-23.92	Peak
2	7236.00	27.95	23.35	16.61	37.30	49.31	74.00	-24.69	Peak
3	10044.00	28.81	19.65	16.98	38.48	46.30	74.00	-27.70	Peak
4	10843.00	28.88	20.27	17.13	39.41	47.93	74.00	-26.07	Peak
5	12883.00	29.18	17.34	18.11	40.42	46.69	74.00	-27.31	Peak
6	14600.00	29.49	15.34	19.75	40.18	45.78	74.00	-28.22	Peak

802.11g 2412MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable&Antenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	33.37	12.01	32.99	50.87	74.00	-23.13	Peak
2	7236.00	27.95	22.16	16.61	37.30	48.12	74.00	-25.88	Peak
3	9211.00	28.48	20.99	16.90	37.65	47.06	74.00	-26.94	Peak
4	10350.00	28.84	18.17	17.04	38.96	45.33	74.00	-28.67	Peak
5	11523.00	28.95	16.90	17.27	39.88	45.10	74.00	-28.90	Peak
6	13580.00	29.32	14.89	18.87	43.08	47.52	74.00	-26.48	Peak

802.11g 2437MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable&Antenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.16	12.14	33.11	50.88	74.00	-23.12	Peak
2	7311.00	27.96	22.00	16.62	37.32	47.98	74.00	-26.02	Peak
3	10112.00	28.81	20.35	16.99	38.59	47.12	74.00	-26.88	Peak
4	11523.00	28.95	18.35	17.27	39.88	46.55	74.00	-27.45	Peak
5	12900.00	29.18	18.94	18.12	40.46	48.34	74.00	-25.66	Peak
6	13563.00	29.31	15.38	18.85	43.07	47.99	74.00	-26.01	Peak

802.11g 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.29	12.14	33.11	51.01	74.00	-22.99	Peak
2	7311.00	27.96	23.25	16.62	37.32	49.23	74.00	-24.77	Peak
3	9534.00	28.61	19.59	16.92	38.03	45.93	74.00	-28.07	Peak
4	10809.00	28.88	18.44	17.13	39.39	46.08	74.00	-27.92	Peak
5	11744.00	28.97	18.59	17.31	39.66	46.59	74.00	-27.41	Peak
6	14090.00	29.41	14.52	19.43	43.00	47.54	74.00	-26.46	Peak

802.11g 2462MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.33	12.28	33.23	50.28	74.00	-23.72	Peak
2	7386.00	27.98	23.25	16.62	37.36	49.25	74.00	-24.75	Peak
3	9466.00	28.59	21.96	16.92	37.96	48.25	74.00	-25.75	Peak
4	10911.00	28.89	20.40	17.15	39.45	48.11	74.00	-25.89	Peak
5	12424.00	29.08	20.83	17.73	39.49	48.97	74.00	-25.03	Peak
6	14107.00	29.42	16.07	19.43	42.90	48.98	74.00	-25.02	Peak

802.11g 2462MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.66	12.28	33.23	50.61	74.00	-23.39	Peak
2	7386.00	27.98	23.12	16.62	37.36	49.12	74.00	-24.88	Peak
3	9364.00	28.54	16.67	16.91	37.83	42.87	74.00	-31.13	Peak
4	10826.00	28.88	15.22	17.13	39.40	42.87	74.00	-31.13	Peak
5	12730.00	29.15	15.74	17.99	40.06	44.64	74.00	-29.36	Peak
6	13920.00	29.38	11.96	19.27	43.42	45.27	74.00	-28.73	Peak

802.11n(HT20) 2412MHz Vertical polarizations

		Preamp	Read	CableAntenna			Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	33.57	12.01	32.99	51.07	74.00	-22.93	Peak
2	7236.00	27.95	23.36	16.61	37.30	49.32	74.00	-24.68	Peak
3	8599.00	28.28	20.66	16.79	36.92	46.09	74.00	-27.91	Peak
4	11404.00	28.94	18.53	17.25	39.82	46.66	74.00	-27.34	Peak
5	13563.00	29.31	14.47	18.85	43.07	47.08	74.00	-26.92	Peak
6	14379.00	29.46	14.80	19.61	41.30	46.25	74.00	-27.75	Peak

802.11n(HT20) 2412MHz Horizontal polarizations

		Preamp	Read	CableAntenna			Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	33.32	12.01	32.99	50.82	74.00	-23.18	Peak
2	7236.00	27.95	22.71	16.61	37.30	48.67	74.00	-25.33	Peak
3	8276.00	28.18	21.01	16.72	36.62	46.17	74.00	-27.83	Peak
4	9840.00	28.74	17.87	16.95	38.28	44.36	74.00	-29.64	Peak
5	11676.00	28.97	19.04	17.30	39.73	47.10	74.00	-26.90	Peak
6	13478.00	29.29	12.72	18.75	42.92	45.10	74.00	-28.90	Peak

802.11n(HT20) 2437MHz Vertical polarizations

		Preamp	Read	CableAntenna			Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.45	12.14	33.11	51.17	74.00	-22.83	Peak
2	7311.00	27.96	23.04	16.62	37.32	49.02	74.00	-24.98	Peak
3	8650.00	28.29	18.62	16.80	36.98	44.11	74.00	-29.89	Peak
4	10435.00	28.84	17.58	17.05	39.09	44.88	74.00	-29.12	Peak
5	13223.00	29.24	14.17	18.46	41.73	45.12	74.00	-28.88	Peak
6	14073.00	29.41	12.73	19.41	43.10	45.83	74.00	-28.17	Peak

802.11n(HT20) 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	33.76	12.14	33.11	51.48	74.00	-22.52	Peak
2	7311.00	27.96	23.65	16.62	37.32	49.63	74.00	-24.37	Peak
3	8395.00	28.22	18.05	16.75	36.72	43.30	74.00	-30.70	Peak
4	10571.00	28.86	16.07	17.08	39.24	43.53	74.00	-30.47	Peak
5	12934.00	29.19	16.96	18.15	40.54	46.46	74.00	-27.54	Peak
6	15246.00	29.59	17.27	20.16	38.45	46.29	74.00	-27.71	Peak

802.11n(HT20) 2462MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.14	12.28	33.23	50.09	74.00	-23.91	Peak
2	7386.00	27.98	23.33	16.62	37.36	49.33	74.00	-24.67	Peak
3	8854.00	28.35	15.87	16.85	37.22	41.59	74.00	-32.41	Peak
4	10622.00	28.86	16.03	17.09	39.27	43.53	74.00	-30.47	Peak
5	12288.00	29.06	16.39	17.61	39.46	44.40	74.00	-29.60	Peak
6	13546.00	29.31	13.32	18.83	43.05	45.89	74.00	-28.11	Peak

802.11n(HT20) 2462MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	CableAntenna Loss	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	32.99	12.28	33.23	50.94	74.00	-23.06	Peak
2	7386.00	27.98	23.32	16.62	37.36	49.32	74.00	-24.68	Peak
3	9347.00	28.54	15.30	16.91	37.81	41.48	74.00	-32.52	Peak
4	12169.00	29.03	13.09	17.52	39.43	41.01	74.00	-32.99	Peak
5	13682.00	29.34	8.89	19.00	43.18	41.73	74.00	-32.27	Peak
6	15467.00	29.62	15.54	20.29	38.41	44.62	74.00	-29.38	Peak

802.11n(HT40) 2422MHz Vertical polarizations

	Freq	Preamplifier	Read	Cable	Antenna	Level	Limit	Over	Remark
	MHz	Factor	Level	Loss	Factor	Level	Line	Limit	
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4844.00	27.51	32.75	12.05	33.03	50.32	74.00	-23.68	Peak
2	7266.00	27.95	22.92	16.61	37.31	48.89	74.00	-25.11	Peak
3	9126.00	28.45	16.12	16.89	37.54	42.10	74.00	-31.90	Peak
4	10452.00	28.85	15.79	17.06	39.12	43.12	74.00	-30.88	Peak
5	12985.00	29.20	14.45	18.20	40.66	44.11	74.00	-29.89	Peak
6	14226.00	29.43	10.82	19.51	42.20	43.10	74.00	-30.90	Peak

802.11n(HT40) 2422MHz Horizontal polarizations

	Freq	Preamplifier	Read	Cable	Antenna	Level	Limit	Over	Remark
	MHz	Factor	Level	Loss	Factor	Level	Line	Limit	
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4844.00	27.51	32.41	12.05	33.03	49.98	74.00	-24.02	Peak
2	7266.00	27.95	22.25	16.61	37.31	48.22	74.00	-25.78	Peak
3	9330.00	28.53	15.74	16.91	37.79	41.91	74.00	-32.09	Peak
4	11251.00	28.93	14.69	17.22	39.70	42.68	74.00	-31.32	Peak
5	13478.00	29.29	9.24	18.75	42.92	41.62	74.00	-32.38	Peak
6	15909.00	29.69	13.11	20.58	39.97	43.97	74.00	-30.03	Peak

802.11n(HT40) 2437MHz Vertical polarizations

	Freq	Preamplifier	Read	Cable	Antenna	Level	Limit	Over	Remark
	MHz	Factor	Level	Loss	Factor	Level	Line	Limit	
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.90	12.14	33.11	49.62	74.00	-24.38	Peak
2	7311.00	27.96	22.33	16.62	37.32	48.31	74.00	-25.69	Peak
3	8616.00	28.28	16.35	16.79	36.94	41.80	74.00	-32.20	Peak
4	9483.00	28.59	14.27	16.92	37.98	40.58	74.00	-33.42	Peak
5	10435.00	28.84	15.58	17.05	39.09	42.88	74.00	-31.12	Peak
6	12968.00	29.19	11.71	18.18	40.62	41.32	74.00	-32.68	Peak

802.11n(HT40) 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Antenna Factor	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	32.46	12.14	33.11	50.18	74.00	-23.82	Peak
2	7311.00	27.96	22.55	16.62	37.32	48.53	74.00	-25.47	Peak
3	9058.00	28.42	15.28	16.88	37.46	41.20	74.00	-32.80	Peak
4	10333.00	28.83	14.12	17.03	38.93	41.25	74.00	-32.75	Peak
5	12288.00	29.06	13.39	17.61	39.46	41.40	74.00	-32.60	Peak
6	13359.00	29.27	9.07	18.63	42.37	40.80	74.00	-33.20	Peak

802.11n(HT40) 2452MHz Horizontal polarizations

		Preamp	Read	CableAntenna		Limit	Over		
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4904.00	27.55	32.49	12.23	33.19	50.36	74.00	-23.64	Peak
2	7356.00	27.97	22.98	16.62	37.34	48.97	74.00	-25.03	Peak
3	9908.00	28.77	15.78	16.96	38.33	42.30	74.00	-31.70	Peak
4	11438.00	28.94	15.33	17.25	39.85	43.49	74.00	-30.51	Peak
5	12628.00	29.13	15.07	17.90	39.82	43.66	74.00	-30.34	Peak
6	14209.00	29.43	11.95	19.49	42.30	44.31	74.00	-29.69	Peak

802.11n(HT40) 2452MHz Vertical polarizations

		Preamp	Read	Cable	Antenna		Limit	Over	
	Freq	Factor	Level	Loss	Factor	Level	Line	Limit	Remark
	MHz	dB	dBuV	dB	dB/m	dBuV/m	dBuV/m	dB	
1	4904.00	27.55	32.10	12.23	33.19	49.97	74.00	-24.03	Peak
2	7356.00	27.97	22.86	16.62	37.34	48.85	74.00	-25.15	Peak
3	10486.00	28.85	15.96	17.06	39.17	43.34	74.00	-30.66	Peak
4	12135.00	29.03	16.03	17.49	39.43	43.92	74.00	-30.08	Peak
5	13903.00	29.38	11.55	19.24	43.40	44.81	74.00	-29.19	Peak
6	14719.00	29.51	13.31	19.83	39.69	43.32	74.00	-30.68	Peak

Above 1GHz (PW600)

802.11b 2412MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	32.06	12.01	49.56	74.00	-24.44	Peak
2	7236.00	27.95	22.90	16.61	48.86	74.00	-25.14	Peak
3	8701.00	28.31	20.32	16.81	45.86	74.00	-28.14	Peak
4	10758.00	28.88	19.20	17.12	46.80	74.00	-27.20	Peak
5	13053.00	29.21	16.72	18.28	46.73	74.00	-27.27	Peak
6	15688.00	29.65	17.02	20.43	46.92	74.00	-27.08	Peak

802.11b 2412MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	31.75	12.01	49.25	74.00	-24.75	Peak
2	7236.00	27.95	23.06	16.61	49.02	74.00	-24.98	Peak
3	9245.00	28.50	23.40	16.90	49.49	74.00	-24.51	Peak
4	11149.00	28.92	19.39	17.20	47.29	74.00	-26.71	Peak
5	13036.00	29.21	19.57	18.26	49.48	74.00	-24.52	Peak
6	15603.00	29.64	19.02	20.39	48.56	74.00	-25.44	Peak

802.11b 2437MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.54	12.14	49.26	74.00	-24.74	Peak
2	7311.00	27.96	22.59	16.62	48.57	74.00	-25.43	Peak
3	9857.00	28.74	18.09	16.95	44.59	74.00	-29.41	Peak
4	11404.00	28.94	15.40	17.25	43.53	74.00	-30.47	Peak
5	12900.00	29.18	14.76	18.12	44.16	74.00	-29.84	Peak
6	16606.00	29.94	12.61	21.04	47.36	74.00	-26.64	Peak

802.11b 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.07	12.14	48.79	74.00	-25.21	Peak
2	7311.00	27.96	22.25	16.62	48.23	74.00	-25.77	Peak
3	9517.00	28.61	20.65	16.92	46.97	74.00	-27.03	Peak
4	11353.00	28.94	19.71	17.24	47.79	74.00	-26.21	Peak
5	13495.00	29.30	16.47	18.77	48.94	74.00	-25.06	Peak
6	15756.00	29.66	18.33	20.48	48.53	74.00	-25.47	Peak

802.11b 2462MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.57	12.28	49.52	74.00	-24.48	Peak
2	7386.00	27.98	22.89	16.62	48.89	74.00	-25.11	Peak
3	9891.00	28.76	19.21	16.96	45.73	74.00	-28.27	Peak
4	12424.00	29.08	19.14	17.73	47.28	74.00	-26.72	Peak
5	13886.00	29.38	14.91	19.22	48.13	74.00	-25.87	Peak
6	16504.00	29.90	14.39	20.98	48.87	74.00	-25.13	Peak

802.11b 2462MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.57	12.28	49.52	74.00	-24.48	Peak
2	7386.00	27.98	22.79	16.62	48.79	74.00	-25.21	Peak
3	8939.00	28.38	17.94	16.87	43.75	74.00	-30.25	Peak
4	11115.00	28.91	16.79	17.19	44.66	74.00	-29.34	Peak
5	13495.00	29.30	13.88	18.77	46.35	74.00	-27.65	Peak
6	16555.00	29.92	12.93	21.02	47.55	74.00	-26.45	Peak

802.11g 2412MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	31.51	12.01	49.01	74.00	-24.99	Peak
2	7236.00	27.95	22.79	16.61	48.75	74.00	-25.25	Peak
3	8565.00	28.27	19.71	16.78	45.10	74.00	-28.90	Peak
4	9857.00	28.74	18.61	16.95	45.11	74.00	-28.89	Peak
5	13189.00	29.24	14.46	18.42	45.21	74.00	-28.79	Peak
6	16113.00	29.75	14.07	20.71	46.05	74.00	-27.95	Peak

802.11g 2412MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4824.00	27.50	31.75	12.01	49.25	74.00	-24.75	Peak
2	7236.00	27.95	22.78	16.61	48.74	74.00	-25.26	Peak
3	9432.00	28.57	18.13	16.91	44.39	74.00	-29.61	Peak
4	11370.00	28.94	17.98	17.24	46.07	74.00	-27.93	Peak
5	14583.00	29.49	14.79	19.73	45.28	74.00	-28.72	Peak
6	16470.00	29.89	12.82	20.96	47.08	74.00	-26.92	Peak

802.11g 2437MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.93	12.14	49.65	74.00	-24.35	Peak
2	7311.00	27.96	22.31	16.62	48.29	74.00	-25.71	Peak
3	9075.00	28.43	19.61	16.88	45.54	74.00	-28.46	Peak
4	10588.00	28.86	19.28	17.08	46.75	74.00	-27.25	Peak
5	12968.00	29.19	17.73	18.18	47.34	74.00	-26.66	Peak
6	16164.00	29.77	13.94	20.75	46.25	74.00	-27.75	Peak

802.11g 2437MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4874.00	27.53	31.41	12.14	49.13	74.00	-24.87	Peak
2	7311.00	27.96	22.89	16.62	48.87	74.00	-25.13	Peak
3	9211.00	28.48	17.13	16.90	43.20	74.00	-30.80	Peak
4	10775.00	28.88	19.49	17.12	47.10	74.00	-26.90	Peak
5	13546.00	29.31	13.34	18.83	45.91	74.00	-28.09	Peak
6	16368.00	29.85	11.62	20.88	45.22	74.00	-28.78	Peak

802.11g 2462MHz Horizontal polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.63	12.28	49.58	74.00	-24.42	Peak
2	7386.00	27.98	22.74	16.62	48.74	74.00	-25.26	Peak
3	9466.00	28.59	21.96	16.92	48.25	74.00	-25.75	Peak
4	11336.00	28.93	18.19	17.23	46.26	74.00	-27.74	Peak
5	13920.00	29.38	13.96	19.27	47.27	74.00	-26.73	Peak
6	16504.00	29.90	14.44	20.98	48.92	74.00	-25.08	Peak

802.11g 2462MHz Vertical polarizations

	Freq	Preamp Factor	Read Level	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dB	dBuV/m	dBuV/m	dB	
1	4924.00	27.56	31.90	12.28	49.85	74.00	-24.15	Peak
2	7386.00	27.98	22.74	16.62	48.74	74.00	-25.26	Peak
3	9857.00	28.74	14.93	16.95	41.43	74.00	-32.57	Peak
4	12475.00	29.09	15.53	17.77	43.71	74.00	-30.29	Peak
5	15484.00	29.62	15.77	20.31	44.86	74.00	-29.14	Peak
6	17643.00	30.36	8.72	21.93	45.61	74.00	-28.39	Peak