

RF EXPOSURE EVALUATION

EUT Specification

EUT	37" HD Sound Bar + Wireless Subwoofer
Frequency band (Operating)	☒ WLAN: 2.403GHz ~ 2.475GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5.825GHz ☒ Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others _____
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	-4.30dBm(0.37mW) for BT2.1+EDR, 82.00 dBuV/m (-13.26dBm)(0.0472mW) for 2.4G
Antenna gain	0dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm²

P_{out} =output power to antenna in Mw

G = gain of antenna in linear scale

π =3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm ²)	Power density Limits (mW/cm ²)
Test mode: GFSK						
Low	2402	-5.44	±0.1	0.29	5.82e-5	1
Middle	2441	-5.82	±0.1	0.27	5.33e-5	1
High	2480	-5.62	±0.1	0.28	5.58e-5	1
Test mode: π/4-DQPSK						
Low	2402	-4.43	±0.1	0.37	7.34e-5	1
Middle	2441	-5.24	±0.1	0.31	6.09e-5	1
High	2480	-4.60	±0.1	0.35	7.06e-5	1
Test mode: 8DPSK						
Low	2402	-4.30	±0.1	0.38	7.56e-5	1
Middle	2441	-5.02	±0.1	0.32	6.41e-5	1
High	2480	-6.13	±0.1	0.25	4.96e-5	1

For 2.4G TX

Channel Frequency (MHz)	Max Output power (dBuv/m)	Max Output power (dBm)	Max Output power (mW)	Power density at 20cm (mW/ cm ²)	Power density Limits (mW/cm ²)
2403	75.12	-20.14	0.0097	1.93e-6	1
2442	78.11	-17.15	0.0193	3.83e-6	1
2475	82.00	-13.26	0.0472	9.39e-6	1

$$E = \text{EIRP} - 20\log D + 104.8$$

where:

E = electric field strength in dB μ V/m,

EIRP = equivalent isotropic radiated power in dBm

D = specified measurement distance in meters.

$$\text{EIRP} = E - 104.8 + 20\log D = \mathbf{82.00} - 104.8 + 20\log 3 = \mathbf{-13.26\text{dBm}}$$

For the device consider simultaneous transmission of BT and 2.4G, the worst
 $\text{MPE} = (7.56\text{e-}5) + (9.36\text{e-}6) = 8.496\text{e-}5\text{mW/ cm}^2 < 1\text{mW/ cm}^2$

According to KDB447498 D01 V06, no simultaneous SAR measurement is required.