

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net



Test Report

Product Name: 462 MHz Walkie Talkie - TX

FCC ID: R5E0401

Applicant:

**Good Faith Industries Ltd.
Unit 2603, 113 Argyle St.
MongKok Kln.
Hong Kong**

Date Receipt: 05/13/2004

Date Tested: 06/25/2004

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

TABLE OF CONTENTS

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT CONTAINING:

PAGE 1.....TEST EQUIPMENT LIST
PAGE 2.....TEST PROCEDURE
PAGE 3-5.....RADIATION INTERFERENCE TEST DATA
PAGE 6.....OCCUPIED BANDWIDTH
PAGE 7.....OCCUPIED BANDWIDTH PLOT

EXHIBITS CONTAINING:

PAGE 1.....FCC ID LABEL SAMPLE
PAGE 2.....SKETCH OF FCC ID LABEL LOCATION
PAGE 3.....BLOCK DIAGRAM
PAGE 4.....SCHEMATIC
PAGE 5A-5C.....PARTS LIST
PAGE 6A-6D.....INSTRUCTION MANUAL

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

TABLE OF CONTENTS

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER
197-22,GURO-DONG GURO-GU SEOUL KOREA
81221095059F81221095056 email thrukang@kornet.net

Test Equipment List

DEVICE	MODEL	MFGR	SERNO	DUE .CAL
EMI Test Receiver	ESVS 10	Rohde & Schwarz	830489/001	2005.04.07.
Spectrum Analyzer	8566B	Hewlett Packard	2311A02394	2005.04.07.
Spectrum Display	85662A	Hewlett Packard	2542A12429	2005.04.07.
Quasi-Peak Adapter	85650A	Hewlett Packard	2521A00887	2005.04.07.
RF Preselector	85685A	Hewlett Packard	2648A00504	2005.04.07.
Pre-Amplifier	8449B	Hewlett Packard	3008A00375	2005.04.07.
Pre-Amplifier	8447F	Hewlett Packard	3113A05367	2005.04.07.
Spectrum Monitor	EZM	Rohde & Schwarz	862304/007	2005.04.07.
Bico-Antenna	94455-1	Eaton	977	2005.03.17.
Log-Periodic Antenna	3146	EMCO	2051	2005.03.17.
Dipole Antenna	TDA25/1/2	Electro Metrics	176/200/200	2005.03.17.
Horn Antenna	SAS-571	A.H Systems	414	2005.03.17.
Spectrum Analyzer	R3261C	Advantest	71720189	2005.04.07.
LISN	KNW-242	Kyoritsu	8-923-2	2004.07.17.
LISN	8012-50-R-24	Solar	8379121	2004.07.17.
Loop Ant	6507	EMCO	1435	2004.10.06.
Signal Generator	SMS	Rohde & Schwarz	872165/100	2005.04.07.
Modulation Analyzer	8901B	Hewlett Packard	3438A05094	2005.04.07.
Frequency Counter	CMC251	Tektronic	CMC-251TW52489	2005.04.07.

APPLICANT: Good Faith Industries Ltd.
FCC ID: R5E0401
REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22, GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

TEST PROCEDURES

GENERAL: This report shall NOT be reproduced except in full without the written approval of THRU Lab & ENGINEERING.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz. The ambient temperature of the UUT was 27°C with a humidity of 60%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF = FS

33 20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

Not Applicable, battery operated.

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NO. 15.109(a) and 15.209

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 2400/F (kHz) AT 300 METERS

OUT-OF-BAND EMISSIONS SHALL NOT EXCEED THE LEVEL OF THE FUNDAMENTAL.

9 to 490 KHz: 2400/F (kHz) uV/m @ 300 METERS
490 to 1705 KHz: 24000/F(kHz) uV/m @ 30 METERS
1705 to 30 MHz: 29.54 dBuV/M @ 30 METERS
30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
88 to 216 MHz: 43.50 dBuV/M
216 to 960 MHz: 46.02 dBuV/M
ABOVE 960 MHz: 54.00 dBuV/M

TEST

CONFIGURATION: The INTENTIONAL RADIATOR was connected to an ignition switch and a harness simulator cable box. The device was tested in both transmitting modes.

TEST DATA:

No	Emission Frequency (MHz)	Meter Reading dBuV	Ant. Polaritry	Correction Factor dB	Cable Loss dB	Field Strength (dBuv/m)	Margin (dBuv)	Limit (dBuv/m)
1	462.37	6.5	H	18.6	4.7	29.7	-16.3	46.0

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

NAME OF TEST: RADIATION INTERFERENCE CONTD.

RULES PART NO. 15.109(a) and 15.209

REQUIREMENTS: CARRIER FREQUENCY WILL NOT EXCEED 2400/F (kHz) AT 300 METERS

OUT-OF-BAND EMISSIONS SHALL NOT EXCEED THE LEVEL OF THE FUNDAMENTAL.

9 to 490 KHz: 2400/F (kHz) uV/m @ 300 METERS
490 to 1705 KHz: 24000/F(kHz) uV/m @ 30 METERS
1705 to 30 MHz: 29.54 dBuV/M @ 30 METERS
30 to 88 MHz: 40.00 dBuV/M @ 3 METERS
88 to 216 MHz: 43.50 dBuV/M
216 to 960 MHz: 46.02 dBuV/M
ABOVE 960 MHz: 54.00 dBuV/M

TEST

CONFIGURATION: The INTENTIONAL RADIATOR was connected to an ignition switch and a harness simulator cable box. The device was tested in both transmitting modes.

TEST DATA:

No	Emission Frequency (MHz)	Meter Reading dBuV	Ant. Polarity	Correction Factor dB	Cable Loss dB	Field Strength (dBuV/m)	Margin (dBuV)	Limit (dBuV/m)
1	462.37	16.5	V	18.6	4.7	39.7	-6.3	46.0
2	924.65	4.1	V	23.2	7.4	34.6	-5.1	39.7

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

NAME OF TEST: RADIATION INTERFERENCE CONTD.

RULES PART NO. 15.109(a) and 15.209

The spectrum was scanned from 10 kHz to 1000 MHz.

SAMPLE CALCULATION: $FSdBuV/m = MR (dBuV) + ACFdB$.

TEST PROCEDURE: The procedure used was ANSI C63.4-1992 Section 8.2. The frequency was scanned from 9.0 kHz to 1.0 GHz. When an emission was found, the table was rotated to produce the maximum signal strength. The EUT was measured in three (3) orthogonal planes. The unit was measured at ThruLab & Engineering 389 Jeam-Rhi HyangNam-Myum HwaSung Kyoungki-do Korea

TEST RESULTS: THE UNIT DOES MEET THE FCC REQUIREMENTS.

PERFORMED BY: K.M Choi

DATE: 06/25/04

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N

THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

NAME OF TEST: Occupied Bandwidth

RULES PART NO.: 15.209

REQUIREMENTS: The field strength of any emissions appearing between the band edges and up to 10 kHz above and below the band edges shall be attenuated at least 26 dB below the level of the unmodulated carrier or to the general limits of 15.209, whichever permits the higher emission levels.

THE GRAPH ON THE FOLLOWING PAGE REPRESENTS THE EMISSIONS TAKEN FOR THE DEVICE.

METHOD OF MEASUREMENT: A small sample of the transmitter output was fed into the spectrum analyzer and the above photo was taken. The vertical scale is set to 10 dB per division. The horizontal scale is set to 10 kHz per division.

TEST RESULTS: The unit DOES meet the FCC requirements.

PERFORMED BY: K.M Choi

DATE: 06/25/04

APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N


THRU Lab & Engineering.

RM1105,11FL, ACE TECHNO TOWER

197-22,GURO-DONG GURO-GU SEOUL KOREA

81221095059F81221095056 email thrukang@kornet.net

OCCUPIED BANDWIDTH PLOT GOES HERE



APPLICANT: Good Faith Industries Ltd.

FCC ID: R5E0401

REPORT #: THRU-406007N