

FCC PART 15.247

TEST REPORT

For

Onglory Rich Limited

Room 208A, 2/F Unit A, 2 Chong Yip Street, Meyer Industrial Building, Kuwn Tong, Kowloon,
Hong Kong

FCC ID: R6DTL700

Report Type: Original Report	Product Type: Mobile phone
Test Engineer: Leon Chen <i>leon chen</i>	
Report Number: R1DG121116004-00A	
Report Date: 2012-11-29	
Reviewed By: Ivan Cao <i>Ivan Cao</i> EMC Engineer	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EUT EXERCISE SOFTWARE	6
EQUIPMENT MODIFICATIONS	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (I) AND §2.1093 – RF EXPOSURE	9
APPLICABLE STANDARD	9
TEST RESULT	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY.....	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST RESULTS SUMMARY	12
TEST DATA	12
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	15
APPLICABLE STANDARD	15
MEASUREMENT UNCERTAINTY.....	15
EUT SETUP	15
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	16
TEST PROCEDURE	16
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST EQUIPMENT LIST AND DETAILS.....	23
TEST DATA	23
FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER	28
APPLICABLE STANDARD	28

TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS.....	28
TEST DATA	28
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	33
FCC §15.247(e) - POWER SPECTRAL DENSITY	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST EQUIPMENT LIST AND DETAILS.....	36
TEST DATA	36

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Onglory Rich Limited's* product, model number: *TL700 (FCC ID: R6DTL700)* (the "EUT") in this report was a *Mobile phone*, which was measured approximately: 12.5 cm (L) x 7.0 cm (W) x 1.5 cm (H), rated input voltage: DC 3.7 V from battery or DC 5V form adapter.

Adapter information: Tonino
Model No: HB12-050100SPA
Input: AC 100-250V, 50/60Hz
Output: AC 100-250V, 50/60Hz or DC 5V

Product function:
GSM and GPRS Multi-slot class 10
Bluetooth:v2.1+EDR
Wifi:802.11b/g

The Operating Frequency Range:
GSM850: 824 ~ 849 MHz (TX), 869 ~ 894 MHz (RX);
DCS1900: 1850 ~ 1910 MHz (TX), 1930 ~ 1990 MHz (RX);
Wi-Fi: 2412~2462 MHz (TX/RX);
Bluetooth: 2402 ~ 2480 MHz (TX/RX)

** All measurement and test data in this report was gathered from production sample serial number: 121116004 (Assigned by BACL.Dongguan). The EUT was received on 2012-11-19.*

Objective

This report is prepared on behalf of *Onglory Rich Limited* accordance with Part 2-Subpart J, Part 15-Subparts A, B and C of the Federal Communication Commissions rules.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 22H&24E PCE submissions with FCC ID: *R6DTL700*.
FCC Part 15B JBP submissions with FCC ID: *R6DTL700*
FCC Part 15C DDS submissions with FCC ID: *R6DTL700* for Bluetooth.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

The uncertainty of any RF tests which use conducted method measurement is ± 0.96 dB, the uncertainty of any radiation on emissions measurement is ± 4.0 dB

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 02, 2012. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing at testing mode, which was provided by manufacturer. For 802.11b and 802.11g, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

EUT for 802.11b, 802.11g modes were tested with Channel 1, 6 and 11.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.


EUT Exercise Software

No EUT Exercise Software

Equipment Modifications

No modification was made to the EUT tested.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307(b) (1), §2.1093	RF Exposure (SAR)	Compliance*
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Peak Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Note: * Please refer to SAR report released by BACL, report number: R1DG121116004-20

FCC §15.247 (I) AND §2.1093 – RF EXPOSURE

Applicable Standard

FCC§15.247 (I)§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R1DG121116004-20

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has an internal antenna, which was complied with 15.203, the maximum gain is -1 dBi, please refer to the internal photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard


FCC§15.207

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at Bay Area Compliance Laboratory Corp. (Dongguan) is ± 2.4 dB ($k=2$, 95% level of confidence), and the uncertainty will not be taken into consideration for all the test data recorded in the report.

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

<u>Frequency Range</u>	<u>IF B/W</u>
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the first LISN and the other support equipments were connected to the outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2012-10-08	2013-10-07
R&S	LISN1	ESH3-Z5	843331/015	2012-09-17	2013-09-16
R&S	LISN2	ESH3-Z5	100113	2012-10-08	2013-10-07

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

4.62 dB at 0.420 MHz in the **Line** conducted mode.

Test Data


Environmental Conditions

Temperature:	23.2 ° C
Relative Humidity:	56 %
ATM Pressure:	101.0kPa


The testing was performed by Leon Chen on 2012-11-28.

Test Mode: Transmitting

AC 120V/60 Hz, Line



Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.160	55.06	0.45	65.71	10.65	AV
0.160	27.65	0.45	55.71	28.06	QP
0.255	50.01	0.37	63.00	12.99	AV
0.255	24.88	0.37	53.00	28.12	AV
0.305	49.11	0.34	61.57	12.46	AV
0.305	31.28	0.34	51.57	20.29	QP
0.345	49.04	0.34	60.43	11.39	QP
0.345	27.43	0.34	50.43	23.00	AV
0.420	53.67	0.32	58.29	4.62	QP
0.420	40.65	0.32	48.29	7.64	QP
0.485	46.52	0.31	56.43	9.91	AV
0.485	28.56	0.31	46.43	17.87	QP

AC 120V/60 Hz, Neutral

Frequency (MHz)	Cord. Reading (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/AV/QP)
0.180	58.48	0.24	65.14	6.66	AV
0.180	40.20	0.24	55.14	14.94	QP
0.235	52.55	0.24	63.57	11.02	AV
0.235	35.50	0.24	53.57	18.07	AV
0.365	51.25	0.23	59.86	8.61	QP
0.365	30.44	0.23	49.86	19.42	AV
0.420	53.13	0.22	58.29	5.16	AV
0.420	36.51	0.22	48.29	11.78	QP
0.445	39.06	0.22	57.57	18.51	QP
0.445	25.34	0.22	47.57	22.23	AV
1.380	50.14	0.25	56.00	5.86	QP
1.380	34.54	0.25	46.00	11.46	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;


Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.


Based on CISPR 16-4-4, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at Bay Area Compliance Laboratories Corp. (Dongguan) is 4.0 dB(k=2, 95% level of confidence) , and the uncertainty will not be taken into consideration for all the test data recorded in the report.

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

<u>Frequency Range</u>	<u>RBW</u>	<u>Video B/W</u>	<u>Detector</u>
30 MHz – 1000 MHz	100 kHz	300 kHz	QP
1000 MHz – 25 GHz	1 MHz	3 MHz	PK
1000 MHz – 25 GHz	1 MHz	10 Hz	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100035	2012-05-14	2013-05-13
Sunol Sciences	Hybrid Antennas	JB3	A060611-1	2011-09-06	2013-09-05
HP	Pre-amplifier	8447E	2434A02181	2012-10-08	2013-10-07
R&S	Spectrum Analyzer	FSEM 30	DE31388	2012-03-15	2013-03-14
ETS-LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2014-09-05
Mini-Circuits	Wideband Amplifier	ZVA-183-S+	96901149	N/A	N/A

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

10.20 dB at 436.82 MHz in the Horizontal polarization (802.11b mode)

Test Data**Environmental Conditions**

Temperature:	25.8 ° C
Relative Humidity:	57 %
ATM Pressure:	100.1kPa

The testing was performed by Leon Chen on 2012-11-22.


Mode: Transmitting

802.11b Mode:


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	FCC 15.247	
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB(1/m))				Limit (dBμV/m)	Margin (dB)
Low Channel:2412MHz									
2412	49.5	AV	H	25.67	3.93	0.00	79.10	N/A	N/A
2412	62.22	PK	H	25.67	3.93	0.00	91.82	N/A	N/A
2412	49.58	AV	V	25.67	3.93	0.00	79.18	N/A	N/A
2412	61.63	PK	V	25.67	3.93	0.00	91.23	N/A	N/A
436.38	38.23	QP	H	16.91	2.50	21.86	35.78	46.00	10.22
2390	14.1	AV	H	25.61	3.84	0.00	43.55	54.00	10.45
4824	30.99	AV	H	30.64	4.73	27.19	39.17	54.00	14.83
2390	29.17	PK	H	25.61	3.84	0.00	58.62	74.00	15.38
9648	18.13	AV	V	36.06	8.70	26.43	36.46	54.00	17.54
4824	45.05	PK	H	30.64	4.73	27.19	53.23	74.00	20.77
7236	18.86	AV	H	34.17	6.56	26.58	33.01	54.00	20.99
6963.3	18.89	AV	V	33.50	6.06	26.31	32.14	54.00	21.86
9648	32.33	PK	V	36.06	8.70	26.43	50.66	74.00	23.34
7236	33.21	PK	H	34.17	6.56	26.58	47.36	74.00	26.64
6963.3	33.37	PK	V	33.50	6.06	26.31	46.62	74.00	27.38
Middle Channel:2437MHz									
2437	50.13	AV	H	25.74	3.98	0.00	79.85	N/A	N/A
2437	62.19	PK	H	25.74	3.98	0.00	91.91	N/A	N/A
2437	46.91	AV	V	25.74	3.98	0.00	76.63	N/A	N/A
2437	59.2	PK	V	25.74	3.98	0.00	88.92	N/A	N/A
436.25	38.12	QP	H	16.91	2.50	21.86	35.67	46.00	10.33
9748	18.3	AV	V	36.30	8.60	26.53	36.67	54.00	17.33
4874	25.89	AV	H	30.77	4.76	27.03	34.39	54.00	19.61
7727.4	18.13	AV	V	34.98	7.22	26.78	33.55	54.00	20.45
7311	18.32	AV	H	34.35	6.70	26.65	32.72	54.00	21.28
6966.9	18.4	AV	V	33.51	6.06	26.31	31.66	54.00	22.34
9748	32.12	PK	V	36.30	8.60	26.53	50.49	74.00	23.51
7727.4	33.72	PK	V	34.98	7.22	26.78	49.14	74.00	24.86
4874	40.04	PK	H	30.77	4.76	27.03	48.54	74.00	25.46
7311	32.98	PK	H	34.35	6.70	26.65	47.38	74.00	26.62
6966.9	33.38	PK	V	33.51	6.06	26.31	46.64	74.00	27.36
High Channel:2462MHz									
2462	49.57	AV	H	25.80	3.93	0.00	79.30	N/A	N/A
2462	62.34	PK	H	25.80	3.93	0.00	92.07	N/A	N/A
2462	49.94	AV	V	25.80	3.93	0.00	79.67	N/A	N/A
2462	61.98	PK	V	25.80	3.93	0.00	91.71	N/A	N/A
436.82	38.24	QP	H	16.92	2.50	21.86	35.80	46.00	10.20
2483.5	13.54	AV	H	25.86	3.80	0.00	43.20	54.00	10.80
2483.5	27.77	PK	H	25.86	3.80	0.00	57.43	74.00	16.57
9848	18.19	AV	V	36.54	8.49	26.63	36.59	54.00	17.41
4924	26.02	AV	H	30.90	4.70	27.17	34.45	54.00	19.55
7386	18.18	AV	H	34.53	6.84	26.73	32.82	54.00	21.18
6987.9	18.41	AV	V	33.57	6.09	26.32	31.75	54.00	22.25
9848	33.12	PK	V	36.54	8.49	26.63	51.52	74.00	22.48
4924	40.81	PK	H	30.90	4.70	27.17	49.24	74.00	24.76
7386	33.22	PK	H	34.53	6.84	26.73	47.86	74.00	26.14
6987.9	33.19	PK	V	33.57	6.09	26.32	46.53	74.00	27.47

802.11g Mode:


Frequency	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBµV/m)	FCC 15.247	
(MHz)	Reading (dBµV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB(1/m))				Limit (dBµV/m)	Margin (dB)
Low Channel:2412MHz									
2412	34.2	AV	H	25.67	3.93	0.00	63.80	N/A	N/A
2412	57.17	PK	H	25.67	3.93	0.00	86.77	N/A	N/A
2412	32.61	AV	V	25.67	3.93	0.00	62.21	N/A	N/A
2412	55.63	PK	V	25.67	3.93	0.00	85.23	N/A	N/A
2390	14.17	AV	H	25.61	3.84	0.00	43.62	54.00	10.38
436.59	37.26	QP	H	16.92	2.50	21.86	34.82	46.00	11.18
9648	18.12	AV	V	36.06	8.70	26.43	36.45	54.00	17.55
2390	24.74	PK	H	25.61	3.84	0.00	54.19	74.00	19.81
7236	18.86	AV	H	34.17	6.56	26.58	33.01	54.00	20.99
6963.3	18.24	AV	V	33.50	6.06	26.31	31.49	54.00	22.51
9648	32.42	PK	V	36.06	8.70	26.43	50.75	74.00	23.25
4824	19.23	AV	H	30.64	4.73	27.19	27.41	54.00	26.59
7236	32.84	PK	H	34.17	6.56	26.58	46.99	74.00	27.01
6963.3	33.16	PK	V	33.50	6.06	26.31	46.41	74.00	27.59
4824	33.69	PK	H	30.64	4.73	27.19	41.87	74.00	32.13
Middle Channel:2437MHz									
2437	34.63	AV	H	25.74	3.98	0.00	64.35	N/A	N/A
2437	57.84	PK	H	25.74	3.98	0.00	87.56	N/A	N/A
2437	32.14	AV	V	25.74	3.98	0.00	61.86	N/A	N/A
2437	55.49	PK	V	25.74	3.98	0.00	85.21	N/A	N/A
437.05	36.94	QP	H	16.93	2.50	21.86	34.51	46.00	11.49
9748	18.03	AV	V	36.30	8.60	26.53	36.40	54.00	17.60
7727.4	18.34	AV	V	34.98	7.22	26.78	33.76	54.00	20.24
7311	18.67	AV	H	34.35	6.70	26.65	33.07	54.00	20.93
6966.9	18.12	AV	V	33.51	6.06	26.31	31.38	54.00	22.62
9748	32.75	PK	V	36.30	8.60	26.53	51.12	74.00	22.88
4874	19.15	AV	H	30.77	4.76	27.03	27.65	54.00	26.35
7727.4	32.16	PK	V	34.98	7.22	26.78	47.58	74.00	26.42
7311	32.54	PK	H	34.35	6.70	26.65	46.94	74.00	27.06
6966.9	33.28	PK	V	33.51	6.06	26.31	46.54	74.00	27.46
4874	33.57	PK	H	30.77	4.76	27.03	42.07	74.00	31.93
High Channel:2462MHz									
2462	34.12	AV	H	25.80	3.93	0.00	63.85	N/A	N/A
2462	58.72	PK	H	25.80	3.93	0.00	88.45	N/A	N/A
2462	31.54	AV	V	25.80	3.93	0.00	61.27	N/A	N/A
2462	53.97	PK	V	25.80	3.93	0.00	83.70	N/A	N/A
2483.5	13.6	AV	H	25.86	3.80	0.00	43.26	54.00	10.74
435.92	37.12	QP	H	16.90	2.49	21.86	34.65	46.00	11.35
2483.5	27.44	PK	H	25.86	3.80	0.00	57.10	74.00	16.90
9848	18.52	AV	V	36.54	8.49	26.63	36.92	54.00	17.08
7386	18.23	AV	H	34.53	6.84	26.73	32.87	54.00	21.13
6987.9	18.34	AV	V	33.57	6.09	26.32	31.68	54.00	22.32
9848	32.16	PK	V	36.54	8.49	26.63	50.56	74.00	23.44
4924	19.45	AV	H	30.90	4.70	27.17	27.88	54.00	26.12
7386	32.69	PK	H	34.53	6.84	26.73	47.33	74.00	26.67
6987.9	33.02	PK	V	33.57	6.09	26.32	46.36	74.00	27.64
4924	33.26	PK	H	30.90	4.70	27.17	41.69	74.00	32.31

Conducted Spurious Emissions at Antenna Port**802.11b Low Channel**


Date: 22.NOV.2012 14:01:43

802.11b Middle Channel

Date: 22.NOV.2012 14:03:23

802.11b High Channel

Date: 22.NOV.2012 14:14:19

802.11g Low Channel

Date: 22.NOV.2012 14:35:58


Ref 21 dBm Att 30 dB RBW 100 kHz VBW 300 kHz SWT 2.5 s

Marker 1 [T1] -9.49 dBm 2.427120000 GHz

Marker 2 [T2] -43.09 dBm 24.300840000 GHz

Center 12.515 GHz 2.497 GHz/ Span 24.97 GHz

802.11g High Channel




Page 22 of 40

FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH**Applicable Standard**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-5-14	2013-5-13

Test Data**Environmental Conditions**

Temperature:	26.3 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1kPa


The testing was performed by Leon Chen on 2012-11-22.

Test Result: Pass.

Please refer to the following tables and plots.


Channel	Frequency	6 dB Bandwidth	Limit
	(MHz)	(MHz)	(kHz)
802.11b mode			
Low	2412	10.24	>500
Middle	2437	10.16	>500
High	2462	10.08	>500
802.11g mode			
Low	2412	16.8	>500
Middle	2437	16.8	>500
High	2462	16.8	>500

802.11b Low Channel




Date: 22.NOV.2012 13:58:30

802.11b Middle Channel




Date: 22.NOV.2012 14:05:26

802.11b High Channel




Date: 22.NOV.2012 14:08:12


802.11g Low Channel



Date: 22.NOV.2012 14:33:26

802.11g Middle Channel

Date: 22.NOV.2012 14:29:23

802.11g High Channel


Date: 22.NOV.2012 14:22:34

FCC §15.247(b) (3) - MAXIMUM PEAK OUTPUT POWER**Applicable Standard**

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to an EMI Test Receiver.
3. Add a correction factor to the display.

**Test Equipment List and Details**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-5-14	2013-5-13

Test Data**Environmental Conditions**

Temperature:	26.3 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1kPa

The testing was performed by Leon Chen on 2012-11-22.

Test Mode: Transmitting

Channel	Frequency	Conducted Output Power	Limit	Result
	(MHz)	(dBm)	(dBm)	
802.11b mode				
Low	2412 MHz	12.4	30	PASS
Middle	2437 MHz	12.19	30	PASS
High	2462 MHz	12.25	30	PASS
802.11g mode				
Low	2412 MHz	10.78	30	PASS
Middle	2437 MHz	10.51	30	PASS
High	2462 MHz	10.66	30	PASS

Please refer to the following plots


Ref 21 dBm Att 30 dB RBW 1 MHz VBW 3 MHz SWT 2.5 ms Marker 1 [21] 4.53 dBm 2.412432000 GHz

Offset 1 dB


Center 2.412 GHz 1.2 MHz/ Span 12 MHz

Tx Channel Bandwidth 10.24 MHz Power 12.40 dBm


802.11b RF Output Power, Middle Channel



Page 30 of 40


802.11b RF Output Power, High Channel

Date: 22.NOV.2012 14:08:42

802.11g RF Output Power, Low Channel


Date: 22.NOV.2012 14:32:27

802.11g RF Output Power, Middle Channel



Date: 22.NOV.2012 14:30:04

802.11g RF Output Power, High Channel



Date: 22.NOV.2012 14:24:35

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-5-14	2013-5-13

Test Data**Environmental Conditions**

Temperature:	26.3 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1kPa

The testing was performed by Leon Chen on 2012-11-22.

Test Result: Compliance

Please refer to following plots.

1 PK
SEARCH

Ref 21 dBm Att 30 dB
RBW 100 kHz Marker 4 [T1] -43.48 dBm
VEW 300 kHz
SWT 15 ms 2.397136000 GHz

20 Offset 1 dB

Marker 1 [T1] -2.01 dBm
2.410576000 GHz

Marker 2 [T1] -49.10 dBm
2.390000000 GHz

Marker 3 [T1] -5.15 dBm
2.400000000 GHz


D1 -2.01 dBm

D2 -22.01 dBm


F1 F2

Start 2.31 GHz 11.2 MHz/ Stop 2.422 GHz


802.11b: Band Edge, Right Side



Page 34 of 40

802.11g: Band Edge, Left Side

Date: 22.NOV.2012 14:35:33

802.11g: Band Edge, Right Side

Date: 22.NOV.2012 14:26:27

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT was set without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. According to KDB 558074 D01 DTS Meas Guidance v01, set the RBW = 100 kHz, VBW $\geq$ 300 kHz, set the span to 5-30 % greater than the EBW.
4. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.
5. Scale the observed power level to an equivalent value in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(3\text{ kHz}/100\text{ kHz}) = -15.2\text{ dB}$.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Spectrum Analyzer	FSP38	100478	2012-5-14	2013-5-13

Test Data

Environmental Conditions

Temperature:	26.3 ° C
Relative Humidity:	55 %
ATM Pressure:	100.1kPa

The testing was performed by Leon Chen on 2012-11-22.


Test Mode: Transmitting

Test Result: Pass

Channel	Reading Level	PSD	Limit	Result
	(dBm/100kHz)	(dBm/3kHz)	(dBm/3kHz)	
802.11b mode				
Low	-2.02	-17.22	8	PASS
Middle	-1.42	-16.62	8	PASS
High	-1.49	-16.69	8	PASS
802.11g mode				
Low	-8.57	-23.77	8	PASS
Middle	-9.02	-24.22	8	PASS
High	-9.04	-24.24	8	PASS


Please refer to the following plots

Power Spectral Density, 802.11b Low Channel




Date: 22.NOV.2012 13:59:28


Power Spectral Density, 802.11b Middle Channel



Date: 22.NOV.2012 14:04:17


Power Spectral Density, 802.11b High Channel

Date: 22.NOV.2012 14:09:19

Power Spectral Density, 802.11g Low Channel


Date: 22.NOV.2012 14:32:07

Power Spectral Density, 802.11g Middle Channel



Date: 22.NOV.2012 14:30:23

Power Spectral Density, 802.11g High Channel



Date: 22.NOV.2012 14:25:26

***** END OF REPORT *****