

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 95 SUBPART C REQUIREMENT**

OF

**Computer
Digital proportional radio control system**

MODEL No.: E8

BRAND NAME: N/A

FCC ID: R6R-ESKYSZ01

REPORT NO:SZE0405037

ISSUE DATE: JULY 12, 2004

Prepared for

**SHENZHEN ESKY TRADE CO.,LTD
NO.62,BURGHER PIAZZA,SHAJING TOWN,
BAOAN DIST,SHENZHEN,CHINA**

Prepared by

COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.

d.b.a.

**COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC.
NO. 6, JINAO INDUSTRIAL PARK, NO. 35 JUKENG ROAD,
DASHUIKENG VILLAGE, GUANLAN TOWN, BAOAN
DISTRICT, SHENZHEN, CHINA**

TEL: 86-755-28055000

FAX: 86-755-28055221

VERIFICATION OF COMPLIANCE

Applicant:	SHENZHEN ESKY TRADE CO.,LTD NO.62,BURGHHER PIAZZA,SHAJING TOWN, BAOAN DIST,SHENZHEN,CHINA
Product Description:	COMPUTER DIGITAL PROPORTIONAL RADIO CONTROL SYSTEM
Brand Name:	N/A
Model Number:	E8
Serial Number:	N/A
File Number:	SZE0405037
Date of Test:	May 20,2004 ~ July 11, 2004

We hereby certify that:

The above equipment was tested by COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in TIA/EIA 603 and the sample tested as described in this report is in compliance with the FCC Rules Part 95 Subpart C.

The test results of this report relate only to the tested sample identified in this report.

Approved By

Clinton Kao / Q.A. Manager
COMPLIANCE CERTIFICATION
SERVICES (SHENZHEN) INC.

Reviewed By

Jimmy
COMPLIANCE CERTIFICATION
SERVICES (SHENZHEN) INC.

Table of Contents

1.	GENERAL INFORMATION	5
1.1	PRODUCT DESCRIPTION.....	5
1.2	RELATED SUBMITTAL(S)/GRANT(S).....	5
1.3	TEST METHODOLOGY	5
1.4	TEST FACILITY	5
2.	SYSTEM TEST CONFIGURATION	6
2.1	EUT CONFIGURATION.....	6
2.2	EUT EXERCISE.....	6
2.3	GENERAL TECHNICAL REQUIREMENTS	6
2.4	CONFIGURATION OF TESTED SYSTEM	7
3.	SUMMARY OF TEST RESULTS	9
4.	DESCRIPTION OF TEST MODES	9
5.	AUTHORIZED OPERATION CHANNELS.....	10
6.	FREQUENCY TOLERANCE.....	11
6.1	PROVISIONS APPLICABLE.....	11
6.2	MEASUREMENT PROCEDURE.....	11
6.2.1	FREQUENCY STABILITY VERSUS ENVIRONMENTAL TEMPERATURE.....	11
6.2.2	FREQUENCY STABILITY VERSUS INPUT VOLTAGE.....	11
6.3	TEST SETUP BLOCK DIAGRAM.....	12
6.4	TEST RESULT.....	12
7.	EMISSION TYPE.....	13
7.1	PROVISIONS APPLICABLE.....	14
7.2	COMPLIANCE.....	14
8.	EMISSION BANDWIDTH.....	15
8.1	PROVISIONS APPLICABLE.....	15
8.2	MEASUREMENT PROCEDURE.....	15
8.3	TEST SETUP BLOCK DIAGRAM.....	15
8.4	MEASUREMENT EQUIPMENT USED.....	15
8.5	MEASUREMENT RESULT.....	15
9.	UNWANTED RADIATION.....	17
9.1	PROVISIONS APPLICABLE.....	17

9.2	MEASUREMENT PROCEDURE.....	17
9.3	TEST SETUP BLOCK DIAGRAM.....	18
9.4	MEASUREMENT EQUIPMENT USED.....	19
9.5	MEASUREMENT RESULTS.....	19
9.6	EMISSION MASK.....	20
10.	MODULATION STANDARDS.....	21
11.	MAXIMUM TRANSMITTER POWER.....	22
11.1	PROVISIONS APPLICABLE.....	22
11.2	MEASUREMENT PROCEDURE.....	22
11.3	TEST SETUP BLOCK DAIGRAM.....	23
11.4	MEASUREMENT EQUIPMENT USED.....	24
11.5	TEST RESULT.....	24
12.	TRANSMITTER ANTENNA.....	25
12.1	PROVISIONS APPLICABLE.....	25
12.2	COMPLIANCE.....	25
13.	POWER CAPABILITY.....	26
13.1	PROVISIONS APPLICABLE.....	26
13.2	COMPLIANCE.....	26
14.	CRYSTAL CONTROL REQUIRED.....	27
14.1	PROVISIONS APPLICABLE.....	27
14.2	COMPLIANCE.....	27
APPENDIX 1		
PHOTOGRAPHS OF SET UP.....		28
APPENDIX 2		
PHOTOGRAPHS OF EUT.....		30

1. GENERAL INFORMATION

1.1 Product Description

The ShenZhen Esky Trade Co.,Ltd. Model:E8 (referred to as the EUT in this report) The EUT is an short range, lower power, wireless Controller designed as an “ Output Device”. It is designed by way of utilizing the FM modulation achieves the system operating.

A major technical descriptions of EUT is described as following:

- A). Operation Frequency: 72.85 MHz
- B). Modulation: FM
- C). Emission type: F1D
- D). Emission designator: 1K82F1D
- E). Antenna Designation: Non-User Replaceable (Fixed)
- F). Power Supply: 12 Vdc by battery.

1.2 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: R6R-ESKYSZ01 filing to comply with the FCC Part 95, Subpart C Rules.

1.3 Test Methodology

The radiated emission testing was performed according to the procedures in TIA/EIA 603 and FCC CFR 47 2.1033, 2.1046, 2.1047, 2.1049, 2.1053, 2.1055 and 2.1057

1.4 Test Facility

The open area test site used to collect the radiated data is located on the address of COMPLIANCE CERTIFICATION SERVICES (SHENZHEN) INC. No. 6, Jinao industrial park, No.35 Jukeng Road, Dashuikeng Village, Guanlan Town, Baoan District, Shenzhen, China. The Open Area Test Site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4: 2001 and CISPR 22/EN 55022 requirements.

1.5 Special Accessories

Not available for this EUT intended for grant.

1.6 Equipment Modifications

Not available for this EUT intended for grant.

2. System Test Configuration

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

The Transmitter was operated in the normal operating mode. the TX frequency was fixed which was for the purpose of the measurements.

2.3 GENERAL TECHNICAL REQUIREMENTS

a). Section 95.207: Authorized operation channels: 72MHz-73MHz

b). Section 95.623 (c) : Frequency Tolerance less than 0.002%

c). Section 95.631 (b) : Transmit non-voice emission

d). Section 95.633 (b) : Emission Bandwidth shall less than 8KHz

e). Section 95.635: Unwanted radiation

According to Section 95.635(b), the power of each unwanted emission shall be less than Transmitted Power as specified below:

1). At least 25 db on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.

2). At least 45 db on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 125% of the authorized bandwidth.

3). At least 55 db on any frequency removed from the center of the authorized bandwidth by more than 125% up to and including 250% of the authorized bandwidth.

4). At least $56 + 10 \log_{10}(T)$ db on any frequency removed from the center of the authorized bandwidth by more than 250%.

f). Section 95.637: Not applicable for this R/C device.

g). Section 95.639: Maximum transmitter power less than 0.75W

h). Section 95.647: Antenna shall be a dedicate type

i). Section 95.649: Output power can't be change

j). Section 95.651: Crystal control required

2.4 Configuration of Tested System

Fig. 2-1 Configuration of Tested System




Table 2-1 Equipment Used in Tested System

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Series No.	Note
E-1	Computer Digital proportional radio control system	N/A	E8	R6R-ESKYSZ01	N/A	EUT

3. SUMMARY OF TEST RESULTS

FCC Rules	Description Of Test	Result
§ 95.207	Authorized operation channels	Compliant
§ 95.623	Frequency tolerance	Compliant
§ 95.631	Emission type	Compliant
§ 95.633	Emission bandwidth	Compliant
§ 95.635	Unwanted radiation	Compliant
§ 95.637	Modulation standard	N/A
§ 95.639	Maximum transmitter power	Compliant
§ 95.647	Transmitter antenna	Compliant
§ 95.649	Power capability	Compliant
§ 95.651	Crystal control required	Compliant

4. DESCRIPTION OF TEST MODES

1. The EUT (Computer Digital proportional radio control system) has been tested under normal operating condition
2. The EUT stay in continuous transmitting mode. Three axes (X,Y,Z) are chosen for testing.

5. AUTHORIZED OPERATION CHANNELS

5.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.207, the authorized operation channels for model aircrafts are located on the frequencies from 72.01 to 72.99 with the interval of 20KHz,

5.2 COMPLIANCE

The EUT designed as a model aircraft controller with the operation frequency on 72.85 MHz is absolutely in accordance with the requirement above.

6. FREQUENCY TOLERANCE

6.1 PROVISIONS APPLICABLE

- a). According to FCC Part 2 Section 2.1055(a)(1), the frequency stability shall be measured with variation of ambient temperature from -30 to +50 centigrade.
- b). According to FCC Part 2 Section 2.1055(d)(2), for hand carried battery powered equipment, the frequency stability shall be measured with reducing primary supply voltage to the battery operating end point, which is specified by the manufacture.
- c). According to FCC Part 95 Section 95.623(c), the frequency tolerance must be maintained within 0.002%.

6.2 MEASUREMENT PROCEDURE

6.2.1 Frequency stability versus environmental temperature

1. Setup the configuration per figure 1 for frequencies measurement inside an environment chamber, Install new battery in the EUT.
2. Turn on EUT and set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz and Frequency Span to 50KHz. Record this frequency as reference frequency.
3. Set the temperature of chamber to 50 . Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize. While maintaining a constant temperature inside the chamber, turn the EUT on and measure the EUT operating frequency.
4. Repeat step 2 with a 10 decreased per stage until the lowest temperature -30 is measured, record all measured frequencies on each temperature step.

6.2.2 Frequency stability versus input voltage

1. Setup the configuration per figure 1 for frequencies measured at temperature if it is within 15 to 25 . Otherwise, an environment chamber set for a temperature of 20 shall be used. Install new battery in the EUT.
2. Set SA center frequency to the EUT radiated frequency. Set SA Resolution Bandwidth to 1KHz and Video Resolution Bandwidth to 1KHz. Record this frequency as reference frequency.
3. For battery operated only device, supply the EUT primary voltage at the operating end point which is specified by manufacturer and record the frequency.

6.3 TEST SETUP BLOCK DIAGRAM(block diagram of configuration)




Figure 1

7 Test equipment used:

Equipment	Model No.	Serial No.	Cal. Due.
Advantest Spectrum Analyzer	R3132	120901472	06/07/2005
Shihin Temperature Chamber	BM50-CB	908	06/29/2005
DC Power Supply	WYK-605	N/A	05/29/2005
Huber + suhner low loss cable	N/A	N/A	06/07/2005
Monopole Antenna	N/A	N/A	N/A

6.4 TEST RESULT

a. Frequency stability versus input voltage (battery operation end point voltage is 10.3V)

Reference Frequency (MHz)	Frequency Measured at end point voltage	Frequency Deviation (%)	Limit (%)
72.85025	72.850450	0.000275	0.002

b. Frequency stability versus ambient temperature

Reference Frequency:72.85025 MHz			Limit: $\pm 0.002\%$
Environment Temperature ()	Power Supply	Frequency deviation measured with time Elapse (10 minutes)	
		(MHz)	%
50	New Battery	72.85001	-0.00033
40	New Battery	72.85015	-0.00014
30	New Battery	72.85025	0.00000
20	New Battery	72.85025	0.00000
10	New Battery	72.85027	0.00003
0	New Battery	72.85032	0.00010
-10	New Battery	72.85037	0.00016
-20	New Battery	72.85046	0.00029
-30	New Battery	72.85055	0.00041

7. EMISSION TYPE

7.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.631(b) : An R/C transmitter may transmit any appropriate non-voice emission which meets the emission limitations of § 95.633.

7.2 COMPLIANCE

The EUT is solely used to control model aircraft without transmitting any voice emission and it has been tested to comply with the emission limitation of § 95.633.

8. EMISSION BANDWIDTH


8.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.633 (b): The authorized bandwidth for any emission type transmitted by an R/C transmitter is 8 KHz.

8.2 MEASUREMENT PROCEDURE

- 1). The EUT was placed on a turn table which is 0.8m above ground plane.
- 2). Set EUT as normal operation
- 3). Set SPA Center Frequency = fundamental frequency , RBW,VBW= 1KHz, Span =50KHz.
- 4). Set SPA Max hold. Mark peak, -26dB.

8.3 TEST SETUP BLOCK DIAGRAM (Block Diagram of Configuration)



8.4 MEASUREMENT EQUIPMENT USED:


Open Area Test Site # 3					
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUMBER	LAST CAL.	CAL DUE.
Spectrum Analyzer	ADVANTEST	R3132	120901472	06/08/2004	06/07/2005
EMI Test Receiver	HP	8546A	3448A00232	06/08/2004	06/07/2005
Pre-Amplifier	HP	8447D	2944A07999	06/08/2004	06/07/2005
Bi-log Antenna	EMCO	3142	9910-1436	06/08/2004	05/07/2005

8.5 MEASUREMENT RESULT:

26dB bandwidth = 7.65 KHz.

Refer to attached data chart.

26 db bandwidth test data



9. UNWANTED RADIATION

9.1 PROVISIONS APPLICABLE

According to Section 95.635(b), the power of each unwanted emission shall be less than Transmitted Power as specified below:

- 1). At least 25 db on any frequency removed from the center of the authorized bandwidth by more than 50% up to and including 100% of the authorized bandwidth.
- 2). At least 45 db on any frequency removed from the center of the authorized bandwidth by more than 100% up to and including 125% of the authorized bandwidth.
- 3). At least 55 db on any frequency removed from the center of the authorized bandwidth by more than 125% up to and including 250% of the authorized bandwidth.
- 4). At least $56 + 10 \log_{10} (TP)$ db on any frequency removed from the center of the authorized bandwidth by more than 250%.

9.2 MEASUREMENT PROCEDURE

- 1). On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- 3). The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- 6). The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- 8). The maximum signal level detected by the measuring receiver shall be noted.
- 9). The measurement shall be repeated with the test antenna set to horizontal polarization.
- 10). Replace the antenna with a proper Antenna (substitution antenna).
- 11). The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- 12). The substitution antenna shall be connected to a calibrated signal generator.

13). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.


14). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.

15). The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.

16). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.

17). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

9.3 TEST SETUP BLOCK DIAGRAM (block diagram of configuration)



9.4 MEASUREMENT EQUIPMENT USED:

Open Area Test Site					
EQUIPMENT TYPE	MFR	MODEL NO.	SERIAL NO.	LAST CAL.	CAL DUE.
Spectrum Analyzer	ADVANTEST	R3132	N/A	06/08/2004	06/07/2005
EMI Test Receiver	HP	8546A	3448A00232	06/08/2004	06/07/2005
Pre-Amplifier	HP	8447D	2944A07999	06/08/2004	06/07/2005
Bi-Log Antenna	EMCO	3142	9910-1436	06/08/2004	06/07/2005
Bi-Log Antenna	SCHAFFNER	CBL6143	5082	06/08/2004	06/07/2005
CABLE	TIME MICROWAVE	LMR-400	N-TYPE04	06/08/2004	06/07/2005

9.5 MEASUREMENT RESULTS:

Calculation: Limit (dBm)= EL-56-10log10 (TP)

Notes: EL is the emission level of the Output Power expressed in dBm,, in this application, the TG is 19.16 dBm.

TP is the Output Power express in Watts, in the application the TP is 0.08241 W


Limit (dBm)=19.16-56-10log10 (0.08241) = -26

Notes: Two 10db attenuators are used between S.G. and substitution antenna while measuring the Spurious Emission, so the 20db attenuation should be added to the cable loss.

Frequency (MHz)	Reading level (dBuV)	Antenna Polarization	S.G. (dBm)	Cable loss (dB)	Ant.Gain (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
72.85	84.63	V	20.30	0.64	-0.5	19.16	28.75	-9.59
145.70	46.44	V	-25.60	21.40	5.3	-41.7	-26.00	-15.7
218.55	35.35	V	-38.80	22.79	6.4	-55.19	-26.00	-29.19
291.40	48.69	V	-24.50	22.74	6.2	-41.04	-26.00	-15.04
364.25	45.35	V	-26.90	22.86	6.0	-43.76	-26.00	-17.76
437.10	50.21	V	-22.10	22.84	6.8	-38.14	-26.00	-12.14
509.95	50.02	V	-22.30	22.90	6.9	-38.3	-26.00	-12.3
582.80	53.51	V	-20.80	22.96	6.8	-36.96	-26.00	-10.96
655.65	57.15	V	-18.30	23.02	6.4	-34.92	-26.00	-8.92
728.50	56.66	V	-18.50	23.24	6.2	-35.54	-26.00	-9.54

Frequency (MHz)	Reading level (dBuV)	Antenna Polarization	S.G. (dBm)	Cable loss (dB)	Ant.Gain (dB)	Emission level (dBm)	Limit (dBm)	Margin (dB)
72.85	65.84	H	1.50	0.64	-0.5	0.36	28.75	-28.39
145.70	57.79	H	-19.30	21.40	5.3	-35.4	-26.00	-9.4
218.55	43.23	H	-26.80	22.79	6.4	-43.19	-26.00	-17.19
291.40	56.04	H	-20.00	22.74	6.2	-36.54	-26.00	-10.54
364.25	53.54	H	-22.50	22.86	6.0	-39.36	-26.00	-13.36
437.10	48.86	H	-24.30	22.84	6.8	-40.34	-26.00	-14.34
509.95	47.33	H	-24.50	22.90	6.9	-40.5	-26.00	-14.5
582.80	54.89	H	-20.30	22.96	6.8	-36.46	-26.00	-10.46
655.65	57.32	H	-19.4	23.02	6.4	-36.02	-26.00	-10.02
728.50	60.22	H	-18.2	23.24	6.2	-35.24	-26.00	-9.24

9.6 EMISSION MASK:



10. MODULATION STANDARDS

The Modulation Standard is not applicable to this kind of R/C devices.

11. Maximum transmitter power

11.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.639(b), under any condition of modulation, the R/C transmitter operate in the 72-76MHz frequency band shall not exceed a carrier power of 0.75W.

11.2 MEASUREMENT PROCEDURE

Notes: The instrument setting used during the measurement procedure is as follow.

HP 8546A:	RW=120KHz, VBW=300KHz, C.F.=fundamental frequency, SPAN 5MHz, A trace MAX HOLD, B trace CLEAR WRIT
ADVANTEST:	RW=100KHz, VBW=100KHz, C.F.=Maximum peak Frequency, SPAN 0,TG ON

- 1). On a test site, the EUT shall be placed on a turntable, and in the position closest to the normal use as declared by the user.
- 2). The test antenna shall be oriented initially for vertical polarization located 3m from the EUT to correspond to the transmitter.
- 3). The output of the antenna shall be connected to the measuring receiver and either a peak or quasi-peak detector was used for the measurement as indicated on the report. The detector selection is based on how close the emission level was approaching the limit.
- 4). The transmitter shall be switched on; if possible, without the modulation and the measurement receiver shall be tuned to the frequency of the transmitter under test.
- 5). The test antenna shall be raised and lowered through the specified range of height until the measuring receiver detects a maximum signal level.
- 6). The transmitter shall then be rotated through 360 ° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.
- 7). The test antenna shall be raised and lowered again through the specified range of height until the measuring receiver detects a maximum signal level.
- 8). The maximum signal level detected by the measuring receiver shall be noted.
- 9). Replace the antenna with a proper Antenna (substitution antenna).
- 10). The substitution antenna shall be oriented for vertical polarization and, if necessary, the length of the substitution antenna shall be adjusted to correspond to the frequency of transmitting.
- 11). The substitution antenna shall be connected to a calibrated signal generator.

12). If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.

13). The test antenna shall be raised and lowered through the specified range of the height to ensure that the maximum signal is received.

14). The input signal to substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuation setting of the measuring receiver.


15). The input level to the substitution antenna shall be recorded as power level in dBm, corrected for any change of input attenuator setting of the measuring receiver.


16). The measurement shall be repeated with the test antenna and the substitution antenna oriented for horizontal polarization.

17). The measure of the effective radiated power is the larger of the two levels recorded, at the input to the substitution antenna, corrected for the gain of the substitution antenna if necessary.

11.3 TEST SETUP BLOCK DAIGRAM(setup block diagram of configuration)

TEST SETUP:



SUBSTITUTION METHOD:**11.4 MEASUREMENT EQUIPMENT USED:**

Open Area Test Site					
EQUIPMENT TYPE	MFR	MODEL NO.	SERIAL NO.	LAST CAL.	CAL DUE.
Spectrum Analyzer	ADVANTEST	R3132	N/A	06/08/2004	06/07/2005
EMI Test Receiver	HP	8546A	3448A00232	06/08/2004	06/07/2005
Pre-Amplifier	HP	8447D	2944A07999	06/08/2004	06/07/2005
Bi-Log Antenna	EMCO	3142	9910-1436	06/08/2004	06/07/2005
Bi-Log Antenna	SCHAFFNER	CBL6143	5082	06/08/2004	06/07/2005
CABLE	TIME MICROWAVE	LMR-400	N-TYPE04	06/08/2004	06/07/2005

11.5 TEST RESULT

Freq (MHz)	Antenna Polarity	Reading (dBuV)	SGOP (dBm)	Ant. Gain (dB)	Dipole Gain (dBi)	Cable (dB)	Corrected Power		Limit (W)
							(dBm)	(mW)	
7285	V	84.63	20.3	-0.5	0	0.64	19.16	82.4138115	0.75
7285	H	65.84	1.5	-0.5	0	0.64	0.36	1.086425624	0.75

12. TRANSMITTER ANTENNA

12.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.647, the antenna of each R/C station transmitting in 72-76 MHz band, must be an integral part of the transmitter. The antenna must have no gain and must be vertically polarized.

12.2 COMPLIANCE

The antenna is designed as a fixed, non-user replaceable with no gain and vertically polarized unit integrated to EUT.

13. POWER CAPABILITY

13.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.649, no R/C unit shall incorporate provisions for increasing its transmitter power to any level in excess of the limits specified in § 95.639

13.2 COMPLIANCE

All the components employed by EUT have the power capability less than 0.75W either being assembled or individual.

14. CRYSTAL CONTROL REQUIRED

14.1 PROVISIONS APPLICABLE

According to FCC Part 95 Section 95.651, all transmitters used in Personal Radio Services must be crystal controlled, except an R/C station that transmits in 26-27 MHz frequency band.

14.2 COMPLIANCE

The crystal is not accessible to user.

APPENDIX 1

PHOTOGRAPHS OF SET UP

Radiated Emission Setup Photos



APPENDIX 2

PHOTOGRAPHS OF EUT

Front View of TX



Back View of TX



Top View of TX



Bottom View of TX



Left View of TX



Right View of TX



Internal of TX- Open




Internal of TX- Open




Internal of TX- Open




Internal of TX- 1



Internal of TX- 2



Internal of TX- 3



Internal of TX- 4

