



Radio Frequency Exposure

EUT INFORMATION

EUT	Evluent VerticalMouse C Replacement Receiver
Frequency band (Operating)	2.405~2.475 GHz
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Field strength	77.15 dBuV/m @3m
Antenna gain (Max)	3.45 dBi

TEST RESULT

According to KDB 447498 section 4.3.1, the 1-g SAR test exclusion thresholds at test separation distance ≤ 50 mm are determined by:

The min. test separation distance (mm) is 5 mm,

$$\text{eirp} = \text{pt} * \text{gt} = (\text{E} * \text{d})^2 / 30$$

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- $10^{((\text{dBuV/m})/20)}/10^6$

d = measurement distance in meters (m) --- 3m

$$\text{So pt} = (\text{E} * \text{d})^2 / (30 * \text{gt})$$

Ant. numeric gain, Ant. = 3.45 dBi = 2.21

$$\text{So pt} = \{ [10^{(77.15/20)} / 10^6 * 3]^2 / (30 * 2.21) \} * 1000 = 0.007 \text{ mW}$$

$$\text{So } (0.007 \text{ mW} / 5 \text{ mm}) * \sqrt{2.475 \text{ GHz}} = \mathbf{0.002} < 3.0 \text{ for 1-g SAR}$$

Therefore, standalone SAR measurements are not required for both head and body.