FCC RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.

FOR

Mobile Phone

ISSUED TO
Guangdong OPPO Mobile Telecommunications Corp., Ltd.

NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, GuangDong, China

Tested by: Ye Hongji
Ye Hongji
Date Jul. 15, 2020

Approved by: Tolan Tu
Tolan Tu
(Testing Director)
Date Jul. 15, 2020

Report No.:	BL-SZ2060102-601
EUT Name:	Mobile Phone
Model Name:	CPH2123
Brand Name:	OPPO
Test Standard:	47 CFR Part 15 Subpart C
FCC ID:	R9C-CPH2123
Test Conclusion:	Pass
Test Date:	Jun. 03, 2020 ~ Jun. 22, 2020
Date of Issue:	Jul. 15, 2020

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong, P. R. China 518055
TEL: +86-755-66850100, FAX: +86-755-61824271
Email: qc@baluntek.com
www.baluntek.com

Revision History

Version	Issue Date	Revisions Content
Rev. 01	Jul. 15, 2020	Initial Issue

TABLE OF CONTENTS

1 ADMINISTRATIVE DATA (GENERAL INFORMATION) 5
1.1 Identification of the Testing Laboratory 5
1.2 Identification of the Responsible Testing Location 5
1.3 Laboratory Condition 5
1.4 Announce 5
2 PRODUCT INFORMATION 6
2.1 Applicant Information 6
2.2 Manufacturer Information 6
2.3 Factory Information 6
2.4 General Description for Equipment under Test (EUT) 6
2.5 Technical Information 7
2.6 Additional Instructions 9
3 SUMMARY OF TEST RESULTS 10
3.1 Test Standards 10
3.2 Verdict 10
4 GENERAL TEST CONFIGURATIONS 11
4.1 Test Environments 11
4.2 Test Equipment List 11
4.3 Measurement Uncertainty 13
4.4 Description of Test Setup 14
4.4.1 For Antenna Port Test 14
4.4.2 For AC Power Supply Port Test 14
4.4.3 For Radiated Test (Below 30 MHz) 15
4.4.4 For Radiated Test (30 MHz-1 GHz) 15
4.4.5 For Radiated Test (Above 1 GHz) 16
4.5 Measurement Results Explanation Example 17
4.5.1 For conducted test items: 17

5 TEST ITEMS 18
5.1 Antenna Requirements 18
5.1.1 Relevant Standards 18
5.1.2 Antenna Anti-Replacement Construction 18
5.1.3 Antenna Gain 18
5.2 Frequency Hopping Systems 19
5.2.1 Relevant Standards 19
5.2.2 Description of the systems 19
5.3 Number of Hopping Frequencies 20
5.3.1 Limit 20
5.3.2 Test Setup 20
5.3.3 Test Procedure 20
5.3.4 Test Result 20
5.4 Peak Output Power and E.I.R.P 21
5.4.1 Test Limit 21
5.4.2 Test Setup 21
5.4.3 Test Procedure 21
5.4.4 Test Result 21
5.5 Occupied Bandwidth 22
5.5.1 Limit 22
5.5.2 Test Setup 22
5.5.3 Test Procedure 22
5.5.4 Test Result 22
5.6 Carrier Frequency Separation 23
5.6.1 Limit 23
5.6.2 Test Setup 23
5.6.3 Test Procedure 23
5.6.4 Test Result 23
5.7 Time of Occupancy (Dwell time) 24
5.7.1 Limit 24
5.7.2 Test Setup 24
5.7.3 Test Procedure 24
5.7.4 Test Result 25

5.8 Conducted Spurious Emission & Authorized-band band-edge 26
5.8.1 Limit 26
5.8.2 Test Setup 26
5.8.3 Test Procedure 26
5.8.4 Test Result 26
5.9 Conducted Emission 27
5.9.1 Limit 27
5.9.2 Test Setup 27
5.9.3 Test Procedure 27
5.9.4 Test Result 27
5.10 Radiated Spurious Emission 28
5.10.1 Limit 28
5.10.2 Test Setup 28
5.10.3 Test Procedure 28
5.10.4 Test Result 29
5.11 Band Edge (Restricted-band band-edge) 30
5.11.1 Limit 30
5.11.2 Test Setup 30
5.11.3 Test Procedure 30
5.11.4 Test Result 30
ANNEX A TEST RESULT 31
A.1 Number of Hopping Frequency 31
A.2 Peak Output Power 32
A.3 20 dB and 99% bandwidth 35
A.4 Hopping Frequency Separation 40
A.5 Average Time of Occupancy 41
A.6 Conducted Spurious Emissions & Authorized-band band-edge 44
A.7 Conducted Emissions 51
A.8 Radiated Spurious Emission 53
A.9 Band Edge (Restricted-band band-edge) 71
ANNEX B TEST SETUP PHOTOS 73
ANNEX C EUT EXTERNAL PHOTOS 73
ANNEX D EUT INTERNAL PHOTOS 73

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20℃ to 25℃
Ambient Relative Humidity	45% to 55%
Ambient Pressure	100 kPa to 102 kPa

1.4 Announce

(1) The test report reference to the report template version v5.7.

(2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.

(3) The test report is invalid if there is any evidence and/or falsification.

(4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.

(5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.

(6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

(7) The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, GuangDong, China

2.2 Manufacturer Information

Manufacturer	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, GuangDong, China

2.3 Factory Information

Factory	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 HaiBin Road, Wusha village, Chang An Town, DongGuan City, GuangDong, China

2.4 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	CPH2123
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	ColorOS 7.2
Dimensions (Approx.)	160.1x73.8x7.5mm
Weight (Approx.)	164g(with battery)

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA/HSPA+ Band 2/4/5 4G Network FDD LTE Band 2/4/5/7/12/17/26/66 TDD LTE Band 38/41 LTE CA Uplink (UL): CA_7C, CA_38C, CA_41C Bluetooth 5.1 (BR+EDR+BLE) 2.4G WIFI 802.11b, 802.11g, 802.11n(HT20) 5G WIFI 802.11a, 802.11n(HT20/40) and 802.11ac(VHT20/40/80) Band 1/2A/2C/3, GPS, GLONASS, BDS, SBAS, Galileo FM receiver, NFC

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, ∏/4-DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of Channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	-3 dBi (In test items related to antenna gain, the final results reflect this figure. This value is provided by the applicant.)
Antenna Impedance	50Ω
Antenna System (MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	**2402**	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	**78**	**2480**
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	**39**	**2441**	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-

2.6 Additional Instructions

EUT Software Settings:

Mode	☒ Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMW.

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power level setup in software			
Test Software Version	*#*#3646633#*#*		
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	Power parameter Settings is 9
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-17 Edition)	Miscellaneous Wireless Communications Services
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	N/A	--	Pass	Note [1]
2	Number of Hopping Frequencies	15.247(a)	Hopping Mode	ANNEX A.1	Pass	Note [2]
3	Peak Output Power and E.I.R.P	15.247(b)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	Low/Middle/High	ANNEX A.3	Pass	Note [2]
5	Carrier Frequency Separation	15.247(a)	Hopping Mode	ANNEX A.4	Pass	Note [2]
6	Time of Occupancy (Dwell time)	15.247(a)	Hopping Mode	ANNEX A.5	Pass	Note [2]
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	Low/Middle/High	ANNEX A.6	Pass	Note [2]
8	Conducted Emission	15.207	Low/Middle/High	ANNEX A.7	Pass	Note [2]
9	Radiated Spurious Emission	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note [2]
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note [2]
11	Receiver Spurious Emissions	--	--	--	N/A	Note [3]

Note [1]: Please refer to section 5.1

Note [2]: Π/4-DQPSK is the EDR 2M rate mode, 8-DPSK is the EDR 3M rate mode. The consistency of test results in Π/4-DQPSK and 8-DPSK is very high. So we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item.

Note [3]: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% to 55%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22℃ to +25℃
Working Voltage of the EUT	NV (Normal Voltage)	3.85 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2019.06.13	2020.06.12
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2019.06.13	2020.06.12
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2019.10.29	2020.10.28
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2019.06.13	2020.06.12
LISN	SCHWARZBECK	NSLK 8127	8127-687	2019.06.13	2020.06.12
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2019.06.13	2020.06.12
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2019.06.18	2020.06.17
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2019.06.13	2020.06.12
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
Temperature Chamber	AHK	SP20	1412	2019.06.24	2020.06.23
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.09	2020.11.08
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2019.07.22	2021.07.21
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2019.01.06	2021.01.05
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.07.19	2020.07.18
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2019.08.23	2020.08.22
Power Amplifier	OPHIR RF	5225F	1037	2020.02.19	2021.02.18
Power Amplifier	OPHIR RF	5273F	1016	2020.02.19	2021.02.18
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Sound Level Meter	B&K	NL-20	00844023	2019.11.12	2020.11.11
Ear Simulator	B&K	4185	2409449	2019.11.12	2020.11.11

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Ear Simulator	B&K	4195	2418189	2019.11.12	2020.11.11
Audio analyzer	B&K	UPL 16	100129	2019.11.12	2020.11.11
Software	BALUN	BL410	-	-	-
Cable	ROHDE&SCHWARZ	JUNFLON	APR0914004	2020.01.08	2021.01.07

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2020.06.08	2021.06.07
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2020.06.08	2021.06.07
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2020.06.09	2021.06.08
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2020.06.09	2021.06.08
LISN	SCHWARZBECK	NSLK 8127	8127-687	2020.06.09	2021.06.08
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW270	100607	2020.06.08	2021.06.07
Bluetooth Signaling Unit	ROHDE&SCHWARZ	CMW500	142028	2020.06.08	2021.06.07
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2020.06.08	2021.06.07
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2020.06.08	2021.06.07
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
Temperature Chamber	AHK	SP20	1412	2020.06.10	2021.06.09
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.11.09	2020.11.08
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2018.08.22	2020.08.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2019.07.22	2021.07.21
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	2019.01.06	2021.01.05
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.21	2022.02.20
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2018.08.08	2021.08.07
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2020.06.08	2021.06.07
Power Amplifier	OPHIR RF	5225F	1037	2020.02.19	2021.02.18
Power Amplifier	OPHIR RF	5273F	1016	2020.02.19	2021.02.18
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Sound Level Meter	B&K	NL-20	00844023	2019.11.12	2020.11.11
Ear Simulator	B&K	4185	2409449	2019.11.12	2020.11.11
Ear Simulator	B&K	4195	2418189	2019.11.12	2020.11.11
Audio analyzer	B&K	UPL 16	100129	2019.11.12	2020.11.11

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Occupied Channel Bandwidth	±4%
RF output power, conducted	±1.4 dB
Power Spectral Density, conducted	±2.5 dB
Unwanted Emissions, conducted	±2.8 dB
All emissions, radiated	±5.4 dB
Temperature	±1°C
Humidity	±4%

4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)

For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:
Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm



(Diagram 1)

4.4.2 For AC Power Supply Port Test



(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)



(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (f)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	An embedded-in antenna design is used.

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Frequency Hopping Systems

5.2.1 Relevant Standards

FCC §15.247(a) (1) (i) (ii) (iii) (iv); FCC §15.247(g); FCC §15.247(h)

Describe how the hopping sequence is generated. Provide an example of the hopping sequence channels, to demonstrate that the sequence meets the requirement specified in the definition of an FHSS system. Per the definition in Section 2.1(c), the hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.
Describe how each individual EUT meets the requirement that each of its hopping channels is used equally on average (e.g., that each new transmission event begins on the next channel in the hopping sequence after the final channel used in the previous transmission event).
Describe how the associated receiver(s) complies with the requirement that the input bandwidth (either RF or IF) matches the bandwidth of the transmitted signal.
Describe how the associated receiver(s) has the ability to shift frequencies in synchronization with the transmitted signals.
For short burst systems, describe how the EUT complies with the requirement that it be designed to be capable of operating as a true frequency hopping system. Specifically, the device shall comply with the equal frequency use and pseudorandom hopping sequence requirement when transmitting in short bursts, and shall be designed to comply when presented with continuous data (or information) stream.
Describe how the EUT complies with the requirement that it not have the ability to be coordinated with other FHSS systems in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

5.2.2 Description of the systems

1. According to the preset procedure of the whole network, all the stations in the automatic control network synchronously change the frequency multiple times within one second, and temporarily stay on each frequency hopping channel. Periodic synchronization signaling is sent from the primary station, instructing all slaves to simultaneously change the operating frequency, then the hopping sequence is generated.
2. The hop set shall appear as random in the near term, shall appear as evenly distributed in the long term, and sequential hops shall be randomly distributed in both direction and magnitude of change.

Reference Documents

3. Channels are classified into two categories, used and unused, where used channels are part of the hopping sequence and unused channels are replaced in the hopping sequence by used channels in a pseudo-

random way. Make each individual EUT meets the requirement that each of its hopping channels is used equally on average.

4. The input bandwith and transmitted bandwith are both 1MHz, the associated receiver(s) complies with the requirement that the input bandwidth matches the bandwidth of the transmitted signal.
5. Connected devices communicate on the same physical channel by synchronizing with a common clock and hopping sequence.
6. EUT isn't short burst systems.
7. EUT can't have the ability to be coordinated with other FHSS systems in an effort.

5.3 Number of Hopping Frequencies

5.3.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (d)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = The frequency band of operation

RBW = To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.3.4 Test Result

Please refer to ANNEX A.1.

5.4 Peak Output Power

5.4.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (b)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.2.

5.5 Occupied Bandwidth

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (a)

Measurement of the 20dB bandwidth of the modulated signal.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.5.4 Test Result

Please refer to ANNEX A.3.

5.6 Carrier Frequency Separation

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (b)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 2/3 of the 20 dB bandwidth of the hopping channel, whichever is greater.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span

Video (or Average) Bandwidth (VBW) ≥ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.6.4 Test Result

Please refer to ANNEX A.4.

5.7 Time of Occupancy (Dwell time)

5.7.1 Limit

FCC §15.247(a); RSS-247, 5.1 (d)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

The EUT shall have its hopping function enabled. Use the following spectrum analyzer settings:
Span: Zero span, centered on a hopping channel
RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel
Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel
Detector function: Peak
Trace: Max hold

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

The average time of occupancy on any channel within the Period can be calculated with formulas:
For GFSK and 8-DPSK:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (1600 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (1600 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (1600 / 6) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For AFH Mode:
For DH1 package type

{Total of Dwell} = {Pulse Time} * (800 / 2) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH3 package type

{Total of Dwell} = {Pulse Time} * (800 / 4) / {Number of Hopping Frequency} * {Period}
{Period} = 0.4 s * {Number of Hopping Frequency}

For DH5 package type

{Total of Dwell} = {Pulse Time} * (800 / 6) / {Number of Hopping Frequency} * {Period}

{Period} = 0.4 s * {Number of Hopping Frequency}

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.7.4 Test Result

Please refer to ANNEX A.5

5.8 Conducted Spurious Emission & Authorized-band band-edge

5.8.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.8.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
RBW = 100 kHz
VBW = 300 kHz
Sweep = auto
Detector function = peak
Trace = max hold
Allow the trace to stabilize

5.8.4 Test Result

Please refer to ANNEX A.6.

5.9 Conducted Emission

5.9.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.9.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.
Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.9.4 Test Result

Please refer to ANNEX A.7.

5.10 Radiated Spurious Emission

5.10.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW

Sweep = auto
Detector function = peak
Trace = max hold
For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.8.

5.11 Band Edge (Restricted-band band-edge)

5.11.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.11.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.11.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured
RBW = 1 MHz for f ≥ 1 GHz, 100 kHz for f < 1 GHz
VBW ≥ RBW
Sweep = auto
Detector function = peak
Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.11.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT

A.1 Number of Hopping Frequency

Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots

GFSK 2.4 GHz ~ 2.4415 GHz



GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	10.57	11.40	21	125	Pass
Middle	10.72	11.80			Pass
High	10.67	11.67			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	∏/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	9.90	9.77	9.91	9.79	21	125	Pass
Middle	9.98	9.95	10.04	10.09			Pass
High	10.04	10.09	10.06	10.14			Pass

Test plots

GFSK LOW CHANNEL



Date: 18.JUN.2020 18:53:59

GFSK MIDDLE CHANNEL



Date: 18.JUN.2020 18:59:10

GFSK HIGH CHANNEL



Date: 18.JUN.2020 19:01:09

Π/4-DQPSK LOW CHANNEL



Date: 18.JUN.2020 19:04:15

Π/4-DQPSK MIDDLE CHANNEL



Date: 18.JUN.2020 19:05:42

Π/4-DQPSK HIGH CHANNEL



Date: 18.JUN.2020 19:07:12

8-DPSK LOW CHANNEL



Date: 18.JUN.2020 19:08:57

8-DPSK MIDDLE CHANNEL



Date: 18.JUN.2020 19:12:05

8-DPSK HIGH CHANNEL



Date: 18.JUN.2020 19:14:10

A.3 20 dB and 99% bandwidth

Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.874023	0.768452
Middle	0.874023	0.764110
High	0.874023	0.764110
∏/4-DQPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.265137	1.146165
Middle	1.265137	1.150507
High	1.265137	1.146165
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.282715	1.154848
Middle	1.269531	1.154848
High	1.273926	1.150507

Test plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



Date: 18.JUN.2020 19:01:25

Π/4-DQPSK LOW CHANNEL

Date: 18.JUN.2020 19:04:31

Π/4-DQPSK MIDDLE CHANNEL



Date: 18.JUN.2020 19:05:57

Π/4-DQPSK HIGH CHANNEL



Date: 18.JUN.2020 19:07:28

8-DPSK LOW CHANNEL

Date: 18.JUN.2020 19:09:12

8-DPSK MIDDLE CHANNEL



Date: 18.JUN.2020 19:12:21

8-DPSK HIGH CHANNEL



Date: 18.JUN.2020 19:14:25

99% Bandwidth

GFSK LOW CHANNEL



Date: 18.JUN.2020 18:54:30

GFSK MIDDLE CHANNEL



Date: 18.JUN.2020 18:59:41

GFSK HIGH CHANNEL



Date: 18.JUN.2020 19:01:40

Π/4-DQPSK LOW CHANNEL

Date: 18.JUN.2020 19:04:47

Π/4-DQPSK MIDDLE CHANNEL

Date: 18.JUN.2020 19:06:13

Π/4-DQPSK HIGH CHANNEL

Date: 18.JUN.2020 19:07:44

8-DPSK LOW CHANNEL

Date: 18.JUN.2020 19:09:28

8-DPSK MIDDLE CHANNEL

Date: 18.JUN.2020 19:12:36

8-DPSK HIGH CHANNEL

Date: 18.JUN.2020 19:14:41

A.4 Hopping Frequency Separation

Test Data

Mode	Frequency separation (MHz)	Max 2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	1.0033	0.874023	Pass
8-DPSK	1.0033	1.282715	Pass

Test Plots

GFSK



8-DPSK



A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.37033	118.506	0.4	Pass
DH 3	1.62483	259.973	0.4	Pass
DH 5	2.88780	308.032	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.37583	120.266	0.4	Pass
DH 3	1.61600	258.560	0.4	Pass
DH 5	2.86420	305.515	0.4	Pass
AFH Mode				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.37050	59.280	0.4	Pass
DH 3	1.62817	130.254	0.4	Pass
DH 5	2.88600	153.920	0.4	Pass

Test Plots

GFSK DH1



GFSK DH3



GFSK DH5



Date: 18.JUN.2020 19:31:08

8-DPSK DH1



Date: 18.JUN.2020 19:36:25

8-DPSK DH3



Date: 18.JUN.2020 19:36:55

8-DPSK DH5



Date: 18.JUN.2020 19:37:28

AFH Mode DH1



Date: 18.JUN.2020 19:32:02

AFH Mode DH3



Date: 18.JUN.2020 19:32:35

AFH Mode DH5



Date: 18.JUN.2020 19:35:21

A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-27.21	9.90	-10.10	Pass
Middle	-27.36	10.16	-9.84	Pass
High	-27.67	10.08	-9.92	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-27.36	9.54	-10.46	Pass
Middle	-27.23	9.70	-10.30	Pass
High	-27.36	9.31	-10.69	Pass

Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-26.52	10.17	-9.83	Pass
8-DPSK	-27.43	8.72	-11.28	Pass

Test Plots

GFSK LOW CHANNEL, CARRIER LEVEL



GFSK LOW CHANNEL, BAND EDGE



GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK MIDDLE CHANNEL, CARRIER LEVEL



GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:00:25

GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.JUN.2020 19:00:38

GFSK HIGH CHANNEL, CARRIER LEVEL



Date: 18.JUN.2020 19:01:54

GFSK HIGH CHANNEL, BAND EDGE



Date: 18.JUN.2020 19:03:12

GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:02:20

GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.JUN.2020 19:02:34

8-DPSK LOW CHANNEL, CARRIER LEVEL

Date: 18.JUN.2020 19:09:42

8-DPSK LOW CHANNEL, BAND EDGE



Date: 18.JUN.2020 19:11:04

8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:10:11

8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.JUN.2020 19:10:24

8-DPSK MIDDLE CHANNEL, CARRIER LEVEL



Date: 18.JUN.2020 19:12:49

8-DPSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ ~ 3 GHz



Date: 18.JUN.2020 19:13:18

8-DPSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.JUN.2020 19:13:31

8-DPSK HIGH CHANNEL, CARRIER LEVEL



Date: 18.JUN.2020 19:14:54

8-DPSK HIGH CHANNEL, BAND EDGE

Date: 18.JUN.2020 19:16:51

8-DPSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:16:00

8-DPSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



Date: 18.JUN.2020 19:16:21

GFSK HOPPING, CARRIER LEVEL



Date: 18.JUN.2020 19:19:28

GFSK HOPPING BAND EDGE (LOW)



Date: 18.JUN.2020 19:21:01

GFSK HOPPING BAND EDGE (HIGH)



Date: 18.JUN.2020 19:21:26

GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:20:08

GFSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



Date: 18.JUN.2020 19:20:26

8-DPSK HOPPING, CARRIER LEVEL



Date: 18.JUN.2020 19:26:22

8-DPSK Hopping BAND EDGE (LOW)



Date: 18.JUN.2020 19:28:06

8-DPSK Hopping BAND EDGE (HIGH)



Date: 18.JUN.2020 19:28:30

8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



Date: 18.JUN.2020 19:27:12

8-DPSK Hopping Mode, SPURIOUS 30 3GHz ~ 25 GHz



Date: 18.JUN.2020 19:27:31

A.7 Conducted Emissions

Note [1]: The EUT is working in the Normal link mode. All modes have been tested and normal link mode is worst.
Note [2]: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (240 VAC, 50 Hz) shown here.
Note [3]: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	45.68	10.41	66.00	-20.32	Peak	L	Pass
1**	0.150	37.96	10.41	56.00	-18.04	AV	L	Pass
2	0.182	46.08	10.39	64.39	-18.31	Peak	L	Pass
2**	0.182	37.50	10.39	54.39	-16.89	AV	L	Pass
3	0.420	45.80	10.31	57.45	-11.65	Peak	L	N/A
3*	0.420	43.75	10.31	57.45	-13.70	QP	L	Pass
3**	0.420	41.44	10.31	47.45	-6.01	AV	L	Pass
4	0.510	41.32	10.30	56.00	-14.68	Peak	L	Pass
4**	0.510	33.58	10.30	46.00	-12.42	AV	L	Pass
5	3.392	39.51	10.27	56.00	-16.49	Peak	L	Pass
5**	3.392	28.38	10.27	46.00	-17.62	AV	L	Pass
6	18.428	37.48	10.51	60.00	-22.52	Peak	L	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Line	Verdict
1	0.150	46.93	10.41	66.00	-19.07	Peak	N	Pass
1**	0.150	36.15	10.41	56.00	-19.85	AV	N	Pass
2	0.180	45.40	10.39	64.49	-19.09	Peak	N	Pass
2**	0.180	34.81	10.39	54.49	-19.68	AV	N	Pass
3	0.422	42.14	10.31	57.41	-15.27	Peak	N	Pass
3**	0.422	38.02	10.31	47.41	-9.39	AV	N	Pass
4	0.452	41.09	10.30	56.84	-15.75	Peak	N	Pass
4**	0.452	32.27	10.30	46.84	-14.57	AV	N	Pass
5	1.548	36.56	10.24	56.00	-19.44	Peak	N	Pass
5**	1.548	24.35	10.24	46.00	-21.65	AV	N	Pass
6	18.378	37.67	10.50	60.00	-22.33	Peak	N	Pass
6**	18.378	26.45	10.50	50.00	-23.55	AV	N	Pass

A.8 Radiated Spurious Emission

Test Data and Plots

Note [1]: The symbol of "--" in the table which means not application.

Note [2]: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note [3]: The EUT is working in the Normal link mode below 1 GHz. All modes have been tested and normal link mode is worst.

Note [4]: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.672	25.39	-22.50	40.0	-14.61	Peak	80.00	100	Horizontal	Pass
2	53.959	19.08	-22.97	40.0	-20.92	Peak	141.60	200	Horizontal	Pass
3	98.967	24.60	-24.85	43.5	-18.90	Peak	281.30	200	Horizontal	Pass
4	104.496	25.92	-24.34	43.5	-17.58	Peak	276.00	200	Horizontal	Pass
5	125.545	23.77	-26.52	43.5	-19.73	Peak	24.80	200	Horizontal	Pass
6	190.486	26.18	-25.20	43.5	-17.32	Peak	119.70	100	Horizontal	Pass

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	48.575	33.40	-22.52	40.0	-6.60	Peak	253.50	100	Vertical	Pass
2	54.395	29.36	-23.07	40.0	-10.64	Peak	187.90	100	Vertical	Pass
3	65.987	24.62	-25.13	40.0	-15.38	Peak	107.00	100	Vertical	Pass
4	103.963	32.23	-24.38	43.5	-11.27	Peak	0.00	200	Vertical	Pass
5	189.807	22.38	-25.25	43.5	-21.12	Peak	13.50	100	Vertical	Pass
6	573.151	28.14	-14.83	46.0	-17.86	Peak	164.40	100	Vertical	Pass

Test Data and Plots (1 GHz ~ 10th Harmonic)

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1521.300	36.39	-15.03	74.0	-37.61	Peak	306.00	150	Horizontal	Pass
1**	1521.300	27.71	-15.03	54.0	-26.29	AV	306.00	150	Horizontal	Pass
2	2401.800	103.83	-10.61	74.0	29.83	Peak	28.00	150	Horizontal	N/A
2**	2401.800	102.37	-10.61	54.0	48.37	AV	28.00	150	Horizontal	N/A
3	4804.200	50.32	-1.20	74.0	-23.68	Peak	35.00	150	Horizontal	Pass
3**	4804.200	47.26	-1.20	54.0	-6.74	AV	35.00	150	Horizontal	Pass
4	6652.600	51.20	4.63	74.0	-22.80	Peak	219.00	150	Horizontal	Pass
4**	6652.600	41.89	4.63	54.0	-12.11	AV	219.00	150	Horizontal	Pass
5	10441.088	48.92	18.76	74.0	-25.08	Peak	153.00	150	Horizontal	Pass
5**	10441.088	38.82	18.76	54.0	-15.18	AV	153.00	150	Horizontal	Pass
6	15514.125	55.03	23.83	74.0	-18.97	Peak	146.00	150	Horizontal	Pass
6**	15514.125	43.33	23.83	54.0	-10.67	AV	146.00	150	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1853.500	37.86	-13.84	74.0	-36.14	Peak	217.00	150	Vertical	Pass
1**	1853.500	29.05	-13.84	54.0	-24.95	AV	217.00	150	Vertical	Pass
2	2401.900	89.43	-10.60	74.0	15.43	Peak	67.00	150	Vertical	N/A
2**	2401.900	88.45	-10.60	54.0	34.45	AV	67.00	150	Vertical	N/A
3	4804.200	49.37	-1.20	74.0	-24.63	Peak	0.00	150	Vertical	Pass
3**	4804.200	43.52	-1.20	54.0	-10.48	AV	0.00	150	Vertical	Pass
4	6535.800	51.88	3.20	74.0	-22.12	Peak	189.00	150	Vertical	Pass
4**	6535.800	43.60	3.20	54.0	-10.40	AV	189.00	150	Vertical	Pass
5	10646.938	48.79	18.24	74.0	-25.21	Peak	260.00	150	Vertical	Pass
5**	10646.938	36.58	18.24	54.0	-17.42	AV	260.00	150	Vertical	Pass
6	15071.813	53.72	21.94	74.0	-20.28	Peak	360.00	150	Vertical	Pass
6**	15071.813	41.59	21.94	54.0	-12.41	AV	360.00	150	Vertical	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1669.800	37.99	-15.23	74.0	-36.01	Peak	0.00	150	Horizontal	Pass
1**	1669.800	27.48	-15.23	54.0	-26.52	AV	0.00	150	Horizontal	Pass
2	2440.900	103.52	-10.41	74.0	29.52	Peak	36.00	150	Horizontal	N/A
2**	2440.900	102.70	-10.41	54.0	48.70	AV	36.00	150	Horizontal	N/A
3	4882.200	50.28	-1.18	74.0	-23.72	Peak	234.00	150	Horizontal	Pass
3**	4882.200	45.35	-1.18	54.0	-8.65	AV	234.00	150	Horizontal	Pass
4	6757.400	51.78	4.27	74.0	-22.22	Peak	73.00	150	Horizontal	Pass
4**	6757.400	43.13	4.27	54.0	-10.87	AV	73.00	150	Horizontal	Pass
5	10389.913	49.33	18.46	74.0	-24.67	Peak	168.00	150	Horizontal	Pass
5**	10389.913	35.10	18.46	54.0	-18.90	AV	168.00	150	Horizontal	Pass
6	17271.824	57.05	24.39	74.0	-16.95	Peak	288.00	150	Horizontal	Pass
6**	17271.824	44.74	24.39	54.0	-9.26	AV	288.00	150	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1591.900	36.82	-15.35	74.0	-37.18	Peak	302.00	150	Vertical	Pass
1**	1591.900	26.84	-15.35	54.0	-27.16	AV	302.00	150	Vertical	Pass
2	2440.900	92.25	-10.41	74.0	18.25	Peak	37.00	150	Vertical	N/A
2**	2440.900	91.38	-10.41	54.0	37.38	AV	37.00	150	Vertical	N/A
3	4850.600	48.13	-1.35	74.0	-25.87	Peak	253.00	150	Vertical	Pass
3**	4850.600	39.30	-1.35	54.0	-14.70	AV	253.00	150	Vertical	Pass
4	6910.600	51.81	4.57	74.0	-22.19	Peak	314.00	150	Vertical	Pass
4**	6910.600	41.16	4.57	54.0	-12.84	AV	314.00	150	Vertical	Pass
5	10513.825	49.12	18.34	74.0	-24.88	Peak	168.00	150	Vertical	Pass
5**	10513.825	37.68	18.34	54.0	-16.32	AV	168.00	150	Vertical	Pass
6	15919.950	54.61	23.64	74.0	-19.39	Peak	327.00	150	Vertical	Pass
6**	15919.950	42.95	23.64	54.0	-11.05	AV	327.00	150	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1604.600	36.83	-15.40	74.0	-37.17	Peak	242.00	150	Horizontal	Pass
1**	1604.600	27.13	-15.40	54.0	-26.87	AV	242.00	150	Horizontal	Pass
2	2479.900	102.68	-10.26	74.0	28.68	Peak	23.00	150	Horizontal	N/A
2**	2479.900	101.15	-10.26	54.0	47.15	AV	23.00	150	Horizontal	N/A
3	4960.000	48.62	-1.74	74.0	-25.38	Peak	60.00	150	Horizontal	Pass
3**	4960.000	44.07	-1.74	54.0	-9.93	AV	60.00	150	Horizontal	Pass
4	6419.400	51.86	4.02	74.0	-22.14	Peak	60.00	150	Horizontal	Pass
4**	6419.400	42.61	4.02	54.0	-11.39	AV	60.00	150	Horizontal	Pass
5	10758.487	48.73	18.16	74.0	-25.27	Peak	293.00	150	Horizontal	Pass
5**	10758.487	35.92	18.16	54.0	-18.08	AV	293.00	150	Horizontal	Pass
6	15355.837	55.85	22.50	74.0	-18.15	Peak	346.00	150	Horizontal	Pass
6**	15355.837	42.93	22.50	54.0	-11.07	AV	346.00	150	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1441.100	36.89	-14.88	74.0	-37.11	Peak	360.00	150	Vertical	Pass
1**	1441.100	28.59	-14.88	54.0	-25.41	AV	360.00	150	Vertical	Pass
2	2479.800	89.41	-10.26	74.0	15.41	Peak	72.00	150	Vertical	N/A
2**	2479.800	87.52	-10.26	54.0	33.52	AV	72.00	150	Vertical	N/A
3	4959.600	49.00	-1.76	74.0	-25.00	Peak	356.00	150	Vertical	Pass
3**	4959.600	42.50	-1.76	54.0	-11.50	AV	356.00	150	Vertical	Pass
4	6765.000	51.38	4.05	74.0	-22.62	Peak	23.00	150	Vertical	Pass
4**	6765.000	42.03	4.05	54.0	-11.97	AV	23.00	150	Vertical	Pass
5	10529.350	49.16	18.31	74.0	-24.84	Peak	303.00	150	Vertical	Pass
5**	10529.350	36.95	18.31	54.0	-17.05	AV	303.00	150	Vertical	Pass
6	15608.625	56.13	23.51	74.0	-17.87	Peak	110.00	150	Vertical	Pass
6**	15608.625	42.74	23.51	54.0	-11.26	AV	110.00	150	Vertical	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1546.400	36.56	-14.94	74.0	-37.44	Peak	67.00	150	Horizontal	Pass
1**	1546.400	27.13	-14.94	54.0	-26.87	AV	67.00	150	Horizontal	Pass
2	2401.900	101.84	-10.60	74.0	27.84	Peak	27.00	150	Horizontal	N/A
2**	2401.900	99.10	-10.60	54.0	45.10	AV	27.00	150	Horizontal	N/A
3	4803.800	49.92	-1.21	74.0	-24.08	Peak	37.00	150	Horizontal	Pass
3**	4803.800	45.25	-1.21	54.0	-8.75	AV	37.00	150	Horizontal	Pass
4	6646.600	52.10	4.41	74.0	-21.90	Peak	247.00	150	Horizontal	Pass
4**	6646.600	43.41	4.41	54.0	-10.59	AV	247.00	150	Horizontal	Pass
5	8072.950	49.51	18.51	74.0	-24.49	Peak	0.00	150	Horizontal	Pass
5**	8072.950	36.00	18.51	54.0	-18.00	AV	0.00	150	Horizontal	Pass
6	15505.463	54.64	23.92	74.0	-19.36	Peak	204.00	150	Horizontal	Pass
6**	15505.463	43.69	23.92	54.0	-10.31	AV	204.00	150	Horizontal	Pass

8-DPSK LOW CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1536.600	36.59	-15.08	74.0	-37.41	Peak	268.00	150	Vertical	Pass
1**	1536.600	26.91	-15.08	54.0	-27.09	AV	268.00	150	Vertical	Pass
2	2402.100	86.88	-10.57	74.0	12.88	Peak	22.00	150	Vertical	N/A
2**	2402.100	84.41	-10.57	54.0	30.41	AV	22.00	150	Vertical	N/A
3	4914.000	48.09	-1.06	74.0	-25.91	Peak	300.00	150	Vertical	Pass
3**	4914.000	38.80	-1.06	54.0	-15.20	AV	300.00	150	Vertical	Pass
4	6559.400	51.06	2.97	74.0	-22.94	Peak	75.00	150	Vertical	Pass
4**	6559.400	42.41	2.97	54.0	-11.59	AV	75.00	150	Vertical	Pass
5	11651.463	49.55	20.37	74.0	-24.45	Peak	281.00	150	Vertical	Pass
5**	11651.463	38.37	20.37	54.0	-15.63	AV	281.00	150	Vertical	Pass
6	15693.674	54.37	23.58	74.0	-19.63	Peak	121.00	150	Vertical	Pass
6**	15693.674	42.57	23.58	54.0	-11.43	AV	121.00	150	Vertical	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1764.700	38.25	-14.70	74.0	-35.75	Peak	166.00	150	Horizontal	Pass
1**	1764.700	28.19	-14.70	54.0	-25.81	AV	166.00	150	Horizontal	Pass
2	2440.900	102.17	-10.41	74.0	28.17	Peak	39.00	150	Horizontal	N/A
2**	2440.900	101.03	-10.41	54.0	47.03	AV	39.00	150	Horizontal	N/A
3	4905.600	48.11	-0.84	74.0	-25.89	Peak	23.00	150	Horizontal	Pass
3**	4905.600	37.73	-0.84	54.0	-16.27	AV	23.00	150	Horizontal	Pass
4	6900.400	51.71	4.80	74.0	-22.29	Peak	149.00	150	Horizontal	Pass
4**	6900.400	41.75	4.80	54.0	-12.25	AV	149.00	150	Horizontal	Pass
5	10404.575	49.37	18.52	74.0	-24.63	Peak	122.00	150	Horizontal	Pass
5**	10404.575	36.18	18.52	54.0	-17.82	AV	122.00	150	Horizontal	Pass
6	15948.826	54.43	23.94	74.0	-19.57	Peak	0.00	150	Horizontal	Pass
6**	15948.826	44.41	23.94	54.0	-9.59	AV	0.00	150	Horizontal	Pass

8-DPSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1478.500	36.84	-15.00	74.0	-37.16	Peak	269.00	150	Vertical	Pass
1**	1478.500	27.80	-15.00	54.0	-26.20	AV	269.00	150	Vertical	Pass
2	2441.000	90.88	-10.42	74.0	16.88	Peak	36.00	150	Vertical	N/A
2**	2441.000	89.15	-10.42	54.0	35.15	AV	36.00	150	Vertical	N/A
3	4747.800	48.53	-1.83	74.0	-25.47	Peak	260.00	150	Vertical	Pass
3**	4747.800	39.17	-1.83	54.0	-14.83	AV	260.00	150	Vertical	Pass
4	6699.200	51.02	2.93	74.0	-22.98	Peak	109.00	150	Vertical	Pass
4**	6699.200	41.07	2.93	54.0	-12.93	AV	109.00	150	Vertical	Pass
5	10549.763	48.47	18.28	74.0	-25.53	Peak	63.00	150	Vertical	Pass
5**	10549.763	37.11	18.28	54.0	-16.89	AV	63.00	150	Vertical	Pass
6	15621.750	54.72	23.46	74.0	-19.28	Peak	211.00	150	Vertical	Pass
6**	15621.750	42.50	23.46	54.0	-11.50	AV	211.00	150	Vertical	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1794.100	37.41	-14.72	74.0	-36.59	Peak	259.00	150	Horizontal	Pass
1**	1794.100	28.14	-14.72	54.0	-25.86	AV	259.00	150	Horizontal	Pass
2	2479.900	100.65	-10.26	74.0	26.65	Peak	15.00	150	Horizontal	N/A
2**	2479.900	97.83	-10.26	54.0	43.83	AV	15.00	150	Horizontal	N/A
3	4960.000	48.83	-1.74	74.0	-25.17	Peak	36.00	150	Horizontal	Pass
3**	4960.000	41.65	-1.74	54.0	-12.35	AV	36.00	150	Horizontal	Pass
4	6781.200	52.13	3.39	74.0	-21.87	Peak	63.00	150	Horizontal	Pass
4**	6781.200	41.45	3.39	54.0	-12.55	AV	63.00	150	Horizontal	Pass
5	9897.713	49.12	17.71	74.0	-24.88	Peak	262.00	150	Horizontal	Pass
5**	9897.713	37.30	17.71	54.0	-16.70	AV	262.00	150	Horizontal	Pass
6	15500.738	54.40	23.96	74.0	-19.60	Peak	140.00	150	Horizontal	Pass
6**	15500.738	43.66	23.96	54.0	-10.34	AV	140.00	150	Horizontal	Pass

8-DPSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1461.600	36.52	-14.75	74.0	-37.48	Peak	75.00	150	Vertical	Pass
1**	1461.600	27.01	-14.75	54.0	-26.99	AV	75.00	150	Vertical	Pass
2	2479.800	89.03	-10.26	74.0	15.03	Peak	75.00	150	Vertical	N/A
2**	2479.800	83.91	-10.26	54.0	29.91	AV	75.00	150	Vertical	N/A
3	4429.000	46.36	-2.12	74.0	-27.64	Peak	360.00	150	Vertical	Pass
3**	4429.000	37.92	-2.12	54.0	-16.08	AV	360.00	150	Vertical	Pass
4	6630.200	51.90	3.64	74.0	-22.10	Peak	103.00	150	Vertical	Pass
4**	6630.200	41.85	3.64	54.0	-12.15	AV	103.00	150	Vertical	Pass
5	9122.612	49.02	17.85	74.0	-24.98	Peak	188.00	150	Vertical	Pass
5**	9122.612	35.79	17.85	54.0	-18.21	AV	188.00	150	Vertical	Pass
6	15492.862	54.54	23.86	74.0	-19.46	Peak	360.00	150	Vertical	Pass
6**	15492.862	43.77	23.86	54.0	-10.23	AV	360.00	150	Vertical	Pass

Hopping Mode:

GFSK MODE 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1598.700	37.11	-15.16	74.0	-36.89	Peak	155.00	150	Horizontal	Pass
1**	1598.700	27.85	-15.16	54.0	-26.15	AV	155.00	150	Horizontal	Pass
2	2469.000	103.53	-10.61	74.0	29.53	Peak	23.00	150	Horizontal	N/A
2**	2469.000	102.80	-10.61	54.0	48.80	AV	23.00	150	Horizontal	N/A
3	4948.200	50.91	-1.61	74.0	-23.09	Peak	32.00	150	Horizontal	Pass
3**	4948.200	43.50	-1.61	54.0	-10.50	AV	32.00	150	Horizontal	Pass
4	6758.000	51.80	4.25	74.0	-22.20	Peak	0.00	150	Horizontal	Pass
4**	6758.000	41.18	4.25	54.0	-12.82	AV	0.00	150	Horizontal	Pass
5	11625.012	49.10	20.27	74.0	-24.90	Peak	4.00	150	Horizontal	Pass
5**	11625.012	37.46	20.27	54.0	-16.54	AV	4.00	150	Horizontal	Pass
6	17329.312	57.62	24.15	74.0	-16.38	Peak	360.00	150	Horizontal	Pass
6**	17329.312	44.01	24.15	54.0	-9.99	AV	360.00	150	Horizontal	Pass

GFSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1314.400	36.83	-14.69	74.0	-37.17	Peak	158.00	150	Vertical	Pass
1**	1314.400	27.66	-14.69	54.0	-26.34	AV	158.00	150	Vertical	Pass
2	2441.900	92.14	-10.46	74.0	18.14	Peak	33.00	150	Vertical	N/A
2**	2441.900	91.05	-10.46	54.0	37.05	AV	33.00	150	Vertical	N/A
3	4854.000	49.46	-1.32	74.0	-24.54	Peak	0.00	150	Vertical	Pass
3**	4854.000	42.79	-1.32	54.0	-11.21	AV	0.00	150	Vertical	Pass
4	6907.400	52.14	4.65	74.0	-21.86	Peak	221.00	150	Vertical	Pass
4**	6907.400	41.04	4.65	54.0	-12.96	AV	221.00	150	Vertical	Pass
5	11620.125	49.25	20.24	74.0	-24.75	Peak	280.00	150	Vertical	Pass
5**	11620.125	37.04	20.24	54.0	-16.96	AV	280.00	150	Vertical	Pass
6	15217.762	54.44	22.09	74.0	-19.56	Peak	132.00	150	Vertical	Pass
6**	15217.762	42.69	22.09	54.0	-11.31	AV	132.00	150	Vertical	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT H

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1972.600	39.45	-13.44	74.0	-34.55	Peak	230.00	150	Horizontal	Pass
1**	1972.600	29.41	-13.44	54.0	-24.59	AV	230.00	150	Horizontal	Pass
2	2424.000	101.95	-10.19	74.0	27.95	Peak	23.00	150	Horizontal	N/A
2**	2424.000	98.99	-10.19	54.0	44.99	AV	23.00	150	Horizontal	N/A
3	4833.600	50.21	-1.33	74.0	-23.79	Peak	33.00	150	Horizontal	Pass
3**	4833.600	42.97	-1.33	54.0	-11.03	AV	33.00	150	Horizontal	Pass
4	6553.200	51.20	3.16	74.0	-22.80	Peak	305.00	150	Horizontal	Pass
4**	6553.200	41.09	3.16	54.0	-12.91	AV	305.00	150	Horizontal	Pass
5	11528.412	50.10	19.52	74.0	-23.90	Peak	270.00	150	Horizontal	Pass
5**	11528.412	36.30	19.52	54.0	-17.70	AV	270.00	150	Horizontal	Pass
6	15868.763	54.77	23.35	74.0	-19.23	Peak	208.00	150	Horizontal	Pass
6**	15868.763	42.20	23.35	54.0	-11.80	AV	208.00	150	Horizontal	Pass

8-DPSK MODE 1 GHz to 18 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Over Limit (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1649.300	37.23	-15.23	74.0	-36.77	Peak	293.00	150	Vertical	Pass
1**	1649.300	27.73	-15.23	54.0	-26.27	AV	293.00	150	Vertical	Pass
2	2448.000	90.19	-10.37	74.0	16.19	Peak	29.00	150	Vertical	N/A
2**	2448.000	79.16	-10.37	54.0	25.16	AV	29.00	150	Vertical	N/A
3	4789.600	47.68	-1.95	74.0	-26.32	Peak	230.00	150	Vertical	Pass
3**	4789.600	39.76	-1.95	54.0	-14.24	AV	230.00	150	Vertical	Pass
4	6592.400	51.56	2.86	74.0	-22.44	Peak	284.00	150	Vertical	Pass
4**	6592.400	41.45	2.86	54.0	-12.55	AV	284.00	150	Vertical	Pass
5	10614.162	48.66	18.49	74.0	-25.34	Peak	103.00	150	Vertical	Pass
5**	10614.162	37.21	18.49	54.0	-16.79	AV	103.00	150	Vertical	Pass
6	15458.475	54.73	23.51	74.0	-19.27	Peak	48.00	150	Vertical	Pass
6**	15458.475	43.16	23.51	54.0	-10.84	AV	48.00	150	Vertical	Pass

A.9 Band Edge (Restricted-band band-edge)

Note [1]: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.
Note [2]: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.
Note [3]: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
Note [4]: The Level (dBuV/m) has been corrected by factor.

Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Factor (dB)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	52.135	31.47	74	21.865	52.135	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
GFSK	HIGH	52.754	31.40	74	21.246	52.754	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
8-DPSK	Low	52.536	31.47	74	21.464	52.536	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
8-DPSK	HIGH	51.941	31.40	74	22.059	51.941	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
GFSK(Hopping)	Low	52.446	31.47	74	21.554	52.446	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
GFSK(Hopping)	HIGH	52.479	31.40	74	21.521	52.479	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
8-DPSK (Hopping)	Low	52.496	31.47	74	21.504	52.496	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	51.808	31.40	74	22.192	51.808	PEAK	Pass
		N/A	N/A	54	N/A	N/A	AVERAGE	Pass

Test Plots

GFSK LOW CHANNEL, PEAK



GFSK HIGH CHANNEL, PEAK



8-DPSK LOW CHANNEL, PEAK



8-DPSK HIGH CHANNEL, PEAK



Hopping Mode:

GFSK LOW FREQUENCY BAND, PEAK



GFSK HIGH FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, PEAK



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2060102-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2060102-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2060102-AI.PDF”.

--END OF REPORT--