

TEST REPORT

Application No.: SUCR2507000669WM

Applicant: Guangdong OPPO Mobile Telecommunications Corp.,Ltd.

Address of Applicant: NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

Manufacturer: Guangdong OPPO Mobile Telecommunications Corp.,Ltd.

Address of Manufacturer: NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

Equipment Under Test (EUT):

EUT Name: Mobile Phone

Model No.: CPH2797

Trade Mark: OPPO

FCC ID: R9C-OP24203

Standard(s) : 47 CFR Part 15, Subpart E 15.407

Date of Receipt: 2025-07-17

Date of Test: 2025-07-25 to 2025-09-04

Date of Issue: 2025-09-09

Test Result:
Pass*

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Revision Record			
Version	Description	Date	Remark
01	Original	2025-09-09	/

Authorized for issue by:				
Tested By		<i>Nature Shen</i>		
		Nature_Shen/Project Engineer		
Approved By		<i>Cloud Peng</i>		
		Cloud Peng /Reviewer		

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Customer Declaration
Transmission in the Absence of Data		N/A	47 CFR Part 15, Subpart E 15.407 ©	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Radiated Emissions (Below 1GHz)		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2013) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2013) Section 12.4.2	Pass
26dB Emission bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band)		ANSI C63.10 (2020) Section 12.5.1	47 CFR Part 15, Subpart E 15.407 (e)	Pass
Maximum Conducted output power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Frequency Stability		ANSI C63.10 (2020) Section 6.8	47 CFR Part 15, Subpart E 15.407 (g)	N/A
Channel Move Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass
Channel Closing Transmission Time		KDB 905462 D02 Section 7.8.3	KDB 905462 D02 Section 5.1	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Environment Parameter	6
4.3 Description of Support Units	6
4.4 Measurement Uncertainty & Decision Rule	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
6.2 Transmission in the Absence of Data	11
7 Radio Spectrum Matter Test Results	12
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)	12
7.2 Radiated Emissions (Below 1GHz)	16
7.3 Radiated Emissions (Above 1GHz).....	21
7.4 Radiated Emissions which fall in the restricted bands	48
7.5 Duty Cycle	193
7.6 99% Bandwidth	194
7.7 26dB Emission bandwidth	195
7.8 Minimum 6 dB bandwidth (5.725-5.85 GHz band)	196
7.9 Maximum Conducted output power	197
7.10 Peak Power spectrum density	199
7.11 Frequency Stability	200
7.12 Non-occupancy period	201
7.13 Channel Move Time	204
7.14 Channel Closing Transmission Time	207
8 Test Setup Photo	210
9 EUT Constructional Details (EUT Photos).....	210
10 Appendix.....	211

4 General Information

4.1 Details of E.U.T.

Hardware Version:	11
Software Version:	Color OS 16.0
Power supply:	DC 3.75V from internal rechargeable battery which can be charged by AC/DC adapter
Operation Frequency/Number of channels (20MHz):	U-NII-1: 5180-5240MHz (4 Channels) U-NII-2A: 5260-5320MHz (4 Channels) U-NII-2C: 5500-5720MHz (12 Channels) U-NII-3: 5745-5825MHz (5 Channels)
Operation Frequency/Number of channels/(40MHz):	U-NII-1: 5190-5230MHz (2 Channels) U-NII-2A: 5270-5310MHz (2 Channels) U-NII-2C: 5510-5710MHz (6 Channels) U-NII-3: 5755-5795MHz (2 Channels)
Operation Frequency/Number of channels (80MHz):	U-NII-1: 5210MHz (1 Channel) U-NII-2A: 5290MHz (1 Channels) U-NII-2C: 5530-5690MHz (3 Channels) U-NII-3: 5775MHz (1 Channel)
Modulation Type:	802.11a: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM) 802.11be: OFDMA with enhancements (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM, 4096-QAM)
Channel Spacing:	802.11a/n/ac/ax/be 20: 20MHz 802.11n/ac/ax/be 40: 40MHz 802.11ac/ax/be 80: 80MHz 802.11ac/ax/be 160: 160MHz
DFS Function:	Slave without Radar detection
TPC Function:	Support TPC function
Antenna Type:	IFA Antenna
Antenna Gain:	5150MHz to 5250MHz: -3dBi(Ant8); 0dBi(Ant10); (Provided by the manufacturer) 5250MHz to 5350MHz: -4.5dBi(Ant8); -1dBi(Ant10); (Provided by the manufacturer) 5470MHz to 5725MHz: -5dBi(Ant8); -1.5dBi(Ant10); (Provided by the manufacturer) 5725MHz to 5850MHz: -5.5dBi(Ant8); -1.5dBi(Ant10); (Provided by the manufacturer)
Antenna Number:	2

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	25°C	3.75V
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 2.6\text{dB}$ (30MHz-1GHz)
		$\pm 2.7\text{dB}$ (1GHz-18GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 6336.01.

- **FCC**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. Has been recognized as an accredited testing laboratory. Designation Number: CN1321.

- **ISED**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. Has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
2	LISN	R&S	ENV216	SUWI-01-19-03	5/8/2025	5/7/2026
3	LISN	Schwarzbeck	ENV216	SUWI-01-19-04	5/8/2025	5/7/2026
4	Test Software	Tonscend	JS32-CE_4.0.0.2	SUWI-02-09-05	N.C.R	N.C.R
RF Conducted Test						
1	Shielding Room	Brilliant-emc	N/A	SUWI-04-08-01	11/9/2022	11/8/2025
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/20/2025	1/19/2026
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2024	11/20/2025
4	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/15/2025	1/14/2026
5	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	3/27/2025	3/26/2026
6	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-8-01	1/16/2025	1/15/2026
7	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	3/17/2025	3/16/2026
8	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	5/8/2025	5/7/2026
9	Wideband Radio Communication Test Sttion	Anritsu	MT8000A	SUWI-01-34-02	11/19/2024	11/18/2025
10	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
11	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/19/2024	11/18/2025
12	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/19/2024	11/18/2025
13	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
14	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/13/2025	2/12/2026
15	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2025	5/6/2026
16	Measurement Software	TST	TST 272 V2.0	SUWI-03-55-03	NCR	NCR
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/20/2025	1/19/2026
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-09	11/21/2024	11/20/2025
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/16/2025	1/15/2026
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	8/22/2024	8/21/2026
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/16/2025	1/15/2026
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/16/2025	1/15/2026
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/20/2025	1/19/2026
13	Wideband Radio Communication	Anritsu	MT8820C	SUWI-01-26-01	9/10/2024	9/9/2025

	Tester					
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	9/10/2024	9/9/2025
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/16/2025	1/15/2026
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/13/2025	2/12/2026
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR

Remark: NCR=No Calibration Requirement.

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is PIFA antenna no consideration of replacement. The best case gain of the

5150MHz to 5250MHz: -3dBi(Ant8); 0dBi(Ant10);

5250MHz to 5350MHz: -4.5dBi(Ant8); -1dBi(Ant10);

5470MHz to 5725MHz: -5dBi(Ant8); -1.5dBi(Ant10);

5725MHz to 5850MHz: -5.5dBi(Ant8); -1.5dBi(Ant10);

Antenna location: Refer to internal photo.

6.2 Transmission in the Absence of Data

6.2.1 Test Requirement:

47 CFR Part 15, Subpart E 15.407 (c)

6.2.2 Conclusion

6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C


Humidity: 43 % RH

Atmospheric Pressure: 101 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark 1: Level=Read Level+ Cable Loss+ LISN Factor

Remark 2: Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case.


Test Mode: 17; Line: Live line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2040	10.06	21.99	32.05	63.45	31.40	11.11	21.17	53.45	32.28	PASS
2	0.2670	10.01	23.27	33.28	61.21	27.93	13.98	23.99	51.21	27.22	PASS
3	0.4695	9.98	17.62	27.60	56.52	28.92	11.46	21.44	46.52	25.08	PASS
4	0.9015	9.85	18.75	28.60	56.00	27.40	12.06	21.91	46.00	24.09	PASS
5	1.7655	9.84	15.16	25.00	56.00	31.00	9.92	19.76	46.00	26.24	PASS
6	3.4350	9.77	10.98	20.75	56.00	35.25	6.21	15.98	46.00	30.02	PASS

Test Mode: 17; Line: Neutral Line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2445	9.94	21.86	31.80	61.94	30.14	15.04	24.98	51.94	26.96	PASS
2	0.3570	9.93	15.75	25.68	58.80	33.12	11.58	21.51	48.80	27.29	PASS
3	0.6405	9.97	11.00	20.97	56.00	35.03	7.06	17.03	46.00	28.97	PASS
4	1.1310	9.95	13.55	23.50	56.00	32.50	8.87	18.82	46.00	27.18	PASS
5	2.2740	9.86	10.10	19.96	56.00	36.04	5.43	15.29	46.00	30.71	PASS
6	3.7905	9.86	9.96	19.82	56.00	36.18	5.39	15.25	46.00	30.75	PASS

7.2 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
960-1000	500	3

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C

Humidity: 44 % RH


Atmospheric Pressure: 101 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have

		been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. For emission below 1GHz, through the pre-scan found the worst case is the lowest channel of 802.11a. Only the worst case is recorded in the report.
3. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.


Test Mode: 17; Polarity: Horizontal



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	49.1575	35.52	18.77	-34.18	20.11	40.00	19.89	218	341	Horizontal
2	55.22	32.90	18.20	-34.14	16.96	40.00	23.04	196	341	Horizontal
3	61.7675	31.47	17.42	-34.08	14.81	40.00	25.19	234	341	Horizontal
4	83.5925	36.88	14.62	-33.89	17.60	40.00	22.40	177	341	Horizontal
5	151.0075	34.18	19.10	-33.51	19.77	43.50	23.73	214	294	Horizontal
6	181.0775	37.59	16.48	-33.34	20.73	43.50	22.77	228	240	Horizontal

Test Mode: 17; Polarity: Vertical



Final Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	44.065	44.06	18.81	-34.18	28.69	40.00	11.31	196	171	Vertical
2	49.1575	46.53	18.77	-34.18	31.12	40.00	8.88	235	201	Vertical
3	55.22	37.92	18.20	-34.14	21.98	40.00	18.02	187	162	Vertical
4	59.585	37.77	17.54	-34.10	21.21	40.00	18.79	220	355	Vertical
5	83.835	43.62	14.67	-33.89	24.39	40.00	15.61	194	359	Vertical
6	94.7475	36.23	14.35	-33.82	16.76	43.50	26.74	218	71	Vertical

7.3 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.6

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (4) For transmitters operating in the 5.725-5.85 GHz band:
 (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.3.1 E.U.T. Operation

Operating Environment:


Temperature: 24 °C Humidity: 44 % RH Atmospheric Pressure: 101 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

Pre-scan	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram




7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

11a_TX_CH_36_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10785.2833	40.47	38.29	-30.34	48.42	74.00	25.58	Horizontal
2	12857.9667	39.56	39.43	-29.61	49.38	68.30	18.92	Horizontal
3	14804.5333	38.15	40.14	-27.32	50.97	68.30	17.33	Horizontal

11a_TX_CH_36_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10452.9333	41.52	38.13	-31.09	48.56	68.30	19.74	Vertical
2	13111.7333	38.71	39.68	-28.93	49.46	68.30	18.84	Vertical
3	15020.7333	39.43	40.06	-28.22	51.27	68.30	17.03	Vertical

11a_TX_CH_44_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10507.75	41.68	38.15	-31.04	48.79	68.30	19.51	Horizontal
2	12759.0667	39.98	39.31	-29.76	49.53	68.30	18.77	Horizontal
3	14839.0333	38.77	40.13	-27.56	51.34	68.30	16.96	Horizontal

11a_TX_CH_44_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10729.3167	41.20	38.26	-30.31	49.15	74.00	24.85	Vertical
2	12409.85	40.65	38.89	-29.05	50.49	74.00	23.51	Vertical
3	14885.4167	39.75	40.12	-27.88	51.99	68.30	16.31	Vertical

11a_TX_CH_48_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10446.0333	41.38	38.12	-31.10	48.40	68.30	19.90	Horizontal
2	12893.6167	39.13	39.47	-29.43	49.17	68.30	19.13	Horizontal
3	14867.7833	39.32	40.13	-27.76	51.69	68.30	16.61	Horizontal

11a_TX_CH_48_Veritical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10130.55	42.69	37.97	-32.04	48.62	68.30	19.68	Vertical
2	12719.9667	40.12	39.26	-29.61	49.77	68.30	18.53	Vertical
3	14839.4167	38.93	40.13	-27.56	51.50	68.30	16.80	Vertical

11a_TX_CH_52_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10712.45	40.43	38.26	-30.31	48.38	74.00	25.62	Horizontal
2	12891.7	39.79	39.47	-29.44	49.82	68.30	18.48	Horizontal
3	14496.7167	40.13	40.20	-29.01	51.32	74.00	22.68	Horizontal

11a_TX_CH_52_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10464.05	41.76	38.13	-31.08	48.82	68.30	19.48	Vertical
2	12181	40.76	38.62	-29.48	49.89	74.00	24.11	Vertical
3	14835.9667	38.99	40.13	-27.54	51.58	68.30	16.72	Vertical

11a_TX_CH_60_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10530.3667	40.84	38.17	-31.08	47.92	68.30	20.38	Horizontal
2	12723.8	39.48	39.27	-29.63	49.12	68.30	19.18	Horizontal
3	14839.0333	39.54	40.13	-27.56	52.11	68.30	16.19	Horizontal

11a_TX_CH_60_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10188.8167	41.59	37.99	-31.61	47.97	68.30	20.33	Vertical
2	12397.2	39.44	38.88	-28.99	49.33	74.00	24.67	Vertical
3	14350.6667	40.26	40.23	-28.89	51.60	68.30	16.70	Vertical

11a_TX_CH_64_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10668.3667	40.91	38.23	-30.58	48.56	74.00	25.44	Horizontal
2	11947.55	40.45	38.40	-29.10	49.75	74.00	24.25	Horizontal
3	14980.1	39.45	40.10	-28.08	51.48	68.30	16.82	Horizontal

11a_TX_CH_64_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10241.7167	43.30	38.02	-31.71	49.61	68.30	18.69	Vertical
2	11975.9167	39.95	38.40	-29.21	49.14	74.00	24.86	Vertical
3	14349.1333	39.88	40.23	-28.91	51.20	68.30	17.10	Vertical

11a_TX_CH_100_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10394.2833	41.78	38.10	-31.21	48.67	68.30	19.63	Horizontal
2	12644.0667	38.90	39.17	-29.71	48.36	74.00	25.64	Horizontal
3	14965.15	39.19	40.11	-28.06	51.24	68.30	17.06	Horizontal

11a_TX_CH_100_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10265.4833	42.77	38.03	-31.82	48.98	68.30	19.32	Vertical
2	12415.6	38.60	38.90	-29.10	48.40	74.00	25.60	Vertical
3	14886.1833	39.58	40.12	-27.88	51.82	68.30	16.48	Vertical

11a_TX_CH_116_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10409.6167	40.80	38.10	-31.15	47.76	68.30	20.54	Horizontal
2	12668.2167	39.14	39.20	-29.64	48.70	74.00	25.30	Horizontal
3	14337.25	40.31	40.23	-29.03	51.51	68.30	16.79	Horizontal

11a_TX_CH_116_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10457.9167	42.08	38.13	-31.08	49.12	68.30	19.18	Vertical
2	12223.1667	40.59	38.67	-29.60	49.66	74.00	24.34	Vertical
3	13810.1667	40.95	40.17	-29.17	51.94	68.30	16.36	Vertical

11a_TX_CH_140_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10454.4667	41.45	38.13	-31.09	48.49	68.30	19.81	Horizontal
2	12478.4667	40.73	38.97	-29.67	50.04	74.00	23.96	Horizontal
3	14486.75	40.23	40.20	-28.95	51.49	74.00	22.51	Horizontal

11a_TX_CH_140_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10525	42.00	38.16	-31.07	49.09	68.30	19.21	Vertical
2	12480	39.73	38.98	-29.68	49.03	74.00	24.97	Vertical
3	14975.1167	39.71	40.10	-28.07	51.74	68.30	16.56	Vertical

11a_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10455.2333	41.32	38.13	-31.09	48.36	68.30	19.94	Horizontal
2	12360.4	40.16	38.83	-29.38	49.62	74.00	24.38	Horizontal
3	14834.05	38.60	40.13	-27.52	51.21	68.30	17.09	Horizontal

11a_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10404.25	41.60	38.10	-31.15	48.55	68.30	19.75	Vertical
2	12413.6833	38.49	38.90	-29.08	48.30	74.00	25.70	Vertical
3	14836.7333	39.42	40.13	-27.54	52.01	68.30	16.29	Vertical

11a_TX_CH_157_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10486.6667	41.03	38.14	-31.05	48.13	68.30	20.17	Horizontal
2	12559.7333	39.96	39.07	-29.85	49.18	74.00	24.82	Horizontal
3	14983.55	39.32	40.10	-28.08	51.34	68.30	16.96	Horizontal

11a_TX_CH_157_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10451.4	41.60	38.13	-31.09	48.63	68.30	19.67	Vertical
2	12411	40.33	38.89	-29.06	50.16	74.00	23.84	Vertical
3	14485.9833	40.99	40.20	-28.94	52.25	74.00	21.75	Vertical

11a_TX_CH_165_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10500.0833	43.00	38.15	-31.03	50.12	68.30	18.18	Horizontal
2	12639.85	40.06	39.17	-29.73	49.50	74.00	24.50	Horizontal
3	14885.0333	39.15	40.12	-27.88	51.40	68.30	16.90	Horizontal

11a_TX_CH_165_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	10142.4333	43.11	37.97	-31.95	49.13	68.30	19.17	Vertical
2	12665.15	40.46	39.20	-29.65	50.01	74.00	23.99	Vertical
3	14476.0167	40.39	40.20	-28.88	51.72	74.00	22.28	Vertical

7.4 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.10.5

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
 (4) For transmitters operating in the 5.725-5.85 GHz band:
 (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
 Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.4.1 E.U.T. Operation

Operating Environment:

Temperature: 24 °C

Humidity: 44 % RH


Atmospheric Pressure: 101 mbar

7.4.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Pre-scan	09	TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

Pre-scan	10	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	14	Charge + TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	15	Charge + TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	16	Charge + TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	17	Charge + TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.4.3 Test Setup Diagram



7.4.4 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.


Remark 3. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

11ac(VHT20)_TX_CH_36_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5141.3	39.18	33.17	-16.08	56.27	74.00	17.73	Horizontal
2	5147.6	38.93	33.17	-16.07	56.03	74.00	17.97	Horizontal

11ac(VHT20)_TX_CH_36_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5139.76	27.05	33.17	-16.08	44.14	54.00	9.86	Horizontal
2	5149.28	27.29	33.17	-16.07	44.39	54.00	9.61	Horizontal

11ac(VHT20)_TX_CH_36_Vetical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5135.7	39.42	33.17	-16.09	56.50	74.00	17.50	Vertical
2	5148.02	39.78	33.17	-16.07	56.88	74.00	17.12	Vertical

11ac(VHT20)_TX_CH_36_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5138.64	26.89	33.17	-16.08	43.98	54.00	10.02	Vertical
2	5147.6	27.07	33.17	-16.07	44.17	54.00	9.83	Vertical

11ac(VHT40)_TX_CH_38_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5143.2	37.98	33.17	-16.08	55.07	74.00	18.93	Horizontal
2	5353.8	40.26	33.13	-15.80	57.59	74.00	16.41	Horizontal

11ac(VHT40)_TX_CH_38_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.6	28.24	33.17	-16.07	45.34	54.00	8.66	Horizontal
2	5352	28.55	33.13	-15.80	45.88	54.00	8.12	Horizontal

11ac(VHT40)_TX_CH_38_Vetical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5146.2	38.64	33.17	-16.07	55.74	74.00	18.26	Vertical
2	5351.7	40.42	33.13	-15.80	57.75	74.00	16.25	Vertical

11ac(VHT40)_TX_CH_38_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5146.2	27.55	33.17	-16.07	44.65	54.00	9.35	Vertical
2	5352	28.47	33.13	-15.80	45.80	54.00	8.20	Vertical

11ac(VHT80)_TX_CH_42_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.3	40.33	33.17	-16.07	57.43	74.00	16.57	Horizontal
2	5350.8	39.58	33.13	-15.80	56.91	74.00	17.09	Horizontal

11ac(VHT80)_TX_CH_42_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.6	28.90	33.17	-16.07	46.00	54.00	8.00	Horizontal
2	5352	28.70	33.13	-15.80	46.03	54.00	7.97	Horizontal

11ac(VHT80)_TX_CH_42_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.6	39.25	33.17	-16.07	56.35	74.00	17.65	Vertical
2	5354.1	39.13	33.13	-15.80	56.46	74.00	17.54	Vertical

11ac(VHT80)_TX_CH_42_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.3	28.04	33.17	-16.07	45.14	54.00	8.86	Vertical
2	5353.8	28.38	33.13	-15.80	45.71	54.00	8.29	Vertical

11ac(VHT160)_TX_CH_50_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5116	42.65	33.18	-16.12	59.70	74.00	14.30	Horizontal
2	5381.5	42.55	33.12	-15.81	59.86	74.00	14.14	Horizontal

11ac(VHT160)_TX_CH_50_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5142.5	30.25	33.17	-16.08	47.34	54.00	6.66	Horizontal
2	5355	31.55	33.13	-15.80	48.88	54.00	5.12	Horizontal

11ac(VHT160)_TX_CH_50_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBµV]	AF [dB/m]	Factor [dB]	Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Polarity
1	5143	40.14	33.17	-16.08	57.23	74.00	16.77	Vertical
2	5372.5	41.37	33.13	-15.81	58.69	74.00	15.31	Vertical

11ac(VHT160)_TX_CH_50_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5144	29.27	33.17	-16.08	46.37	54.00	7.63	Vertical
2	5352	29.56	33.13	-15.80	46.89	54.00	7.11	Vertical

11ac(VHT80)_TX_CH_58_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5148	38.76	33.17	-16.07	55.86	74.00	18.14	Horizontal
2	5352.6	40.83	33.13	-15.80	58.16	74.00	15.84	Horizontal

11ac(VHT80)_TX_CH_58_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.3	27.34	33.17	-16.07	44.44	54.00	9.56	Horizontal
2	5352.3	31.08	33.13	-15.80	48.41	54.00	5.59	Horizontal

11ac(VHT80)_TX_CH_58_Vetical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5147.1	38.46	33.17	-16.07	55.56	74.00	18.44	Vertical
2	5352.3	39.57	33.13	-15.80	56.90	74.00	17.10	Vertical

11ac(VHT80)_TX_CH_58_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5144.7	27.52	33.17	-16.07	44.62	54.00	9.38	Vertical
2	5353.8	28.93	33.13	-15.80	46.26	54.00	7.74	Vertical

11ac(VHT40)_TX_CH_62_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5145.3	38.71	33.17	-16.07	55.81	74.00	18.19	Horizontal
2	5369.1	39.26	33.13	-15.80	56.58	74.00	17.42	Horizontal

11ac(VHT40)_TX_CH_62_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5146.5	27.31	33.17	-16.07	44.41	54.00	9.59	Horizontal
2	5351.7	29.47	33.13	-15.80	46.80	54.00	7.20	Horizontal

11ac(VHT40)_TX_CH_62_Vetical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5146.2	38.41	33.17	-16.07	55.51	74.00	18.49	Vertical
2	5355.3	40.25	33.13	-15.80	57.58	74.00	16.42	Vertical

11ac(VHT40)_TX_CH_62_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5147.7	27.80	33.17	-16.07	44.90	54.00	9.10	Vertical
2	5355.6	28.77	33.13	-15.80	46.10	54.00	7.90	Vertical

11ac(VHT20)_TX_CH_64_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5351.1	39.73	33.13	-15.80	57.06	74.00	16.94	Horizontal
2	5357.1	39.55	33.13	-15.80	56.88	74.00	17.12	Horizontal

11ac(VHT20)_TX_CH_64_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5350.8	27.62	33.13	-15.80	44.95	54.00	9.05	Horizontal
2	5359	27.60	33.13	-15.80	44.93	54.00	9.07	Horizontal

11ac(VHT20)_TX_CH_64_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5350.7	39.50	33.13	-15.80	56.83	74.00	17.17	Vertical
2	5357.4	39.36	33.13	-15.80	56.69	74.00	17.31	Vertical

11ac(VHT20)_TX_CH_64_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5352	27.60	33.13	-15.80	44.93	54.00	9.07	Vertical
2	5358	27.61	33.13	-15.80	44.94	54.00	9.06	Vertical

11ac(VHT20)_TX_CH_100_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5455.64	38.73	33.11	-15.50	56.34	74.00	17.66	Horizontal
2	5465.9	38.70	33.11	-15.44	56.36	68.30	11.94	Horizontal

11ac(VHT20)_TX_CH_100_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5440.06	27.51	33.11	-15.59	45.03	54.00	8.97	Horizontal
2	5456.78	27.39	33.11	-15.50	45.00	54.00	9.00	Horizontal

11ac(VHT20)_TX_CH_100_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5456.02	38.61	33.11	-15.50	56.22	74.00	17.78	Vertical
2	5466.28	38.31	33.11	-15.44	55.97	68.30	12.33	Vertical

11ac(VHT20)_TX_CH_100_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5440.63	27.26	33.11	-15.59	44.78	54.00	9.22	Vertical
2	5457.92	27.20	33.11	-15.49	44.82	54.00	9.18	Vertical

11ac(VHT40)_TX_CH_102_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5437.98	39.49	33.11	-15.60	57.00	74.00	17.00	Horizontal
2	5461.635	41.32	33.11	-15.47	58.96	68.30	9.34	Horizontal
3	5730.14	38.76	33.88	-14.93	57.72	68.30	10.58	Horizontal

11ac(VHT40)_TX_CH_102_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5433	28.43	33.11	-15.63	45.91	54.00	8.09	Horizontal
2	5452.505	28.39	33.11	-15.52	45.98	54.00	8.02	Horizontal

11ac(VHT40)_TX_CH_102_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5446.28	39.98	33.11	-15.56	57.53	74.00	16.47	Vertical
2	5463.295	39.42	33.11	-15.46	57.07	68.30	11.23	Vertical
3	5730.555	38.57	33.88	-14.92	57.53	68.30	10.77	Vertical

11ac(VHT40)_TX_CH_102_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5425.945	28.09	33.11	-15.67	45.53	54.00	8.47	Vertical
2	5454.995	28.29	33.11	-15.51	45.89	54.00	8.11	Vertical

11ac(VHT80)_TX_CH_106_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5435.905	39.33	33.11	-15.62	56.83	74.00	17.17	Horizontal
2	5465.37	40.25	33.11	-15.45	57.91	68.30	10.39	Horizontal
3	5733.46	38.15	33.89	-14.90	57.14	68.30	11.16	Horizontal

11ac(VHT80)_TX_CH_106_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5440.885	29.59	33.11	-15.59	47.11	54.00	6.89	Horizontal
2	5458.73	28.98	33.11	-15.49	46.60	54.00	7.40	Horizontal

11ac(VHT80)_TX_CH_106_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5440.47	39.20	33.11	-15.59	56.72	74.00	17.28	Vertical
2	5464.54	39.12	33.11	-15.45	56.77	68.30	11.53	Vertical
3	5732.63	39.24	33.89	-14.91	58.22	68.30	10.08	Vertical

11ac(VHT80)_TX_CH_106_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5429.265	28.22	33.11	-15.65	45.68	54.00	8.32	Vertical
2	5457.485	28.22	33.11	-15.49	45.84	54.00	8.16	Vertical

11ac(VHT160)_TX_CH_114_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5443.79	40.63	33.11	-15.57	58.17	74.00	15.83	Horizontal
2	5462.88	40.80	33.11	-15.46	58.45	68.30	9.85	Horizontal
3	5752.965	39.63	33.96	-14.77	58.82	68.30	9.48	Horizontal

11ac(VHT160)_TX_CH_114_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5416.815	29.60	33.12	-15.72	46.99	54.00	7.01	Horizontal
2	5434.66	29.81	33.11	-15.62	47.30	54.00	6.70	Horizontal

11ac(VHT160)_TX_CH_114_Vetical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5424.285	41.57	33.12	-15.68	59.00	74.00	15.00	Vertical
2	5463.71	40.35	33.11	-15.46	58.00	68.30	10.30	Vertical
3	5741.76	39.30	33.92	-14.85	58.38	68.30	9.92	Vertical

11ac(VHT160)_TX_CH_114_Vetical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5391.915	28.50	33.12	-15.82	45.81	54.00	8.19	Vertical
2	5430.925	28.82	33.11	-15.64	46.29	54.00	7.71	Vertical

11ac(VHT40)_TX_CH_134_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5441.3	39.37	33.11	-15.58	56.90	74.00	17.10	Horizontal
2	5460.805	39.41	33.11	-15.47	57.04	68.30	11.26	Horizontal
3	5731.8	39.35	33.89	-14.91	58.32	68.30	9.98	Horizontal

11ac(VHT40)_TX_CH_134_Horizontal_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5440.055	28.49	33.11	-15.59	46.01	54.00	7.99	Horizontal
2	5454.995	28.14	33.11	-15.51	45.74	54.00	8.26	Horizontal

11ac(VHT40)_TX_CH_134_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5450.015	40.19	33.11	-15.53	57.77	74.00	16.23	Vertical
2	5469.105	39.92	33.11	-15.43	57.60	68.30	10.70	Vertical
3	5737.61	39.04	33.91	-14.87	58.07	68.30	10.23	Vertical

11ac(VHT40)_TX_CH_134_Vertical_Average




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5424.7	28.60	33.12	-15.68	46.04	54.00	7.96	Vertical
2	5450.015	28.36	33.11	-15.53	45.94	54.00	8.06	Vertical

11ac(VHT20)_TX_CH_140_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5726.6	38.29	33.87	-14.95	57.21	68.30	11.09	Horizontal
2	5737.85	40.28	33.91	-14.87	59.32	68.30	8.98	Horizontal

11ac(VHT20)_TX_CH_140_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5725.85	39.00	33.87	-14.95	57.91	68.30	10.39	Vertical
2	5735.15	38.89	33.90	-14.89	57.90	68.30	10.40	Vertical

11ac(VHT20)_TX_CH_149_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5644.825	39.50	33.59	-15.23	57.86	68.30	10.44	Horizontal
2	5670.825	39.11	33.68	-15.18	57.61	83.75	26.14	Horizontal
3	5713.4	39.99	33.83	-15.04	58.78	109.05	50.27	Horizontal
4	5722.5	39.19	33.86	-14.98	58.07	116.60	58.53	Horizontal

11ac(VHT20)_TX_CH_149_Vertical_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5638.325	38.72	33.57	-15.24	57.05	68.30	11.25	Vertical
2	5676.025	38.45	33.70	-15.17	56.98	87.60	30.62	Vertical
3	5708.2	38.78	33.81	-15.07	57.51	107.60	50.09	Vertical
4	5722.825	38.71	33.86	-14.97	57.59	117.34	59.75	Vertical

11ac(VHT40)_TX_CH_151_Horizontal_Peak




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5642.55	38.46	33.58	-15.23	56.81	68.30	11.49	Horizontal
2	5672.125	38.57	33.69	-15.18	57.08	84.71	27.63	Horizontal
3	5709.175	39.20	33.81	-15.07	57.94	107.87	49.93	Horizontal
4	5720.55	39.65	33.85	-14.99	58.51	112.15	53.64	Horizontal
5	5852.5	39.16	34.30	-14.49	58.97	116.60	57.63	Horizontal
6	5867.775	38.97	34.35	-14.50	58.82	107.32	48.50	Horizontal
7	5900.6	39.06	34.46	-14.53	58.99	86.32	27.33	Horizontal
8	5936.025	39.26	34.58	-14.54	59.30	68.30	9.00	Horizontal

11ac(VHT40)_TX_CH_151_Vertical_Peak



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5635.4	38.76	33.56	-15.25	57.07	68.30	11.23	Vertical
2	5679.925	38.65	33.71	-15.17	57.20	90.48	33.28	Vertical
3	5708.85	38.62	33.81	-15.07	57.36	107.78	50.42	Vertical
4	5720.225	39.07	33.85	-14.99	57.93	111.41	53.48	Vertical
5	5852.175	39.18	34.30	-14.49	58.99	117.34	58.35	Vertical
6	5866.475	39.14	34.35	-14.50	58.98	107.68	48.70	Vertical
7	5896.375	38.93	34.45	-14.53	58.85	89.44	30.59	Vertical
8	5933.75	38.41	34.57	-14.54	58.44	68.30	9.86	Vertical

11ac(VHT80)_TX_CH_155_Horizontal_Peak



Data List

NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	5634.1	39.22	33.56	-15.25	57.53	68.30	10.77	Horizontal
2	5680.9	42.05	33.72	-15.16	60.60	91.20	30.60	Horizontal
3	5710.8	42.18	33.82	-15.06	60.94	108.33	47.39	Horizontal
4	5723.8	43.27	33.86	-14.97	62.16	119.56	57.40	Horizontal
5	5852.825	41.42	34.30	-14.49	61.23	115.86	54.63	Horizontal
6	5866.8	39.77	34.35	-14.50	59.61	107.59	47.98	Horizontal
7	5917.175	39.45	34.52	-14.54	59.43	74.07	14.64	Horizontal
8	5935.375	39.91	34.58	-14.54	59.95	68.30	8.35	Horizontal