

TEST REPORT

Application No.: SUCR2507000669WM
Applicant: Guangdong OPPO Mobile Telecommunications Corp.,Ltd.
Address of Applicant: NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China
Manufacturer: Guangdong OPPO Mobile Telecommunications Corp.,Ltd.
Address of Manufacturer: NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China
EUT Description: Mobile Phone
Model No.: CPH2797
Trade Mark: OPPO
FCC ID: R9C-OP24203
Standards: FCC 47 CFR Part 15, Subpart E
Date of Receipt: 2025-07-17
Date of Test: 2025-07-25 to 2025-09-04
Date of Issue: 2025-09-09

Test Result :	PASS *
----------------------	---------------

* In the configuration tested, the EUT detailed in this report complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Version

Revision Record			
Version	Description	Date	Remark
01	Original	2025-09-09	

Authorized for issue by:			
Tested By		<i>Nature Shen</i>	
		Nature Shen / Project Manager	
Approved By		<i>Cloud Peng</i>	
		Cloud Peng/Technical Manager	

Contents

Version	2
1 Test Summary.....	4
2 General Information	5
2.1 Details of Client	5
2.2 Test Location	5
2.3 Test Facility	5
2.4 General Description of EUT	6
2.5 Test Environment and Mode	9
2.6 Description of Support Units	9
2.7 Worst-case configuration and mode.....	9
3 Equipment List	10
4 Measurement Uncertainty (95% confidence levels, k=2)	12
5 Test results and Measurement Data.....	13
5.1 Antenna Requirement.....	13
5.2 AC Power Line Conducted Emissions.....	15
5.3 Duty Cycle	19
5.4 Maximum e.i.r.p.	20
5.5 26dB Emission Bandwidth	21
5.6 99% Occupied Bandwidth.....	22
5.7 Power Spectral Density.....	23
5.8 In-Band Emissions.....	24
5.9 Contention Based Protocol	25
5.10 Radiated Spurious Emissions	27
5.11 Restricted bands around fundamental frequency.....	29
6 Photographs - Setup Photos	31
7 Appendix.....	32

1 Test Summary

Test Item	FCC Rule No.	Test Requirements	Test Result	Result
Antenna Requirement	15.203/15.407(a)	--	Clause 5.1	PASS
AC Power Line Conducted Emissions	15.407(b)(8)	< FCC 15.207 limits	Clause 5.2	PASS
Duty Cycle	--	No limit.	Clause 5.3	For Report Purpose
Maximum e.i.r.p.	15.407(a)(8) 15.407(a)(5)	< 24dBm over the frequency band of Operation, e.i.r.p. the maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm.	Clause 5.4	PASS
26dB Emission Bandwidth	15.407(a)(11)	The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.	Clause 5.5	PASS
99% Occupied Bandwidth	-	No limit.	Clause 5.6	For Report Purpose
Maximum Power Spectral Density	15.407(a)(8) 15.407(a)(5)	< -1dBm/MHz e.i.r.p. not exceed 5 dBm e.i.r.p. in any 1-megahertz band	Clause 5.7	PASS
In-Band Emissions	15.407(b)(7)	EUT must meet the limits detailed in 15.407(b)(7)	Clause 5.8	PASS
Contention Based Protocol	15.407(d)(6)	EUT must detect AWGN signal with 90% (or better) certainty	Clause 5.9	PASS
Unwanted Emissions that fall Out of the Restricted Bands (Radiated)	15.407(b)(6) 15.205, 15.209	< -27dBm/MHz e.i.r.p. outside of the 5.925 - 7.125GHz band	Clause 5.10	PASS
Unwanted Emissions in the Restricted Bands (Radiated)	15.407(b)(6) 15.205, 15.209	Emissions in restricted bands must meet the radiated limits detailed in 15.209	Clause 5.11	PASS

2 General Information

2.1 Details of Client

Applicant:	Guangdong OPPO Mobile Telecommunications Corp.,Ltd.
Address of Applicant:	NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China
Manufacturer:	Guangdong OPPO Mobile Telecommunications Corp.,Ltd.
Address of Manufacturer:	NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

2.2 Test Location

Company:	SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.
Address:	South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone
Post code:	215000
Test engineer:	King-p Li

2.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

- **FCC –Designation Number: CN1312**

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an accredited testing laboratory.

Designation Number: CN1312.

Test Firm Registration Number: 717327

2.4 General Description of EUT

Hardware Version:	11	
Software Version:	Color OS 16.0	
Power Supply:	DC 3.75V from internal rechargeable battery which can be charged by AC/DC adapter	
IMEI:	RF Conducted	862847080019855
	RSE & AC power line	863215080048119
IEEE 802.11 WLAN Mode Supported:	☒ 802.11a (20 MHz channel bandwidth), ☒ 802.11ax/be (20 MHz channel bandwidth) ☒ 802.11ax/be (40 MHz channel bandwidth) ☒ 802.11ax/be (80 MHz channel bandwidth) ☒ 802.11ax/be (160 MHz channel bandwidth) ☒ 802.11be (320 MHz channel bandwidth)	
Operation Frequency:	5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz	
Type of Modulation:	OFDM/OFDMA	
FCC Classification:	6GHz Low Power Indoor Client (6XD)	
Antenna Type:	IFA Antenna	
Smart System:	☒ SISO	802.11a/n/ac/ax/be
	☒ MIMO	802.11a/n/ac/ax/be: 2Tx & 2Rx
	☒ Diversity	CDD: 802.11a: 2Tx & 2Rx
Antenna Gain:	ANT8:UNII-5:-5dBi; UNII-6:-6dBi; UNII-7:-9.5dBi; UNII-8:-10dBi; (Provided by the manufacturer) ANT10:UNII-5:-5dBi; UNII-6:-6dBi; UNII-7:-7dBi; UNII-8:-6.5dBi; (Provided by the manufacturer)	
RF Cable:	☒ Provided by client	
	2.5dB	
Remark: 1. As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information. 2. 802.11ax/be support OFDMA full RU tone and partial RU tone, both full RU and partial RU-left (for low CH) and partial RU-right (for high CH) test output power, the full RU power > partial RU, therefore the full RU perform full test to cover partial RU except for PSD/Duty cycle/BE.		

Remark:

In FCC 15.31, for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table, and the selected channel to perform the test as below:

Frequency range over which device operates	Number of Measurement Frequencies Required	Location of Measurement Frequency in Band of Operation
1 MHz or less	1	centre
1 MHz to 10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near centre, 1 near low end

For UNII-5:

Mode	Channel	Frequency(MHz)
IEEE 802.11a/ax/be 20MHz	1	5955
	45	6175
	93	6415
IEEE 802.11ax/be 40MHz	3	5965
	43	6165
	91	6405
IEEE 802.11ax/be 80MHz	7	5985
	39	6145
IEEE 802.11ax/be 160MHz	15	6025
	47	6185
	79	6345
IEEE 802.11be 320MHz	32	6105
	64	6265

For UNII-6:

Mode	Channel	Frequency(MHz)
IEEE 802.11a/ax/be 20MHz	97	6435
	105	6475
	113	6515
IEEE 802.11ax/be 40MHz	99	6445
	107	6485
	115	6525
IEEE 802.11ax/be 80MHz	87	6385
	103	6465
IEEE 802.11ax/be 160MHz	111	6505

For UNII-7:		
Mode	Channel	Frequency(MHz)
IEEE 802.11a/ax/be 20MHz	117	6535
	149	6695
	181	6855
	185	6875
IEEE 802.11ax/be 40MHz	123	6565
	147	6685
	179	6845
IEEE 802.11ax/be 80MHz	119	6545
	135	6625
	151	6705
	167	6785
	183	6865
IEEE 802.11ax/be 160MHz	143	6665
	175	6825

For UNII-8:		
Mode	Channel	Frequency(MHz)
IEEE 802.11a/ax/be 20MHz	189	6895
	209	6995
	233	7115
IEEE 802.11ax/be 40MHz	187	6885
	195	6925
	203	6965
	227	7085
IEEE 802.11ax/be 80MHz	199	6945
	215	7025
IEEE 802.11ax/be 160MHz	207	6985

2.5 Test Environment and Mode

Environment Parameter	101.0 kPa Selected Values During Tests	
Relative Humidity	44-46 % RH Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	22-25	3.75
Remark: NV: Normal Voltage NT: Normal Temperature		

2.6 Description of Support Units

The EUT has been tested as an independent unit.

2.7 Worst-case configuration and mode

Low data rate was used to test on antenna port conducted tests and radiated spurious emissions since it has the highest maximum power. Following are the worst-case data rates set for test:

Modulation Type	SISO - Data Rate	CDD/MIMO - Data Rate
802.11a	6 Mbps	/
802.11ax (HE 20)	MCS0 (8 Mbps)	MCS0 (16 Mbps)
802.11ax (HE 40)	MCS0 (16 Mbps)	MCS0 (32 Mbps)
802.11ax (HE 80)	MCS0 (34 Mbps)	MCS0 (68 Mbps)
802.11ax (HE 160)	MCS0 (68 Mbps)	MCS0 (136 Mbps)
802.11be (EHT 20)	MCS0 (8 Mbps)	MCS0 (16 Mbps)
802.11be (EHT 40)	MCS0 (16 Mbps)	MCS0 (32 Mbps)
802.11be (EHT 80)	MCS0 (34 Mbps)	MCS0 (68 Mbps)
802.11be (EHT 160)	MCS0 (68 Mbps)	MCS0 (136 Mbps)
802.11be (EHT 320)	MCS0 (136 Mbps)	MCS0 (272 Mbps)

3 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
2	LISN	R&S	ENV216	SUWI-01-19-03	5/8/2025	5/7/2026
3	LISN	Schwarzbeck	ENV216	SUWI-01-19-04	5/8/2025	5/7/2026
4	Test Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	N.C.R	N.C.R
RF Conducted Test						
1	Shielding Room	Brilliant-emc	N/A	SUWI-04-08-01	11/9/2022	11/8/2025
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/20/2025	1/19/2026
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2024	11/20/2025
4	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/15/2025	1/14/2026
5	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	3/27/2025	3/26/2026
6	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-8-01	1/16/2025	1/15/2026
7	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	3/17/2025	3/16/2026
8	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	5/8/2025	5/7/2026
9	Wideband Radio Communication Test Sttion	Anritsu	MT8000A	SUWI-01-34-02	11/19/2024	11/18/2025
10	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
11	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/19/2024	11/18/2025
12	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/19/2024	11/18/2025
13	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
14	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/13/2025	2/12/2026
15	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2025	5/6/2026
16	Measurement Software	TST	TST 272 V2.0	SUWI-03-55-03	NCR	NCR
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/20/2025	1/19/2026
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-09	11/21/2024	11/20/2025
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/15/2025	1/14/2026
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/16/2025	1/15/2026
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	8/22/2024	8/21/2026
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/16/2025	1/15/2026
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/16/2025	1/15/2026
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/20/2025	1/19/2026
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	9/10/2024	9/9/2025
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/19/2024	11/18/2025
15	Wideband Radio	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	9/10/2024	9/9/2025

	Communication Tester					
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/19/2024	11/18/2025
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/16/2025	1/15/2026
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/15/2025	1/14/2026
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/13/2025	2/12/2026
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR

Remark: NCR=No Calibration Requirement.

4 Measurement Uncertainty (95% confidence levels, k=2)

No.	Item	Measurement Uncertainty
1	Total RF power, conducted	$\pm 0.54\text{dB}$
2	RF power density, conducted	$\pm 1.03\text{dB}$
3	Spurious emissions, conducted	$\pm 0.54\text{dB}$
4	Radio Frequency	1%
5	Duty Cycle	$\pm 0.37\%$
6	Occupied Bandwidth	1%
7	Conduction Emission	$\pm 2.9\text{dB}$ (150kHz to 30MHz)
8	Radiated Emission(966-01)	$\pm 3.13\text{dB}$ (9k -30MHz)
		$\pm 4.88\text{dB}$ (30M -1GHz)
		$\pm 4.75\text{dB}$ (1GHz to 18GHz)
		$\pm 4.77\text{dB}$ (Above 18GHz)

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15 Section 15.203
The antenna is IFA Antenna and no consideration of replacement. The best case gain of the antenna is ANT8:UNII-5:-5dBi; UNII-6:-6dBi; UNII-7:-9.5dBi; UNII-8:-10dBi;* ANT10:UNII-5:-5dBi; UNII-6:-6dBi; UNII-7:-7dBi; UNII-8:-6.5dBi;* <i>Note:</i> The antenna gain are derived from the gain information report provided by the manufacturer. <i>Remark:</i> As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.	

Cyclic Delay Diversity (CDD) System:

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

If all antennas have the same gain, G_{ANT} , Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,
Array Gain = $10 \log(N_{ANT}/N_{SS}=1)$ dB.
- For power measurements on IEEE 802.11 devices:
Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

For power, the directional gain may be calculated by using the formulas applicable to equal gain antennas with G_{ANT} set equal to the gain of the antenna having the highest gain.

For PSD, the directional gain calculation is following F)2)f)ii) of KDB 662911 D01 v02r01.

The Power and PSD limit should be modified if the directional gain of eut is over 6dbi.

The EUT supports CDD System.

Unequal antenna gain:

Operation Frequency	ANT Gain0 (dBi)	ANT Gain1 (dBi)	Directional gain For Power (dBi)	Directional gain For PSD (dBi)
5925 MHz to 6425 MHz	-5	-5	-5	-1.99
6425 MHz to 6525 MHz	-6	-6	-6	-2.99
6525 MHz to 6875 MHz	-9.5	-7	-7	-5.15
6875 MHz to 7125 MHz	-10	-6.5	-6.5	-5.06

5925 MHz to 6425 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

6425 MHz to 6525 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

6525 MHz to 6875 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0


6875 MHz to 7125 MHz:

Power Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0

PSD Limit Reduction = Directional gain – 6dBi, (Directional gain < 6dBi) =0


5.2 AC Power Line Conducted Emissions

Test Requirement:	47 CFR Part 15 Section 15.407(b)		
Test Method:	ANSI C63.10: 2013 Section 6.2		
Test Frequency Range:	150kHz to 30MHz		
Receiver Setup:	RBW = 9kHz, VBW = 30kHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
* Decreases with the logarithm of the frequency.			
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.		


Test Setup:	
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Refer to section 2.7 for details. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.



Phase: Neutral




Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2445	9.94	21.86	31.80	61.94	30.14	15.04	24.98	51.94	26.96	PASS
2	0.3570	9.93	15.75	25.68	58.80	33.12	11.58	21.51	48.80	27.29	PASS
3	0.6405	9.97	11.00	20.97	56.00	35.03	7.06	17.03	46.00	28.97	PASS
4	1.1310	9.95	13.55	23.50	56.00	32.50	8.87	18.82	46.00	27.18	PASS
5	2.2740	9.86	10.10	19.96	56.00	36.04	5.43	15.29	46.00	30.71	PASS
6	3.7905	9.86	9.96	19.82	56.00	36.18	5.39	15.25	46.00	30.75	PASS


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Value = Reading[dBμV] + Factor(Lisn factor[dB] + cable loss[dB]).
3. Margin = Limit[dBμV] – Value[dBμV]


5.3 Duty Cycle

Test Requirement:	ANSI C63.10 :2013 Section 12.2
Test Method:	ANSI C63.10 :2013 Section 12.2
Test Setup:	 The diagram illustrates the test setup for Duty Cycle testing. A PC is connected to a Test system. The Test system consists of several modules: Vector Signal Generator, Spectrum Analyzer, Communication Tester, RF Control Unit, Analog Signal Generator, and DC Power. The RF Control Unit is connected to an E.U.T. (Equipment Under Test). All components are connected to a Ground Reference Plane.
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details.
Limit:	No restriction limits
Test Results:	For report purpose
The detailed test data see: Appendix	


5.4 Maximum e.i.r.p.

Test Requirement:	47 CFR Part 15 Section 15.407(a) 15.407(a)(5)
Test Method:	ANSI C63.10 :2013 Section11.9.2.3
Test Setup:	 * Test with power meter (Detector function: Average)
Test Instruments:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details.
Limit:	For client devices operating under the control of an indoor access point in the 5.925-7.125GHz bands, the maximum e.i.r.p. over the frequency band of operation must not exceed 24 dBm. For an indoor access point operating in the 5.925-7.125 GHz band, the maximum e.i.r.p. over the frequency band of operation must not exceed 30 dBm.
Test Results:	Pass
The detailed test data see: Appendix	


5.5 26dB Emission Bandwidth

Test Requirement:	47 CFR Part 15 Section 15.407(a), KDB 789033 D02
Test Method:	ANSI C63.10: 2013 Section 11.8 Option 2
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details.
Limit:	The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 megahertz.
Test Results:	Pass
The detailed test data see: Appendix	


5.6 99% Occupied Bandwidth

Test Requirement:	KDB 789033 D02§ D
Test Method:	ANSI C63.10: 2013 Section 6.9.3
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details.
Limit:	No restriction limits
Test Results:	For report purpose
The detailed test data see: Appendix	


5.7 Power Spectral Density

Test Requirement:	47 CFR Part 15 Section 15.407(a) 15.407(a)(5)
Test Method:	ANSI C63.10: 2013 Section 11.10.2 KDB 789033 D02 v02r01, Section F.
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details.
Limit:	For client devices operating under the control of an indoor access point in the 5.925-7.125GHz bands, the maximum power spectral density must not exceed -1 dBm e.i.r.p. in any 1-megahertz band. For an indoor access point operating in the 5.925-7.125 GHz band, the maximum power spectral density must not exceed 5 dBm e.i.r.p. in any 1-megahertz band.
Test Results:	Pass
The detailed test data see: Appendix	

5.8 In-Band Emissions

Test Requirement:	47 CFR Part 15 Section 15.407(b)(7)
Test Method:	KDB 987594 D02 U-NII 6GHz EMC Measurement v01
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Refer to section 2.7 for details. Only the worst case is recorded in the report.
Limit:	For transmitters operating within the 5.925-7.125 GHz bands: Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB.
Test Results:	Pass
The detailed test data see: Appendix	

5.9 Contention Based Protocol

Test Requirement:	47 CFR Part 15 Section 15.407(d)
Test Method:	ANSI C63.10: 2013 KDB 987594 D02 U-NII 6GHz EMC Measurement v01
Test Setup:	
Instruments Used:	Refer to section 3 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Test Procedure:	1) Configure the EUT to transmit with a constant duty cycle. 2) Set the operating parameters of the EUT including power level, operating frequency, modulation and bandwidth. 3) Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT. Connect the output port of the EUT to the signal analyzer 2, as shown in Figure 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver. 4) Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters set at step two. 5) Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10MHz-wide AWGN signal. Use Table 1 to determine the center frequency of the 10MHz AWGN signal relative to the EUT's channel bandwidth and center frequency. 6) Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT as shown in Figure 2. 7) Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1. 8) Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting. 9) (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty. 10) Refer to Table 1 to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step 5, choose a different center frequency for the AWGN signal and repeat the process.

Limit:	Unlicensed low-power indoor devices must detect co-channel radio frequency power that is at least -62 dBm or lower. Upon detection of energy in the band, unlicensed low power indoor devices must vacate the channel and stay off the channel as long as detected radio frequency power is equal to or greater than the threshold (-62 dBm). The -62 dBm (or lower) threshold is referenced to a 0 dBi antenna gain. To ensure incumbent operations are reliably detected in the band, low power indoor devices must detect RF energy throughout their intended operating channel. For example, an 802.11 device that plans to transmit a 40 MHz- wide signal (on a primary 20 MHz channel and a secondary 20 MHz channel) must detect energy throughout the entire 40 MHz channel. Additionally, low-power indoor devices must detect co-channel energy with 90% or greater certainty.
Test Results:	Pass
The detailed test data see: Appendix	

5.10 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15 Section 15.205 and 15.209
Test Method:	ANSI C63.10: 2013 Section 6.4 / 6.5 / 6.6
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)
Test frequency:	9kHz ~ 40GHz(or 10 Harmonic)

Test Setup:




Figure 1. 9kHz to 30MHz




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz


Test Procedure:	- For below 1GHz test, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. - For above 1GHz test, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation (Distance from antenna to EUT is 1m for measurements >18GHz). - The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. - For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the
-----------------	---

	rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. g. Test the EUT in the outermost channels. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is worse case. i. Repeat above procedures until all frequencies measured was complete. j. The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported k. The disturbance above 18GHz was very low, and the harmonics were the highest point could be found when testing, so only the harmonics had been displayed. l. At a measurement distance of 1 meter the limit line was increased by $20 \times \log(3/1) = 9.54$ dB.
Test Configuration:	Measurements below 30MHz • RBW = 10 kHz • VBW = 30 kHz • Detector = Peak & Average & Quasi-peak • Trace mode = max hold Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Refer to section 2.7 for details. For below 1GHz part, through pre-scan all channels, but only the worst case is recorded in the report.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass
The detailed test data see: Appendix	

5.11 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15 Section 15.407(b)		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:



Test Procedure:

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel
- Test the EUT in the outermost channels.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.

Test Configuration:	Measurements Below 1000MHz • RBW = 120 kHz • VBW = 300 kHz • Detector = Quasi-peak • Trace mode = max hold Peak Measurements Above 1000 MHz • RBW = 1 MHz • VBW $\geq$ 3 MHz • Detector = Peak • Sweep time = auto • Trace mode = max hold Average Measurements Above 1000MHz • RBW = 1 MHz • VBW = 10Hz, when duty cycle is no less than 98 percent. • VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Refer to section 2.7 for details.
Instruments Used:	Refer to section 3 for details
Test Results:	Pass
The detailed test data see: Appendix	

6 Photographs - Setup Photos

Refer to Appendix - Test Setup Photo for SUCR2507000669WM

7 Appendix

For WIFI 6E:

1. Duty Cycle

1.1 Test Result

1.1.1 Ant10

Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11a	MIMO	5955	/	/	1.394	1.445	96.47	0.16	0.03
			6175	/	/	1.392	1.445	96.33	0.16	0.03
			6415	/	/	1.393	1.445	96.40	0.16	0.10
	802.11ax (HEW20)	MIMO	5955	RU242	Left	1.015	1.066	95.22	0.21	0.07
			6175	RU242	Left	1.015	1.066	95.22	0.21	0.04
			6415	RU242	Left	1.014	1.066	95.12	0.22	0.07
	802.11ax (HEW40)	MIMO	5965	RU484	Left	0.535	0.586	91.30	0.40	0.07
			6165	RU484	Left	0.535	0.586	91.30	0.40	0.07
			6405	RU484	Left	0.534	0.586	91.13	0.40	0.06
	802.11ax (HEW80)	MIMO	5985	RU996	Left	0.291	0.340	85.59	0.68	0.05
			6145	RU996	Left	0.291	0.340	85.59	0.68	0.09
			6385	RU996	Left	0.289	0.340	85.00	0.71	0.06
	802.11ax (HEW160)	MIMO	6025	2xRU996	Left	0.171	0.223	76.68	1.15	23.24
			6185	2xRU996	Left	0.171	0.223	76.68	1.15	0.09
			6345	2xRU996	Left	0.027	0.079	34.18	4.66	43.07

1.1.2 Ant10

Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11a	MIMO	6435	/	/	1.393	1.445	96.40	0.16	0.03
			6475	/	/	1.393	1.445	96.40	0.16	0.03
			6515	/	/	1.392	1.444	96.40	0.16	0.03
	802.11ax (HEW20)	MIMO	6435	RU242	Left	1.014	1.066	95.12	0.22	0.07
			6475	RU242	Left	1.015	1.066	95.22	0.21	0.07
			6515	RU242	Left	1.014	1.066	95.12	0.22	0.07
	802.11ax (HEW40)	MIMO	6445	RU484	Left	0.534	0.586	91.13	0.40	0.09
			6485	RU484	Left	0.534	0.586	91.13	0.40	0.07
	802.11ax (HEW80)	MIMO	6465	RU996	Left	0.287	0.340	84.41	0.74	0.06

1.1.3 Ant10

Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11a	MIMO	6535	/	/	1.393	1.445	96.40	0.16	0.07
			6695	/	/	1.393	1.446	96.33	0.16	0.07
			6855	/	/	1.392	1.445	96.33	0.16	0.03
	802.11ax (HEW20)	MIMO	6535	RU242	Left	1.015	1.067	95.13	0.22	0.07
			6695	RU242	Left	1.014	1.066	95.12	0.22	0.07

			6855	RU242	Left	1.014	1.066	95.12	0.22	0.07
	802.11ax (HEW40)	MIMO	6565	RU484	Left	0.535	0.586	91.30	0.40	0.07
			6685	RU484	Left	0.535	0.586	91.30	0.40	0.10
			6845	RU484	Left	0.534	0.586	91.13	0.40	0.03
	802.11ax (HEW80)	MIMO	6625	RU996	Left	0.287	0.340	84.41	0.74	15.43
			6705	RU996	Left	0.287	0.340	84.41	0.74	0.10
			6785	RU996	Left	0.288	0.340	84.71	0.72	0.09
	802.11ax (HEW160)	MIMO	6665	2xRU996	Left	0.170	0.223	76.23	1.18	0.13

1.1.4 Ant10

Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11a	MIMO	6895	/	/	1.394	1.445	96.47	0.16	0.03
			6995	/	/	1.394	1.446	96.40	0.16	0.07
			7115	/	/	1.393	1.445	96.40	0.16	0.03
	802.11ax (HEW20)	MIMO	6895	RU242	Left	1.014	1.065	95.21	0.21	0.07
			6995	RU242	Left	1.015	1.067	95.13	0.22	0.07
			7115	RU242	Left	1.015	1.066	95.22	0.21	0.03
	802.11ax (HEW40)	MIMO	6925	RU484	Left	0.534	0.586	91.13	0.40	0.03
			7005	RU484	Left	0.535	0.586	91.30	0.40	0.10
			7085	RU484	Left	0.535	0.586	91.30	0.40	0.00
	802.11ax (HEW80)	MIMO	6945	RU996	Left	0.290	0.340	85.29	0.69	0.03
			7025	RU996	Left	0.288	0.340	84.71	0.72	0.06
	802.11ax (HEW160)	MIMO	6985	2xRU996	Left	0.173	0.223	77.58	1.10	0.18

1.1.5 Ant10


Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11a	MIMO	6875	/	/	1.393	1.445	96.40	0.16	0.03
	802.11ax (HEW20)	MIMO	6875	RU242	Left	1.015	1.066	95.22	0.21	0.07
	802.11ax (HEW40)	MIMO	6885	RU484	Left	0.534	0.586	91.13	0.40	0.07
	802.11ax (HEW80)	MIMO	6865	RU996	Left	0.287	0.340	84.41	0.74	0.09
	802.11ax (HEW160)	MIMO	6825	2xRU996	Left	0.173	0.223	77.58	1.10	0.12

1.1.6 Ant10


Ant10										
ENV	Mode	TX Type	Frequency (MHz)	RU	RU Pos	T_on (ms)	Period (ms)	Duty Cycle (%)	Duty Cycle Correction Factor (dB)	Max. DC Variation (%)
NTNV	802.11ax (HEW40)	MIMO	6525	RU484	Left	0.535	0.586	91.30	0.40	0.03
	802.11ax (HEW80)	MIMO	6545	RU996	Left	0.288	0.340	84.71	0.72	0.05
	802.11ax (HEW160)	MIMO	6505	2xRU996	Left	0.171	0.223	76.68	1.15	0.18

1.2 Test Graph


1.2.1 Ant10




802.11a_HCH_6415MHz_Ant10_NTNV




802.11ax(HEW20)_LCH_5955MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_MCH_6175MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_HCH_6415MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW40)_LCH_5965MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_MCH_6165MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_HCH_6405MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW80)_LCH_5985MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW80)_MCH_6145MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW80)_HCH_6385MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW160)_LCH_6025MHz_2xRU996_Left_Ant10_NTNV



802.11ax(HEW160)_MCH_6185MHz_2xRU996_Left_Ant10_NTNV




802.11ax(HEW160)_HCH_6345MHz_2xRU996_Left_Ant10_NTNV




1.2.2 Ant10


802.11a_LCH_6435MHz_Ant10_NTNV




802.11a_MCH_6475MHz_Ant10_NTNV




802.11a_HCH_6515MHz_Ant10_NTNV




802.11ax(HEW20)_LCH_6435MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_MCH_6475MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_HCH_6515MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW40)_LCH_6445MHz_RU484_Left_Ant10_NTNV



802.11ax(HEW40)_MCH_6485MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW80)_LCH_6465MHz_RU996_Left_Ant10_NTNV




1.2.3 Ant10


802.11a_LCH_6535MHz_Ant10_NTNV




802.11a_MCH_6695MHz_Ant10_NTNV




802.11a_HCH_6855MHz_Ant10_NTNV




802.11ax(HEW20)_LCH_6535MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_MCH_6695MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_HCH_6855MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW40)_LCH_6565MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_MCH_6685MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_HCH_6845MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW80)_LCH_6625MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW80)_MCH_6705MHz_RU996_Left_Ant10_NTNV



802.11ax(HEW80)_HCH_6785MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW160)_MCH_6665MHz_2xRU996_Left_Ant10_NTNV




1.2.4 Ant10


802.11a_LCH_6895MHz_Ant10_NTNV




802.11a_MCH_6995MHz_Ant10_NTNV




802.11a_HCH_7115MHz_Ant10_NTNV




802.11ax(HEW20)_LCH_6895MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_MCH_6995MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW20)_HCH_7115MHz_RU242_Left_Ant10_NTNV




802.11ax(HEW40)_LCH_6925MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_MCH_7005MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW40)_HCH_7085MHz_RU484_Left_Ant10_NTNV




802.11ax(HEW80)_LCH_6945MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW80)_HCH_7025MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW160)_MCH_6985MHz_2xRU996_Left_Ant10_NTNV




1.2.5 Ant10




802.11ax(HEW40) HCH_6885MHz_RU484_Left_Ant10_NTNV



802.11ax(HEW80) HCH_6865MHz_RU996_Left_Ant10_NTNV




802.11ax(HEW160)_HCH_6825MHz_2xRU996_Left_Ant10_NTNV




1.2.6 Ant10

802.11ax(HEW40)_HCH_6525MHz_RU484_Left_Ant10_NTNV



802.11ax(HEW80)_HCH_6545MHz_RU996_Left_Ant10_NTNV



802.11ax(HEW160)_HCH_6505MHz_2xRU996_Left_Ant10_NTNV

