

TEST REPORT

Applicant: Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address: NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China
Equipment Type: Mobile Phone
Model Name: CPH2817
Brand Name: OPPO
FCC ID: R9C-OP25255
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Aug. 20, 2025
Test Date: Aug. 22, 2025 - Sep. 30, 2025
Date of Issue: Sep. 30, 2025

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Qiu Yongjing**Checked by:** Zong Liyao**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Sep. 30, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	General Description for Equipment under Test (EUT).....	4
2.4	Ancillary Equipment.....	4
2.5	Technical Information	5
3	SUMMARY OF TEST RESULTS	6
3.1	Test Standards	6
3.2	Verdict.....	6
3.3	Test Uncertainty	6
4	GENERAL TEST CONFIGURATIONS	7
4.1	Test Enclosure List.....	7
4.2	Test Configurations	7
4.3	Test Setups	9
5	TEST ITEMS	11
5.1	Emission Tests	11
ANNEX A	TEST RESULTS.....	16
A.1	Radiated Emission.....	16
A.2	Conducted Emission, AC Ports.....	28
ANNEX B	TEST SETUP PHOTOS	33
ANNEX C	EUT EXTERNAL PHOTOS.....	33
ANNEX D	EUT INTERNAL PHOTOS.....	33

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The certification body is American Association for Laboratory Accreditation (A2LA).

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

2.2 Manufacturer Information

Manufacturer	Guangdong OPPO Mobile Telecommunications Corp., Ltd.
Address	NO.18 HaiBin Road, Wusha Village, Chang'an Town, DongGuan City, Guangdong Province, P.R. China

2.3 General Description for Equipment under Test (EUT)

EUT Name	Mobile Phone
Model Name Under Test	CPH2817
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	11
Software Version	ColorOS 15.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
EUT ID	SC-SZ2580357:S07
IMEI Number	SC-SZ2580357-S07: IMEI1: 864681080023098 IMEI2: 864681080023080

2.4 Ancillary Equipment

Please refer the document "BL-SZ2580928-AW EUT external photo.pdf".

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM/GPRS/EDGE 850/900/1800/1900 3G Network WCDMA/HSDPA/HSUPA/DC-HSDPA Band 1/2/4/5/8/6/19 4G Network FDD LTE Band 1/2/3/4/5/7/8/13/18/19/26/28/66 TDD LTE Band 38/40/41 Bluetooth (BR+EDR+BLE) 802.11a, 802.11b, 802.11g, 802.11n(HT20/40), 802.11ac(VHT20/40/80) GNSS
Classification of equipment	Class B
The highest internal frequency of EUT	5850 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	Pass	--

3.3 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions (9 kHz-30 MHz)	3.2 dB
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Laptop	N/A	N/A	N/A	N/A	N/A	☒
Data connector	N/A	N/A	N/A	N/A	N/A	☒
USB disk	N/A	N/A	N/A	N/A	N/A	☒
TF Card	N/A	N/A	N/A	N/A	N/A	☒
Earphone	N/A	N/A	N/A	N/A	N/A	☒
Type-C Earphone	N/A	N/A	N/A	N/A	N/A	☒
Wireless Communications Test Set	R&S	CMW500	102318	N/A	Cal. Due 2026.05.27	☒

4.2 Test Configurations

All test modes of EUT are listed in the table below.


Test Mode Configuration	Description
Mode 1	<u>The Front Camera Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
Mode 2	<u>The Rear Camera Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
Mode 3	<u>The Video Play Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
Mode 4	<u>The Charging Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Headset
Mode 5	<u>The USB Test Mode</u> EUT + USB Cable + Battery + Laptop + TF Card + Headset
Mode 6	<u>The OTG Test Mode</u> EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 7	<u>The Type-C Earphone Test Mode</u> EUT + Adapter + USB Cable + Battery + TF Card + Type-C Earphone
Mode 8	<u>The GSM 850 RX Test Mode</u> GSM 850 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 9	<u>The GSM 900 RX Test Mode</u> GSM 900 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 10	<u>The WCDMA Band 5 RX Test Mode</u>

	WCDMA Band 5 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 11	<u>The WCDMA Band 8 RX Test Mode</u> WCDMA Band 8 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 12	<u>The WCDMA Band 19 RX Test Mode</u> WCDMA Band 19 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 13	<u>The LTE Band 5 RX Test Mode</u> LTE Band 5 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 14	<u>The LTE Band 8 RX Test Mode</u> LTE Band 8 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 15	<u>The LTE Band 13 RX Test Mode</u> LTE Band 13 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 16	<u>The LTE Band 18 RX Test Mode</u> LTE Band 18 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 17	<u>The LTE Band 19 RX Test Mode</u> LTE Band 19 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 18	<u>The LTE Band 26 RX Test Mode</u> LTE Band 26 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset
Mode 19	<u>The LTE Band 28 RX Test Mode</u> LTE Band 28 RX + EUT + Battery + Data connector + USB Disk + TF Card + Headset


Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 19	4
Conducted Emission, AC Ports	Mode 1~Mode 5 Mode 8~Mode 19	4
Note: All operation modes were tested, but only test data of the worst mode was presented in this report.		

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission


Note 1: The symbol of "--" in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Sample No.	S07	Temperature	22.7℃
Humidity	45%RH	Pressure	101kPa
Test Engineer	Chen Jingran	Test Date	2025.09.25


Test Mode 4

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	38.487	26.54	-25.87	40.0	13.46	Peak	150.00	100	Vertical	Pass
2	42.513	26.44	-25.76	40.0	13.56	Peak	207.00	200	Vertical	Pass
3	45.374	26.34	-25.95	40.0	13.66	Peak	264.00	200	Vertical	Pass
4	146.594	27.75	-30.28	43.5	15.75	Peak	282.00	100	Vertical	Pass
5	267.262	27.00	-24.49	46.0	19.00	Peak	134.00	100	Vertical	Pass
6	291.366	23.52	-23.81	46.0	22.48	Peak	154.00	100	Vertical	Pass


2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	44.259	17.39	-25.98	40.0	22.61	Peak	152.00	100	Horizontal	Pass
2	82.234	16.45	-30.44	40.0	23.55	Peak	324.00	200	Horizontal	Pass
3	137.137	21.88	-30.35	43.5	21.62	Peak	0.00	200	Horizontal	Pass
4	146.448	22.11	-30.28	43.5	21.39	Peak	292.00	200	Horizontal	Pass
5	265.856	26.07	-24.74	46.0	19.93	Peak	81.00	100	Horizontal	Pass
6	290.299	24.05	-23.82	46.0	21.95	Peak	58.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2025.06.17	2026.06.16	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00883	2025.03.23	2028.03.22	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1322.010	39.51	-15.49	74.0	34.49	Peak	42.00	100	Vertical	Pass
1**	1322.010	29.95	-15.49	54.0	24.05	AV	42.00	100	Vertical	Pass
2	2203.020	44.01	-12.00	74.0	29.99	Peak	86.00	100	Vertical	Pass
2**	2203.020	33.85	-12.00	54.0	20.15	AV	86.00	100	Vertical	Pass
3	3133.300	47.99	-5.60	74.0	26.01	Peak	278.00	100	Vertical	Pass
3**	3133.300	37.45	-5.60	54.0	16.55	AV	278.00	100	Vertical	Pass
4	7846.880	55.83	2.66	74.0	18.17	Peak	325.00	100	Vertical	Pass
4**	7846.880	45.33	2.66	54.0	8.67	AV	325.00	100	Vertical	Pass
5	10795.000	56.28	4.44	74.0	17.72	Peak	203.00	100	Vertical	Pass
5**	10795.000	47.45	4.44	54.0	6.55	AV	203.00	100	Vertical	Pass
6	13817.000	56.71	5.61	74.0	17.29	Peak	216.00	100	Vertical	Pass
6**	13817.000	47.94	5.61	54.0	6.06	AV	216.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1465.270	39.59	-15.45	74.0	34.41	Peak	93.00	100	Horizontal	Pass
1**	1465.270	29.81	-15.45	54.0	24.19	AV	93.00	100	Horizontal	Pass
2	2240.590	44.07	-11.50	74.0	29.93	Peak	68.00	100	Horizontal	Pass
2**	2240.590	33.68	-11.50	54.0	20.32	AV	68.00	100	Horizontal	Pass
3	3884.020	50.79	-1.86	74.0	23.21	Peak	276.00	100	Horizontal	Pass
3**	3884.020	39.58	-1.86	54.0	14.42	AV	276.00	100	Horizontal	Pass
4	7897.920	55.24	2.14	74.0	18.76	Peak	353.00	100	Horizontal	Pass
4**	7897.920	45.16	2.14	54.0	8.84	AV	353.00	100	Horizontal	Pass
5	10702.500	57.00	3.89	74.0	17.00	Peak	117.00	100	Horizontal	Pass
5**	10702.500	47.91	3.89	54.0	6.09	AV	117.00	100	Horizontal	Pass
6	13846.500	56.59	5.33	74.0	17.41	Peak	158.00	100	Horizontal	Pass
6**	13846.500	46.74	5.33	54.0	7.26	AV	158.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2025.06.17	2026.06.16	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2025.05.20	2028.05.19	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


Test Mode 5

5) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	63.290	40.96	-27.31	40.0	-0.96	Peak	47.00	111	Vertical	N/A
1*	63.290	31.09	-27.31	40.0	8.91	QP	47.00	111	Vertical	Pass
2	63.706	42.56	-26.75	40.0	-2.56	Peak	18.00	100	Vertical	N/A
2*	63.706	31.83	-26.75	40.0	8.17	QP	18.00	100	Vertical	Pass
3	167.012	33.17	-29.05	43.5	10.33	Peak	270.00	100	Vertical	Pass
4	286.710	33.71	-23.75	46.0	12.29	Peak	181.00	200	Vertical	Pass
5	479.983	35.35	-19.17	46.0	10.65	Peak	6.00	100	Vertical	Pass
6	789.025	33.02	-11.97	46.0	12.98	Peak	224.00	200	Vertical	Pass


6) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	63.774	39.55	-26.75	40.0	0.45	Peak	1.00	188	Horizontal	N/A
1*	63.774	28.96	-26.75	40.0	11.04	QP	1.00	188	Horizontal	Pass
2	167.788	32.61	-29.18	43.5	10.89	Peak	23.00	200	Horizontal	Pass
3	275.653	35.68	-24.26	46.0	10.32	Peak	14.00	100	Horizontal	Pass
4	296.992	35.19	-23.54	46.0	10.81	Peak	56.00	100	Horizontal	Pass
5	479.983	37.49	-19.17	46.0	8.51	Peak	121.00	100	Horizontal	Pass
6	789.122	36.36	-11.96	46.0	9.64	Peak	143.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2025.06.17	2026.06.16	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2024.11.28	2025.11.27	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00883	2025.03.23	2028.03.22	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

7) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1198.380	40.25	-15.64	74.0	33.75	Peak	49.00	100	Vertical	Pass
1**	1198.380	32.69	-15.64	54.0	21.31	AV	49.00	100	Vertical	Pass
2	1328.900	43.33	-15.64	74.0	30.67	Peak	231.00	100	Vertical	Pass
2**	1328.900	31.28	-15.64	54.0	22.72	AV	231.00	100	Vertical	Pass
3	2516.060	45.05	-9.91	74.0	28.95	Peak	15.00	100	Vertical	Pass
3**	2516.060	33.96	-9.91	54.0	20.04	AV	15.00	100	Vertical	Pass
4	7316.240	55.16	0.97	74.0	18.84	Peak	26.00	100	Vertical	Pass
4**	7316.240	45.31	0.97	54.0	8.69	AV	26.00	100	Vertical	Pass
5	9285.000	56.34	4.62	74.0	17.66	Peak	309.00	100	Vertical	Pass
5**	9285.000	46.72	4.62	54.0	7.28	AV	309.00	100	Vertical	Pass
6	10770.500	56.31	3.56	74.0	17.69	Peak	229.00	100	Vertical	Pass
6**	10770.500	47.31	3.56	54.0	6.69	AV	229.00	100	Vertical	Pass

8) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1125.970	40.80	-15.60	74.0	33.20	Peak	86.00	100	Horizontal	Pass
1**	1125.970	30.68	-15.60	54.0	23.32	AV	86.00	100	Horizontal	Pass
2	1330.850	41.79	-15.60	74.0	32.21	Peak	91.00	100	Horizontal	Pass
2**	1330.850	32.57	-15.60	54.0	21.43	AV	91.00	100	Horizontal	Pass
3	4058.260	50.14	-1.14	74.0	23.86	Peak	96.00	100	Horizontal	Pass
3**	4058.260	40.97	-1.14	54.0	13.03	AV	96.00	100	Horizontal	Pass
4	7929.600	55.20	2.24	74.0	18.80	Peak	239.00	100	Horizontal	Pass
4**	7929.600	45.19	2.24	54.0	8.81	AV	239.00	100	Horizontal	Pass
5	9305.000	56.48	4.75	74.0	17.52	Peak	184.00	100	Horizontal	Pass
5**	9305.000	47.07	4.75	54.0	6.93	AV	184.00	100	Horizontal	Pass
6	13530.000	55.80	4.32	74.0	18.20	Peak	306.00	100	Horizontal	Pass
6**	13530.000	46.07	4.32	54.0	7.93	AV	306.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2025.06.17	2026.06.16	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2024.11.28	2025.11.27	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2024.11.28	2025.11.27	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2025.05.20	2028.05.19	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


A.2 Conducted Emission, AC Ports

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Sample No.	S07	Temperature	22.3℃
Humidity	48%RH	Pressure	101kPa
Test Engineer	Yang Panxia	Test Date	2025.08.26


Test Mode 4

1) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	55.63	10.30	65.46	9.83	Peak	L	Pass
1**	0.160	39.11	10.30	55.46	16.35	AV	L	Pass
2	0.242	47.29	10.26	62.03	14.74	Peak	L	Pass
2**	0.242	32.80	10.26	52.03	19.23	AV	L	Pass
3	0.560	43.79	10.28	56.00	12.21	Peak	L	Pass
3**	0.560	33.70	10.28	46.00	12.30	AV	L	Pass
4	3.914	34.50	10.69	56.00	21.50	Peak	L	Pass
4**	3.914	21.44	10.69	46.00	24.56	AV	L	Pass
5	16.268	51.21	13.45	60.00	8.79	Peak	L	Pass
5**	16.268	38.49	13.45	50.00	11.51	AV	L	Pass
6	25.392	50.00	15.55	60.00	10.00	Peak	L	Pass
6**	25.392	39.72	15.55	50.00	10.28	AV	L	Pass


2) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.184	51.15	10.28	64.30	13.15	Peak	N	Pass
1**	0.184	34.41	10.28	54.30	19.89	AV	N	Pass
2	0.252	43.89	10.26	61.69	17.80	Peak	N	Pass
2**	0.252	30.70	10.26	51.69	20.99	AV	N	Pass
3	0.336	42.01	10.26	59.30	17.29	Peak	N	Pass
3**	0.336	30.04	10.26	49.30	19.26	AV	N	Pass
4	0.558	39.09	10.28	56.00	16.91	Peak	N	Pass
4**	0.558	24.69	10.28	46.00	21.31	AV	N	Pass
5	1.794	36.93	10.41	56.00	19.07	Peak	N	Pass
5**	1.794	21.54	10.41	46.00	24.46	AV	N	Pass
6	17.288	51.76	13.73	60.00	8.24	Peak	N	Pass
6**	17.288	38.02	13.73	50.00	11.98	AV	N	Pass


Test Mode 5

3) AC Ports - L Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.186	54.13	10.28	64.21	10.08	Peak	L	Pass
1**	0.186	38.18	10.28	54.21	16.03	AV	L	Pass
2	0.276	49.28	10.26	60.94	11.66	Peak	L	Pass
2**	0.276	32.57	10.26	50.94	18.37	AV	L	Pass
3	0.832	42.89	10.30	56.00	13.11	Peak	L	Pass
3**	0.832	25.91	10.30	46.00	20.09	AV	L	Pass
4	4.168	42.67	10.73	56.00	13.33	Peak	L	Pass
4**	4.168	26.28	10.73	46.00	19.72	AV	L	Pass
5	11.826	51.16	12.31	60.00	8.84	Peak	L	Pass
5**	11.826	35.13	12.31	50.00	14.87	AV	L	Pass
6	21.554	42.41	14.78	60.00	17.59	Peak	L	Pass
6**	21.554	24.33	14.78	50.00	25.67	AV	L	Pass

4) AC Ports - N Phase



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.190	56.81	10.28	64.04	7.23	Peak	N	Pass
1**	0.190	39.32	10.28	54.04	14.72	AV	N	Pass
2	0.260	58.41	10.26	61.43	3.02	Peak	N	N/A
2*	0.260	47.48	10.26	61.43	13.95	QP	N	Pass
2**	0.260	29.39	10.26	51.43	22.04	AV	N	Pass
3	0.340	52.93	10.26	59.20	6.27	Peak	N	Pass
3**	0.340	33.91	10.26	49.20	15.29	AV	N	Pass
4	0.514	48.38	10.28	56.00	7.62	Peak	N	Pass
4**	0.514	30.94	10.28	46.00	15.06	AV	N	Pass
5	0.676	44.76	10.29	56.00	11.24	Peak	N	Pass
5**	0.676	31.59	10.29	46.00	14.41	AV	N	Pass
6	11.424	55.73	12.21	60.00	4.27	Peak	N	N/A
6*	11.424	46.28	12.21	60.00	13.72	QP	N	Pass
6**	11.424	36.78	12.21	50.00	13.22	AV	N	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2025.06.16	2026.06.15	☒
LISN	SCHWARZBECK	NSLK 8127	8127-687	2025.04.29	2026.04.28	☒
Shielded Room	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2025.02.14	2028.02.13	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2580928-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2580928-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2580928-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--