TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: **47 CFR FCC Part 15, Subpart E (Section 15.407)**
Report No.: RFBCMA-WTW-P25030861-5
FCC ID: RAXTMOG5AR
Product: 5G Gateway
Brand: T-Mobile
Model No.: TMO-G5AR
Received Date: 2025/3/24
Test Date: 2025/5/7 ~ 2025/5/19
Issued Date: 2025/5/29

Applicant: Arcadyan Technology Corporation
Address: No. 8, Sec. 2, Guangfu Rd., Hsinchu City 30071, Taiwan, R.O.C.
Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories
Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan
Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, Taiwan
FCC Registration / Designation Number: 788550 / TW0003

Approved by: Jeremy . Lin , **Date:** 2025/5/29
Jeremy Lin / Project Engineer

This test report consists of 182 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.

Prepared by : Celine Chou / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record **4**

1 Certificate **5**

2 Summary of Test Results **6**

2.1 Measurement Uncertainty 6
2.2 Supplementary Information 6

3 General Information **7**

3.1 General Description of EUT 7
3.2 Antenna Description of EUT 8
3.3 Channel List 9
3.4 Test Mode Applicability and Tested Channel Detail 11
3.5 Duty Cycle of Test Signal 13
3.6 Test Program Used and Operation Descriptions 16
3.7 Connection Diagram of EUT and Peripheral Devices 16
3.8 Configuration of Peripheral Devices and Cable Connections 16

4 Test Instruments **17**

4.1 Maximum RF Output Power 17
4.2 Maximum Power Spectral Density 17
4.3 Emission Bandwidth 17
4.4 In-Band Emission Mask 18
4.5 Occupied Bandwidth 18
4.6 Contention-based Protocol 18
4.7 AC Power Conducted Emissions 18
4.8 Unwanted Emissions below 1 GHz 19
4.9 Unwanted Emissions above 1 GHz 20

5 Limits of Test Items **21**

5.1 Maximum RF Output Power 21
5.2 Maximum Power Spectral Density 21
5.3 Emission Bandwidth 21
5.4 In-Band Emission Mask 21
5.5 Occupied Bandwidth 21
5.6 Contention-based Protocol 21
5.7 AC Power Conducted Emissions 22
5.8 Unwanted Emissions below 1 GHz 22
5.9 Unwanted Emissions above 1 GHz 22

6 Test Arrangements **23**

6.1 Maximum RF Output Power 23
6.1.1 Test Setup 23
6.1.2 Test Procedure 23
6.2 Maximum Power Spectral Density 24
6.2.1 Test Setup 24
6.2.2 Test Procedure 24
6.3 Emission Bandwidth 25
6.3.1 Test Setup 25
6.3.2 Test Procedure 25
6.4 In-Band Emission Mask 25
6.4.1 Test Setup 25
6.4.2 Test Procedure 25
6.5 Occupied Bandwidth 26
6.5.1 Test Setup 26
6.5.2 Test Procedure 26
6.6 Contention-based Protocol 27
6.6.1 Test Setup 27
6.6.2 Test Procedure 27
6.7 AC Power Conducted Emissions 28

6.7.1 Test Setup 28
6.7.2 Test Procedure 28
6.8 Unwanted Emissions below 1 GHz 29
6.8.1 Test Setup 29
6.8.2 Test Procedure 30
6.9 Unwanted Emissions above 1 GHz 31
6.9.1 Test Setup 31
6.9.2 Test Procedure 31

7 Test Results of Test Item 32

7.1 Maximum RF Output Power 32
7.2 Maximum Power Spectral Density 38
7.3 Emission Bandwidth 44
7.4 In-Band Emission Mask 48
7.5 Occupied Bandwidth 87
7.6 Contention-based Protocol 91
7.7 AC Power Conducted Emissions 107
7.8 Unwanted Emissions below 1 GHz 109
7.9 Unwanted Emissions above 1 GHz 111

8 Pictures of Test Arrangements 181

9 Information of the Testing Laboratories 182

Release Control Record

Issue No.	Description	Date Issued
RFBCMA-WTW-P25030861-5	Original release.	2025/5/29

1 Certificate

Product:	5G Gateway
Brand:	T-Mobile
Test Model:	TMO-G5AR
Sample Status:	Engineering sample
Applicant:	Arcadyan Technology Corporation
Test Date:	2025/5/7 ~ 2025/5/19
Standard:	47 CFR FCC Part 15, Subpart E (Section 15.407)
Measurement procedure:	ANSI C63.10-2013 KDB 987594 D02 U-NII 6 GHz EMC Measurement v03 KDB 789033 D02 General UNII Test Procedure New Rules v02r01 KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
Clause	Test Item	Result	Remark
15.407(a)(5)	Maximum RF Output Power	Pass	Meet the requirement of limit.
15.407(a)(5)	Maximum Power Spectral Density	Pass	Meet the requirement of limit.
15.407(a)(11)	Emission Bandwidth	Pass	Meet the requirement of limit.
---	Occupied Bandwidth	-	Reference only.
15.407(b)(9)	AC Power Conducted Emissions	Pass	Minimum passing margin is -7.52 dB at 0.52600 MHz
15.407(b)(9)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -10.2 dB at 31.41 MHz
15.407(b)(6) 15.407(b)(10)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -5.9 dB at 13390.00 MHz
15.407(b)(7)	In-Band Emission Mask	Pass	Meet the requirement of limit.
15.407(d)(6)	Contention-based Protocol	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is MHF1 not a standard connector.

Notes:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
2. Per TCBC notice, FCC allows 99% BW measurements for Wi-Fi 320MHz BW mode instead of Emission Bandwidth.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Uncertainty (±)
Maximum RF Output Power	1 GHz ~ 18 GHz	2.29 dB
Maximum Power Spectral Density	1 GHz ~ 18 GHz	2.29 dB
Occupied Bandwidth	-	72 Hz
AC Power Conducted Emissions	9 kHz ~ 30 MHz	2.90 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.59 dB
	30 MHz ~ 1 GHz	3.64 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	2.29 dB
	18 GHz ~ 40 GHz	2.29 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	5G Gateway
Brand	T-Mobile
Test Model	TMO-G5AR
Status of EUT	Engineering sample
Power Supply Rating	100-240 Vac
EUT Category	Mobile station
Modulation Technology	OFDM, OFDMA
Transfer Rate	Up to 11529.4 Mbps
Operating Frequency	5.955 GHz ~ 6.415 GHz 6.435 GHz ~ 6.525 GHz 6.535 GHz ~ 6.865 GHz 6.875 GHz ~ 7.115 GHz
Number of Channel	802.11a, 802.11ax (HE20), 802.11be (EHT20): 59 802.11ax (HE40), 802.11be (EHT40): 29 802.11ax (HE80), 802.11be (EHT80): 14 802.11ax (HE160), 802.11be (EHT160): 7 802.11be (EHT320): 6
Output Power	5.955 GHz ~ 6.415 GHz: EIRP: 639.735 mW (28.06 dBm) 6.435 GHz ~ 6.525 GHz: EIRP: 272.270 mW (24.35 dBm) 6.535 GHz ~ 6.865 GHz: EIRP: 583.445 mW (27.66 dBm) 6.875 GHz ~ 7.115 GHz: EIRP: 726.106 mW (28.61 dBm)
Equipment Class	6ID: 15E 6 GHz Low-power indoor access point

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
AC Adapter 1	MOSO	P30-V3000R200-060Q0-US	AC Input: 100~240 Vac, 1.7 A, 50/60 Hz DC Output: 5.0 Vdc, 3.0 A; 9.0 Vdc, 3.0 A; 12.0 Vdc, 3.0 A;15.0 Vdc, 3.0 A; 20.0 Vdc, 3.0 A DC Output Cable: 1.85 m, non-shielded cable, W/O ferrite core Plug: US
AC Adapter 2	MASS POWER	PD065E-D1C0AVU	AC Input: 100~240 Vac, 1.5 A, 50/60 Hz DC Output: 5.0 Vdc, 3.0 A; 9.0 Vdc, 3.0 A; 12.0 Vdc, 3.0 A; 15.0 Vdc, 3.0 A; 20.0 Vdc, 2.25 A DC Output Cable: 1.8 m, non-shielded cable, W/O ferrite core Plug: US

2. There are WLAN (2.4 GHz), WLAN (5 GHz), WLAN (6 GHz), BT LE, Zigbee and WWAN technology used for the EUT.
3. Simultaneously transmission combination.

Combination	Technology				
1	WLAN 2.4 GHz or 5 GHz	WLAN 6 GHz	Zigbee	BT LE	LTE
2	WLAN 2.4 GHz or 5 GHz	WLAN 6 GHz	Zigbee	BT LE	5G NR
Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.					

4. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna No.	Brand	Model	RF Chain No.	Antenna Net Gain (dBi)	Frequency Range	Antenna Type	Connector Type
6G1	ARC	120800158000J	0	4.17	5.925 GHz ~ 6.425 GHz	Dipole	MHF1
				4.06	6.425 GHz ~ 6.525 GHz		
				4.09	6.525 GHz ~ 6.875 GHz		
				4.07	6.875 GHz ~ 7.125 GHz		
6G2	ARC	120800157900J	1	3.90	5.925 GHz ~ 6.425 GHz	Dipole	MHF1
				4.23	6.425 GHz ~ 6.525 GHz		
				4.12	6.525 GHz ~ 6.875 GHz		
				4.12	6.875 GHz ~ 7.125 GHz		
6G3	ARC	120800158100J	2	3.89	5.925 GHz ~ 6.425 GHz	Dipole	MHF1
				4.19	6.425 GHz ~ 6.525 GHz		
				4.05	6.525 GHz ~ 6.875 GHz		
				4.21	6.875 GHz ~ 7.125 GHz		
6G4	ARC	120800158200J	3	4.39	5.925 GHz ~ 6.425 GHz	Dipole	MHF1
				4.35	6.425 GHz ~ 6.525 GHz		
				4.08	6.525 GHz ~ 6.875 GHz		
				4.13	6.875 GHz ~ 7.125 GHz		
6G5 Rx	ARC	120800158400J	0	4.57	5.925 GHz ~ 6.425 GHz	Dipole	MHF1
				5.01	6.425 GHz ~ 6.525 GHz		
				5.08	6.525 GHz ~ 6.875 GHz		
				4.99	6.875 GHz ~ 7.125 GHz		

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a MIMO function:

6 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11a	4TX	5RX
802.11ax (HE20)	4TX	5RX
802.11ax (HE40)	4TX	5RX
802.11ax (HE80)	4TX	5RX
802.11ax (HE160)	4TX	5RX
802.11be (EHT20)	4TX	5RX
802.11be (EHT40)	4TX	5RX
802.11be (EHT80)	4TX	5RX
802.11be (EHT160)	4TX	5RX
802.11be (EHT320)	4TX	5RX

Note:

1. All of modulation mode support beamforming function except 802.11a modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth of 802.11ax and 802.11be modes are similar at 20MHz (40MHz, 80MHz,160MHz). Therefore the investigated worst case is the representative mode in test report.

3.3 Channel List

U-NII-5:

24 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	5955 MHz	5	5975 MHz	9	5995 MHz	13	6015 MHz
17	6035 MHz	21	6055 MHz	25	6075 MHz	29	6095 MHz
33	6115 MHz	37	6135 MHz	41	6155 MHz	45	6175 MHz
49	6195 MHz	53	6215 MHz	57	6235 MHz	61	6255 MHz
65	6275 MHz	69	6295 MHz	73	6315 MHz	77	6335 MHz
81	6355 MHz	85	6375 MHz	89	6395 MHz	93	6415 MHz

12 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
3	5965 MHz	11	6005 MHz	19	6045 MHz	27	6085 MHz
35	6125 MHz	43	6165 MHz	51	6205 MHz	59	6245 MHz
67	6285 MHz	75	6325 MHz	83	6365 MHz	91	6405 MHz

6 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
7	5985 MHz	23	6065 MHz	39	6145 MHz	55	6225 MHz
71	6305 MHz	87	6385 MHz				

3 channels are provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency	Channel	Frequency	Channel	Frequency
15	6025 MHz	47	6185 MHz	79	6345 MHz

2 channels are provided for 802.11be (EHT320):

Channel	Frequency	Channel	Frequency
31	6105 MHz	63	6265 MHz

U-NII-6:

5 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
97	6435 MHz	101	6455 MHz	105	6475 MHz	109	6495 MHz
113	6515 MHz						

3 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency
99	6445 MHz	107	6485 MHz	*115	6525 MHz

1 channel is provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency
103	6465 MHz

1 channel is provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency
*111	6505 MHz

1 channel is provided for 802.11be (EHT320):

Channel	Frequency
*95	6425 MHz

U-NII-7:

17 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
117	6535 MHz	121	6555 MHz	125	6575 MHz	129	6595 MHz
133	6615 MHz	137	6635 MHz	141	6655 MHz	145	6675 MHz
149	6695 MHz	153	6715 MHz	157	6735 MHz	161	6755 MHz
165	6775 MHz	169	6795 MHz	173	6815 MHz	177	6835 MHz
181	6855 MHz						

8 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
123	6565 MHz	131	6605 MHz	139	6645 MHz	147	6685 MHz
155	6725 MHz	163	6765 MHz	171	6805 MHz	179	6845 MHz

5 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*119	6545 MHz	135	6625 MHz	151	6705 MHz	167	6785 MHz
*183	6865 MHz						

2 channels are provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency	Channel	Frequency
143	6665 MHz	*175	6825 MHz

2 channels are provided for 802.11be (EHT320):

Channel	Frequency	Channel	Frequency
*127	6585 MHz	*159	6745 MHz

U-NII-8:

13 channels are provided for 802.11a, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*185	6875 MHz	189	6895 MHz	193	6915 MHz	197	6935 MHz
201	6955 MHz	205	6975 MHz	209	6995 MHz	213	7015 MHz
217	7035 MHz	221	7055 MHz	225	7075 MHz	229	7095 MHz
233	7115 MHz						

6 channels are provided for 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
*187	6885 MHz	195	6925 MHz	203	6965 MHz	211	7005 MHz
219	7045 MHz	227	7085 MHz				

2 channels are provided for 802.11ax (HE80), 802.11be (EHT80):

Channel	Frequency	Channel	Frequency
199	6945 MHz	215	7025 MHz

1 channel is provided for 802.11ax (HE160), 802.11be (EHT160):

Channel	Frequency
207	6985 MHz

1 channel is provided for 802.11be (EHT320):

Channel	Frequency
*191	6905 MHz

Note: * mean these are straddle channels.

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. The AC Adapter has the following models: MOSO P30-V3000R200-060Q0-US / MASS POWER PD065E-D1C0AVU. Pre-scan these models of AC Adapters and find the worst case as a representative test condition. 2. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. AC Adapter Worst Condition: MASS POWER PD065E-D1C0AVU 2. The EUT is designed to be positioned on the Z-axis only.

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
Maximum RF Output Power	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD, Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0
Maximum Power Spectral Density	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	CDD, Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0
Emission Bandwidth	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
In-Band Emission Mask	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0
Occupied Bandwidth	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0
Contention-based Protocol	802.11be (EHT20)	-	1, 97, 129, 189	BPSK	MCS0
	802.11be (EHT320)		31, 127, 159, 191	BPSK	MCS0
AC Power Conducted Emissions	802.11be (EHT320)	Beamforming	191	BPSK	MCS0
Unwanted Emissions below 1 GHz	802.11be (EHT320)	Beamforming	191	BPSK	MCS0
Unwanted Emissions above 1 GHz	802.11a	CDD	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	6Mb/s
	802.11be (EHT20)	Beamforming	1, 45, 93, 97, 105, 113, 117, 149, 181, 185, 209, 233	BPSK	MCS0
	802.11be (EHT40)		3, 43, 91, 99, 107, 115, 123, 155, 179, 187, 211, 227	BPSK	MCS0
	802.11be (EHT80)		7, 39, 87, 103, 119, 151, 183, 199, 215	BPSK	MCS0
	802.11be (EHT160)		15, 47, 79, 111, 143, 175, 207	BPSK	MCS0
	802.11be (EHT320)		31, 63, 95, 127, 159, 191	BPSK	MCS0
Note: Partial RU (resource unit) and channel puncturing mechanisms are not supported.					

3.5 Duty Cycle of Test Signal

802.11a: Duty cycle = 2.74 ms / 2.77 ms x 100% = 98.9%
802.11be (EHT20) Beamforming: Duty cycle = 3.88 ms / 3.91 ms x 100% = 99.2%
802.11be (EHT40) Beamforming: Duty cycle = 4.83 ms / 4.86 ms x 100% = 99.4%
802.11be (EHT80) Beamforming: Duty cycle = 3.795 ms / 3.825 ms x 100% = 99.2%
802.11be (EHT160) Beamforming: Duty cycle = 2.91 ms / 2.95 ms x 100% = 98.6%
802.11be (EHT320) Beamforming: Duty cycle = 2.34 ms / 2.38 ms x 100% = 98.3%



802.11a



802.11be (EHT20) Beamforming



802.11be (EHT40) Beamforming



802.11be (EHT80) Beamforming



802.11be (EHT160) Beamforming



802.11be (EHT320) Beamforming

3.6 Test Program Used and Operation Descriptions

Controlling software QATool has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Laptop	DELL	E5430	2RL3YW1	N/A	Provided by Lab
B	Load	N/A	N/A	N/A	N/A	Provided by Lab
C	Adapter	MASS POWER	PD065E-D1C0AVU	N/A	N/A	Supplied by applicant
D	USB Flash	SanDisk	SDDDC3-032G	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	RJ-45 Cable	1	10	N	0	Provided by Lab
2	RJ-45 Cable	1	1.5	N	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 Maximum RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
EMI Test Receiver R&S	ESR3	102782	2024/12/10	2025/12/9
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-408	2024/11/10	2025/11/9
Preamplifier Keysight	83017A	MY53270295	2025/4/27	2026/4/26
RF Coaxial Cable HUBER+SUHNER	EMC104-SM-SM-10000	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-4)	2025/4/27	2026/4/26
	SUCOFLEX 104	Cable-CH4-03(250724)	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSV3044	101105	2025/2/25	2026/2/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2025/5/19

4.2 Maximum Power Spectral Density

Refer to section 4.1 to get the tested date and information of the instruments.

4.3 Emission Bandwidth

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Signal & Spectrum Analyzer R&S	FSV3044	101504	2024/6/18	2025/6/17
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room.
2. Tested Date: 2025/5/19

4.4 In-Band Emission Mask

Refer to section 4.3 to get the tested date and information of the instruments.

4.5 Occupied Bandwidth

Refer to section 4.3 to get the tested date and information of the instruments.

4.6 Contention-based Protocol

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MXG Vector Signal Generator Agilent	N5182B	MY53050430	2024/11/29	2025/11/28
MXG Vector Signal Generator Keysight	N5182BU	MY59360189	2024/11/29	2025/11/28
Power Divider Woken	0120A02058001M	DCMD33WIK3	2025/4/27	2026/4/26
		DCMD33WIK7	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSW26	102023	2024/11/11	2025/11/10

Notes:

1. The test was performed in Adaptivity room.
2. Tested Date: 2025/5/7

4.7 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2024/11/28	2025/11/27
	E1-011280	05	2024/11/28	2025/11/27
	E1-011311	09	2024/11/28	2025/11/27
DC-LISN Schwarzbeck	NNBM 8126G	8126G-069	2024/11/5	2025/11/4
EMI Test Receiver R&S	ESCI	100613	2024/11/25	2025/11/24
Fixed Attenuator Mini-Circuits	HAT-10+	PAD-COND1-01	2025/1/5	2026/1/4
LISN R&S	ENV216	101826	2025/3/24	2026/3/23
	ESH3-Z5	100311	2024/9/5	2025/9/4
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2025/1/5	2026/1/4
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2024/8/28	2025/8/27

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2025/5/14

4.8 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-155	2024/10/14	2025/10/13
EMI Test Receiver R&S	ESR3	102782	2024/12/10	2025/12/9
Loop Antenna TESEQ	HLA 6121	45745	2024/8/21	2025/8/20
Preamplifier Agilent	8447D	2944A10631	2025/4/27	2026/4/26
RF Coaxial Cable Woken	8D-FB	Cable-CH4-01	2024/7/6	2025/7/5
Signal & Spectrum Analyzer R&S	FSV3044	101105	2025/2/25	2026/2/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2025/5/14

4.9 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower inn-co GmbH	MA 4000	010303	N/A	N/A
Boresight antenna tower fixture BV	BAF-02	5	N/A	N/A
EMI Test Receiver R&S	ESR3	102782	2024/12/10	2025/12/9
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-408	2024/11/10	2025/11/9
	BBHA 9170	9170-480	2024/11/10	2025/11/9
		BBHA9170241	2024/10/18	2025/10/17
		BBHA9170243	2024/11/10	2025/11/9
Preamplifier EMCI	EMC 184045	980116	2024/9/24	2025/9/23
Preamplifier Keysight	83017A	MY53270295	2025/4/27	2026/4/26
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	2024/7/6	2025/7/5
	EMC102-KM-KM-3000	150929	2024/7/6	2025/7/5
RF Coaxial Cable HUBER+SUHNER	EMC104-SM-SM-10000	Cable-CH1-01(RFC-SMS-100-SMS-120+RFC-SMS-100-SMS-4)	2025/4/27	2026/4/26
	SUCOFLEX 104	Cable-CH4-03(250724)	2025/4/27	2026/4/26
Signal & Spectrum Analyzer R&S	FSV3044	101105	2025/2/25	2026/2/24
Software BV ADT	ADT_Radiated_ V7.6.15.9.5	N/A	N/A	N/A
Turn Table BV ADT	TT100	TT93021705	N/A	N/A
Turn Table Controller BV ADT	SC100	SC93021705	N/A	N/A

Notes:

1. The test was performed in HY - 966 chamber 3.
2. Tested Date: 2025/5/8 ~ 2025/5/13

5 Limits of Test Items

5.1 Maximum RF Output Power

Operation Band	Equipment Class	Limit
		Maximum Average Power
U-NII-5 U-NII-6 U-NII-7 U-NII-8	6ID: 15E 6 GHz Low-power indoor access point	EIRP 30 dBm

5.2 Maximum Power Spectral Density

Operation Band	Equipment Class	Limit
		Maximum Power Density
U-NII-5 U-NII-6 U-NII-7 U-NII-8	6ID: 15E 6 GHz Low-power indoor access point	EIRP 5 dBm/MHz

5.3 Emission Bandwidth

The maximum transmitter channel bandwidth for U-NII devices in the 5.925-7.125 GHz band is 320 MHz.

5.4 In-Band Emission Mask

Test Item	Frequencies (MHz)	(X) dBc*1
Emission Mask	At 1 MHz outside of channel edge	20
	At one channel bandwidth from the channel center*2	28
	At one- and one-half times the channel bandwidth away from channel center*3	40
	More than one- and one-half times the channel bandwidth	40

*1 : The power spectral density must be suppressed by “x” dB

*2 : At frequencies between one megahertz outside an unlicensed device’s channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression,

*3 : At frequencies between one and one- and one-half times an unlicensed device’s channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression.

5.5 Occupied Bandwidth

The results are for reference only.

5.6 Contention-based Protocol

Unlicensed indoor low-power devices must detect co-channel radio frequency power that is at least -62 dBm (The threshold is referenced to a 0 dBi antenna gain.) or lower. Additionally, indoor low-power devices must detect co-channel energy with 90% or greater certainty.

5.7 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.8 Unwanted Emissions below 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.9 Unwanted Emissions above 1 GHz

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Frequencies (MHz)	EIRP Limit	Equivalent Field Strength at 3 m
5925 MHz > F > 7125 MHz	Peak: -7 (dBm/MHz)	88.2 (dBuV/m)
	Average: -27 (dBm/MHz)	68.2 (dBuV/m)

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts).

6 Test Arrangements

6.1 Maximum RF Output Power

6.1.1 Test Setup



6.1.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.

e. Follow ANSI C63.10 section 12.7.3, EIRP Value (dBm) = Field Strength Value (dBuV / m) + Correction Factor @ 3 m.

f. Correction Factor (dB) @ 3 m = 20log(D) – 104.77 = -95.23 dB; where D is the measurement distance @3 m.

Spectrum analyzer setting as below:
Method SA-1

a. Set span to encompass the entire emission bandwidth (EBW) of the signal.

b. Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS

c. Sweep points ≥ [2 × span / RBW]. (This gives bin-to-bin spacing ≤ RBW / 2, so that narrowband signals are not lost between frequency bins.)

d. Sweep time = auto, trigger set to “free run”.

e. Trace average at least 100 traces in power averaging mode.

f. Record the max value

Note: When measuring power, use compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument’s band power measurement function, with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.

6.2 Maximum Power Spectral Density

6.2.1 Test Setup



6.2.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. Perform a field strength measurement and record the worse read value, is the field strength value via a spectrum reading obtained corrected for antenna factor, cable loss and pre-amplifier factor and then mathematically convert the measured field strength level to EIRP level.

e. Follow ANSI C63.10 section 12.7.3, EIRP Value (dBm) = Field Strength Value (dBuV/m) + Correction Factor @ 3 m.

f. Correction Factor (dB) @ 3 m = 20log(D) – 104.77; where D is the measurement distance @3 m = -95.23 dB

Spectrum analyzer setting as below:
Method SA-1

a. Set span to encompass the entire emission bandwidth (EBW) of the signal.

b. Set RBW = 1 MHz, Set VBW ≥ 3 MHz, Detector = RMS

c. Sweep points ≥ [2 × span / RBW]. (This gives bin-to-bin spacing ≤ RBW / 2, so that narrowband signals are not lost between frequency bins.)

d. Sweep time = auto, trigger set to “free run”.

e. Trace average at least 100 traces in power averaging mode.

f. Record the max value

6.3 Emission Bandwidth

6.3.1 Test Setup



6.3.2 Test Procedure

a. Set RBW = approximately 1% of the emission bandwidth.
b. Set the VBW > RBW.
c. Detector = Peak.
d. Trace mode = max hold.
e. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.

6.4 In-Band Emission Mask

6.4.1 Test Setup



6.4.2 Test Procedure

a. Connect output of the antenna port to a spectrum analyzer and adjust appropriate attenuation.
b. Measure the 26 dB EBW using the test procedure 12.4.1 of ANSI C63.10-2013. (Determine the channel edge.)
c. Measure the power spectral density (for emissions mask reference) using the following procedure:
   a) Set the span to encompass the entire 26 dB EBW of the signal.
   b) Set RBW = same RBW used for 26 dB EBW measurement.
   c) Set VBW ≥ [3 X RBW].
   d) Number of points in sweep ≥ [2 X span / RBW].
   e) Sweep time = auto.
   f) Detector = RMS (i.e., power averaging).
   g) Trace average at least 100 traces in power averaging (rms) mode.
   h) Use the peak search function on the instrument to find the peak of the spectrum.
d. Using the measuring equipment limit line function, develop the emissions mask based on the following requirements. The emissions power spectral density must be reduced below the peak power spectral density (in dB) as follows:
   a) Suppressed by 20 dB at 1 MHz outside of the channel edge. (The channel edge is defined as the 26-dB point on either side of the carrier center frequency.)
   b) Suppressed by 28 dB at one channel bandwidth from the channel center.
   c) Suppressed by 40 dB at one- and one-half times the channel bandwidth from the channel center.
e. Adjust the span to encompass the entire mask as necessary and clear trace.
f. Trace average at least 100 traces in power averaging (rms) mode.
g. Adjust the reference level as necessary so that the crest of the channel touches the top of the emission mask

6.5 Occupied Bandwidth

6.5.1 Test Setup



6.5.2 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to Sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean power of a given emission.

6.6 Contention-based Protocol

6.6.1 Test Setup



6.6.2 Test Procedure

a. Set the signal analyzer center frequency to the nominal EUT channel center frequency. The span range of the signal analyzer shall be between two times and five times the OBW of the EUT. Connect the output port of the EUT to the signal analyzer 2. Ensure that the attenuator 2 provides enough attenuation to not overload the signal analyzer 2 receiver.

b. Monitoring the signal analyzer 2, verify the EUT is operating and transmitting with the parameters (set as following section 4.7.5 EUT operating condition).

c. Determine number of times detection threshold test as following table,

If	Number of Tests	Placement of Incumbent Transmission
$BW_{EUT} \leqq BW_{Inc}$	Once	Same as EUT transmission
$BW_{Inc} < BW_{EUT} \leqq 2xBW_{Inc}$	Once	Contained within BW_{EUT}
$2xBW_{Inc} < BW_{EUT} \leqq 4xBW_{Inc}$	Twice. (Incumbent transmission is contained within BW_{EUT})	Closely to the lower edge and upper edge of the EUT Channel
$BW_{EUT} > 4xBW_{Inc}$	Three times	Closely to the lower edge ,in the middle and upper edge of the EUT Channel

d. The power measurement of AWGN signal refers to method SA-1 in section 12.4.2.2 of ANSI C63.10-2020.

e. Using an AWGN signal source, generate (but do not transmit, i.e., RF OFF) a 10 MHz-wide AWGN signal. Use step c table to determine the center frequency of the 10 MHz AWGN signal relative to the EUT's channel bandwidth and center frequency.

f. Set the AWGN signal power to an extremely low level (more than 20 dB below the -62 dBm threshold). Connect the AWGN signal source, via a 3-dB splitter, to the signal analyzer 1 and the EUT.

g. Transmit the AWGN signal (RF ON) and verify its characteristics on the signal analyzer 1.

h. Monitor the signal analyzer 2 to verify if the AWGN signal has been detected and the EUT has ceased transmission. If the EUT continues to transmit, then incrementally increase the AWGN signal power level until the EUT stops transmitting.

i. (Including all losses in the RF paths) Determine and record the AWGN signal power level (at the EUT's antenna port) at which the EUT ceased transmission. Repeat the procedure at least 10 times to verify the EUT can detect an AWGN signal with 90% (or better) level of certainty.

j. Refer to step c table to determine number of times the detection threshold testing needs to be repeated. If testing is required more than once, then go back to step d, choose a different center frequency for the AWGN signal and repeat the process.

6.7 AC Power Conducted Emissions

6.7.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

a. The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.

6.8 Unwanted Emissions below 1 GHz

6.8.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.8.2 Test Procedure

For Radiated emission below 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.9 Unwanted Emissions above 1 GHz

6.9.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.9.2 Test Procedure

a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98%) or 10 Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1 GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.
4. For 802.11be (EHT20) CH233: Integration method
   a) For peak emissions measurements:
      1) Set RBW = 100 kHz
      2) Detection = peak.
      3) Max hold.
      4) Perform band-power integration across the 1 MHz bandwidth in which the band-edge emission level is to be measured.
   b) For average emissions measurements:
      1) Set RBW = 100 kHz.
      2) Perform band-power integration across the 1 MHz bandwidth in which the band-edge emission level is to be measured.

7 Test Results of Test Item

7.1 Maximum RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	108.45	-95.23	20.989	13.22	30	Pass
45	6175	108.85	-95.23	23.014	13.62	30	Pass
93	6415	108.72	-95.23	22.336	13.49	30	Pass
97	6435	107.92	-95.23	18.578	12.69	30	Pass
105	6475	107.71	-95.23	17.701	12.48	30	Pass
113	6515	107.35	-95.23	16.293	12.12	30	Pass
117	6535	108.02	-95.23	19.011	12.79	30	Pass
149	6695	108.55	-95.23	21.478	13.32	30	Pass
181	6855	108.08	-95.23	19.275	12.85	30	Pass
185	6875	108.45	-95.23	20.989	13.22	30	Pass
209	6995	108.15	-95.23	19.588	12.92	30	Pass
233	7115	108.52	-95.23	21.33	13.29	30	Pass

802.11be (EHT20)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	108.52	-95.23	21.33	13.29	30	Pass
45	6175	109.57	-95.23	27.164	14.34	30	Pass
93	6415	108.79	-95.23	22.699	13.56	30	Pass
97	6435	108.47	-95.23	21.086	13.24	30	Pass
105	6475	108.28	-95.23	20.184	13.05	30	Pass
113	6515	108.38	-95.23	20.654	13.15	30	Pass
117	6535	108.57	-95.23	21.577	13.34	30	Pass
149	6695	108.59	-95.23	21.677	13.36	30	Pass
181	6855	108.58	-95.23	21.627	13.35	30	Pass
185	6875	108.52	-95.23	21.33	13.29	30	Pass
209	6995	107.65	-95.23	17.458	12.42	30	Pass
233	7115	108.57	-95.23	21.577	13.34	30	Pass

802.11be (EHT40)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	112.15	-95.23	49.204	16.92	30	Pass
43	6165	112.02	-95.23	47.753	16.79	30	Pass
91	6405	111.57	-95.23	43.053	16.34	30	Pass
99	6445	111.89	-95.23	46.345	16.66	30	Pass
107	6485	111.02	-95.23	37.931	15.79	30	Pass
115	6525	111.65	-95.23	43.853	16.42	30	Pass
123	6565	112.22	-95.23	50.003	16.99	30	Pass
155	6725	111.07	-95.23	38.371	15.84	30	Pass
179	6845	111.64	-95.23	43.752	16.41	30	Pass
187	6885	111.58	-95.23	43.152	16.35	30	Pass
211	7005	111.61	-95.23	43.451	16.38	30	Pass
227	7085	110.41	-95.23	32.961	15.18	30	Pass

802.11be (EHT80)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	114.92	-95.23	93.111	19.69	30	Pass
39	6145	114.95	-95.23	93.756	19.72	30	Pass
87	6385	114.31	-95.23	80.91	19.08	30	Pass
103	6465	114.76	-95.23	89.743	19.53	30	Pass
119	6545	114.78	-95.23	90.157	19.55	30	Pass
151	6705	114.12	-95.23	77.446	18.89	30	Pass
183	6865	114.75	-95.23	89.536	19.52	30	Pass
199	6945	114.22	-95.23	79.25	18.99	30	Pass
215	7025	114.42	-95.23	82.985	19.19	30	Pass

802.11be (EHT160)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	118.35	-95.23	205.116	23.12	30	Pass
47	6185	118.05	-95.23	191.426	22.82	30	Pass
79	6345	117.02	-95.23	151.008	21.79	30	Pass
111	6505	117.05	-95.23	152.055	21.82	30	Pass
143	6665	117.35	-95.23	162.93	22.12	30	Pass
175	6825	117.45	-95.23	166.725	22.22	30	Pass
207	6985	118.02	-95.23	190.108	22.79	30	Pass

802.11be (EHT320)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
31	6105	120.62	-95.23	345.939	25.39	30	Pass
63	6265	120.05	-95.23	303.389	24.82	30	Pass
95	6425	120.01	-95.23	300.608	24.78	30	Pass
127	6585	119.78	-95.23	285.102	24.55	30	Pass
159	6745	120.72	-95.23	353.997	25.49	30	Pass
191	6905	120.68	-95.23	350.752	25.45	30	Pass

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
1	5955	111.85	-95.23	45.92	16.62	30	Pass
45	6175	113.45	-95.23	66.374	18.22	30	Pass
93	6415	111.57	-95.23	43.053	16.34	30	Pass
97	6435	111.35	-95.23	40.926	16.12	30	Pass
105	6475	112.37	-95.23	51.761	17.14	30	Pass
113	6515	112.12	-95.23	48.865	16.89	30	Pass
117	6535	112.35	-95.23	51.523	17.12	30	Pass
149	6695	112.51	-95.23	53.456	17.28	30	Pass
181	6855	111.72	-95.23	44.566	16.49	30	Pass
185	6875	111.64	-95.23	43.752	16.41	30	Pass
209	6995	111.47	-95.23	42.073	16.24	30	Pass
233	7115	111.12	-95.23	38.815	15.89	30	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
3	5965	115.32	-95.23	102.094	20.09	30	Pass
43	6165	115.56	-95.23	107.895	20.33	30	Pass
91	6405	114.15	-95.23	77.983	18.92	30	Pass
99	6445	113.62	-95.23	69.024	18.39	30	Pass
107	6485	114.65	-95.23	87.498	19.42	30	Pass
115	6525	114.22	-95.23	79.25	18.99	30	Pass
123	6565	114.15	-95.23	77.983	18.92	30	Pass
155	6725	114.08	-95.23	76.736	18.85	30	Pass
179	6845	115.05	-95.23	95.94	19.82	30	Pass
187	6885	115.25	-95.23	100.462	20.02	30	Pass
211	7005	114.32	-95.23	81.096	19.09	30	Pass
227	7085	113.05	-95.23	60.534	17.82	30	Pass

802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
7	5985	118.21	-95.23	198.609	22.98	30	Pass
39	6145	117.62	-95.23	173.38	22.39	30	Pass
87	6385	117.84	-95.23	182.39	22.61	30	Pass
103	6465	116.86	-95.23	145.546	21.63	30	Pass
119	6545	116.85	-95.23	145.211	21.62	30	Pass
151	6705	117.52	-95.23	169.434	22.29	30	Pass
183	6865	118.32	-95.23	203.704	23.09	30	Pass
199	6945	117.05	-95.23	152.055	21.82	30	Pass
215	7025	116.62	-95.23	137.721	21.39	30	Pass

802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
15	6025	120.42	-95.23	330.37	25.19	30	Pass
47	6185	121.05	-95.23	381.944	25.82	30	Pass
79	6345	119.96	-95.23	297.167	24.73	30	Pass
111	6505	119.58	-95.23	272.27	24.35	30	Pass
143	6665	119.45	-95.23	264.241	24.22	30	Pass
175	6825	119.78	-95.23	285.102	24.55	30	Pass
207	6985	120.05	-95.23	303.389	24.82	30	Pass

802.11be (EHT320) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP (mW)	EIRP (dBm)	EIRP Limit (dBm)	Test Result
31	6105	123.29	-95.23	639.735	28.06	30	Pass
63	6265	122.72	-95.23	561.048	27.49	30	Pass
95	6425	122.65	-95.23	552.077	27.42	30	Pass
127	6585	122.39	-95.23	519.996	27.16	30	Pass
159	6745	122.89	-95.23	583.445	27.66	30	Pass
191	6905	123.84	-95.23	726.106	28.61	30	Pass

Spectrum Plot of Maximum Value



802.11a : CH 45



802.11be (EHT20) : CH 45

802.11be (EHT40) : CH 43

802.11be (EHT80) : CH 183

802.11be (EHT160) : CH 47

802.11be (EHT320) : CH 191

7.2 Maximum Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin

802.11a

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.18	-95.23	4.95	5	Pass
45	6175	100.21	-95.23	4.98	5	Pass
93	6415	100.17	-95.23	4.94	5	Pass
97	6435	100.17	-95.23	4.94	5	Pass
105	6475	100.17	-95.23	4.94	5	Pass
113	6515	100.08	-95.23	4.85	5	Pass
117	6535	100.12	-95.23	4.89	5	Pass
149	6695	100.19	-95.23	4.96	5	Pass
181	6855	100.19	-95.23	4.96	5	Pass
185	6875	100.18	-95.23	4.95	5	Pass
209	6995	100.08	-95.23	4.85	5	Pass
233	7115	100.09	-95.23	4.86	5	Pass

802.11be (EHT20)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.05	-95.23	4.82	5	Pass
45	6175	100.15	-95.23	4.92	5	Pass
93	6415	100.19	-95.23	4.96	5	Pass
97	6435	100.05	-95.23	4.82	5	Pass
105	6475	100.08	-95.23	4.85	5	Pass
113	6515	100.07	-95.23	4.84	5	Pass
117	6535	100.08	-95.23	4.85	5	Pass
149	6695	100.12	-95.23	4.89	5	Pass
181	6855	100.19	-95.23	4.96	5	Pass
185	6875	100.09	-95.23	4.86	5	Pass
209	6995	100.11	-95.23	4.88	5	Pass
233	7115	100.06	-95.23	4.83	5	Pass

802.11be (EHT40)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
3	5965	100.18	-95.23	4.95	5	Pass
43	6165	100.12	-95.23	4.89	5	Pass
91	6405	100.15	-95.23	4.92	5	Pass
99	6445	100.12	-95.23	4.89	5	Pass
107	6485	100.16	-95.23	4.93	5	Pass
115	6525	100.15	-95.23	4.92	5	Pass
123	6565	100.18	-95.23	4.95	5	Pass
155	6725	100.08	-95.23	4.85	5	Pass
179	6845	100.18	-95.23	4.95	5	Pass
187	6885	100.05	-95.23	4.82	5	Pass
211	7005	100.16	-95.23	4.93	5	Pass
227	7085	100.12	-95.23	4.89	5	Pass

802.11be (EHT80)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
7	5985	100.09	-95.23	4.86	5	Pass
39	6145	100.15	-95.23	4.92	5	Pass
87	6385	100.19	-95.23	4.96	5	Pass
103	6465	100.14	-95.23	4.91	5	Pass
119	6545	100.05	-95.23	4.82	5	Pass
151	6705	100.12	-95.23	4.89	5	Pass
183	6865	100.05	-95.23	4.82	5	Pass
199	6945	100.07	-95.23	4.84	5	Pass
215	7025	100.05	-95.23	4.82	5	Pass

802.11be (EHT160)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
15	6025	100.12	-95.23	4.89	5	Pass
47	6185	100.15	-95.23	4.92	5	Pass
79	6345	100.16	-95.23	4.93	5	Pass
111	6505	100.17	-95.23	4.94	5	Pass
143	6665	100.18	-95.23	4.95	5	Pass
175	6825	100.12	-95.23	4.89	5	Pass
207	6985	100.06	-95.23	4.83	5	Pass

802.11be (EHT320)

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
31	6105	100.08	-95.23	4.85	5	Pass
63	6265	100.07	-95.23	4.84	5	Pass
95	6425	100.05	-95.23	4.82	5	Pass
127	6585	100.09	-95.23	4.86	5	Pass
159	6745	100.16	-95.23	4.93	5	Pass
191	6905	100.05	-95.23	4.82	5	Pass

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
1	5955	100.20	-95.23	4.97	5	Pass
45	6175	100.21	-95.23	4.98	5	Pass
93	6415	100.15	-95.23	4.92	5	Pass
97	6435	100.16	-95.23	4.93	5	Pass
105	6475	100.19	-95.23	4.96	5	Pass
113	6515	100.19	-95.23	4.96	5	Pass
117	6535	100.18	-95.23	4.95	5	Pass
149	6695	100.18	-95.23	4.95	5	Pass
181	6855	100.21	-95.23	4.98	5	Pass
185	6875	100.18	-95.23	4.95	5	Pass
209	6995	100.19	-95.23	4.96	5	Pass
233	7115	100.07	-95.23	4.84	5	Pass

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
3	5965	100.19	-95.23	4.96	5	Pass
43	6165	100.15	-95.23	4.92	5	Pass
91	6405	100.15	-95.23	4.92	5	Pass
99	6445	100.18	-95.23	4.95	5	Pass
107	6485	100.14	-95.23	4.91	5	Pass
115	6525	100.19	-95.23	4.96	5	Pass
123	6565	100.15	-95.23	4.92	5	Pass
155	6725	100.16	-95.23	4.93	5	Pass
179	6845	100.18	-95.23	4.95	5	Pass
187	6885	100.18	-95.23	4.95	5	Pass
211	7005	100.15	-95.23	4.92	5	Pass
227	7085	100.17	-95.23	4.94	5	Pass

802.11be (EHT80) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
7	5985	100.19	-95.23	4.96	5	Pass
39	6145	100.05	-95.23	4.82	5	Pass
87	6385	100.21	-95.23	4.98	5	Pass
103	6465	100.14	-95.23	4.91	5	Pass
119	6545	100.15	-95.23	4.92	5	Pass
151	6705	100.04	-95.23	4.81	5	Pass
183	6865	100.19	-95.23	4.96	5	Pass
199	6945	100.18	-95.23	4.95	5	Pass
215	7025	100.15	-95.23	4.92	5	Pass

802.11be (EHT160) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
15	6025	100.20	-95.23	4.97	5	Pass
47	6185	100.19	-95.23	4.96	5	Pass
79	6345	100.06	-95.23	4.83	5	Pass
111	6505	100.20	-95.23	4.97	5	Pass
143	6665	100.17	-95.23	4.94	5	Pass
175	6825	100.15	-95.23	4.92	5	Pass
207	6985	100.15	-95.23	4.92	5	Pass

802.11be (EHT320) Beamforming

Chan.	Chan. Freq. (MHz)	Field Strength (dBuV/m)	Correction Factor (dB)	EIRP PSD (dBm/MHz)	EIRP PSD Limit (dBm/MHz)	Test Result
31	6105	100.18	-95.23	4.95	5	Pass
63	6265	100.15	-95.23	4.92	5	Pass
95	6425	100.12	-95.23	4.89	5	Pass
127	6585	100.14	-95.23	4.91	5	Pass
159	6745	100.16	-95.23	4.93	5	Pass
191	6905	100.18	-95.23	4.95	5	Pass

Spectrum Plot of Maximum Value



802.11a : CH 45



802.11be (EHT20) : CH 45



802.11be (EHT40) : CH 3



802.11be (EHT80) : CH 87



802.11be (EHT160) : CH 15



802.11be (EHT320) : CH 191

7.3 Emission Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin

802.11a

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	5955	18.56	18.56	18.49	18.55	320	Pass
45	6175	18.62	18.72	18.68	18.72	320	Pass
93	6415	18.71	18.64	18.76	18.62	320	Pass
97	6435	18.76	18.80	18.84	18.68	320	Pass
105	6475	18.69	18.66	18.70	18.78	320	Pass
113	6515	18.77	18.66	18.71	18.73	320	Pass
117	6535	18.77	18.72	18.66	18.77	320	Pass
149	6695	18.75	18.76	18.70	18.77	320	Pass
181	6855	18.74	18.81	18.72	18.75	320	Pass
185	6875	18.60	18.76	18.76	18.53	320	Pass
209	6995	18.76	18.72	18.81	18.73	320	Pass
233	7115	18.67	18.70	18.85	18.68	320	Pass

802.11be (EHT20)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	5955	19.99	20.00	19.98	19.96	320	Pass
45	6175	20.13	20.02	20.03	19.99	320	Pass
93	6415	20.11	19.98	19.93	19.97	320	Pass
97	6435	20.11	20.03	20.05	20.01	320	Pass
105	6475	20.14	20.01	20.00	20.02	320	Pass
113	6515	20.14	20.02	20.00	20.02	320	Pass
117	6535	20.12	19.98	19.99	20.01	320	Pass
149	6695	20.14	19.94	19.96	19.99	320	Pass
181	6855	20.09	19.97	20.00	20.03	320	Pass
185	6875	20.04	19.99	20.02	20.05	320	Pass
209	6995	20.10	20.03	19.98	19.96	320	Pass
233	7115	20.15	20.03	20.03	20.06	320	Pass

802.11be (EHT40)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
3	5965	39.71	39.67	39.66	39.62	320	Pass
43	6165	39.85	39.99	39.94	39.98	320	Pass
91	6405	39.94	39.91	39.85	39.90	320	Pass
99	6445	39.77	39.96	39.95	39.83	320	Pass
107	6485	39.86	39.92	39.93	40.30	320	Pass
115	6525	39.88	39.92	39.89	39.91	320	Pass
123	6565	39.90	39.95	39.88	39.92	320	Pass
155	6725	39.89	39.94	39.90	39.95	320	Pass
179	6845	39.91	39.84	39.92	39.91	320	Pass
187	6885	39.89	39.93	39.92	39.89	320	Pass
211	7005	39.97	39.99	39.93	39.88	320	Pass
227	7085	39.89	39.90	39.84	39.91	320	Pass

802.11be (EHT80)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
7	5985	80.75	80.72	80.77	80.80	320	Pass
39	6145	81.28	81.22	81.29	81.28	320	Pass
87	6385	81.14	81.20	81.17	81.22	320	Pass
103	6465	81.22	81.25	81.30	81.25	320	Pass
119	6545	80.79	81.28	81.27	81.26	320	Pass
151	6705	81.20	81.15	81.19	81.16	320	Pass
183	6865	81.25	81.16	81.21	81.29	320	Pass
199	6945	81.27	81.26	81.20	81.15	320	Pass
215	7025	81.25	81.26	81.16	81.26	320	Pass

802.11be (EHT160)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
15	6025	162.80	162.93	163.00	162.69	320	Pass
47	6185	163.71	163.70	163.76	163.53	320	Pass
79	6345	163.56	163.54	163.52	163.68	320	Pass
111	6505	163.38	163.58	163.70	163.64	320	Pass
143	6665	163.61	163.47	163.60	163.29	320	Pass
175	6825	163.72	163.59	163.62	163.50	320	Pass
207	6985	163.51	163.66	163.41	163.68	320	Pass

802.11be (EHT320)

Channel	Frequency (MHz)	26dB Bandwidth (MHz)				Maximum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
31	6105	325.57	325.48	325.29	325.54	320	Note
63	6265	327.22	326.87	326.78	327.34	320	Note
95	6425	325.34	325.42	325.13	325.55	320	Note
127	6585	326.82	327.02	327.04	326.75	320	Note
159	6745	326.91	326.66	326.70	326.54	320	Note
191	6905	326.64	327.07	326.65	326.95	320	Note

Note: For channels with a nominal bandwidth of 320 MHz, compliance is demonstrated by way of the 99% BW.

Spectrum Plot of Maximum Value



802.11a / Chain 2 : CH 233



802.11be (EHT20) / Chain 0 : CH 233



802.11be (EHT40) / Chain 3 : CH 107



802.11be (EHT80) / Chain 2 : CH 103



802.11be (EHT160) / Chain 2 : CH 47



802.11be (EHT320) / Chain 3 : CH 63

7.4 In-Band Emission Mask

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin

802.11a

Spectrum Plot



802.11a / Chain 0 : CH 1



802.11a / Chain 0 : CH 45



802.11a / Chain 0 : CH 93



802.11a / Chain 0 : CH 97



802.11a / Chain 0 : CH 105



802.11a / Chain 0 : CH 113

Spectrum Plot



802.11a / Chain 0 : CH 117



802.11a / Chain 0 : CH 149



802.11a / Chain 0 : CH 181



802.11a / Chain 0 : CH 185



802.11a / Chain 0 : CH 209



802.11a / Chain 0 : CH 233

Spectrum Plot



802.11a / Chain 1 : CH 1



802.11a / Chain 1 : CH 45



802.11a / Chain 1 : CH 93



802.11a / Chain 1 : CH 97



802.11a / Chain 1 : CH 105



802.11a / Chain 1 : CH 113

Spectrum Plot



802.11a / Chain 1 : CH 117



802.11a / Chain 1 : CH 149



802.11a / Chain 1 : CH 181



802.11a / Chain 1 : CH 185



802.11a / Chain 1 : CH 209



802.11a / Chain 1 : CH 233

Spectrum Plot



802.11a / Chain 2 : CH 1



802.11a / Chain 2 : CH 45



802.11a / Chain 2 : CH 93



802.11a / Chain 2 : CH 97



802.11a / Chain 2 : CH 105



802.11a / Chain 2 : CH 113

Spectrum Plot



802.11a / Chain 2 : CH 117



802.11a / Chain 2 : CH 149



802.11a / Chain 2 : CH 181



802.11a / Chain 2 : CH 185



802.11a / Chain 2 : CH 209



802.11a / Chain 2 : CH 233

Spectrum Plot



802.11a / Chain 3 : CH 1



802.11a / Chain 3 : CH 45



802.11a / Chain 3 : CH 93



802.11a / Chain 3 : CH 97



802.11a / Chain 3 : CH 105



802.11a / Chain 3 : CH 113

Spectrum Plot



802.11a / Chain 3 : CH 117



802.11a / Chain 3 : CH 149



802.11a / Chain 3 : CH 181



802.11a / Chain 3 : CH 185



802.11a / Chain 3 : CH 209



802.11a / Chain 3 : CH 233

802.11be (EHT20)

Spectrum Plot



802.11be (EHT20) / Chain 0 : CH 1



802.11be (EHT20) / Chain 0 : CH 45



802.11be (EHT20) / Chain 0 : CH 93



802.11be (EHT20) / Chain 0 : CH 97



802.11be (EHT20) / Chain 0 : CH 105



802.11be (EHT20) / Chain 0 : CH 113

Spectrum Plot



802.11be (EHT20) / Chain 0 : CH 117



802.11be (EHT20) / Chain 0 : CH 149



802.11be (EHT20) / Chain 0 : CH 181



802.11be (EHT20) / Chain 0 : CH 185



802.11be (EHT20) / Chain 0 : CH 209



802.11be (EHT20) / Chain 0 : CH 233

Spectrum Plot



802.11be (EHT20) / Chain 1 : CH 1



802.11be (EHT20) / Chain 1 : CH 45



802.11be (EHT20) / Chain 1 : CH 93



802.11be (EHT20) / Chain 1 : CH 97



802.11be (EHT20) / Chain 1 : CH 105



802.11be (EHT20) / Chain 1 : CH 113

Spectrum Plot



802.11be (EHT20) / Chain 1 : CH 117



802.11be (EHT20) / Chain 1 : CH 149



802.11be (EHT20) / Chain 1 : CH 181



802.11be (EHT20) / Chain 1 : CH 185



802.11be (EHT20) / Chain 1 : CH 209



802.11be (EHT20) / Chain 1 : CH 233

Spectrum Plot



802.11be (EHT20) / Chain 2 : CH 1



802.11be (EHT20) / Chain 2 : CH 45



802.11be (EHT20) / Chain 2 : CH 93



802.11be (EHT20) / Chain 2 : CH 97



802.11be (EHT20) / Chain 2 : CH 105



802.11be (EHT20) / Chain 2 : CH 113

Spectrum Plot



802.11be (EHT20) / Chain 2 : CH 117



802.11be (EHT20) / Chain 2 : CH 149



802.11be (EHT20) / Chain 2 : CH 181



802.11be (EHT20) / Chain 2 : CH 185



802.11be (EHT20) / Chain 2 : CH 209



802.11be (EHT20) / Chain 2 : CH 233

Spectrum Plot



802.11be (EHT20) / Chain 3 : CH 1



802.11be (EHT20) / Chain 3 : CH 45



802.11be (EHT20) / Chain 3 : CH 93



802.11be (EHT20) / Chain 3 : CH 97



802.11be (EHT20) / Chain 3 : CH 105



802.11be (EHT20) / Chain 3 : CH 113

Spectrum Plot



802.11be (EHT20) / Chain 3 : CH 117



802.11be (EHT20) / Chain 3 : CH 149



802.11be (EHT20) / Chain 3 : CH 181



802.11be (EHT20) / Chain 3 : CH 185



802.11be (EHT20) / Chain 3 : CH 209



802.11be (EHT20) / Chain 3 : CH 233

802.11be (EHT40)

Spectrum Plot



802.11be (EHT40) / Chain 0 : CH 3



802.11be (EHT40) / Chain 0 : CH 43



802.11be (EHT40) / Chain 0 : CH 91



802.11be (EHT40) / Chain 0 : CH 99



802.11be (EHT40) / Chain 0 : CH 107



802.11be (EHT40) / Chain 0 : CH 115

Spectrum Plot



802.11be (EHT40) / Chain 0 : CH 123



802.11be (EHT40) / Chain 0 : CH 155



802.11be (EHT40) / Chain 0 : CH 179



802.11be (EHT40) / Chain 0 : CH 187



802.11be (EHT40) / Chain 0 : CH 211



802.11be (EHT40) / Chain 0 : CH 227

Spectrum Plot



802.11be (EHT40) / Chain 1 : CH 3



802.11be (EHT40) / Chain 1 : CH 43



802.11be (EHT40) / Chain 1 : CH 91



802.11be (EHT40) / Chain 1 : CH 99



802.11be (EHT40) / Chain 1 : CH 107



802.11be (EHT40) / Chain 1 : CH 115

Spectrum Plot



802.11be (EHT40) / Chain 1 : CH 123



802.11be (EHT40) / Chain 1 : CH 155



802.11be (EHT40) / Chain 1 : CH 179



802.11be (EHT40) / Chain 1 : CH 187



802.11be (EHT40) / Chain 1 : CH 211



802.11be (EHT40) / Chain 1 : CH 227

Spectrum Plot



802.11be (EHT40) / Chain 2 : CH 3



802.11be (EHT40) / Chain 2 : CH 43



802.11be (EHT40) / Chain 2 : CH 91



802.11be (EHT40) / Chain 2 : CH 99



802.11be (EHT40) / Chain 2 : CH 107



802.11be (EHT40) / Chain 2 : CH 115

Spectrum Plot



802.11be (EHT40) / Chain 2 : CH 123



802.11be (EHT40) / Chain 2 : CH 155



802.11be (EHT40) / Chain 2 : CH 179



802.11be (EHT40) / Chain 2 : CH 187



802.11be (EHT40) / Chain 2 : CH 211



802.11be (EHT40) / Chain 2 : CH 227

Spectrum Plot



802.11be (EHT40) / Chain 3 : CH 3



802.11be (EHT40) / Chain 3 : CH 43



802.11be (EHT40) / Chain 3 : CH 91



802.11be (EHT40) / Chain 3 : CH 99



802.11be (EHT40) / Chain 3 : CH 107



802.11be (EHT40) / Chain 3 : CH 115

Spectrum Plot



802.11be (EHT40) / Chain 3 : CH 123



802.11be (EHT40) / Chain 3 : CH 155



802.11be (EHT40) / Chain 3 : CH 179



802.11be (EHT40) / Chain 3 : CH 187



802.11be (EHT40) / Chain 3 : CH 211



802.11be (EHT40) / Chain 3 : CH 227

802.11be (EHT80)

Spectrum Plot



802.11be (EHT80) / Chain 0 : CH 7



802.11be (EHT80) / Chain 0 : CH 39



802.11be (EHT80) / Chain 0 : CH 87



802.11be (EHT80) / Chain 0 : CH 103



802.11be (EHT80) / Chain 0 : CH 119



802.11be (EHT80) / Chain 0 : CH 151

Spectrum Plot



802.11be (EHT80) / Chain 0 : CH 183



802.11be (EHT80) / Chain 0 : CH 199



802.11be (EHT80) / Chain 0 : CH 215



802.11be (EHT80) / Chain 1 : CH 7



802.11be (EHT80) / Chain 1 : CH 39



802.11be (EHT80) / Chain 1 : CH 87

Spectrum Plot



802.11be (EHT80) / Chain 1 : CH 103



802.11be (EHT80) / Chain 1 : CH 119



802.11be (EHT80) / Chain 1 : CH 151



802.11be (EHT80) / Chain 1 : CH 183



802.11be (EHT80) / Chain 1 : CH 199



802.11be (EHT80) / Chain 1 : CH 215

Spectrum Plot



802.11be (EHT80) / Chain 2 : CH 7



802.11be (EHT80) / Chain 2 : CH 39



802.11be (EHT80) / Chain 2 : CH 87



802.11be (EHT80) / Chain 2 : CH 103



802.11be (EHT80) / Chain 2 : CH 119



802.11be (EHT80) / Chain 2 : CH 151

Spectrum Plot



802.11be (EHT80) / Chain 2 : CH 183



802.11be (EHT80) / Chain 2 : CH 199



802.11be (EHT80) / Chain 2 : CH 215



802.11be (EHT80) / Chain 3 : CH 7



802.11be (EHT80) / Chain 3 : CH 39



802.11be (EHT80) / Chain 3 : CH 87

Spectrum Plot



802.11be (EHT80) / Chain 3 : CH 103



802.11be (EHT80) / Chain 3 : CH 119



802.11be (EHT80) / Chain 3 : CH 151



802.11be (EHT80) / Chain 3 : CH 183



802.11be (EHT80) / Chain 3 : CH 199



802.11be (EHT80) / Chain 3 : CH 215

802.11be (EHT160)

Spectrum Plot



802.11be (EHT160) / Chain 0 : CH 15



802.11be (EHT160) / Chain 0 : CH 47



802.11be (EHT160) / Chain 0 : CH 79



802.11be (EHT160) / Chain 0 : CH 111



802.11be (EHT160) / Chain 0 : CH 143



802.11be (EHT160) / Chain 0 : CH 175

Spectrum Plot



802.11be (EHT160) / Chain 0 : CH 207



802.11be (EHT160) / Chain 1 : CH 15



802.11be (EHT160) / Chain 1 : CH 47



802.11be (EHT160) / Chain 1 : CH 79



802.11be (EHT160) / Chain 1 : CH 111



802.11be (EHT160) / Chain 1 : CH 143

Spectrum Plot



802.11be (EHT160) / Chain 1 : CH 175



802.11be (EHT160) / Chain 1 : CH 207



802.11be (EHT160) / Chain 2 : CH 15



802.11be (EHT160) / Chain 2 : CH 47



802.11be (EHT160) / Chain 2 : CH 79



802.11be (EHT160) / Chain 2 : CH 111

Spectrum Plot



802.11be (EHT160) / Chain 2 : CH 143



802.11be (EHT160) / Chain 2 : CH 175



802.11be (EHT160) / Chain 2 : CH 207



802.11be (EHT160) / Chain 3 : CH 15



802.11be (EHT160) / Chain 3 : CH 47



802.11be (EHT160) / Chain 3 : CH 79

Spectrum Plot



802.11be (EHT160) / Chain 3 : CH 111



802.11be (EHT160) / Chain 3 : CH 143



802.11be (EHT160) / Chain 3 : CH 175



802.11be (EHT160) / Chain 3 : CH 207

802.11be (EHT320)

Spectrum Plot



802.11be (EHT320) / Chain 0 : CH 31



802.11be (EHT320) / Chain 0 : CH 63



802.11be (EHT320) / Chain 0 : CH 95



802.11be (EHT320) / Chain 0 : CH 127



802.11be (EHT320) / Chain 0 : CH 159



802.11be (EHT320) / Chain 0 : CH 191

Spectrum Plot



802.11be (EHT320) / Chain 1 : CH 31



802.11be (EHT320) / Chain 1 : CH 63



802.11be (EHT320) / Chain 1 : CH 95



802.11be (EHT320) / Chain 1 : CH 127



802.11be (EHT320) / Chain 1 : CH 159



802.11be (EHT320) / Chain 1 : CH 191

Spectrum Plot



802.11be (EHT320) / Chain 2 : CH 31



802.11be (EHT320) / Chain 2 : CH 63



802.11be (EHT320) / Chain 2 : CH 95



802.11be (EHT320) / Chain 2 : CH 127



802.11be (EHT320) / Chain 2 : CH 159



802.11be (EHT320) / Chain 2 : CH 191

Spectrum Plot



802.11be (EHT320) / Chain 3 : CH 31



802.11be (EHT320) / Chain 3 : CH 63



802.11be (EHT320) / Chain 3 : CH 95



802.11be (EHT320) / Chain 3 : CH 127



802.11be (EHT320) / Chain 3 : CH 159



802.11be (EHT320) / Chain 3 : CH 191

7.5 Occupied Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Chris Lin

802.11a

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
1	5955	16.50	16.44	16.50	16.50
45	6175	16.44	16.56	16.56	16.56
93	6415	16.44	16.44	16.56	16.56
97	6435	16.44	16.56	16.44	16.56
105	6475	16.44	16.56	16.56	16.56
113	6515	16.44	16.56	16.56	16.56
117	6535	16.44	16.56	16.56	16.56
149	6695	16.44	16.56	16.56	16.56
181	6855	16.44	16.56	16.56	16.56
185	6875	16.50	16.56	16.56	16.50
209	6995	16.44	16.56	16.56	16.56
233	7115	16.56	16.44	16.56	16.56

802.11be (EHT20)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
1	5955	18.90	18.90	18.90	18.90
45	6175	18.96	18.90	18.90	18.90
93	6415	18.96	18.90	18.90	18.90
97	6435	18.96	18.90	18.90	18.90
105	6475	18.96	18.90	18.90	18.90
113	6515	18.96	18.96	18.96	18.90
117	6535	18.96	18.90	18.90	18.90
149	6695	18.96	18.90	18.90	18.90
181	6855	18.96	18.90	18.90	18.90
185	6875	18.90	18.90	18.90	18.90
209	6995	18.96	18.90	18.90	18.90
233	7115	18.96	18.96	18.90	18.96

802.11be (EHT40)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
3	5965	38.16	38.04	37.92	37.92
43	6165	38.16	38.16	37.92	38.16
91	6405	38.16	38.16	38.16	37.92
99	6445	37.92	37.92	38.16	37.92
107	6485	38.16	38.16	37.92	38.16
115	6525	37.92	37.92	38.16	38.16
123	6565	38.16	38.16	38.16	38.16
155	6725	37.92	37.92	38.16	38.16
179	6845	38.16	38.16	38.16	38.16
187	6885	38.16	37.92	38.16	38.16
211	7005	37.92	38.40	37.92	38.16
227	7085	38.16	38.16	38.16	37.92

802.11be (EHT80)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
7	5985	77.52	77.52	77.52	77.52
39	6145	77.76	77.76	77.76	77.76
87	6385	77.76	77.76	77.76	77.76
103	6465	77.76	77.76	77.76	77.76
119	6545	77.52	77.76	77.76	77.76
151	6705	77.76	77.76	77.28	77.76
183	6865	77.76	77.76	77.76	77.76
199	6945	77.76	77.76	77.76	77.76
215	7025	77.76	77.76	77.76	77.76

802.11be (EHT160)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
15	6025	156.96	156.48	157.44	156.96
47	6185	158.40	157.44	157.44	158.40
79	6345	157.44	157.44	156.48	157.44
111	6505	157.44	157.44	157.44	157.44
143	6665	157.44	157.44	157.44	157.44
175	6825	157.44	157.44	157.44	157.44
207	6985	157.44	158.40	158.40	157.44

802.11be (EHT320)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)			
		Chain 0	Chain 1	Chain 2	Chain 3
31	6105	315.84	316.80	315.84	314.88
63	6265	316.80	316.80	316.80	316.80
95	6425	314.88	314.88	314.88	313.92
127	6585	316.80	318.72	316.80	316.80
159	6745	316.80	314.88	316.80	316.80
191	6905	316.80	316.80	316.80	316.80

Spectrum Plot of Maximum Value



802.11a / Chain 0 : CH 233



802.11be (EHT20) / Chain 0 : CH 45



802.11be (EHT40) / Chain 1 : CH 211



802.11be (EHT80) / Chain 0 : CH 39



802.11be (EHT160) / Chain 0 : CH 47



802.11be (EHT320) / Chain 1 : CH 127

7.6 Contention-based Protocol

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Gary Cheng

Companion Device Information			
Product	**Brand**	**Model No.**	**Software/Firmware Version**
Intel(R) Wi-Fi 7 BE200 320MHz	Intel	BE200	23.60.1.2

For U-NII-5

Contention Based Protocol Measurement										
Operation Mode	**Channel Bandwidth (MHz)**	**Channel Number**	**Channel Freq. (MHz)**	**Injected Signal (AWGN)**		**Antenna Gain (dBi)**	**Path Loss (dB) (Note 3)**	**Adjusted Power (dBm)**	**Detection Limit**	**EUT TX Status**
				Freq. (MHz)	**Power (dBm)**					
802.11be	20	1	5955	5955	-71.89	3.89	0	-75.78	-62	OFF
					-72.39	3.89	0	-76.28	-62	Minimal
					-78.11	3.89	0	-82	-62	ON
	320	31	6105	5950	-70.4	3.89	0	-74.29	-62	OFF
					-70.9	3.89	0	-74.79	-62	Minimal
					-78.11	3.89	0	-82	-62	ON
				6105	-70.75	3.89	0	-74.64	-62	OFF
					-71.25	3.89	0	-75.14	-62	Minimal
					-78.11	3.89	0	-82	-62	ON
				6260	-71.96	3.89	0	-75.85	-62	OFF
					-72.46	3.89	0	-76.35	-62	Minimal
					-78.11	3.89	0	-82	-62	ON

Notes:

1. After investigation (consider antenna gain and path loss), the one representative port (Chain 2) was measured and presented in the report.
2. Adjusted Power (dBm) = Injected Signal (AWGN) Power (dBm) - Antenna Gain (dBi) + Path Loss (dB)
3. Antenna gain values include all the applicable path losses.
4. This device does not use the channel puncturing and bandwidth reduction mechanisms for incumbent avoidance, the EUT's connection has been restored.

Contention Based Protocol Detection Probability															
Operation Mode	Channel Bandwidth (MHz)	AWGN Signal Freq. (MHz)	#01	#02	#03	#04	#05	#06	#07	#08	#09	#10	Detection Probability	Detection Limit	Test Result
802.11be	20	5955	v	v	v	v	v	v	v	v	v	v	100%	90%	Pass
	320	5950	v	v	v	v	v	v	v	v	v	v	100%	90%	Pass
		6105	v	v	v	v	v	v	v	v	v	v	100%	90%	Pass
		6260	v	v	v	v	v	x	v	v	v	v	90%	90%	Pass

Plots of EUT Tx waveform



802.11be (EHT20) / CH1



802.11be (EHT320) / CH31

Plots of Injected signal (AWGN) level



802.11be (EHT20) / CH1



802.11be (EHT320) / CH31(Low Edge)



802.11be (EHT320) / CH31(Middle)



802.11be (EHT320) / CH31(High Edge)