

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Report No.: RFBCMA-WTW-P25030859

FCC ID: RAXWE8214443

Product: Wi-Fi Extender

Brand: T-Mobile

Model No.: T-MOBILE V2 Wi-Fi MESH ACCESS POINT

Received Date: 2025/3/25

Test Date: 2025/5/12 ~ 2025/6/2

Issued Date: 2025/7/9

Applicant: Arcadyan Technology Corporation

Address: No.8, Sec.2, Guangfu Rd., Hsinchu City 30071, Taiwan, R.O.C.

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300, Taiwan

FCC Registration / 723255 / TW2022

Designation Number:

Approved by:



Wen Yu / Assistant Manager

, Date:

2025/7/9

This test report consists of 76 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Phoenix Huang / Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description.....	7
3.2 Antenna Description of EUT.....	8
3.3 Channel List.....	10
3.4 Test Mode Applicability and Tested Channel Detail.....	11
3.5 Duty Cycle of Test Signal.....	12
3.6 Test Program Used and Operation Descriptions.....	15
3.7 Connection Diagram of EUT and Peripheral Devices.....	15
3.8 Configuration of Peripheral Devices and Cable Connections	15
4 Test Instruments	16
4.1 RF Output Power.....	16
4.2 Power Spectral Density	16
4.3 6 dB Bandwidth	16
4.4 Conducted Out of Band Emissions	16
4.5 AC Power Conducted Emissions	17
4.6 Unwanted Emissions below 1 GHz	17
4.7 Unwanted Emissions above 1 GHz.....	18
5 Limits of Test Items.....	19
5.1 RF Output Power.....	19
5.2 Power Spectral Density	19
5.3 6 dB Bandwidth	19
5.4 Conducted Out of Band Emissions	19
5.5 AC Power Conducted Emissions	19
5.6 Unwanted Emissions below 1 GHz	20
5.7 Unwanted Emissions above 1 GHz.....	20
6 Test Arrangements.....	21
6.1 RF Output Power.....	21
6.1.1 Test Setup	21
6.1.2 Test Procedure.....	21
6.2 Power Spectral Density	21
6.2.1 Test Setup	21
6.2.2 Test Procedure.....	21
6.3 6 dB Bandwidth	22
6.3.1 Test Setup	22
6.3.2 Test Procedure.....	22
6.4 Conducted Out of Band Emissions	22
6.4.1 Test Setup	22
6.4.2 Test Procedure.....	22
6.5 AC Power Conducted Emissions	23
6.5.1 Test Setup	23
6.5.2 Test Procedure.....	23
6.6 Unwanted Emissions below 1 GHz	24
6.6.1 Test Setup	24
6.6.2 Test Procedure.....	25
6.7 Unwanted Emissions above 1 GHz.....	26
6.7.1 Test Setup	26
6.7.2 Test Procedure.....	26
7 Test Results of Test Item	27

7.1	RF Output Power.....	27
7.2	Power Spectral Density	31
7.3	6 dB Bandwidth	33
7.4	Conducted Out of Band Emissions	35
7.5	AC Power Conducted Emissions	51
7.6	Unwanted Emissions below 1 GHz	53
7.7	Unwanted Emissions above 1 GHz.....	55
8	Pictures of Test Arrangements	75
9	Information of the Testing Laboratories	76

Release Control Record

Issue No.	Description	Date Issued
RFBCMA-WTW-P25030859	Original release.	2025/7/9

1 Certificate

Product: Wi-Fi Extender

Brand: T-Mobile

Test Model: T-MOBILE V2 Wi-Fi MESH ACCESS POINT

Sample Status: Engineering sample

Applicant: Arcadyan Technology Corporation

Test Date: 2025/5/12 ~ 2025/6/2

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement ANSI C63.10-2013

procedure: KDB 558074 D01 15.247 Meas Guidance v05r02

KDB 662911 D01 Multiple Transmitter Output v02r01

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -5.55 dB at 0.66172 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -5.7 dB at 64.24 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -0.2 dB at 2390.00 MHz
15.203	Antenna Requirement	Pass	Antenna connector is ipex(MHF) not a standard connector.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.1 dB
Power Spectral Density	-	1.3 dB
6 dB Bandwidth	-	1050.00 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.6 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	1.9 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3.1 dB
	30 MHz ~ 1 GHz	5.1 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	5.1 dB
	18 GHz ~ 40 GHz	5.3 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Wi-Fi Extender
Brand	T-Mobile
Test Model	T-MOBILE V2 Wi-Fi MESH ACCESS POINT
Status of EUT	Engineering sample
Power Supply Rating	15 Vdc from power adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM 256QAM for OFDM in VHT mode 1024QAM for OFDMA in 11ax mode 4096QAM for OFDMA in 11be mode
Modulation Technology	DSSS, OFDM, OFDMA
Transfer Rate	802.11b: up to 11 Mbps 802.11g: up to 54 Mbps 802.11n: up to 600 Mbps VHT: up to 800 Mbps 802.11ax: up to 1147.1 Mbps 802.11be: up to 1376.5 Mbps
Operating Frequency	2.412 GHz ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20), 802.11be (EHT20): 11 802.11n (HT40), VHT40, 802.11ax (HE40), 802.11be (EHT40): 7
Output Power	CDD Mode: 848.413 mW (29.29 dBm) Beamforming Mode: 568.961 mW (27.55 dBm)

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
AC Adapter 1	Mass power	PD030E-A1C0AVU	AC Input: 100-240 Vac, 0.8 A, 50-60 Hz DC Output: 15 Vdc, 2 A DC Output Cable: 1.8 m, unshielded cable, w/o ferrite core
AC Adapter 2	MOSO	P40-V1500R200-030CC0-US	AC Input: 100-240 Vac, 0.8 A, 50-60 Hz DC Output: 15 Vdc, 2 A DC Output Cable: 1.8 m, unshielded cable, w/o ferrite core
RJ45 Cable	-	-	Signal Line: 2 meter, unshielded, w/o ferrite core

2. The EUT has below radios as following table:

Radio 1	Radio 2	Radio 3	Radio 4
WLAN (2.4GHz)	WLAN (5GHz)	BT-LE	BT-LE / 802.15.4 (Zigbee/Open Thread/Matter)

3. Simultaneously transmission combination.

Combination	Technology
1	WLAN (2.4 GHz) + WLAN (5 GHz) + 802.15.4 (Zigbee/Open Thread/Matter) + BT-LE

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Antenna NO.	RF Chain NO.	Brand	Model	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
1_DB	0	HONGBO	290-70562	3.6	2.4 ~ 2.4835	Monopole	ipex(MHF)
				3.8	5.15 ~ 5.25		
				3.5	5.25 ~ 5.35		
				3.4	5.47 ~ 5.725		
				3.5	5.725 ~ 5.85		
2_DB	1	HONGBO	290-70563	2.8	2.4 ~ 2.4835	Monopole	ipex(MHF)
				1.7	5.15 ~ 5.25		
				1.8	5.25 ~ 5.35		
				2	5.47 ~ 5.725		
				2.2	5.725 ~ 5.85		
3_DB	2	HONGBO	290-70564	3.1	2.4 ~ 2.4835	Monopole	ipex(MHF)
				1.5	5.15 ~ 5.25		
				1.3	5.25 ~ 5.35		
				1.5	5.47 ~ 5.725		
				1.3	5.725 ~ 5.85		
4_DB	3	HONGBO	290-70565	2.8	2.4 ~ 2.4835	Monopole	ipex(MHF)
				2.5	5.15 ~ 5.25		
				2	5.25 ~ 5.35		
				1.8	5.47 ~ 5.725		
				2.2	5.725 ~ 5.85		
5_RX	0	HONGBO	290-70566	3.2	5.15 ~ 5.25	Monopole	ipex(MHF)
				3	5.25 ~ 5.35		
				2.7	5.47 ~ 5.725		
				2.2	5.725 ~ 5.85		
6_BT	BJ1	HONGBO	290-70567	4.1	2.4 ~ 2.4835	Monopole	ipex(MHF)
7_iOT	ZJ1	HONGBO	290-70568	5.1	2.4 ~ 2.4835	Monopole	ipex(MHF)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The directional antenna gain, please refer to the following table:

Frequency Range (GHz)	Directional Gain (dBi)
2.4~2.4835	5.13
5.15~5.25	5.8
5.25~5.35	6.02
5.47~5.725	5.57
5.725~5.85	5.67

3. The EUT incorporates a MIMO function:

2.4 GHz Band		
Modulation Mode	TX & RX Configuration	
802.11b	4TX	4RX
802.11g	4TX	4RX
802.11n (HT20)	4TX	4RX
802.11n (HT40)	4TX	4RX
VHT20	4TX	4RX
VHT40	4TX	4RX
802.11ax (HE20)	4TX	4RX
802.11ax (HE40)	4TX	4RX
802.11be (EHT20)	4TX	4RX
802.11be (EHT40)	4TX	4RX

Note:

1. All of modulation mode support beamforming function except 802.11b/g modulation mode.
2. The EUT support Beamforming and CDD mode, therefore both mode were investigated and the worst case scenario was identified. The worst case data were presented in test report.
3. The modulation and bandwidth are similar for 802.11n mode for 20 MHz (40 MHz), VHT mode for 20 MHz (40 MHz), 802.11ax mode for 20 MHz (40 MHz) and 802.11be mode for 20 MHz (40 MHz). Therefore the investigated worst case is the representative mode in test report.

3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20), VHT20, 802.11ax (HE20), 802.11be (EHT20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40), VHT40, 802.11ax (HE40), 802.11be (EHT40):

Channel	Frequency	Channel	Frequency
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. The AC Adapter has the following models: AC Adapter 1 (MASS power)/ AC Adapter 2 (MOSO). Pre-scan these models of AC Adapters and find the worst case as a representative test condition. 2. Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
Worst Case:	1. AC Adapter worst condition: AC Adapter 2 (MOSO)

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g		1, 6, 11	BPSK	6Mb/s
	VHT20	CDD & Beamforming	1, 6, 11	BPSK	MCS0
	VHT40		3, 6, 9	BPSK	MCS0
	802.11be (EHT20)		1, 6, 11	BPSK	MCS0
	802.11be (EHT40)		3, 6, 9	BPSK	MCS0
Power Spectral Density	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g		1, 6, 11	BPSK	6Mb/s
	802.11be (EHT20)		1, 6, 11	BPSK	MCS0
	802.11be (EHT40)		3, 6, 9	BPSK	MCS0
6 dB Bandwidth / Conducted Out of Band Emissions	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g		1, 6, 11	BPSK	6Mb/s
	802.11be (EHT20)		1, 6, 11	BPSK	MCS0
	802.11be (EHT40)		3, 6, 9	BPSK	MCS0
AC Power Conducted Emissions	802.11b	CDD	6	DBPSK	1Mb/s
Unwanted Emissions below 1 GHz	802.11b	CDD	6	DBPSK	1Mb/s
Unwanted Emissions above 1 GHz	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g		1, 6, 11	BPSK	6Mb/s
	802.11be (EHT20)		1, 6, 11	BPSK	MCS0
	802.11be (EHT40)		3, 6, 9	BPSK	MCS0

Note: Partial RU (resource unit) mechanism is not supported.

3.5 Duty Cycle of Test Signal

802.11b: Duty cycle = 8.388 ms / 8.457 ms x 100% = 99.2%


802.11g: Duty cycle = 2.733 ms / 2.784 ms x 100% = 98.2%

VHT20: Duty cycle = 4.645 ms / 4.695 ms x 100% = 98.9%


VHT40: Duty cycle = 4.534 ms / 4.592 ms x 100% = 98.7%

802.11be (EHT20): Duty cycle = 4.645 ms / 4.695 ms x 100% = 98.9%

802.11be (EHT40): Duty cycle = 4.534 ms / 4.592 ms x 100% = 98.7%




Duty Cycle Analysis




VHT20

Duty Cycle Analysis




VHT40

Duty Cycle Analysis




802.11be (EHT20)



3.6 Test Program Used and Operation Descriptions

Controlling software (QATool_20240327_External (MT7992 V0.0.2.106)) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Laptop	DELL	E6420	H62T3R1	DoC	Provided by Lab
B	SWITCH	D-Link	DGS-1005D	DR8WC92000523	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1.8	No	0	Supplied by applicant
2	RJ-45 Cable	1	2	No	0	Supplied by applicant
3	RJ-45 Cable	1	10	No	0	Provided by Lab
4	RJ-45 Cable	1	10	No	0	Provided by Lab

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-20	00800A1K01A-20-02	2025/5/23	2026/5/22
Pulse Power Sensor Anritsu	MA2411B	1726434	2025/5/28	2026/5/27
RF Power Meter Anritsu	ML2495A	1529002	2024/6/7	2025/6/6

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2025/6/2

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2025/5/23	2026/5/22
PXA Signal Analyzer Keysight	N9030A	MY55410176	2024/6/12	2025/6/11
Software	ADT_RF Test Software V8	N/A	N/A	N/A

Notes:

1. The test was performed in Oven room 2.
2. Tested Date: 2025/6/2

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance Telegartner	50 ohm	3	2024/11/1	2025/10/31
EMI Test Receiver R&S	ESCS 30	100375	2025/5/21	2026/5/20
Fixed Attenuator STI	STI02-2200-10	005	2025/2/17	2026/2/16
LISN R&S	ESH3-Z5	835239/001	2025/3/27	2026/3/26
		848773/004	2024/10/7	2025/10/6
RF Coaxial Cable JYEBAO	5D-FB	COCCAB-001	2025/2/17	2026/2/16
Software BVADT	BVADT_Cond_V7.3.7.4	N/A	N/A	N/A

Notes:

1. The test was performed in Conduction 1
2. Tested Date: 2025/5/26 ~ 2025/5/27

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-0842	2024/10/8	2025/10/7
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2025/3/25	2026/3/24
Fixed Attenuator Mini-Circuits	UNAT-5+	PAD-ATT5-02	2025/3/29	2026/3/28
Loop Antenna TESEQ	HLA 6121	63620	2024/10/17	2025/10/16
Preamplifier EMCI	EMC330N	980538	2025/3/29	2026/3/28
	EMC001340	980142	2025/2/17	2026/2/16
PXA Signal Analyzer Keysight	N9030B	MY57141948	2025/5/20	2026/5/19
RF Coaxial Cable PEWC	8D	966-5-1	2025/3/29	2026/3/28
		966-5-2	2025/3/29	2026/3/28
		966-5-3	2025/3/29	2026/3/28
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.
2. Tested Date: 2025/5/26

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Boresight Antenna Tower & Turn Table Max-Full	MF-7802BS	MF780208530	N/A	N/A
EMI Test Receiver R&S	ESR7	102026	2025/3/25	2026/3/24
Horn Antenna Schwarzbeck	BBHA 9120D	9120D-1819	2024/11/10	2025/11/9
	BBHA 9170	9170-739	2024/11/10	2025/11/9
Preamplifier EMCI	EMC12630SE	980509	2025/1/18	2026/1/17
	EMC184045SE	980387	2024/8/8	2025/8/7
PXA Signal Analyzer Keysight	N9030B	MY57141948	2024/5/20 2025/5/20	2025/5/19 2026/5/19
RF Coaxial Cable EMCI	EMC102-KM-KM-1200	160924	2025/1/24	2026/1/23
	EMC102-KM-KM-4000	200214	2025/1/24	2026/1/23
	EMC104-SM-SM-1500	180503	2025/3/8	2026/3/7
	EMC104-SM-SM-2000	180501	2025/3/8	2026/3/7
	EMC104-SM-SM-6000	180506	2025/3/8	2026/3/7
Software	ADT_Radiated_V8.7.08	N/A	N/A	N/A

Notes:

1. The test was performed in 966 Chamber No. 5.
2. Tested Date: 2025/5/12 ~ 2025/5/26

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less, for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 30 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup




6.1.2 Test Procedure

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




6.2.2 Test Procedure

- Measure the duty cycle (x).
- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to: 3 kHz.
- Set VBW $\geq 3 \times$ RBW.
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- Sweep time = auto couple.
- Do not use sweep triggering. Allow sweep to "free run".
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

Note: If Duty cycle < 98%, Add $10 \log (1/x)$, where x is the duty cycle measured in step (a), to the measured PSD to compute the average PSD during the actual transmission time.

6.3 6 dB Bandwidth

6.3.1 Test Setup




6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	26°C, 63% RH	Tested By:	Dolly Chung
--------------	----------------	---------------------------	--------------	------------	-------------

802.11b CDD

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	22.33	21.15	21.82	21.69	600.944	27.79	30	Pass
6	2437	23.61	22.89	23.36	23.17	848.413	29.29	30	Pass
11	2462	21.21	20.95	21.45	21.56	539.437	27.32	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11g CDD

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	18.76	17.99	18.43	18.55	279.39	24.46	30	Pass
6	2437	22.76	22.11	22.46	22.39	700.932	28.46	30	Pass
11	2462	18.98	18.69	19.17	19.21	319	25.04	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

VHT20

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	17.61	16.93	17.31	17.38	215.523	23.33	30	Pass
6	2437	21.66	20.92	21.24	21.40	541.233	27.33	30	Pass
11	2462	17.68	17.53	17.95	18.16	243.075	23.86	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

VHT40

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	17.87	17.15	17.74	17.79	232.662	23.67	30	Pass
6	2437	19.46	18.68	19.26	19.25	330.571	25.19	30	Pass
9	2452	17.97	16.98	17.43	17.59	225.296	23.53	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11be (EHT20)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	17.90	17.15	17.59	17.65	229.161	23.60	30	Pass
6	2437	21.95	21.13	21.49	21.63	572.868	27.58	30	Pass
11	2462	17.97	17.79	18.16	18.39	257.266	24.10	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11be (EHT40)

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.17	17.44	17.95	18.01	246.692	23.92	30	Pass
6	2437	19.69	18.94	19.41	19.50	347.876	25.41	30	Pass
9	2452	18.19	17.27	17.67	17.79	237.847	23.76	30	Pass

Notes:

1. Directional gain is the maximum gain of antennas.
2. The maximum gain is 3.6 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

VHT20 Beamforming

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	17.57	16.90	17.29	17.36	214.156	23.31	30	Pass
6	2437	21.62	20.88	21.20	21.37	536.587	27.30	30	Pass
11	2462	17.66	17.49	17.92	18.13	241.406	23.83	30	Pass

Notes:

1. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
2. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

VHT40 Beamforming

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	17.84	17.12	17.71	17.77	231.198	23.64	30	Pass
6	2437	19.43	18.65	19.23	19.21	328.104	25.16	30	Pass
9	2452	17.94	16.95	17.41	17.56	223.872	23.50	30	Pass

Notes:

1. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
2. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11be (EHT20) Beamforming

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
1	2412	17.87	17.12	17.57	17.62	227.715	23.57	30	Pass
6	2437	21.92	21.09	21.46	21.61	568.961	27.55	30	Pass
11	2462	17.95	17.77	18.13	18.35	255.619	24.08	30	Pass

Notes:

1. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
2. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

802.11be (EHT40) Beamforming

Chan.	Chan. Freq. (MHz)	Average Power (dBm)				Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3				
3	2422	18.14	17.41	17.92	17.99	245.138	23.89	30	Pass
6	2437	19.66	18.92	19.37	19.49	345.87	25.39	30	Pass
9	2452	18.15	17.24	17.65	17.75	236.056	23.73	30	Pass

Notes:

1. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
2. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	26°C, 63% RH	Tested By:	Dolly Chung
--------------	----------------	---------------------------	--------------	------------	-------------

802.11b CDD

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)				Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3			
1	2412	-9.81	-9.37	-9.89	-9.84	-3.70	8	Pass
6	2437	-8.39	-8.62	-8.39	-8.64	-2.49	8	Pass
11	2462	-9.87	-9.96	-9.55	-10.01	-3.82	8	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
3. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

802.11g CDD

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)				Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3			
1	2412	-16.32	-16.34	-16.41	-16.19	-10.29	8	Pass
6	2437	-12.55	-12.73	-12.39	-12.12	-6.42	8	Pass
11	2462	-14.81	-15.49	-15.39	-15.47	-9.26	8	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
3. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

802.11be (EHT20) CDD

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)				Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3			
1	2412	-17.80	-17.72	-17.88	-17.73	-11.76	8	Pass
6	2437	-13.77	-13.64	-13.65	-13.31	-7.57	8	Pass
11	2462	-16.94	-16.90	-16.93	-16.58	-10.81	8	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
3. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.


802.11be (EHT40) CDD

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)				Total PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3			
3	2422	-20.34	-20.16	-20.60	-19.81	-14.20	8	Pass
6	2437	-18.72	-18.68	-18.82	-18.20	-12.58	8	Pass
9	2452	-20.60	-20.57	-20.54	-20.13	-14.44	8	Pass

Notes:

1. Method E) 2) b) Measure and sum spectral maxima across the outputs of KDB 662911 is using for calculating total power density.
2. Directional gain is the measured value according to KDB 662911 D03 Method of MIMO Antenna Gain Measurement.
3. The directional gain is 5.13 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	26°C, 63% RH	Tested By:	Dolly Chung
--------------	----------------	---------------------------	--------------	------------	-------------

802.11b CDD

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	8.08	8.07	8.07	8.09	0.5	Pass
6	2437	8.10	9.02	8.57	9.07	0.5	Pass
11	2462	8.05	8.09	8.07	8.07	0.5	Pass

802.11g CDD

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	16.04	16.06	16.30	16.33	0.5	Pass
6	2437	16.03	16.29	16.31	16.30	0.5	Pass
11	2462	16.02	16.29	16.28	16.28	0.5	Pass


802.11be (EHT20) CDD

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
1	2412	18.68	18.83	18.74	18.88	0.5	Pass
6	2437	18.56	18.80	18.64	18.81	0.5	Pass
11	2462	18.50	18.67	18.57	18.84	0.5	Pass


802.11be (EHT40) CDD

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)				Minimum Limit (MHz)	Test Result
		Chain 0	Chain 1	Chain 2	Chain 3		
3	2422	36.64	37.26	35.97	35.85	0.5	Pass
6	2437	35.79	36.78	36.53	35.96	0.5	Pass
9	2452	35.19	36.58	35.96	35.55	0.5	Pass


Spectrum Plot of Minimum Value




802.11b CDD / Chain 0 : CH 11



802.11g CDD / Chain 0 : CH 11



802.11be (EHT20) CDD / Chain 0 : CH 11











802.11be (EHT40) CDD / Chain 0 : CH 9









7.4 Conducted Out of Band Emissions









Input Power:	120 Vac, 60 Hz	Environmental Conditions:	26°C, 63% RH	Tested By:	Dolly Chung
--------------	----------------	---------------------------	--------------	------------	-------------

802.11b









































802.11g

































802.11be (EHT20)

































802.11be (EHT40)










7.5 AC Power Conducted Emissions

RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Louis Yang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	10.01	32.44	19.73	42.45	29.74	64.98	54.98	-22.53	-25.24
2	0.26719	10.03	22.61	0.02	32.64	10.05	61.20	51.20	-28.56	-41.15
3	0.62656	10.06	29.40	18.08	39.46	28.14	56.00	46.00	-16.54	-17.86
4	1.81641	10.15	12.30	3.94	22.45	14.09	56.00	46.00	-33.55	-31.91
5	3.57422	10.27	10.97	1.74	21.24	12.01	56.00	46.00	-34.76	-33.99
6	18.24609	11.06	17.56	12.83	28.62	23.89	60.00	50.00	-31.38	-26.11

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Louis Yang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16953	10.02	34.33	26.27	44.35	36.29	64.98	54.98	-20.63	-18.69
2	0.25156	10.03	30.20	24.89	40.23	34.92	61.71	51.71	-21.48	-16.79
3	0.66172	10.05	40.40	29.84	50.45	39.89	56.00	46.00	-5.55	-6.11
4	0.98594	10.08	25.04	12.16	35.12	22.24	56.00	46.00	-20.88	-23.76
5	1.89453	10.13	25.70	13.31	35.83	23.44	56.00	46.00	-20.17	-22.56
6	5.43750	10.35	16.07	7.06	26.42	17.41	60.00	50.00	-33.58	-32.59

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 68% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.73	22.0 QP	40.0	-18.0	3.00 H	274	35.6	-13.6
2	115.82	26.0 QP	43.5	-17.5	3.00 H	113	40.9	-14.9
3	183.99	26.0 QP	43.5	-17.5	2.00 H	281	40.7	-14.7
4	388.80	29.8 QP	46.0	-16.2	1.00 H	270	39.0	-9.2
5	510.17	30.7 QP	46.0	-15.3	1.00 H	323	37.3	-6.6
6	628.59	31.3 QP	46.0	-14.7	1.50 H	182	35.1	-3.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 68% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	64.24	34.3 QP	40.0	-5.7	2.00 V	1	48.1	-13.8
2	115.94	21.4 QP	43.5	-22.1	1.50 V	176	36.3	-14.9
3	291.56	26.2 QP	46.0	-19.8	1.50 V	122	38.1	-11.9
4	510.15	32.3 QP	46.0	-13.7	1.00 V	122	38.9	-6.6
5	642.63	31.4 QP	46.0	-14.6	1.00 V	109	34.9	-3.5
6	744.57	35.1 QP	46.0	-10.9	3.00 V	228	37.2	-2.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	802.11b	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	2.45 H	154	60.0	-3.1
2	2390.00	49.5 AV	54.0	-4.5	2.45 H	154	52.6	-3.1
3	*2412.00	115.2 PK			2.45 H	154	118.4	-3.2
4	*2412.00	111.8 AV			2.45 H	154	115.0	-3.2
5	4824.00	48.6 PK	74.0	-25.4	2.62 H	168	46.6	2.0
6	4824.00	47.1 AV	54.0	-6.9	2.62 H	168	45.1	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.6 PK	74.0	-14.4	2.88 V	320	62.7	-3.1
2	2390.00	53.4 AV	54.0	-0.6	2.88 V	320	56.5	-3.1
3	*2412.00	117.6 PK			2.88 V	320	120.8	-3.2
4	*2412.00	112.3 AV			2.88 V	320	115.5	-3.2
5	4824.00	44.8 PK	74.0	-29.2	1.45 V	57	42.8	2.0
6	4824.00	40.5 AV	54.0	-13.5	1.45 V	57	38.5	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.6 PK	74.0	-18.4	2.38 H	154	58.7	-3.1
2	2390.00	45.4 AV	54.0	-8.6	2.38 H	154	48.5	-3.1
3	*2437.00	115.8 PK			2.38 H	154	119.1	-3.3
4	*2437.00	112.0 AV			2.38 H	154	115.3	-3.3
5	2483.50	58.3 PK	74.0	-15.7	2.38 H	154	61.4	-3.1
6	2483.50	50.8 AV	54.0	-3.2	2.38 H	154	53.9	-3.1
7	4874.00	48.7 PK	74.0	-25.3	2.68 H	166	46.7	2.0
8	4874.00	46.9 AV	54.0	-7.1	2.68 H	166	44.9	2.0
9	7311.00	54.4 PK	74.0	-19.6	1.89 H	270	46.9	7.5
10	7311.00	50.5 AV	54.0	-3.5	1.89 H	270	43.0	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.6 PK	74.0	-17.4	2.62 V	319	59.7	-3.1
2	2390.00	47.1 AV	54.0	-6.9	2.62 V	319	50.2	-3.1
3	*2437.00	118.1 PK			2.62 V	319	121.4	-3.3
4	*2437.00	112.8 AV			2.62 V	319	116.1	-3.3
5	2483.50	58.0 PK	74.0	-16.0	2.62 V	319	61.1	-3.1
6	2483.50	52.3 AV	54.0	-1.7	2.62 V	319	55.4	-3.1
7	4874.00	44.5 PK	74.0	-29.5	1.50 V	60	42.5	2.0
8	4874.00	40.2 AV	54.0	-13.8	1.50 V	60	38.2	2.0
9	7311.00	45.5 PK	74.0	-28.5	3.06 V	284	38.0	7.5
10	7311.00	37.2 AV	54.0	-16.8	3.06 V	284	29.7	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11b	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	112.4 PK			2.98 H	284	115.5	-3.1
2	*2462.00	109.9 AV			2.98 H	284	113.0	-3.1
3	2483.50	58.8 PK	74.0	-15.2	2.98 H	284	61.9	-3.1
4	2483.50	51.8 AV	54.0	-2.2	2.98 H	284	54.9	-3.1
5	4924.00	48.8 PK	74.0	-25.2	2.68 H	158	46.7	2.1
6	4924.00	47.0 AV	54.0	-7.0	2.68 H	158	44.9	2.1
7	7386.00	54.4 PK	74.0	-19.6	1.94 H	277	46.9	7.5
8	7386.00	50.8 AV	54.0	-3.2	1.94 H	277	43.3	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	113.7 PK			2.17 V	316	116.8	-3.1
2	*2462.00	112.6 AV			2.17 V	316	115.7	-3.1
3	2483.50	57.8 PK	74.0	-16.2	2.17 V	316	60.9	-3.1
4	2483.50	53.5 AV	54.0	-0.5	2.17 V	316	56.6	-3.1
5	4924.00	44.1 PK	74.0	-29.9	1.48 V	72	42.0	2.1
6	4924.00	39.8 AV	54.0	-14.2	1.48 V	72	37.7	2.1
7	7386.00	45.6 PK	74.0	-28.4	3.08 V	272	38.1	7.5
8	7386.00	37.4 AV	54.0	-16.6	3.08 V	272	29.9	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	68.8 PK	74.0	-5.2	1.51 H	339	71.9	-3.1
2	2390.00	46.1 AV	54.0	-7.9	1.51 H	339	49.2	-3.1
3	*2412.00	112.9 PK			1.51 H	339	116.1	-3.2
4	*2412.00	102.4 AV			1.51 H	339	105.6	-3.2
5	4824.00	48.3 PK	74.0	-25.7	2.65 H	170	46.3	2.0
6	4824.00	46.7 AV	54.0	-7.3	2.65 H	170	44.7	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	73.8 PK	74.0	-0.2	1.51 V	132	76.9	-3.1
2	2390.00	52.7 AV	54.0	-1.3	1.51 V	132	55.8	-3.1
3	*2412.00	115.4 PK			1.51 V	132	118.6	-3.2
4	*2412.00	105.1 AV			1.51 V	132	108.3	-3.2
5	4824.00	44.4 PK	74.0	-29.6	1.46 V	67	42.4	2.0
6	4824.00	40.3 AV	54.0	-13.7	1.46 V	67	38.3	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.0 PK	74.0	-5.0	1.74 H	153	72.1	-3.1
2	2390.00	48.4 AV	54.0	-5.6	1.74 H	153	51.5	-3.1
3	*2437.00	117.6 PK			1.74 H	153	120.9	-3.3
4	*2437.00	107.0 AV			1.74 H	153	110.3	-3.3
5	2483.50	68.0 PK	74.0	-6.0	1.74 H	153	71.1	-3.1
6	2483.50	51.3 AV	54.0	-2.7	1.74 H	153	54.4	-3.1
7	4874.00	48.2 PK	74.0	-25.8	2.73 H	179	46.2	2.0
8	4874.00	46.4 AV	54.0	-7.6	2.73 H	179	44.4	2.0
9	7311.00	54.5 PK	74.0	-19.5	1.84 H	263	47.0	7.5
10	7311.00	50.7 AV	54.0	-3.3	1.84 H	263	43.2	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	71.6 PK	74.0	-2.4	1.52 V	127	74.7	-3.1
2	2390.00	51.3 AV	54.0	-2.7	1.52 V	127	54.4	-3.1
3	*2437.00	119.4 PK			1.52 V	127	122.7	-3.3
4	*2437.00	108.7 AV			1.52 V	127	112.0	-3.3
5	2483.50	71.8 PK	74.0	-2.2	1.52 V	127	74.9	-3.1
6	2483.50	53.1 AV	54.0	-0.9	1.52 V	127	56.2	-3.1
7	4874.00	44.5 PK	74.0	-29.5	1.49 V	76	42.5	2.0
8	4874.00	40.5 AV	54.0	-13.5	1.49 V	76	38.5	2.0
9	7311.00	45.3 PK	74.0	-28.7	3.02 V	280	37.8	7.5
10	7311.00	37.1 AV	54.0	-16.9	3.02 V	280	29.6	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11g	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	114.9 PK			1.00 H	346	118.0	-3.1
2	*2462.00	106.4 AV			1.00 H	346	109.5	-3.1
3	2483.50	69.2 PK	74.0	-4.8	1.00 H	346	72.3	-3.1
4	2483.50	49.8 AV	54.0	-4.2	1.00 H	346	52.9	-3.1
5	4924.00	48.2 PK	74.0	-25.8	2.63 H	166	46.1	2.1
6	4924.00	46.5 AV	54.0	-7.5	2.63 H	166	44.4	2.1
7	7386.00	54.3 PK	74.0	-19.7	1.87 H	254	46.8	7.5
8	7386.00	50.2 AV	54.0	-3.8	1.87 H	254	42.7	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	117.3 PK			2.20 V	317	120.4	-3.1
2	*2462.00	107.7 AV			2.20 V	317	110.8	-3.1
3	2483.50	73.2 PK	74.0	-0.8	2.20 V	317	76.3	-3.1
4	2483.50	52.4 AV	54.0	-1.6	2.20 V	317	55.5	-3.1
5	4924.00	44.8 PK	74.0	-29.2	1.50 V	48	42.7	2.1
6	4924.00	40.5 AV	54.0	-13.5	1.50 V	48	38.4	2.1
7	7386.00	45.8 PK	74.0	-28.2	3.10 V	283	38.3	7.5
8	7386.00	37.6 AV	54.0	-16.4	3.10 V	283	30.1	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	68.1 PK	74.0	-5.9	1.56 H	297	71.2	-3.1
2	2390.00	46.1 AV	54.0	-7.9	1.56 H	297	49.2	-3.1
3	*2412.00	114.2 PK			1.56 H	297	117.4	-3.2
4	*2412.00	102.8 AV			1.56 H	297	106.0	-3.2
5	4824.00	48.7 PK	74.0	-25.3	2.67 H	152	46.7	2.0
6	4824.00	46.7 AV	54.0	-7.3	2.67 H	152	44.7	2.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	73.6 PK	74.0	-0.4	1.51 V	131	76.7	-3.1
2	2390.00	48.0 AV	54.0	-6.0	1.51 V	131	51.1	-3.1
3	*2412.00	116.5 PK			1.51 V	131	119.7	-3.2
4	*2412.00	104.5 AV			1.51 V	131	107.7	-3.2
5	4824.00	45.4 PK	74.0	-28.6	1.45 V	36	43.4	2.0
6	4824.00	40.8 AV	54.0	-13.2	1.45 V	36	38.8	2.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.7 PK	74.0	-9.3	1.31 H	296	67.8	-3.1
2	2390.00	46.9 AV	54.0	-7.1	1.31 H	296	50.0	-3.1
3	*2437.00	117.5 PK			1.31 H	296	120.8	-3.3
4	*2437.00	105.8 AV			1.31 H	296	109.1	-3.3
5	2483.50	67.2 PK	74.0	-6.8	1.31 H	296	70.3	-3.1
6	2483.50	49.4 AV	54.0	-4.6	1.31 H	296	52.5	-3.1
7	4874.00	48.5 PK	74.0	-25.5	2.66 H	151	46.5	2.0
8	4874.00	46.9 AV	54.0	-7.1	2.66 H	151	44.9	2.0
9	7311.00	54.9 PK	74.0	-19.1	1.94 H	280	47.4	7.5
10	7311.00	50.9 AV	54.0	-3.1	1.94 H	280	43.4	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	70.6 PK	74.0	-3.4	1.51 V	131	73.7	-3.1
2	2390.00	50.4 AV	54.0	-3.6	1.51 V	131	53.5	-3.1
3	*2437.00	120.2 PK			1.51 V	131	123.5	-3.3
4	*2437.00	109.1 AV			1.51 V	131	112.4	-3.3
5	2483.50	70.4 PK	74.0	-3.6	1.51 V	131	73.5	-3.1
6	2483.50	51.9 AV	54.0	-2.1	1.51 V	131	55.0	-3.1
7	4874.00	44.8 PK	74.0	-29.2	1.55 V	58	42.8	2.0
8	4874.00	40.2 AV	54.0	-13.8	1.55 V	58	38.2	2.0
9	7311.00	45.3 PK	74.0	-28.7	3.06 V	282	37.8	7.5
10	7311.00	37.3 AV	54.0	-16.7	3.06 V	282	29.8	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT20)	Channel	CH 11 : 2462 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	114.9 PK			2.72 H	296	118.0	-3.1
2	*2462.00	103.6 AV			2.72 H	296	106.7	-3.1
3	2483.50	70.6 PK	74.0	-3.4	2.72 H	296	73.7	-3.1
4	2483.50	49.2 AV	54.0	-4.8	2.72 H	296	52.3	-3.1
5	4924.00	49.0 PK	74.0	-25.0	2.64 H	164	46.9	2.1
6	4924.00	46.8 AV	54.0	-7.2	2.64 H	164	44.7	2.1
7	7386.00	54.0 PK	74.0	-20.0	1.93 H	273	46.5	7.5
8	7386.00	50.3 AV	54.0	-3.7	1.93 H	273	42.8	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	117.3 PK			1.48 V	131	120.4	-3.1
2	*2462.00	105.4 AV			1.48 V	131	108.5	-3.1
3	2483.50	72.8 PK	74.0	-1.2	1.48 V	131	75.9	-3.1
4	2483.50	53.4 AV	54.0	-0.6	1.48 V	131	56.5	-3.1
5	4924.00	45.0 PK	74.0	-29.0	1.47 V	57	42.9	2.1
6	4924.00	40.8 AV	54.0	-13.2	1.47 V	57	38.7	2.1
7	7386.00	45.4 PK	74.0	-28.6	3.13 V	267	37.9	7.5
8	7386.00	37.2 AV	54.0	-16.8	3.13 V	267	29.7	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT40)	Channel	CH 3 : 2422 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.8 PK	74.0	-10.2	1.78 H	299	66.9	-3.1
2	2390.00	47.6 AV	54.0	-6.4	1.78 H	299	50.7	-3.1
3	*2422.00	111.0 PK			1.78 H	299	114.2	-3.2
4	*2422.00	99.5 AV			1.78 H	299	102.7	-3.2
5	4844.00	48.4 PK	74.0	-25.6	2.64 H	167	46.4	2.0
6	4844.00	46.5 AV	54.0	-7.5	2.64 H	167	44.5	2.0
7	7266.00	54.2 PK	74.0	-19.8	1.89 H	279	46.5	7.7
8	7266.00	50.5 AV	54.0	-3.5	1.89 H	279	42.8	7.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	72.6 PK	74.0	-1.4	1.51 V	128	75.7	-3.1
2	2390.00	52.8 AV	54.0	-1.2	1.51 V	128	55.9	-3.1
3	*2422.00	116.1 PK			1.51 V	128	119.3	-3.2
4	*2422.00	103.1 AV			1.51 V	128	106.3	-3.2
5	4844.00	44.6 PK	74.0	-29.4	1.54 V	51	42.6	2.0
6	4844.00	40.1 AV	54.0	-13.9	1.54 V	51	38.1	2.0
7	7266.00	45.2 PK	74.0	-28.8	3.10 V	298	37.5	7.7
8	7266.00	37.3 AV	54.0	-16.7	3.10 V	298	29.6	7.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT40)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.1 PK	74.0	-13.9	2.80 H	293	63.2	-3.1
2	2390.00	45.5 AV	54.0	-8.5	2.80 H	293	48.6	-3.1
3	*2437.00	111.4 PK			2.80 H	293	114.7	-3.3
4	*2437.00	100.3 AV			2.80 H	293	103.6	-3.3
5	2483.50	60.8 PK	74.0	-13.2	2.80 H	293	63.9	-3.1
6	2483.50	47.2 AV	54.0	-6.8	2.80 H	293	50.3	-3.1
7	4874.00	48.8 PK	74.0	-25.2	2.70 H	146	46.8	2.0
8	4874.00	46.8 AV	54.0	-7.2	2.70 H	146	44.8	2.0
9	7311.00	55.1 PK	74.0	-18.9	1.92 H	289	47.6	7.5
10	7311.00	50.9 AV	54.0	-3.1	1.92 H	289	43.4	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.9 PK	74.0	-4.1	3.53 V	328	73.0	-3.1
2	2390.00	53.2 AV	54.0	-0.8	3.53 V	328	56.3	-3.1
3	*2437.00	119.4 PK			3.53 V	328	122.7	-3.3
4	*2437.00	106.5 AV			3.53 V	328	109.8	-3.3
5	2483.50	70.9 PK	74.0	-3.1	3.53 V	328	74.0	-3.1
6	2483.50	52.8 AV	54.0	-1.2	3.53 V	328	55.9	-3.1
7	4874.00	45.0 PK	74.0	-29.0	1.49 V	46	43.0	2.0
8	4874.00	40.6 AV	54.0	-13.4	1.49 V	46	38.6	2.0
9	7311.00	45.7 PK	74.0	-28.3	3.15 V	279	38.2	7.5
10	7311.00	37.7 AV	54.0	-16.3	3.15 V	279	30.2	7.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	802.11be (EHT40)	Channel	CH 9 : 2452 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	26 °C, 72% RH
Tested By	Louis Yang		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	111.9 PK			2.70 H	295	115.0	-3.1
2	*2452.00	100.0 AV			2.70 H	295	103.1	-3.1
3	2483.50	66.4 PK	74.0	-7.6	2.70 H	295	69.5	-3.1
4	2483.50	52.5 AV	54.0	-1.5	2.70 H	295	55.6	-3.1
5	4904.00	48.4 PK	74.0	-25.6	2.62 H	161	46.3	2.1
6	4904.00	46.5 AV	54.0	-7.5	2.62 H	161	44.4	2.1
7	7356.00	55.1 PK	74.0	-18.9	1.97 H	281	47.6	7.5
8	7356.00	51.0 AV	54.0	-3.0	1.97 H	281	43.5	7.5
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	115.5 PK			1.11 V	127	118.6	-3.1
2	*2452.00	103.1 AV			1.11 V	127	106.2	-3.1
3	2483.50	71.9 PK	74.0	-2.1	1.11 V	127	75.0	-3.1
4	2483.50	52.6 AV	54.0	-1.4	1.11 V	127	55.7	-3.1
5	4904.00	44.8 PK	74.0	-29.2	1.50 V	60	42.7	2.1
6	4904.00	40.5 AV	54.0	-13.5	1.50 V	60	38.4	2.1
7	7356.00	45.5 PK	74.0	-28.5	3.08 V	275	38.0	7.5
8	7356.00	37.2 AV	54.0	-16.8	3.08 V	275	29.7	7.5


Remarks:


1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

Plot of Band Edge


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--

802.11b Channel 1




802.11b Channel 11


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11g Channel 1




802.11g Channel 11




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11be (EHT20) Channel 1




Horizontal (Peak)




Horizontal (Average)




Vertical (Peak)




Vertical (Average)

802.11be (EHT20) Channel 11


Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--


802.11be (EHT40) Channel 3




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


802.11be (EHT40) Channel 9




Horizontal (Peak)



Horizontal (Average)



Vertical (Peak)



Vertical (Average)

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---