

## APPLICATION FOR CERTIFICATION

On Behalf of

Tsann Kuen Enterprise Co., Ltd.

Microwave Oven

Model : (1)TSK-M3204ME (2)TSK-M3204MEQ

FCC ID : RBJ-TSKM320X

Prepared for : Tsann Kuen Enterprise Co., Ltd.  
3, Kai Fa 2<sup>nd</sup> Road, Pao An Industrial District,  
Ren Teh Hsiang, Tainan, Taiwan

Prepared By : Audix Corporation  
Technical Division EMC Department  
No. 53-11, Tin-Fu Tsun, Lin-Kou,  
Taipei County, Taiwan, R.O.C.

Tel : (02) 2609-9301, 2609-2133

Fax : (02) 2609-9303

File Number : EM950955  
Report Number : EM-F950299  
Date of Test : Jul. 07 ~ 28, 2006  
Date of Report : Aug. 03, 2006

# TABLE OF CONTENTS

| Description                                                                    | Page |
|--------------------------------------------------------------------------------|------|
| TEST REPORT CERTIFICATION .....                                                | 3    |
| 1.GENERAL INFORMATION .....                                                    | 4    |
| 1.1.Description of Device (EUT).....                                           | 4    |
| 1.2.Description of Test Facility .....                                         | 5    |
| 1.3.Measurement Uncertainty .....                                              | 5    |
| 2.INPUT POWER MEASUREMENT .....                                                | 6    |
| 2.1.Test Equipment.....                                                        | 6    |
| 2.2.Test Setup .....                                                           | 6    |
| 2.3.Operating Condition of EUT and Measurement Procedure.....                  | 6    |
| 2.4.Measurement Results.....                                                   | 6    |
| 3.OUTPUT POWER MEASUREMENT .....                                               | 7    |
| 3.1.Test Equipment.....                                                        | 7    |
| 3.2.Test Setup .....                                                           | 7    |
| 3.3.Operating Condition of EUT and Measurement Procedure.....                  | 7    |
| 3.4.Measurement Results.....                                                   | 7    |
| 4.OUTPUT FREQUENCY MEASUREMENT .....                                           | 9    |
| 4.1.Test Equipment.....                                                        | 9    |
| 4.2.Test Setup .....                                                           | 9    |
| 4.3.Operating Condition of EUT and Measurement Procedure.....                  | 9    |
| 4.4.Measurement Results.....                                                   | 10   |
| 5.FREQUENCY MEASUREMENT .....                                                  | 11   |
| 5.1.Test Equipment.....                                                        | 11   |
| 5.2.Test Setup .....                                                           | 11   |
| 5.3.Operating Condition of EUT and Measurement Procedure.....                  | 11   |
| 5.4.Measurement Results.....                                                   | 12   |
| 6.CONDUCTED EMISSION MEASUREMENT.....                                          | 20   |
| 6.1.Test Equipment.....                                                        | 20   |
| 6.2.Test Setup .....                                                           | 20   |
| 6.3.Conduction Limits [18.307(b)] .....                                        | 20   |
| 6.4.Operating Condition of EUT .....                                           | 21   |
| 6.5.Test Procedure .....                                                       | 21   |
| 6.6.Conducted Emission Measurement Results.....                                | 21   |
| 7.RADIATED EMISSION MEASUREMENT .....                                          | 44   |
| 7.1.Test Equipment.....                                                        | 44   |
| 7.2.Test Setup .....                                                           | 44   |
| 7.3.Radiation Limits .....                                                     | 45   |
| 7.4.Operating Condition of EUT .....                                           | 45   |
| 7.5.Test Procedure .....                                                       | 45   |
| 7.6.Radiated Emission Measurement Results.....                                 | 46   |
| 8.DEVIATION TO TEST SPECIFICATIONS .....                                       | 102  |
| 9.PHOTOGRAPHS .....                                                            | 103  |
| 9.1.Photo of Input Power Measurement .....                                     | 103  |
| 9.2.Photo of Output Frequency Measurement.....                                 | 104  |
| 9.3.Photo of Frequency Measurement .....                                       | 105  |
| 9.4.Photos of Conducted Emission Measurement .....                             | 106  |
| 9.5.Photos of Radiated Measurement at Semi-Anechoic Chamber (Below 1GHz) ..... | 108  |
| 9.6.Photos of Radiated Measurement at Semi-Anechoic Chamber (Above 1GHz) ..... | 110  |

## TEST REPORT CERTIFICATION

Applicant : Tsann Kuen Enterprise Co., Ltd.  
Manufacturer : Tsann Kuen (Zhangzhou) Enterprise Co., Ltd.  
EUT Description : Microwave Oven  
FCC ID : RBJ-TSKM320X  
(A) MODEL NO. : (1)TSK-M3204ME  
(2)TSK-M3204MEQ  
(B) SERIAL NO. : N/A  
(C) POWER SUPPLY : AC 120V, 60Hz

Measurement Procedure Used:

FCC RULES AND REGULATIONS PART 18 SUBPART C, OCT 2005  
AND FCC/OST MP-5 FEBRUARY 1986

The device described above was tested by Audix Corporation to determine the maximum emission levels emanating from the device. The maximum emission levels were compared to the FCC Part 18 subpart C limits both radiated and conducted emissions.

The measurement results are contained in this test report and Audix Corporation is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliant with the FCC official limits.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of Audix Corporation.

Date of Test : Jul. 07 ~ 28, 2006

Prepared by : Nita Lee Aug. 03, 2006  
(Nita Lee/Assistant Administrator)

Test Engineer : Ben Cheng Aug. 03, 2006  
(Ben Cheng/Section Manager)

Approved & Authorized Signer : Leon Liu Aug. 3 2006  
(Leon Liu/Senior Manager)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

Description : Microwave Oven

Model Number : (1)TSK-M3204ME (2)TSK-M3204MEQ  
The difference in above models are in PCB layout and function.

| Model Number | TSK-M3204ME | TSK-M3204MEQ     |
|--------------|-------------|------------------|
| Function     | Microwave   | Microwave+ Grill |

All models are representative selected and tested in this report.

FCC ID : RBJ-TSKM320X

Applicant : Tsann Kuen Enterprise Co., Ltd.  
3, Kai Fa 2<sup>nd</sup> Road, Pao An Industrial District,  
Ren Teh Hsiang, Tainan, Taiwan

Manufacturer : Tsann Kuen (Zhangzhou) Enterprise Co., Ltd.  
Tsann Kuen Industrial Park, Longchi  
Development District, Zhangzhou, Fujian,  
363000, P.R. China

Magnetron : Witol, Type No. 2M319K

H.V. Transformer : YLEC, Type No. YL-R101ACKA-1

Fan Motor : Heng Cheng, Type YJF62A-120(07)

Frequency : 2450MHz

Power Supply : AC 120V, 60Hz

Rated Current : 15A

Microwave Output : 1000W

Grill Output : 1300W (Only M/N TSK-M3204MEQ)

Rated Power Consumption : 1550W

Power Cord : Non-Shielded, Undetachable, 1.1m (3-Pin)

Date of Receipt of Sample : Jul. 05, 2006

Date of Test : Jul. 07 ~ 28, 2006

## 1.2. Description of Test Facility

Name of Firm : **Audix Corporation**  
**Technical Division EMC Department**  
 No. 53-11, Tin-Fu Tsun, Lin-Kou Hsiang,  
 Taipei County, Taiwan, R.O.C.

Test Site : **No. 2 Shielded Room**  
 (C2/AC) No. 53-11, Tin-Fu Tsun, Lin-Kou Hsiang,  
 Taipei County, Taiwan, R.O.C.

**Semi-Anechoic Chamber**  
 Federal Communication Commission  
 Registration Number: 90993  
 Filing on May 16, 2003  
 No. 53-11, Tin-Fu Tsun, Lin-Kou,  
 Taipei County, Taiwan, R.O.C.

NVLAP Lab. Code : 200077-0  
 (NVLAP is a NATA accredited body under Mutual Recognition Agreement)

DAR-Registration No. : DAT-P-145/03-01

## 1.3. Measurement Uncertainty

| Test Item                        | Frequency Range | Uncertainty (dB) |
|----------------------------------|-----------------|------------------|
| Conduction Test                  | 150kHz~30MHz    | ±1.73dB          |
| Radiation Test<br>(Distance: 3m) | 30MHz~300MHz    | ±2.91dB          |
|                                  | 300MHz~1000MHz  | ±2.94dB          |

Remark : Uncertainty =  $ku_c(y)$

## 2. INPUT POWER MEASUREMENT

### 2.1. Test Equipment

The following test equipment was used during the input power measurement :

| Item | Type                     | Manufacturer | Model No. | Serial No. | Last Cal.   | Next Cal.   |
|------|--------------------------|--------------|-----------|------------|-------------|-------------|
| 1.   | Universal Power Analyzer | Voltech      | PM3000A   | AL109/9072 | May 16, 06' | May 15, 07' |

### 2.2. Test Setup

#### 2.2.1. Block Diagram of connection between EUT and simulators

**MICROWAVE OVEN (EUT)**

#### 2.2.2. Block Diagram of connection between EUT and test equipment



### 2.3. Operating Condition of EUT and Measurement Procedure

The input power was measured using a universal power analyzer. 700 milliliters of water in the beaker was placed in the center of the Microwave Oven (EUT). The Microwave Oven (EUT) was operated at the rated input and full output power for 6 minutes.

### 2.4. Measurement Results

EUT : Microwave Oven                      M/N : TSK-M3204ME  
 Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%

Load : 700ml

| Measured Input |             |                 | Manufacturer's Input |                 |
|----------------|-------------|-----------------|----------------------|-----------------|
| Voltage (Vac)  | Current (A) | Input Power (W) | Current (A)          | Input Power (W) |
| 120            | 13.5        | 1514            | 15A                  | 1550W           |

EUT : Microwave Oven                      M/N : TSK-M3204MEQ  
 Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%

Load : 700ml

| Measured Input |             |                 | Manufacturer's Input |                 |
|----------------|-------------|-----------------|----------------------|-----------------|
| Voltage (Vac)  | Current (A) | Input Power (W) | Current (A)          | Input Power (W) |
| 120            | 13.3        | 1462            | 15A                  | 1550W           |

### 3. OUTPUT POWER MEASUREMENT

#### 3.1. Test Equipment

None.

#### 3.2. Test Setup

**MICROWAVE OVEN (EUT)**

#### 3.3. Operating Condition of EUT and Measurement Procedure

The Calorimetric Method was used to determine maximum output power. 1000 milliliters of water in the beaker was placed in the center of the Microwave Oven (EUT). A mercury thermometer was used to measure temperature rise.

#### 3.4. Measurement Results

EUT : Microwave Oven

M/N : TSK-M3204ME

Test Date : Jul. 27, 2006      Temperature : 22°C      Humidity : 41%

Load : 1000ml

Manufacture's Output : 1000W

| Load   | Initial Water Temperature °C | Final Water Temperature °C | Heating Duration (Sec.) |
|--------|------------------------------|----------------------------|-------------------------|
| 1000ml | 17 °C                        | 35.5 °C                    | 120                     |

$$\text{Power [W]} = \frac{4.2 (\text{Joules/Cal}) \times \text{Volume in ml} \times \text{Temperature Rise}}{\text{Time in Seconds}}$$

$$\text{Power [W]} = \frac{4.2 \times 1000 \times 18.5}{120} = 647.5\text{W}$$

EUT : Microwave Oven

M/N : TSK-M3204MEQ

Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%

Load : 1000ml

Manufacture's Output : 1000W

| Load   | Initial Water Temperature °C | Final Water Temperature °C | Heating Duration (Sec.) |
|--------|------------------------------|----------------------------|-------------------------|
| 1000ml | 16 °C                        | 37.5 °C                    | 120                     |

$$\text{Power [W]} = \frac{4.2 \text{ (Joules/Cal)} \times \text{Volume in ml} \times \text{Temperature Rise}}{\text{Time in Seconds}}$$

$$\text{Power [W]} = \frac{4.2 \times 1000 \times 21.5}{120} = 752.5\text{W}$$

## 4. OUTPUT FREQUENCY MEASUREMENT

### 4.1. Test Equipment

The following test equipment was used during the input power measurement :


| Item | Type              | Manufacturer | Model No. | Serial No. | Last Cal.    | Next Cal.    |
|------|-------------------|--------------|-----------|------------|--------------|--------------|
| 1.   | Spectrum Analyzer | HP           | 8593EM    | 3826A00248 | Sep. 26, 05' | Sep. 25, 06' |
| 2.   | Horn Antenna      | EMCO         | 3115      | 9112-3775  | Jun. 01, 06' | May 31, 07'  |
| 3.   | Pre-Amplifier     | HP           | 8449B     | 3008A01284 | Jun. 30, 06' | Jun. 29, 07' |

### 4.2. Test Setup

#### 4.2.1. Block Diagram of connection between EUT and simulators



#### 4.2.2. Block Diagram of connection between EUT and test equipment



### 4.3. Operating Condition of EUT and Measurement Procedure

The fundamental frequency was measured using a spectrum analyzer. The Microwave Oven (EUT) was operated in “Power-High” mode and without load.

## 4.4. Measurement Results

EUT : Microwave Oven

M/N : TSK-M3204ME

Test Date : Jul. 25, 2006    Temperature : 22°C    Humidity : 41%

Load : No Load

| Measured Frequency (MHz) | Manufacture's Rated Frequency |
|--------------------------|-------------------------------|
| 2452.8                   | 2450                          |

EUT : Microwave Oven

M/N : TSK-M3204MEQ

Test Date : Jul. 25, 2006    Temperature : 22°C    Humidity : 41%

Load : No Load

| Measured Frequency (MHz) | Manufacture's Rated Frequency |
|--------------------------|-------------------------------|
| 2472.4                   | 2450                          |

## 5. FREQUENCY MEASUREMENT

### 5.1. Test Equipment

The following test equipment was used during the input power measurement :


| Item | Type              | Manufacturer | Model No. | Serial No. | Last Cal.    | Next Cal.    |
|------|-------------------|--------------|-----------|------------|--------------|--------------|
| 1.   | Spectrum Analyzer | HP           | 8593EM    | 3826A00248 | Sep. 26, 05' | Sep. 25, 06' |
| 2.   | Horn Antenna      | EMCO         | 3115      | 9112-3775  | Jun. 01, 06' | May 31, 07'  |
| 3.   | Pre-Amplifier     | HP           | 8447D     | 2944A06305 | Mar. 09, 06' | Mar. 08, 07' |

### 5.2. Test Setup

#### 5.2.1. Block Diagram of connection between EUT and simulators



#### 5.2.2. Block Diagram of connection between EUT and test equipment



### 5.3. Operating Condition of EUT and Measurement Procedure

#### 5.3.1. The Variation of frequency with time

The operating frequency was measured using a spectrum analyzer. Starting with the EUT at room temperature, 1000 milliliters of water in the beaker was placed in the center of the Microwave Oven (EUT) and the EUT was operated at maximum output power.

The fundamental operating frequency was monitored until the water load was reduced to 20% of the original load.

#### 5.3.2. The Variation of frequency for line voltage

Following the above test, after operating the oven long enough to assure that stable operating temperature were obtained, the operating frequency was monitored as the input voltage was varied between 80 to 125 percent of the nominal rating.

The water load was maintained at 1000ml for the duration of the test.

## 5.4. Measurement Results

**PASSED.** All the test results are listed in the following and next two pages.

EUT : Microwave Oven

M/N : TSK-M3204ME

Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%

### 5.4.1. The Variation of frequency with time

Frequency was measured at the rated input voltage (AC 120V).

Initial Load: 1000ml

Final Load: 200ml

Fundamental Frequency: 2452.8MHz

Limit:  $2.4\text{GHz} < f < 2.5\text{GHz}$

Maximum Frequency Observed: 2459.8MHz

Minimum Frequency Observed: 2444.4MHz

Results: **PASSED.**

### 5.4.2. The Variation of frequency for line voltage

Variation of line voltage from 80% (96V) to 125% (150V)

Load: 1000ml

Fundamental Frequency: 2452.8MHz


Limit:  $2.4\text{GHz} < f < 2.5\text{GHz}$

Maximum Frequency Observed: 2456.3MHz


Minimum Frequency Observed: 2452.8MHz


Results: **PASSED.**

Fundamental Frequency: 2452.8MHz




Load: 200ml, Voltage: 120V



**Load: 1000ml, Voltage: 120V**

Trace: (Discrete)


Site no. : A/C Chamber Data no. : 21  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit :  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 1000 milliliters of waters in the beaker  
 located in the center of the oven

**Voltage Variation: 80%, Voltage: 96V, Load: 1000ml**

Trace: (Discrete)

Site no. : A/C Chamber Data no. : 22  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit :  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 96Vac/60Hz  
 Test Mode : POWER(HI)  
 1000 milliliters of waters in the beaker  
 located in the center of the oven

Voltage Variation: 125%, Voltage: 150V, Load: 1000ml



EUT : Microwave Oven

M/N : TSK-M3204MEQ

Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%

5.4.3. The Variation of frequency with time

Frequency was measured at the rated input voltage (AC 120V).

Initial Load: 1000ml

Final Load: 200ml

Fundamental Frequency: 2472.4MHz

Limit:  $2.4\text{GHz} < f < 2.5\text{GHz}$

Maximum Frequency Observed: 2454.9MHz

Minimum Frequency Observed: 2449.3MHz

Results: PASSED.

5.4.4. The Variation of frequency for line voltage

Variation of line voltage from 80% (96V) to 125% (150V)

Load: 1000ml

Fundamental Frequency: 2472.4MHz


Limit:  $2.4\text{GHz} < f < 2.5\text{GHz}$

Maximum Frequency Observed: 2456.3MHz


Minimum Frequency Observed: 2442.3MHz


Results: PASSED.

Fundamental Frequency: 2472.4MHz




Load: 200ml, Voltage: 120V



**Load: 1000ml, Voltage: 120V**

Trace: (Discrete)


|              |                                                                               |           |              |
|--------------|-------------------------------------------------------------------------------|-----------|--------------|
| Site no.     | : A/C Chamber                                                                 | Data no.  | : 23         |
| Dis. / Ant.  | : 3m 3115                                                                     | Ant. pol. | : VERTICAL   |
| Limit        | :                                                                             |           |              |
| Env. / Ins.  | : 8593EM 22°C/41%                                                             | Engineer  | : Cater Chou |
| EUT          | : Microwave Oven M/N:TSK-M3204MEQ                                             |           |              |
| Power Rating | : 120Vac/60Hz                                                                 |           |              |
| Test Mode    | : POWER(HI)                                                                   |           |              |
|              | 1000 milliliters of waters in the beaker<br>located in the center of the oven |           |              |

**Voltage Variation: 80%, Voltage: 96V, Load: 1000ml**

Trace: (Discrete)

|              |                                                                               |           |              |
|--------------|-------------------------------------------------------------------------------|-----------|--------------|
| Site no.     | : A/C Chamber                                                                 | Data no.  | : 24         |
| Dis. / Ant.  | : 3m 3115                                                                     | Ant. pol. | : VERTICAL   |
| Limit        | :                                                                             |           |              |
| Env. / Ins.  | : 8593EM 22°C/41%                                                             | Engineer  | : Cater Chou |
| EUT          | : Microwave Oven M/N:TSK-M3204MEQ                                             |           |              |
| Power Rating | : 96Vac/60Hz                                                                  |           |              |
| Test Mode    | : POWER(HI)                                                                   |           |              |
|              | 1000 milliliters of waters in the beaker<br>located in the center of the oven |           |              |

Voltage Variation: 125%, Voltage: 150V, Load: 1000ml




## 6. CONDUCTED EMISSION MEASUREMENT

### 6.1. Test Equipment

The following test equipment was used during the conducted emission measurement:

| Item | Type          | Manufacturer | Model No. | Serial No. | Last Cal.    | Next Cal.    |
|------|---------------|--------------|-----------|------------|--------------|--------------|
| 1.   | Test Receiver | R&S          | ESCS30    | 100265     | Sep. 27, 05' | Sep. 26, 06' |
| 2.   | L.I.S.N.      | Kyoritsu     | KNW-407   | 8-855-9    | Apr. 19, 06' | Apr. 18, 07' |
| 3.   | Pulse Limiter | R&S          | ESH3Z2    | 001        | Mar. 11, 06' | Mar. 10, 07' |

### 6.2. Test Setup



### 6.3. Conduction Limits [18.307(b)]

| Frequency of Emission | Maximum RF Line Voltage |                     |
|-----------------------|-------------------------|---------------------|
|                       | Quasi-Peak Level        | Average Level       |
| 150kHz ~ 500kHz       | 66 ~ 56 dB $\mu$ V*     | 56 ~ 46 dB $\mu$ V* |
| 500kHz ~ 5MHz         | 56 dB $\mu$ V           | 46 dB $\mu$ V       |
| 5MHz ~ 30MHz          | 60 dB $\mu$ V           | 50 dB $\mu$ V       |

Remark 1.: If the average limit is met when using a Quasi-Peak detector, the EUT shall be deemed to meet both limits and measurement with the average detector is unnecessary.

2.: \* Decreases with the logarithm of the frequency.

## 6.4. Operating Condition of EUT

- 6.4.1. Setup the EUT and simulator as shown on 6.2.
- 6.4.2. Turned on the power of all equipment.
- 6.4.3. The Microwave Oven (EUT) was set in test modes, and all the test modes are listed in section 6.6.

## 6.5. Test Procedure

The EUT was put on table which was above the ground by 80cm and its power cord was connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provided a 50 ohm coupling impedance for the measuring equipment. (Please refer to the block diagram of the test setup and photographs.) Both sides of A.C. line were checked for maximum conducted interference. In order to find the maximum emission, the relative positions simulators of the interface cables were manipulated according to FCC PART 18 during conducted measurement.

The bandwidth of the R&S Test Receiver ESCS30 was set at 9kHz.

The frequency range from 0.15MHz to 30MHz was pre-scanned with a peak detector. All the final readings from test receiver were measured with Quasi-Peak detector and Average detector. (Remark: If the Average limit is met when using a Quasi-Peak detector, the Average detector is unnecessary)

## 6.6. Conducted Emission Measurement Results

**PASSED.** All emissions not reported below are too low against the prescribed limits.

The EUT [Microwave Oven, M/N: (1)TSK-M3204ME (2)TSK-M3204MEQ] with following test modes were performed during this section testing and selected two worst test modes **[Mode 1 & 10]** to read Q.P. values, all the test results are attached in next pages. (※ **the worst test mode**)

Test Date : Jul. 28, 2006    Temperature : 25°C    Humidity : 40%


The details of test mode and reference test data are as follows :

| NO. | Test Model  | Test Mode           | Reference Test Data No. |             |
|-----|-------------|---------------------|-------------------------|-------------|
|     |             |                     | Neutral                 | Line        |
| ※1. | TSK-M3204ME | <b>Power (Max.)</b> | <b># 29</b>             | <b># 30</b> |
| 2.  |             | Power (Mid.)        | # 28                    | # 27        |
| 3.  |             | Power (Min.)        | # 25                    | # 26        |
| 4.  |             | Beverage            | # 21                    | # 22        |
| 5.  |             | Pizza               | # 24                    | # 23        |
| 6.  |             | Popcorn             | # 36                    | # 35        |
| 7.  |             | Defrost             | # 37                    | # 38        |
| 8.  |             | Cook (Potato)       | # 33                    | # 34        |
| 9.  |             | Reheat (Casserole)  | # 32                    | # 31        |

| NO.  | Test Model   | Test Mode          | Reference Test Data No. |      |
|------|--------------|--------------------|-------------------------|------|
|      |              |                    | Neutral                 | Line |
| ※10. | TSK-M3204MEQ | Power (Max.)       | # 13                    | # 14 |
| 11.  |              | Power (Mid.)       | # 12                    | # 11 |
| 12.  |              | Power (Min.)       | # 9                     | # 10 |
| 13.  |              | Beverage           | # 1                     | # 2  |
| 14.  |              | Pizza              | # 4                     | # 3  |
| 15.  |              | Popcorn            | # 5                     | # 6  |
| 16.  |              | Defrost            | # 8                     | # 7  |
| 17.  |              | Cook (Potato)      | # 20                    | # 19 |
| 18.  |              | Reheat (Casserole) | # 17                    | # 18 |
| 19.  |              | Combi              | # 16                    | # 15 |



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw




Site : No.2 Shielded room Data : 29  
Condition : KHW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MAX)

|       |        | LISN | Cable   | Emission |        |        |        |    |
|-------|--------|------|---------|----------|--------|--------|--------|----|
| Freq. | Factor | Loss | Reading | Level    | Limits | Margin | Remark |    |
| (MHz) | (dB)   | (dB) | (dBuV)  | (dBuV)   | (dBuV) | (dB)   |        |    |
| 1     | 0.156  | 0.29 | 0.24    | 50.43    | 50.96  | 65.69  | 14.74  | QP |
| 2     | 0.377  | 0.11 | 0.31    | 36.22    | 36.64  | 58.34  | 21.70  | QP |
| 3     | 0.909  | 0.10 | 0.39    | 31.96    | 32.45  | 56.00  | 23.55  | QP |
| 4     | 2.474  | 0.10 | 0.40    | 24.39    | 24.89  | 56.00  | 31.11  | QP |
| 5     | 7.566  | 0.10 | 0.61    | 13.05    | 13.76  | 60.00  | 46.24  | QP |
| 6     | 19.326 | 0.29 | 0.70    | 24.53    | 25.52  | 60.00  | 34.48  | QP |

Remarks: 1. Emission Level = LISN Factor + Cable Loss + Reading.  
2. If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw




Site : No.2 Shielded room Data : 30  
Condition : KHW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MAX)

|       |        | LISN | Cable   | Emission |        |        |        |    |
|-------|--------|------|---------|----------|--------|--------|--------|----|
| Freq. | Factor | Loss | Reading | Level    | Limits | Margin | Remark |    |
| (MHz) | (dB)   | (dB) | (dBμV)  | (dBμV)   | (dBμV) | (dB)   |        |    |
| 1     | 0.173  | 0.25 | 0.25    | 48.24    | 48.74  | 64.81  | 16.07  | QP |
| 2     | 0.327  | 0.13 | 0.30    | 43.86    | 44.29  | 59.53  | 15.24  | QP |
| 3     | 1.106  | 0.10 | 0.40    | 34.61    | 35.11  | 56.00  | 20.89  | QP |
| 4     | 2.474  | 0.10 | 0.40    | 28.47    | 28.97  | 56.00  | 27.03  | QP |
| 5     | 6.878  | 0.16 | 0.58    | 13.45    | 14.19  | 60.00  | 45.81  | QP |
| 6     | 19.021 | 0.28 | 0.70    | 26.97    | 27.95  | 60.00  | 32.05  | QP |

Remarks: 1.Emission Level= LISN Factor + Cable Loss + Reading.  
2.If the average limit is met when using a quasi-peak detector ,the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 28  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MID)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 27  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MID)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 25  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MIN)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 26  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MIN)



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                   |           |           |
|--------------|-----------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room              | Data      | : 21      |
| Condition    | : KNW-407                         | Phase     | : NEUTRAL |
| Limit        | : FCC PART 18                     |           |           |
| Env. / Ins.  | : 25°C, 40% / ESCS 30             | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204ME |           |           |
| Power Rating | : 120Vac/60Hz                     |           |           |
| Test Mode    | : BEVERAGE                        |           |           |



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                   |           |           |
|--------------|-----------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room              | Data      | : 22      |
| Condition    | : KNW-407                         | Phase     | : LINE    |
| Limit        | : FCC PART 18                     |           |           |
| Env. / Ins.  | : 25°C, 40% / ESCS 30             | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204ME |           |           |
| Power Rating | : 120Vac/60Hz                     |           |           |
| Test Mode    | : BEVERAGE                        |           |           |




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 24  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : PIZZA




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 23  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : PIZZA




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 36  
Condition : KMW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POPCORN




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 35  
Condition : KMW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C,40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POPCORN




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 37  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : DEFROST




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 38  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : DEFROST




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 33  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : COOK(POTATO)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 34  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : COOK(POTATO)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 32  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : REHEAT(CASSEROLE)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 31  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 40% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : REHEAT(CASSEROLE)



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttmc@ttmc.com.tw



Trace: (Discrete)


Site : No.2 Shielded room Data : 13  
Condition : KHW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C,43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MAX)

|       |        | LISN | Cable   | Emission |        |        |        |    |
|-------|--------|------|---------|----------|--------|--------|--------|----|
| Freq. | Factor | Loss | Reading | Level    | Limits | Margin | Remark |    |
| (MHz) | (dB)   | (dB) | (dBuV)  | (dBuV)   | (dBuV) | (dB)   |        |    |
| 1     | 0.177  | 0.24 | 0.25    | 50.51    | 51.00  | 64.64  | 13.63  | QP |
| 2     | 0.389  | 0.10 | 0.32    | 36.82    | 37.24  | 58.08  | 20.84  | QP |
| 3     | 0.880  | 0.10 | 0.39    | 21.84    | 22.33  | 56.00  | 33.67  | QP |
| 4     | 2.581  | 0.10 | 0.40    | 20.64    | 21.14  | 56.00  | 34.86  | QP |
| 5     | 7.810  | 0.10 | 0.62    | 12.92    | 13.64  | 60.00  | 46.36  | QP |
| 6     | 18.721 | 0.28 | 0.70    | 32.41    | 33.39  | 60.00  | 26.61  | QP |

Remarks: 1.Emission Level= LISN Factor + Cable Loss + Reading.  
2.If the average limit is met when using a quasi-peak detector ,the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site : No.2 Shielded room Data : 14  
Condition : KHW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C,43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N:TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MAX)

|       |        | LISN | Cable   | Emission |        |        |        |    |
|-------|--------|------|---------|----------|--------|--------|--------|----|
| Freq. | Factor | Loss | Reading | Level    | Limits | Margin | Remark |    |
| (MHz) | (dB)   | (dB) | (dBuV)  | (dBuV)   | (dBuV) | (dB)   |        |    |
| 1     | 0.181  | 0.24 | 0.25    | 52.03    | 52.51  | 64.46  | 11.95  | QP |
| 2     | 0.419  | 0.10 | 0.32    | 36.01    | 36.43  | 57.46  | 21.03  | QP |
| 3     | 0.690  | 0.10 | 0.37    | 26.23    | 26.70  | 56.00  | 29.30  | QP |
| 4     | 2.513  | 0.10 | 0.40    | 21.16    | 21.66  | 56.00  | 34.34  | QP |
| 5     | 7.728  | 0.17 | 0.62    | 13.22    | 14.01  | 60.00  | 45.99  | QP |
| 6     | 18.039 | 0.26 | 0.70    | 31.86    | 32.82  | 60.00  | 27.18  | QP |

Remarks: 1.Emission Level= LISN Factor + Cable Loss + Reading.  
2.If the average limit is met when using a quasi-peak detector  
,the EUT shall be deemed to meet both limits and measurement  
with average detector is unnecessary.




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 12  
Condition : KMW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MID)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 11  
Condition : KMW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MID)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 9  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MIN)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 10  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MIN)



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                    |           |           |
|--------------|------------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room               | Data      | : 1       |
| Condition    | : KNW-407                          | Phase     | : NEUTRAL |
| Limit        | : FCC PART 18                      |           |           |
| Env. / Ins.  | : 25°C, 43% / ESCS 30              | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204MEQ |           |           |
| Power Rating | : 120Vac/60Hz                      |           |           |
| Test Mode    | : BEVERAGE                         |           |           |



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                    |           |           |
|--------------|------------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room               | Data      | : 2       |
| Condition    | : KNW-407                          | Phase     | : LINE    |
| Limit        | : FCC PART 18                      |           |           |
| Env. / Ins.  | : 25°C, 43% / ESCS 30              | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204MEQ |           |           |
| Power Rating | : 120Vac/60Hz                      |           |           |
| Test Mode    | : BEVERAGE                         |           |           |




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 4  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : PIZZA




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 3  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : PIZZA



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                    |           |           |
|--------------|------------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room               | Data      | : 5       |
| Condition    | : KNW-407                          | Phase     | : NEUTRAL |
| Limit        | : FCC PART 18                      |           |           |
| Env. / Ins.  | : 25°C, 43% / ESCS 30              | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204MEQ |           |           |
| Power Rating | : 120Vac/60Hz                      |           |           |
| Test Mode    | : POPCORN                          |           |           |



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

|              |                                    |           |           |
|--------------|------------------------------------|-----------|-----------|
| Site         | : No.2 Shielded room               | Data      | : 6       |
| Condition    | : KNW-407                          | Phase     | : LINE    |
| Limit        | : FCC PART 18                      |           |           |
| Env. / Ins.  | : 25°C, 43% / ESCS 30              | Engineer: | Ada Huang |
| EUT          | : Microwave Oven M/N: TSK-M3204MEQ |           |           |
| Power Rating | : 120Vac/60Hz                      |           |           |
| Test Mode    | : POPCORN                          |           |           |




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 8  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : DEFROST




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 7  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : DEFROST




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 20  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : COOK(POTATO)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw



Site : No.2 Shielded room Data : 19  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : COOK(POTATO)



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

Site : No.2 Shielded room Data : 17  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : REHEAT(CASSEROLE)



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:tiemc@tiemc.com.tw




Trace: (Discrete)

Site : No.2 Shielded room Data : 18  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : REHEAT(CASSEROLE)




AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 16  
Condition : KNW-407 Phase : NEUTRAL  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : COMBI



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Site : No.2 Shielded room Data : 15  
Condition : KNW-407 Phase : LINE  
Limit : FCC PART 18  
Env. / Ins. : 25°C, 43% / ESCS 30 Engineer: Ada Huang  
EUT : Microwave Oven M/N: TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : COMBI

## 7. RADIATED EMISSION MEASUREMENT

### 7.1. Test Equipment

The following test equipment was used during the radiated emission tests :

#### 7.1.1. Below 1GHz (at Semi-Anechoic Chamber)

| Item | Type                 | Manufacturer | Model No.   | Serial No. | Last Cal.    | Next Cal.    |
|------|----------------------|--------------|-------------|------------|--------------|--------------|
| 1.   | Spectrum Analyzer    | HP           | 8593EM      | 3826A00248 | Sep. 26, 05' | Sep. 25, 06' |
| 2.   | Pre-Amplifier        | HP           | 8447D       | 2944A06305 | Mar. 09, 06' | Mar. 08, 07' |
| 3.   | Biconical Antenna    | CHASE        | VBA6106A    | 1264       | Nov.11, 05'  | Nov.10, 06'  |
| 4.   | Log Periodic Antenna | Schwarzbeck  | UHALP9108-A | 0139       | Nov. 19, 05' | Nov. 19, 06' |

#### 7.1.2. Above 1GHz (at Semi-Anechoic Chamber)


| Item | Type                               | Manufacturer | Model No.   | Serial No. | Last Cal.    | Next Cal.    |
|------|------------------------------------|--------------|-------------|------------|--------------|--------------|
| 1.   | Spectrum Analyzer                  | HP           | 8593EM      | 3826A00248 | Sep. 26, 05' | Sep. 25, 06' |
| 2.   | Pre-Amplifier                      | HP           | 8449B       | 3008A01284 | Jun. 30, 06' | Jun. 29, 07' |
| 3.   | Horn Antenna                       | EMCO         | 3115        | 9112-3775  | Jun. 01, 06' | May 31, 07'  |
| 4.   | For Above 3.5GHz -High Pass Filter | HP           | 84300-80038 | 005        | Jan. 13, 06' | Jan. 12, 07' |

### 7.2. Test Setup

#### 7.2.1. Block Diagram of connection between EUT and simulators

**MICROWAVE OVEN (EUT)**

#### 7.2.2. Semi-Anechoic Chamber (3m) Setup Diagram



### 7.3. Radiation Limits

The radiated limits of the **[Microwave Oven, M/N : TSK-M3204ME]** are complied with FCC CFR Title 47 Part 18 Subpart C & MP-5. The limits are calculated as below:

Calculated formula:

$$\text{Limit } (E_{300m}) = 25 * (\text{Power} / 500)^{1/2} (\mu\text{V/m})$$

$$E_{3m} = E_{300m} / K$$

$$\text{Power Output} = 647.5\text{W}$$

$$\text{Limit } (E_{300m}) = 25 * (647.5 / 500)^{1/2} (\mu\text{V/m}) = 28.4495 (\mu\text{V/m})$$

$$E_{3m} = 28.4495 / 6.2335 * 10^{-3} = 4563.9175 (\mu\text{V/m})$$

$$20\log(4563.9175) = 73.186 (\text{dB}\mu\text{V/m})$$

The radiated limits of the **[Microwave Oven, M/N : TSK-M3204MEQ]** are complied with FCC CFR Title 47 Part 18 Subpart C & MP-5. The limits are calculated as below:

Calculated formula:

$$\text{Limit } (E_{300m}) = 25 * (\text{Power} / 500)^{1/2} (\mu\text{V/m})$$

$$E_{3m} = E_{300m} / K$$

$$\text{Power Output} = 752.5\text{W}$$

$$\text{Limit } (E_{300m}) = 25 * (752.5 / 500)^{1/2} (\mu\text{V/m}) = 30.6696 (\mu\text{V/m})$$

$$E_{3m} = 30.6696 / 6.2849 * 10^{-3} = 4879.8234 (\mu\text{V/m})$$

$$20\log(4879.8234) = 73.768 (\text{dB}\mu\text{V/m})$$

### 7.4. Operating Condition of EUT

- 7.4.1. Setup the EUT and simulator as shown on 7.2.
- 7.4.2. Turned on the power of all equipment.
- 7.4.3. The beaker with two loads (700ml & 300ml) and two locations (center & right front corner) was placed into the Microwave Oven (EUT).
- 7.4.4. The Microwave Oven (EUT) was set in test modes, and all the test modes are listed in section 7.6.

### 7.5. Test Procedure

The EUT was placed on a turn table which was 0.8 meter or 1 meter (0.8 meter for measurement below 1GHz and 1 meter for measurement above 1GHz) above the ground. The turn table rotated 360 degrees to determine the position of the maximum emission level. The EUT was set to 3 meters away from the receiving antenna which was mounted on a antenna tower. The antenna moved up and down between 1 to 4 meters above reference plane to find out the maximum emission level. Broadband antenna such as calibrated biconical and log- periodical antenna or horn antenna was used as a receiving antenna. Both horizontal and vertical polarizations of the antenna were set on measurement. In order to find the maximum emission, all of the interface cables were manipulated according to FCC/OST MP-5 (1986) regulation.

The resolution bandwidth of spectrum analyzer using Peak detector was set at 120kHz for measurement below 1GHz and resolution bandwidth of spectrum analyzer using Average detector was set at 1MHz for measurement above 1GHz.

Load for measurement on second and third harmonics: Two loads one of 700 and the other of 300 ml, of water are used. Each load is tested both with the beaker located in the center of the microwave oven and with it in the right front corner.

Load for all other measurement: 700ml of water, with the beaker located in the center of the microwave oven.

The frequency range from 30MHz to 1000MHz was pre-scanned with Peak detector at simple anechoic chamber and frequency range above 1GHz was pre-scanned with Average detector at simple anechoic chamber.

## 7.6. Radiated Emission Measurement Results

**PASSED.** All emissions not reported below are too low against the prescribed limits.

The EUT [Microwave Oven, M/N: (1)TSK-M3204ME (2)TSK-M3204MEQ] with following test modes were measured at Semi-Anechoic Chamber and all the test results are listed in next pages.

Test Date : Jul. 07, 2006    Temperature : 22°C    Humidity : 41%

Test Date : Jul. 27, 2006    Temperature : 22°C    Humidity : 41%


The details of test mode and reference test data are as follows :

| NO. | Test Model  | Frequency range                                   | Test Mode                                                           | Reference Test Data No. |          |
|-----|-------------|---------------------------------------------------|---------------------------------------------------------------------|-------------------------|----------|
|     |             |                                                   |                                                                     | Horizontal              | Vertical |
| 1.  | TSK-M3204ME | Below 1GHz<br>(30MHz-1GHz)                        | Load: 700ml,<br>Beaker Location: Center Power (Max.)                | # 10                    | # 9      |
| 2.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center Power (Mid.)                | # 7                     | # 8      |
| 3.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center Power (Min.)                | # 6                     | # 5      |
| 4.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center (Beverage)                  | # 18                    | # 17     |
| 5.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center (Pizza)                     | # 16                    | # 15     |
| 6.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center (Popcorn)                   | # 14                    | # 13     |
| 7.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center (Defrost)                   | # 11                    | # 12     |
| 8.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center [Cook (Potato)]             | # 2                     | # 1      |
| 9.  |             |                                                   | Load: 700ml,<br>Beaker Location: Center [Reheat<br>(Casserole)]     | # 3                     | # 4      |
| 10. |             | Above 1GHz                                        | Load: 1000ml,<br>Beaker Location: Center Power (Max.)               | # 24                    | # 25     |
| 11. |             | Above 1GHz.<br>(At second and<br>third harmonics) | Load: 700ml,<br>Beaker Location: Right Front Corner<br>Power (Max.) | # 27                    | # 26     |
| 12. |             |                                                   | Load: 300ml,<br>Beaker Location: Center Power (Max.)                | # 31                    | # 30     |
| 13. |             |                                                   | Load: 300ml,<br>Beaker Location: Right Front Corner<br>Power (Max.) | # 28                    | # 29     |

| NO. | Test Model   | Frequency range                                   | Test Mode                                                           | Reference Test Data No. |          |
|-----|--------------|---------------------------------------------------|---------------------------------------------------------------------|-------------------------|----------|
|     |              |                                                   |                                                                     | Horizontal              | Vertical |
| 14. | TSK-M3204MEQ | Below 1GHz<br>(30MHz-1GHz)                        | Load: 700ml,<br>Beaker Location: Center Power (Max.)                | # 11                    | # 12     |
| 15. |              |                                                   | Load: 700ml,<br>Beaker Location: Center Power (Mid.)                | # 10                    | # 9      |
| 16. |              |                                                   | Load: 700ml,<br>Beaker Location: Center Power (Min.)                | # 7                     | # 8      |
| 17. |              |                                                   | Load: 700ml,<br>Beaker Location: Center (Beverage)                  | # 20                    | # 19     |
| 18. |              |                                                   | Load: 700ml,<br>Beaker Location: Center (Pizza)                     | # 17                    | # 18     |
| 19. |              |                                                   | Load: 700ml,<br>Beaker Location: Center (Popcorn)                   | # 16                    | # 15     |
| 20. |              |                                                   | Load: 700ml,<br>Beaker Location: Center (Defrost)                   | # 13                    | # 14     |
| 21. |              |                                                   | Load: 700ml,<br>Beaker Location: Center [Cook (Potato)]             | # 1                     | # 2      |
| 22. |              |                                                   | Load: 700ml,<br>Beaker Location: Center [Reheat<br>(Casserole)]     | # 3                     | # 4      |
| 23. |              |                                                   | Load: 700ml,<br>Beaker Location: Center (Combi)                     | # 6                     | # 5      |
| 24. |              | Above 1GHz                                        | Load: 700ml,<br>Beaker Location: Center Power (Max.)                | # 27                    | # 26     |
| 25. |              | Above 1GHz.<br>(At second and<br>third harmonics) | Load: 700ml,<br>Beaker Location: Right Front Corner<br>Power (Max.) | # 28                    | # 29     |
| 26. |              |                                                   | Load: 300ml,<br>Beaker Location: Center Power (Max.)                | # 32                    | # 33     |
| 27. |              |                                                   | Load: 300ml,<br>Beaker Location: Right Front Corner<br>Power (Max.) | # 31                    | # 30     |



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 10  
Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
Limit : 73.1 dBuV/m  
Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : Power(MAX)  
700 milliliters of waters in the beaker  
located in the center of the oven

|   | Freq.   | Ant.   | Cable |         | Emission |          |        |        |
|---|---------|--------|-------|---------|----------|----------|--------|--------|
|   | (MHz)   | Factor | Loss  | Reading | Level    | Limits   | Margin | Remark |
|   |         | (dB/m) | (dB)  | (dBuV)  | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1 | 92.080  | 16.08  | 2.00  | 1.91    | 19.98    | 73.10    | 53.12  | QP     |
| 2 | 261.830 | 24.57  | 3.60  | -1.70   | 26.47    | 73.10    | 46.63  | QP     |
| 3 | 369.500 | 16.93  | 4.60  | 9.09    | 30.62    | 73.10    | 42.48  | QP     |
| 4 | 462.620 | 17.99  | 5.70  | -0.91   | 22.79    | 73.10    | 50.31  | QP     |
| 5 | 617.820 | 21.32  | 6.30  | -2.10   | 25.52    | 73.10    | 47.58  | QP     |
| 6 | 854.500 | 25.81  | 7.10  | -4.80   | 28.11    | 73.10    | 44.99  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 9  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : Power(MAX)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 62.010  | 13.37  | 1.60  | 5.81         | 20.78          | 73.10          | 52.32  | QP     |
| 2 | 247.280 | 24.78  | 3.50  | 0.26         | 28.54          | 73.10          | 44.56  | QP     |
| 3 | 382.110 | 16.94  | 4.60  | 0.99         | 22.53          | 73.10          | 50.57  | QP     |
| 4 | 609.090 | 21.64  | 6.20  | -1.94        | 25.91          | 73.10          | 47.19  | QP     |
| 5 | 747.800 | 24.27  | 6.70  | 0.55         | 31.52          | 73.10          | 41.58  | QP     |
| 6 | 929.190 | 26.01  | 7.50  | -1.17        | 32.34          | 73.10          | 40.76  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 7  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MID)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 92.080  | 16.08  | 2.00  | 1.89         | 19.96          | 73.10          | 53.14  | QP     |
| 2 | 252.130 | 23.99  | 3.59  | 8.44         | 36.01          | 73.10          | 37.09  | QP     |
| 3 | 371.440 | 17.08  | 4.60  | 12.62        | 34.30          | 73.10          | 38.80  | QP     |
| 4 | 515.000 | 19.97  | 6.80  | 11.25        | 38.02          | 73.10          | 35.08  | QP     |
| 5 | 665.350 | 22.65  | 6.40  | 7.09         | 36.14          | 73.10          | 36.96  | QP     |
| 6 | 813.760 | 23.98  | 7.00  | -1.65        | 29.33          | 73.10          | 43.77  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 8  
Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
Limit : 73.1 dB  $\mu$ V/m  
Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : POWER(MID)  
700 milliliters of waters in the beaker  
located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 47.460  | 16.67  | 1.40  | 5.82         | 23.89          | 73.10          | 49.21  | QP     |
| 2 | 200.720 | 22.94  | 3.00  | 2.70         | 28.65          | 73.10          | 44.45  | QP     |
| 3 | 313.240 | 15.31  | 4.00  | 13.10        | 32.41          | 73.10          | 40.69  | QP     |
| 4 | 450.010 | 17.51  | 5.40  | 4.54         | 27.45          | 73.10          | 45.65  | QP     |
| 5 | 634.310 | 21.13  | 6.30  | -1.28        | 26.15          | 73.10          | 46.95  | QP     |
| 6 | 787.570 | 25.44  | 6.90  | -2.63        | 29.72          | 73.10          | 43.38  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 6  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MIN)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.   | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | (MHz)   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   |         | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 155.130 | 20.71  | 2.63  | 12.83        | 36.16          | 73.10          | 36.94  | QP     |
| 2 | 373.380 | 17.13  | 4.60  | 12.15        | 33.89          | 73.10          | 39.21  | QP     |
| 3 | 501.420 | 18.95  | 6.52  | -1.99        | 23.49          | 73.10          | 49.61  | QP     |
| 4 | 612.970 | 21.36  | 6.30  | 10.65        | 38.31          | 73.10          | 34.79  | QP     |
| 5 | 715.790 | 22.74  | 6.55  | 5.99         | 35.29          | 73.10          | 37.81  | QP     |
| 6 | 871.960 | 25.52  | 7.20  | 0.75         | 33.47          | 73.10          | 39.63  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 5  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MIN)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 95.960  | 17.19  | 2.00  | 12.99        | 32.18          | 73.10          | 40.92  | QP     |
| 2 | 247.280 | 24.78  | 3.50  | 4.92         | 33.20          | 73.10          | 39.90  | QP     |
| 3 | 380.170 | 16.80  | 4.60  | 20.12        | 41.52          | 73.10          | 31.58  | QP     |
| 4 | 588.720 | 21.52  | 6.30  | 5.20         | 33.01          | 73.10          | 40.09  | QP     |
| 5 | 702.210 | 22.43  | 6.50  | 20.76        | 49.68          | 73.10          | 23.42  | QP     |
| 6 | 850.620 | 26.34  | 7.10  | 1.01         | 34.46          | 73.10          | 38.64  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 18  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : BEVERAGE  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 78.500  | 13.43 | 1.80         | 3.05           | 18.29          | 73.10  | 54.81  | QP |
| 2     | 178.410 | 21.28 | 2.90         | -2.08          | 22.09          | 73.10  | 51.01  | QP |
| 3     | 278.320 | 25.25 | 3.80         | -2.58          | 26.47          | 73.10  | 46.63  | QP |
| 4     | 441.280 | 17.63 | 5.30         | -2.57          | 20.36          | 73.10  | 52.74  | QP |
| 5     | 608.120 | 21.47 | 6.20         | -2.24          | 25.43          | 73.10  | 47.67  | QP |
| 6     | 859.350 | 26.01 | 7.20         | -2.82          | 30.38          | 73.10  | 42.72  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 17  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$  V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : BEVERAGE  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 66.860  | 12.52  | 1.70  | 6.92         | 21.13          | 73.10          | 51.97  | QP     |
| 2 | 198.780 | 22.74  | 3.00  | -2.47        | 23.27          | 73.10          | 49.83  | QP     |
| 3 | 278.320 | 25.94  | 3.80  | -1.09        | 28.64          | 73.10          | 44.46  | QP     |
| 4 | 443.220 | 17.42  | 5.33  | -3.74        | 19.02          | 73.10          | 54.08  | QP     |
| 5 | 645.950 | 21.60  | 6.30  | -3.50        | 24.40          | 73.10          | 48.70  | QP     |
| 6 | 921.430 | 25.69  | 7.40  | -2.68        | 30.41          | 73.10          | 42.69  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 16  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : PIZZA  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 191.990 | 21.60  | 3.00  | -2.54        | 22.06          | 73.10          | 51.04  | QP     |
| 2 | 297.720 | 26.68  | 3.98  | -3.53        | 27.13          | 73.10          | 45.97  | QP     |
| 3 | 476.200 | 18.55  | 6.00  | -1.73        | 22.82          | 73.10          | 50.28  | QP     |
| 4 | 593.570 | 20.95  | 6.20  | -0.57        | 26.58          | 73.10          | 46.52  | QP     |
| 5 | 720.640 | 22.24  | 6.54  | -0.66        | 28.12          | 73.10          | 44.98  | QP     |
| 6 | 870.020 | 25.71  | 7.20  | -2.14        | 30.77          | 73.10          | 42.33  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 15  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : PIZZA  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 95.960  | 17.19  | 2.00  | 6.34         | 25.53          | 73.10          | 47.57  | QP     |
| 2 | 236.610 | 24.51  | 3.40  | -2.26        | 25.65          | 73.10          | 47.45  | QP     |
| 3 | 322.940 | 15.59  | 4.15  | -2.60        | 17.14          | 73.10          | 55.96  | QP     |
| 4 | 443.220 | 17.42  | 5.33  | -2.18        | 20.58          | 73.10          | 52.52  | QP     |
| 5 | 591.630 | 21.48  | 6.20  | -2.04        | 25.64          | 73.10          | 47.46  | QP     |
| 6 | 884.570 | 25.53  | 7.30  | -3.50        | 29.33          | 73.10          | 43.77  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 14  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POPCORN  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 190.050 | 21.51  | 2.92  | -1.56        | 22.88          | 73.10          | 50.22  | QP     |
| 2 | 299.660 | 26.77  | 3.90  | -2.45        | 28.22          | 73.10          | 44.88  | QP     |
| 3 | 441.280 | 17.63  | 5.30  | -2.73        | 20.20          | 73.10          | 52.90  | QP     |
| 4 | 599.390 | 21.30  | 6.30  | -3.57        | 24.03          | 73.10          | 49.08  | QP     |
| 5 | 709.000 | 23.54  | 6.60  | -0.44        | 29.71          | 73.10          | 43.39  | QP     |
| 6 | 878.750 | 25.35  | 7.30  | -3.35        | 29.30          | 73.10          | 43.80  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 13  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POPCORN  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 99.840  | 17.62  | 2.10  | 3.38         | 23.10          | 73.10          | 50.00  | QP     |
| 2 | 201.690 | 22.93  | 3.03  | -0.56        | 25.39          | 73.10          | 47.71  | QP     |
| 3 | 367.560 | 15.79  | 4.46  | 2.76         | 23.01          | 73.10          | 50.09  | QP     |
| 4 | 455.830 | 18.57  | 5.50  | -2.08        | 21.99          | 73.10          | 51.11  | QP     |
| 5 | 650.800 | 21.76  | 6.30  | -2.73        | 25.32          | 73.10          | 47.78  | QP     |
| 6 | 837.040 | 26.47  | 7.10  | -1.51        | 32.06          | 73.10          | 41.04  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 11  
Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
Limit : 73.1 dB  $\mu$ V/m  
Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
EUT : Microwave Oven M/N:TSK-M3204ME  
Power Rating : 120Vac/60Hz  
Test Mode : DEFROST  
700 milliliters of waters in the beaker  
located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 117.300 | 18.85  | 2.30  | 13.50        | 34.65          | 73.10          | 38.45  | QP     |
| 2 | 229.820 | 22.08  | 3.30  | 0.60         | 25.98          | 73.10          | 47.12  | QP     |
| 3 | 266.680 | 24.74  | 3.70  | -0.30        | 28.14          | 73.10          | 44.96  | QP     |
| 4 | 441.280 | 17.63  | 5.30  | 3.69         | 26.62          | 73.10          | 46.48  | QP     |
| 5 | 659.530 | 22.30  | 6.40  | -1.90        | 26.80          | 73.10          | 46.30  | QP     |
| 6 | 958.290 | 26.34  | 7.60  | -3.55        | 30.39          | 73.10          | 42.71  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 12  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : DEFROST  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.   | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | (MHz)   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   |         | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 145.430 | 21.26  | 2.59  | 2.84         | 26.68          | 73.10          | 46.42  | QP     |
| 2 | 220.120 | 22.46  | 3.30  | 1.15         | 26.91          | 73.10          | 46.19  | QP     |
| 3 | 345.250 | 15.58  | 4.40  | 5.95         | 25.93          | 73.10          | 47.17  | QP     |
| 4 | 447.100 | 17.47  | 5.40  | -3.34        | 19.54          | 73.10          | 53.56  | QP     |
| 5 | 639.160 | 21.22  | 6.28  | 3.38         | 30.88          | 73.10          | 42.22  | QP     |
| 6 | 841.890 | 26.62  | 7.10  | -2.26        | 31.46          | 73.10          | 41.64  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 2  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : COOK(POTATO)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 55.220  | 14.39 | 1.50         | 14.36          | 30.25          | 73.10  | 42.85  | QP |
| 2     | 260.860 | 24.58 | 3.60         | -1.91          | 26.27          | 73.10  | 46.83  | QP |
| 3     | 373.380 | 17.13 | 4.60         | 9.92           | 31.66          | 73.10  | 41.44  | QP |
| 4     | 519.850 | 19.99 | 6.90         | 2.47           | 29.36          | 73.10  | 43.74  | QP |
| 5     | 687.660 | 23.26 | 6.50         | -3.29          | 26.47          | 73.10  | 46.63  | QP |
| 6     | 847.710 | 25.43 | 7.10         | -1.05          | 31.48          | 73.10  | 41.62  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 1  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : COOK(POTATO)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 125.060 | 17.89 | 2.30         | 11.40          | 31.59          | 73.10  | 41.51  | QP |
| 2     | 182.290 | 21.55 | 2.90         | 10.11          | 34.55          | 73.10  | 38.55  | QP |
| 3     | 469.410 | 19.07 | 5.80         | -2.06          | 22.81          | 73.10  | 50.29  | QP |
| 4     | 663.410 | 22.22 | 6.32         | -2.34          | 26.20          | 73.10  | 46.90  | QP |
| 5     | 735.190 | 23.26 | 6.68         | 6.90           | 36.84          | 73.10  | 36.26  | QP |
| 6     | 967.990 | 26.97 | 7.69         | -1.29          | 33.37          | 73.10  | 39.73  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 3  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : REHEAT(CASSEROLE)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 61.040  | 12.55  | 1.60  | 19.04        | 33.19          | 73.10          | 39.91  | QP     |
| 2 | 240.490 | 23.10  | 3.40  | -1.89        | 24.62          | 73.10          | 48.48  | QP     |
| 3 | 448.070 | 17.63  | 5.40  | -2.52        | 20.51          | 73.10          | 52.59  | QP     |
| 4 | 567.380 | 20.97  | 6.50  | -1.44        | 26.04          | 73.10          | 47.06  | QP     |
| 5 | 793.390 | 23.98  | 6.90  | -2.65        | 28.23          | 73.10          | 44.87  | QP     |
| 6 | 913.670 | 24.96  | 7.40  | -2.58        | 29.78          | 73.10          | 43.32  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 4  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.1 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : REHEAT(CASSEROLE)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 48.430  | 16.41  | 1.40  | 9.86         | 27.67          | 73.10          | 45.43  | QP     |
| 2 | 195.870 | 22.50  | 3.00  | 3.36         | 28.85          | 73.10          | 44.25  | QP     |
| 3 | 382.110 | 16.94  | 4.60  | 1.50         | 23.04          | 73.10          | 50.06  | QP     |
| 4 | 536.340 | 20.10  | 7.07  | -0.43        | 26.74          | 73.10          | 46.36  | QP     |
| 5 | 735.190 | 23.26  | 6.68  | 7.98         | 37.92          | 73.10          | 35.18  | QP     |
| 6 | 935.980 | 26.53  | 7.50  | -3.47        | 30.56          | 73.10          | 42.54  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 24  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 1000 milliliters of waters in the beaker  
 located in the center of the oven

|             |        | Ant.  | Cable        |                | Emission       |        |         |  |
|-------------|--------|-------|--------------|----------------|----------------|--------|---------|--|
| Freq.       | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)       | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4162.000  | 32.87  | 8.56  | 3.83         | 45.26          | 73.10          | 27.84  | Average |  |
| 2 4905.600  | 33.85  | 9.16  | 4.88         | 47.89          | 73.10          | 25.21  | Average |  |
| 3 7358.400  | 37.10  | 11.48 | -4.05        | 44.52          | 73.10          | 28.58  | Average |  |
| 4 9811.200  | 38.47  | 12.93 | -4.33        | 47.06          | 73.10          | 26.04  | Average |  |
| 5 12264.000 | 38.85  | 15.00 | -5.76        | 48.09          | 73.10          | 25.01  | Average |  |
| 6 14716.800 | 39.38  | 16.82 | -4.69        | 51.51          | 73.10          | 21.59  | Average |  |
| 7 17169.600 | 43.34  | 17.16 | -15.55       | 44.95          | 73.10          | 28.15  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 25  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.1 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 1000 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.     | Ant.   | Cable |              | Emission       |                |        |         |
|---|-----------|--------|-------|--------------|----------------|----------------|--------|---------|
|   | (MHz)     | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark  |
|   |           | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |
| 1 | 4905.600  | 33.85  | 9.16  | 2.18         | 45.19          | 73.10          | 27.91  | Average |
| 2 | 6304.000  | 34.88  | 10.42 | -5.98        | 39.32          | 73.10          | 33.78  | Average |
| 3 | 7358.400  | 37.10  | 11.48 | -4.88        | 43.69          | 73.10          | 29.41  | Average |
| 4 | 9811.200  | 38.47  | 12.93 | -6.50        | 44.89          | 73.10          | 28.21  | Average |
| 5 | 12264.000 | 38.85  | 15.00 | -6.88        | 46.96          | 73.10          | 26.14  | Average |
| 6 | 14716.800 | 39.38  | 16.82 | -5.57        | 50.63          | 73.10          | 22.47  | Average |
| 7 | 17169.600 | 43.34  | 17.16 | -12.22       | 48.28          | 73.10          | 24.82  | Average |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 27  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$  V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4890.640 | 33.82  | 9.16       | 11.87        | 54.85          | 73.10          | 18.25  | Average |  |
| 2 7328.200 | 37.00  | 11.44      | 6.36         | 54.80          | 73.10          | 18.30  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 26  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.1 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4876.000 | 33.78  | 9.15       | 10.24        | 53.17          | 73.10          | 19.93  | Average |  |
| 2 7335.520 | 37.00  | 11.44      | 5.53         | 53.98          | 73.10          | 19.12  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 31  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the center of the oven

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4912.600 | 33.89  | 9.16       | 12.90        | 55.95          | 73.10          | 17.15  | Average |  |
| 2 7386.760 | 37.15  | 11.54      | 9.21         | 57.90          | 73.10          | 15.20  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 30  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the center of the oven

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4927.240 | 33.92  | 9.13       | 10.16        | 53.22          | 73.10          | 19.88  | Average |  |
| 2 7364.800 | 37.10  | 11.51      | 7.17         | 55.78          | 73.10          | 17.32  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 28  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4861.360 | 33.75  | 9.15       | 8.99         | 51.89          | 73.10          | 21.21  | Average |  |
| 2 7313.560 | 36.95  | 11.41      | 6.01         | 54.37          | 73.10          | 18.73  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 29  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.1 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204ME  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4876.000 | 33.78  | 9.15       | 11.46        | 54.39          | 73.10          | 18.71  | Average |  |
| 2 7313.560 | 36.95  | 11.41      | 7.31         | 55.67          | 73.10          | 17.43  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 11  
Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
Limit : 73.7 dB $\mu$ V/m  
Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
EUT : Microwave Oven M/N:TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : Power(MAX)  
700 milliliters of waters in the beaker  
located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 80.440  | 13.81 | 1.89         | 1.84           | 17.53          | 73.70  | 56.17  | QP |
| 2     | 221.090 | 21.91 | 3.30         | -2.27          | 22.95          | 73.70  | 50.75  | QP |
| 3     | 369.500 | 16.93 | 4.60         | 0.46           | 21.99          | 73.70  | 51.71  | QP |
| 4     | 579.020 | 20.96 | 6.40         | -2.40          | 24.96          | 73.70  | 48.74  | QP |
| 5     | 700.270 | 23.46 | 6.50         | 0.61           | 30.57          | 73.70  | 43.13  | QP |
| 6     | 903.970 | 24.88 | 7.40         | -0.21          | 32.07          | 73.70  | 41.63  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 12  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : Power(MAX)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 76.560  | 13.50  | 1.80  | 0.58         | 15.88          | 73.70          | 57.82  | QP     |
| 2 | 243.400 | 24.36  | 3.40  | -1.32        | 26.44          | 73.70          | 47.26  | QP     |
| 3 | 408.300 | 17.15  | 4.90  | 1.32         | 23.37          | 73.70          | 50.33  | QP     |
| 4 | 612.000 | 21.50  | 6.30  | -1.47        | 26.33          | 73.70          | 47.37  | QP     |
| 5 | 772.050 | 25.13  | 6.80  | -2.52        | 29.40          | 73.70          | 44.30  | QP     |
| 6 | 901.060 | 25.82  | 7.40  | -2.56        | 30.66          | 73.70          | 43.04  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 10  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MID)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 58.130  | 13.43  | 1.60  | 1.89         | 16.92          | 73.70          | 56.78  | QP     |
| 2 | 206.540 | 21.91  | 3.10  | -3.29        | 21.72          | 73.70          | 51.98  | QP     |
| 3 | 299.660 | 26.77  | 3.90  | -2.54        | 28.13          | 73.70          | 45.57  | QP     |
| 4 | 448.070 | 17.63  | 5.40  | 8.02         | 31.05          | 73.70          | 42.65  | QP     |
| 5 | 604.240 | 21.42  | 6.30  | -0.76        | 26.95          | 73.70          | 46.75  | QP     |
| 6 | 861.290 | 26.09  | 7.20  | -2.05        | 31.24          | 73.70          | 42.46  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 9  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MID)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 87.230  | 15.32 | 2.00         | 11.13          | 28.45          | 73.70  | 45.25  | QP |
| 2     | 208.480 | 22.33 | 3.12         | 1.09           | 26.54          | 73.70  | 47.16  | QP |
| 3     | 375.320 | 16.03 | 4.60         | 9.07           | 29.70          | 73.70  | 44.00  | QP |
| 4     | 493.660 | 19.00 | 6.40         | -1.03          | 24.38          | 73.70  | 49.32  | QP |
| 5     | 607.150 | 21.72 | 6.20         | -3.26          | 24.66          | 73.70  | 49.04  | QP |
| 6     | 812.790 | 24.56 | 7.00         | -3.26          | 28.30          | 73.70  | 45.40  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 7  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MIN)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 68.800  | 11.93 | 1.70         | 6.33           | 19.96          | 73.70  | 53.74  | QP |
| 2     | 216.240 | 21.86 | 3.20         | -2.04          | 23.02          | 73.70  | 50.68  | QP |
| 3     | 336.520 | 15.08 | 4.20         | 8.98           | 28.27          | 73.70  | 45.43  | QP |
| 4     | 480.080 | 18.68 | 6.05         | -2.37          | 22.36          | 73.70  | 51.34  | QP |
| 5     | 679.900 | 22.97 | 6.40         | -3.44          | 25.92          | 73.70  | 47.78  | QP |
| 6     | 882.630 | 25.28 | 7.30         | -2.64          | 29.94          | 73.70  | 43.76  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 8  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dBuV/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(MIN)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |         | Emission |          |        |        |
|---|---------|--------|-------|---------|----------|----------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading | Level    | Limits   | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dBuV)  | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1 | 53.280  | 15.05  | 1.50  | 12.67   | 29.22    | 73.70    | 44.48  | QP     |
| 2 | 191.990 | 22.07  | 3.00  | -2.22   | 22.85    | 73.70    | 50.85  | QP     |
| 3 | 337.490 | 15.53  | 4.20  | -0.77   | 18.96    | 73.70    | 54.74  | QP     |
| 4 | 488.810 | 18.80  | 6.24  | -0.96   | 24.08    | 73.70    | 49.62  | QP     |
| 5 | 639.160 | 21.22  | 6.28  | 0.53    | 28.03    | 73.70    | 45.67  | QP     |
| 6 | 820.550 | 25.07  | 7.00  | -0.75   | 31.32    | 73.70    | 42.38  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 20  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : BEVERAGE  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.   | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | (MHz)   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   |         | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 92.080  | 16.08  | 2.00  | 1.71         | 19.78          | 73.70          | 53.92  | QP     |
| 2 | 400.540 | 17.66  | 4.80  | -2.60        | 19.86          | 73.70          | 53.84  | QP     |
| 3 | 623.640 | 21.32  | 6.20  | -2.21        | 25.31          | 73.70          | 48.39  | QP     |
| 4 | 765.260 | 23.82  | 6.80  | -2.38        | 28.24          | 73.70          | 45.46  | QP     |
| 5 | 830.250 | 24.75  | 7.10  | -2.92        | 28.93          | 73.70          | 44.77  | QP     |
| 6 | 946.650 | 25.76  | 7.50  | -2.48        | 30.78          | 73.70          | 42.92  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 19  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : BEVERAGE  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 97.900  | 17.54  | 2.10  | 0.20         | 19.84          | 73.70          | 53.86  | QP     |
| 2 | 233.700 | 24.84  | 3.38  | -2.99        | 25.23          | 73.70          | 48.47  | QP     |
| 3 | 383.080 | 17.08  | 4.62  | -0.11        | 21.58          | 73.70          | 52.12  | QP     |
| 4 | 528.580 | 20.22  | 6.90  | 4.37         | 31.50          | 73.70          | 42.20  | QP     |
| 5 | 686.690 | 23.55  | 6.50  | -1.79        | 28.26          | 73.70          | 45.44  | QP     |
| 6 | 921.430 | 25.69  | 7.40  | -2.41        | 30.68          | 73.70          | 43.02  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 17  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : PIZZA  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 80.440  | 13.81  | 1.89  | -0.17        | 15.52          | 73.70          | 58.18  | QP     |
| 2 | 223.030 | 21.94  | 3.30  | -2.05        | 23.19          | 73.70          | 50.51  | QP     |
| 3 | 483.960 | 18.84  | 6.14  | -2.55        | 22.43          | 73.70          | 51.27  | QP     |
| 4 | 604.240 | 21.42  | 6.30  | 3.68         | 31.39          | 73.70          | 42.31  | QP     |
| 5 | 710.940 | 23.54  | 6.51  | -0.07        | 29.97          | 73.70          | 43.73  | QP     |
| 6 | 865.170 | 26.00  | 7.20  | -1.75        | 31.45          | 73.70          | 42.25  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 18  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : PIZZA  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 56.190  | 14.21  | 1.60  | 6.40         | 22.21          | 73.70          | 51.49  | QP     |
| 2 | 182.290 | 21.55  | 2.90  | -0.04        | 24.40          | 73.70          | 49.30  | QP     |
| 3 | 334.580 | 15.55  | 4.20  | 1.74         | 21.49          | 73.70          | 52.21  | QP     |
| 4 | 549.920 | 21.38  | 6.80  | -1.77        | 26.41          | 73.70          | 47.29  | QP     |
| 5 | 719.670 | 22.04  | 6.60  | -0.65        | 27.99          | 73.70          | 45.71  | QP     |
| 6 | 903.970 | 25.79  | 7.40  | -2.63        | 30.55          | 73.70          | 43.15  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 16  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POPCORN  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 88.200  | 15.42  | 2.00  | 0.78         | 18.20          | 73.70          | 55.50  | QP     |
| 2 | 278.320 | 25.25  | 3.80  | -2.21        | 26.84          | 73.70          | 46.86  | QP     |
| 3 | 390.840 | 17.50  | 4.80  | 0.62         | 22.92          | 73.70          | 50.78  | QP     |
| 4 | 627.520 | 21.15  | 6.31  | 1.18         | 28.64          | 73.70          | 45.06  | QP     |
| 5 | 812.790 | 24.02  | 7.00  | -2.12        | 28.90          | 73.70          | 44.80  | QP     |
| 6 | 924.340 | 24.48  | 7.40  | 2.97         | 34.85          | 73.70          | 38.85  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
County, Taiwan R.O.C. Post Code:24443  
Tel:02-26092133 Fax:02-26099303  
Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 15  
Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
Limit : 73.7 dB  $\mu$ V/m  
Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
EUT : Microwave Oven M/N:TSK-M3204MEQ  
Power Rating : 120Vac/60Hz  
Test Mode : POPCORN  
700 milliliters of waters in the beaker  
located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 63.950  | 13.06  | 1.67  | 4.55         | 19.28          | 73.70          | 54.42  | QP     |
| 2 | 238.550 | 24.38  | 3.40  | -2.08        | 25.70          | 73.70          | 48.00  | QP     |
| 3 | 463.590 | 18.86  | 5.70  | 3.17         | 27.73          | 73.70          | 45.97  | QP     |
| 4 | 619.760 | 21.24  | 6.20  | -0.22        | 27.22          | 73.70          | 46.48  | QP     |
| 5 | 798.240 | 24.92  | 6.90  | -0.95        | 30.87          | 73.70          | 42.83  | QP     |
| 6 | 935.980 | 26.53  | 7.50  | -2.83        | 31.20          | 73.70          | 42.50  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 13  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : DEFROST  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 71.710  | 12.26  | 1.80  | 10.35        | 24.41          | 73.70          | 49.29  | QP     |
| 2 | 254.070 | 24.13  | 3.60  | -2.35        | 25.38          | 73.70          | 48.32  | QP     |
| 3 | 446.130 | 17.59  | 5.40  | 7.85         | 30.84          | 73.70          | 42.86  | QP     |
| 4 | 569.320 | 21.17  | 6.50  | 6.19         | 33.87          | 73.70          | 39.83  | QP     |
| 5 | 735.190 | 22.18  | 6.68  | 10.39        | 39.25          | 73.70          | 34.45  | QP     |
| 6 | 891.360 | 25.06  | 7.30  | 9.65         | 42.01          | 73.70          | 31.69  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 14  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : DEFROST  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 65.890  | 12.69 | 1.70         | 18.54          | 32.93          | 73.70  | 40.77  | QP |
| 2     | 247.280 | 24.78 | 3.50         | 7.56           | 35.84          | 73.70  | 37.86  | QP |
| 3     | 441.280 | 17.40 | 5.30         | -0.87          | 21.82          | 73.70  | 51.88  | QP |
| 4     | 576.110 | 21.86 | 6.40         | 4.70           | 32.96          | 73.70  | 40.74  | QP |
| 5     | 728.400 | 22.41 | 6.60         | 6.57           | 35.58          | 73.70  | 38.12  | QP |
| 6     | 938.890 | 26.70 | 7.50         | -2.22          | 31.99          | 73.70  | 41.71  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 1  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : COOK(POTATO)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 92.080  | 16.08  | 2.00  | 2.03         | 20.10          | 73.70          | 53.60  | QP     |
| 2 | 260.860 | 24.58  | 3.60  | -2.14        | 26.04          | 73.70          | 47.66  | QP     |
| 3 | 435.460 | 17.41  | 5.30  | 0.12         | 22.83          | 73.70          | 50.87  | QP     |
| 4 | 611.030 | 21.41  | 6.30  | 6.55         | 34.26          | 73.70          | 39.44  | QP     |
| 5 | 754.590 | 23.51  | 6.70  | 1.32         | 31.53          | 73.70          | 42.17  | QP     |
| 6 | 967.990 | 26.90  | 7.69  | -5.16        | 29.43          | 73.70          | 44.27  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 2  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : COOK(POTATO)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 60.070  | 13.44 | 1.60         | 7.25           | 22.28          | 73.70  | 51.42  | QP |
| 2     | 149.310 | 22.02 | 2.60         | -1.95          | 22.67          | 73.70  | 51.03  | QP |
| 3     | 285.110 | 26.17 | 3.80         | -1.62          | 28.34          | 73.70  | 45.36  | QP |
| 4     | 581.930 | 21.72 | 6.30         | -1.65          | 26.37          | 73.70  | 47.33  | QP |
| 5     | 754.590 | 24.69 | 6.70         | -1.19          | 30.20          | 73.70  | 43.50  | QP |
| 6     | 954.410 | 27.16 | 7.60         | -2.29          | 32.47          | 73.70  | 41.23  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 3  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : REHEAT(CASSEROLE)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 92.080  | 16.08  | 2.00  | 1.62         | 19.69          | 73.70          | 54.01  | QP     |
| 2 | 193.930 | 21.70  | 3.00  | -2.27        | 22.43          | 73.70          | 51.27  | QP     |
| 3 | 337.490 | 15.09  | 4.20  | 1.61         | 20.91          | 73.70          | 52.79  | QP     |
| 4 | 466.500 | 18.18  | 5.80  | -2.88        | 21.10          | 73.70          | 52.60  | QP     |
| 5 | 581.930 | 20.91  | 6.30  | -1.55        | 25.66          | 73.70          | 48.04  | QP     |
| 6 | 800.180 | 24.14  | 6.90  | -3.04        | 28.00          | 73.70          | 45.70  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 4  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : REHEAT(CASSEROLE)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|       |         | Ant.  | Cable        |                | Emission       |        |        |    |
|-------|---------|-------|--------------|----------------|----------------|--------|--------|----|
| Freq. | Factor  | Loss  | Reading      | Level          | Limits         | Margin | Remark |    |
| (MHz) | (dB/m)  | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |    |
| 1     | 102.750 | 17.72 | 2.10         | -2.75          | 17.08          | 73.70  | 56.62  | QP |
| 2     | 197.810 | 22.65 | 3.00         | -1.76          | 23.89          | 73.70  | 49.81  | QP |
| 3     | 353.980 | 15.84 | 4.30         | 1.87           | 22.02          | 73.70  | 51.68  | QP |
| 4     | 526.640 | 20.26 | 6.90         | -1.55          | 25.61          | 73.70  | 48.09  | QP |
| 5     | 709.000 | 22.05 | 6.60         | 0.81           | 29.46          | 73.70  | 44.24  | QP |
| 6     | 933.070 | 26.27 | 7.50         | -2.20          | 31.57          | 73.70  | 42.13  | QP |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 6  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : COMBI  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 38.730  | 21.21  | 1.20  | -3.17        | 19.24          | 73.70          | 54.46  | QP     |
| 2 | 224.000 | 21.96  | 3.30  | -2.71        | 22.56          | 73.70          | 51.14  | QP     |
| 3 | 315.180 | 14.71  | 4.01  | 9.95         | 28.67          | 73.70          | 45.03  | QP     |
| 4 | 502.390 | 19.00  | 6.60  | 0.56         | 26.15          | 73.70          | 47.55  | QP     |
| 5 | 697.360 | 23.32  | 6.50  | 5.84         | 35.66          | 73.70          | 38.04  | QP     |
| 6 | 911.730 | 24.99  | 7.40  | -2.38        | 30.01          | 73.70          | 43.69  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 5  
 Dis. / Ant. : 3m VBA6106A/UHALP9108-A Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : COMBI  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   |         | Ant.   | Cable |              | Emission       |                |        |        |
|---|---------|--------|-------|--------------|----------------|----------------|--------|--------|
|   | Freq.   | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark |
|   | (MHz)   | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |        |
| 1 | 80.440  | 14.22  | 1.89  | 10.64        | 26.75          | 73.70          | 46.95  | QP     |
| 2 | 173.560 | 20.30  | 2.80  | 10.62        | 33.72          | 73.70          | 39.98  | QP     |
| 3 | 299.660 | 26.86  | 3.90  | -2.63        | 28.13          | 73.70          | 45.57  | QP     |
| 4 | 411.210 | 17.08  | 4.90  | 2.59         | 24.57          | 73.70          | 49.13  | QP     |
| 5 | 604.240 | 21.69  | 6.30  | 9.85         | 37.84          | 73.70          | 35.86  | QP     |
| 6 | 835.100 | 26.32  | 7.10  | -2.39        | 31.03          | 73.70          | 42.67  | QP     |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 27  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.     | Ant.   | Cable |              | Emission       |                |        |         |
|---|-----------|--------|-------|--------------|----------------|----------------|--------|---------|
|   | (MHz)     | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark  |
|   |           | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |
| 1 | 4944.800  | 33.96  | 9.10  | -6.39        | 36.67          | 73.70          | 37.03  | Average |
| 2 | 7417.200  | 37.20  | 11.58 | -5.68        | 43.09          | 73.70          | 30.61  | Average |
| 3 | 9889.600  | 38.57  | 12.89 | -7.94        | 43.51          | 73.70          | 30.19  | Average |
| 4 | 12362.000 | 38.91  | 15.01 | -8.14        | 45.78          | 73.70          | 27.92  | Average |
| 5 | 13835.000 | 42.53  | 16.12 | -5.68        | 52.97          | 73.70          | 20.73  | Average |
| 6 | 14834.400 | 38.83  | 16.90 | -4.34        | 51.40          | 73.70          | 22.30  | Average |
| 7 | 17306.800 | 43.96  | 17.37 | -6.27        | 55.05          | 73.70          | 18.65  | Average |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 26  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the center of the oven

|   | Freq.     | Ant.   | Cable |              | Emission       |                |        |         |
|---|-----------|--------|-------|--------------|----------------|----------------|--------|---------|
|   | (MHz)     | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark  |
|   |           | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |
| 1 | 4944.800  | 33.96  | 9.10  | -2.03        | 41.03          | 73.70          | 32.67  | Average |
| 2 | 6253.000  | 34.85  | 10.40 | -6.15        | 39.10          | 73.70          | 34.60  | Average |
| 3 | 7417.200  | 37.20  | 11.58 | -7.55        | 41.22          | 73.70          | 32.48  | Average |
| 4 | 9889.600  | 38.57  | 12.89 | -8.87        | 42.58          | 73.70          | 31.12  | Average |
| 5 | 12362.000 | 38.91  | 15.01 | -8.69        | 45.23          | 73.70          | 28.47  | Average |
| 6 | 14834.400 | 38.83  | 16.90 | -6.80        | 48.94          | 73.70          | 24.76  | Average |
| 7 | 17306.800 | 43.96  | 17.37 | -10.97       | 50.36          | 73.70          | 23.34  | Average |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw




Site no. : A/C Chamber Data no. : 28  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB  $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4912.600 | 33.89  | 9.16       | 7.18         | 50.23          | 73.70          | 23.47  | Average |  |
| 2 7394.080 | 37.15  | 11.54      | 4.86         | 53.55          | 73.70          | 20.15  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 29  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 700 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4890.640 | 33.82  | 9.16       | -1.99        | 41.00          | 73.70          | 32.70  | Average |  |
| 2 7386.760 | 37.15  | 11.54      | 0.90         | 49.59          | 73.70          | 24.11  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 32  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the center of the oven

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4905.280 | 33.85  | 9.16       | 5.86         | 48.88          | 73.70          | 24.82  | Average |  |
| 2 7350.160 | 37.05  | 11.48      | 6.85         | 55.37          | 73.70          | 18.33  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 33  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the center of the oven

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4897.960 | 33.85  | 9.16       | -1.96        | 41.06          | 73.70          | 32.64  | Average |  |
| 2 7357.480 | 37.05  | 11.48      | -0.62        | 47.90          | 73.70          | 25.80  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)


Site no. : A/C Chamber Data no. : 31  
 Dis. / Ant. : 3m 3115 Ant. pol. : HORIZONTAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant. Cable |              | Emission       |                |        |         |  |
|------------|--------|------------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss       | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)       | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4883.320 | 33.82  | 9.15       | -1.41        | 41.56          | 73.70          | 32.14  | Average |  |
| 2 7320.880 | 37.00  | 11.44      | -0.01        | 48.43          | 73.70          | 25.27  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.



AUDIX Corp. EMC Laboratory  
 No.53-11, Tin-fu Tsun, Lin-kou Hsiang, Taipei  
 County, Taiwan R.O.C. Post Code:24443  
 Tel:02-26092133 Fax:02-26099303  
 Email:ttemc@ttemc.com.tw



Trace: (Discrete)

Site no. : A/C Chamber Data no. : 30  
 Dis. / Ant. : 3m 3115 Ant. pol. : VERTICAL  
 Limit : 73.7 dB $\mu$ V/m  
 Env. / Ins. : 8593EM 22°C/41% Engineer : Cater Chou  
 EUT : Microwave Oven M/N:TSK-M3204MEQ  
 Power Rating : 120Vac/60Hz  
 Test Mode : POWER(HI)  
 300 milliliters of waters in the beaker  
 located in the right front corner

|            |        | Ant.  | Cable        |                | Emission       |        |         |  |
|------------|--------|-------|--------------|----------------|----------------|--------|---------|--|
| Freq.      | Factor | Loss  | Reading      | Level          | Limits         | Margin | Remark  |  |
| (MHz)      | (dB/m) | (dB)  | (dB $\mu$ V) | (dB $\mu$ V/m) | (dB $\mu$ V/m) | (dB)   |         |  |
| 1 4876.000 | 33.78  | 9.15  | -1.39        | 41.54          | 73.70          | 32.16  | Average |  |
| 2 7328.200 | 37.00  | 11.44 | -1.57        | 46.87          | 73.70          | 26.83  | Average |  |

Remarks: 1. Emission Level=Antenna Factor + Cable Loss + Reading  
 2. The emission levels that are 20dB below the official  
 limit are not reported.

## **8. DEVIATION TO TEST SPECIFICATIONS**

**【NONE】**

## 9. PHOTOGRAPHS

### 9.1. Photo of Input Power Measurement

Test Model: TSK-M3204ME



Test Model: TSK-M3204MEQ



## 9.2. Photo of Output Frequency Measurement

Test Model: TSK-M3204ME



Test Model: TSK-M3204MEQ



### 9.3. Photo of Frequency Measurement

Test Model: TSK-M3204ME



Test Model: TSK-M3204MEQ



#### 9.4. Photos of Conducted Emission Measurement

Test Model: TSK-M3204ME



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT

Test Model: TSK-M3204MEQ



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT

9.5. Photos of Radiated Measurement at Semi-Anechoic Chamber (Below 1GHz)

Test Model: TSK-M3204ME



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT

Test Model: TSK-M3204MEQ



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT

9.6. Photos of Radiated Measurement at Semi-Anechoic Chamber (Above 1GHz)

Test Model: TSK-M3204ME



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT

Test Model: TSK-M3204MEQ



FRONT VIEW OF RADIATED MEASUREMENT



BACK VIEW OF RADIATED MEASUREMENT