



Electrical (EMC)

DATE: 06 August 2003

I.T.L. (PRODUCT TESTING) LTD.

EMC Test

for

RACAM - TECH LTD.*

* See customer's statement on page 5.

Equipment under test:

Terminal Unit

TU

Approved by: _____

I. Raz, EMC Laboratory Manager

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.

Spurious Radiated Emission

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal
Test Distance: 3 meters

Frequency range: 30 MHz to 1.0 GHz
Detector: Peak

Frequency (MHz)	Peak Amp (1) (dBμV/m)	D.C.F. (2) (dB)	Correction (3) (dB)	Final Result (4) (dBμV/m)	Specification (dBμV/m)	Margin (dB μV/m)
73.60	18.2	-14.0	10.3	+4.2	40.0	-35.8
114.43	19.5	-14.0	13.3	+5.5	43.5	-38.0
156.75	21.4	-14.0	15.2	+7.4	43.5	-36.1
170.30	21.7	-14.0	15.5	+7.7	43.5	-35.8
248.19	27.3	-14.0	20.4	+13.3	46.0	-32.7
274.31	27.9	-14.0	21.7	+13.9	46.0	-32.1
325.34	23.6	-14.0	15.7	+9.6	46.0	-36.4
609.18	30.6	-14.0	22.4	+16.6	46.0	-29.4
968.03	36.3	-14.0	28.3	+22.3	54.0	-31.7

**Figure 1. Spurious Radiated Emission. Antenna Polarization: HORIZONTAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

(1) "Peak Amp." (dBμV/m) includes the "correction" numbers.

(2) "Duty Cycle Factor (D.C.F.)= $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14 \text{ dB}$ (See Section 4.2 of this report).

(3) "Correction" (dB) = Test Antenna Correction Factor(dB) + Coax Cable.

(4) "Final Result" (dBμV/m)=Peak Amp. (dBμV/m)+D.C.F. (dB).

Spurious Radiated Emission

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Vertical
Test Distance: 3 meters

Frequency range: 30 MHz to 1.0 GHz
Detector: Peak

Frequency (MHz)	Peak Amp (1) (dBμV/m)	D.C.F. (2) (dB)	Correction (3) (dB)	Final Result (4) (dBμV/m)	Specification (dBμV/m)	Margin (dB μV/m)
74.40	23.6	-14.0	10.3	+9.6	40.0	-30.4
130.63	19.5	-14.0	13.9	+5.5	60.3 (5)	-54.8
143.71	20.1	-14.0	14.6	+6.1	60.3 (5)	-54.2
158.75	21.1	-14.0	15.2	+7.1	43.5	-36.4
248.30	27.0	-14.0	20.4	+13.0	46.0	-33.0
274.34	28.0	-14.0	21.7	+14.0	46.0	-32.0
325.34	21.9	-14.0	15.7	+7.9	46.0	-38.1
609.18	29.4	-14.0	22.4	+15.4	46.0	-30.6
968.03	35.6	-14.0	28.3	+21.6	54.0	-32.4

**Figure 2. Spurious Radiated Emission. Antenna Polarization: VERTICAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

- (1) "Peak Amp." (dBμV/m) includes the "correction" numbers.
- (2) "Duty Cycle Factor (D.C.F.)= $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14dB$ (See Section 4.2 of this report).
- (3) "Correction" (dB) = Test Antenna Correction Factor(dB) + Coax Cable.
- (4) "Final Result" (dBμV/m)=Peak Amp. (dBμV/m)+D.C.F. (dB).
- (5) Out of restricted band signal: Limit = fundamental limit (80.3dB)-20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal
Test Distance: 3 meters

Frequency range: 1 GHz to 2.9 GHz
Detector: Average

Frequency (MHz)	Peak Amp (1) (dBμV/m)	D.C.F. (2) (dB)	Correction (3) (dB)	Final Result (4) (dBμV/m)	Avg. Specification (dBμV/m)	Margin (dB μV/m)
1253.92	49.6	-14.0	34.1	+35.6	60.3 (5)	-24.7
1306.20	45.6	-14.0	34.5	+31.6	54.0	-16.6
1436.72	45.5	-14.0	35.8	+31.5	54.0	-22.5
1671.90	49.2	-14.0	37.7	+35.2	54.0	-18.8
1698.04	47.8	-14.0	37.9	+33.8	54.0	-20.2
2246.57	52.2	-14.0	41.6	+38.2	54.0	-15.8

**Figure 10. Radiated Emission. Antenna Polarization: HORIZONTAL.
Detector: Average**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

(1) "Peak Amp." (dBμV/m) includes the "correction" numbers.

(2) "Duty Cycle Factor (D.C.F.)" = $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14 \text{ dB}$ (See Section 4.2 of this report).

(3) "Correction" (dB) = Test Antenna Correction Factor(dB) + Coax Cable.

(4) "Final Result" (dBμV/m)=Peak Amp. (dBμV/m)+D.C.F. (dB).

(5) Out of restricted band signal: Limit = fundamental limit (80.3dB)-20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal
Test Distance: 3 meters

Frequency range: 1 GHz to 2.9 GHz
Detector: Peak

Frequency (MHz)	Peak Amp (dB μ V/m)	Correction (dB)	Specification (dB μ V/m)	Margin (dB μ V/m)
1253.92	49.6	34.1	80.3 (Note*)	-30.7
1306.20	45.6	34.5	74.0	-28.4
1436.72	45.5	35.8	74.0	-28.5
1671.90	49.2	37.7	74.0	-24.8
1698.04	47.8	37.9	74.0	-26.2
2246.57	52.2	41.6	74.0	-21.8

**Figure 3. Radiated Emission. Antenna Polarization: HORIZONTAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note* Out of restricted band signal: Limit = Average limit + 20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal
Test Distance: 3 meters

Frequency range: 2.9 GHz to 4.2 GHz
Detector: Peak

Freq. (MHz)	Peak Amp (dBμV)	Correction Factors			Peak. Specification (dB μV/m)	Peak Final Result FR (P)* (dB μV/m) See Note *	Peak. Margin (dB)
		Antenna AF (dB)	Cable CF (dB)	Low Noise Amp (dB)			
2925.80	45.0	32.6	1.8	30.5	80.3 (Note **)	48.9	-31.4
3343.80	48.2	33.4	2.0	30.5	80.3 (Note **)	53.1	-27.2
3761.80	40.6	34.0	2.4	30.5	74.0	46.5	-23.5

**Figure 4. Radiated Emission. Antenna Polarization: HORIZONTAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note *: In the frequency range above 2.9 GHz, the field strength was manually calculated by using the following equation:

$$FR(P) = \text{Peak} + AF + CF - PF$$

Where: FR (P) is final peak detector result.

Peak is peak detector measurement.

AF is antenna factor.

CF is cable factor.

PF is preamplifier factor.

Note** Out of restricted band signal: Limit = Average limit + 20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Horizontal
Test Distance: 3 meters

Frequency range: 2.9 GHz to 4.2 GHz
Detector: Average

Freq. (MHz)	Peak Amp (dBμV)	D.C.F. (See Note**)	Correction Factors			AVG Specification (dB μV/m)	AVG Final Result FR (A) (dB μV/m) See Note *	AVG Margin (dB)
			Antenna AF (dB)	Cable CF (dB)	Low Noise Amp (dB)			
2925.80	45.0	-14.0	32.6	1.8	30.5	60.3 (Note***)	31.3	-29.0
3343.80	48.2	-14.0	33.4	2.0	30.5	60.3 (Note***)	39.1	-21.2
3761.80	40.6	-14.0	34.0	2.4	30.5	54.0	32.5	-21.5

**Figure 13. Radiated Emission. Antenna Polarization: HORIZONTAL.
Detector: Average**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note*: In the frequency range above 2.9 GHz, the field strength was manually calculated by using the following equation:

$$FR(A) = \text{Peak} + \text{D.C.F.} + \text{AF} + \text{CF} - \text{LN}$$

Where: FR(A) is final average detector result.

Peak is Peak detector measurement.

AF is antenna factor.

CF is cable factor.

LN is low noise amplifier factor.

Note**: "Duty Cycle Factor" (D.C.F.) = $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14 \text{ dB}$ (See Section 4.2 of this report).

Note***: Out of restricted band signal:

$$\text{Limit} = \text{fundamental limit (80.3dB)} - 20 \text{ dB}$$

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Vertical
Test Distance: 3 meters

Frequency range: 1 GHz to 2.9 GHz
Detector: Average

Frequency (MHz)	Peak Amp (1) (dBμV/m)	D.C.F. (2) (dB)	Correction (3) (dB)	Final Result (4) (dBμV/m)	Avg. Specification (dBμV/m)	Margin (dB μV/m)
1253.92	49.6	-14.0	34.1	+35.6	60.3 (5)	-24.7
1306.20	44.5	-14.0	34.5	+30.5	54.0	-23.5
1436.72	45.5	-14.0	35.8	+31.5	54.0	-22.5
1671.90	49.7	-14.0	37.7	+35.7	54.0	-18.3
1698.04	48.4	-14.0	37.9	+34.4	54.0	-19.6
2246.57	53.6	-14.0	41.6	+39.6	54.0	-14.4

**Figure 14. Radiated Emission. Antenna Polarization: VERTICAL.
Detector: Average**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

(1) "Peak Amp." (dBμV/m) includes the "correction" numbers.

(2) "Duty Cycle Factor" (D.C.F.)= $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14 \text{ dB}$ (See Section 4.2 of this report).

(3) "Correction" (dB) = Test Antenna Correction Factor(dB) + Coax Cable.

(4) "Final Result" (dBμV/m)=Peak Amp. (dBμV/m)+D.C.F. (dB).

(5) Out of restricted band signal: Limit = fundamental limit (80.3dB)-20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Vertical
Test Distance: 3 meters

Frequency range: 1 GHz to 2.9 GHz
Detector: Peak

Frequency (MHz)	Peak Amp (dB μ V/m)	Correction (dB)	Specification (dB μ V/m)	Margin (dB μ V/m)
1253.93	49.6	34.1	80.3 (Note *)	-30.7
1306.20	44.5	34.5	74.0	-29.5
1436.72	45.5	35.8	74.0	-28.5
1671.89	49.7	37.7	74.0	-24.3
1698.04	48.4	37.9	74.0	-25.6
2246.57	53.6	41.6	74.0	-20.4

**Figure 5. Radiated Emission. Antenna Polarization: VERTICAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note* Out of restricted band signal: Limit = Average limit + 20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Vertical
Test Distance: 3 meters

Frequency range: 2.9 GHz to 4.2 GHz
Detector: Peak

Freq. (MHz)	Peak Amp (dBμV/m)	Correction Factors			Peak. Specification (dB μV/m)	Peak Final Result FR (P) (dB μV/m) See Note *	Peak. Margin (dB)
		Antenna AF (dB)	Cable CF (dB)	Low Noise Amp (dB)			
2925.80	43.7	32.6	1.8	30.5	80.3**	47.6	-32.4
3343.80	47.4	33.4	2.0	30.5	80.3**	52.3	-28.0
3761.80	38.9	34.0	34.0	30.5	74.0	44.8	-29.2

**Figure 6. Radiated Emission. Antenna Polarization: VERTICAL.
Detector: Peak**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note*: In the frequency range above 2.9 GHz, the field strength was manually calculated by using the following equation:

$$FR(P) = Peak + AF + CF - PF$$

Where: FR (P) is final peak detector result,

Peak is peak detector measurement,

AF is antenna factor,

CF is cable factor,

PF is preamplifier factor.

Note** Out of restricted band signal: Limit = Average limit + 20dB

Spurious Radiated Emission Above 1 GHz

E.U.T Description Terminal Unit
Type TU
Serial Number: 00378

Specification: F.C.C., Part 15, Subpart C

Antenna Polarization: Vertical
Test Distance: 3 meters

Frequency range: 2.9 GHz to 4.2 GHz
Detector: Average

Freq. (MHz)	Peak Amp (dBμV)	D.C.F. (See Note**) (dB)	Correction Factors			AVG Specification (dB μV/m)	Final Result FR (A) (dB μV/m) See Note *	AVG Margin (dB)
			Antenna AF (dB)	Cable CF (dB)	Low Noise Amp (dB)			
2925.80	43.7	-14.0	32.6	1.8	30.5	60.3 (Note***)	33.6	-26.7
3343.80	47.4	-14.0	33.4	2.0	30.5	60.3 (Note***)	38.3	-22.0
3761.80	38.9	-14.0	34.0	2.4	30.5	54.0	30.8	-23.2

**Figure 17. Radiated Emission. Antenna Polarization: VERTICAL
Detector: Average**

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

Note*: In the frequency range above 2.9 GHz, the field strength was manually calculated by using the following equation:

$$FR(A) = \text{Peak} - DCF + AF + CF - LN$$

Where: FR(A) is average detector result,

Peak is Peak detector measurement,

AF is antenna factor,

CF is cable factor,

LN is low noise amplifier factor.

Note**: "Duty Cycle Factor" (D.C.F.) = $20 \log \frac{20(m \text{ sec})}{100(m \text{ sec})} = -14dB$ (See Section 4.2 of this report).

Note***: Out of restricted band signal:

$$\text{Limit} = \text{fundamental limit (80.3dB)} - 20dB$$