FCC RADIO TEST REPORT

Applicant	:	Elo Touch Solutions, Inc.
Address	:	670 N. McCarthy Blvd., Suite 100, Milpitas, CA 95035, USA
Equipment	:	Touch All-in-One Computer
Model No.	:	ESY22I1D
Trade Name	:	Elo or elo
FCC ID	:	RBWESY22I1DNFC

I HEREBY CERTIFY THAT :

The sample was received on Mar. 01, 2024 and the testing was completed on May. 15, 2024 at Cerpass Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of Cerpass Technology Corp., the test report shall not be reproduced except in full.

Approved by:

Mark Liao / Supervisor

Laboratory Accreditation:

Cerpass Technology Corporation Test Laboratory

CONTENTS

1. Summary of Test Procedure and Test Results 5
1.1 Applicable Standards 5
2. Test Configuration of Equipment under Test 6
2.1 Feature of Equipment under Test 6
2.2 Carrier Frequency of Channes 7
2.3 Test Mode & Test Software 8
2.4 Description of Test System 9
2.5 General Information of Test 10
2.6 Measurement Uncertainty 11
3. Test Equipment and Ancillaries Used for Tests 12
4. Antenna Requirements 14
4.1 Standard Applicable 14
4.2 Antenna Construction and Directional Gain 14
5. Frequency Hopping System Requirements 15
5.1 Frequency Hopping Requirement 15
5.2 EUT Hopping System 16
5.3 Pseudorandom Frequency Hopping Sequence 16
6. Test of AC Power Line Conducted Emission 17
6.1 Test Limit 17
6.2 Test Procedures 17
6.3 Typical Test Setup 18
6.4 Test Result and Data 19
6.5 Test Photographs 21
7. Test of Radiated Spurious Emission 22
7.1 Test Limit 22
7.2 Test Procedures 23
7.3 Typical Test Setup 24
7.4 Test Result and Data (9kHz ~ 30MHz) 25
7.5 Test Result and Data (30MHz ~ 1GHz) 25
7.6 Test Result and Data (1GHz ~ 25GHz) 27
7.7 Restricted Bands of Operation 39
7.8 Test Photographs (30MHz ~ 1GHz) 40
7.9 Test Photographs (1GHz ~ 25GHz) 41
8. Test of Conducted Spurious Emission 43
8.1 Test Limit 43
8.2 Test Procedure 43
8.3 Test Setup Layout 43
8.4 Test Result and Data 43
9. 20dB Bandwidth Measurement Data 51
9.1 Test Limit 51
9.2 Test Procedures 51
9.3 Test Setup Layout 51

9.4 Test Result and Data 52
10. Carrier Frequency Separation 55
10.1 Test Limit 55
10.2 Test Procedures 55
10.3 Test Setup Layout 55
10.4 Test Result and Data 56
11. Dwell Time on each channel 59
11.1 Test Limit 59
11.2 Test Procedures 59
11.3 Test Setup Layout 59
11.4 Test Result and Data 60
12. Number of Hopping Channels 63
12.1 Test Limit 63
12.2 Test Procedures 63
12.3 Test Setup Layout 63
12.4 Test Result and Data 63
13. Maximum Average Output Power 65
13.1 Test Limit 65
13.2 Test Procedures 65
13.3 Test Setup Layout 65
13.4 Test Result and Data 66
14. Radio Frequency Exposure 67
14.1 Applicable Standards 67
14.1 EUT Specification 68
14.2 Result 68

History of this test report

Report No.	Issued Date	Description
24030030-TRFCC01	Jun. 07, 2024	Original

1. Summary of Test Procedure and Test Results

1.1 Applicable Standards

ANSI C63.10:2013

FCC Rules and Regulations Part 15 Subpart C §15.247

FCC Rule	. Description of Test	Result
15.203	. Antenna Requirement	PASS
15.247(a)(1)	.Pseudorandom Frequency Hopping Sequence	PASS
15.207	. AC Power Line Conducted Emission	PASS
15.209 15.205	. Radiated Spurious Emission	PASS
15.247(d)	. Conducted Spurious Emission	PASS
15.247(a)(1)	. Channel Carrier Frequencies Separation	PASS
15.247(a)(1)	. 20dB Bandwidth	PASS
15.247(a)(1)	. Dwell Time	PASS
15.247(b)	. Number of Hopping Channels	PASS
15.247(b)	. Output Power	PASS
2.1091	. Radio Frequency Exposure	PASS

*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement,measurement uncertainty evaluation is not considered.

2. Test Configuration of Equipment under Test

2.1 Feature of Equipment under Test

Operation Frequency Range	NFC: 13.553MHz~13.567MHz BT / BLE: 2400-2483.5MHz 802.11b/g/n: 2400-2483.5MHz 802.11a/n/ac: 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz
Center Frequency Range	NFC: 13.56MHz BT / BLE: 2402MHz-2480MHz 802.11b/g/n: 2412MHz-2462MHz 802.11a/n/ac: 5180-5240MHz, 5260-5320MHz, 5500-5700MHz, 5745-5825MHz
Modulation Type	NFC: ASK BT: GFSK, π/4-DQPSK, 8DPSK BLE: GFSK WLAN: 802.11b: CCK, DQPSK, DBPSK 802.11g/n: BPSK, QPSK, 16QAM, 64QAM 802.11a: BPSK, QPSK, 16QAM, 64QAM 802.11ac: BPSK, QPSK, 16QAM, 64QAM, 256QAM
Modulation Technology	DSSS, OFDM, FHSS, DTS
Data Rate	BT: GFSK: 1Mbps, π/4-DQPSK: 2Mbps, 8DPSK: 3Mbps BLE: GFSK: 1Mbps WLAN: 2.4GHz: 802.11b: 1, 2, 5.5, 11Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 5GHz: 802.11a: 6, 9, 12, 18, 24, 36, 48, 54Mbps 802.11n: MCS0 – MCS15, HT20/40 802.11ac: MCS0 – MCS9, VHT20/40/80
Antenna Type	NFC: Loop Antenna BT/BLE/2.4G/5G: Dipole Antenna
Antenna Gain	For NFC: 0dBi For BT / BLE: 2400-2480MHz: ANT A: 4.45dBi For WLAN: 2400-2500MHz: ANT A: 4.45dBi, ANT B: 2.5dBi 5150-5250MHz: ANT A: 3.79dBi, ANT B: 4.80dBi 5250-5350MHz: ANT A: 3.62dBi, ANT B: 4.98dBi 5471-5725MHz: ANT A: 2.12dBi, ANT B: 5.87dBi 5725-5850MHz: ANT A: 1.87dBi, ANT B: 5.97dBi
Adapter	Brand: DELTA Model: ADP-65JH HB
	Brand: BILLION Model: BA090-190474MBX
	Brand: BILLION Model: BA070-190342MBX
Panel	Brand: LG Model: LM215WF3
	Brand: AUO Model: M215HAN01.2

Firmware Number	22in-I-Series-4
Serial Number	SWEP_sdm660la50_v12.047.03.p_01

Note:
1. EUT support TPC Function.
2. EUT support Client Mode without radar detection.
3. EUT WLAN 2.4GHz 802.11b and 802.11g 1TX diversity
4. WLAN and BT can simultaneously transmission.
5. For more details, please refer to the User's manual of the EUT.
6. Panel (Brand: LG, Model: LM215WF3) is worst case, hence used at test report.

2.2 Carrier Frequency of Channes

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
***00**	**2402**	20	2422	40	2442	60	2462
01	2403	21	2423	41	2443	61	2463
02	2404	22	2424	42	2444	62	2464
03	2405	23	2425	43	2445	63	2465
04	2406	24	2426	44	2446	64	2466
05	2407	25	2427	45	2447	65	2467
06	2408	26	2428	46	2448	66	2468
07	2409	27	2429	47	2449	67	2469
08	2410	28	2430	48	2450	68	2470
09	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	***78**	**2480**
19	2421	***39**	**2441**	59	2461	---	---

Note: Channels remarked * are selected to perform test.

2.3 Test Mode & Test Software

a. During testing, the interface cables and equipment positions were varied according to ANSI C63.10
b. The complete test system included Notebook and EUT for RF test.
c. An executive program, " QRCT ver.4.0.00189.0" under Windows OS system was executed to transmit and receive data via Bluetooth.
d. The following test modes were performed for the test:

Conducted Emissions from the AC mains power ports	
Test Mode	Operating Description
1	GFSK (1Mbps) , From Adapter
2	π/4-DQPSK (2Mbps) , From Adapter
3	8DPSK (3Mbps) , From Adapter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (Below1GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) , From Adapter
2	π/4-DQPSK (2Mbps) , From Adapter
3	8DPSK (3Mbps) , From Adapter
caused "Test Mode 1" generated the worst case, it was reported as the final data.	
Radiation Emissions (1GHz ~ 25GHz)	
Test Mode	Operating Description
1	GFSK (1Mbps) , From Adapter
2	π/4-DQPSK (2Mbps) , From Adapter
3	8DPSK (3Mbps) , From Adapter
caused "Test Mode 1, 3" generated the worst case, they were reported as the final data.	

Note:
1.There are two kinds of test voltage: AC 120V / 60Hz and AC 240V / 60Hz.
For AC Power Line Conducted Emission, AC 120V / 60Hz is worst case.
For Radiated Spurious Emission, AC 120V / 60Hz is worst case.

2.There are three types of Adapters with the shipment, After engineering evaluation, Model: ADP-65JH HB are worst case, hence, are used at test report.

Modulation Type	TX CONFIGURATION
GFSK	1TX
π /4-DQPSK	1TX
8DPSK	1TX

2.4 Description of Test System

RF Conducted				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	lenovo	S1GL2W	N/A	N/A
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A
Radiated Emissions				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5470	N/A	Adapter / 1.8m / NS
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A
AC Power Line Conducted Emission				
Equipment	Brand	Model	Length/Type	Power cord/Length/Type
Notebook	DELL	Latitude E5470	N/A	Adapter / 1.8m / NS
USB Cable (A to A)	BENEVO	E210567AWM	1m / NS	N/A

2.5 General Information of Test

☒ Test Site	Cerpass Technology Corporation Test Laboratory Address: No.10, Ln. 2, Lianfu St., Luzhu Dist., Taoyuan City 33848, Taiwan (R.O.C.) Tel: +886-3-3226-888 Fax: +886-3-3226-881	
	FCC	TW1439, TW1079
	IC	4934E-1, 4934E-2
Frequency Range Investigated	Conducted: from 150kHz to 30 MHz Radiation: from 9kHz to 25,000MHz	
Test Distance	The test distance of radiated emission from antenna to EUT is 3 M.	

Test Item	Test Site	Test period	Environmental Conditions	Tested By
RF Conducted	RFCON01-NK	2024/04/08	23.8℃ / 62%	Leon Huang
Radiated Emissions	3M02-NK	2024/03/12	19.3℃ / 47%	Leon Huang
Radiated Emissions	3M02-NK	2024/05/15	22.1℃ / 36%	Leon Huang
AC Power Line Conducted Emission	CON02-NK	2024/03/21	21.7℃ / 47%	Leon Huang

2.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.12dB
Radiated Spurious Emission(9KHz~30MHz)	±3.5dB
Radiated Spurious Emission(30MHz~1GHz)	±5.1dB
Radiated Spurious Emission(1GHz~25GHz)	±5.2dB
Conducted Spurious Emission	±2.1dB
6dB Bandwidth	±5.4%
20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.5%
Peak Output Power(Conducted Power Meter)	±1.1dB
Dwell Time / Deactivation Time	±7.6%
Power Spectral Density	±2.0dB
Duty Cycle	±3.5%

3. Test Equipment and Ancillaries Used for Tests

Test Item	Radiated Emissions				
Test Site	Semi Anechoic Room(3M02-NK)				
Instrument	**Manufacturer**	**Model No**	**Serial No**	**Calibration Date**	**Valid Date**
Bilog Antenna	Schwarzbeck	VULB9168	369	2024/02/19	2025/02/18
Active Loop Antenna	Schwarzbeck	FMZB 1513	414	2024/01/16	2025/01/15
Horn Antenna	EMCO	3115	31601	2023/10/18	2024/10/17
Horn Antenna	EMCO	3116	31974	2023/10/16	2024/10/15
EMI Receiver	ROHDE & SCHWARZ	ESCI	101423	2023/07/05	2024/07/04
Spectrum Analyzer	ROHDE & SCHWARZ	FSV 40-N	102151	2023/08/15	2024/08/14
Preamplifier	Agilent	8449B	3008A01954	2024/03/01	2025/02/28
Preamplifier	EMC INSTRUMENTS	EMC184045	980065	2023/10/13	2024/10/12
Preamplifier	EM Electronics corp.	EM330	60659	2024/02/17	2025/02/16
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2023/07/31	2024/07/30
Cable-3in1(30M-1G)	HARBOUR INDUSTRIES	LL142	CCE1315	2024/02/23	2025/02/22
Cable-0.5m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805443/4	2024/03/05	2025/03/04
Cable-3m(1G-40G)	HUBER SUHNER	SUCOFLEX 104	805796/4	2024/03/05	2025/03/04
Cable-8m(1G-26.5G)	WOKEN	WCBA-WCA203SM	CCE1374	2024/03/05	2025/03/04
Cable-1m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	552450	2023/06/08	2024/06/07
Cable-3m(1G-40G)	HUBER SUHNER	HUBER SUHNER / SF102	552451	2023/06/08	2024/06/07
E3	AUDIX	v8.2014-8-6	RK-000529	NA	NA
High Pass Filter	Warison	WFIL-H3000-18000F-03	WRJ5CFWC2J1	2023/07/03	2024/07/02
Highpass Filter	WOKEN	WFIL-H7000-18000F-01	WR468FWC2B1	2023/08/18	2024/08/17

Test Item	RF Conducted				
Test Site	RFCON01-NK				
Instrument	**Manufacturer**	**Model No**	**Serial No**	**Calibration Date**	**Valid Date**
Spectrum Analyzer	ROHDE & SCHWARZ	FSP 40	100047	2024/03/01	2025/02/28
Attenuator	KEYSIGHT	8491B	MY39250703	2024/02/20	2025/02/19
Cable-0.5m(30M-40G)	HUBER SUHNER	SUCOFLEX 102	28420/2	2023/10/12	2024/10/11
Power Meter	Anritsu	ML2495A	1224005	2024/02/17	2025/02/16
Power Sensor	Anritsu	MA2411B	1207295	2024/02/17	2025/02/16
Switch Box	Theda	1-4	TW5451159	NA	NA

Test Item	AC Power Line Conducted Emission				
Test Site	CON02-NK				
Instrument	**Manufacturer**	**Model No**	**Serial No**	**Calibration Date**	**Valid Date**
EMI Receiver	ROHDE & SCHWARZ	ESR 7	101906	2023/05/08	2024/05/07
TWO-LINE V-NETWORK	ROHDE & SCHWARZ	ENV216	102185	2023/08/29	2024/08/28
Cable-4m(9k-3G)	EMEC	RG-223	18274M	2023/07/31	2024/07/30
E3	AUDIX	v8.2014-8-6	RK-000536	NA	NA

4. Antenna Requirements

4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.2 Antenna Construction and Directional Gain

Antenna Type	Dipole Antenna
Antenna Gain	4.45 dBi

5. Frequency Hopping System Requirements

5.1 Frequency Hopping Requirement

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 EUT Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.
This deviceuses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for thepiconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must knowthe master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFHidentifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

5.3 Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:
Channel number:

31	12	45	73	60	5	45	6	68	47
44	58	32	48	2	15	75	44	34	12
2	46	15	67	63	49	58	74	36	50
52	70	35	9	6	7	26	64	76	34

etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6. Test of AC Power Line Conducted Emission

6.1 Test Limit

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 KHz, according to the methods defined in ANSI C63.10-2013. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position produced maximum conducted emissions.

Frequency (MHz)	Quasi Peak (dB μ V)	Average (dB μ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

*Decreases with the logarithm of the frequency.

6.2 Test Procedures

a. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
b. Connect EUT to the power mains through a line impedance stabilization network (LISN).
c. All the support units are connecting to the other LISN.
d. The LISN provides 50 ohm coupling impedance for the measuring instrument.
e. The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
f. Both sides of AC line were checked for maximum conducted interference.
g. The frequency range from 150 kHz to 30 MHz was searched.
h. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

6.3 Typical Test Setup



6.4 Test Result and Data

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC 120V/60Hz)
Phase : Line



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1714	9.65	24.43	34.08	54.89	-20.81	Average	P
2	0.1714	9.65	33.67	43.32	64.89	-21.57	QP	P
3	0.2097	9.64	18.80	28.44	53.22	-24.78	Average	P
4	0.2097	9.64	28.36	38.00	63.22	-25.22	QP	P
5	0.2788	9.64	14.33	23.97	50.85	-26.88	Average	P
6	0.2788	9.64	23.65	33.29	60.85	-27.56	QP	P
7	0.4544	9.66	18.81	28.47	46.79	-18.32	Average	P
8	0.4544	9.66	28.11	37.77	56.79	-19.02	QP	P
9	14.8345	9.90	25.53	35.43	50.00	-14.57	Average	P
10	14.8345	9.90	30.81	40.71	60.00	-19.29	QP	P
11	19.3043	9.94	27.00	36.94	50.00	-13.06	Average	P
12	19.3043	9.94	31.96	41.90	60.00	-18.10	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC 120V/60Hz)
Phase : Neutral



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F
1	0.1558	9.56	10.33	19.89	55.68	-35.79	Average	P
2	0.1558	9.56	35.17	44.73	65.68	-20.95	QP	P
3	0.2136	9.59	11.52	21.11	53.07	-31.96	Average	P
4	0.2136	9.59	28.44	38.03	63.07	-25.04	QP	P
5	0.2578	9.58	0.28	9.86	51.50	-41.64	Average	P
6	0.2578	9.58	22.73	32.31	61.50	-29.19	QP	P
7	0.4510	9.57	25.06	34.63	46.86	-12.23	Average	P
8	0.4510	9.57	29.91	39.48	56.86	-17.38	QP	P
9	15.6040	9.91	25.84	35.75	50.00	-14.25	Average	P
10	15.6040	9.91	31.20	41.11	60.00	-18.89	QP	P
11	19.5129	9.97	23.33	33.30	50.00	-16.70	Average	P
12	19.5129	9.97	28.68	38.65	60.00	-21.35	QP	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=(LISN or ISN or Current Probe)Factor + Cable Loss

7. Test of Radiated Spurious Emission

7.1 Test Limit

In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. If the transmitter measurement is based on the maximum conducted output power, the attenuation required under this paragraph shall be 30dB instead of 20dB. In addition, radiated emissions which fall in section 15.205(a) the restricted bands must also comply with the radiated emission limit specified in section 15.209(a).

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Test Procedures

a. The EUT was placed on a rotatable table top 0.8 meter above ground.

b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.

c. The table was rotated 360 degrees to determine the position of the highest radiation.

d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.

e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.

f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.

g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.

h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

i. “Cone of radiation” has been considered to be 3dB bandwidth of the measurement antenna.

Note:

1.The supporting fixture shall permit orientation of the EUT in each of three orthogonal axis positions such that emissions from the EUT are maximized.

2.Due to the test software function limit the operation band setting(200dBuV/m). There's no corresponding limitation in the actual test item.

7.3 Typical Test Setup

Below 30MHz test setup



30MHz- 1GHz Test Setup



Above 1GHz Test Setup



7.4 Test Result and Data (9kHz ~ 30MHz)

The 9kHz-30MHz spurious emission is under limit 20dB more.

7.5 Test Result and Data (30MHz ~ 1GHz)

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	55.30	-9.21	47.20	37.99	40.00	-2.01	QP	100	62	P
2	168.78	-9.63	49.11	39.48	43.50	-4.02	QP	100	76	P
3	253.10	-10.04	50.45	40.41	46.00	-5.59	Peak	400	0	P
4	421.88	-5.07	44.99	39.92	46.00	-6.08	Peak	400	0	P
5	507.24	-3.18	38.54	35.36	46.00	-10.64	Peak	400	0	P
6	761.38	1.97	35.84	37.81	46.00	-8.19	Peak	400	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	59.10	-9.44	43.36	33.92	40.00	-6.08	Peak	400	0	P
2	167.74	-9.55	45.20	35.65	43.50	-7.85	Peak	400	0	P
3	253.10	-10.04	51.79	41.75	46.00	-4.25	Peak	400	0	P
4	421.88	-5.07	43.45	38.38	46.00	-7.62	Peak	400	0	P
5	714.82	0.89	36.99	37.88	46.00	-8.12	Peak	400	0	P
6	901.06	3.79	38.82	42.61	46.00	-3.39	Peak	400	0	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

7.6 Test Result and Data (1GHz ~ 25GHz)

Test Mode : BT 1TX GFSK CH00 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.53	39.20	54.00	-14.80	Average	100	152	P
2	2390.00	-2.33	55.10	52.77	74.00	-21.23	Peak	100	152	P
3	2402.00	-2.32	89.00	86.68	200.00	-113.32	Average	100	152	P
4	2402.00	-2.32	111.50	109.18	200.00	-90.82	Peak	100	152	P
5	4804.00	6.01	20.82	26.83	54.00	-27.17	Average	100	183	P
6	4804.00	6.01	43.32	49.33	74.00	-24.67	Peak	100	183	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH00 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	42.40	40.07	54.00	-13.93	Average	100	213	P
2	2390.00	-2.33	54.74	52.41	74.00	-21.59	Peak	100	213	P
3	2402.00	-2.32	82.31	79.99	200.00	-120.01	Average	100	213	P
4	2402.00	-2.32	104.81	102.49	200.00	-97.51	Peak	100	213	P
5	4804.00	6.01	19.98	25.99	54.00	-28.01	Average	100	173	P
6	4804.00	6.01	42.48	48.49	74.00	-25.51	Peak	100	173	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH39 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.60	39.27	54.00	-14.73	Average	116	154	P
2	2390.00	-2.33	54.54	52.21	74.00	-21.79	Peak	116	154	P
3	2441.00	-2.16	88.06	85.90	200.00	-114.10	Average	116	154	P
4	2441.00	-2.16	110.56	108.40	200.00	-91.60	Peak	116	154	P
5	2483.50	-2.01	42.00	39.99	54.00	-14.01	Average	116	154	P
6	2483.50	-2.01	55.25	53.24	74.00	-20.76	Peak	116	154	P
7	4882.00	6.26	20.08	26.34	54.00	-27.66	Average	100	181	P
8	4882.00	6.26	42.58	48.84	74.00	-25.16	Peak	100	181	P
9	7323.00	11.36	19.95	31.31	54.00	-22.69	Average	100	167	P
10	7323.00	11.36	42.45	53.81	74.00	-20.19	Peak	100	167	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH39 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.91	39.58	54.00	-14.42	Average	100	268	P
2	2390.00	-2.33	54.36	52.03	74.00	-21.97	Peak	100	268	P
3	2441.00	-2.16	79.36	77.20	200.00	-122.80	Average	100	268	P
4	2441.00	-2.16	101.86	99.70	200.00	-100.30	Peak	100	268	P
5	2483.50	-2.01	41.70	39.69	54.00	-14.31	Average	100	268	P
6	2483.50	-2.01	55.21	53.20	74.00	-20.80	Peak	100	268	P
7	4882.00	6.26	19.60	25.86	54.00	-28.14	Average	100	115	P
8	4882.00	6.26	42.10	48.36	74.00	-25.64	Peak	100	115	P
9	7323.00	11.36	20.17	31.53	54.00	-22.47	Average	100	115	P
10	7323.00	11.36	42.67	54.03	74.00	-19.97	Peak	100	115	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-2.01	89.45	87.44	200.00	-112.56	Average	100	158	P
2	2480.00	-2.01	111.95	109.94	200.00	-90.06	Peak	100	158	P
3	2483.50	-2.01	42.49	40.48	54.00	-13.52	Average	100	158	P
4	2483.50	-2.01	59.10	57.09	74.00	-16.91	Peak	100	158	P
5	4960.00	6.51	20.58	27.09	54.00	-26.91	Average	100	138	P
6	4960.00	6.51	43.08	49.59	74.00	-24.41	Peak	100	138	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX GFSK CH78 1Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-2.01	81.15	79.14	200.00	-120.86	Average	100	214	P
2	2480.00	-2.01	103.65	101.64	200.00	-98.36	Peak	100	214	P
3	2483.50	-2.01	41.64	39.63	54.00	-14.37	Average	100	214	P
4	2483.50	-2.01	56.02	54.01	74.00	-19.99	Peak	100	214	P
5	4960.00	6.51	21.12	27.63	54.00	-26.37	Average	100	185	P
6	4960.00	6.51	43.62	50.13	74.00	-23.87	Peak	100	185	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH00 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.86	39.53	54.00	-14.47	Average	100	152	P
2	2390.00	-2.33	54.34	52.01	74.00	-21.99	Peak	100	152	P
3	2402.00	-2.32	87.89	85.57	200.00	-114.43	Average	100	152	P
4	2402.00	-2.32	110.39	108.07	200.00	-91.93	Peak	100	152	P
5	4804.00	6.01	19.67	25.68	54.00	-28.32	Average	100	159	P
6	4804.00	6.01	42.17	48.18	74.00	-25.82	Peak	100	159	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH00 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.50	39.17	54.00	-14.83	Average	100	292	P
2	2390.00	-2.33	55.44	53.11	74.00	-20.89	Peak	100	292	P
3	2402.00	-2.32	81.64	79.32	200.00	-120.68	Average	100	292	P
4	2402.00	-2.32	104.14	101.82	200.00	-98.18	Peak	100	292	P
5	4804.00	6.01	19.09	25.10	54.00	-28.90	Average	100	225	P
6	4804.00	6.01	41.59	47.60	74.00	-26.40	Peak	100	225	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH39 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	43.98	41.65	54.00	-12.35	Average	100	159	P
2	2390.00	-2.33	55.54	53.21	74.00	-20.79	Peak	100	159	P
3	2441.00	-2.16	82.52	80.36	200.00	-119.64	Average	100	159	P
4	2441.00	-2.16	105.02	102.86	200.00	-97.14	Peak	100	159	P
5	2483.50	-2.01	41.70	39.69	54.00	-14.31	Average	100	159	P
6	2483.50	-2.01	54.36	52.35	74.00	-21.65	Peak	100	159	P
7	4882.00	6.26	18.68	24.94	54.00	-29.06	Average	100	192	P
8	4882.00	6.26	41.18	47.44	74.00	-26.56	Peak	100	192	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH39 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2390.00	-2.33	41.49	39.16	54.00	-14.84	Average	113	213	P
2	2390.00	-2.33	54.58	52.25	74.00	-21.75	Peak	113	213	P
3	2441.00	-2.16	79.20	77.04	200.00	-122.96	Average	113	213	P
4	2441.00	-2.16	101.70	99.54	200.00	-100.46	Peak	113	213	P
5	2483.50	-2.01	41.72	39.71	54.00	-14.29	Average	113	213	P
6	2483.50	-2.01	55.17	53.16	74.00	-20.84	Peak	113	213	P
7	4882.00	6.26	19.60	25.86	54.00	-28.14	Average	100	168	P
8	4882.00	6.26	42.10	48.36	74.00	-25.64	Peak	100	168	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH78 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Vertical



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-2.01	86.95	84.94	200.00	-115.06	Average	100	164	P
2	2480.00	-2.01	109.45	107.44	200.00	-92.56	Peak	100	164	P
3	2483.50	-2.01	42.98	40.97	54.00	-13.03	Average	100	164	P
4	2483.50	-2.01	57.69	55.68	74.00	-18.32	Peak	100	164	P
5	4960.00	6.51	19.96	26.47	54.00	-27.53	Average	100	133	P
6	4960.00	6.51	42.46	48.97	74.00	-25.03	Peak	100	133	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

Test Mode : BT 1TX 8DPSK CH78 3Mbps
Voltage : From Adapter(AC120V/60Hz)
Pol : Horizontal



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg)	P/F
1	2480.00	-2.01	87.93	85.92	200.00	-114.08	Average	100	161	P
2	2480.00	-2.01	110.43	108.42	200.00	-91.58	Peak	100	161	P
3	2483.50	-2.01	43.15	41.14	54.00	-12.86	Average	100	161	P
4	2483.50	-2.01	58.77	56.76	74.00	-17.24	Peak	100	161	P
5	4960.00	6.51	20.12	26.63	54.00	-27.37	Average	100	131	P
6	4960.00	6.51	42.62	49.13	74.00	-24.87	Peak	100	131	P

Note: Level=Reading+Factor
Margin=Level-Limit
Factor=Antenna Factor + cable loss - Amplifier Factor

7.7 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.09000 – 0.11000	16.42000 – 16.42300	399.9 – 410.0	4.500 – 5.250
0.49500 – 0.505**	16.69475 – 16.69525	608.0 – 614.0	5.350 – 5.460
2.17350 – 2.19050	16.80425 – 16.80475	960.0 – 1240.0	7.250 – 7.750
4.12500 – 4.12800	25.50000 – 25.67000	1300.0 – 1427.0	8.025 – 8.500
4.17725 – 4.17775	37.50000 – 38.25000	1435.0 – 1626.5	9.000 – 9.200
4.20725 – 4.20775	73.00000 – 74.60000	1645.5 – 1646.5	9.300 – 9.500
6.21500 – 6.21800	74.80000 – 75.20000	1660.0 – 1710.0	10.600 – 12.700
6.26775 – 6.26825	108.00000 – 121.94000	1718.8 – 1722.2	13.250 – 13.400
6.31175 – 6.31225	123.00000 – 138.00000	2200.0 – 2300.0	14.470 – 14.500
8.29100 – 8.29400	149.90000 – 150.05000	2310.0 – 2390.0	15.350 – 16.200
8.36200 – 8.36600	156.52475 – 156.52525	2483.5 – 2500.0	17.700 – 21.400
8.37625 – 8.38675	156.70000 – 156.90000	2655.0 – 2900.0	22.010 – 23.120
8.41425 – 8.41475	162.01250 – 167.17000	3260.0 – 3267.0	23.600 – 24.000
12.29000 – 12.29300	167.72000 – 173.20000	3332.0 – 3339.0	31.200 – 31.800
12.51975 – 12.52025	240.00000 – 285.00000	3345.8 – 3358.0	36.430 – 36.500
12.57675 – 12.57725	322.00000 – 335.40000	3600.0 – 4400.0	Above 38.6
13.36000 – 13.41000			

**: Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

8. Test of Conducted Spurious Emission

8.1 Test Limit

According to the methods defined in ANSI C63.10-2013 Section 7.8.8

Below –30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

8.2 Test Procedure

According to the methods defined in ANSI C63.10-2013

a. The transmitter output was connected to the spectrum analyzer via a low loss cable.

b. Set RBW of spectrum analyzer to 100 KHz and VBW of spectrum analyzer to 300 KHz with convenient frequency span including 100 KHz bandwidth from band edge.

c. The band edges was measured and recorded.

8.3 Test Setup Layout



8.4 Test Result and Data

Note: Test plots refer to the following pages.

Modulation Type: GFSK (1Mbps)
Channel: 00



Modulation Type: GFSK (1Mbps)
Channel: 39











Modulation Type: GFSK (1Mbps)
Channel: 78



Modulation Type: π/4-DQPSK (2Mbps)
Channel: 00











Modulation Type: π/4-DQPSK (2Mbps)
Channel: 39



Modulation Type: π/4-DQPSK (2Mbps)
Channel: 78











Modulation Type: 8DPSK (3Mbps)
Channel: 00



Modulation Type: 8DPSK (3Mbps)
Channel: 39











Modulation Type: 8DPSK (3Mbps)
Channel: 78







Hopping Mode:

Modulation Type: GFSK



Modulation Type: π/4-DQPSK











Modulation Type: 8DPSK







9. 20dB Bandwidth Measurement Data

9.1 Test Limit

For reference data.

9.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 6.9

a. The transmitter output was connected to the spectrum analyzer.

b. Set RBW of spectrum analyzer to 1% to 5% of the 20dB Bandwidth and VBW to approximately three times RBW.

c. The 20 dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20 dB.

9.3 Test Setup Layout



9.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	20dB Bandwidth (MHz)	2/3 20dB Bandwidth (MHz)
GFSK	0	2402	0.873	0.582
	39	2441	0.897	0.598
	78	2480	0.888	0.592
π/4-DQPSK	0	2402	1.284	0.856
	39	2441	1.281	0.854
	78	2480	1.278	0.852
8DPSK	0	2402	1.299	0.866
	39	2441	1.296	0.864
	78	2480	1.302	0.868

Modulation Type: GFSK (1Mbps)
Channel: 00



Modulation Type: π/4-DQPSK (2Mbps)
Channel: 00



CH39



CH39



CH78



CH78



Modulation Type: 8DPSK (3Mbps)
Channel: 00



CH39



CH78



10. Carrier Frequency Separation

10.1 Test Limit

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than125 mW.

10.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 7.8.2

a. The transmitter output was connected to the spectrum analyzer.
b. Set RBW of spectrum analyzer to 300 KHz and VBW to 1000 KHz.
c. By using the MaxHold function record the separation of two adjacent channels.
d. Measure the frequency difference of these two adjacent channels.

10.3 Test Setup Layout



10.4 Test Result and Data

Modulation Type	Channel	Frequency (MHz)	Channel Separation (MHz)	Limit (MHz)
GFSK	0	2402	1.002	0.582
	39	2441	1.002	0.598
	78	2480	1.002	0.592
π/4-DQPSK	0	2402	1.002	0.856
	39	2441	1.002	0.854
	78	2480	1.002	0.852
8DPSK	0	2402	1.002	0.866
	39	2441	1.002	0.864
	78	2480	1.002	0.868

Modulation Type: GFSK (1Mbps)
Channel: 00



Modulation Type: π/4-DQPSK (2Mbps)
Channel: 00



CH39



CH39



CH78



CH78



Modulation Type: 8DPSK (3Mbps)
Channel: 00



CH39



CH78



11. Dwell Time on each channel

11.1 Test Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

11.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 7.8.4

1. The transmitter output was connected to the spectrum analyzer.
2. Adjust the center frequency to measure frequency, then set zero span mode.
3. Set RBW of spectrum analyzer to 300KHz and VBW to 1MHz.
4. Measure the time duration of one transmission on the measured frequency.

11.3 Test Setup Layout



11.4 Test Result and Data

Channel	Frequency (MHz)	Length of transmission time (ms)	Number of transmission in a 31.6 (79 Hopping*0.4)	Dwell Time (ms)	Limit (ms)
GFSK-DH1	2402	0.388	320.00	124.28	400
GFSK-DH3	2402	1.651	160.00	264.19	400
GFSK-DH5	2402	2.896	106.67	308.91	400
π/4-DQPSK-DH1	2402	0.398	320.00	127.42	400
π/4-DQPSK-DH3	2402	1.642	160.00	262.66	400
π/4-DQPSK-DH5	2402	2.880	106.67	307.20	400
8DPSK-DH1	2402	0.398	320.00	127.42	400
8DPSK-DH3	2402	1.656	160.00	264.96	400
8DPSK-DH5	2402	2.896	106.67	308.91	400

Channel	Frequency (MHz)	Length of transmission time (ms)	Number of transmission in a 8 (20 Hopping*0.4)	Dwell Time (ms)	Limit (ms)
AFH-DH1	2402-2421	0.393	160.00	62.93	400
AFH-DH3	2402-2421	1.649	80.00	131.89	400
AFH-DH5	2402-2421	2.906	53.33	155.00	400

Modulation Type: GFSK-DH1
Channel: 00



Modulation Type: π/4-DQPSK-DH1
Channel: 00



Modulation Type: GFSK-DH3
Channel: 00



Modulation Type: π/4-DQPSK-DH3
Channel: 00



Modulation Type: GFSK-DH5
Channel: 00



Modulation Type: π/4-DQPSK-DH5
Channel: 00



Modulation Type: 8DPSK-DH1
Channel: 00



Modulation Type: AFH (DH1)



Modulation Type: 8DPSK-DH3
Channel: 00



Modulation Type: AFH (DH3)



Modulation Type: 8DPSK-DH5
Channel: 00



Modulation Type: AFH (DH5)



12. Number of Hopping Channels

12.1 Test Limit

Frequency hopping systems in the 2400 ~ 2483.5 MHz band shall use at least 15 channels.

12.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 7.8.3

a. The transmitter output was connected to the spectrum analyzer.

b. 2. Set RBW of spectrum analyzer to 100 KHz and VBW to 300 KHz.

c. 3. Set the MaxHold function, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been record.

12.3 Test Setup Layout



12.4 Test Result and Data

Modulation Type	Hopping Channels
GFSK	79
π/4-DQPSK	79
8DPSK	79

Modulation Type: GFSK (1Mbps)



Modulation Type: π/4-DQPSK (2Mbps)



Modulation Type: 8DPSK (3Mbps)



13. Maximum Average Output Power

13.1 Test Limit

The Maximum Average Output Power Measurement is 30dBm.

13.2 Test Procedures

According to the methods defined in ANSI C63.10-2013 Section 7.8.5

The antenna port(RF output)of the EUT was connected to the input(RF input)of a power meter. Power was read directly from the meter and cable loss connection was added to the reading to obtain power at the EUT antenna terminal. The EUT Output Power was set to maximum to produce the worse case test result.

13.3 Test Setup Layout



13.4 Test Result and Data

Modulation Type	Setting	Channel	Frequency (MHz)	AV Output Power (dBm)	AV Output Power (mW)
GFSK	9	0	2402	10.90	12.303
	9	39	2441	10.01	10.023
	9	78	2480	10.92	12.359
π/4-DQPSK	9	0	2402	8.15	6.531
	9	39	2441	7.12	5.152
	9	78	2480	8.61	7.261
8DPSK	9	0	2402	8.14	6.516
	9	39	2441	7.13	5.164
	9	78	2480	8.63	7.295

AFH Mode

Modulation Type	Setting	Channel	Frequency (MHz)	AV Output Power (dBm)	AV Output Power (mW)
GFSK	9	0-19	2402-2421	10.93	12.388
π/4-DQPSK	9	0-19	2402-2421	8.17	6.561
8DPSK	9	0-19	2402-2421	8.15	6.531