

Analysis Report

The Equipment Under Test (EUT), is a portable 2.4GHz Transceiver for a piano. The sample supplied operated on a single channel, 2470MHz.

The EUT is powered by 3 x 1.5V AA batteries. After switching on the EUT, the piano can be paired up with the guitar and the drum by pressing the button on the piano. Different note and music will be played on all units based on the buttons and sensors pressed on the piano, or by inserting the card into the reader on top of the piano and then press the button on the piano. Volume of sound played can also be adjusted based on the button pressed on the piano.

Antenna Type: Internal integral antenna

Antenna Gain: 0dBi

Maximum field strength: 0dBm (Average)

According to the KDB 447498 D04 Interim General RF Exposure Guidance v01

Based on the Maximum allowed average field strength of production tolerance was 0dBm.

Thus, it below calculated field strength according to minimum SAR exclusion threshold level as follows:

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than $ERP_{20\text{cm}}$ in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{\text{th}} (\text{mW}) = ERP_{20\text{ cm}} (\text{mW}) = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B. 2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1). The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

The worst case of SAR Exclusion Threshold Level at 2.48GHz with distance 5mm:
= 2.717mW (4.3dBm)

Since maximum average field strength plus production tolerance $\leq 4.3\text{dBm}$ and antenna gain is $\geq 0.0\text{dBi}$, it is concluded that maximum Conducted Power and Field Strength are well below the SAR Exclusion threshold level, so the EUT is considered to comply with SAR requirement without testing.