




HOVERCRAFT

INSTRUCTION

NOTE: THE MANUFACTURER IS NOT RESPONSIBLE FOR ANY RADIO OR TV INTERFERENCE CAUSED BY UNAUTHORIZED MODIFICATIONS TO THIS EQUIPMENT. SUCH MODIFICATIONS COULD VOID THE USER'S AUTHORITY TO OPERATE THE EQUIPMENT.

OWNER'S MANUAL

Important! Please read your Owner's Manual all the way before operating your vehicle. Contains important information — keep for future reference.

Safety First

- Adult supervision is strongly recommended.
- Adult supervision strongly recommended, and use extra caution when operating vehicle near water or ice. Do not go onto ice on a lake or other body of water that will become dangerous if it breaks.
- Operate your vehicle in a safe area away from people, pets, cars, etc. In addition, do not operate vehicle on streets or in darkness.
- Do not touch or try to pick up vehicle when it is in motion. Wait until it stops completely.
- Keep hair, fingers, face and loose clothing away from top and rear propellers while the vehicle is switched "on" or while the transmitter is operating.
- Never block rotation of top lift fan or stick any object through top, bottom or rear grilles.
- Do not drive hovercraft into walls or other hard objects.
- Be a responsible HOVERCRAFT operator!

NOTICE: EXOTIC VEHICLE! NOTE SPECIAL OPERATING CONDITIONS

• No wheels	• Rides on cushion of air created by lift fan blowing downward and into air bag "skirt".
• Goes on floor, dirt, pavement, ice, snow	• Needs flats, smooth, clean surface so skirt can "seal" with ground for best results.
• Multi-terrain capable	• Not for use on rough or broken pavement/ground, carpet, rocks, pebbles, grass, decking, hills, inclines or any surface that "lets the air out" or damages skirt.
• Goes on fresh water (pool, pond or lake, not salt/sea/ocean water)	• Pilot must keep craft within radio and battery life range on water to ensure retrieval.
• True amphibious vehicle	• Not a boat; Needs lift fan on with full power and air bag skirt inflated to float properly.
• High-power, triple motor design	• Battery life 7-13 minutes between charges, depending on battery type and conditions.
• Real rubber air bag skirt	• Skirt is durable but can puncture on sharp rocks, sticks.

How it Works

Lift fan/air compressor blows downward, inflating air bag skirt, which seals with the ground and creates a cushion of air under the hovercraft. Propellers at rear of vehicle provide thrust for movement along the ground.



Batteries and Charger Required

9.6-Volt Rechargeable Battery Pack and Battery Charger for NiMH or NiCd Battery Packs

For longer run time, use high-capacity "NiMH" or "NiCd" battery packs with highest "mAh" rating number (750mAh or higher).

One 9-Volt Battery for Transmitter (not rechargeable)

Battery Cautions

CAUTION: TO AVOID BATTERY LEAKAGE

1. Make sure the batteries are inserted correctly and follow the toy and battery manufacturer's instructions.
2. Make sure battery polarity (direction) is correct.
3. Use only battery type(s) recommended.
4. Remove rechargeable batteries from the product before charging. Recharge batteries only under adult supervision and follow the battery and charger manufacturers' instructions.

Other Battery Cautions

1. Use caution when removing battery from vehicle after use. Battery may be hot.
2. Never pull the battery pack out of the vehicle by the wire or plug. Never unplug the battery plug by pulling on the battery.
3. Remove batteries from the product for storage.
4. Battery life may vary with the brand used.
5. Do not recharge non-rechargeable batteries.
6. Do not short-circuit battery terminals.
7. Dispose of batteries safely and properly, according to your local requirements.

NOTE: NICKEL CADMIUM BATTERIES MUST BE RECYCLED OR DISPOSED OF PROPERLY.

Battery Charging and Care

Vehicle will not run without a 9.6V rechargeable NiCd or NiMH battery pack and matching charger, commonly available for R/C vehicles at many toy and hobby dealers.

Always follow the instructions that came with your battery pack and charger. Adult supervision of battery charging is recommended.

Drain Down – Cool Down – Charge Up

1. For best performance, run battery pack all the way down before recharging. Run until lift fan and rear propellers slow to a stop. Note: If you are operating vehicle in water, retrieve the vehicle while battery power is still strong and perform this Drain Down procedure on land.
2. Allow the battery pack to cool before recharging.
3. Charge fully according to the battery/charger manufacturer's instructions. Charging times differ with different types, brands, models, ages and conditions of battery packs and chargers. The first few charges of a new battery may require more time for a full charge than later charges.

Battery Heat


1. Battery gets hot after use! This is normal, but be careful. Wait until battery is cool (20 minutes or more if needed) before charging. Charging batteries when they are hot will severely reduce the number of times they can be recharged.
2. After charging, battery pack will be warm. This is normal.

Running and Charging Times

1. NiCd and NiMH battery packs are not like alkaline batteries. They lose all their power suddenly, not gradually, and will stop very soon after slowing down becomes noticeable with little warning. This is normal, but keep it in mind, especially when operating on water, since you need to get the vehicle back before the battery power runs out.




Typical running time will be between 7 to 8 minutes for a typical freshly charged NiCd battery pack in good condition (9 to 13 min. for NiMH), but do not rely on this until you observe how long your battery runs in your vehicle under the conditions you operate in. Running time may vary over life of battery, with the first few charge cycles yielding shorter run times than later charges.

Hovercraft Features



Transmitter Battery Installation

1. Slide open BATTERY DOOR on back of TRANSMITTER. (Fig.1)
2. Insert a fresh, new 9-VOLT BATTERY with the polarity (+/-) as shown on the bottom of battery compartment. (Fig.2)
3. Hold battery in place with thumb and replace BATTERY DOOR. (Fig.3)
4. Check for transmitter operation by looking for the red "POWER ON" LIGHT on front to light when a JOYSTICK is pushed. If LIGHT does not come on, check battery polarity. If LIGHT still does not light, install a brand-new battery.



Transmitter Operation

Your Hovercraft is piloted similar to a tank or a twin-motor boat.

1. **LEFT STICK** powers left side Prop (propeller). When pushed up (forward) it turns vehicle to **RIGHT**.
2. **RIGHT STICK** powers right side prop. When pushed up (forward) it turns vehicle to **LEFT**.
3. **BOTH STICKS** when pushed up together make the vehicle go straight ahead.
4. **RED BUTTON** on back of transmitter cuts the lift power.

LEFT STICK

Left Motor Forward / Release for Left Motor Neutral / Left Motor Reverse

RIGHT STICK

Right Motor Forward / Release for Right Motor Neutral / Right Motor Reverse

LIFT DOWN BUTTON

Press to cut power to Lift Fan. Release to power "on" Lift Fan.

STOP BOTTON



Press to cut power of Lift /(air bag)/ Fan. Release to power on Lift /(air bag)/ Fan.

ANTENNA

Hold Transmitter so antenna points straight up in the air. Do not touch during operation.




POWER ON INDICATOR LIGHT

Note: There is no on/off switch on Transmitter. Moving the sticks turns it on. It turns off after releasing the stick.



Battery Installation

1. Turn red **LATCHES** on vehicle **BATTERY DOOR**, lift door up at rear and remove. (Figs.4)
2. Insert fully charged **BATTERY PACK** into battery compartment as shown. Observe position of wire as shown. (Figs. 5)
3. Firmly insert **BATTERY PLUG** all the way into **SOCKET** as shown. Make sure the "key" (bump) on plug is facing downward to fit into notch in socket.
4. Replace **BATTERY DOOR** front first by aligning front edge of door and compartment, lowering rear of door into place and turning **LATCHES** to locked position (latches click onto little "bumps" in door). (Fig.6)
5. Check operation by turning **POWER KNOB** to point arrow to **ON** and then to **OFF** again. **POWER KNOB** is located on top rear of vehicle just in front of **ANTENNA**. Lift fan should go on and off. If not, remove and reinsert battery plug. Turn switch off to save power whenever possible.



Hovercraft Operation

FORWARD

Push both sticks up. Release to coast.

BRAKING / REVERSE THRUST

Pull both sticks down.

Use Reverse to slow vehicle down faster than coasting.

LEFT TURN-MOVING

When moving forward with both sticks up, release left stick to turn left.

RIGHT TURN-MOVING

When moving forward with both sticks up, release right stick to turn right.

LEFT TURN-STATIONARY

With vehicle standing still, push right stick up.

RIGHT TURN-STATIONARY


With vehicle standing still, push left stick up.

RIGHT SPIN

At the same time, push left stick up and pull right stick down.

LEFT SPIN

At the same time, push right stick up and pull left stick down.



Operating on Water

Fresh water only – not sea or salt water!

CAUTION: ADULT SUPERVISION IS STRONGLY RECOMMENDED WHEN OPERATING ON OR NEAR WATER OR ICE.

Important: Time the use of the vehicle on water so you can recover it before the battery runs out! Run each launch for only 5 minutes with a freshly charged battery to be sure.

Launching

1. Turn vehicle power on. Release red transmitter button so lift fan comes on.

2. Hold vehicle as shown. Make sure lift fan is at full speed and air bag skirt is fully inflated. Carefully place vehicle on water.

Important: Lift fan must be operating for vehicle to operate properly. Air bag skirt may fill with water if lift fan is not running.

When removing from water, remove battery door and battery pack, hold vehicle as shown and shake out excess water. Dry vehicle after use with a clean soft cloth.

Hovercraft Tips

1. Hovercraft is not designed to go up hills or inclines.

2. Water should be calm, without waves, turbulence or strong currents. Do not operate in rivers or streams.

Do not operate vehicle in salt water. Salt will corrode metal parts and void warranty.

Air Bag Skirt Care

1. Edge of air bag skirt must seal with lower edge of body for proper operation. If skirt becomes loose, push the edge of the skirt back into the slot on the body. Use a small coin if necessary. Important: Do not use sharp tools such as screwdriver, pen or pencil point, knife, etc or bag may tear.

2. Small holes and tears in skirt may be repaired by an adult using "Super Glue" or "Crazy Glue" (cyanoacrylate) type glue. Use a small amount and follow glue maker's instructions.

For larger holes and tears, skirt needs to be replaced. Order replacement air bags direct from your distributor. Not sold in stores.

R/C Facts for Improved Operation

1. When battery starts to fully discharge, vehicle may slow, stop, or refuse to respond to your control. It's time to recharge vehicle battery or replace transmitter battery. This is absolutely the #1 cause of all problems and questions!
2. Radio frequency interference can interfere with the control of your vehicle. Buildings, power wires, other R/C transmitters, or CB radio can all cause problems. Pick a place to operate that's away from these things.
3. Hold Transmitter so antenna points up, not toward the vehicle. Keep vehicle within range (about 65 feet) to keep control. If vehicle goes out of range, try lifting transmitter high into air to increase range for vehicle recovery.
4. Wipe vehicle clean and dry after each use, including inside battery compartments.
Turn vehicle power switch off immediately after running. Remove batteries for storing. Keep vehicle and Transmitter away from heat and direct sunlight and moisture.


Troubleshooting Guide

Don't take your hovercraft back to the store – try solving problems using this valuable guide.

Problem	Probable Cause	Correction
Vehicle runs slowly, or won't move, or won't steer	• Batteries dead or low • Batteries installed incorrectly • Loose battery connection • Power switch is off	• Remove and replace batteries, making sure battery direction (polarity,+/-) is correct and battery compartment contacts are clean. • Recharge vehicle battery. • Turn on Power switch.
Erratic operation, loss of control, short range	• Radio interference • Weak Transmitter battery • Weak vehicle battery	• Move to another location. • Point antenna up in the air, not at vehicle. Don't touch antenna. • Recharge 9.6V battery pack or replace 9V battery in transmitter.
Vehicle stops working after going in water or snow	• Water in battery / electronics / motor areas	• Turn power knob off IMMEDIATELY, remove all batteries, dry inside and out with clean soft cloth and allow to dry overnight with battery door off.
Battery life is short	• Battery pack not charge fully • Battery pack charged when hot • Battery pack faulty or worn out • Battery pack old or has too little capacity (mAh)	• Recharge battery pack • Always allow battery pack to cool before charging • Replace battery pack • Use battery backs with high mAh rating, 750 or more is best

CAUTION-ELECTRICALLY OPERATED PRODUCT: NOT RECOMMENDED FOR CHILDREN UNDER 8 YEARS OF AGE. AS WITH ALL ELECTRIC PRODUCTS, PRECAUTIONS SHOULD BE OBSERVED DURING HANDLING AND USE TO PREVENT ELECTRIC SHOCK, INPUT: 220/240 VAC, 50 Hz, 6W, OUTPUT: 12VDC, 400mA

CAUTION: RISK OF ELECTRIC SHOCK, CHARGE ONLY 9.6V NI-CD (NICKEL CADMIUM) TYPE RECHARGEABLE BATTERY PACKS, OTHER TYPES OF BATTERIES MAY BURST, CAUSING INJURY TO PERSONS AND DAMAGE, DRY LOCATION USE ONLY.



9.6V RECHARGEABLE BATTERY PACK AND CHARGER

READ AND FOLLOW ALL INSTRUCTIONS

SAVE THESE INSTRUCTIONS FOR FUTURE REFERENCE. THEY CONTAIN IMPORTANT INFORMATION.

SAFETY NOTICE TO ADULTS

1. This product should be used under adult supervision.
2. Regularly examine charger and battery pack for damage, including plugs, casings and all other parts. If damaged, do not use.
3. Not a toy-not intended for children under 8 years old.

IMPORTANT BATTERY SAFETY INFORMATION

CAUTION: TO AVOID BATTERY LEAKAGE

- Make sure the batteries are inserted with the correct polarity and follow the toy and battery manufacturers' instructions.
- Do not mix old and new batteries.
- Do not mix alkaline, standard (carbon-zinc), or rechargeable (nickel-cadmium) batteries.
- Remove weak or exhausted batteries from the product.

ADDITIONAL IMPORTANT BATTERY SAFETY INFORMATION

- An adult should help with battery replacement
- Only batteries of the same or equivalent type as recommended in the "Battery Installation" (or replacement) instructions are to be used.
- Non-rechargeable batteries are not to be recharged.
- If rechargeable batteries are used, they are only to be charged under adult supervision.
- Rechargeable batteries are to be removed from the product before they are charged.
- If you use a battery charger, it should be examined regularly for damage to the cord, plug, enclosure and other parts. Do not use damaged battery charger until it has been properly repaired.
- Dispose of batteries safely and properly.




Ni-Cd

THIS PRODUCT USES A NICKEL CADMIUM BATTERY. MUST BE RECYCLED OR DISPOSED OF PROPERLY. Contact your local area office of solid waste management or other appropriate local agency for information.

BATTERY CHARGING INSTRUCTIONS

NOTE: "CONDITION" BATTERY PACK FOR BEST RESULTS BY CHARGING ACCORDING TO THESE INSTRUCTIONS ON EVERY CHARGE. ON THE FIRST CHARGE, EXPECT A SHORTER RUN TIME. RUN TIMES WILL INCREASE OVER THE NEXT 6 CHARGES, REACHING SPECIFIED RUN TIMES.



110V

**This product
should be used
with adult
supervision**

Drain Down – Cool Down – Charge Up

1. After the first charge, for best performance always run the battery pack all the way down before recharging. Run until vehicle wheels/fans/motors slow to a stop. Note: If you are operating a boat, hovercraft or other water vehicle in water, retrieve the vehicle while battery power is still strong and perform this Drain Down procedure on land. (Don't operate other kinds of vehicles in or near water.)
2. Allow the battery pack to cool before recharging.

Battery Heat

1. Battery gets hot after use! This is normal, but be careful. Wait until battery is cool (20 minutes or more if needed) before charging. Charging batteries when they are hot will severely reduce the number of times they can be recharged.
2. After charging, battery pack will be warm. This is normal.

RECHARGING INSTRUCTIONS

1. Plug wall pack charger into a standard wall outlet.
2. Connect the battery pack plug to the charger plug as shown.
3. Red light on charger will light to show charger is operating. Normal charging time is approximately 3 hours.
4. Unplug charger from wall after 3 hours of charging.
5. After charging, battery pack will feel warm. This is normal.

Rechargeable Battery Tips

1. Don't overcharge the battery pack. Unplug the charger from the wall at the end of the recommended charging time.
2. NiCd battery packs are not like alkaline batteries. They lose all their power suddenly, not gradually, and vehicle will stop very soon after slowing down becomes noticeable, with little warning. This is normal, but keep it in mind, especially when operating on water, since you need to get the vehicle back before the battery power runs out.
3. Store your battery pack discharged.
4. Your battery pack will hold a charge for a shorter time in hot weather. Otherwise, you can charge a battery a day or so in advance of when you want to use it or give it as a gift.
5. It's better to charge for the full 2 hours, even though the vehicle may operate with a partial battery charge.
6. When your battery pack's running time gets shorter and shorter, probably it's getting close to the end of its life and needs to be replaced.

PRINTED IN CHINA



Please return damaged or defective merchandise to the Kohl's store where it was purchased. To order replacement parts, please visit <http://mfagifts.com/parts> or call 419-867-9500 Monday through Friday 8:15 am-5:00 pm EST.