RF Exposure

Applicant	:	Dongguan Hele Electronics Co.,Ltd
Address	:	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
Product Name	:	Bluetooth headset
Brand Mark	:	QCY
Model	:	BH26H6A
FCC ID	:	RDR-BH26H6AR
Report Number	:	BLA-EMC-202606-A94-07
Date of Receipt	:	June 24, 2026
Date of Test	:	June 24, 2026 to July 7, 2026
Test Standard	:	47 CFR Part 15, Part1.1307 47 CFR Part 15, Part2.1093 KDB447498D04 General RF Exposure Guidance v01
Test Result	:	Pass

Compiled by: Hugh **Review by:** Xavier **Approved by:** Blue Zheng

Issued Date: July 7, 2026

BlueAsia Technical Services (Shenzhen) Co., Ltd
Address: No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict,Bao'an District, Shenzhen, Guangdong, China

The test report is effective only with both signature and specialized stamp and The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full. The results described in this report do not represent the quality or characteristics of the sampled batch, nor do they represent any similar or identical products that are not explicitly stated.

Table of Contents

1 General information 4

1.1 General information 4

1.2 General description of EUT 4

2 Laboratory and accreditations 6

3 RF Exposure Compliance Requirement 7

3.1 Standard Requirement 7

3.2 Limits 7

3.3 Result 8

BlueAsia

Revise Record

Version No.	Date	Description
01	July 7, 2026	Original

BlueAsia

1 General information

1.1 General information

Applicant	Dongguan Hele Electronics Co.,Ltd
Address	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
Manufacturer	Dongguan Hele Electronics Co.,Ltd
Address	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China
Factory	Dongguan Hele Electronics Co.,Ltd
Address	No.325 Yuehui Rd. Daojiao Town Dongguan City Guangdong Province China

1.2 General description of EUT

Product name	Bluetooth headset
Model no.	BH26H6A
Series model	N/A
Power supply	DC3.8V by battery
Hardware Version	V1.0
Software Version	V1.0

BlueAsia

BT:

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, π/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Internal antenna
Antenna Gain:	Right: 1.86dBi (Provided by customer)

BLE:

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Rate data:	1Mbps; 2Mbps
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Internal antenna
Antenna Gain:	Right: 1.86dBi (Provided by customer)

BlueAsia

2 Laboratory and accreditations

The test facility is recognized, certified, or accredited by the following organizations:

Company name:	BlueAsia Technical Services (Shenzhen) Co.,Ltd.
Address:	No.41, South of Beihuan Road, Shangwu Community, Shiyan Subdistrict, Bao'an District, Shenzhen, Guangdong, China
CNAS accredited No.:	L9788
A2LA Cert. No.:	5071.01
FCC Designation No.:	CN1252
ISED CAB identifier No.:	CN0028
Telephone:	+86-755-28682673
FAX:	+86-755-28682673

BlueAsia

3 RF Exposure Compliance Requirement

3.1 Standard Requirement

According to 447498 D04 Interim General RF Exposure Guidance v01

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

3.2 Limits

$$P_{\text{th}}\ (\text{mW}) = \begin{cases} ERP_{20\ \text{cm}}(d/20\ \text{cm})^x & d \le 20\ \text{cm} \\ ERP_{20\ \text{cm}} & 20\ \text{cm} < d \le 40\ \text{cm} \end{cases} \qquad \text{(B.2)}$$

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20\ \text{cm}}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20\text{cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

Frequency (MHz)	Distance (mm)									
	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

$$P_{\text{th}}\ (\text{mW}) = ERP_{20\ \text{cm}}\ (\text{mW}) = \begin{cases} 2040f & 0.3\ \text{GHz} \le f < 1.5\ \text{GHz} \\ 3060 & 1.5\ \text{GHz} \le f \le 6\ \text{GHz} \end{cases} \qquad \text{(B.1)}$$

3.3 Result

EIRP = pt x gt = $(E \times d)^2/30$

Where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m,

d = measurement distance in meters (m)

Spot = $(EXd)^2/30$ x gt

Separation distance= 0.5cm

Right

Ant gain = 1.86dBi

For BT(Worst):

Max Output power = -1.013dBm @ 2402MHz 8DPSK

EIRP = -1.013dBm + 1.86dBi=0.847dBm =1.215mW< 2.788mW

ERP = 0.847-2.15= -1.303dBm

Comply with RF exposure exemption limit.

For BLE(Worst):

Max Output power = -2.32dBm @ 2402MHz BLE2M

EIRP = -2.32dBm + 1.86dBi=-0.46dBm =0.899mW< 2.717mW

ERP = -0.46-2.15= -2.61dBm

Comply with RF exposure exemption limit.

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, the result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.