



Appendix Test Data for BLE (Conducted Measurement)

Product Name: Bluetooth Earbuds

Trade Mark: /

Test Model: BH26HT22A

FCC ID: RDR-HT22AR

Environmental Conditions

Temperature:	23.5℃
Relative Humidity:	58%
ATM Pressure:	100.0 kPa
Test Engineer:	Allen Lai
Supervised by:	Max Zhang
NOTE	N/A

Appendix A: DTS Bandwidth

Test Result


Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.720	2401.632	2402.352	0.5	PASS
BLE_1M	Ant1	2440	0.664	2439.672	2440.336	0.5	PASS
BLE_1M	Ant1	2480	0.704	2479.628	2480.332	0.5	PASS
BLE_2M	Ant1	2402	1.136	2401.444	2402.580	0.5	PASS
BLE_2M	Ant1	2440	1.148	2439.440	2440.588	0.5	PASS
BLE_2M	Ant1	2480	1.104	2479.452	2480.556	0.5	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs





BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS





BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS





Appendix B: Occupied Channel Bandwidth

Test Result


Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL [MHz]	FH [MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.0238	2401.4874	2402.5112	---	---
BLE_1M	Ant1	2440	1.0310	2439.4862	2440.5172	---	---
BLE_1M	Ant1	2480	1.0385	2479.4828	2480.5213	---	---
BLE_2M	Ant1	2402	2.0299	2400.9901	2403.0200	---	---
BLE_2M	Ant1	2440	2.0472	2438.9920	2441.0392	---	---
BLE_2M	Ant1	2480	2.0564	2478.9852	2481.0416	---	---

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs





BLE_1M-Ant1-2480



BLE_2M-Ant1-2402





BLE_2M-Ant1-2440



BLE_2M-Ant1-2480





Appendix C: Maximum peak conducted output power

Test Result Peak


Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power [dBm]	Conducted Limit [dBm]	Verdict
BLE_1M	Ant1	2402	-0.53	≤30	PASS
BLE_1M	Ant1	2440	-0.79	≤30	PASS
BLE_1M	Ant1	2480	-1.27	≤30	PASS
BLE_2M	Ant1	2402	-0.44	≤30	PASS
BLE_2M	Ant1	2440	-0.61	≤30	PASS
BLE_2M	Ant1	2480	-1.10	≤30	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)






Test Graphs Peak




BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2440-PASS






BLE_1M-Ant1-2480-PASS




BLE_2M-Ant1-2402-PASS





BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS





Appendix D: Maximum peak power spectral density

Test Result


Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-16.42	≤8.00	PASS
BLE_1M	Ant1	2440	-16.86	≤8.00	PASS
BLE_1M	Ant1	2480	-17.09	≤8.00	PASS
BLE_2M	Ant1	2402	-18.31	≤8.00	PASS
BLE_2M	Ant1	2440	-18.49	≤8.00	PASS
BLE_2M	Ant1	2480	-19.01	≤8.00	PASS

Note: offset(dB) = cable loss(dB) + attenuator factor(dB)





Test Graphs






BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS





BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS





Appendix E: Band edge measurements

Test Result


Test Mode	Antenna	Ch. Name	Frequency [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	Low	2402	-0.98	-48.97	≤ -20.98	PASS
BLE_1M	Ant1	High	2480	-2.37	-47.91	≤ -22.37	PASS
BLE_2M	Ant1	Low	2402	-3.08	-34.85	≤ -23.08	PASS
BLE_2M	Ant1	High	2480	-2.45	-48.63	≤ -22.45	PASS


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)






Test Graphs





BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2480-PASS





Appendix F: Conducted Spurious Emission

Test Result


Test Mode	Antenna	Frequency [MHz]	Freq. Range [MHz]	Ref. Level [dBm]	Result [dBm]	Limit [dBm]	Verdict
BLE_1M	Ant1	2402	0~Reference	-1.28	-1.28	---	PASS
BLE_1M	Ant1	2402	30~1000	-1.28	-63.69	≤ -21.28	PASS
BLE_1M	Ant1	2402	1000~26500	-1.28	-37.4	≤ -21.28	PASS
BLE_1M	Ant1	2440	0~Reference	-2.22	-2.22	---	PASS
BLE_1M	Ant1	2440	30~1000	-2.22	-62	≤ -22.22	PASS
BLE_1M	Ant1	2440	1000~26500	-2.22	-37.07	≤ -22.22	PASS
BLE_1M	Ant1	2480	0~Reference	-2.06	-2.06	---	PASS
BLE_1M	Ant1	2480	30~1000	-2.06	-61.96	≤ -22.06	PASS
BLE_1M	Ant1	2480	1000~26500	-2.06	-37.94	≤ -22.06	PASS
BLE_2M	Ant1	2402	0~Reference	-0.74	-0.74	---	PASS
BLE_2M	Ant1	2402	30~1000	-0.74	-62.43	≤ -20.74	PASS
BLE_2M	Ant1	2402	1000~26500	-0.74	-36.89	≤ -20.74	PASS
BLE_2M	Ant1	2440	0~Reference	-1.04	-1.04	---	PASS
BLE_2M	Ant1	2440	30~1000	-1.04	-62.39	≤ -21.04	PASS
BLE_2M	Ant1	2440	1000~26500	-1.04	-37.42	≤ -21.04	PASS
BLE_2M	Ant1	2480	0~Reference	-1.48	-1.48	---	PASS
BLE_2M	Ant1	2480	30~1000	-1.48	-62.48	≤ -21.48	PASS
BLE_2M	Ant1	2480	1000~26500	-1.48	-37.92	≤ -21.48	PASS


Note: offset(dB) in Reference test plots = cable loss(dB) + attenuator factor(dB); For spurious emissions plots from 30MHz to 26.5GHz, the cable loss and attenuator factors have been set in the 'Input Correction' of the Spectrum Analyzer during the test.





Test Graphs






BLE_1M-Ant1-2402-1000~26500-PASS




BLE_1M-Ant1-2440-0~Reference-PASS





BLE_1M-Ant1-2440-30~1000-PASS




BLE_1M-Ant1-2440-1000~26500-PASS





BLE_1M-Ant1-2480-0~Reference-PASS




BLE_1M-Ant1-2480-30~1000-PASS






BLE_1M-Ant1-2480-1000~26500-PASS




BLE_2M-Ant1-2402-0~Reference-PASS






BLE_2M-Ant1-2402-30~1000-PASS




BLE_2M-Ant1-2402-1000~26500-PASS






BLE_2M-Ant1-2440-0~Reference-PASS




BLE_2M-Ant1-2440-30~1000-PASS






BLE_2M-Ant1-2440-1000~26500-PASS




BLE_2M-Ant1-2480-0~Reference-PASS





BLE_2M-Ant1-2480-30~1000-PASS



BLE_2M-Ant1-2480-1000~26500-PASS





Appendix G: Duty Cycle

Test Result

Test Mode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dB]
BLE_1M	Ant1	2402	2.14	2.50	85.60	0.68
BLE_1M	Ant1	2440	2.14	2.50	85.60	0.68
BLE_1M	Ant1	2480	2.14	2.50	85.60	0.68
BLE_2M	Ant1	2402	1.08	2.50	43.20	3.65
BLE_2M	Ant1	2440	1.08	2.50	43.20	3.65
BLE_2M	Ant1	2480	1.08	2.50	43.20	3.65


Note: offset(dB) = cable loss(dB) + attenuator factor(dB)






Test Graphs






NTNV-BLE_1M-Ant1-2480




NTNV-BLE_2M-Ant1-2402





NTNV-BLE_2M-Ant1-2440



NTNV-BLE_2M-Ant1-2480

