

RF Exposure Report

Report No.: MFBCKS-WTW-P23030625

FCC ID: RF41689A

Test Model: WS-A01

Received Date: 2023/3/22

Test Date: 2023/7/7

Issued Date: 2023/10/31

Applicant: KEYENCE CORPORATION

Address: 1-3-14, Higashi-Nakajima, Higashi-Yodogawa-ku, Osaka, 533-8555, Japan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result of Maximum Conducted Power	7

Release Control Record

Issue No.	Description	Date Issued
MFCKS-WTW-P23030625	Original release.	2023/10/31

1 Certificate of Conformity

Product: Industrial Wireless System

Brand: KEYENCE

Test Model: WS-A01

Sample Status: Engineering sample

Applicant: KEYENCE CORPORATION

Test Date: 2023/7/7

FCC Rule Part: FCC Part 2 (Section 2.1091)

Standard: KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Vito Lung , Date: 2023/10/31
Vito Lung / Specialist

Approved by : [Signature] , Date: 2023/10/31
May Chen / Manager

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 24 cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

Antenna No.	RF Chain No.	Antenna Net Gain (dBi)	Frequency Range (GHz)	Antenna Type	Connector Type
DB1	Chain 0	3.79	2.4~2.4835	PIFA	ipex(MHF)
		5.07	5.15~5.25		
		5.07	5.25~5.35		
		5.32	5.47~5.725		
		5.46	5.725~5.85		
DB2	Chain 1	2.84	2.4~2.4835	PIFA	ipex(MHF)
		4.77	5.15~5.25		
		4.77	5.25~5.35		
		5.63	5.47~5.725		
		5.64	5.725~5.85		
SB1	Chain 0	3.63	5.955-6.415	PIFA	ipex(MHF)
SB2	Chain 1	4.40	5.955-6.415	PIFA	ipex(MHF)

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2.5 Calculation Result of Maximum Conducted Power

CDD

For Single RF Source

RF Exposure								
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Test Result
WLAN 2.4 GHz	2412-2462	899.562	3.79	2152.936	24	0.2974	1	Pass
WLAN 5 GHz	5180-5240 5745-5825	627.779	5.64	2300.418	24	0.3178	1	Pass
WLAN 6 GHz	5955-7115	-	-	146.893	24	0.0203	1	Pass

Note: Calculate the EIRP of WLAN 6 GHz from the radiated field strength:

$EIRP (dBm) = Radiated\ field\ strength (dBuV/m) + 20 \times \log(d) - 104.77$

d is the measurement distance, in 3 m.

$EIRP = 116.9 + 20 \times \log(3) - 104.77 = 21.67\ dBm\ (146.893\ mW)$

For Multiple RF Sources (Simultaneous Operations)

Multiple RF Sources (Simultaneous Operations)							
RF Exposure					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio			
WLAN 2.4 GHz	2412-2462	0.2974	1	0.297	0.635	1	Pass
WLAN 5 GHz	5180-5240 5745-5825	0.3178	1	0.318			
WLAN 6 GHz	5955-7115	0.0203	1	0.02			

Beamforming

For Single RF Source

RF Exposure								
Operation Mode	Frequency Band (MHz)	Average Power (mW)	Antenna Gain (dBi)	Maximum EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Test Result
WLAN 2.4 GHz	2412-2462	584.483	6.34	2516.355	24	0.3476	1	Pass
WLAN 5 GHz	5180-5240 5745-5825	620.104	8.56	4451.071	24	0.6149	1	Pass
WLAN 6 GHz	5955-7115	-	-	217.27	24	0.03	1	Pass

Note: Calculate the EIRP of WLAN 6 GHz from the radiated field strength:

$$\text{EIRP (dBm)} = \text{Radiated field strength (dBuV/m)} + 20 \times \text{Log(d)} - 104.77$$

d is the measurement distance, in 3 m.

$$\text{EIRP} = 118.6 + 20 \times \text{Log}(3) - 104.77 = 23.37 \text{ dBm (217.27 mW)}$$

For Multiple RF Sources (Simultaneous Operations)

Multiple RF Sources (Simultaneous Operations)							
RF Exposure					Sum of Ratios	Limit of Ratios	Test Result
Operation Mode	Frequency Band (MHz)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Ratio			
WLAN 2.4 GHz	2412-2462	0.3476	1	0.348	0.993	1	Pass
WLAN 5 GHz	5180-5240 5745-5825	0.6149	1	0.615			
WLAN 6 GHz	5955-7115	0.03	1	0.03			

NOTE:

- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

Source-base time average power is below Exemption Criteria and/or Routine Evaluation MPE thresholds, therefore the device is compliant FCC RF exposure requirement.

--- END ---