

TEST REPORT

Application No.: SUCR2512001214TL
FCC ID: RF41995A
Applicant: KEYENCE CORPORATION
Address of Applicant: 1-3-14, Higashinakajima Higashiyodogawa-ku, Osaka 533-8555, Japan
Manufacturer: KEYENCE CORPORATION
Address of Manufacturer: 1-3-14, Higashinakajima Higashiyodogawa-ku, Osaka 533-8555, Japan
Equipment Under Test (EUT):
EUT Description: Handheld Terminal
Model No.: BT-A800M
Trade Mark: KEYENCE
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2025-12-22
Date of Test: 2026-01-22 to 2026-02-03
Date of Issue: 2026-02-06

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Revision Record			
Version	Description	Date	Remark
00	Original	2026-02-06	/

Authorized for issue by:			
Tested By		Nature Shen	
		Nature Shen/Project Engineer	
Approved By		Cedar cheng	
		Cedar Cheng /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Radiated Emissions (Below 1GHz)		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6 & 12.7	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5 & 12.7.2	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
In-Band Emissions		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (b)	Pass
Contention-based Protocol		KDB 987594 D02 Section II.I.	47 CFR Part 15, Subpart E 15.407 (d)(6)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2020) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2020) Section 12.5.3	Pass
26dB Emission bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Maximum Conducted output power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass

3 Contents

	Page
1 COVER PAGE	1
2 Test Summary	3
3 Contents.....	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Environment Parameter	5
4.3 Description of Support Units	5
4.4 Measurement Uncertainty & Decision Rule	6
4.5 Test Location	7
4.6 Test Facility	7
4.7 Deviation from Standards.....	7
4.8 Abnormalities from Standard Conditions.....	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	10
6.1 Antenna Requirement	10
7 Radio Spectrum Matter Test Results	11
7.1 Conducted Emissions at AC Power Line (150kHz-30MHz).....	11
7.2 Radiated Emissions (Below 1GHz)	15
7.3 Radiated Emissions (Above 1GHz).....	19
7.4 Radiated Emissions which fall in the restricted bands	114
7.5 In-Band Emissions	156
7.6 Contention-based Protocol.....	158
7.7 Duty Cycle	159
7.8 99% Bandwidth	160
7.9 26dB Emission bandwidth	161
7.10 Maximum Conducted output power	162
7.11 Peak Power spectrum density	164
8 Test Setup Photo	166
9 EUT Constructional Details (EUT Photos).....	166
10 Appendix.....	167

4 General Information

4.1 Details of E.U.T.

Hardware Version:	V1.04
Software Version:	T23
Power Supply:	5V
SN:	P0ES200036/ P0ES200031/ P0ES200048
IEEE 802.11 WLAN Mode Supported:	☒ 802.11ax(HE20)/be(HE20): 20 MHz channel bandwidth ☒ 802.11ax(HE40) /be(HE40): (40 MHz channel bandwidth) ☒ 802.11ax(HE80)/be(HE80): (80 MHz channel bandwidth) ☒ 802.11ax(HE160)/be(HE160) (160 MHz channel bandwidth) ☒ 802.11be(HE320) (320 MHz channel bandwidth)
Operation Frequency:	5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz
Modulation Type:	802.11ax: OFDM/OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM); 802.11be: OFDMA with enhancements (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM, 4096-QAM)
FCC Classification:	6GHz Low Power Indoor Client (6XD)
Antenna Type:	LDS Antenna
Smart System:	☒ MIMO 802.11ax/be: 2Tx & 2Rx
Antenna Gain:	UNII-5: 0.6dBi(Ant5); -2.5dBi(Ant6); UNII-6: 0.2dBi(Ant5); -2.5dBi(Ant6); UNII-7: -0.3dBi(Ant5); -2.5dBi(Ant6); UNII-8: -1.3dBi(Ant5); -2.2dBi(Ant6); (Provided by the manufacturer)

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	25	3.6
Note: NV:Normal Voltage LV:Low Extreme Test Voltage HV:High Extreme Test Voltage NT:Normal Temperature LT:Low Extreme Test Temperature HT:High Extreme Test Temperature		

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Computer	Lenovo	T14	2YK6GR
Mouse	Lenovo	3D optical Mouse	N/A

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 1.56\text{dB}$ (9KHz-30MHz)
		$\pm 4.80\text{dB}$ (30MHz-1GHz)
		$\pm 4.80\text{dB}$ (1GHz-18GHz)
		$\pm 4.80\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number:717327

- **ISED (CAB Identifier: CN0120)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
2	LISN	R&S	ENV216	SUWI-01-19-03	5/8/2025	5/7/2026
3	LISN	Schwarzbeck	ENV216	SUWI-01-19-04	5/8/2025	5/7/2026
4	Test Software	Tonscend	JS32-CE 4.0.0.2	SUWI-02-09-05	N.C.R	N.C.R
5	Test Cable	Tonscend	NA	SUWI-01-03-04	2025/4/22	2026/4/21
RF Conducted Test						
1	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
2	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2025	11/20/2026
3	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/14/2026	1/13/2027
4	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-08-01	1/14/2026	1/13/2027
6	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	11/21/2025	11/20/2026
7	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	5/8/2025	5/7/2026
8	Wideband Radio Communication Test Station	Anritsu	MT8000A	SUWI-01-34-02	11/21/2025	11/20/2026
9	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/21/2025	11/20/2026
10	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/21/2025	11/20/2026
11	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/21/2025	11/20/2026
12	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
13	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/13/2025	2/12/2026
14	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2025	5/6/2026
15	Measurement Software	TST	TST 272 V2.02	SUWI-03-55-03	NCR	NCR
16	RF Control unit	TST	TSCB3023R2	SUWI-02-20-01	NCR	NCR
17	RFCables	Tonscend	NA	SUWI-01-03-01	1/15/2026	1/14/2027
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026

2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-09	11/21/2025	11/20/2026
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/14/2026	1/13/2027
6	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	VULB 9168	SUWI-01-11-04	9/10/2025	9/9/2027
7	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS-ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS-ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/14/2026	1/13/2027
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/14/2026	1/13/2027
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/14/2026	1/13/2027
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	11/21/2025	11/20/2026
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	8/25/2025	8/24/2026
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	8/26/2025	8/25/2026
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/21/2025	11/20/2026
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/14/2026	1/13/2027
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/13/2025	2/12/2026
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR
21	RF Control unit	Tonscend	JS0806-1	SUWI-02-20-01	NCR	NCR
22	RFCables	Tonscend	NA	SUWI-01-03-02	1/15/2026	1/14/2027

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is Integral Antenna and no consideration of replacement. The best case gain of the

UNII-5: 0.6dBi(Ant5); -2.5dBi(Ant6);

UNII-6: 0.2dBi(Ant5); -2.5dBi(Ant6);

UNII-7: -0.3dBi(Ant5); -2.5dBi(Ant6);

UNII-8: -1.3dBi(Ant5); -2.2dBi(Ant6);

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 50\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark 1: Level=Read Level+ Cable Loss+ LISN Factor

Remark 2: Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case.


Test Mode: 09; Line: Live line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.2130	9.96	32.72	42.68	63.09	20.41	16.34	26.30	53.09	26.79	PASS
2	0.3885	9.96	29.94	39.90	58.10	18.20	16.25	26.21	48.10	21.89	PASS
3	0.5325	9.94	31.33	41.27	56.00	14.73	16.73	26.67	46.00	19.33	PASS
4	0.7710	9.95	29.20	39.15	56.00	16.85	16.63	26.58	46.00	19.42	PASS
5	1.3155	9.94	21.15	31.09	56.00	24.91	10.89	20.83	46.00	25.17	PASS
6	2.4000	10.12	14.58	24.70	56.00	31.30	8.21	18.33	46.00	27.67	PASS

Test Mode: 09; Line: Neutral Line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.3120	9.97	29.79	39.76	59.92	20.16	16.93	26.90	49.92	23.02	PASS
2	0.4065	9.94	29.49	39.43	57.72	18.29	19.29	29.23	47.72	18.49	PASS
3	0.6180	9.92	32.56	42.48	56.00	13.52	16.13	26.05	46.00	19.95	PASS
4	0.7575	9.92	28.91	38.83	56.00	17.17	13.88	23.80	46.00	22.20	PASS
5	0.9195	9.90	26.02	35.92	56.00	20.08	13.48	23.38	46.00	22.62	PASS
6	19.4145	10.91	32.97	43.88	60.00	16.12	22.74	33.65	50.00	16.35	PASS

7.2 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only below points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
2. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.


Test Mode: 09; Polarity: Horizontal



Final Data List

NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.005	14.30	-41.06	28.20	40.00	11.80	154	313	Horizontal
2	82.865	8.87	-40.54	30.18	40.00	9.82	179	56	Horizontal
3	95.2325	10.52	-40.41	22.36	43.50	21.14	164	236	Horizontal
4	190.535	10.60	-39.36	27.71	43.50	15.79	111	17	Horizontal
5	240.005	12.50	-38.73	26.13	46.00	19.87	152	191	Horizontal
6	992.4825	21.95	-33.77	23.29	54.00	30.71	145	335	Horizontal

Test Mode: 09; Polarity: Vertical



Final Data List

NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.2475	14.25	-41.06	29.12	40.00	10.88	193	17	Vertical
2	79.47	8.35	-40.59	27.69	40.00	12.31	152	170	Vertical
3	111.2375	12.03	-40.13	19.97	43.50	23.53	186	344	Vertical
4	170.8925	9.60	-39.54	21.22	43.50	22.28	174	321	Vertical
5	240.005	12.50	-38.73	17.79	46.00	28.21	125	239	Vertical
6	980.6	21.90	-33.79	24.24	54.00	29.76	118	223	Vertical

7.3 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.6 & 12.7

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3
*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C

Humidity: 44 % RH


Atmospheric Pressure: 1001 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

been tested, Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram



Above 1GHz


7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, The points marked on below plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

11be(EHT20)_TX_CH_001_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7945.3125	39.25	37.19	-18.82	57.62	88.20	30.58	Horizontal
2	8953.3333	46.32	37.97	-38.76	45.53	88.20	42.67	Horizontal
3	12738	43.23	39.59	-34.69	48.13	88.20	40.07	Horizontal
4	15402	41.90	39.08	-33.39	47.58	74.00	26.42	Horizontal
5	17848.6667	39.74	41.26	-30.67	50.33	74.00	23.67	Horizontal
6	17921.3333	30.81	41.47	-30.97	41.31	54.00	12.69	Horizontal

11be(EHT20)_TX_CH_001_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7856.5	39.25	37.01	-18.79	57.47	88.20	30.73	Vertical
2	9003.6667	46.02	38.00	-38.55	45.47	74.00	28.53	Vertical
3	11271.6667	43.11	39.14	-35.39	46.85	74.00	27.15	Vertical
4	13316.3333	42.42	40.06	-34.75	47.73	74.00	26.27	Vertical
5	17867.3333	39.58	41.32	-30.80	50.09	74.00	23.91	Vertical
6	17989	31.19	41.67	-30.76	42.10	54.00	11.90	Vertical

11be(EHT20)_TX_CH_045_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7889.75	40.60	37.08	-18.84	58.83	88.20	29.37	Horizontal
2	9578	45.38	38.06	-37.91	45.53	88.20	42.67	Horizontal
3	11864	42.30	38.78	-35.00	46.08	74.00	27.92	Horizontal
4	14529.6667	41.89	40.08	-34.54	47.43	88.20	40.77	Horizontal
5	17863.3333	39.53	41.30	-30.78	50.06	74.00	23.94	Horizontal
6	17888.3333	31.29	41.38	-30.96	41.71	54.00	12.29	Horizontal

11be(EHT20)_TX_CH_045_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7927.375	39.76	37.15	-18.84	58.08	88.20	30.12	Vertical
2	9482.3333	45.33	38.05	-38.21	45.16	74.00	28.84	Vertical
3	11553.3333	42.98	38.97	-35.19	46.76	74.00	27.24	Vertical
4	13911.6667	42.12	40.36	-34.39	48.08	88.20	40.12	Vertical
5	17974.3333	39.59	41.63	-30.80	50.41	74.00	23.59	Vertical
6	17996.6667	30.70	41.69	-30.73	41.66	54.00	12.34	Vertical

11be(EHT20)_TX_CH_093_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7970.6875	39.27	37.24	-18.80	57.71	88.20	30.49	Horizontal
2	9582	44.86	38.06	-37.89	45.02	88.20	43.18	Horizontal
3	11481.3333	43.47	39.01	-35.74	46.74	74.00	27.26	Horizontal
4	13795.6667	41.91	40.30	-34.88	47.33	88.20	40.87	Horizontal
5	17951.3333	39.06	41.56	-30.88	49.74	74.00	24.26	Horizontal
6	17955.3333	30.47	41.57	-30.86	41.18	54.00	12.82	Horizontal

11be(EHT20)_TX_CH_093_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7942.25	40.33	37.18	-18.83	58.69	88.20	29.51	Vertical
2	8990	46.22	37.99	-38.58	45.63	88.20	42.57	Vertical
3	10976	42.78	39.27	-35.73	46.32	74.00	27.68	Vertical
4	13750.6667	42.59	40.28	-34.85	48.01	88.20	40.19	Vertical
5	17987	39.45	41.66	-30.76	50.35	74.00	23.65	Vertical
6	17981.6667	30.44	41.65	-30.78	41.31	54.00	12.69	Vertical

11be(EHT20)_TX_CH_097_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7877.5	40.95	37.06	-18.83	59.18	88.20	29.02	Horizontal
2	9437	45.02	38.04	-38.28	44.79	74.00	29.21	Horizontal
3	10959.3333	43.59	39.25	-35.79	47.05	74.00	26.95	Horizontal
4	13317.3333	41.80	40.06	-34.75	47.11	74.00	26.89	Horizontal
5	17962.6667	38.91	41.59	-30.84	49.66	74.00	24.34	Horizontal
6	17849.6667	30.37	41.26	-30.68	40.96	54.00	13.04	Horizontal

11be(EHT20)_TX_CH_097_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7962.8125	39.59	37.23	-18.81	58.01	88.20	30.19	Vertical
2	9044.3333	46.86	38.00	-38.83	46.03	74.00	27.97	Vertical
3	11151.3333	42.27	39.21	-35.63	45.85	74.00	28.15	Vertical
4	13689	41.81	40.24	-34.77	47.29	88.20	40.91	Vertical
5	17800	38.79	41.12	-30.32	49.59	74.00	24.41	Vertical
6	17994.6667	30.06	41.68	-30.74	41.01	54.00	12.99	Vertical

11be(EHT20)_TX_CH_105_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7958.875	39.92	37.22	-18.81	58.32	88.20	29.88	Horizontal
2	9030.3333	46.51	38.00	-38.74	45.78	74.00	28.22	Horizontal
3	11514.3333	42.36	38.99	-35.57	45.78	74.00	28.22	Horizontal
4	14395.3333	42.09	40.16	-33.78	48.48	88.20	39.72	Horizontal
5	17230.6667	39.34	39.47	-31.35	47.46	88.20	40.74	Horizontal
6	17286	30.49	39.63	-31.54	38.58	68.20	29.62	Horizontal

11be(EHT20)_TX_CH_105_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7987.3125	39.47	37.27	-18.79	57.95	88.20	30.25	Vertical
2	9500.3333	45.66	38.05	-38.19	45.52	88.20	42.68	Vertical
3	11391.6667	43.10	39.06	-35.84	46.32	74.00	27.68	Vertical
4	13889	42.35	40.34	-34.37	48.32	88.20	39.88	Vertical
5	17961	39.25	41.59	-30.84	49.99	74.00	24.01	Vertical
6	17994.3333	30.21	41.68	-30.74	41.16	54.00	12.84	Vertical

11be(EHT20)_TX_CH_113_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7761.5625	39.98	36.82	-18.68	58.12	88.20	30.08	Horizontal
2	9483.6667	44.84	38.05	-38.21	44.68	74.00	29.32	Horizontal
3	12797.6667	41.71	39.66	-34.59	46.77	88.20	41.43	Horizontal
4	14679.3333	40.92	39.99	-33.69	47.23	88.20	40.97	Horizontal
5	17995	39.09	41.69	-30.74	50.04	74.00	23.96	Horizontal
6	17907	30.67	41.43	-31.02	41.08	54.00	12.92	Horizontal

11be(EHT20)_TX_CH_113_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7996.0625	40.28	37.29	-18.78	58.79	88.20	29.41	Vertical
2	9526.3333	45.92	38.05	-38.10	45.88	88.20	42.32	Vertical
3	11559	42.29	38.96	-35.14	46.12	74.00	27.88	Vertical
4	13790.3333	41.57	40.30	-34.87	46.99	88.20	41.21	Vertical
5	17951.6667	39.16	41.56	-30.87	49.85	74.00	24.15	Vertical
6	17983.6667	30.69	41.65	-30.77	41.57	54.00	12.43	Vertical

11be(EHT20)_TX_CH_117_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.0625	39.49	37.28	-18.79	57.98	88.20	30.22	Horizontal
2	9949	44.43	38.09	-37.34	45.18	88.20	43.02	Horizontal
3	11436.3333	43.13	39.04	-35.82	46.34	74.00	27.66	Horizontal
4	13931.3333	41.63	40.37	-34.53	47.47	88.20	40.73	Horizontal
5	17374.3333	39.70	39.89	-31.83	47.76	88.20	40.44	Horizontal
6	17332.3333	31.06	39.76	-31.69	39.13	68.20	29.07	Horizontal

11be(EHT20)_TX_CH_117_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7792.625	39.41	36.89	-18.70	57.59	88.20	30.61	Vertical
2	9412	45.31	38.04	-38.31	45.04	74.00	28.96	Vertical
3	10989.6667	43.33	39.29	-35.69	46.93	74.00	27.07	Vertical
4	13866.6667	41.60	40.33	-34.50	47.43	88.20	40.77	Vertical
5	17817	38.65	41.17	-30.44	49.38	74.00	24.62	Vertical
6	17978	30.75	41.64	-30.79	41.60	54.00	12.40	Vertical

11be(EHT20)_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7849.0625	39.52	37.00	-18.78	57.73	88.20	30.47	Horizontal
2	9545.6667	46.33	38.05	-38.03	46.36	88.20	41.84	Horizontal
3	11391.3333	42.53	39.07	-35.84	45.76	74.00	28.24	Horizontal
4	14384.3333	41.10	40.17	-33.86	47.41	88.20	40.79	Horizontal
5	17983.6667	38.84	41.65	-30.77	49.72	74.00	24.28	Horizontal
6	17982.3333	30.51	41.65	-30.78	41.38	54.00	12.62	Horizontal

11be(EHT20)_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7996.5	39.49	37.29	-18.78	58.00	88.20	30.20	Vertical
2	9424.3333	45.38	38.04	-38.30	45.13	74.00	28.87	Vertical
3	11720	42.34	38.87	-35.52	45.69	74.00	28.31	Vertical
4	14159	41.90	40.30	-34.96	47.24	88.20	40.96	Vertical
5	17929.6667	39.76	41.50	-30.95	50.31	74.00	23.69	Vertical
6	17971	30.13	41.62	-30.81	40.93	54.00	13.07	Vertical

11be(EHT20)_TX_CH_185_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7842.0625	39.57	36.98	-18.77	57.78	88.20	30.42	Horizontal
2	8922.6667	46.65	37.95	-38.91	45.69	88.20	42.51	Horizontal
3	11928.3333	42.15	38.74	-34.93	45.96	74.00	28.04	Horizontal
4	14966	41.05	39.82	-33.75	47.12	88.20	41.08	Horizontal
5	17895.6667	39.87	41.40	-31.01	50.26	74.00	23.74	Horizontal
6	17964	30.56	41.60	-30.84	41.32	54.00	12.68	Horizontal

11be(EHT20)_TX_CH_185_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7931.75	40.32	37.16	-18.83	58.65	88.20	29.55	Vertical
2	8798.3333	46.23	37.86	-39.14	44.95	88.20	43.25	Vertical
3	10916.3333	42.93	39.20	-35.93	46.20	74.00	27.80	Vertical
4	13868.6667	42.11	40.33	-34.49	47.96	88.20	40.24	Vertical
5	17880.3333	39.14	41.35	-30.90	49.59	74.00	24.41	Vertical
6	17984.3333	30.25	41.65	-30.77	41.13	54.00	12.87	Vertical

11be(EHT20)_TX_CH_189_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7972.875	39.28	37.25	-18.80	57.72	88.20	30.48	Horizontal
2	9067.3333	46.85	38.01	-38.99	45.87	74.00	28.13	Horizontal
3	11915	42.07	38.75	-34.87	45.95	74.00	28.05	Horizontal
4	13792.6667	44.61	40.30	-34.88	50.03	88.20	38.17	Horizontal
5	17971	38.98	41.62	-30.81	49.78	74.00	24.22	Horizontal
6	17867.6667	30.53	41.32	-30.81	41.04	54.00	12.96	Horizontal

11be(EHT20)_TX_CH_189_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7960.625	40.25	37.22	-18.81	58.66	88.20	29.54	Vertical
2	9016.6667	46.54	38.00	-38.64	45.90	74.00	28.10	Vertical
3	10974.6667	43.02	39.27	-35.74	46.55	74.00	27.45	Vertical
4	13924.3333	42.12	40.36	-34.48	48.00	88.20	40.20	Vertical
5	17992.6667	38.43	41.68	-30.74	49.37	74.00	24.63	Vertical
6	18000	30.41	41.70	-30.72	41.39	54.00	12.61	Vertical

11be(EHT20)_TX_CH_209_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7965.4375	40.02	37.23	-18.81	58.44	88.20	29.76	Horizontal
2	9009.6667	45.47	38.00	-38.60	44.88	74.00	29.12	Horizontal
3	11376	42.66	39.07	-35.75	45.99	74.00	28.01	Horizontal
4	13987	42.68	40.39	-34.92	48.15	88.20	40.05	Horizontal
5	17815.6667	38.75	41.17	-30.43	49.48	74.00	24.52	Horizontal
6	17997.3333	30.41	41.69	-30.73	41.37	54.00	12.63	Horizontal

11be(EHT20)_TX_CH_209_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7917.3125	40.08	37.13	-18.85	58.37	88.20	29.83	Vertical
2	8887.3333	46.09	37.92	-39.04	44.98	88.20	43.22	Vertical
3	10943	42.92	39.23	-35.84	46.31	74.00	27.69	Vertical
4	13988.6667	42.61	40.39	-34.93	48.07	88.20	40.13	Vertical
5	17921	39.54	41.47	-30.97	50.04	74.00	23.96	Vertical
6	17286.3333	30.68	39.63	-31.54	38.77	68.20	29.43	Vertical

11be(EHT20)_TX_CH_233_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7907.6875	39.51	37.12	-18.85	57.77	88.20	30.43	Horizontal
2	9538.6667	44.89	38.05	-38.05	44.89	88.20	43.31	Horizontal
3	12813	42.88	39.68	-34.62	47.93	88.20	40.27	Horizontal
4	15207	40.72	39.43	-33.30	46.85	88.20	41.35	Horizontal
5	17883.3333	39.66	41.36	-30.92	50.10	74.00	23.90	Horizontal
6	17993.6667	30.11	41.68	-30.74	41.05	54.00	12.95	Horizontal

11be(EHT20)_TX_CH_233_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7949.25	40.11	37.20	-18.82	58.49	88.20	29.71	Vertical
2	9011.6667	46.57	38.00	-38.61	45.96	74.00	28.04	Vertical
3	11331.6667	43.01	39.10	-35.48	46.63	74.00	27.37	Vertical
4	13881.3333	42.16	40.34	-34.42	48.08	88.20	40.12	Vertical
5	17992.6667	39.38	41.68	-30.74	50.32	74.00	23.68	Vertical
6	17999.3333	30.37	41.70	-30.72	41.35	54.00	12.65	Vertical

11be(EHT40)_TX_CH_003_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7982.5	39.60	37.27	-18.79	58.07	88.20	30.13	Horizontal
2	9372.6667	44.85	38.04	-38.42	44.46	74.00	29.54	Horizontal
3	12310.3333	42.01	39.07	-34.31	46.77	74.00	27.23	Horizontal
4	14498.6667	42.00	40.10	-34.65	47.45	74.00	26.55	Horizontal
5	17967	38.95	41.60	-30.83	49.73	74.00	24.27	Horizontal
6	12307.3333	33.93	39.07	-34.29	38.71	54.00	15.29	Horizontal

11be(EHT40)_TX_CH_003_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7856.0625	38.86	37.01	-18.79	57.08	88.20	31.12	Vertical
2	8999.3333	45.25	38.00	-38.53	44.72	88.20	43.48	Vertical
3	10920.3333	43.16	39.20	-35.92	46.44	74.00	27.56	Vertical
4	13829.6667	41.82	40.31	-34.71	47.42	88.20	40.78	Vertical
5	17844	38.76	41.25	-30.64	49.37	74.00	24.63	Vertical
6	17852.6667	30.18	41.27	-30.70	40.75	54.00	13.25	Vertical

11be(EHT40)_TX_CH_043_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7890.625	39.40	37.08	-18.85	57.64	88.20	30.56	Horizontal
2	9443.6667	44.58	38.04	-38.27	44.36	74.00	29.64	Horizontal
3	10908	42.94	39.19	-35.96	46.17	74.00	27.83	Horizontal
4	13279	42.59	40.04	-34.75	47.88	74.00	26.12	Horizontal
5	17299.6667	40.51	39.67	-31.59	48.59	88.20	39.61	Horizontal
6	17759	29.43	41.00	-30.62	39.81	54.00	14.19	Horizontal

11be(EHT40)_TX_CH_043_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7954.5	40.00	37.21	-18.82	58.39	88.20	29.81	Vertical
2	9409.6667	44.68	38.04	-38.32	44.40	74.00	29.60	Vertical
3	11604	41.30	38.94	-34.77	45.46	74.00	28.54	Vertical
4	14686.6667	40.61	39.99	-33.63	46.96	88.20	41.24	Vertical
5	17967	38.97	41.60	-30.83	49.75	74.00	24.25	Vertical
6	17918.6667	30.52	41.46	-30.98	41.00	54.00	13.00	Vertical

11be(EHT40)_TX_CH_091_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7887.125	39.51	37.07	-18.84	57.74	88.20	30.46	Horizontal
2	9579.6667	45.58	38.06	-37.90	45.73	88.20	42.47	Horizontal
3	11512.3333	41.94	38.99	-35.59	45.34	74.00	28.66	Horizontal
4	13867	42.39	40.33	-34.50	48.23	88.20	39.97	Horizontal
5	17379	40.60	39.90	-31.84	48.66	88.20	39.54	Horizontal
6	17337.6667	30.61	39.78	-31.71	38.68	68.20	29.52	Horizontal

11be(EHT40)_TX_CH_091_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7980.75	40.39	37.26	-18.80	58.86	88.20	29.34	Vertical
2	9052.6667	45.49	38.01	-38.89	44.61	74.00	29.39	Vertical
3	10639.3333	43.95	38.87	-36.31	46.50	74.00	27.50	Vertical
4	13338	42.09	40.07	-34.79	47.37	74.00	26.63	Vertical
5	17999.6667	39.40	41.70	-30.72	50.38	74.00	23.62	Vertical
6	17991.3333	30.42	41.67	-30.75	41.35	54.00	12.65	Vertical

11be(EHT40)_TX_CH_099_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7853.875	38.93	37.01	-18.79	57.15	88.20	31.05	Horizontal
2	9025.3333	45.59	38.00	-38.70	44.89	74.00	29.11	Horizontal
3	11151.6667	43.06	39.21	-35.63	46.64	74.00	27.36	Horizontal
4	13720.3333	42.05	40.26	-34.83	47.48	88.20	40.72	Horizontal
5	17991.3333	38.51	41.67	-30.75	49.44	74.00	24.56	Horizontal
6	17988.6667	30.43	41.67	-30.76	41.34	54.00	12.66	Horizontal

11be(EHT40)_TX_CH_099_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7963.6875	40.47	37.23	-18.81	58.89	88.20	29.31	Vertical
2	8956.3333	45.92	37.97	-38.74	45.15	88.20	43.05	Vertical
3	11147.3333	42.36	39.21	-35.62	45.95	74.00	28.05	Vertical
4	13884	42.48	40.34	-34.40	48.42	88.20	39.78	Vertical
5	17975.3333	39.59	41.63	-30.80	50.42	74.00	23.58	Vertical
6	17987	30.59	41.66	-30.76	41.49	54.00	12.51	Vertical

11be(EHT40)_TX_CH_107_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7983.375	39.55	37.27	-18.79	58.02	88.20	30.18	Horizontal
2	8993.3333	45.99	38.00	-38.56	45.42	88.20	42.78	Horizontal
3	11330.3333	43.83	39.10	-35.47	47.46	74.00	26.54	Horizontal
4	13463.6667	43.08	40.13	-34.65	48.56	88.20	39.64	Horizontal
5	17273	39.29	39.59	-31.50	47.39	88.20	40.81	Horizontal
6	17281	30.63	39.61	-31.52	38.72	68.20	29.48	Horizontal

11be(EHT40)_TX_CH_107_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7933.9375	40.10	37.17	-18.83	58.44	88.20	29.76	Vertical
2	9022	46.19	38.00	-38.68	45.51	74.00	28.49	Vertical
3	11332.6667	42.86	39.10	-35.49	46.47	74.00	27.53	Vertical
4	13278.3333	42.33	40.04	-34.75	47.62	74.00	26.38	Vertical
5	17864.6667	39.14	41.31	-30.79	49.66	74.00	24.34	Vertical
6	17999.3333	30.34	41.70	-30.72	41.32	54.00	12.68	Vertical

11be(EHT40)_TX_CH_115_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7967.1875	39.75	37.23	-18.81	58.18	88.20	30.02	Horizontal
2	8953.6667	45.99	37.97	-38.76	45.20	88.20	43.00	Horizontal
3	10995.3333	43.23	39.29	-35.67	46.86	74.00	27.14	Horizontal
4	13628.6667	41.70	40.21	-34.47	47.44	88.20	40.76	Horizontal
5	17302.6667	39.74	39.68	-31.60	47.82	88.20	40.38	Horizontal
6	17283	31.33	39.62	-31.53	39.42	68.20	28.78	Horizontal

11be(EHT40)_TX_CH_115_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7944	39.53	37.19	-18.82	57.89	88.20	30.31	Vertical
2	9001.3333	46.60	38.00	-38.54	46.06	74.00	27.94	Vertical
3	10941	43.61	39.23	-35.85	46.99	74.00	27.01	Vertical
4	13455.3333	41.52	40.13	-34.69	46.96	88.20	41.24	Vertical
5	17331	39.18	39.76	-31.69	47.25	88.20	40.95	Vertical
6	17369.3333	30.52	39.87	-31.81	38.58	68.20	29.62	Vertical

11be(EHT40)_TX_CH_123_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7896.75	39.81	37.09	-18.86	58.05	88.20	30.15	Horizontal
2	8948	46.34	37.96	-38.78	45.52	88.20	42.68	Horizontal
3	12774.6667	43.14	39.63	-34.63	48.14	88.20	40.06	Horizontal
4	15248.3333	40.28	39.35	-33.31	46.32	88.20	41.88	Horizontal
5	17287.3333	39.69	39.63	-31.55	47.78	88.20	40.42	Horizontal
6	17284.6667	30.77	39.63	-31.54	38.86	68.20	29.34	Horizontal

11be(EHT40)_TX_CH_123_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7953.625	39.95	37.21	-18.82	58.34	88.20	29.86	Vertical
2	8965	46.09	37.98	-38.70	45.36	88.20	42.84	Vertical
3	10993.6667	42.98	39.29	-35.67	46.60	74.00	27.40	Vertical
4	13796.3333	42.51	40.30	-34.88	47.93	88.20	40.27	Vertical
5	17277.3333	39.70	39.60	-31.51	47.79	88.20	40.41	Vertical
6	17368	30.62	39.87	-31.81	38.68	68.20	29.52	Vertical

11be(EHT40)_TX_CH_147_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7936.125	39.13	37.17	-18.83	57.47	88.20	30.73	Horizontal
2	8906.6667	46.72	37.93	-38.99	45.67	88.20	42.53	Horizontal
3	10968.6667	43.07	39.26	-35.76	46.58	74.00	27.42	Horizontal
4	13319.6667	42.77	40.06	-34.75	48.08	74.00	25.92	Horizontal
5	17235.3333	39.42	39.48	-31.36	47.54	88.20	40.66	Horizontal
6	17355.3333	30.79	39.83	-31.77	38.85	68.20	29.35	Horizontal

11be(EHT40)_TX_CH_147_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7991.25	40.08	37.28	-18.79	58.58	88.20	29.62	Vertical
2	8990.6667	46.06	37.99	-38.58	45.48	88.20	42.72	Vertical
3	11399.3333	42.86	39.06	-35.89	46.03	74.00	27.97	Vertical
4	15083	41.38	39.65	-33.87	47.16	88.20	41.04	Vertical
5	17863.6667	39.95	41.30	-30.78	50.48	74.00	23.52	Vertical
6	17988	30.44	41.67	-30.76	41.35	54.00	12.65	Vertical

11be(EHT40)_TX_CH_179_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7986	40.71	37.27	-18.79	59.19	88.20	29.01	Horizontal
2	8934	45.83	37.95	-38.85	44.93	88.20	43.27	Horizontal
3	10990	43.24	39.29	-35.68	46.84	74.00	27.16	Horizontal
4	13627	42.38	40.21	-34.46	48.13	88.20	40.07	Horizontal
5	17024.3333	39.02	38.87	-31.07	46.82	88.20	41.38	Horizontal
6	17288	31.41	39.64	-31.55	39.50	68.20	28.70	Horizontal


11be(EHT40)_TX_CH_179_Vertical



Data List


NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7917.75	39.15	37.14	-18.85	57.44	88.20	30.76	Vertical
2	8948.3333	46.00	37.96	-38.78	45.18	88.20	43.02	Vertical
3	10938.3333	43.59	39.23	-35.86	46.96	74.00	27.04	Vertical
4	13629	42.46	40.21	-34.47	48.20	88.20	40.00	Vertical
5	17277	39.92	39.60	-31.51	48.01	88.20	40.19	Vertical
6	17253.3333	31.13	39.53	-31.43	39.24	68.20	28.96	Vertical

11be(EHT40)_TX_CH_187_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7904.1875	40.18	37.11	-18.86	58.43	88.20	29.77	Horizontal
2	8937.3333	46.03	37.96	-38.84	45.15	88.20	43.05	Horizontal
3	11318.6667	43.45	39.11	-35.40	47.16	74.00	26.84	Horizontal
4	13808.6667	41.84	40.30	-34.83	47.31	88.20	40.89	Horizontal
5	17980	38.87	41.64	-30.78	49.73	74.00	24.27	Horizontal
6	17983	30.25	41.65	-30.77	41.13	54.00	12.87	Horizontal

11be(EHT40)_TX_CH_187_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.5	39.32	37.28	-18.79	57.81	88.20	30.39	Vertical
2	9585.6667	46.53	38.06	-37.88	46.71	88.20	41.49	Vertical
3	10649	43.24	38.88	-36.28	45.84	74.00	28.16	Vertical
4	13081.6667	41.25	39.94	-34.78	46.41	88.20	41.79	Vertical
5	17847	40.64	41.26	-30.66	51.24	74.00	22.76	Vertical
6	17933	30.59	41.51	-30.93	41.16	54.00	12.84	Vertical

11be(EHT40)_TX_CH_203_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7993.875	39.08	37.29	-18.78	57.58	88.20	30.62	Horizontal
2	8914	46.16	37.94	-38.95	45.15	88.20	43.05	Horizontal
3	10967	42.99	39.26	-35.76	46.49	74.00	27.51	Horizontal
4	12764	42.40	39.62	-34.65	47.37	88.20	40.83	Horizontal
5	17989.6667	39.24	41.67	-30.75	50.16	74.00	23.84	Horizontal
6	17852.6667	30.64	41.27	-30.70	41.21	54.00	12.79	Horizontal

11be(EHT40)_TX_CH_203_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7888.4375	40.01	37.08	-18.84	58.24	88.20	29.96	Vertical
2	8598.6667	47.20	37.72	-39.09	45.83	88.20	42.37	Vertical
3	10915.6667	42.97	39.20	-35.94	46.23	74.00	27.77	Vertical
4	13932	42.14	40.37	-34.53	47.97	88.20	40.23	Vertical
5	17841.3333	39.61	41.24	-30.62	50.23	74.00	23.77	Vertical
6	17992	30.88	41.68	-30.75	41.81	54.00	12.19	Vertical

11be(EHT40)_TX_CH_227_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7987.75	39.36	37.28	-18.79	57.85	88.20	30.35	Horizontal
2	9001	45.99	38.00	-38.54	45.45	74.00	28.55	Horizontal
3	10801.6667	44.17	39.06	-36.42	46.81	74.00	27.19	Horizontal
4	13884.3333	41.88	40.34	-34.40	47.82	88.20	40.38	Horizontal
5	17858.3333	38.68	41.29	-30.74	49.23	74.00	24.77	Horizontal
6	17999.6667	30.25	41.70	-30.72	41.23	54.00	12.77	Horizontal

11be(EHT40)_TX_CH_227_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7966.3125	39.81	37.23	-18.81	58.24	88.20	29.96	Vertical
2	8930.3333	46.46	37.95	-38.87	45.54	88.20	42.66	Vertical
3	10942.6667	43.22	39.23	-35.84	46.61	74.00	27.39	Vertical
4	13642	41.31	40.22	-34.54	47.00	88.20	41.20	Vertical
5	17931	39.74	41.50	-30.94	50.30	74.00	23.70	Vertical
6	17996.3333	30.39	41.69	-30.73	41.35	54.00	12.65	Vertical

11be(EHT80)_TX_CH_007_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7988.1875	40.05	37.28	-18.79	58.54	88.20	29.66	Horizontal
2	9064	46.26	38.01	-38.97	45.30	74.00	28.70	Horizontal
3	10970	42.79	39.26	-35.75	46.30	74.00	27.70	Horizontal
4	13288	42.55	40.04	-34.73	47.86	74.00	26.14	Horizontal
5	17978	39.00	41.64	-30.79	49.85	74.00	24.15	Horizontal
6	17985	30.98	41.66	-30.77	41.87	54.00	12.13	Horizontal

11be(EHT80)_TX_CH_007_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7897.1875	39.42	37.09	-18.86	57.66	88.20	30.54	Vertical
2	9086.3333	46.70	38.01	-39.12	45.59	74.00	28.41	Vertical
3	11396	43.42	39.06	-35.87	46.62	74.00	27.38	Vertical
4	13616	41.81	40.21	-34.41	47.61	88.20	40.59	Vertical
5	17852.6667	39.08	41.27	-30.70	49.65	74.00	24.35	Vertical
6	17240.6667	30.76	39.50	-31.38	38.88	68.20	29.32	Vertical

11be(EHT80)_TX_CH_039_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	8000	39.27	37.30	-18.78	57.79	88.20	30.41	Horizontal
2	9507.6667	45.92	38.05	-38.16	45.81	88.20	42.39	Horizontal
3	12264.6667	42.34	39.02	-34.55	46.81	74.00	27.19	Horizontal
4	15052.3333	41.34	39.71	-33.90	47.14	88.20	41.06	Horizontal
5	17998	39.44	41.69	-30.73	50.41	74.00	23.59	Horizontal
6	17988	30.49	41.67	-30.76	41.40	54.00	12.60	Horizontal

11be(EHT80)_TX_CH_039_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7963.25	39.30	37.23	-18.81	57.72	88.20	30.48	Vertical
2	8926	45.95	37.95	-38.89	45.01	88.20	43.19	Vertical
3	11071.6667	42.54	39.26	-35.61	46.19	74.00	27.81	Vertical
4	13884.3333	43.54	40.34	-34.40	49.48	88.20	38.72	Vertical
5	17863	39.53	41.30	-30.77	50.06	74.00	23.94	Vertical
6	17863	30.90	41.30	-30.77	41.43	54.00	12.57	Vertical

11be(EHT80)_TX_CH_087_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7991.25	39.72	37.28	-18.79	58.22	88.20	29.98	Horizontal
2	9054.3333	46.84	38.01	-38.90	45.95	74.00	28.05	Horizontal
3	10969	43.34	39.26	-35.76	46.85	74.00	27.15	Horizontal
4	13765.3333	42.42	40.28	-34.86	47.84	88.20	40.36	Horizontal
5	17830.3333	39.29	41.21	-30.54	49.96	74.00	24.04	Horizontal
6	17959	30.46	41.58	-30.85	41.19	54.00	12.81	Horizontal

11be(EHT80)_TX_CH_087_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.9375	39.67	37.28	-18.79	58.16	88.20	30.04	Vertical
2	10400	44.62	38.58	-36.38	46.82	88.20	41.38	Vertical
3	12799.3333	41.40	39.66	-34.59	46.47	88.20	41.73	Vertical
4	15391.6667	41.16	39.09	-33.40	46.85	74.00	27.15	Vertical
5	17988.6667	38.91	41.67	-30.76	49.82	74.00	24.18	Vertical
6	17863.3333	30.90	41.30	-30.78	41.43	54.00	12.57	Vertical

11be(EHT80)_TX_CH_103_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7875.3125	40.41	37.05	-18.82	58.64	88.20	29.56	Horizontal
2	9375.3333	45.44	38.04	-38.41	45.06	74.00	28.94	Horizontal
3	11275.6667	42.72	39.13	-35.38	46.47	74.00	27.53	Horizontal
4	13331	42.40	40.07	-34.78	47.69	74.00	26.31	Horizontal
5	16644	40.16	38.52	-32.63	46.04	88.20	42.16	Horizontal
6	16772.3333	31.52	38.62	-32.42	37.72	68.20	30.48	Horizontal

11be(EHT80)_TX_CH_103_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7978.5625	39.16	37.26	-18.80	57.62	88.20	30.58	Vertical
2	8962	46.69	37.97	-38.72	45.95	88.20	42.25	Vertical
3	10945	43.48	39.23	-35.84	46.88	74.00	27.12	Vertical
4	14314.6667	42.36	40.21	-34.39	48.18	88.20	40.02	Vertical
5	17939	39.39	41.52	-30.92	50.00	74.00	24.00	Vertical
6	17989.3333	30.30	41.67	-30.75	41.21	54.00	12.79	Vertical

11be(EHT80)_TX_CH_119_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7951.4375	39.32	37.20	-18.82	57.70	88.20	30.50	Horizontal
2	9008.6667	46.52	38.00	-38.59	45.93	74.00	28.07	Horizontal
3	11307.6667	42.14	39.12	-35.34	45.92	74.00	28.08	Horizontal
4	13850.3333	43.17	40.33	-34.59	48.90	88.20	39.30	Horizontal
5	17953.6667	39.31	41.57	-30.87	50.01	74.00	23.99	Horizontal
6	17814	30.08	41.16	-30.42	40.82	54.00	13.18	Horizontal

11be(EHT80)_TX_CH_119_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7958.4375	39.82	37.22	-18.81	58.22	88.20	29.98	Vertical
2	10110.3333	44.88	38.23	-36.94	46.17	88.20	42.03	Vertical
3	12903.6667	43.19	39.78	-34.85	48.12	88.20	40.08	Vertical
4	16097.6667	40.29	38.08	-32.01	46.36	74.00	27.64	Vertical
5	17990	39.02	41.67	-30.75	49.94	74.00	24.06	Vertical
6	17997	30.71	41.69	-30.73	41.67	54.00	12.33	Vertical

11be(EHT80)_TX_CH_151_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7966.75	39.91	37.23	-18.81	58.34	88.20	29.86	Horizontal
2	8962	46.25	37.97	-38.72	45.51	88.20	42.69	Horizontal
3	10991.3333	42.91	39.29	-35.68	46.52	74.00	27.48	Horizontal
4	13859.6667	42.45	40.33	-34.54	48.24	88.20	39.96	Horizontal
5	17981	39.36	41.64	-30.78	50.22	74.00	23.78	Horizontal
6	17863.6667	30.52	41.30	-30.78	41.05	54.00	12.95	Horizontal

11be(EHT80)_TX_CH_151_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7969.375	39.62	37.24	-18.80	58.05	88.20	30.15	Vertical
2	8919	46.18	37.94	-38.93	45.20	88.20	43.00	Vertical
3	10965.3333	43.11	39.26	-35.77	46.60	74.00	27.40	Vertical
4	13940.3333	41.26	40.37	-34.59	47.04	88.20	41.16	Vertical
5	17986.6667	38.84	41.66	-30.76	49.74	74.00	24.26	Vertical
6	17881.3333	30.90	41.36	-30.91	41.35	54.00	12.65	Vertical

11be(EHT80)_TX_CH_183_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.0625	39.41	37.28	-18.79	57.90	88.20	30.30	Horizontal
2	9549.6667	46.13	38.05	-38.01	46.17	88.20	42.03	Horizontal
3	11845.3333	43.49	38.79	-35.11	47.18	74.00	26.82	Horizontal
4	13921.3333	42.70	40.36	-34.46	48.60	88.20	39.60	Horizontal
5	17426.6667	39.71	40.04	-31.80	47.94	88.20	40.26	Horizontal
6	17252.3333	31.22	39.53	-31.42	39.33	68.20	28.87	Horizontal


11be(EHT80)_TX_CH_183_Vertical



Data List


NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7935.25	39.56	37.17	-18.83	57.90	88.20	30.30	Vertical
2	8946.6667	46.41	37.96	-38.79	45.58	88.20	42.62	Vertical
3	10925	43.14	39.21	-35.90	46.45	74.00	27.55	Vertical
4	14669.6667	41.01	40.00	-33.76	47.25	88.20	40.95	Vertical
5	17994.3333	38.62	41.68	-30.74	49.57	74.00	24.43	Vertical
6	17999.6667	30.62	41.70	-30.72	41.60	54.00	12.40	Vertical

11be(EHT80)_TX_CH_199_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7992.5625	39.74	37.29	-18.79	58.24	88.20	29.96	Horizontal
2	8884.6667	47.04	37.92	-39.04	45.92	88.20	42.28	Horizontal
3	10973.3333	43.11	39.27	-35.74	46.64	74.00	27.36	Horizontal
4	13924	41.56	40.36	-34.48	47.44	88.20	40.76	Horizontal
5	17985.3333	39.21	41.66	-30.77	50.10	74.00	23.90	Horizontal
6	17999	30.11	41.70	-30.72	41.08	54.00	12.92	Horizontal

11be(EHT80)_TX_CH_199_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7976.8125	39.15	37.25	-18.80	57.61	88.20	30.59	Vertical
2	8993	45.98	38.00	-38.56	45.41	88.20	42.79	Vertical
3	11008.6667	42.80	39.29	-35.64	46.45	74.00	27.55	Vertical
4	12786.3333	43.41	39.64	-34.61	48.44	88.20	39.76	Vertical
5	17995.3333	39.33	41.69	-30.73	50.28	74.00	23.72	Vertical
6	17999.3333	30.42	41.70	-30.72	41.40	54.00	12.60	Vertical

11be(EHT80)_TX_CH_215_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7956.6875	39.93	37.21	-18.81	58.33	88.20	29.87	Horizontal
2	9062.6667	45.94	38.01	-38.96	44.99	74.00	29.01	Horizontal
3	11444	43.07	39.03	-35.81	46.29	74.00	27.71	Horizontal
4	13798.6667	42.78	40.30	-34.88	48.20	88.20	40.00	Horizontal
5	16757	40.11	38.61	-32.51	46.21	88.20	41.99	Horizontal
6	17336.6667	31.04	39.78	-31.71	39.11	68.20	29.09	Horizontal

11be(EHT80)_TX_CH_215_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.5	39.76	37.28	-18.79	58.25	88.20	29.95	Vertical
2	8962.6667	45.72	37.97	-38.71	44.98	88.20	43.22	Vertical
3	11443.3333	42.83	39.03	-35.81	46.05	74.00	27.95	Vertical
4	14712.6667	40.41	39.97	-33.61	46.77	88.20	41.43	Vertical
5	17997.6667	39.25	41.69	-30.73	50.22	74.00	23.78	Vertical
6	17875	30.65	41.34	-30.86	41.13	54.00	12.87	Vertical

11be(EHT160)_TX_CH_015_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7976.8125	39.41	37.25	-18.80	57.87	88.20	30.33	Horizontal
2	8828.3333	45.99	37.88	-39.11	44.76	88.20	43.44	Horizontal
3	11346.3333	42.88	39.09	-35.57	46.40	74.00	27.60	Horizontal
4	14844.3333	40.76	39.89	-33.77	46.88	88.20	41.32	Horizontal
5	17941.6667	39.31	41.53	-30.91	49.93	74.00	24.07	Horizontal
6	17305.3333	30.79	39.69	-31.61	38.87	68.20	29.33	Horizontal

11be(EHT160)_TX_CH_015_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7971.5625	39.55	37.24	-18.80	57.99	88.20	30.21	Vertical
2	9001	45.47	38.00	-38.54	44.93	74.00	29.07	Vertical
3	10968.3333	43.24	39.26	-35.76	46.74	74.00	27.26	Vertical
4	13874.6667	41.29	40.34	-34.45	47.17	88.20	41.03	Vertical
5	17241.6667	39.52	39.50	-31.39	47.63	88.20	40.57	Vertical
6	17355.6667	31.20	39.83	-31.77	39.26	68.20	28.94	Vertical

11be(EHT160)_TX_CH_047_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7980.75	40.25	37.26	-18.80	58.72	88.20	29.48	Horizontal
2	8947	46.32	37.96	-38.79	45.49	88.20	42.71	Horizontal
3	11275.6667	42.58	39.13	-35.38	46.33	74.00	27.67	Horizontal
4	13860	42.40	40.33	-34.54	48.19	88.20	40.01	Horizontal
5	17967	40.20	41.60	-30.83	50.98	74.00	23.02	Horizontal
6	17968.6667	30.60	41.61	-30.82	41.39	54.00	12.61	Horizontal

11be(EHT160)_TX_CH_047_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7996.0625	40.11	37.29	-18.78	58.62	88.20	29.58	Vertical
2	9500	45.09	38.05	-38.19	44.95	74.00	29.05	Vertical
3	12206.3333	42.31	38.95	-35.07	46.18	74.00	27.82	Vertical
4	15036.6667	40.26	39.73	-33.92	46.07	88.20	42.13	Vertical
5	17372.6667	40.50	39.88	-31.82	48.56	88.20	39.64	Vertical
6	17334.6667	30.88	39.77	-31.70	38.95	68.20	29.25	Vertical

11be(EHT160)_TX_CH_079_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7957.5625	39.66	37.22	-18.81	58.06	88.20	30.14	Horizontal
2	8916.3333	46.87	37.94	-38.94	45.87	88.20	42.33	Horizontal
3	10974.3333	42.91	39.27	-35.74	46.44	74.00	27.56	Horizontal
4	13951.3333	41.92	40.38	-34.67	47.63	88.20	40.57	Horizontal
5	17813.3333	38.93	41.16	-30.42	49.67	74.00	24.33	Horizontal
6	17247.6667	30.77	39.52	-31.41	38.88	68.20	29.32	Horizontal

11be(EHT160)_TX_CH_079_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7994.3125	40.03	37.29	-18.78	58.53	88.20	29.67	Vertical
2	9549.6667	45.48	38.05	-38.01	45.52	88.20	42.68	Vertical
3	11859.6667	41.28	38.78	-35.02	45.04	74.00	28.96	Vertical
4	15176.3333	40.27	39.48	-33.43	46.32	88.20	41.88	Vertical
5	17975	39.26	41.63	-30.80	50.09	74.00	23.91	Vertical
6	17985.3333	30.42	41.66	-30.77	41.31	54.00	12.69	Vertical

11be(EHT160)_TX_CH_111_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7907.6875	39.71	37.12	-18.85	57.97	88.20	30.23	Horizontal
2	9592.6667	46.39	38.06	-37.86	46.59	88.20	41.61	Horizontal
3	11037.6667	42.21	39.28	-35.63	45.86	74.00	28.14	Horizontal
4	14694.6667	41.63	39.98	-33.58	48.04	88.20	40.16	Horizontal
5	17871.3333	40.13	41.33	-30.83	50.62	74.00	23.38	Horizontal
6	17809.3333	30.32	41.15	-30.39	41.08	54.00	12.92	Horizontal

11be(EHT160)_TX_CH_111_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7893.6875	39.20	37.09	-18.85	57.44	88.20	30.76	Vertical
2	9018.3333	45.75	38.00	-38.65	45.10	74.00	28.90	Vertical
3	12257.3333	42.69	39.01	-34.61	47.08	74.00	26.92	Vertical
4	15407	41.16	39.07	-33.35	46.87	74.00	27.13	Vertical
5	17243	39.67	39.50	-31.39	47.78	88.20	40.42	Vertical
6	17991.3333	30.60	41.67	-30.75	41.53	54.00	12.47	Vertical

11be(EHT160)_TX_CH_143_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7922.125	39.66	37.14	-18.84	57.96	88.20	30.24	Horizontal
2	8593	47.00	37.72	-39.15	45.57	88.20	42.63	Horizontal
3	10664	43.50	38.90	-36.23	46.17	74.00	27.83	Horizontal
4	13003.3333	41.80	39.90	-34.85	46.85	88.20	41.35	Horizontal
5	17951.3333	39.42	41.56	-30.88	50.10	74.00	23.90	Horizontal
6	17819	29.83	41.18	-30.46	40.55	54.00	13.45	Horizontal

11be(EHT160)_TX_CH_143_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7888	40.35	37.08	-18.84	58.58	88.20	29.62	Vertical
2	9604.3333	45.04	38.06	-37.82	45.28	88.20	42.92	Vertical
3	12135.3333	41.67	38.86	-34.99	45.54	74.00	28.46	Vertical
4	13871	42.34	40.34	-34.48	48.20	88.20	40.00	Vertical
5	17856.6667	39.06	41.28	-30.73	49.62	74.00	24.38	Vertical
6	17976.6667	30.25	41.63	-30.79	41.09	54.00	12.91	Vertical

11be(EHT160)_TX_CH_175_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7979.875	39.28	37.26	-18.80	57.74	88.20	30.46	Horizontal
2	9555	45.06	38.06	-37.99	45.12	88.20	43.08	Horizontal
3	12281.6667	41.26	39.04	-34.39	45.90	74.00	28.10	Horizontal
4	14669	40.73	40.00	-33.76	46.97	88.20	41.23	Horizontal
5	17847.3333	40.05	41.26	-30.66	50.65	74.00	23.35	Horizontal

11be(EHT160)_TX_CH_175_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7917.3125	39.37	37.13	-18.85	57.66	88.20	30.54	Vertical
2	8600.6667	46.52	37.72	-39.08	45.16	88.20	43.04	Vertical
3	10888.3333	43.97	39.17	-36.04	47.09	74.00	26.91	Vertical
4	15852.6667	40.54	38.27	-33.04	45.77	74.00	28.23	Vertical
5	17975.3333	38.89	41.63	-30.80	49.72	74.00	24.28	Vertical
6	17992	30.41	41.68	-30.75	41.34	54.00	12.66	Vertical

11be(EHT160)_TX_CH_207_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7942.6875	39.53	37.19	-18.83	57.89	88.20	30.31	Horizontal
2	9005	45.64	38.00	-38.56	45.08	74.00	28.92	Horizontal
3	10861.6667	44.36	39.13	-36.16	47.34	74.00	26.66	Horizontal
4	12865.3333	41.90	39.74	-34.76	46.88	88.20	41.32	Horizontal
5	17254.6667	39.59	39.54	-31.43	47.70	88.20	40.50	Horizontal
6	17307	30.67	39.69	-31.61	38.75	68.20	29.45	Horizontal