

TEST REPORT

Application No.: SUCR2512001219TL
FCC ID: RF41995B
Applicant: KEYENCE CORPORATION
Address of Applicant: 1-3-14, Higashinakajima Higashiyodogawa-ku, Osaka 533-8555, Japan
Manufacturer: KEYENCE CORPORATION
Address of Manufacturer: 1-3-14, Higashinakajima Higashiyodogawa-ku, Osaka 533-8555, Japan
Equipment Under Test (EUT):
EUT Description: Handheld Terminal
Model No.: BT-A800
Trade Mark: KEYENCE
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2025-12-22
Date of Test: 2026-02-23 to 2026-04-23
Date of Issue: 2026-04-23

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone:(86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Revision Record			
Version	Description	Date	Remark
00	Original	2026-04-23	/

Authorized for issue by:			
Tested By		Nature Shen	
		Nature_Shen/Project Engineer	
Approved By		Cedar cheng	
		Cedar Cheng /Reviewer	

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2020) Section 6.2	47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)	Pass
Radiated Emissions (Below 1GHz)		ANSI C63.10 (2020) Section 6.4,6.5	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions (Above 1GHz)		ANSI C63.10 (2020) Section 6.6 & 12.7	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		ANSI C63.10 (2020) Section 6.10.5 & 12.7.2	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
In-Band Emissions		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (b)	Pass
Contention-based Protocol		KDB 987594 D02 Section II.I.	47 CFR Part 15, Subpart E 15.407 (d)(6)	Pass
Duty Cycle		ANSI C63.10 (2020) Section 12.2	ANSI C63.10 (2020) Section 12.2	Pass
99% Bandwidth		ANSI C63.10 (2020) Section 12.5.3	ANSI C63.10 (2020) Section 12.5.3	Pass
26dB Emission bandwidth		ANSI C63.10 (2020) Section 12.5.2	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Maximum Conducted output power		ANSI C63.10 (2020) Section 12.4	47 CFR Part 15, Subpart E 15.407 (a)	Pass
Peak Power spectrum density		ANSI C63.10 (2020) Section 12.6	47 CFR Part 15, Subpart E 15.407 (a)	Pass

3 Contents

Page

1	COVER PAGE	1
2	Test Summary	3
3	Contents.....	4
4	General Information.....	5
4.1	Details of E.U.T.	5
4.2	Environment Parameter	5
4.3	Description of Support Units	6
4.4	Measurement Uncertainty & Decision Rule	6
4.5	Test Location	7
4.6	Test Facility	7
4.7	Deviation from Standards.....	7
4.8	Abnormalities from Standard Conditions.....	7
5	Equipment List	8
6	Radio Spectrum Technical Requirement.....	10
6.1	Antenna Requirement	10
7	Radio Spectrum Matter Test Results	11
7.1	Conducted Emissions at AC Power Line (150kHz-30MHz).....	11
7.2	Radiated Emissions (Below 1GHz)	15
7.3	Radiated Emissions (Above 1GHz).....	19
7.4	Radiated Emissions which fall in the restricted bands	114
7.5	In-Band Emissions	156
7.6	Contention-based Protocol.....	158
7.7	Duty Cycle	159
7.8	99% Bandwidth	160
7.9	26dB Emission bandwidth	161
7.10	Maximum Conducted output power	162
7.11	Peak Power spectrum density	164
8	Test Setup Photo	166
9	EUT Constructional Details (EUT Photos).....	166
2	Appendix.....	167

4 General Information

4.1 Details of E.U.T.

Hardware Version:	V1.04
Software Version:	T23
SN:	B0ES200005/B0ES200019
Power Supply:	5V
IEEE 802.11 WLAN Mode Supported:	☒ 802.11ax(HE20)/be(HE20): 20 MHz channel bandwidth) ☒ 802.11ax(HE40) /be(HE40): (40 MHz channel bandwidth) ☒ 802.11ax(HE80)/be(HE80): (80 MHz channel bandwidth) ☒ 802.11ax(HE160)/be(HE160) (160 MHz channel bandwidth) ☒ 802.11be(HE320) (320 MHz channel bandwidth)
Operation Frequency:	5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz
Modulation Type:	802.11ax: OFDM/OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM); 802.11be: OFDMA with enhancements (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024-QAM, 4096-QAM)
FCC Classification:	6GHz Low Power Indoor Client (6XD)
Antenna Type:	LDS Antenna
Smart System:	☒ MIMO 802.11ax/be: 2Tx & 2Rx
Antenna Gain:	UNII-5: 0.6dBi(Ant5); -2.5dBi(Ant6); UNII-6: 0.2dBi(Ant5); -2.5dBi(Ant6); UNII-7: -0.3dBi(Ant5); -2.5dBi(Ant6); UNII-8: -1.3dBi(Ant5); -2.2dBi(Ant6); (Provided by the manufacturer)

4.2 Environment Parameter

Environment Parameter	Selected Values During Tests	
Relative Humidity	Ambient	
Value	Temperature(°C)	Voltage(V)
NTNV	25	3.6
Note:		
NV:Normal Voltage	LV:Low Extreme Test Voltage	HV:High Extreme Test Voltage
NT:Normal Temperature	LT:Low Extreme Test Temperature	HT:High Extreme Test Temperature

4.3 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Computer	Lenovo	T14	2YK6GR
Mouse	Lenovo	3D optical Mouse	N/A

4.4 Measurement Uncertainty & Decision Rule

No.	Item	Measurement Uncertainty
1	Radio Frequency	$\pm 7.25 \times 10^{-8}$
2	Duty cycle	$\pm 0.37\%$
3	Occupied Bandwidth	$\pm 3\%$
4	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
5	RF conducted power	$\pm 0.75\text{dB}$
6	RF power density	$\pm 2.84\text{dB}$
7	Conducted Spurious emissions	$\pm 0.75\text{dB}$
8	RF Radiated power	$\pm 1.56\text{dB}$ (9KHz-30MHz)
		$\pm 4.80\text{dB}$ (30MHz-1GHz)
		$\pm 4.80\text{dB}$ (1GHz-18GHz)
		$\pm 4.80\text{dB}$ (18GHz-40GHz)
9	Temperature test	$\pm 1^\circ\text{C}$
10	Humidity test	$\pm 3\%$
11	Supply voltages	$\pm 1\%$
12	Time	$\pm 3\%$
Remark: The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results – compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit; – non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.		

4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.

South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu)
Pilot Free Trade Zone

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
3. Sample source: sent by customer.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 6336.01)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd.is accredited by the American Association for Laboratory Accreditation (A2LA).

- **FCC (Designation Number: CN1312)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized as an accredited testing laboratory. Test Firm Registration Number:717327

- **ISED (CAB Identifier: CN0120)**

SGS-CSTC Standards Technical Services (Suzhou) Co., Ltd. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory.

Company Number: 27594

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None

5 Equipment List

Item	Equipment	Manufacturer	Model	Inventory No	Cal Date	Cal. Due Date
Conducted Emission at Mains Terminals						
1	EMI Test Receive	R&S	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
2	LISN	R&S	ENV216	SUWI-01-19-03	5/8/2025	5/7/2026
3	LISN	Schwarzbeck	ENV216	SUWI-01-19-04	5/8/2025	5/7/2026
4	Test Software	Tonscend	JS32-CE_4.0.0.2	SUWI-02-09-05	N.C.R	N.C.R
RF Conducted Test						
1	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
2	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-15	11/21/2025	11/20/2026
3	MXG Vector signal genitor	KEYSIGHT	N5182B	SUWI-01-38-01	1/14/2026	1/13/2027
4	Signal Generator	ROHDE&SCHWARZ	SMW200A	SUWI-01-07-08	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-08-01	1/14/2026	1/13/2027
6	MXG Vector Signal Generator	ROHDE&SCHWARZ	SMR20	SUWI-01-33-01	11/21/2025	11/20/2026
7	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-13	5/8/2025	5/7/2026
8	Wideband Radio Communication Test Station	Anritsu	MT8000A	SUWI-01-34-02	11/21/2025	11/20/2026
9	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	11/21/2025	11/20/2026
10	Power meter	Anritsu	ML2495A	SUWI-01-31-01	11/21/2025	11/20/2026
11	Pulse power sensor	Anritsu	MA2411B	SUWI-01-32-01	11/21/2025	11/20/2026
12	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
13	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-07	2/11/2026	2/10/2027
14	Temperature Chamber	GIANT FORCE	ICT-017-40-SP-SD	SUWI-01-13-02	5/7/2025	5/6/2026
15	Measurement Software	TST	TST 272 V2.02	SUWI-03-55-03	NCR	NCR
16	RF Control unit	TST	TSCB3023R2	SUWI-02-20-01	NCR	NCR
17	RFCables	Tonscend	NA	SUWI-01-03-01	1/15/2026	1/14/2027
RF Radiated Test						
1	Semi-Anechoic Chamber	Brilliant-emc	N/A	SUWI-04-02-01	6/3/2023	6/2/2026
2	Signal Analyzer	ROHDE&SCHWARZ	FSW43	SUWI-01-02-04	1/14/2026	1/13/2027
3	Signal Analyzer	KEYSIGHT	N9020A	SUWI-01-02-09	11/21/2025	11/20/2026
4	Test receiver	ROHDE&SCHWARZ	ESR7	SUWI-01-10-01	1/14/2026	1/13/2027
5	Signal Generator	ROHDE&SCHWARZ	SMW100A	SUWI-01-18-01	1/14/2026	1/13/2027

6	Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	VULB 9168	SUWI-01-11-04	9/10/2025	9/9/2027
7	Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9120D	SUWI-01-11-02	5/7/2025	5/6/2027
8	Receiving antenna	SCHWRZBECK MESS- ELEKTRONIK	BBHA 9170	SUWI-01-11-03	5/7/2025	5/6/2027
9	Active Loop Antenna	SCHWRZBECK MESS- ELEKTRONIK	FMZB 1519B	SUWI-01-21-01	5/7/2025	5/6/2027
10	Amplifier	Tonscend	TAP9K3G40	SUWI-01-14-01	1/14/2026	1/13/2027
11	Amplifier	Tonscend	TAP01018050	SUWI-01-14-02	1/14/2026	1/13/2027
12	Amplifier	Tonscend	TAP18040048	SUWI-01-14-03	1/14/2026	1/13/2027
13	Wideband Radio Communication Tester	Anritsu	MT8820C	SUWI-01-26-01	11/21/2025	11/20/2026
14	Wideband Radio Communication Tester	Anritsu	MT8821C	SUWI-01-26-03	8/25/2025	8/24/2026
15	Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	SUWI-01-16-09	8/26/2025	8/25/2026
16	Radio Communication Analyzer	StarPoint	SP9500E	SUWI-01-28-02	11/21/2025	11/20/2026
17	Signal Generator	ROHDE&SCHWARZ	SMB100A	SUWI-01-08-01	1/14/2026	1/13/2027
18	DC Power Supply	HYELEC	HY3005B	SUWI-01-18-01	1/14/2026	1/13/2027
19	Temperature and humidity meter	MingGao	TH101B	SUWI-01-01-05	2/11/2026	2/10/2027
20	Measurement Software	Tonscend	JS32-RE 4.0.0.0	SUWI-02-09-06	NCR	NCR
21	RF Control unit	Tonscend	JS0806-1	SUWI-02-20-01	NCR	NCR
22	RFCables	Tonscend	NA	SUWI-01-03-02	1/15/2026	1/14/2027

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is LSD Antenna and no consideration of replacement. The best case gain of the

UNII-5: 0.6dBi(Ant5); -2.5dBi(Ant6);

UNII-6: 0.2dBi(Ant5); -2.5dBi(Ant6);

UNII-7: -0.3dBi(Ant5); -2.5dBi(Ant6);

UNII-8: -1.3dBi(Ant5); -2.2dBi(Ant6);

Antenna location: Refer to internal photo.

7 Radio Spectrum Matter Test Results

7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 & Subpart E 15.407 b(9)

Test Method: ANSI C63.10 (2020) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C


Humidity: 44 % RH

Atmospheric Pressure: 1001 mbar

7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram




7.1.4 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 50\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark 1: Level=Read Level+ Cable Loss+ LISN Factor

Remark 2: Pre-test AC 120V/50-60Hz&AC 240V/50-60Hz then choose the AC 120/60Hz as worst case.


Test Mode: 09; Line: Live line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1680	9.95	33.21	43.16	65.06	21.90	17.06	27.01	55.06	28.05	PASS
2	0.3120	9.97	29.70	39.67	59.92	20.25	16.35	26.32	49.92	23.60	PASS
3	0.5055	9.94	30.36	40.30	56.00	15.70	16.41	26.35	46.00	19.65	PASS
4	0.7575	9.95	29.20	39.15	56.00	16.85	15.05	25.00	46.00	21.00	PASS
5	1.0590	9.93	25.71	35.64	56.00	20.36	13.70	23.63	46.00	22.37	PASS
6	19.3425	11.08	14.58	25.66	60.00	34.34	9.24	20.32	50.00	29.68	PASS

Test Mode: 09; Line: Neutral Line



Final Data List

NO.	Frequency [MHz]	Factor [dB]	QP Reading [dBμV]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Reading [dBμV]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1590	9.96	33.93	43.89	65.52	21.63	16.64	26.60	55.52	28.92	PASS
2	0.3975	9.94	29.97	39.91	57.91	18.00	17.42	27.36	47.91	20.55	PASS
3	0.6360	9.91	31.56	41.47	56.00	14.53	16.37	26.28	46.00	19.72	PASS
4	1.0815	9.90	23.70	33.60	56.00	22.40	11.89	21.79	46.00	24.21	PASS
5	1.8690	9.91	13.34	23.25	56.00	32.75	7.93	17.84	46.00	28.16	PASS
6	16.3140	10.74	33.86	44.60	60.00	15.40	20.98	31.72	50.00	18.28	PASS

7.2 Radiated Emissions (Below 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.4,6.5

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C


Humidity: 43 % RH

Atmospheric Pressure: 1001 mbar

7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Pre-scan	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram



7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8m above the ground at a semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3m or 10m away from the interference-receiving antenna, which was mounted on the variable-height antenna tower.
- c. The antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1m to 4m (for the test frequency of below 30MHz, the antenna was tuned to heights 1m) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using quasi-peak method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. At frequencies below 1GHz, measurements may be performed at a distance different to specified in the regulations.

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.


EX. Below 30MHz, Aux Factor = 40 dB/decade of distance, the aux factor is $40\log(3/300) = -80\text{dB}$ (for 3m test distance).

EX. Above 30MHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(10/3) = 10.46\text{dB}$ (for 10m test distance).

2. Scan from 9kHz to 30MHz, the disturbance below 30MHz was very low. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

3. The disturbance below 1GHz was very low and the harmonics were the highest point could be found when testing, so only the worst-case test curve is displayed.


Test Mode: 09; Polarity: Horizontal



Final Data List

NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.49	14.20	-41.05	28.02	40.00	11.98	180	137	Horizontal
2	82.1375	8.73	-40.55	30.51	40.00	9.49	175	241	Horizontal
3	106.8725	13.07	-40.22	24.24	43.50	19.26	135	237	Horizontal
4	188.595	10.56	-39.35	31.45	43.50	12.05	129	176	Horizontal
5	235.8825	12.34	-38.84	29.24	46.00	16.76	108	184	Horizontal
6	996.8475	22.00	-33.72	23.57	54.00	30.43	158	71	Horizontal

Test Mode: 09; Polarity: Vertical



Final Data List									
NO.	Frequency [MHz]	AF [dB/m]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Polarity
1	46.2475	14.25	-41.06	28.47	40.00	11.53	104	40	Vertical
2	78.985	8.40	-40.60	31.18	40.00	8.82	138	190	Vertical
3	170.65	9.60	-39.54	23.67	43.50	19.83	162	9	Vertical
4	250.675	12.63	-38.60	23.70	46.00	22.30	175	108	Vertical
5	773.7475	19.70	-35.16	27.09	46.00	18.91	145	114	Vertical
6	980.8425	21.90	-33.79	23.94	54.00	30.06	129	114	Vertical

7.3 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: ANSI C63.10 (2020) Section 6.6 & 12.7

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark:

1. The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

2. Above 18GHz, measurements may be performed at a distance shorter than that specified in the regulations

Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor+ Aux Factor (if applicable)

The aux factor needs to be added when measurements are performed at a distance other than the limit distance provided.

EX. Above 18GHz, Aux Factor = 20 dB/decade of distance, the aux factor is $20\log(1/3) = -9.54\text{dB}$ (for 1m test distance).

7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 23 °C


Humidity: 44 % RH

Atmospheric Pressure: 1001 mbar

7.3.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	09	TX mode (U-NII-5) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	10	TX mode (U-NII-6) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	11	TX mode (U-NII-7) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.
Final test	12	TX mode (U-NII-8) _Keep the EUT in continuously transmitting mode with all modulation types and being charged. All data rates for each modulation type have been tested, Only the data of worst case is recorded in the report.

7.3.3 Test Setup Diagram




7.3.4 Measurement Procedure and Data

- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:


1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 40GHz, The points marked on below plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the below harmonics were the highest point could be found when testing, so only the below harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.
6. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for Peak detection (PK) and Average detection (AV) at frequency above 1GHz.
7. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle<98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.

11be(EHT20)_TX_CH_001_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7897.625	39.39	37.10	-18.86	57.63	88.20	30.57	Horizontal
2	8824.3333	46.82	37.88	-39.11	45.59	88.20	42.61	Horizontal
3	10573.3333	43.80	38.79	-36.40	46.19	88.20	42.01	Horizontal
4	13638.6667	42.35	40.22	-34.52	48.05	88.20	40.15	Horizontal
5	17818.6667	39.38	41.17	-30.45	50.10	74.00	23.90	Horizontal
6	17935.6667	30.94	41.51	-30.93	41.53	54.00	12.47	Horizontal

11be(EHT20)_TX_CH_001_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7980.75	39.60	37.26	-18.80	58.07	88.20	30.13	Vertical
2	8959	45.73	37.97	-38.73	44.97	88.20	43.23	Vertical
3	11423.6667	43.81	39.05	-35.85	47.01	74.00	26.99	Vertical
4	13907.3333	41.91	40.35	-34.36	47.90	88.20	40.30	Vertical
5	17995	39.21	41.69	-30.74	50.16	74.00	23.84	Vertical
6	17936	30.97	41.51	-30.92	41.56	54.00	12.44	Vertical

11be(EHT20)_TX_CH_045_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7973.75	39.17	37.25	-18.80	57.62	88.20	30.58	Horizontal
2	8988	45.55	37.99	-38.59	44.95	88.20	43.25	Horizontal
3	10920	43.55	39.20	-35.92	46.83	74.00	27.17	Horizontal
4	13626	42.21	40.21	-34.46	47.97	88.20	40.23	Horizontal
5	17845	39.21	41.25	-30.64	49.82	74.00	24.18	Horizontal
6	17984.6667	30.83	41.66	-30.77	41.72	54.00	12.28	Horizontal

11be(EHT20)_TX_CH_045_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7973.3125	39.57	37.25	-18.80	58.02	88.20	30.18	Vertical
2	9013.6667	45.14	38.00	-38.62	44.52	74.00	29.48	Vertical
3	10488	43.27	38.69	-36.27	45.68	88.20	42.52	Vertical
4	14417.6667	41.64	40.15	-33.90	47.89	88.20	40.31	Vertical
5	17753.3333	38.17	40.98	-30.67	48.49	74.00	25.51	Vertical
6	17985.6667	31.02	41.66	-30.77	41.91	54.00	12.09	Vertical

11be(EHT20)_TX_CH_093_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.9375	39.34	37.28	-18.79	57.83	88.20	30.37	Horizontal
2	9055.6667	46.07	38.01	-38.91	45.17	74.00	28.83	Horizontal
3	11217.3333	42.85	39.17	-35.60	46.42	74.00	27.58	Horizontal
4	14566.3333	41.76	40.06	-34.39	47.43	88.20	40.77	Horizontal
5	17959.6667	39.25	41.58	-30.85	49.98	74.00	24.02	Horizontal
6	17843.3333	30.79	41.25	-30.63	41.40	54.00	12.60	Horizontal

11be(EHT20)_TX_CH_093_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7981.625	39.44	37.26	-18.79	57.91	88.20	30.29	Vertical
2	8994.6667	46.35	38.00	-38.56	45.79	88.20	42.41	Vertical
3	10994	42.94	39.29	-35.67	46.56	74.00	27.44	Vertical
4	14682	41.39	39.99	-33.67	47.71	88.20	40.49	Vertical
5	17996.3333	39.57	41.69	-30.73	50.53	74.00	23.47	Vertical
6	17988.6667	30.80	41.67	-30.76	41.71	54.00	12.29	Vertical

11be(EHT20)_TX_CH_097_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7991.25	39.38	37.28	-18.79	57.88	88.20	30.32	Horizontal
2	9024.3333	45.94	38.00	-38.70	45.25	74.00	28.75	Horizontal
3	10995.3333	44.14	39.29	-35.67	47.77	74.00	26.23	Horizontal
4	13850.3333	42.05	40.33	-34.59	47.78	88.20	40.42	Horizontal
5	17973.6667	38.97	41.62	-30.80	49.79	74.00	24.21	Horizontal
6	17997.6667	30.79	41.69	-30.73	41.76	54.00	12.24	Horizontal

11be(EHT20)_TX_CH_097_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7992.125	40.20	37.28	-18.79	58.70	88.20	29.50	Vertical
2	9036	46.16	38.00	-38.77	45.39	74.00	28.61	Vertical
3	11006.3333	42.86	39.30	-35.65	46.51	74.00	27.49	Vertical
4	15391.3333	41.81	39.10	-33.40	47.50	74.00	26.50	Vertical
5	17839.3333	38.78	41.23	-30.60	49.41	74.00	24.59	Vertical
6	17888	31.12	41.38	-30.95	41.54	54.00	12.46	Vertical

11be(EHT20)_TX_CH_105_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7963.6875	39.60	37.23	-18.81	58.02	88.20	30.18	Horizontal
2	9015	45.89	38.00	-38.63	45.26	74.00	28.74	Horizontal
3	11456	43.47	39.03	-35.79	46.71	74.00	27.29	Horizontal
4	14403.3333	41.51	40.16	-33.77	47.90	88.20	40.30	Horizontal
5	17907.6667	39.88	41.43	-31.02	50.30	74.00	23.70	Horizontal
6	17879.3333	30.88	41.35	-30.89	41.34	54.00	12.66	Horizontal

11be(EHT20)_TX_CH_105_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7984.25	39.53	37.27	-18.79	58.01	88.20	30.19	Vertical
2	9011.6667	45.87	38.00	-38.61	45.26	74.00	28.74	Vertical
3	10901.3333	43.50	39.18	-35.99	46.70	74.00	27.30	Vertical
4	14597.3333	42.44	40.04	-34.26	48.22	88.20	39.98	Vertical
5	17992.3333	38.96	41.68	-30.74	49.89	74.00	24.11	Vertical
6	17987.6667	30.33	41.66	-30.76	41.23	54.00	12.77	Vertical

11be(EHT20)_TX_CH_113_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7986.4375	39.10	37.27	-18.79	57.58	88.20	30.62	Horizontal
2	9011.6667	46.33	38.00	-38.61	45.72	74.00	28.28	Horizontal
3	11033.6667	42.89	39.28	-35.63	46.54	74.00	27.46	Horizontal
4	13403.3333	43.64	40.10	-34.92	48.83	88.20	39.37	Horizontal
5	17854.3333	39.27	41.28	-30.71	49.84	74.00	24.16	Horizontal
6	17747	29.72	40.97	-30.71	39.97	54.00	14.03	Horizontal

11be(EHT20)_TX_CH_113_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7974.1875	39.42	37.25	-18.80	57.87	88.20	30.33	Vertical
2	8982.3333	45.89	37.99	-38.62	45.26	88.20	42.94	Vertical
3	11253	42.60	39.15	-35.46	46.28	74.00	27.72	Vertical
4	14302.6667	41.90	40.22	-34.48	47.64	88.20	40.56	Vertical
5	17979.6667	38.91	41.64	-30.79	49.77	74.00	24.23	Vertical
6	17972	30.96	41.62	-30.81	41.77	54.00	12.23	Vertical

11be(EHT20)_TX_CH_117_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7968.5	39.71	37.24	-18.81	58.14	88.20	30.06	Horizontal
2	8926.6667	46.89	37.95	-38.89	45.95	88.20	42.25	Horizontal
3	10880.3333	43.33	39.16	-36.08	46.41	74.00	27.59	Horizontal
4	14331.6667	41.69	40.20	-34.26	47.63	88.20	40.57	Horizontal
5	17928.6667	39.57	41.49	-30.95	50.11	74.00	23.89	Horizontal
6	17868.6667	30.69	41.32	-30.81	41.19	54.00	12.81	Horizontal

11be(EHT20)_TX_CH_117_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.9375	39.34	37.28	-18.79	57.83	88.20	30.37	Vertical
2	8969	45.80	37.98	-38.68	45.10	88.20	43.10	Vertical
3	12236	42.23	38.98	-34.81	46.41	74.00	27.59	Vertical
4	14258	42.38	40.25	-34.75	47.88	88.20	40.32	Vertical
5	17861.6667	39.57	41.30	-30.76	50.10	74.00	23.90	Vertical
6	17980.3333	30.53	41.64	-30.78	41.39	54.00	12.61	Vertical

11be(EHT20)_TX_CH_149_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7982.5	39.39	37.27	-18.79	57.86	88.20	30.34	Horizontal
2	8954.3333	46.79	37.97	-38.75	46.00	88.20	42.20	Horizontal
3	10888.6667	43.46	39.17	-36.04	46.59	74.00	27.41	Horizontal
4	13887.3333	42.50	40.34	-34.38	48.46	88.20	39.74	Horizontal
5	17892	39.76	41.39	-30.98	50.16	74.00	23.84	Horizontal
6	17983.3333	30.62	41.65	-30.77	41.50	54.00	12.50	Horizontal

11be(EHT20)_TX_CH_149_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7947.0625	39.48	37.19	-18.82	57.85	88.20	30.35	Vertical
2	8965.3333	46.60	37.98	-38.70	45.88	88.20	42.32	Vertical
3	10982.6667	43.79	39.28	-35.71	47.36	74.00	26.64	Vertical
4	13968	42.36	40.38	-34.79	47.96	88.20	40.24	Vertical
5	17865.6667	39.17	41.31	-30.79	49.69	74.00	24.31	Vertical
6	17867	30.83	41.31	-30.80	41.34	54.00	12.66	Vertical

11be(EHT20)_TX_CH_185_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7987.3125	40.85	37.27	-18.79	59.33	88.20	28.87	Horizontal
2	8980.3333	46.69	37.99	-38.63	46.05	88.20	42.15	Horizontal
3	10929.6667	44.09	39.22	-35.89	47.42	74.00	26.58	Horizontal
4	13741.3333	43.00	40.27	-34.84	48.43	88.20	39.77	Horizontal
5	17853.3333	39.64	41.27	-30.70	50.21	74.00	23.79	Horizontal
6	17972.3333	30.58	41.62	-30.81	41.39	54.00	12.61	Horizontal

11be(EHT20)_TX_CH_185_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7927.8125	39.49	37.16	-18.84	57.81	88.20	30.39	Vertical
2	9019	46.31	38.00	-38.66	45.65	74.00	28.35	Vertical
3	10961.6667	43.66	39.25	-35.78	47.13	74.00	26.87	Vertical
4	13747.3333	42.60	40.27	-34.85	48.03	88.20	40.17	Vertical
5	17989	39.35	41.67	-30.76	50.26	74.00	23.74	Vertical
6	17859.3333	31.06	41.29	-30.75	41.60	54.00	12.40	Vertical

11be(EHT20)_TX_CH_189_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7954.9375	39.55	37.21	-18.82	57.94	88.20	30.26	Horizontal
2	9005.6667	46.27	38.00	-38.57	45.70	74.00	28.30	Horizontal
3	11393	43.04	39.06	-35.85	46.26	74.00	27.74	Horizontal
4	13796.6667	43.49	40.30	-34.88	48.91	88.20	39.29	Horizontal
5	17999	39.92	41.70	-30.72	50.89	74.00	23.11	Horizontal
6	13793.6667	35.53	40.30	-34.88	40.95	68.20	27.25	Horizontal

11be(EHT20)_TX_CH_189_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7937.4375	39.40	37.17	-18.83	57.74	88.20	30.46	Vertical
2	8951.3333	45.64	37.97	-38.77	44.84	88.20	43.36	Vertical
3	10907.3333	43.52	39.19	-35.97	46.74	74.00	27.26	Vertical
4	13859.6667	41.93	40.33	-34.54	47.72	88.20	40.48	Vertical
5	17951.3333	39.92	41.56	-30.88	50.60	74.00	23.40	Vertical
6	17995	30.28	41.69	-30.74	41.23	54.00	12.77	Vertical

11be(EHT20)_TX_CH_209_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7907.6875	39.83	37.12	-18.85	58.09	88.20	30.11	Horizontal
2	8889.6667	46.86	37.92	-39.03	45.75	88.20	42.45	Horizontal
3	10958	43.19	39.25	-35.79	46.65	74.00	27.35	Horizontal
4	13987.3333	44.31	40.39	-34.92	49.78	88.20	38.42	Horizontal
5	17824	39.49	41.19	-30.49	50.19	74.00	23.81	Horizontal
6	13991	35.75	40.40	-34.95	41.20	68.20	27.00	Horizontal

11be(EHT20)_TX_CH_209_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7940.5	39.32	37.18	-18.83	57.67	88.20	30.53	Vertical
2	8984	45.77	37.99	-38.61	45.15	88.20	43.05	Vertical
3	11010.6667	43.90	39.29	-35.64	47.55	74.00	26.45	Vertical
4	13994.6667	44.83	40.40	-34.97	50.25	88.20	37.95	Vertical
5	17907.6667	39.21	41.43	-31.02	49.63	74.00	24.37	Vertical
6	13994.3333	35.03	40.40	-34.97	40.46	68.20	27.74	Vertical

11be(EHT20)_TX_CH_233_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7869.625	39.92	37.04	-18.81	58.14	88.20	30.06	Horizontal
2	9014.6667	46.68	38.00	-38.63	46.05	74.00	27.95	Horizontal
3	11274.3333	42.66	39.14	-35.38	46.41	74.00	27.59	Horizontal
4	13710.6667	42.79	40.26	-34.83	48.22	88.20	39.98	Horizontal
5	17982.6667	39.26	41.65	-30.78	50.13	74.00	23.87	Horizontal
6	17999.6667	30.55	41.70	-30.72	41.53	54.00	12.47	Horizontal

11be(EHT20)_TX_CH_233_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7966.75	39.55	37.23	-18.81	57.98	88.20	30.22	Vertical
2	9524.6667	45.89	38.05	-38.10	45.84	88.20	42.36	Vertical
3	11311.6667	42.73	39.11	-35.36	46.48	74.00	27.52	Vertical
4	15054	41.18	39.70	-33.90	46.98	88.20	41.22	Vertical
5	17967.3333	39.69	41.61	-30.82	50.47	74.00	23.53	Vertical
6	17880.3333	31.03	41.35	-30.90	41.48	54.00	12.52	Vertical

11be(EHT40)_TX_CH_003_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7977.25	39.97	37.25	-18.80	58.43	88.20	29.77	Horizontal
2	8953	46.15	37.97	-38.76	45.36	88.20	42.84	Horizontal
3	11342.6667	42.59	39.09	-35.55	46.14	74.00	27.86	Horizontal
4	13811	41.97	40.31	-34.82	47.46	88.20	40.74	Horizontal
5	17991.3333	39.38	41.67	-30.75	50.31	74.00	23.69	Horizontal
6	13880.6667	34.15	40.34	-34.42	40.07	68.20	28.13	Horizontal

11be(EHT40)_TX_CH_003_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7954.5	40.16	37.21	-18.82	58.55	88.20	29.65	Vertical
2	9009.3333	45.93	38.00	-38.59	45.34	74.00	28.66	Vertical
3	11010.3333	43.73	39.29	-35.64	47.38	74.00	26.62	Vertical
4	13806.6667	42.21	40.30	-34.84	47.67	88.20	40.53	Vertical
5	17965.3333	39.07	41.60	-30.83	49.84	74.00	24.16	Vertical
6	17864	30.86	41.31	-30.78	41.38	54.00	12.62	Vertical

11be(EHT40)_TX_CH_043_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7998.25	39.79	37.30	-18.78	58.31	88.20	29.89	Horizontal
2	8926.3333	46.53	37.95	-38.89	45.59	88.20	42.61	Horizontal
3	10815.3333	44.13	39.08	-36.36	46.85	74.00	27.15	Horizontal
4	13640	42.78	40.22	-34.53	48.47	88.20	39.73	Horizontal
5	17999.3333	38.98	41.70	-30.72	49.96	74.00	24.04	Horizontal
6	17996.6667	30.51	41.69	-30.73	41.47	54.00	12.53	Horizontal

11be(EHT40)_TX_CH_043_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7989.9375	39.87	37.28	-18.79	58.36	88.20	29.84	Vertical
2	8925.3333	46.11	37.95	-38.90	45.16	88.20	43.04	Vertical
3	11234	42.59	39.16	-35.53	46.22	74.00	27.78	Vertical
4	14684	42.28	39.99	-33.65	48.62	88.20	39.58	Vertical
5	17969	39.15	41.61	-30.82	49.94	74.00	24.06	Vertical
6	17904.3333	30.92	41.42	-31.03	41.32	54.00	12.68	Vertical

11be(EHT40)_TX_CH_091_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7888.4375	40.07	37.08	-18.84	58.30	88.20	29.90	Horizontal
2	8960.6667	45.79	37.97	-38.72	45.04	88.20	43.16	Horizontal
3	11521.3333	43.53	38.99	-35.50	47.01	74.00	26.99	Horizontal
4	13873.6667	41.77	40.34	-34.46	47.65	88.20	40.55	Horizontal
5	17848.3333	39.79	41.26	-30.67	50.38	74.00	23.62	Horizontal
6	17933.6667	30.77	41.51	-30.93	41.35	54.00	12.65	Horizontal

11be(EHT40)_TX_CH_091_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7944	39.30	37.19	-18.82	57.66	88.20	30.54	Vertical
2	8993.3333	46.17	38.00	-38.56	45.60	88.20	42.60	Vertical
3	12291.6667	42.88	39.05	-34.30	47.63	74.00	26.37	Vertical
4	15323	40.92	39.22	-33.35	46.79	88.20	41.41	Vertical
5	17345.6667	41.05	39.80	-31.74	49.12	88.20	39.08	Vertical
6	17354.6667	31.09	39.83	-31.76	39.15	68.20	29.05	Vertical

11be(EHT40)_TX_CH_099_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7984.6875	39.39	37.27	-18.79	57.87	88.20	30.33	Horizontal
2	9438.6667	46.14	38.04	-38.28	45.91	74.00	28.09	Horizontal
3	10957.3333	42.79	39.25	-35.80	46.24	74.00	27.76	Horizontal
4	13641.6667	42.36	40.22	-34.53	48.05	88.20	40.15	Horizontal
5	17996.6667	39.34	41.69	-30.73	50.30	74.00	23.70	Horizontal
6	17997.3333	30.71	41.69	-30.73	41.67	54.00	12.33	Horizontal

11be(EHT40)_TX_CH_099_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7967.625	39.89	37.24	-18.81	58.32	88.20	29.88	Vertical
2	8917	46.21	37.94	-38.94	45.22	88.20	42.98	Vertical
3	10968.6667	43.09	39.26	-35.76	46.60	74.00	27.40	Vertical
4	13926.6667	42.06	40.36	-34.50	47.93	88.20	40.27	Vertical
5	17805	39.05	41.13	-30.36	49.83	74.00	24.17	Vertical
6	17860.6667	30.82	41.30	-30.76	41.36	54.00	12.64	Vertical

11be(EHT40)_TX_CH_107_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7970.6875	39.97	37.24	-18.80	58.41	88.20	29.79	Horizontal
2	9485.3333	45.84	38.05	-38.21	45.68	74.00	28.32	Horizontal
3	11517.6667	43.09	38.99	-35.54	46.54	74.00	27.46	Horizontal
4	13899	41.91	40.35	-34.32	47.94	88.20	40.26	Horizontal
5	17963.6667	38.92	41.59	-30.84	49.68	74.00	24.32	Horizontal
6	17978.3333	30.31	41.64	-30.79	41.16	54.00	12.84	Horizontal

11be(EHT40)_TX_CH_107_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7953.1875	39.81	37.21	-18.82	58.20	88.20	30.00	Vertical
2	9014	46.37	38.00	-38.63	45.75	74.00	28.25	Vertical
3	10976	42.98	39.27	-35.73	46.52	74.00	27.48	Vertical
4	13320.3333	42.36	40.06	-34.75	47.67	74.00	26.33	Vertical
5	17811.3333	37.96	41.15	-30.40	48.71	74.00	25.29	Vertical
6	17676.6667	29.67	40.76	-31.28	39.16	68.20	29.04	Vertical

11be(EHT40)_TX_CH_115_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7992.5625	39.83	37.29	-18.79	58.33	88.20	29.87	Horizontal
2	8942.6667	46.57	37.96	-38.81	45.72	88.20	42.48	Horizontal
3	11380.3333	43.20	39.07	-35.77	46.50	74.00	27.50	Horizontal
4	13815.3333	42.18	40.31	-34.79	47.70	88.20	40.50	Horizontal
5	17990	39.54	41.67	-30.75	50.46	74.00	23.54	Horizontal
6	17859	30.94	41.29	-30.74	41.49	54.00	12.51	Horizontal

11be(EHT40)_TX_CH_115_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7975.0625	39.57	37.25	-18.80	58.02	88.20	30.18	Vertical
2	8991.3333	45.62	37.99	-38.57	45.04	88.20	43.16	Vertical
3	11387	43.72	39.07	-35.81	46.98	74.00	27.02	Vertical
4	14643	41.60	40.01	-33.94	47.67	88.20	40.53	Vertical
5	18000	40.95	41.70	-30.72	51.93	74.00	22.07	Vertical
6	17994.6667	30.77	41.68	-30.74	41.72	54.00	12.28	Vertical

11be(EHT40)_TX_CH_123_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7994.75	39.31	37.29	-18.78	57.82	88.20	30.38	Horizontal
2	8992.6667	46.11	37.99	-38.57	45.54	88.20	42.66	Horizontal
3	10918	43.38	39.20	-35.93	46.65	74.00	27.35	Horizontal
4	13632.3333	42.04	40.22	-34.49	47.77	88.20	40.43	Horizontal
5	17946.3333	40.20	41.54	-30.89	50.85	74.00	23.15	Horizontal
6	17877.6667	31.01	41.35	-30.88	41.48	54.00	12.52	Horizontal

11be(EHT40)_TX_CH_123_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7952.3125	39.98	37.20	-18.82	58.37	88.20	29.83	Vertical
2	8936.3333	45.92	37.96	-38.84	45.03	88.20	43.17	Vertical
3	11416.3333	44.15	39.05	-35.86	47.34	74.00	26.66	Vertical
4	14283.6667	42.11	40.23	-34.60	47.74	88.20	40.46	Vertical
5	17998.3333	39.09	41.70	-30.73	50.06	74.00	23.94	Vertical
6	17973	30.69	41.62	-30.81	41.51	54.00	12.49	Vertical

11be(EHT40)_TX_CH_147_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7986	39.85	37.27	-18.79	58.33	88.20	29.87	Horizontal
2	9530.3333	45.76	38.05	-38.08	45.73	88.20	42.47	Horizontal
3	12315	41.57	39.08	-34.35	46.30	74.00	27.70	Horizontal
4	14914	40.20	39.85	-33.43	46.62	88.20	41.58	Horizontal
5	17843.3333	39.16	41.25	-30.63	49.77	74.00	24.23	Horizontal
6	17986.3333	30.65	41.66	-30.76	41.55	54.00	12.45	Horizontal

11be(EHT40)_TX_CH_147_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7999.5625	40.23	37.30	-18.78	58.75	88.20	29.45	Vertical
2	9030	45.86	38.00	-38.73	45.13	74.00	28.87	Vertical
3	11554.6667	42.67	38.97	-35.18	46.46	74.00	27.54	Vertical
4	14345.3333	41.83	40.19	-34.16	47.87	88.20	40.33	Vertical
5	17919	39.49	41.47	-30.98	49.98	74.00	24.02	Vertical
6	17989	30.50	41.67	-30.76	41.41	54.00	12.59	Vertical

11be(EHT40)_TX_CH_179_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7986.875	39.64	37.27	-18.79	58.12	88.20	30.08	Horizontal
2	8946	46.41	37.96	-38.79	45.58	88.20	42.62	Horizontal
3	10928.3333	43.68	39.21	-35.89	47.00	74.00	27.00	Horizontal
4	13772.6667	42.45	40.29	-34.86	47.87	88.20	40.33	Horizontal
5	17947	39.98	41.55	-30.89	50.64	74.00	23.36	Horizontal
6	17989.3333	30.47	41.67	-30.75	41.38	54.00	12.62	Horizontal

11be(EHT40)_TX_CH_179_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7947.0625	39.64	37.19	-18.82	58.01	88.20	30.19	Vertical
2	9014	46.23	38.00	-38.63	45.61	74.00	28.39	Vertical
3	11309	43.38	39.11	-35.34	47.15	74.00	26.85	Vertical
4	13700	42.92	40.25	-34.82	48.35	88.20	39.85	Vertical
5	17864.6667	39.67	41.31	-30.79	50.19	74.00	23.81	Vertical
6	17999.3333	31.68	41.70	-30.72	42.66	54.00	11.34	Vertical

11be(EHT40)_TX_CH_187_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7974.1875	39.67	37.25	-18.80	58.12	88.20	30.08	Horizontal
2	8903.6667	46.19	37.93	-39.00	45.12	88.20	43.08	Horizontal
3	11376.3333	42.62	39.07	-35.75	45.95	74.00	28.05	Horizontal
4	13934.6667	41.69	40.37	-34.55	47.50	88.20	40.70	Horizontal
5	17864	40.07	41.31	-30.78	50.59	74.00	23.41	Horizontal
6	17992.6667	30.39	41.68	-30.74	41.33	54.00	12.67	Horizontal

11be(EHT40)_TX_CH_187_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7941.8125	39.34	37.18	-18.83	57.70	88.20	30.50	Vertical
2	8561	47.88	37.69	-39.46	46.11	88.20	42.09	Vertical
3	10958.3333	44.08	39.25	-35.79	47.54	74.00	26.46	Vertical
4	13097.6667	42.88	39.95	-34.76	48.07	88.20	40.13	Vertical
5	17393.6667	39.83	39.94	-31.89	47.88	88.20	40.32	Vertical
6	17362.6667	31.30	39.85	-31.79	39.36	68.20	28.84	Vertical

11be(EHT40)_TX_CH_203_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7988.1875	39.35	37.28	-18.79	57.84	88.20	30.36	Horizontal
2	8916.6667	46.67	37.94	-38.94	45.67	88.20	42.53	Horizontal
3	11449.3333	43.50	39.03	-35.80	46.73	74.00	27.27	Horizontal
4	14325.3333	42.54	40.20	-34.31	48.44	88.20	39.76	Horizontal
5	17998.3333	39.19	41.70	-30.73	50.16	74.00	23.84	Horizontal
6	17937.3333	30.60	41.52	-30.92	41.20	54.00	12.80	Horizontal

11be(EHT40)_TX_CH_203_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7975.9375	40.56	37.25	-18.80	59.01	88.20	29.19	Vertical
2	8942.6667	46.03	37.96	-38.81	45.18	88.20	43.02	Vertical
3	10791.6667	44.08	39.05	-36.40	46.73	74.00	27.27	Vertical
4	13932.3333	42.41	40.37	-34.54	48.24	88.20	39.96	Vertical
5	17832	40.48	41.21	-30.55	51.14	74.00	22.86	Vertical
6	17963.6667	30.60	41.59	-30.84	41.36	54.00	12.64	Vertical

11be(EHT40)_TX_CH_227_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7953.1875	39.60	37.21	-18.82	57.99	88.20	30.21	Horizontal
2	9066.3333	45.63	38.01	-38.98	44.66	74.00	29.34	Horizontal
3	12261.6667	42.13	39.01	-34.57	46.57	74.00	27.43	Horizontal
4	14673	42.35	40.00	-33.73	48.61	88.20	39.59	Horizontal
5	17995.3333	39.44	41.69	-30.73	50.39	74.00	23.61	Horizontal
6	17983.6667	30.36	41.65	-30.77	41.24	54.00	12.76	Horizontal

11be(EHT40)_TX_CH_227_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7947.5	39.22	37.20	-18.82	57.59	88.20	30.61	Vertical
2	8959.3333	46.41	37.97	-38.73	45.65	88.20	42.55	Vertical
3	11221.3333	42.64	39.17	-35.58	46.23	74.00	27.77	Vertical
4	13296	41.89	40.05	-34.72	47.22	74.00	26.78	Vertical
5	17905.6667	40.04	41.43	-31.02	50.44	74.00	23.56	Vertical
6	17994.6667	31.08	41.68	-30.74	42.03	54.00	11.97	Vertical

11be(EHT80)_TX_CH_007_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7922.125	39.99	37.14	-18.84	58.29	88.20	29.91	Horizontal
2	9524.6667	46.06	38.05	-38.10	46.01	88.20	42.19	Horizontal
3	12195.6667	42.27	38.93	-35.12	46.08	74.00	27.92	Horizontal
4	15197.6667	41.02	39.44	-33.31	47.15	88.20	41.05	Horizontal
5	17990.6667	38.96	41.67	-30.75	49.88	74.00	24.12	Horizontal
6	17915	30.98	41.45	-30.99	41.44	54.00	12.56	Horizontal

11be(EHT80)_TX_CH_007_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7973.75	40.14	37.25	-18.80	58.59	88.20	29.61	Vertical
2	9066	45.81	38.01	-38.98	44.84	74.00	29.16	Vertical
3	11260.3333	42.67	39.14	-35.44	46.38	74.00	27.62	Vertical
4	13891.6667	42.95	40.35	-34.36	48.94	88.20	39.26	Vertical
5	17821.6667	39.87	41.18	-30.48	50.58	74.00	23.42	Vertical
6	17978.3333	30.71	41.64	-30.79	41.56	54.00	12.44	Vertical

11be(EHT80)_TX_CH_039_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7944	39.51	37.19	-18.82	57.87	88.20	30.33	Horizontal
2	8962	45.95	37.97	-38.72	45.21	88.20	42.99	Horizontal
3	10462.6667	45.20	38.66	-36.30	47.55	88.20	40.65	Horizontal
4	13854	42.17	40.33	-34.57	47.92	88.20	40.28	Horizontal
5	17966	39.59	41.60	-30.83	50.36	74.00	23.64	Horizontal
6	17991.6667	30.88	41.68	-30.75	41.81	54.00	12.19	Horizontal


11be(EHT80)_TX_CH_039_Vertical



Data List


NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7997.375	39.95	37.29	-18.78	58.46	88.20	29.74	Vertical
2	8885.3333	46.83	37.92	-39.04	45.71	88.20	42.49	Vertical
3	10973.3333	43.82	39.27	-35.74	47.35	74.00	26.65	Vertical
4	13817.3333	42.01	40.31	-34.78	47.54	88.20	40.66	Vertical
5	17874.6667	39.99	41.34	-30.86	50.47	74.00	23.53	Vertical
6	17995.3333	31.17	41.69	-30.73	42.12	54.00	11.88	Vertical

11be(EHT80)_TX_CH_087_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7971.125	39.41	37.24	-18.80	57.85	88.20	30.35	Horizontal
2	8959	46.93	37.97	-38.73	46.17	88.20	42.03	Horizontal
3	11009.6667	42.58	39.29	-35.64	46.23	74.00	27.77	Horizontal
4	14997.6667	41.16	39.80	-33.95	47.02	88.20	41.18	Horizontal
5	17994.6667	39.13	41.68	-30.74	50.08	74.00	23.92	Horizontal
6	17876	30.88	41.34	-30.87	41.35	54.00	12.65	Horizontal

11be(EHT80)_TX_CH_087_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7965	39.65	37.23	-18.81	58.07	88.20	30.13	Vertical
2	8960.3333	46.16	37.97	-38.72	45.41	88.20	42.79	Vertical
3	11415.3333	43.83	39.05	-35.86	47.02	74.00	26.98	Vertical
4	13850.6667	42.43	40.33	-34.59	48.16	88.20	40.04	Vertical
5	17998.3333	38.89	41.70	-30.73	49.86	74.00	24.14	Vertical
6	17989.3333	30.36	41.67	-30.75	41.27	54.00	12.73	Vertical

11be(EHT80)_TX_CH_103_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7889.3125	39.50	37.08	-18.84	57.73	88.20	30.47	Horizontal
2	8967	46.58	37.98	-38.69	45.87	88.20	42.33	Horizontal
3	10711.3333	43.88	38.95	-36.14	46.70	74.00	27.30	Horizontal
4	13861.3333	42.61	40.33	-34.53	48.41	88.20	39.79	Horizontal
5	17931.3333	39.61	41.50	-30.94	50.17	74.00	23.83	Horizontal
6	17985.6667	30.52	41.66	-30.77	41.41	54.00	12.59	Horizontal


11be(EHT80)_TX_CH_103_Vertical



Data List


NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7980.75	39.38	37.26	-18.80	57.85	88.20	30.35	Vertical
2	8962.3333	46.07	37.97	-38.71	45.33	88.20	42.87	Vertical
3	10981	42.76	39.28	-35.71	46.32	74.00	27.68	Vertical
4	12904.6667	43.87	39.79	-34.85	48.81	88.20	39.39	Vertical
5	17967	40.01	41.60	-30.83	50.79	74.00	23.21	Vertical
6	17852.6667	31.20	41.27	-30.70	41.77	54.00	12.23	Vertical

11be(EHT80)_TX_CH_119_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7993.4375	39.92	37.29	-18.79	58.42	88.20	29.78	Horizontal
2	8935.3333	46.47	37.95	-38.85	45.58	88.20	42.62	Horizontal
3	12258.6667	43.24	39.01	-34.60	47.65	74.00	26.35	Horizontal
4	15554.3333	40.17	38.80	-32.97	46.00	74.00	28.00	Horizontal
5	17828.3333	39.25	41.20	-30.52	49.93	74.00	24.07	Horizontal
6	17820.3333	30.98	41.18	-30.47	41.69	54.00	12.31	Horizontal

11be(EHT80)_TX_CH_119_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7944	39.97	37.19	-18.82	58.33	88.20	29.87	Vertical
2	8781	45.49	37.85	-39.16	44.18	88.20	44.02	Vertical
3	10969	43.21	39.26	-35.76	46.72	74.00	27.28	Vertical
4	13889	42.00	40.34	-34.37	47.97	88.20	40.23	Vertical
5	17970.3333	39.03	41.61	-30.81	49.83	74.00	24.17	Vertical
6	17991	30.98	41.67	-30.75	41.91	54.00	12.09	Vertical

11be(EHT80)_TX_CH_151_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7985.5625	39.59	37.27	-18.79	58.07	88.20	30.13	Horizontal
2	8958.3333	46.26	37.97	-38.73	45.50	88.20	42.70	Horizontal
3	11580.3333	42.52	38.95	-34.93	46.54	74.00	27.46	Horizontal
4	14399.6667	40.96	40.16	-33.74	47.38	88.20	40.82	Horizontal
5	17969.3333	39.13	41.61	-30.82	49.92	74.00	24.08	Horizontal
6	17985.6667	30.15	41.66	-30.77	41.04	54.00	12.96	Horizontal

11be(EHT80)_TX_CH_151_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7993.4375	38.93	37.29	-18.79	57.43	88.20	30.77	Vertical
2	8601	45.82	37.72	-39.08	44.46	88.20	43.74	Vertical
3	10625.3333	43.64	38.85	-36.36	46.13	74.00	27.87	Vertical
4	14455	43.30	40.13	-34.25	49.18	88.20	39.02	Vertical
5	17924.3333	39.90	41.48	-30.96	50.42	74.00	23.58	Vertical
6	17992.6667	30.43	41.68	-30.74	41.37	54.00	12.63	Vertical

11be(EHT80)_TX_CH_183_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7944.4375	39.85	37.19	-18.82	58.21	88.20	29.99	Horizontal
2	9421	45.32	38.04	-38.30	45.06	74.00	28.94	Horizontal
3	11928	41.84	38.74	-34.93	45.65	74.00	28.35	Horizontal
4	14510.6667	42.20	40.09	-34.62	47.68	88.20	40.52	Horizontal
5	17947	40.02	41.55	-30.89	50.68	74.00	23.32	Horizontal
6	17989.3333	30.53	41.67	-30.75	41.44	54.00	12.56	Horizontal

11be(EHT80)_TX_CH_183_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7957.5625	39.72	37.22	-18.81	58.12	88.20	30.08	Vertical
2	8967.3333	47.12	37.98	-38.69	46.41	88.20	41.79	Vertical
3	11515.6667	43.53	38.99	-35.56	46.96	74.00	27.04	Vertical
4	13725.6667	42.71	40.26	-34.84	48.14	88.20	40.06	Vertical
5	17846	39.71	41.25	-30.65	50.31	74.00	23.69	Vertical
6	17870.6667	31.19	41.32	-30.83	41.69	54.00	12.31	Vertical

11be(EHT80)_TX_CH_199_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7990.375	39.59	37.28	-18.79	58.08	88.20	30.12	Horizontal
2	8931	46.22	37.95	-38.87	45.30	88.20	42.90	Horizontal
3	10920.3333	43.30	39.20	-35.92	46.58	74.00	27.42	Horizontal
4	13870.6667	42.15	40.34	-34.48	48.01	88.20	40.19	Horizontal
5	17836.3333	39.58	41.23	-30.58	50.22	74.00	23.78	Horizontal
6	17864	31.12	41.31	-30.78	41.64	54.00	12.36	Horizontal

11be(EHT80)_TX_CH_199_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7946.625	39.81	37.19	-18.82	58.18	88.20	30.02	Vertical
2	8996	46.15	38.00	-38.55	45.60	88.20	42.60	Vertical
3	10996.6667	42.83	39.30	-35.66	46.46	74.00	27.54	Vertical
4	13862	42.38	40.33	-34.53	48.18	88.20	40.02	Vertical
5	17301.6667	40.04	39.67	-31.60	48.12	88.20	40.08	Vertical
6	17018.3333	30.72	38.85	-31.06	38.51	68.20	29.69	Vertical

11be(EHT80)_TX_CH_215_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7982.0625	39.54	37.26	-18.79	58.01	88.20	30.19	Horizontal
2	8965.3333	46.45	37.98	-38.70	45.73	88.20	42.47	Horizontal
3	11931.3333	41.52	38.74	-34.95	45.31	74.00	28.69	Horizontal
4	15296.6667	40.72	39.27	-33.33	46.66	88.20	41.54	Horizontal
5	17939	39.51	41.52	-30.92	50.12	74.00	23.88	Horizontal
6	17997.3333	30.44	41.69	-30.73	41.40	54.00	12.60	Horizontal

11be(EHT80)_TX_CH_215_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7998.6875	39.60	37.30	-18.78	58.12	88.20	30.08	Vertical
2	9348	45.89	38.03	-38.51	45.42	74.00	28.58	Vertical
3	11580.3333	42.17	38.95	-34.93	46.19	74.00	27.81	Vertical
4	14666	41.58	40.00	-33.78	47.80	88.20	40.40	Vertical
5	17867.3333	41.43	41.32	-30.80	51.94	74.00	22.06	Vertical
6	17987	30.62	41.66	-30.76	41.52	54.00	12.48	Vertical

11be(EHT160)_TX_CH_015_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7979.875	39.23	37.26	-18.80	57.69	88.20	30.51	Horizontal
2	8961.3333	46.05	37.97	-38.72	45.30	88.20	42.90	Horizontal
3	10690.6667	43.52	38.93	-36.13	46.32	74.00	27.68	Horizontal
4	13820.3333	42.05	40.31	-34.76	47.60	88.20	40.60	Horizontal
5	17812.6667	39.12	41.16	-30.41	49.87	74.00	24.13	Horizontal
6	17981	30.39	41.64	-30.78	41.25	54.00	12.75	Horizontal

11be(EHT160)_TX_CH_015_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7966.75	39.22	37.23	-18.81	57.65	88.20	30.55	Vertical
2	9346	45.39	38.03	-38.51	44.91	74.00	29.09	Vertical
3	11514	42.78	38.99	-35.57	46.20	74.00	27.80	Vertical
4	13941.6667	42.39	40.37	-34.60	48.16	88.20	40.04	Vertical
5	17866	39.52	41.31	-30.80	50.04	74.00	23.96	Vertical
6	17868.6667	30.93	41.32	-30.81	41.43	54.00	12.57	Vertical

11be(EHT160)_TX_CH_047_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7964.5625	39.64	37.23	-18.81	58.06	88.20	30.14	Horizontal
2	9062.3333	45.06	38.01	-38.95	44.11	74.00	29.89	Horizontal
3	11281.3333	43.47	39.13	-35.36	47.24	74.00	26.76	Horizontal
4	13994	42.32	40.40	-34.97	47.75	88.20	40.45	Horizontal
5	17933.6667	39.15	41.51	-30.93	49.73	74.00	24.27	Horizontal
6	17987.6667	30.45	41.66	-30.76	41.35	54.00	12.65	Horizontal

11be(EHT160)_TX_CH_047_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7979.875	39.52	37.26	-18.80	57.98	88.20	30.22	Vertical
2	8998	47.11	38.00	-38.54	46.57	88.20	41.63	Vertical
3	11331.6667	42.23	39.10	-35.48	45.85	74.00	28.15	Vertical
4	14335.3333	42.41	40.20	-34.23	48.38	88.20	39.82	Vertical
5	17989.3333	39.10	41.67	-30.75	50.01	74.00	23.99	Vertical
6	17990	30.19	41.67	-30.75	41.11	54.00	12.89	Vertical

11be(EHT160)_TX_CH_079_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7928.6875	39.63	37.16	-18.84	57.95	88.20	30.25	Horizontal
2	9371.6667	45.68	38.04	-38.43	45.29	74.00	28.71	Horizontal
3	11516.3333	43.20	38.99	-35.55	46.64	74.00	27.36	Horizontal
4	14700	41.36	39.98	-33.54	47.80	88.20	40.40	Horizontal
5	17995	38.88	41.69	-30.74	49.83	74.00	24.17	Horizontal
6	17996	30.29	41.69	-30.73	41.25	54.00	12.75	Horizontal

11be(EHT160)_TX_CH_079_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7872.25	40.78	37.04	-18.82	59.01	88.20	29.19	Vertical
2	9017.6667	46.21	38.00	-38.65	45.56	74.00	28.44	Vertical
3	11269.6667	43.41	39.14	-35.40	47.15	74.00	26.85	Vertical
4	14072.3333	41.80	40.36	-34.84	47.31	88.20	40.89	Vertical
5	17993.6667	39.75	41.68	-30.74	50.69	74.00	23.31	Vertical
6	17872	31.03	41.33	-30.84	41.52	54.00	12.48	Vertical

11be(EHT160)_TX_CH_111_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7990.375	39.26	37.28	-18.79	57.75	88.20	30.45	Horizontal
2	9058	45.76	38.01	-38.92	44.84	74.00	29.16	Horizontal
3	11219.6667	42.78	39.17	-35.59	46.36	74.00	27.64	Horizontal
4	13850.3333	42.93	40.33	-34.59	48.66	88.20	39.54	Horizontal
5	17984	39.16	41.65	-30.77	50.04	74.00	23.96	Horizontal
6	17857.6667	31.33	41.29	-30.74	41.88	54.00	12.12	Horizontal

11be(EHT160)_TX_CH_111_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7974.1875	39.08	37.25	-18.80	57.53	88.20	30.67	Vertical
2	8941.3333	46.61	37.96	-38.82	45.75	88.20	42.45	Vertical
3	10864.3333	43.60	39.14	-36.15	46.59	74.00	27.41	Vertical
4	13894.3333	42.11	40.35	-34.34	48.11	88.20	40.09	Vertical
5	17817	39.66	41.17	-30.44	50.39	74.00	23.61	Vertical
6	17834.3333	30.53	41.22	-30.57	41.18	54.00	12.82	Vertical

11be(EHT160)_TX_CH_143_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7976.375	39.61	37.25	-18.80	58.06	88.20	30.14	Horizontal
2	9013	46.13	38.00	-38.62	45.51	74.00	28.49	Horizontal
3	10980.6667	44.25	39.28	-35.72	47.81	74.00	26.19	Horizontal
4	14387	41.41	40.17	-33.84	47.74	88.20	40.46	Horizontal
5	17845.6667	39.37	41.25	-30.65	49.97	74.00	24.03	Horizontal
6	17360.3333	31.00	39.84	-31.78	39.06	68.20	29.14	Horizontal

11be(EHT160)_TX_CH_143_Vertical




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7956.25	40.28	37.21	-18.82	58.68	88.20	29.52	Vertical
2	8959.6667	46.36	37.97	-38.73	45.60	88.20	42.60	Vertical
3	10858.3333	43.48	39.13	-36.17	46.44	74.00	27.56	Vertical
4	13920	42.97	40.36	-34.45	48.88	88.20	39.32	Vertical
5	17309	40.20	39.70	-31.62	48.28	88.20	39.92	Vertical
6	17334.6667	30.74	39.77	-31.70	38.81	68.20	29.39	Vertical

11be(EHT160)_TX_CH_175_Horizontal




Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7949.6875	39.82	37.20	-18.82	58.20	88.20	30.00	Horizontal
2	8963.3333	45.81	37.97	-38.71	45.07	88.20	43.13	Horizontal
3	10915	43.95	39.20	-35.94	47.21	74.00	26.79	Horizontal
4	13914	41.99	40.36	-34.41	47.94	88.20	40.26	Horizontal
5	17833.6667	39.52	41.22	-30.56	50.18	74.00	23.82	Horizontal
6	17923	30.98	41.48	-30.97	41.49	54.00	12.51	Horizontal

11be(EHT160)_TX_CH_175_Vertical



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7996.9375	39.25	37.29	-18.78	57.76	88.20	30.44	Vertical
2	8955.3333	46.75	37.97	-38.75	45.97	88.20	42.23	Vertical
3	10991	43.43	39.29	-35.68	47.04	74.00	26.96	Vertical
4	13883.6667	42.35	40.34	-34.40	48.29	88.20	39.91	Vertical
5	17934	39.88	41.51	-30.93	50.46	74.00	23.54	Vertical
6	17984.6667	30.34	41.66	-30.77	41.23	54.00	12.77	Vertical

11be(EHT160)_TX_CH_207_Horizontal



Data List								
NO.	Frequency [MHz]	Reading [dBμV]	AF [dB/m]	Factor [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity
1	7900.6875	39.26	37.10	-18.86	57.50	88.20	30.70	Horizontal
2	9006.3333	45.23	38.00	-38.57	44.66	74.00	29.34	Horizontal
3	10690.3333	43.08	38.93	-36.13	45.87	74.00	28.13	Horizontal
4	13639.6667	41.38	40.22	-34.52	47.08	88.20	41.12	Horizontal
5	17935	39.67	41.51	-30.93	50.25	74.00	23.75	Horizontal
6	17985.3333	30.08	41.66	-30.77	40.97	54.00	13.03	Horizontal