

**COSPAS/SARSAT
EMERGENCY LOCATOR BEACON**

Operating Temp: -20°C to 55°C (Class 2)

THIS SATELLITE PLB WILL NOT FLOAT

OPERATING INSTRUCTIONS:

- 1) Remove cover
- 2) Activate and connect GPS receiver
- 3) Pull pin completely out
Blinking green = transmission
Single Blink = GPS NOT Acquired
Double Blink = GPS Acquired

SELF TEST INSTRUCTIONS:

- 1) Remove cover
- 2) Push pin down into hole
GREEN = PASS
RED = NOT PASS
- 3) Release pin within 30 seconds
to avoid false alarms

Battery Type US DOT Approved Li/MnO₂

MBT 040600 SN: **DUMMY**

Frequency 406.025 MHz 121.5MHz

Battery Expiration Date: 00/0000

ID: 0000000000000000

FCC ID: RG6-MBT-040600

**MICROWAVE MONOLITHICS INCORPORATED
SIMI VALLEY, CA 93065 USA**

**COSPAS/SARSAT
EMERGENCY LOCATOR BEACON**

Operating Temp: -20°C to 55°C (Class 2)

THIS SATELLITE PLB WILL NOT FLOAT

OPERATING INSTRUCTIONS:

- 1) Remove cover
- 2) Pull pin completely out
Blinking green = transmission
Single Blink = GPS NOT Acquired
Double Blink = GPS Acquired

SELF TEST INSTRUCTIONS:

- 1) Remove cover
- 2) Push pin down into hole
GREEN = PASS
RED = NOT PASS
- 3) Release pin within 30 seconds
to avoid false alarms

Battery Type US DOT Approved Li/MnO₂

MBT 04060 SN: **DUMMY**

TYPE GP

Frequency 406.025 MHz 121.5MHz

Battery Expiration Date: 00/0000

ID: 0000000000000000

FCC ID: RG6-MBT-040600

**MICROWAVE MONOLITHICS INCORPORATED
SIMI VALLEY, CA 93065 USA**