



RADIO TEST REPORT

Report No: STS1604079F02

Issued for

Adams Future Limited

Unit 1008,10/F, Fook Hong Industrial Building,No.19 Sheung
Yuet Road,Kowloon Bay Kowloon Hong Kong

Product Name:	Video
Brand Name:	KATA
Model Name:	Kata Box
Series Model:	Kata BoxXXXX (X: could be a~z or A~Z or 0~9 or blank)
FCC ID:	RGF- K0316
Test Standard:	FCC Part 15.247

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented test sample.

Shenzhen STS Test Services Co., Ltd.
1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China
TEL: +86-755 3688 6288 FAX: +86-755 3688 6277 E-mail:sts@stsapp.com





TEST RESULT CERTIFICATION

Applicant's name : Adams Future Limited
Address : Unit 1008,10/F, Fook Hong Industrial Building, No.19 Sheung Yuet Road, Kowloon Bay Kowloon Hong Kong
Manufacture's Name : Shenzhen Mele Star Technology Limited
Address : 3F, Bldg#1, 28 Cuijing Road, Pingshan New District, Shenzhen, China

Product description

Product name : Video
Brand name : KATA
Model and/or type reference .. : Kata Box

Standards : FCC Part15.247

Test procedure ANSI C63.10-2013 and ANSI C63.4-2014

This device described above has been tested by STS, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document may be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test :

Date (s) of performance of tests : 15 Apr. 2016~26 Apr. 2016

Date of Issue : 27 Apr. 2016

Test Result : **Pass**

Testing Engineer :

(Jin Ming)

Technical Manager :

(Vita Li)

Authorized Signatory :

(Bovey Yang)






Table of Contents	Page
1. SUMMARY OF TEST RESULTS	6
1.1 TEST FACTORY	7
1.2 MEASUREMENT UNCERTAINTY	7
2. GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 DESCRIPTION OF TEST MODES	10
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	11
2.4 DESCRIPTION OF SUPPORT UNITS	12
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	13
3. EMC EMISSION TEST	14
3.1 CONDUCTED EMISSION MEASUREMENT	14
3.2 RADIATED EMISSION MEASUREMENT	18
4. CONDUCTED SPURIOUS & BAND EDGE EMISSION	33
4.1 APPLIED PROCEDURES / LIMIT	33
4.2 TEST PROCEDURE	33
4.3 DEVIATION FROM STANDARD	33
4.4 TEST SETUP	33
4.5 EUT OPERATION CONDITIONS	33
4.6 TEST RESULTS	34
5. POWER SPECTRAL DENSITY TEST	43
5.1 APPLIED PROCEDURES / LIMIT	43
5.2 TEST PROCEDURE	43
5.3 DEVIATION FROM STANDARD	43
5.4 TEST SETUP	43
5.5 EUT OPERATION CONDITIONS	43
5.6 TEST RESULTS	44
6. BANDWIDTH TEST	50
6.1 APPLIED PROCEDURES / LIMIT	50
6.2 TEST PROCEDURE	50
6.3 DEVIATION FROM STANDARD	50
6.4 TEST SETUP	50
6.5 EUT OPERATION CONDITIONS	50
6.6 TEST RESULTS	51



Table of Contents	Page
7. PEAK OUTPUT POWER TEST	57
7.1 APPLIED PROCEDURES / LIMIT	57
7.2 TEST PROCEDURE	57
7.3 DEVIATION FROM STANDARD	57
7.4 TEST SETUP	57
7.5 EUT OPERATION CONDITIONS	57
7.6 TEST RESULTS	58
8. ANTENNA REQUIREMENT	59
8.1 STANDARD REQUIREMENT	59
8.2 EUT ANTENNA	59
APPENDIX - PHOTOS OF TEST SETUP	60



**Revision History**

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	27 Apr. 2016	STS1604079F01	ALL	Initial Issue





1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:
KDB 558074 D01 DTS Meas Guidance v03r04

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)(3)	Output Power	PASS	
15.247 (c)	Radiated Spurious Emission	PASS	
15.247 (d)	Conducted Spurious & Band Edge Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Radiated Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) all tests are according to ANSI C63.10-2013 and ANSI C63.4-2014.



1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190,Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong,China

CNAS Registration No.: L7649;

FCC Registration No.: 842334; IC Registration No.: 12108A-1

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission (9KHz-150KHz)	$\pm 2.88\text{dB}$
2	Conducted Emission (150KHz-30MHz)	$\pm 2.67\text{dB}$
3	RF power,conducted	$\pm 0.70\text{dB}$
4	Spurious emissions,conducted	$\pm 1.19\text{dB}$
5	All emissions,radiated(<30M) (9KHz-30MHz)	$\pm 2.45\text{dB}$
6	All emissions,radiated(<1G) 30MHz-200MHz	$\pm 2.83\text{dB}$
7	All emissions,radiated(<1G) 200MHz-1000MHz	$\pm 2.94\text{dB}$
8	All emissions,radiated(>1G)	$\pm 3.03\text{dB}$
9	Temperature	$\pm 0.5^{\circ}\text{C}$
10	Humidity	$\pm 2\%$



2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

Equipment	Video	
Trade Name	KATA	
Model Name	Kata Box	
Series Model	Kata BoxXXXX (X: could be a~z or A~Z or 0~9 or blank)	
Model Difference	Only different in model name	
Product Description	The EUT is a Video	
	Operation Frequency:	802.11b/g/n 20: 2412~2462 MHz
	Modulation Type:	CCK/BPSK/QPSK/16QAM
	Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n(20MHz):300/150/144.44/130/117/115.56/104/86.67/78/52/6.5Mbps
	Number Of Channel	802.11b/g/n20: 11CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	2.3 dBi
	Duty Cycle	>98%
Channel List	Please refer to the Note 2.	
Adapter	Input: AC100-240V, 500mA, 50/60 Hz Output: DC 5V, 2A	
Hardware version number	1.10-2	
Software version number	1.10-3	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

- 1 For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



2

Channel List for 802.11b/g/n(20MHz)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3 Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	KATA	Kata Box	PIFA Antenna	N/A	2.3	N/A





2.2 DESCRIPTION OF TEST MODES

Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description	Data Rate
Mode 1	TX IEEE 802.11b CH1	1 Mbps
Mode 2	TX IEEE 802.11b CH6	1 Mbps
Mode 3	TX IEEE 802.11 b CH11	1 Mbps
Mode 4	TX IEEE 802.11g CH1	6 Mbps
Mode 5	TX IEEE 802.11g CH6	6 Mbps
Mode 6	TX IEEE 802.11g CH11	6 Mbps
Mode 7	TX IEEE 802.11n HT20 CH1	MCS 0
Mode 8	TX IEEE 802.11n HT20 CH6	MCS 0
Mode 9	TX IEEE 802.11n HT20 CH11	MCS 0

Note:


- (1) Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table.
- (2) We have be tested for all avaiable U.S. voltage and frequencies(For 120V,60Hz) for which the device is capable of operation.
- (3) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

AC Conducted Emission


Test Case	
AC Conducted Emission	Mode10: Keeping WIFI TX

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



Conducted Emission Test





2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Serial No.	Note
E-1	Video	KATA	Kata Box	N/A	EUT
E-2	Adapter	N/A	S12A02-050A200-06	N/A	EUT
E-3	TV	ROWA	LED24C310A/MSV59/RKG1423	N/A	N/A

Item	Shielded Type	Ferrite Core	Length	Note
C-1	USB Cable shielded line (Charging)	NO	100cm	N/A
C-2	USB Cable shielded line (Charging)	NO	110cm	N/A

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.
- (3) “YES” is means “shielded” “with core”; “NO” is means “unshielded” “without core”.



2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Test Receiver	R&S	ESCI	101427	2015.10.25	2016.10.24
Bilog Antenna	TESEQ	CBL6111D	34678	2015.11.25	2016.11.24
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2016.03.06	2017.03.05
Horn Antenna	Schwarzbeck	BBHA 9170	9170-0741	2016.03.06	2017.03.05
50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.06	2016.06.05
PreAmplifier	Agilent	8449B	60538	2015.10.25	2016.10.24
Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07
Preamplifier	Agilent	8449B	60538	2015.11.05	2016.11.05
Low frequency cable	EM	R01	N/A	N/A	N/A
High frequency cable	SCHWARZBECK	AK9515H	SN-96286/96287	N/A	N/A

Conduction Test equipment

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
EMI Test Receiver	R&S	ESPI	102086	2015.11.20	2016.11.19
LISN	R&S	ENV216	101242	2015.10.25	2016.10.24
LISN	EMCO	3810/2NM	000-23625	2015.10.25	2016.10.24
Conduction Cable	EM	C01	N/A	N/A	N/A

RF Connected Test

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
USB RF power sensor	DARE	RPR3006W	15I00041SNO03	2015.10.25	2016.10.24
Spectrum Analyzer	Agilent	E4407B	MY50140340	2015.10.25	2016.10.24
Signal Analyzer	Agilent	N9020A	MY49100060	2015.11.18	2016.11.17



3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION LIMITS

operating frequency band. In case the emission fall within the restricted band specified on Part 15. 207(a) limit in the table below has to be followed.

FREQUENCY (MHz)	Conducted Emission limit (dBuV)	
	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.


The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

- The EUT was placed 0.4 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- LISN at least 80 cm from nearest part of EUT chassis.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.4 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



3.1.5 TEST RESULT


Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	L
Mode :	Mode 10		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.2340	33.16	9.20	42.36	62.31	-19.95	QP
0.2340	21.60	9.20	30.80	52.31	-21.51	AVG
0.6260	31.64	9.20	40.84	56.00	-15.16	QP
0.6260	19.06	9.20	28.26	46.00	-17.74	AVG
0.6780	34.59	9.23	43.82	56.00	-12.18	QP
0.6780	24.13	9.23	33.36	46.00	-12.64	AVG
1.0620	30.85	9.16	40.01	56.00	-15.99	QP
1.0620	19.56	9.16	28.72	46.00	-17.28	AVG
1.7140	33.70	9.22	42.92	56.00	-13.08	QP
1.7140	20.26	9.22	29.48	46.00	-16.52	AVG
7.9340	24.41	9.35	33.76	60.00	-26.24	QP
7.9340	12.96	9.35	22.31	50.00	-27.69	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV






Temperature:	26 °C	Relative Humidity:	54%
Pressure:	1010hPa	Phase:	N
Mode :	Mode 10		

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
0.2260	36.45	9.20	45.65	62.60	-16.95	QP
0.2260	22.42	9.20	31.62	52.60	-20.98	AVG
0.6780	37.78	9.23	47.01	56.00	-8.99	QP
0.6780	27.06	9.23	36.29	46.00	-9.71	AVG
0.9580	32.65	9.25	41.90	56.00	-14.10	QP
0.9580	18.89	9.25	28.14	46.00	-17.86	AVG
1.3620	32.62	9.25	41.87	56.00	-14.13	QP
1.3620	20.24	9.25	29.49	46.00	-16.51	AVG
1.7820	34.07	9.25	43.32	56.00	-12.68	QP
1.7820	21.53	9.25	30.78	46.00	-15.22	AVG
8.1140	23.80	9.33	33.13	60.00	-26.87	QP
8.1140	11.22	9.33	20.55	50.00	-29.45	AVG

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

100.0 dBuV





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS

in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on Part 15. 205(a)&209(a) limit in the table below has to be followed.

LIMITS OF RADIATED EMISSION MEASUREMENT (0.009MHz - 1000MHz)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (1000MHz-25GHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

For Radiated Emission

Spectrum Parameter	Setting
Attenuation	Auto
Detector	Peak
Start Frequency	1000 MHz(Peak/AV)
Stop Frequency	10 th carrier hamonic(Peak/AV)
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /10 Hz

For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz, AV=1 MHz /10 Hz



Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~90kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	90kHz~110kHz / RB 200Hz for QP
Start ~ Stop Frequency	110kHz~490kHz / RB 200Hz for PK & AV
Start ~ Stop Frequency	490kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE


- The measuring distance of at 3 m shall be used for measurements at frequency 0.009MHz up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- The EUT was placed on the top of a rotating table 0.8 meters(above 1GHz is 1.5 m) above the ground at a 3 meter anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The height of the equipment shall be 0.8 m(above 1GHz is 1.5 m); the height of the test antenna shall vary between 1 m to 4 m. Horizontal and vertical polarizations of the antenna are set to make the measurement
- The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed test to three orthogonal axis. The worst case emissions were reported

3.2.3 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz





3.2.4 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.





3.2.5 TEST RESULT

9KHz-30MHz

Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX Mode	Polarization :	--


Freq.	Reading	Limit	Margin	State	Test Result
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F	
--	--	--	--	--	PASS
--	--	--	--	--	PASS

Note:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuV) + distance extrapolation factor.





(30MHz - 1000MHz)


Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)	Polarization :	Horizontal

Frequency	Reading	Correct	Result	Limit	Margin	Remark
(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	
48.8430	44.61	-20.89	23.72	40.00	-16.28	QP
88.9637	42.75	-20.45	22.30	43.50	-21.20	QP
163.7550	48.44	-18.81	29.63	43.50	-13.87	QP
455.9057	40.78	-10.29	30.49	46.00	-15.51	QP
601.4265	46.31	-7.12	39.19	46.00	-6.81	QP
684.7454	45.07	-5.66	39.41	46.00	-6.59	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m






Temperature:	20 °C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 1/2/3/4/5/6/7/8/9 (Mode 3-1M worst mode)	Polarization :	Vertical

Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
43.6584	47.65	-18.21	29.44	40.00	-10.56	QP
81.2116	51.85	-22.40	29.45	40.00	-10.55	QP
141.3298	53.66	-17.58	36.08	43.50	-7.42	QP
455.9057	42.51	-10.29	32.22	46.00	-13.78	QP
684.7454	43.67	-5.66	38.01	46.00	-7.99	QP
801.7862	40.32	-3.49	36.83	46.00	-9.17	QP

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

80.0 dBuV/m





(1000MHz-25GHz)

Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz

802.11b Low Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.26	45.13	-9.80	35.33	74.00	-38.67	PK	Vertical
3265.25	42.10	-9.80	32.30	54.00	-21.70	AV	Vertical
3265.19	45.11	-9.80	35.31	74.00	-38.69	PK	Horizontal
3265.23	42.08	-9.80	32.28	54.00	-21.72	AV	Horizontal
3334.84	42.85	-9.75	33.10	74.00	-40.90	PK	Vertical
3335.03	39.85	-9.75	30.10	54.00	-23.90	AV	Vertical
3334.84	42.84	-9.75	33.09	74.00	-40.91	PK	Horizontal
3335.06	39.87	-9.75	30.12	54.00	-23.88	AV	Horizontal
3349.87	42.61	-9.75	32.86	74.00	-41.14	PK	Vertical
3349.99	39.63	-9.75	29.88	54.00	-24.12	AV	Vertical
3349.89	42.66	-9.75	32.91	74.00	-41.09	PK	Horizontal
3349.95	39.64	-9.75	29.89	54.00	-24.11	AV	Horizontal
4000.22	39.98	-6.60	33.38	74.00	-40.62	PK	Vertical
4000.10	36.98	-6.60	30.38	54.00	-23.62	AV	Vertical
4000.17	39.98	-6.60	33.38	74.00	-40.62	PK	Horizontal
4000.09	36.95	-6.60	30.35	54.00	-23.65	AV	Horizontal
4823.93	39.39	-3.56	35.83	74.00	-38.17	PK	Vertical
4823.92	36.38	-3.56	32.82	54.00	-21.18	AV	Vertical
4823.90	39.38	-3.56	35.82	74.00	-38.18	PK	Horizontal
4823.97	36.43	-3.56	32.87	54.00	-21.13	AV	Horizontal
5360.21	38.31	-2.34	35.97	74.00	-38.03	PK	Vertical
5360.12	35.32	-2.34	32.98	54.00	-21.02	AV	Vertical
5360.19	38.31	-2.34	35.97	74.00	-38.03	PK	Horizontal
5360.11	35.33	-2.34	32.99	54.00	-21.01	AV	Horizontal
7236.27	37.75	3.40	41.15	74.00	-32.85	PK	Vertical
7236.35	34.76	3.40	38.16	54.00	-15.84	AV	Vertical
7236.31	37.81	3.40	41.21	74.00	-32.79	PK	Horizontal
7236.33	34.81	3.40	38.21	54.00	-15.79	AV	Horizontal
8124.44	36.25	4.80	41.05	74.00	-32.95	PK	Vertical



8124.41	33.20	4.80	38.00	54.00	-16.00	AV	Vertical
8124.41	36.25	4.80	41.05	74.00	-32.95	PK	Horizontal
8124.42	33.23	4.80	38.03	54.00	-15.97	AV	Horizontal
9105.09	35.03	5.00	40.03	74.00	-33.97	PK	Vertical
9105.26	32.06	5.00	37.06	54.00	-16.94	AV	Vertical
9105.13	35.03	5.00	40.03	74.00	-33.97	PK	Horizontal
9105.22	32.02	5.00	37.02	54.00	-16.98	AV	Horizontal
11036.36	34.04	10.20	44.24	74.00	-29.76	PK	Vertical
11036.52	31.03	10.20	41.23	54.00	-12.77	AV	Vertical
11036.39	34.05	10.20	44.25	74.00	-29.75	PK	Horizontal
11036.55	31.03	10.20	41.23	54.00	-12.77	AV	Horizontal
13299.86	32.87	12.20	45.07	74.00	-28.93	PK	Vertical
13299.87	29.88	12.20	42.08	54.00	-11.92	AV	Vertical
13299.89	32.86	12.20	45.06	74.00	-28.94	PK	Horizontal
13299.87	29.86	12.20	42.06	54.00	-11.94	AV	Horizontal
14480.21	31.78	13.40	45.18	74.00	-28.82	PK	Vertical
14480.35	28.77	13.40	42.17	54.00	-11.83	AV	Vertical
14480.19	31.78	13.40	45.18	74.00	-28.82	PK	Horizontal
14480.35	28.79	13.40	42.19	54.00	-11.81	AV	Horizontal
16000.23	30.95	12.40	43.35	74.00	-30.65	PK	Vertical
16000.30	27.90	12.40	40.30	54.00	-13.70	AV	Vertical
16000.22	30.93	12.40	43.33	74.00	-30.67	PK	Horizontal
16000.30	27.87	12.40	40.27	54.00	-13.73	AV	Horizontal
17998.26	28.12	23.10	51.22	74.00	-22.78	PK	Vertical
17998.16	25.07	23.10	48.17	54.00	-5.83	AV	Vertical
17998.19	28.07	23.10	51.17	74.00	-22.83	PK	Horizontal
17998.04	25.06	23.10	48.16	54.00	-5.84	AV	Horizontal



802.11b Mid Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.18	45.05	-9.80	35.25	74.00	-38.75	PK	Vertical
3265.13	42.03	-9.80	32.23	54.00	-21.77	AV	Vertical
3265.12	45.06	-9.80	35.26	74.00	-38.74	PK	Horizontal
3265.15	42.07	-9.80	32.27	54.00	-21.73	AV	Horizontal
3334.79	42.78	-9.75	33.03	74.00	-40.97	PK	Vertical
3334.94	39.79	-9.75	30.04	54.00	-23.96	AV	Vertical
3334.74	42.77	-9.75	33.02	74.00	-40.98	PK	Horizontal
3334.96	39.79	-9.75	30.04	54.00	-23.96	AV	Horizontal
3349.78	42.52	-9.75	32.77	74.00	-41.23	PK	Vertical
3349.88	39.54	-9.75	29.79	54.00	-24.21	AV	Vertical
3349.79	42.55	-9.75	32.80	74.00	-41.20	PK	Horizontal
3349.84	39.56	-9.75	29.81	54.00	-24.19	AV	Horizontal
4000.14	39.91	-6.60	33.31	74.00	-40.69	PK	Vertical
4000.00	36.92	-6.60	30.32	54.00	-23.68	AV	Vertical
4000.12	39.91	-6.60	33.31	74.00	-40.69	PK	Horizontal
3999.98	36.90	-6.60	30.30	54.00	-23.70	AV	Horizontal
4874.88	39.36	-3.56	35.80	74.00	-38.20	PK	Vertical
4874.90	36.36	-3.56	32.80	54.00	-21.20	AV	Vertical
4874.84	39.33	-3.56	35.77	74.00	-38.23	PK	Horizontal
4874.87	36.29	-3.56	32.73	54.00	-21.27	AV	Horizontal
5360.08	38.27	-2.34	35.93	74.00	-38.07	PK	Vertical
5360.00	35.26	-2.34	32.92	54.00	-21.08	AV	Vertical
5360.14	38.22	-2.34	35.88	74.00	-38.12	PK	Horizontal
5360.04	35.24	-2.34	32.90	54.00	-21.10	AV	Horizontal
7336.24	37.69	3.40	41.09	74.00	-32.91	PK	Vertical
7336.18	34.67	3.40	38.07	54.00	-15.93	AV	Vertical
7336.20	37.71	3.40	41.11	74.00	-32.89	PK	Horizontal
7336.23	34.73	3.40	38.13	54.00	-15.87	AV	Horizontal
8124.33	36.17	4.80	40.97	74.00	-33.03	PK	Vertical
8124.36	33.13	4.80	37.93	54.00	-16.07	AV	Vertical
8124.34	36.14	4.80	40.94	74.00	-33.06	PK	Horizontal
8124.35	33.17	4.80	37.97	54.00	-16.03	AV	Horizontal
9105.05	34.98	5.00	39.98	74.00	-34.02	PK	Vertical
9105.15	31.94	5.00	36.94	54.00	-17.06	AV	Vertical



9105.03	35.02	5.00	40.02	74.00	-33.98	PK	Horizontal
9105.13	31.96	5.00	36.96	54.00	-17.04	AV	Horizontal
11036.28	33.94	10.20	44.14	74.00	-29.86	PK	Vertical
11036.47	30.97	10.20	41.17	54.00	-12.83	AV	Vertical
11036.29	33.95	10.20	44.15	74.00	-29.85	PK	Horizontal
11036.47	30.91	10.20	41.11	54.00	-12.89	AV	Horizontal
13299.84	32.83	12.20	45.03	74.00	-28.97	PK	Vertical
13299.79	29.86	12.20	42.06	54.00	-11.94	AV	Vertical
13299.79	32.80	12.20	45.00	74.00	-29.00	PK	Horizontal
13299.83	29.80	12.20	42.00	54.00	-12.00	AV	Horizontal
14480.16	31.74	13.40	45.14	74.00	-28.86	PK	Vertical
14480.28	28.72	13.40	42.12	54.00	-11.88	AV	Vertical
14480.11	31.71	13.40	45.11	74.00	-28.89	PK	Horizontal
14480.31	28.70	13.40	42.10	54.00	-11.90	AV	Horizontal
16000.13	30.88	12.40	43.28	74.00	-30.72	PK	Vertical
16000.24	27.87	12.40	40.27	54.00	-13.73	AV	Vertical
16000.12	30.84	12.40	43.24	74.00	-30.76	PK	Horizontal
16000.23	27.82	12.40	40.22	54.00	-13.78	AV	Horizontal
17998.28	28.01	23.10	51.11	74.00	-22.89	PK	Vertical
17998.18	25.01	23.10	48.11	54.00	-5.89	AV	Vertical
17998.15	27.98	23.10	51.08	74.00	-22.92	PK	Horizontal
17998.07	25.05	23.10	48.15	54.00	-5.85	AV	Horizontal



802.11b High Channel

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	
3265.14	44.99	-9.80	35.19	74.00	-38.81	PK	Vertical
3265.16	42.06	-9.80	32.26	54.00	-21.74	AV	Vertical
3265.14	45.00	-9.80	35.20	74.00	-38.80	PK	Horizontal
3265.21	42.05	-9.80	32.25	54.00	-21.75	AV	Horizontal
3334.73	42.79	-9.75	33.04	74.00	-40.96	PK	Vertical
3334.98	39.74	-9.75	29.99	54.00	-24.01	AV	Vertical
3334.75	42.76	-9.75	33.01	74.00	-40.99	PK	Horizontal
3334.97	39.78	-9.75	30.03	54.00	-23.97	AV	Horizontal
3349.78	42.57	-9.75	32.82	74.00	-41.18	PK	Vertical
3349.88	39.53	-9.75	29.78	54.00	-24.22	AV	Vertical
3349.80	42.61	-9.75	32.86	74.00	-41.14	PK	Horizontal
3349.89	39.55	-9.75	29.80	54.00	-24.20	AV	Horizontal
4000.17	39.90	-6.60	33.30	74.00	-40.70	PK	Vertical
4000.00	36.96	-6.60	30.36	54.00	-23.64	AV	Vertical
4000.13	39.94	-6.60	33.34	74.00	-40.66	PK	Horizontal
4000.00	36.91	-6.60	30.31	54.00	-23.69	AV	Horizontal
4924.88	39.30	-3.56	35.74	74.00	-38.26	PK	Vertical
4924.89	36.33	-3.56	32.77	54.00	-21.23	AV	Vertical
4924.86	39.32	-3.56	35.76	74.00	-38.24	PK	Horizontal
4924.87	36.37	-3.56	32.81	54.00	-21.19	AV	Horizontal
5360.14	38.27	-2.34	35.93	74.00	-38.07	PK	Vertical
5360.03	35.26	-2.34	32.92	54.00	-21.08	AV	Vertical
5360.11	38.28	-2.34	35.94	74.00	-38.06	PK	Horizontal
5360.02	35.27	-2.34	32.93	54.00	-21.07	AV	Horizontal
7386.21	37.74	3.40	41.14	74.00	-32.86	PK	Vertical
7386.17	34.70	3.40	38.10	54.00	-15.90	AV	Vertical
7386.25	37.70	3.40	41.10	74.00	-32.90	PK	Horizontal
7386.20	34.71	3.40	38.11	54.00	-15.89	AV	Horizontal
8124.35	36.18	4.80	40.98	74.00	-33.02	PK	Vertical
8124.36	33.12	4.80	37.92	54.00	-16.08	AV	Vertical
8124.33	36.17	4.80	40.97	74.00	-33.03	PK	Horizontal
8124.34	33.16	4.80	37.96	54.00	-16.04	AV	Horizontal
9105.01	35.02	5.00	40.02	74.00	-33.98	PK	Vertical
9105.16	31.94	5.00	36.94	54.00	-17.06	AV	Vertical



9105.03	35.01	5.00	40.01	74.00	-33.99	PK	Horizontal
9105.10	32.02	5.00	37.02	54.00	-16.98	AV	Horizontal
11036.28	33.93	10.20	44.13	74.00	-29.87	PK	Vertical
11036.46	30.99	10.20	41.19	54.00	-12.81	AV	Vertical
11036.29	33.93	10.20	44.13	74.00	-29.87	PK	Horizontal
11036.44	30.92	10.20	41.12	54.00	-12.88	AV	Horizontal
13299.79	32.79	12.20	44.99	74.00	-29.01	PK	Vertical
13299.74	29.80	12.20	42.00	54.00	-12.00	AV	Vertical
13299.79	32.83	12.20	45.03	74.00	-28.97	PK	Horizontal
13299.81	29.85	12.20	42.05	54.00	-11.95	AV	Horizontal
14480.13	31.69	13.40	45.09	74.00	-28.91	PK	Vertical
14480.28	28.75	13.40	42.15	54.00	-11.85	AV	Vertical
14480.12	31.73	13.40	45.13	74.00	-28.87	PK	Horizontal
14480.30	28.71	13.40	42.11	54.00	-11.89	AV	Horizontal
16000.15	30.85	12.40	43.25	74.00	-30.75	PK	Vertical
16000.21	27.78	12.40	40.18	54.00	-13.82	AV	Vertical
16000.14	30.87	12.40	43.27	74.00	-30.73	PK	Horizontal
16000.25	27.79	12.40	40.19	54.00	-13.81	AV	Horizontal
17998.30	28.03	23.10	51.13	74.00	-22.87	PK	Vertical
17998.18	25.02	23.10	48.12	54.00	-5.88	AV	Vertical
17998.16	28.02	23.10	51.12	74.00	-22.88	PK	Horizontal
17998.08	25.00	23.10	48.10	54.00	-5.90	AV	Horizontal

Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.

2. Scan with 802.11b, 802.11g, 802.11n (HT-20), the worst case is 802.11b.

Emission Level = Meter Reading + Factor

Margin = Limit - Emission Level

3. The frequency emission of peak points that did not show above the forms are at least 20dB below the limit, the frequency emission is mainly from the environment noise.



3.2.6 TEST RESULTS (Band edge)

Temperature :	20 °C	Relative Humidity :	48%
Pressure :	1010 hPa	Test Voltage :	AC 120V/60Hz

Frequency (MHz)	Reading (dBuV)	Factor (dB)	Emission Level (dBμV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Comment
802.11 b							
2400.0	69.10	-12.99	56.11	74	-17.89	PK	Vertical
2400.0	54.89	-12.99	41.90	54	-12.10	AV	Vertical
2400.0	70.13	-12.99	57.14	74	-16.86	PK	Horizontal
2400.0	54.03	-12.99	41.04	54	-12.96	AV	Horizontal
2483.5	70.91	-12.78	58.13	74	-15.87	PK	Vertical
2483.5	53.96	-12.78	41.18	54	-12.82	AV	Vertical
2483.5	71.01	-12.78	58.23	74	-15.77	PK	Horizontal
2483.5	53.99	-12.78	41.21	54	-12.79	AV	Horizontal
802.11 g							
2400.0	68.88	-12.99	55.89	74	-18.11	PK	Vertical
2400.0	54.99	-12.99	42.00	54	-12.00	AV	Vertical
2400.0	70.03	-12.99	57.04	74	-16.96	PK	Horizontal
2400.0	53.89	-12.99	40.90	54	-13.10	AV	Horizontal
2483.5	71.00	-12.78	58.22	74	-15.78	PK	Vertical
2483.5	54.20	-12.78	41.42	54	-12.58	AV	Vertical
2483.5	70.96	-12.78	58.18	74	-15.82	PK	Horizontal
2483.5	54.07	-12.78	41.29	54	-12.71	AV	Horizontal



802.11 n20							
2400.0	69.00	-12.99	56.01	74	-17.99	PK	Vertical
2400.0	54.95	-12.99	41.96	54	-12.04	AV	Vertical
2400.0	69.97	-12.99	56.98	74	-17.02	PK	Horizontal
2400.0	53.99	-12.99	41.00	54	-13.00	AV	Horizontal
2483.5	71.09	-12.78	58.31	74	-15.69	PK	Vertical
2483.5	53.96	-12.78	41.18	54	-12.82	AV	Vertical
2483.5	70.94	-12.78	58.16	74	-15.84	PK	Horizontal
2483.5	53.92	-12.78	41.14	54	-12.86	AV	Horizontal
Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier.							
Low measurement frequencies is range from 2310 to 2400 MHz, high measurement frequencies is range from 2483.5 to 2500 MHz. Only show the worst point data of the emissions in the frequency 2310-2400 MHz and 2483.5-2500 MHz.							

4. CONDUCTED SPURIOUS & BAND EDGE EMISSION

4.1 APPLIED PROCEDURES / LIMIT

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

4.2 TEST PROCEDURE

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	30 MHz to 10th carrier harmonic
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold


For Band edge

Spectrum Parameter	Setting
Detector	Peak
Start/Stop Frequency	Lower Band Edge: 2300 to 2430 MHz Upper Band Edge: 2450 to 2500 MHz
RB / VB (emission in restricted band)	100 KHz/300 KHz
Trace-Mode:	Max hold

4.3 DEVIATION FROM STANDARD

No deviation.

4.4 TEST SETUP



The EUT which is powered by the Battery, is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

4.5 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




4.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		

CH 01




CH 06






CH 11






Band edge

CH 01




CH 11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		

CH 01




CH06






CH 11






Band edge

CH 01




CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		

CH 01




CH 06






CH 11






Band edge

CH 01



CH 11





5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(e)	Power Spectral Density	<8 dBm (RBW $\geq$ 3KHz)	2400-2483.5	PASS


5.2 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS channel bandwidth.
3. Set the 100 kHz $\geq$ RBW $\geq$ 3 kHz.
4. Set the VBW $\geq$ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 DEVIATION FROM STANDARD

No deviation.

5.4 TEST SETUP



5.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




5.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm/3kHz)	Limit (dBm)	Result
2412 MHz	-8.025	<8	PASS
2437 MHz	-8.213	<8	PASS
2462 MHz	-6.929	<8	PASS

TX CH01






TX CH06



TX CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	Power Density (dBm/3kHz)	Limit (dBm)	Result
2412 MHz	-10.969	<8	PASS
2437 MHz	-10.405	<8	PASS
2462 MHz	-12.042	<8	PASS

TX CH01






TX CH06



TX CH11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1015 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	Power Density (dBm/3kHz)	Limit (dBm)	Result
2412 MHz	-11.620	<8	PASS
2437 MHz	-11.665	<8	PASS
2462 MHz	-12.880	<8	PASS

TX CH01






TX CH06



TX CH11





6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS

6.2 TEST PROCEDURE

The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described above (i.e., RBW = 100 kHz, VBW $\geq$ 3RBW, peak detector with maximum hold) is implemented by the instrumentation function. When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.

6.3 DEVIATION FROM STANDARD

No deviation.

6.4 TEST SETUP



6.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.




6.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX b Mode /CH01, CH06, CH11		

Remark: PEAK DETECTOR IS USED


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	8.554	≥500KHz	PASS
2437 MHz	9.032	≥500KHz	PASS
2462 MHz	9.032	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX g Mode /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	16.28	≥500KHz	PASS
2437 MHz	16.28	≥500KHz	PASS
2462 MHz	16.29	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11






Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	TX n Mode(20M) /CH01, CH06, CH11		


Frequency	6dB Bandwidth (MHz)	Channel Separation (KHz)	Result
2412 MHz	17.56	≥500KHz	PASS
2437 MHz	17.57	≥500KHz	PASS
2462 MHz	17.56	≥500KHz	PASS

TX CH 01






TX CH 06



TX CH 11





7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.2 TEST PROCEDURE

- a. The EUT was directly connected to the Power Sensor&PC

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP



7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.



7.6 TEST RESULTS

Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	AC 120V/60Hz

TX 802.11b Mode				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak(dBm)	AVG(dBm)	dBm
CH01	2412	12.36	12.27	30
CH06	2437	13.63	13.54	30
CH11	2462	13.85	13.76	30

TX 802.11g Mode				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak(dBm)	AVG(dBm)	dBm
CH01	2412	11.25	10.79	30
CH06	2437	11.30	10.84	30
CH11	2462	11.47	11.01	30

TX 802.11n20 Mode				
Test Channe	Frequency	Conducted Output Power		LIMIT
	(MHz)	Peak(dBm)	AVG(dBm)	dBm
CH01	2412	11.15	10.69	30
CH06	2437	11.07	10.61	30
CH11	2462	11.20	10.74	30



8. ANTENNA REQUIREMENT

8.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2 EUT ANTENNA



The EUT antenna is PIFA Antenna. It comply with the standard requirement.





APPENDIX - PHOTOS OF TEST SETUP

Radiated Measurement Photos





Conducted Measurement Photos



※※※※END OF THE REPORT※※※※