


TEST REPORT

Application No.: SZCR2402000543AT
Applicant: Telit Communications S.p.A.
Address of Applicant: Via Stazione di Prosecco 5/b, 34010 Sgonico, Trieste, Italy
Manufacturer: Telit Communications S.p.A.
Address of Manufacturer: Via Stazione di Prosecco 5/b, 34010 Sgonico, Trieste, Italy
Factory: Fushan Technology Vietnam
Address of Factory: No. 8, Road 6, VSIP Bac Ninh, Phu Chan, Tu Son, Bac Ninh, Vietnam
Equipment Under Test (EUT):
EUT Name: 802.11 a/b/g/n WiFi Module+BT combo module
Model No.: WE310G4-P
Trade Mark: 
FCC ID: RI7WE310G4
Standard(s) : 47 CFR Part 15, Subpart E 15.407
Date of Receipt: 2024-02-20
Date of Test: 2024-02-22 to 2024-03-08
Date of Issue: 2024-03-11

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240200054302

Page: 2 of 158

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2024-03-11		Original

Authorized for issue by:				
				
		Charlie Dai/Project Engineer		
				
		Eric Fu/Reviewer		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Inspection Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Radiated Emissions (Above 1GHz)	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands		KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)	Pass

Remark:

Model No.: WE310G4-P

This test report (Ref. No.: SZCR240200054302) is only valid with the original test report (Ref. No.: FR261411AN).

According to the declaration from the applicant, the models in this report and models in original report were identical, the only difference is that the antenna has been replaced and the BLE function has been disabled through software.

Items	Original Antenna	New Antenna
2.4G WIFI	Dipole Antenna 2.5dBi	Ceramic Antenna 1.0dBi
5G WIFI	Dipole Antenna 4.5dBi	Ceramic Antenna 2.6dBi
BLE	Dipole Antenna 2.5dBi	N/A

Considering to the difference, pre-scan were performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

Therefore in this report the section 2 items were fully retested on model and shown the data in this report, other tests please refer to original report FR261411AN.



3 Contents

	Page
1 Cover Page	1
2 Test Summary.....	3
3 Contents	4
4 General Information.....	5
4.1 Details of E.U.T.	5
4.2 Description of Support Units	5
4.3 Measurement Uncertainty	6
4.4 Test Location	7
4.5 Test Facility.....	7
4.6 Deviation from Standards	7
4.7 Abnormalities from Standard Conditions	7
5 Equipment List	8
6 Radio Spectrum Technical Requirement.....	9
6.1 Antenna Requirement	9
6.1.1 Test Requirement:	9
6.1.2 Conclusion	9
7 Radio Spectrum Matter Test Results	10
7.1 Radiated Emissions (Above 1GHz).....	10
7.1.1 E.U.T. Operation	10
7.1.2 Test Mode Description	11
7.1.3 Test Setup Diagram	11
7.1.4 Measurement Procedure and Data.....	12
7.2 Radiated Emissions which fall in the restricted bands	77
7.2.1 E.U.T. Operation	77
7.2.2 Test Mode Description	78
7.2.3 Test Setup Diagram	78
7.2.4 Measurement Procedure and Data.....	79
8 Test Setup Photo	158
9 EUT Constructional Details (EUT Photos).....	158



4 General Information

4.1 Details of E.U.T.

Power supply:	DC 3.7V
Operation Frequency/Number of channels (20MHz):	5180-5240MHz (4 Channels); U-NII-2A: 5260-5320MHz (4 Channels); U-NII-2C: 5500-5700MHz (11 Channels); U-NII-3: 5745-5825MHz (5 Channels)
Operation Frequency/Number of channels/(40MHz):	5190-5230MHz (2 Channels); U-NII-2A: 5270-5310MHz (2 Channels); U-NII-2C: 5510-5670MHz (5 Channels); U-NII-3: 5755-5795MHz (2 Channels)
Modulation Type:	OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM)
Channel Spacing:	802.11a/n 20: 20MHz; 802.11n 40: 40MHz;
DFS Function:	Slave without Radar detection
TPC Function:	Support TPC function
Antenna Type:	Ceramic Antenna
Antenna Gain:	2.6dBi

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
--	--	--	--
The EUT has been tested as an independent unit.			



4.3 Measurement Uncertainty

Test Item	Measurement Uncertainty
Radiated Emissions (Above 1GHz)	$\pm 4.6\text{dB}$ (1-18GHz); $\pm 4.8\text{dB}$ (18-40GHz)
Radiated Emissions which fall in the restricted bands	$\pm 6.0\text{dB}$ (below 1GHz); $\pm 4.6\text{dB}$ (above 1GHz);

Remark:

The U_{lab} (lab Uncertainty) is less than $U_{\text{CISPR/ETSI}}$ (CISPR/ETSI Uncertainty), so the test results

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240200054302

Page: 7 of 158

4.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.6 Deviation from Standards

None

4.7 Abnormalities from Standard Conditions

None



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Radiated Emissions (Above 1GHz)					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2023-04-01	2026-03-31
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2023-09-19	2024-09-18
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2023-07-07	2024-07-06
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2022-08-10	2024-08-09
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2023-03-20	2024-03-19

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
3m Fully-Anechoic Chamber	AUDIX	N/A	SEM001-02	2023-04-01	2026-03-31
Signal Analyzer	Rohde & Schwarz	FSV40	SEM008-04	2023-03-20	2024-03-19
Horn Antenna	Rohde&Schwarz	HF907	SEM003-07	2023-07-23	2025-07-22
Microwave system amplifier	Agilent	83017A	SEM005-25	2023-09-19	2024-09-18
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2023-07-07	2024-07-06

General used equipment					
Equipment	Manufacturer	Model No.	Inventory No.	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	deli	8838	SEM002-32	2023-07-28	2024-07-27
Humidity/ Temperature Indicator	deli	8838	SEM002-33	2023-07-28	2024-07-27
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2023-03-23	2024-03-22



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch Laboratory
 No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
 中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Technical Requirement

6.1 Antenna Requirement

6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

6.1.2 Conclusion

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.6dBi

Antenna location: Refer to internal photos



7 Radio Spectrum Matter Test Results

7.1 Radiated Emissions (Above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
Above 1GHz	500	3
*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz. (4) For transmitters operating in the 5.725-5.85 GHz band: (i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge. Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.		

7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar



7.1.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode (U-NII-1) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	09	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.

7.1.3 Test Setup Diagram



7.1.4 Measurement Procedure and Data


- a. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 18GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
3. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.
4. The disturbance above 18GHz were very low and the harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
5. For devices with multiple operating modes, measurements on the middle channel is used to determine the worst-case mode(s). Only the worst case mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum) is recorded in the test report.



Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	3.53	24.12	38.33	41.84	31.16	74.00	-42.84	peak
2	1516.210	4.08	26.86	38.39	40.30	32.85	74.00	-41.15	peak
3	4379.699	7.04	34.64	35.81	37.48	43.35	74.00	-30.65	peak
4	8738.852	11.47	36.90	37.35	38.03	49.05	68.20	-19.15	peak
5	10360.000	12.73	37.10	37.54	39.32	51.61	68.20	-16.59	peak
6	15540.000	14.23	41.10	37.23	35.14	53.24	74.00	-20.76	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.65	24.94	38.35	40.57	30.81	74.00	-43.19	peak
2	1520.598	4.09	26.88	38.39	39.81	32.39	74.00	-41.61	peak
3	4430.628	7.08	34.43	35.77	37.60	43.34	68.20	-24.86	peak
4	8764.146	11.51	36.96	37.37	38.39	49.49	68.20	-18.71	peak
5	10360.000	12.73	37.10	37.54	38.43	50.72	68.20	-17.48	peak
6	15540.000	14.23	41.10	37.23	34.18	52.28	74.00	-21.72	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5200 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	41.16	31.51	68.20	-36.69	peak
2	1653.550	4.27	26.29	38.41	40.09	32.24	68.20	-35.96	peak
3	4405.090	7.06	34.74	35.79	37.18	43.19	68.20	-25.01	peak
4	8688.480	11.38	36.90	37.30	38.27	49.25	68.20	-18.95	peak
5	10400.000	12.74	37.10	37.56	38.48	50.76	68.20	-17.44	peak
6	15600.000	14.25	41.10	37.26	34.72	52.81	74.00	-21.19	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5200 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	3.53	24.12	38.33	41.37	30.69	74.00	-43.31	peak
2	1542.733	4.12	26.97	38.39	40.27	32.97	74.00	-41.03	peak
3	4329.354	7.01	34.23	35.85	38.16	43.55	74.00	-30.45	peak
4	8814.957	11.60	37.13	37.42	38.76	50.07	68.20	-18.13	peak
5	10400.000	12.74	37.10	37.56	38.65	50.93	68.20	-17.27	peak
6	15600.000	14.25	41.10	37.26	34.75	52.84	74.00	-21.16	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5240 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	3.75	24.82	38.36	40.75	30.96	68.20	-37.24	peak
2	1516.210	4.08	26.86	38.39	39.63	32.18	74.00	-41.82	peak
3	4430.628	7.08	34.43	35.77	37.94	43.68	68.20	-24.52	peak
4	8440.945	10.93	36.62	37.04	38.61	49.12	74.00	-24.88	peak
5	10480.000	12.76	37.26	37.60	38.15	50.57	68.20	-17.63	peak
6	15720.000	14.29	41.22	37.31	34.48	52.68	74.00	-21.32	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1148.823	3.49	23.90	38.33	42.12	31.18	74.00	-42.82	peak
2	1551.677	4.13	26.99	38.40	39.77	32.49	74.00	-41.51	peak
3	4304.400	6.99	34.04	35.87	38.36	43.52	74.00	-30.48	peak
4	8343.918	10.75	36.70	36.94	38.64	49.15	74.00	-24.85	peak
5	10480.000	12.76	37.26	37.60	38.52	50.94	68.20	-17.26	peak
6	15720.000	14.29	41.22	37.31	34.48	52.68	74.00	-21.32	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	3.68	25.06	38.35	40.30	30.69	68.20	-37.51	peak
2	1516.210	4.08	26.86	38.39	39.74	32.29	74.00	-41.71	peak
3	4443.453	7.09	34.28	35.77	37.16	42.76	68.20	-25.44	peak
4	7519.349	9.55	36.10	36.10	39.56	49.11	74.00	-24.89	peak
5	10360.000	12.73	37.10	37.54	37.66	49.95	68.20	-18.25	peak
6	15540.000	14.23	41.10	37.23	34.44	52.54	74.00	-21.46	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	41.27	31.62	68.20	-36.58	peak
2	1525.000	4.10	26.90	38.39	39.72	32.33	74.00	-41.67	peak
3	4417.841	7.07	34.59	35.78	37.16	43.04	68.20	-25.16	peak
4	8013.020	10.13	36.40	36.57	39.21	49.17	68.20	-19.03	peak
5	10360.000	12.73	37.10	37.54	38.74	51.03	68.20	-17.17	peak
6	15540.000	14.23	41.10	37.23	35.01	53.11	74.00	-20.89	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5200 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1155.483	3.50	23.95	38.33	41.25	30.37	74.00	-43.63	peak
2	1583.392	4.18	26.87	38.40	40.21	32.86	74.00	-41.14	peak
3	4392.376	7.05	34.74	35.80	36.89	42.88	74.00	-31.12	peak
4	8713.630	11.42	36.90	37.32	38.07	49.07	68.20	-19.13	peak
5	10400.000	12.74	37.10	37.56	38.73	51.01	68.20	-17.19	peak
6	15600.000	14.25	41.10	37.26	34.61	52.70	74.00	-21.30	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5200 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	3.64	24.89	38.35	40.42	30.60	74.00	-43.40	peak
2	1556.169	4.14	26.98	38.40	40.76	33.48	74.00	-40.52	peak
3	4417.841	7.07	34.59	35.78	37.46	43.34	68.20	-24.86	peak
4	8713.630	11.42	36.90	37.32	37.98	48.98	68.20	-19.22	peak
5	10400.000	12.74	37.10	37.56	38.20	50.48	68.20	-17.72	peak
6	15600.000	14.25	41.10	37.26	34.63	52.72	74.00	-21.28	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5240 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.67	25.09	38.35	40.38	30.79	68.20	-37.41	peak
2	1507.470	4.07	26.83	38.39	41.43	33.94	74.00	-40.06	peak
3	4367.058	7.04	34.54	35.82	37.32	43.08	74.00	-30.92	peak
4	8638.399	11.29	36.90	37.24	38.90	49.85	68.20	-18.35	peak
5	10480.000	12.76	37.26	37.60	38.92	51.34	68.20	-16.86	peak
6	15720.000	14.29	41.22	37.31	34.90	53.10	74.00	-20.90	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	3.63	24.79	38.34	41.20	31.28	74.00	-42.72	peak
2	1477.276	4.03	26.16	38.38	41.30	33.11	74.00	-40.89	peak
3	4354.454	7.03	34.44	35.83	37.44	43.08	74.00	-30.92	peak
4	8764.146	11.51	36.96	37.37	38.40	49.50	68.20	-18.70	peak
5	10480.000	12.76	37.26	37.60	38.72	51.14	68.20	-17.06	peak
6	15720.000	14.29	41.22	37.31	34.12	52.32	74.00	-21.68	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5190 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	3.64	24.89	38.35	40.42	30.60	74.00	-43.40	peak
2	1525.000	4.10	26.90	38.39	39.72	32.33	74.00	-41.67	peak
3	4405.090	7.06	34.74	35.79	37.32	43.33	68.20	-24.87	peak
4	7497.646	9.53	36.10	36.08	39.64	49.19	74.00	-24.81	peak
5	10380.000	12.74	37.10	37.55	37.82	50.11	68.20	-18.09	peak
6	15570.000	14.24	41.10	37.25	34.51	52.60	74.00	-21.40	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5190 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.64	30.99	68.20	-37.21	peak
2	1569.721	4.16	26.92	38.40	39.49	32.17	74.00	-41.83	peak
3	4405.090	7.06	34.74	35.79	37.94	43.95	68.20	-24.25	peak
4	8764.146	11.51	36.96	37.37	37.96	49.06	68.20	-19.14	peak
5	10380.000	12.74	37.10	37.55	38.36	50.65	68.20	-17.55	peak
6	15570.000	14.24	41.10	37.25	35.01	53.10	74.00	-20.90	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5230 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1285.904	3.73	24.88	38.35	41.03	31.29	68.20	-36.91	peak
2	1520.598	4.09	26.88	38.39	39.64	32.22	74.00	-41.78	peak
3	4379.699	7.04	34.64	35.81	36.95	42.82	74.00	-31.18	peak
4	8764.146	11.51	36.96	37.37	39.04	50.14	68.20	-18.06	peak
5	10460.000	12.76	37.22	37.59	39.01	51.40	68.20	-16.80	peak
6	15690.000	14.28	41.19	37.30	35.06	53.23	74.00	-20.77	peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5230 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1103.264	3.40	23.71	38.32	42.25	31.04	74.00	-42.96	peak
2	1583.392	4.18	26.87	38.40	39.72	32.37	74.00	-41.63	peak
3	4430.628	7.08	34.43	35.77	37.91	43.65	68.20	-24.55	peak
4	8764.146	11.51	36.96	37.37	38.94	50.04	68.20	-18.16	peak
5	10460.000	12.76	37.22	37.59	38.09	50.48	68.20	-17.72	peak
6	15690.000	14.28	41.19	37.30	33.96	52.13	74.00	-21.87	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.65	24.94	38.35	40.72	30.96	74.00	-43.04	peak
2	1520.598	4.09	26.88	38.39	40.54	33.12	74.00	-40.88	peak
3	4417.841	7.07	34.59	35.78	36.98	42.86	68.20	-25.34	peak
4	7989.893	10.09	36.40	36.55	40.34	50.28	68.20	-17.92	peak
5	10520.000	12.77	37.30	37.62	38.00	50.45	68.20	-17.75	peak
6	15780.000	14.31	41.28	37.33	34.39	52.65	74.00	-21.35	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5260 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.67	25.09	38.35	40.86	31.27	68.20	-36.93	peak
2	1583.392	4.18	26.87	38.40	40.26	32.91	74.00	-41.09	peak
3	4405.090	7.06	34.74	35.79	37.32	43.33	68.20	-24.87	peak
4	8392.292	10.84	36.70	36.99	38.95	49.50	74.00	-24.50	peak
5	10520.000	12.77	37.30	37.62	39.03	51.48	68.20	-16.72	peak
6	15780.000	14.31	41.28	37.33	34.39	52.65	74.00	-21.35	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5300 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1249.269	3.67	25.09	38.35	40.98	31.39	68.20	-36.81	peak
2	1592.571	4.19	26.83	38.40	40.10	32.72	74.00	-41.28	peak
3	4405.090	7.06	34.74	35.79	38.00	44.01	68.20	-24.19	peak
4	8082.804	10.26	36.47	36.65	40.24	50.32	74.00	-23.68	peak
5	10600.000	12.80	37.30	37.66	37.56	50.00	68.20	-18.20	peak
6	15900.000	14.35	41.40	37.38	34.47	52.84	74.00	-21.16	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5300 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1162.182	3.51	24.02	38.33	41.48	30.68	74.00	-43.32	peak
2	1525.000	4.10	26.90	38.39	40.13	32.74	74.00	-41.26	peak
3	4367.058	7.04	34.54	35.82	37.07	42.83	74.00	-31.17	peak
4	8764.146	11.51	36.96	37.37	39.18	50.28	68.20	-17.92	peak
5	10600.000	12.80	37.30	37.66	38.63	51.07	68.20	-17.13	peak
6	15900.000	14.35	41.40	37.38	34.26	52.63	74.00	-21.37	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 TX RSE
Note : 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	41.86	32.21	68.20	-35.99	peak
2	1556.169	4.14	26.98	38.40	39.92	32.64	74.00	-41.36	peak
3	4443.453	7.09	34.28	35.77	37.51	43.11	68.20	-25.09	peak
4 p	8688.480	11.38	36.90	37.30	39.36	50.34	68.20	-17.86	peak
5	10640.000	12.81	37.22	37.68	38.07	50.42	74.00	-23.58	peak
6	15960.000	14.37	41.52	37.40	34.50	52.99	74.00	-21.01	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5320 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1220.714	3.62	24.69	38.34	41.49	31.46	74.00	-42.54	peak
2	1620.431	4.23	26.60	38.40	40.53	32.96	74.00	-41.04	peak
3	4405.090	7.06	34.74	35.79	36.93	42.94	68.20	-25.26	peak
4 p	8013.020	10.13	36.40	36.57	39.71	49.67	68.20	-18.53	peak
5	10640.000	12.81	37.22	37.68	38.75	51.10	74.00	-22.90	peak
6	15960.000	14.37	41.52	37.40	34.15	52.64	74.00	-21.36	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 TX RSE
Note : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1155.483	3.50	23.95	38.33	41.32	30.44	74.00	-43.56	peak
2	1547.199	4.13	26.99	38.39	40.19	32.92	74.00	-41.08	peak
3	4367.058	7.04	34.54	35.82	38.46	44.22	74.00	-29.78	peak
4	8106.200	10.30	36.50	36.68	40.19	50.31	74.00	-23.69	peak
5	10520.000	12.77	37.30	37.62	38.33	50.78	68.20	-17.42	peak
6	15780.000	14.31	41.28	37.33	34.33	52.59	74.00	-21.41	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5260 TX RSE
 Note : 5G WIFI 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1103.264	3.40	23.71	38.32	42.80	31.59	74.00	-42.41	peak
2	1587.975	4.18	26.85	38.40	40.40	33.03	74.00	-40.97	peak
3	4405.090	7.06	34.74	35.79	37.46	43.47	68.20	-24.73	peak
4	8688.480	11.38	36.90	37.30	38.61	49.59	68.20	-18.61	peak
5	10520.000	12.77	37.30	37.62	38.22	50.67	68.20	-17.53	peak
6	15780.000	14.31	41.28	37.33	34.26	52.52	74.00	-21.48	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5300 TX RSE
 Note : 5G WIFI 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.71	24.97	38.35	40.54	30.87	68.20	-37.33	peak
2	1507.470	4.07	26.83	38.39	40.91	33.42	74.00	-40.58	peak
3	4405.090	7.06	34.74	35.79	37.27	43.28	68.20	-24.92	peak
4	8713.630	11.42	36.90	37.32	38.94	49.94	68.20	-18.26	peak
5	10600.000	12.80	37.30	37.66	37.89	50.33	68.20	-17.87	peak
6	15900.000	14.35	41.40	37.38	33.84	52.21	74.00	-21.79	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5300 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.69	25.04	38.35	40.61	30.99	68.20	-37.21	peak
2	1587.975	4.18	26.85	38.40	40.58	33.21	74.00	-40.79	peak
3	4392.376	7.05	34.74	35.80	37.32	43.31	74.00	-30.69	peak
4	8713.630	11.42	36.90	37.32	38.80	49.80	68.20	-18.40	peak
5	10600.000	12.80	37.30	37.66	38.73	51.17	68.20	-17.03	peak
6	15900.000	14.35	41.40	37.38	34.53	52.90	74.00	-21.10	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1285.904	3.73	24.88	38.35	40.63	30.89	68.20	-37.31	peak
2	1525.000	4.10	26.90	38.39	39.36	31.97	74.00	-42.03	peak
3	4392.376	7.05	34.74	35.80	37.27	43.26	74.00	-30.74	peak
4 p	8688.480	11.38	36.90	37.30	39.04	50.02	68.20	-18.18	peak
5	10640.000	12.81	37.22	37.68	37.53	49.88	74.00	-24.12	peak
6	15960.000	14.37	41.52	37.40	33.88	52.37	74.00	-21.63	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5320 TX RSE
Note : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.32	30.67	68.20	-37.53	peak
2	1611.091	4.22	26.69	38.40	39.50	32.01	74.00	-41.99	peak
3	4341.886	7.02	34.34	35.84	37.65	43.17	74.00	-30.83	peak
4 p	8688.480	11.38	36.90	37.30	39.10	50.08	68.20	-18.12	peak
5	10640.000	12.81	37.22	37.68	37.66	50.01	74.00	-23.99	peak
6	15960.000	14.37	41.52	37.40	34.12	52.61	74.00	-21.39	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5270 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1142.201	3.48	23.87	38.33	42.22	31.24	74.00	-42.76	peak
2	1490.142	4.05	26.52	38.39	41.21	33.39	74.00	-40.61	peak
3	4417.841	7.07	34.59	35.78	36.86	42.74	68.20	-25.46	peak
4	8663.404	11.33	36.90	37.27	38.73	49.69	68.20	-18.51	peak
5	10540.000	12.78	37.30	37.63	37.46	49.91	68.20	-18.29	peak
6	15810.000	14.32	41.31	37.34	34.61	52.90	74.00	-21.10	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5270 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1271.123	3.71	24.97	38.35	40.33	30.66	68.20	-37.54	peak
2	1547.199	4.13	26.99	38.39	39.79	32.52	74.00	-41.48	peak
3	4354.454	7.03	34.44	35.83	37.45	43.09	74.00	-30.91	peak
4 p	8814.957	11.60	37.13	37.42	38.44	49.75	68.20	-18.45	peak
5	10540.000	12.78	37.30	37.63	37.20	49.65	68.20	-18.55	peak
6	15810.000	14.32	41.31	37.34	34.54	52.83	74.00	-21.17	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5310 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1142.201	3.48	23.87	38.33	42.09	31.11	74.00	-42.89	peak
2	1529.414	4.10	26.92	38.39	39.90	32.53	74.00	-41.47	peak
3	4379.699	7.04	34.64	35.81	37.06	42.93	74.00	-31.07	peak
4 p	8663.404	11.33	36.90	37.27	39.30	50.26	68.20	-17.94	peak
5	10620.000	12.80	37.26	37.67	38.91	51.30	74.00	-22.70	peak
6	15930.000	14.36	41.46	37.39	34.61	53.04	74.00	-20.96	peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5310 TX RSE
 Note : 5G WIFI 11N40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1129.072	3.45	23.82	38.33	41.80	30.74	74.00	-43.26	peak
2	1574.265	4.17	26.90	38.40	39.70	32.37	74.00	-41.63	peak
3	4304.400	6.99	34.04	35.87	38.16	43.32	74.00	-30.68	peak
4 p	8713.630	11.42	36.90	37.32	38.91	49.91	68.20	-18.29	peak
5	10620.000	12.80	37.26	37.67	38.32	50.71	74.00	-23.29	peak
6	15930.000	14.36	41.46	37.39	34.72	53.15	74.00	-20.85	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5500 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1106.457	3.41	23.73	38.32	42.46	31.28	74.00	-42.72	peak
2	1556.169	4.14	26.98	38.40	39.75	32.47	74.00	-41.53	peak
3	4405.090	7.06	34.74	35.79	37.84	43.85	68.20	-24.35	peak
4	8713.630	11.42	36.90	37.32	38.77	49.77	68.20	-18.43	peak
5	11000.000	12.90	37.50	37.84	38.68	51.24	74.00	-22.76	peak
6	16500.000	14.47	42.10	37.47	33.91	53.01	68.20	-15.19	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5500 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1238.483	3.65	24.94	38.35	40.52	30.76	74.00	-43.24	peak
2	1507.470	4.07	26.83	38.39	40.57	33.08	74.00	-40.92	peak
3	4367.058	7.04	34.54	35.82	37.23	42.99	74.00	-31.01	peak
4	8814.957	11.60	37.13	37.42	37.99	49.30	68.20	-18.90	peak
5	11000.000	12.90	37.50	37.84	37.45	50.01	74.00	-23.99	peak
6	16500.000	14.47	42.10	37.47	33.41	52.51	68.20	-15.69	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5580 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1234.909	3.64	24.89	38.35	41.08	31.26	74.00	-42.74	peak
2	1511.833	4.08	26.85	38.39	40.01	32.55	74.00	-41.45	peak
3	4341.886	7.02	34.34	35.84	37.39	42.91	74.00	-31.09	peak
4	8789.516	11.55	37.06	37.40	37.62	48.83	68.20	-19.37	peak
5	11160.000	12.93	37.62	37.79	38.37	51.13	74.00	-22.87	peak
6	p16740.000	14.51	42.78	37.49	33.10	52.90	68.20	-15.30	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5580 TX RSE
 Note : 5G WIFI 11A


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1199.726	3.58	24.40	38.34	41.00	30.64	74.00	-43.36	peak
2	1587.975	4.18	26.85	38.40	39.98	32.61	74.00	-41.39	peak
3	4443.453	7.09	34.28	35.77	37.46	43.06	68.20	-25.14	peak
4	8638.399	11.29	36.90	37.24	38.46	49.41	68.20	-18.79	peak
5	11160.000	12.93	37.62	37.79	37.42	50.18	74.00	-23.82	peak
6	p16740.000	14.51	42.78	37.49	33.56	53.36	68.20	-14.84	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5700 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.19	30.54	68.20	-37.66	peak
2	1485.841	4.04	26.40	38.39	40.37	32.42	74.00	-41.58	peak
3	4405.090	7.06	34.74	35.79	37.09	43.10	68.20	-25.10	peak
4	8638.399	11.29	36.90	37.24	39.00	49.95	68.20	-18.25	peak
5	11400.000	12.98	37.70	37.72	37.94	50.90	74.00	-23.10	peak
6	17100.000	14.62	43.10	37.53	32.51	52.70	68.20	-15.50	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5700 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.12	30.47	68.20	-37.73	peak
2	1560.673	4.15	26.96	38.40	39.80	32.51	74.00	-41.49	peak
3	4392.376	7.05	34.74	35.80	37.48	43.47	74.00	-30.53	peak
4	8866.062	11.69	37.20	37.48	38.44	49.85	68.20	-18.35	peak
5	11400.000	12.98	37.70	37.72	39.01	51.97	74.00	-22.03	peak
6	p17100.000	14.62	43.10	37.53	32.13	52.32	68.20	-15.88	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5500 TX RSE
Note : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1227.791	3.63	24.79	38.34	40.59	30.67	74.00	-43.33	peak
2	1592.571	4.19	26.83	38.40	40.08	32.70	74.00	-41.30	peak
3	4405.090	7.06	34.74	35.79	36.63	42.64	68.20	-25.56	peak
4	8688.480	11.38	36.90	37.30	39.52	50.50	68.20	-17.70	peak
5	11000.000	12.90	37.50	37.84	38.13	50.69	74.00	-23.31	peak
6	p16500.000	14.47	42.10	37.47	33.97	53.07	68.20	-15.13	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5500 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1203.199	3.59	24.44	38.34	41.34	31.03	74.00	-42.97	peak
2	1565.191	4.15	26.94	38.40	40.33	33.02	74.00	-40.98	peak
3	4417.841	7.07	34.59	35.78	37.69	43.57	68.20	-24.63	peak
4	8663.404	11.33	36.90	37.27	38.38	49.34	68.20	-18.86	peak
5	11000.000	12.90	37.50	37.84	38.25	50.81	74.00	-23.19	peak
6	p16500.000	14.47	42.10	37.47	33.44	52.54	68.20	-15.66	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5580 TX RSE
 Note : 5G WIFI 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1179.100	3.54	24.19	38.34	41.87	31.26	74.00	-42.74	peak
2	1525.000	4.10	26.90	38.39	39.70	32.31	74.00	-41.69	peak
3	4341.886	7.02	34.34	35.84	37.71	43.23	74.00	-30.77	peak
4	8663.404	11.33	36.90	37.27	38.84	49.80	68.20	-18.40	peak
5	11160.000	12.93	37.62	37.79	37.55	50.31	74.00	-23.69	peak
6	16740.000	14.51	42.78	37.49	32.99	52.79	68.20	-15.41	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5580 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.49	30.84	68.20	-37.36	peak
2	1547.199	4.13	26.99	38.39	39.62	32.35	74.00	-41.65	peak
3	4392.376	7.05	34.74	35.80	37.79	43.78	74.00	-30.22	peak
4	8663.404	11.33	36.90	37.27	38.58	49.54	68.20	-18.66	peak
5	11160.000	12.93	37.62	37.79	37.24	50.00	74.00	-24.00	peak
6	16740.000	14.51	42.78	37.49	32.82	52.62	68.20	-15.58	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5700 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1260.149	3.69	25.04	38.35	40.03	30.41	68.20	-37.79	peak
2	1511.833	4.08	26.85	38.39	40.60	33.14	74.00	-40.86	peak
3	4417.841	7.07	34.59	35.78	37.62	43.50	68.20	-24.70	peak
4	8764.146	11.51	36.96	37.37	39.69	50.79	68.20	-17.41	peak
5	11400.000	12.98	37.70	37.72	38.69	51.65	74.00	-22.35	peak
6	17100.000	14.62	43.10	37.53	32.50	52.69	68.20	-15.51	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5700 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.53	30.88	68.20	-37.32	peak
2	1574.265	4.17	26.90	38.40	40.60	33.27	74.00	-40.73	peak
3	4430.628	7.08	34.43	35.77	37.89	43.63	68.20	-24.57	peak
4	8663.404	11.33	36.90	37.27	38.64	49.60	68.20	-18.60	peak
5	11400.000	12.98	37.70	37.72	38.97	51.93	74.00	-22.07	peak
6	p17100.000	14.62	43.10	37.53	33.20	53.39	68.20	-14.81	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
 Condition: 3m HORIZONTAL
 Job No : 00543AT\00622AT
 Mode : 5510 TX RSE
 Note : 5G WIFI 11N40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1129.072	3.45	23.82	38.33	41.35	30.29	74.00	-43.71	peak
2	1503.119	4.07	26.81	38.39	40.83	33.32	74.00	-40.68	peak
3	4379.699	7.04	34.64	35.81	37.78	43.65	74.00	-30.35	peak
4	7966.832	10.06	36.40	36.53	39.66	49.59	68.20	-18.61	peak
5	11020.000	12.90	37.50	37.83	37.78	50.35	74.00	-23.65	peak
6	16530.000	14.48	42.16	37.47	33.48	52.65	68.20	-15.55	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5510 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1231.345	3.64	24.84	38.35	40.98	31.11	74.00	-42.89	peak
2	1583.392	4.18	26.87	38.40	39.83	32.48	74.00	-41.52	peak
3	4417.841	7.07	34.59	35.78	37.02	42.90	68.20	-25.30	peak
4	8082.804	10.26	36.47	36.65	40.18	50.26	74.00	-23.74	peak
5	11020.000	12.90	37.50	37.83	38.39	50.96	74.00	-23.04	peak
6	p16530.000	14.48	42.16	37.47	33.70	52.87	68.20	-15.33	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5670 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1168.920	3.53	24.09	38.33	40.93	30.22	74.00	-43.78	peak
2	1601.804	4.20	26.78	38.40	39.79	32.37	74.00	-41.63	peak
3	4443.453	7.09	34.28	35.77	37.51	43.11	68.20	-25.09	peak
4	8613.468	11.24	36.90	37.22	38.96	49.88	68.20	-18.32	peak
5	11100.000	12.92	37.50	37.81	37.94	50.55	74.00	-23.45	peak
6	p16650.000	14.50	42.50	37.48	33.59	53.11	68.20	-15.09	peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5670 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1172.303	3.53	24.12	38.33	41.56	30.88	74.00	-43.12	peak
2	1667.951	4.29	26.26	38.41	40.91	33.05	74.00	-40.95	peak
3	4430.628	7.08	34.43	35.77	37.33	43.07	68.20	-25.13	peak
4	8764.146	11.51	36.96	37.37	39.43	50.53	68.20	-17.67	peak
5	11100.000	12.92	37.50	37.81	38.57	51.18	74.00	-22.82	peak
6	p16650.000	14.50	42.50	37.48	33.42	52.94	68.20	-15.26	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5745 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	3.68	25.06	38.35	40.70	31.09	68.20	-37.11	peak
2	1560.673	4.15	26.96	38.40	40.69	33.40	74.00	-40.60	peak
3	4405.090	7.06	34.74	35.79	37.18	43.19	68.20	-25.01	peak
4	8713.630	11.42	36.90	37.32	38.51	49.51	68.20	-18.69	peak
5	11490.000	13.00	37.79	37.69	37.75	50.85	74.00	-23.15	peak
6	p17235.000	14.70	43.03	37.55	32.96	53.14	68.20	-15.06	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5745 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1158.828	3.51	23.99	38.33	42.15	31.32	74.00	-42.68	peak
2	1494.455	4.05	26.64	38.39	40.20	32.50	74.00	-41.50	peak
3	4405.090	7.06	34.74	35.79	37.80	43.81	68.20	-24.39	peak
4	8713.630	11.42	36.90	37.32	38.91	49.91	68.20	-18.29	peak
5	11490.000	13.00	37.79	37.69	37.90	51.00	74.00	-23.00	peak
6	p17235.000	14.70	43.03	37.55	32.52	52.70	68.20	-15.50	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5785 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1252.885	3.67	25.08	38.35	41.63	32.03	68.20	-36.17	peak
2	1583.392	4.18	26.87	38.40	39.44	32.09	74.00	-41.91	peak
3	4417.841	7.07	34.59	35.78	36.76	42.64	68.20	-25.56	peak
4	8465.379	10.97	36.63	37.06	39.37	49.91	74.00	-24.09	peak
5	11570.000	13.01	37.73	37.67	38.14	51.21	74.00	-22.79	peak
6	p17355.000	14.77	43.26	37.56	32.12	52.59	68.20	-15.61	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5785 TX RSE
 Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.74	24.86	38.36	40.63	30.87	68.20	-37.33	peak
2	1611.091	4.22	26.69	38.40	39.67	32.18	74.00	-41.82	peak
3	4417.841	7.07	34.59	35.78	37.24	43.12	68.20	-25.08	peak
4	7989.893	10.09	36.40	36.55	40.39	50.33	68.20	-17.87	peak
5	11570.000	13.01	37.73	37.67	38.60	51.67	74.00	-22.33	peak
6	17355.000	14.77	43.26	37.56	32.18	52.65	68.20	-15.55	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5825 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1293.359	3.74	24.84	38.36	40.12	30.34	68.20	-37.86	peak
2	1597.181	4.20	26.81	38.40	39.47	32.08	74.00	-41.92	peak
3	4367.058	7.04	34.54	35.82	37.57	43.33	74.00	-30.67	peak
4	8688.480	11.38	36.90	37.30	39.50	50.48	68.20	-17.72	peak
5	11650.000	13.03	37.80	37.65	37.79	50.97	74.00	-23.03	peak
6	p17475.000	14.84	43.40	37.58	32.22	52.88	68.20	-15.32	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5825 TX RSE
Note : 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.61	30.96	68.20	-37.24	peak
2	1547.199	4.13	26.99	38.39	39.76	32.49	74.00	-41.51	peak
3	4443.453	7.09	34.28	35.77	37.50	43.10	68.20	-25.10	peak
4	8638.399	11.29	36.90	37.24	39.67	50.62	68.20	-17.58	peak
5	11650.000	13.03	37.80	37.65	37.94	51.12	74.00	-22.88	peak
6	p17475.000	14.84	43.40	37.58	32.65	53.31	68.20	-14.89	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5745 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1274.802	3.71	24.95	38.35	40.60	30.91	68.20	-37.29	peak
2	1538.281	4.12	26.95	38.39	39.96	32.64	74.00	-41.36	peak
3	4392.376	7.05	34.74	35.80	37.48	43.47	74.00	-30.53	peak
4	8789.516	11.55	37.06	37.40	38.98	50.19	68.20	-18.01	peak
5	11490.000	13.00	37.79	37.69	37.63	50.73	74.00	-23.27	peak
6	p17235.000	14.70	43.03	37.55	32.16	52.34	68.20	-15.86	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5745 TX RSE
 Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1256.512	3.68	25.06	38.35	39.94	30.33	68.20	-37.87	peak
2	1606.441	4.21	26.74	38.40	40.35	32.90	74.00	-41.10	peak
3	4430.628	7.08	34.43	35.77	37.46	43.20	68.20	-25.00	peak
4	8713.630	11.42	36.90	37.32	38.92	49.92	68.20	-18.28	peak
5	11490.000	13.00	37.79	37.69	38.09	51.19	74.00	-22.81	peak
6	17235.000	14.70	43.03	37.55	32.55	52.73	68.20	-15.47	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5785 TX RSE
Note : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1220.714	3.62	24.69	38.34	40.71	30.68	74.00	-43.32	peak
2	1606.441	4.21	26.74	38.40	40.14	32.69	74.00	-41.31	peak
3	4341.886	7.02	34.34	35.84	36.90	42.42	74.00	-31.58	peak
4	8563.818	11.15	36.83	37.17	38.80	49.61	68.20	-18.59	peak
5	11570.000	13.01	37.73	37.67	37.87	50.94	74.00	-23.06	peak
6	17355.000	14.77	43.26	37.56	32.56	53.03	68.20	-15.17	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5785 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1252.885	3.67	25.08	38.35	40.18	30.58	68.20	-37.62	peak
2	1490.142	4.05	26.52	38.39	41.15	33.33	74.00	-40.67	peak
3	4316.859	7.00	34.13	35.86	38.64	43.91	74.00	-30.09	peak
4	8688.480	11.38	36.90	37.30	39.52	50.50	68.20	-17.70	peak
5	11570.000	13.01	37.73	37.67	38.65	51.72	74.00	-22.28	peak
6	p17355.000	14.77	43.26	37.56	32.19	52.66	68.20	-15.54	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5825 TX RSE
Note : 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1245.663	3.66	25.04	38.35	40.22	30.57	68.20	-37.63	peak
2	4417.841	7.07	34.59	35.78	36.97	42.85	68.20	-25.35	peak
3	7411.461	9.42	35.85	35.99	38.36	47.64	74.00	-26.36	peak
4	8840.473	11.64	37.18	37.45	39.04	50.41	68.20	-17.79	peak
5	11650.000	13.03	37.80	37.65	38.08	51.26	74.00	-22.74	peak
6	p17475.000	14.84	43.40	37.58	31.49	52.15	68.20	-16.05	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5825 TX RSE
Note : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1220.714	3.62	24.69	38.34	40.87	30.84	74.00	-43.16	peak
2	1547.199	4.13	26.99	38.39	40.46	33.19	74.00	-40.81	peak
3	4417.841	7.07	34.59	35.78	37.37	43.25	68.20	-24.95	peak
4	8840.473	11.64	37.18	37.45	38.62	49.99	68.20	-18.21	peak
5	11650.000	13.03	37.80	37.65	38.11	51.29	74.00	-22.71	peak
6	17475.000	14.84	43.40	37.58	32.20	52.86	68.20	-15.34	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5755 TX RSE
Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1297.103	3.75	24.82	38.36	40.82	31.03	68.20	-37.17	peak
2	1516.210	4.08	26.86	38.39	39.61	32.16	74.00	-41.84	peak
3	4417.841	7.07	34.59	35.78	37.83	43.71	68.20	-24.49	peak
4	8713.630	11.42	36.90	37.32	39.13	50.13	68.20	-18.07	peak
5	11510.000	13.00	37.79	37.69	38.60	51.70	74.00	-22.30	peak
6	p17265.000	14.72	43.06	37.55	33.10	53.33	68.20	-14.87	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5755 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1224.247	3.62	24.74	38.34	41.12	31.14	74.00	-42.86	peak
2	1547.199	4.13	26.99	38.39	40.11	32.84	74.00	-41.16	peak
3	4279.589	6.98	33.92	35.89	37.81	42.82	74.00	-31.18	peak
4	8663.404	11.33	36.90	37.27	39.00	49.96	68.20	-18.24	peak
5	11510.000	13.00	37.79	37.69	38.23	51.33	74.00	-22.67	peak
6	17265.000	14.72	43.06	37.55	32.47	52.70	68.20	-15.50	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5795 TX RSE
Note : 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1289.627	3.74	24.86	38.36	40.59	30.83	68.20	-37.37	peak
2	1520.598	4.09	26.88	38.39	40.53	33.11	74.00	-40.89	peak
3	4379.699	7.04	34.64	35.81	38.03	43.90	74.00	-30.10	peak
4	8814.957	11.60	37.13	37.42	38.80	50.11	68.20	-18.09	peak
5	11590.000	13.01	37.71	37.67	37.32	50.37	74.00	-23.63	peak
6	p17385.000	14.79	43.35	37.57	32.06	52.63	68.20	-15.57	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5795 TX RSE
 Note : 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1203.199	3.59	24.44	38.34	42.17	31.86	74.00	-42.14	peak
2	1611.091	4.22	26.69	38.40	40.13	32.64	74.00	-41.36	peak
3	4443.453	7.09	34.28	35.77	37.61	43.21	68.20	-24.99	peak
4	8866.062	11.69	37.20	37.48	38.62	50.03	68.20	-18.17	peak
5	11590.000	13.01	37.71	37.67	38.04	51.09	74.00	-22.91	peak
6	p17385.000	14.79	43.35	37.57	32.21	52.78	68.20	-15.42	peak



7.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & Subpart E 15.407(b)

Test Method: KDB 789033 D02 II G

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 23.5 °C

Humidity: 56.3 % RH


Atmospheric Pressure: 1020 mbar



7.2.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
Final test	06	TX mode (U-NII-1) Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	07	TX mode (U-NII-2A) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	08	TX mode (U-NII-2C) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.
Final test	09	TX mode (U-NII-3) _Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n 20/40, Only the data of worst case is recorded in the report.

7.2.3 Test Setup Diagram




7.2.4 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
 - f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
 - g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
 - h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
 - i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
 - j. Repeat above procedures until all frequencies measured was complete.
- Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor



Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5102.477	7.51	34.00	35.34	46.26	52.43	74.00	-21.57	peak
2	5149.980	7.55	33.90	35.31	44.47	50.61	74.00	-23.39	peak
3 p	5180.000	7.57	33.96	35.29	91.13	97.37	68.20	29.17	peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5104.756		7.51	33.99	35.33	34.16	40.33	54.00	-13.67 Average
2 5149.980		7.55	33.90	35.31	33.71	39.85	54.00	-14.15 Average
3 5180.000		7.57	33.96	35.29	82.45	88.69	-----	----- Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5105.053	7.51	33.99	35.33	45.95	52.12	74.00	-21.88 Peak
2	5149.980	7.55	33.90	35.31	44.47	50.61	74.00	-23.39 Peak
3 p	5180.000	7.57	33.96	35.29	90.81	97.05	68.20	28.85 Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5106.243	7.52	33.99	35.33	33.79	39.97	54.00	-14.03 Average
2 q	5149.980	7.55	33.90	35.31	33.97	40.11	54.00	-13.89 Average
3	5180.000	7.57	33.96	35.29	82.08	88.32	-----	----- Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5240.000	7.62	34.08	35.26	92.49	98.93	68.20	30.73 peak
2	5350.020	7.70	34.40	35.21	44.46	51.35	74.00	-22.65 peak
3	5357.447	7.71	34.43	35.20	45.04	51.98	74.00	-22.02 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5240.000	7.62	34.08	35.26	83.79	90.23	-----	----- Average
2	5350.020	7.70	34.40	35.21	33.18	40.07	54.00	-13.93 Average
3 q	5359.433	7.71	34.44	35.20	33.62	40.57	54.00	-13.43 Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5240.000	7.62	34.08	35.26	90.74	97.18	68.20	28.98	Peak
2 5350.020	7.70	34.40	35.21	44.20	51.09	74.00	-22.91	Peak
3 5360.000	7.71	34.44	35.20	44.81	51.76	74.00	-22.24	Peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240200054302

Page: 87 of 158

Test Mode: 06; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5240.000	7.62	34.08	35.26	82.42	88.86	-----	----- Average
2	5350.020	7.70	34.40	35.21	32.94	39.83	54.00	-14.17 Average
3 q	5353.479	7.71	34.41	35.21	33.55	40.46	54.00	-13.54 Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5123.724	7.53	33.95	35.32	46.57	52.73	74.00	-21.27	peak
2	5149.980	7.55	33.90	35.31	44.78	50.92	74.00	-23.08	peak
3 p	5180.000	7.57	33.96	35.29	89.49	95.73	68.20	27.53	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5100.892	7.51	34.00	35.34	34.11	40.28	54.00	-13.72	Average
2 5149.980	7.55	33.90	35.31	33.84	39.98	54.00	-14.02	Average
3 5180.000	7.57	33.96	35.29	81.20	87.44	-----	-----	Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5109.317	7.52	33.98	35.33	45.82	51.99	74.00	-22.01 Peak
2	5149.980	7.55	33.90	35.31	44.69	50.83	74.00	-23.17 Peak
3 p	5180.000	7.57	33.96	35.29	89.20	95.44	68.20	27.24 Peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5180 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5148.857		7.55	33.90	35.31	33.78	39.92	54.00	-14.08 Average
2 5149.980		7.55	33.90	35.31	33.44	39.58	54.00	-14.42 Average
3 5180.000		7.57	33.96	35.29	80.72	86.96	-----	----- Average



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 5240.000		7.62	34.08	35.26	91.45	97.89	68.20	29.69 peak
2 5350.020		7.70	34.40	35.21	44.53	51.42	74.00	-22.58 peak
3 5351.212		7.71	34.40	35.21	44.78	51.68	74.00	-22.32 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5240.000	7.62	34.08	35.26	83.20	89.64	-----	----- Average
2	5350.020	7.70	34.40	35.21	33.36	40.25	54.00	-13.75 Average
3 q	5351.495	7.71	34.41	35.21	33.64	40.55	54.00	-13.45 Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5240.000	7.62	34.08	35.26	90.10	96.54	68.20	28.34	Peak
2 5350.020	7.70	34.40	35.21	43.92	50.81	74.00	-23.19	Peak
3 5356.596	7.71	34.43	35.20	44.78	51.72	74.00	-22.28	Peak




SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR240200054302

Page: 95 of 158

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5240 Band edge
: 5G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5240.000	7.62	34.08	35.26	82.01	88.45	-----	-----	Average
2	5350.020	7.70	34.40	35.21	33.10	39.99	54.00	-14.01	Average
3 q	5357.873	7.71	34.43	35.20	33.26	40.20	54.00	-13.80	Average




SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Calibration Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5190 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5114.253	7.52	33.97	35.33	45.58	51.74	74.00	-22.26 peak
2	5149.980	7.55	33.90	35.31	45.27	51.41	74.00	-22.59 peak
3 p	5190.000	7.58	33.98	35.29	88.60	94.87	68.20	26.67 peak



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5190 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5149.461		7.55	33.90	35.31	34.56	40.70	54.00	-13.30 Average
2 5149.980		7.55	33.90	35.31	34.34	40.48	54.00	-13.52 Average
3 5190.000		7.58	33.98	35.29	79.08	85.35	-----	----- Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5190 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5129.262	7.53	33.94	35.32	46.09	52.24	74.00	-21.76 Peak
2	5149.980	7.55	33.90	35.31	44.81	50.95	74.00	-23.05 Peak
3 p	5190.000	7.58	33.98	35.29	86.41	92.68	68.20	24.48 Peak



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5190 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5145.391	7.55	33.91	35.31	34.07	40.22	54.00	-13.78	Average
2 5149.980	7.55	33.90	35.31	33.89	40.03	54.00	-13.97	Average
3 5190.000	7.58	33.98	35.29	77.88	84.15	-----	-----	Average



Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5230 Band edge
: 5G WIFI 11N40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dB	
1 p	5230.000	7.61	34.06	35.27	89.07	95.47	68.20	27.27 peak
2	5350.020	7.70	34.40	35.21	43.77	50.66	74.00	-23.34 peak
3	5351.884	7.71	34.41	35.21	45.36	52.27	74.00	-21.73 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5230 Band edge
: 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5230.000	7.61	34.06	35.27	80.01	86.41	-----	-----	Average
2	5350.020	7.70	34.40	35.21	33.20	40.09	54.00	-13.91	Average
3 q	5355.778	7.71	34.42	35.21	33.43	40.35	54.00	-13.65	Average



Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5230 Band edge
: 5G WIFI 11N40


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5230.000	7.61	34.06	35.27	88.50	94.90	68.20	26.70 Peak
2	5350.020	7.70	34.40	35.21	43.49	50.38	74.00	-23.62 Peak
3	5352.371	7.71	34.41	35.21	45.39	52.30	74.00	-21.70 Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 06; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5230 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5230.000	7.61	34.06	35.27	79.07	85.47	-----	-----	Average
2 5350.020	7.70	34.40	35.21	32.90	39.79	54.00	-14.21	Average
3 q 5356.590	7.71	34.43	35.20	33.35	40.29	54.00	-13.71	Average



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5112.575	7.52	33.97	35.33	45.96	52.12	74.00	-21.88	peak
2	5149.980	7.55	33.90	35.31	44.03	50.17	74.00	-23.83	peak
3 p	5260.000	7.64	34.12	35.25	93.34	99.85	68.20	31.65	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5109.916	7.52	33.98	35.33	33.75	39.92	54.00	-14.08	Average
2 5149.980	7.55	33.90	35.31	33.30	39.44	54.00	-14.56	Average
3 5260.000	7.64	34.12	35.25	83.78	90.29	-----	-----	Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11A

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5106.549	7.52	33.99	35.33	45.82	52.00	74.00	-22.00	Peak
2	5149.980	7.55	33.90	35.31	44.47	50.61	74.00	-23.39	Peak
3 p	5260.000	7.64	34.12	35.25	92.02	98.53	68.20	30.33	Peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5119.496	7.53	33.96	35.33	33.65	39.81	54.00	-14.19	Average
2 5149.980	7.55	33.90	35.31	33.20	39.34	54.00	-14.66	Average
3 5260.000	7.64	34.12	35.25	82.73	89.24	-----	-----	Average



Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 5320.000		7.68	34.28	35.22	90.80	97.54	68.20	29.34 peak
2 5350.020		7.70	34.40	35.21	44.76	51.65	74.00	-22.35 peak
3 5375.427		7.72	34.50	35.20	46.01	53.03	74.00	-20.97 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5320.000	7.68	34.28	35.22	82.47	89.21	-----	-----	Average
2 5350.020	7.70	34.40	35.21	33.60	40.49	54.00	-13.51	Average
3 q 5399.395	7.74	34.60	35.18	33.60	40.76	54.00	-13.24	Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11A


	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000	7.68	34.28	35.22	90.29	97.03	68.20	28.83	Peak
2 5350.020	7.70	34.40	35.21	45.15	52.04	74.00	-21.96	Peak
3 5352.967	7.71	34.41	35.21	46.06	52.97	74.00	-21.03	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 5320.000	7.68	34.28	35.22	81.92	88.66	-----	-----	Average
2 5350.020	7.70	34.40	35.21	33.55	40.44	54.00	-13.56	Average
3 q 5400.000	7.74	34.60	35.18	33.61	40.77	54.00	-13.23	Average



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5127.315	7.53	33.95	35.32	45.90	52.06	74.00	-21.94	peak
2	5149.980	7.55	33.90	35.31	44.35	50.49	74.00	-23.51	peak
3 p	5260.000	7.64	34.12	35.25	92.26	98.77	68.20	30.57	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5124.648		7.53	33.95	35.32	33.67	39.83	54.00	-14.17	Average
2 5149.980		7.55	33.90	35.31	33.19	39.33	54.00	-14.67	Average
3 5260.000		7.64	34.12	35.25	83.94	90.45	-----	-----	Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5260 Band edge
 : 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5101.416	7.51	34.00	35.34	45.51	51.68	74.00	-22.32	Peak
2	5149.980	7.55	33.90	35.31	44.21	50.35	74.00	-23.65	Peak
3 p	5260.000	7.64	34.12	35.25	90.39	96.90	68.20	28.70	Peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5260 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5104.247		7.51	33.99	35.33	33.50	39.67	54.00	-14.33 Average
2 5149.980		7.55	33.90	35.31	33.19	39.33	54.00	-14.67 Average
3 5260.000		7.64	34.12	35.25	82.42	88.93	-----	----- Average



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000	7.68	34.28	35.22	92.10	98.84	68.20	30.64	peak
2 5350.020	7.70	34.40	35.21	44.36	51.25	74.00	-22.75	peak
3 5361.679	7.71	34.45	35.20	45.99	52.95	74.00	-21.05	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5320.000	7.68	34.28	35.22	82.58	89.32	-----	-----	Average
2	5350.020	7.70	34.40	35.21	33.62	40.51	54.00	-13.49	Average
3 q	5399.798	7.74	34.60	35.18	33.65	40.81	54.00	-13.19	Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5320 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5320.000		7.68	34.28	35.22	90.38	97.12	68.20	28.92	Peak
2 5350.020		7.70	34.40	35.21	44.09	50.98	74.00	-23.02	Peak
3 5389.009		7.73	34.56	35.19	45.68	52.78	74.00	-21.22	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
 Condition: 3m VERTICAL
 Job No : 00543AT\00622AT
 Mode : 5320 Band edge
 : 5G WIFI 11N20


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5320.000	7.68	34.28	35.22	81.84	88.58	-----	-----	Average
2	5350.020	7.70	34.40	35.21	33.53	40.42	54.00	-13.58	Average
3 q	5399.596	7.74	34.60	35.18	33.69	40.85	54.00	-13.15	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5270 Band edge
: 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5119.458	7.53	33.96	35.33	45.39	51.55	74.00	-22.45	peak
2	5149.980	7.55	33.90	35.31	44.26	50.40	74.00	-23.60	peak
3 p	5270.000	7.64	34.14	35.25	89.33	95.86	68.20	27.66	peak



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5270 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5108.443	7.52	33.98	35.33	33.65	39.82	54.00	-14.18	Average
2 5149.980	7.55	33.90	35.31	33.30	39.44	54.00	-14.56	Average
3 5270.000	7.64	34.14	35.25	80.82	87.35	-----	-----	Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5270 Band edge
: 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5126.750	7.53	33.95	35.32	45.44	51.60	74.00	-22.40	Peak
2	5149.980	7.55	33.90	35.31	44.39	50.53	74.00	-23.47	Peak
3 p	5270.000	7.64	34.14	35.25	88.82	95.35	68.20	27.15	Peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5270 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5112.374		7.52	33.98	35.33	33.73	39.90	54.00	-14.10 Average
2 5149.980		7.55	33.90	35.31	33.26	39.40	54.00	-14.60 Average
3 5270.000		7.64	34.14	35.25	79.23	85.76	-----	----- Average



Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5310 Band edge
: 5G WIFI 11N40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5310.000	7.67	34.24	35.23	89.12	95.80	68.20	27.60 peak
2	5350.020	7.70	34.40	35.21	44.64	51.53	74.00	-22.47 peak
3	5371.316	7.72	34.49	35.20	45.89	52.90	74.00	-21.10 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 07; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5310 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5310.000	7.67	34.24	35.23	80.16	86.84	-----	----- Average
2 q	5350.020	7.70	34.40	35.21	34.40	41.29	54.00	-12.71 Average
3	5396.846	7.74	34.59	35.18	33.79	40.94	54.00	-13.06 Average



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5310 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p	5310.000	7.67	34.24	35.23	88.26	94.94	68.20	26.74	Peak
2	5350.020	7.70	34.40	35.21	44.38	51.27	74.00	-22.73	Peak
3	5350.714	7.71	34.40	35.21	45.69	52.59	74.00	-21.41	Peak



Test Mode: 07; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5310 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5310.000	7.67	34.24	35.23	79.01	85.69	-----	Average
2	5350.020	7.70	34.40	35.21	33.82	40.71	54.00	-13.29 Average
3 q	5352.638	7.71	34.41	35.21	34.34	41.25	54.00	-12.75 Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5419.619	7.76	34.64	35.17	46.30	53.53	74.00	-20.47 peak
2	5461.471	7.79	34.65	35.15	45.96	53.25	68.20	-14.95 peak
3 p	5500.000	7.82	34.50	35.13	91.89	99.08	68.20	30.88 peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5420.333	7.76	34.64	35.17	34.25	41.48	54.00	-12.52	Average
2 5500.000	7.82	34.50	35.13	83.15	90.34	-----	-----	Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5431.543	7.77	34.66	35.17	45.82	53.08	74.00	-20.92	Peak
2	5463.392	7.79	34.65	35.15	45.34	52.63	68.20	-15.57	peak
3 p	5500.000	7.82	34.50	35.13	91.82	99.01	68.20	30.81	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5416.403	7.75	34.63	35.18	34.10	41.30	54.00	-12.70	Average
2 5500.000	7.82	34.50	35.13	82.98	90.17	-----	-----	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5700 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5700.000	7.96	34.30	35.04	93.06	100.28	68.20	32.08 peak
2	5750.000	8.00	34.20	35.01	46.39	53.58	68.20	-14.62 peak
3	5759.760	8.00	34.22	35.01	46.38	53.59	68.20	-14.61 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5700 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5700.000	7.96	34.30	35.04	90.68	97.90	68.20	29.70 Peak
2	5750.000	8.00	34.20	35.01	45.86	53.05	68.20	-15.15 Peak
3	5763.983	8.01	34.23	35.01	46.01	53.24	68.20	-14.96 Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5433.215	7.77	34.67	35.17	45.86	53.13	74.00	-20.87	peak
2	5465.673	7.79	34.64	35.15	45.85	53.13	68.20	-15.07	peak
3 p	5500.000	7.82	34.50	35.13	92.18	99.37	68.20	31.17	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q	5425.578	7.76	34.65	35.17	34.34	41.58	54.00	-12.42	Average
2	5500.000	7.82	34.50	35.13	83.15	90.34	-----	-----	Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5413.071	7.75	34.63	35.18	46.16	53.36	74.00	-20.64	Peak
2	5466.995	7.79	34.63	35.15	45.33	52.60	68.20	-15.60	peak
3 p	5500.000	7.82	34.50	35.13	91.73	98.92	68.20	30.72	Peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5500 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 q 5427.963	7.76	34.66	35.17	34.27	41.52	54.00	-12.48	Average
2 5500.000	7.82	34.50	35.13	82.75	89.94	-----	-----	Average



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5700 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5700.000	7.96	34.30	35.04	92.32	99.54	68.20	31.34 peak
2	5750.000	8.00	34.20	35.01	46.20	53.39	68.20	-14.81 peak
3	5756.343	8.00	34.21	35.01	45.82	53.02	68.20	-15.18 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5700 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5700.000	7.96	34.30	35.04	90.26	97.48	68.20	29.28 Peak
2	5750.000	8.00	34.20	35.01	46.03	53.22	68.20	-14.98 Peak
3	5754.435	8.00	34.21	35.01	46.43	53.63	68.20	-14.57 Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5510 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5427.714	7.76	34.66	35.17	45.77	53.02	74.00	-20.98	peak
2	5467.453	7.79	34.63	35.15	46.25	53.52	68.20	-14.68	peak
3 p	5510.000	7.82	34.54	35.13	86.68	93.91	68.20	25.71	peak



Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5510 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5429.659		7.76	34.66	35.17	34.04	41.29	54.00	-12.71 Average
2 5510.000		7.82	34.54	35.13	78.35	85.58	-----	----- Average



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5510 Band edge
: 5G WIFI 11N40


	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5430.354	7.77	34.66	35.17	45.68	52.94	74.00	-21.06	Peak
2	5468.432	7.79	34.63	35.15	45.04	52.31	68.20	-15.89	peak
3 p	5510.000	7.82	34.54	35.13	86.10	93.33	68.20	25.13	Peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5510 Band edge
: 5G WIFI 11N40


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Line	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 q 5434.248		7.77	34.67	35.17	33.91	41.18	54.00	-12.82 Average
2 5510.000		7.82	34.54	35.13	78.00	85.23	-----	----- Average



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 08; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5670 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Limit	Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5670.000	7.94	34.36	35.05	89.47	96.72	68.20	28.52 peak
2	5750.000	8.00	34.20	35.01	46.10	53.29	68.20	-14.91 peak
3	5764.432	8.01	34.23	35.01	46.55	53.78	68.20	-14.42 peak



Test Mode: 08; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5670 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5670.000	7.94	34.36	35.05	87.67	94.92	68.20	26.72 Peak
2	5750.000	8.00	34.20	35.01	46.08	53.27	68.20	-14.93 Peak
3	5762.735	8.01	34.23	35.01	46.29	53.52	68.20	-14.68 Peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5745 Band edge
: 5G WIFI 11A


		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5641.106	7.92	34.45	35.07	46.03	53.33	68.20	-14.87 peak
2	5715.000	7.97	34.27	35.03	46.11	53.32	109.40	-56.08 peak
3	5725.000	7.98	34.25	35.03	55.35	62.55	122.20	-59.65 peak
4	5745.000	7.99	34.21	35.02	94.84	102.02	-----	----- peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5745 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 p 5649.550	7.93	34.40	35.06	45.62	52.89	68.20	-15.31	peak
2 5715.000	7.97	34.27	35.03	44.44	51.65	109.40	-57.75	peak
3 5725.000	7.98	34.25	35.03	52.88	60.08	122.20	-62.12	peak
4 5745.000	7.99	34.21	35.02	92.78	99.96	-----	-----	peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5825 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	8.05	34.35	34.98	92.17	99.59	-----	----- peak
2	5850.000	8.07	34.40	34.97	45.59	53.09	122.20	-69.11 peak
3	5860.000	8.07	34.44	34.96	45.84	53.39	109.40	-56.01 peak
4 p	5940.290	8.13	34.68	34.93	46.34	54.22	68.20	-13.98 peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5825 Band edge
: 5G WIFI 11A

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	8.05	34.35	34.98	90.75	98.17	-----	----- peak
2	5850.000	8.07	34.40	34.97	46.20	53.70	122.20	-68.50 peak
3	5860.000	8.07	34.44	34.96	46.16	53.71	109.40	-55.69 peak
4 p	5926.653	8.12	34.65	34.93	46.59	54.43	68.20	-13.77 peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5745 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5646.919	7.92	34.42	35.06	46.28	53.56	68.20	-14.64 peak
2	5715.000	7.97	34.27	35.03	45.60	52.81	109.40	-56.59 peak
3	5725.000	7.98	34.25	35.03	59.92	67.12	122.20	-55.08 peak
4	5745.000	7.99	34.21	35.02	94.38	101.56	-----	----- peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5745 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5642.352	7.92	34.45	35.07	45.61	52.91	68.20	-15.29 peak
2	5715.000	7.97	34.27	35.03	44.94	52.15	109.40	-57.25 peak
3	5725.000	7.98	34.25	35.03	58.23	65.43	122.20	-56.77 peak
4	5745.000	7.99	34.21	35.02	92.81	99.99	-----	----- peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5825 Band edge
: 5G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	8.05	34.35	34.98	91.67	99.09	-----	----- peak
2	5850.000	8.07	34.40	34.97	45.84	53.34	122.20	-68.86 peak
3	5860.000	8.07	34.44	34.96	46.02	53.57	109.40	-55.83 peak
4 p	5940.133	8.13	34.68	34.93	46.74	54.62	68.20	-13.58 peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5825 Band edge
: 5G WIFI 11N20


		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5825.000	8.05	34.35	34.98	90.51	97.93	-----	----- peak
2	5850.000	8.07	34.40	34.97	45.59	53.09	122.20	-69.11 peak
3	5860.000	8.07	34.44	34.96	46.09	53.64	109.40	-55.76 peak
4 p	5925.557	8.12	34.65	34.93	47.12	54.96	68.20	-13.24 peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5755 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p	5643.212	7.92	34.44	35.06	45.44	52.74	68.20	-15.46 peak
2	5715.000	7.97	34.27	35.03	53.30	60.51	109.40	-48.89 peak
3	5725.000	7.98	34.25	35.03	59.11	66.31	122.20	-55.89 peak
4	5755.000	8.00	34.21	35.01	91.97	99.17	-----	----- peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5755 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 p 5644.742		7.92	34.43	35.06	46.34	53.63	68.20	-14.57 peak
2 5715.000		7.97	34.27	35.03	50.50	57.71	109.40	-51.69 peak
3 5725.000		7.98	34.25	35.03	55.81	63.01	122.20	-59.19 peak
4 5755.000		8.00	34.21	35.01	89.84	97.04	-----	----- peak



Test Mode: 09; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High




Site : chamber
Condition: 3m HORIZONTAL
Job No : 00543AT\00622AT
Mode : 5795 Band edge
: 5G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamplifier Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	5795.000	8.03	34.29	34.99	91.42	98.75	-----	-----	peak
2	5850.000	8.07	34.40	34.97	45.38	52.88	122.20	-69.32	peak
3	5860.000	8.07	34.44	34.96	46.80	54.35	109.40	-55.05	peak
4 p	5944.390	8.13	34.69	34.93	46.75	54.64	68.20	-13.56	peak



Test Mode: 09; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Site : chamber
Condition: 3m VERTICAL
Job No : 00543AT\00622AT
Mode : 5795 Band edge
: 5G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz		dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5795.000	8.03	34.29	34.99	88.84	96.17	-----	----- peak
2	5850.000	8.07	34.40	34.97	45.25	52.75	122.20	-69.45 peak
3	5860.000	8.07	34.44	34.96	46.37	53.92	109.40	-55.48 peak
4 p	5942.559	8.13	34.69	34.93	47.00	54.89	68.20	-13.31 peak



8 Test Setup Photo

Refer to Appendix - Test Setup Photo for SZCR2402000543AT

9 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2402000543AT

- End of the Report -

