

Abbott Laboratories

RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Merlin 2 PCS Programmer, Model: MER3700

REPORT NUMBER

105602398MPK-004

ISSUE DATE

January 09, 2024

REVISED DATE

January 26, 2024

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



**RF Exposure Exhibit
(mobile devices)**

Report Number: 105602398MPK-004

Project Number: G105602398

Report Issue Date: January 09, 2024

Revised Date: January 26, 2024

Product Designation: Merlin 2 PCS Programmer

Model Tested: MER3700

to

**47CFR 2.1091
RSS-102 Issue 5**

for

Abbott Laboratories

Test Performed by:

Intertek

1365 Adams Court

Menlo Park, CA 94025 USA

Test Authorized by:

Abbott Laboratories

15900 Valley View Court

Sylmar, CA 91342 USA

Prepared by: _____



Gilberto Gallegos Rangel

Date: January 09, 2024

Reviewed by: _____



Minh Ly

Date: January 09, 2024

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to copy or distribute this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

Report No. 105602398MPK-004	
Equipment Under Test:	Merlin 2 PCS Programmer
Trade Name:	Abbott Laboratories
Model(s) Tested:	MER3700
Applicant:	Abbott Laboratories
Contact:	Perry Li
Address:	Abbott Laboratories 15900 Valley View Court Sylmar, CA 91342
Country:	USA
Tel. Number:	(818) 493-3793
Email:	perry.li@abbott.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

TABLE OF CONTENTS

Abbott Laboratories..... **1**

1.0 RF Exposure Summary..... **5**

2.0 RF Exposure Limits **5**

3.0 Test Results (Mobile Configuration) **7**

4.0 Document History **10**

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	$0.73/f$	-	6**
1.1-10	$87/f^{0.5}$	-	-	6**
10-20	27.46	0.0728	-2	6
20-48	$58.07/f^{0.25}$	$0.1540/f^{0.25}$	$8.944/f^{0.5}$	6
48-300	22.06	0.05852	1.291	6
300-6000	$3.142 f^{0.3417}$	$0.008335 f^{0.3417}$	$0.02619 f^{0.6834}$	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	$616000/f^{1.2}$
150000-300000	$0.158 f^{0.5}$	$4.21 \times 10^{-4} f^{0.5}$	$6.67 \times 10^{-5} f$	$616000/f^{1.2}$
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is installed at least 20cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Merlin 2, model: MER3700 consists of one radio module model: 9260NGW (FCC ID: PD99260NG).

- 2.4GHz Wifi.
- 5GHz U-NII 1.
- 5GHz U-NII 2A
- 5GHz U-NII 2C.
- 5GHz U-NII 3.

3.3 Maximum RF Power

Frequency Range (MHz)	RF Output (dBm)	Antenna Gain ¹ (dBi)	Note
2400-2483.5	22.54	5.03	Conducted power measurements were taken from Report # 105602398MPK-001.
5150 – 5250	17.74	5.32	Conducted power measurements were taken from Report # 105602398MPK-002.
5250 – 5350	17.33	5.32	Conducted power measurements were taken from Report # 105602398MPK-002.
5470 – 5725	17.85	5.32	Conducted power measurements were taken from Report # 105602398MPK-002.
5725 – 5850	17.30	5.32	Conducted power measurements were taken from Report # 105602398MPK-002.

¹As declared by the manufacturer.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation.

Calculations for this report are based on highest power measured for each band.

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (mW/cm ²) @20cm	FCC Limit (mW/cm ²)
2400-2483.5	27.57	571.478	0.1137	1
5150 – 5250	23.06	202.301	0.04024	1
5250 – 5350	22.65	184.077	0.03662	1
5470 – 5725	23.17	207.491	0.04127	1
5725 – 5850	22.62	182.810	0.03636	1

Frequency Range (MHz)	EIRP ¹ (dBm)	EIRP ¹ (mW)	Power Density (W/m ²) @20cm	RSS Limit (W/m ²)
2400-2483.5	27.57	571.478	1.1137	5.469
5150 – 5250	23.06	202.301	0.4024	9.831
5250 – 5350	22.65	184.077	0.3662	9.831
5470 – 5725	23.17	207.491	0.4127	9.831
5725 – 5850	22.62	182.810	0.3636	9.831

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0/ G105602398	GGR	ML	January 09, 2024	Original document
2.0/ G105602398	GGR	ML	January 26, 2024	Fixed typo on customer contact phone number.