FCC TEST REPORT

REPORT NO.: RF950224L17

MODEL NO.: BT-332

RECEIVED: Feb. 24, 2006

TESTED: Mar. 20 ~ Mar. 22, 2006

ISSUED: Mar. 24, 2006

APPLICANT: GlobalSat Technology Corporation

ADDRESS: 2-1F,No.16,Chien 8 Road Far East Century Park,Chung Ho City,Taipei, Taiwan, R.O.C..

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei Shan Hsiang, Taoyuan Hsien 333, Taiwan, R.O.C.

This test report consists of 74 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.

NO. 2177-01

TABLE OF CONTENTS

1. CERTIFICATION……..…….. …….. …….. 4
2. SUMMARY OF TEST RESULTS…….. …….. …….. 5
2.1 MEASUREMENT UNCERTAINTY.....6
3. GENERAL INFORMATION…….. …….. …….. 7
3.1 GENERAL DESCRIPTION OF EUT.....7
3.2 DESCRIPTION OF TEST MODES.....8
3.2.1 CONFIGURATION OF SYSTEM UNDER TEST.....9
3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....10
3.3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....12
3.3.4 DESCRIPTION OF SUPPORT UNITS.....12
4. TEST TYPES AND RESULTS…….. …….. …….....13
4.1 CONDUCTED EMISSION MEASUREMENT.....13
4.2 RADIATED EMISSION MEASUREMENT.....13
4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT.....13
4.2.2 TEST INSTRUMENTS.....14
4.2.3 TEST PROCEDURES.....15
4.2.4 DEVIATION FROM TEST STANDARD.....15
4.2.5 TEST SETUP.....16
4.2.6 EUT OPERATING CONDITIONS.....16
4.2.7 TEST RESULTS.....17
4.3 NUMBER OF HOPPING FREQUENCY USED.....30
4.3.1 LIMIT OF HOPPING FREQUENCY USED.....30
4.3.2 TEST INSTRUMENTS.....30
4.3.3 TEST PROCEDURES.....30
4.3.4 DEVIATION FROM TEST STANDARD.....31
4.3.5 TEST SETUP.....31
4.3.6 TEST RESULTS.....31
4.4 DWELL TIME ON EACH CHANNEL.....34
4.4.1 LIMIT OF DWELL TIME USED.....34
4.4.2 TEST INSTRUMENTS.....34
4.4.3 TEST PROCEDURES.....34
4.4.4 DEVIATION FROM TEST STANDARD.....34
4.4.5 TEST SETUP.....35
4.4.6 TEST RESULTS.....35
4.5 CHANNEL BANDWIDTH.....43
4.5.1 LIMITS OF CHANNEL BANDWIDTH.....43
4.5.2 TEST INSTRUMENTS.....43
4.5.3 TEST PROCEDURE.....43

4.5.4 DEVIATION FROM TEST STANDARD.....44
4.5.5 TEST SETUP.....44
4.5.6 EUT OPERATING CONDITION.....44
4.5.7 TEST RESULTS 44
4.6 HOPPING CHANNEL SEPARATION.....50
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 50
4.6.2 TEST INSTRUMENTS.....50
4.6.3 TEST PROCEDURES 50
4.6.4 DEVIATION FROM TEST STANDARD.....51
4.6.5 TEST SETUP.....51
4.6.6 TEST RESULTS 51
4.7 MAXIMUM PEAK OUTPUT POWER.....57
4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 57
4.7.2 TEST INSTRUMENTS.....57
4.7.3 TEST PROCEDURES 57
4.7.4 DEVIATION FROM TEST STANDARD.....57
4.7.5 TEST SETUP.....58
4.7.6 EUT OPERATING CONDITION.....58
4.7.7 TEST RESULTS 58
4.8 BAND EDGES MEASUREMENT 64
4.8.1 LIMITS OF BAND EDGES MEASUREMENT.....64
4.8.2 TEST INSTRUMENTS.....64
4.8.3 TEST PROCEDURE.....64
4.8.4 DEVIATION FROM TEST STANDARD.....64
4.8.5 EUT OPERATING CONDITION.....64
4.8.6 TEST RESULTS 65
4.9 ANTENNA REQUIREMENT 71
4.9.1 STANDARD APPLICABLE 71
4.9.2 ANTENNA CONNECTED CONSTRUCTION 71
5. PHOTOGRAPHS OF THE TEST CONFIGURATION…….. 72
6. INFORMATION ON THE TESTING LABORATORIES…….....73
APPENDIX-A..... A-1

1. CERTIFICATION

PRODUCT:	Bluetooth GPS receiver
MODEL NO.:	BT-332
BRAND NAME:	DELL
APPLICANT:	GlobalSat Technology Corporation
TESTED:	Mar. 20 ~ Mar. 22, 2006
TEST SAMPLE:	ENGINEERING SAMPLE
STANDARDS:	FCC Part 15, Subpart C (Section 15.247), ANSI C63.4-2003

The above equipment have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Windy Chou , **DATE:** Mar. 22, 2006
(Windy Chou)

TECHNICAL ACCEPTANCE : Long Chen , **DATE:** Mar. 22, 2006
Responsible for RF (Long Chen)

APPROVED BY : Gary Chang , **DATE:** Mar. 22, 2006
(Gary Chang / Supervisor)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	NA	Power supply is 3.7Vdc from battery
15.247(a)(1)(iii)	Number of Hopping Frequency Used Spec.: At least 15 channels	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel Spec. : Max. 0.4 second within 31.6 second	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation Spec. : Min. 25 kHz or 20 dB bandwidth, whichever is greater (see Note 1) 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Spec.: max. 30dBm (see Note 1)	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions Spec.: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is –8.82 dB at 2483.5MHz.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.

NOTE: If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth GPS receiver
MODEL NO.	BT-332
FCC ID	RIDBT-332
POWER SUPPLY	3.7Vdc from batteries 12Vdc and 24Vdc from car charger
MODULATION TYPE	GFSK, π /4-DQPSK, 8DPSK
RADIO TECHNOLOGY	FHSS
TRANSFER RATE	1/2/3Mbps
FREQUENCY RANGE	2400 ~ 2483.5 MHz
NUMBER OF CHANNEL	79
OUTPUT POWER	2.838mW
ANTENNA TYPE	Chip antenna with 2dBi gain
DATA CABLE	NA
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT was powered by the following battery and car charger:

Battery:

Brand:	Welldone co.
Model:	NP-120
Rating:	3.7Vdc, 1700mAh

Car charger:

Brand:	Axim
Model:	IC-DX3-GPS
Input:	12Vdc / 24Vdc, 12A
Output:	5Vdc, 5A
Power Line:	DC 0.4 m non-shielded cable without core

Note: After pre-test, the EUT powered from 24Vdc car charger was the worst case and the test data were present in this report.

2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2431	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	Applicable to			Description
	RE<1G	RE≥1G	APCM	
A	√	√	√	Car Charger: 24Vdc (GFSK Modulation)
B	-	√	√	Car Charger: 24Vdc (8DPSK Modulation)

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types, data rate and XYZ axis.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE	AXIS
A	0 to 78	78	FHSS	GFSK	DH5	1	Y

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types, data rate and XYZ axis.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE	AXIS
A	0 to 78	0, 39, 78	FHSS	GFSK	DH5	1	Y
B	0 to 78	0, 39, 78	FHSS	8DPSK	DH5	3	Y

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE	AXIS
A	0 to 78	0, 78	FHSS	GFSK	DH5	1	Y
B	0 to 78	0, 78	FHSS	8DPSK	DH5	3	Y

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and packet types.

☒ Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE	DATE RATE
A	0 to 78	0, 78	GFSK	DH5	DH5	1
B	0 to 78	0, 78	8DPSK	DH5	DH5	3

3.3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Bluetooth GPS receiver. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Automotive Battery	YUASA	36B20L	NA	NA
2	Automotive Battery	HEXA	NT-50-24LMF	NA	NA
3	NOTEBOOK COMPUTER	DELL	PP05L	12130898320	E2K24CLNS
4	PRINTER	EPSON	LQ-300+	DCGY047265	FCC DoC Approved

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	NA
3	NA
4	1.2m shielded cable without core

NOTE: All power cords of the above support units are non shielded (1.8m).

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

NA

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	100033	May. 19, 2006
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100025	Dec. 05, 2006
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Jun. 01, 2006
HORN Antenna SCHWARZBECK	9120D	9120D-408	Jan. 08, 2007
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 19, 2007
Preamplifier Agilent	8447D	2944A10633	Nov. 04, 2006
Preamplifier Agilent	8449B	3008A01964	Oct. 30, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	214377/4	Dec. 13, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	219272/4	Dec. 13, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA
Turn Table ADT.	TT100.	TT93021703	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 2.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The VCCI Site Registration No. is R-237.
5. The IC Site Registration No. is IC4924-3.

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

The EUT connected with battery via car charger at charging mode and placed on the test table.

4.2.7 TEST RESULTS

RADIATED WORST CASE DATA: BELOW 1GHZ: FOR GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	Below 1000MHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Quasi-Peak
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	96.09	28.33 QP	43.50	-15.17	1.75 H	115	18.98	9.35
2	127.19	27.68 QP	43.50	-15.82	1.75 H	52	15.77	11.90
3	169.96	33.47 QP	43.50	-10.03	1.25 H	343	20.49	12.98
4	199.12	34.51 QP	43.50	-8.99	1.25 H	313	23.30	11.21
5	255.49	29.52 QP	46.00	-16.48	1.25 H	199	16.88	12.63
6	319.64	31.51 QP	46.00	-14.49	1.00 H	61	15.30	16.20
7	500.42	32.10 QP	46.00	-13.90	1.25 H	193	11.62	20.48

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	59.16	25.07 QP	40.00	-14.93	1.00 V	10	11.51	13.56
2	117.47	28.04 QP	43.50	-15.46	1.00 V	190	17.14	10.91
3	199.12	34.09 QP	43.50	-9.41	1.00 V	10	22.87	11.21
4	249.66	23.79 QP	46.00	-22.21	1.50 V	91	11.13	12.66
5	333.25	24.87 QP	46.00	-21.13	1.50 V	214	8.46	16.42
6	399.34	28.12 QP	46.00	-17.88	1.25 V	247	9.84	18.28
7	601.50	28.42 QP	46.00	-17.58	1.00 V	10	5.26	23.16
8	733.69	35.94 QP	46.00	-10.06	1.50 V	76	10.30	25.64

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

RADIATED WORST CASE DATA: ABOVE 1GHz: FOR GFSK

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	45.68 PK	74.00	-28.32	1.30 H	263	16.55	29.13
1	1602.00	41.25 AV	54.00	-12.75	1.30 H	263	12.12	29.13
2	2390.00	52.58 PK	74.00	-21.42	1.53 H	164	20.67	31.91
2	2390.00	44.77 AV	54.00	-9.23	1.53 H	164	12.86	31.91
3	*2402.00	95.58 PK			1.53 H	164	63.60	31.98
3	*2402.00	65.58 AV			1.53 H	164	33.60	31.98
4	4804.00	48.13 PK	74.00	-25.87	1.00 H	96	10.64	37.49
4	4804.00	18.13 AV	54.00	-35.87	1.00 H	96	-19.36	37.49

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	44.56 PK	74.00	-29.44	1.12 V	129	15.43	29.13
1	1602.00	40.68 AV	54.00	-13.32	1.12 V	129	11.55	29.13
2	2390.00	50.33 PK	74.00	-23.67	1.15 V	325	18.42	31.91
2	2390.00	42.62 AV	54.00	-11.38	1.15 V	325	10.71	31.91
3	*2402.00	93.43 PK			1.15 V	325	61.45	31.98
3	*2402.00	63.43 AV			1.15 V	325	31.45	31.98
4	4804.00	47.06 PK	74.00	-26.94	1.05 V	72	9.57	37.49
4	4804.00	17.06 AV	54.00	-36.94	1.05 V	72	-20.43	37.49

REMARKS: 1Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).

2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	45.98 PK	74.00	-28.02	1.22 H	252	16.82	29.16
1	1628.00	41.56 AV	54.00	-12.44	1.22 H	252	12.40	29.16
2	*2441.00	98.01 PK			1.22 H	174	65.79	32.22
2	*2441.00	68.01 AV			1.22 H	174	35.79	32.22
3	4882.00	49.66 PK	74.00	-24.34	1.08 H	76	12.10	37.56
3	4882.00	19.66 AV	54.00	-34.34	1.08 H	76	-17.90	37.56

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	44.35 PK	74.00	-29.65	1.08 V	123	15.19	29.16
1	1628.00	40.21 AV	54.00	-13.79	1.08 V	123	11.05	29.16
2	*2441.00	96.08 PK			1.18 V	133	63.86	32.22
2	*2441.00	66.08 AV			1.18 V	133	33.86	32.22
3	4882.00	48.52 PK	74.00	-25.48	1.10 V	65	10.96	37.56
3	4882.00	18.52 AV	54.00	-35.48	1.10 V	65	-19.04	37.56

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1654.00	46.11 PK	74.00	-27.89	1.25 H	255	16.93	29.18
1	1654.00	41.39 AV	54.00	-12.61	1.25 H	255	12.21	29.18
2	*2480.00	95.22 PK			1.16 H	222	62.75	32.47
2	*2480.00	65.22 AV			1.16 H	222	32.75	32.47
3	2483.50	53.22 PK	74.00	-20.78	1.16 H	222	20.73	32.49
3	**2483.50**	**45.18 AV**	**54.00**	**-8.82**	**1.16 H**	**222**	**12.69**	**32.49**
4	4960.00	49.55 PK	74.00	-24.45	1.05 H	31	11.96	37.59
4	4960.00	19.55 AV	54.00	-34.45	1.05 H	31	-18.04	37.59

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	GFSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 68%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Morgan Chen	**TEST MODE**	A

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1654.00	45.08 PK	74.00	-28.92	1.16 V	244	15.90	29.18
1	1654.00	40.22 AV	54.00	-13.78	1.16 V	244	11.04	29.18
2	*2480.00	93.18 PK			1.33 V	151	60.71	32.47
2	*2480.00	63.18 AV			1.33 V	151	30.71	32.47
3	2483.50	51.11 PK	74.00	-22.89	1.33 V	151	18.62	32.49
3	2483.50	44.05 AV	54.00	-9.95	1.33 V	151	11.56	32.49
4	4960.00	48.39 PK	74.00	-25.61	1.18 V	352	10.80	37.59
4	4960.00	18.39 AV	54.00	-35.61	1.18 V	352	-19.20	37.59

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

RADIATED WORST CASE DATA: ABOVE 1GHZ: FOR 8DPSK

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	46.05 PK	74.00	-27.95	1.00 H	109	16.92	29.13
1	1602.00	43.69 AV	54.00	-10.31	1.00 H	109	14.56	29.13
2	2388.00	50.13 PK	74.00	-23.87	1.00 H	142	18.23	31.90
2	2388.00	40.92 AV	54.00	-13.08	1.00 H	142	9.02	31.90
3	*2402.00	94.81 PK			1.00 H	142	62.83	31.98
3	*2402.00	64.81 AV			1.00 H	142	32.83	31.98
4	4804.00	47.48 PK	74.00	-26.52	1.46 H	251	9.99	37.49
4	4804.00	17.48 AV	54.00	-36.52	1.46 H	251	-20.01	37.49

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 0	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1602.00	46.79 PK	74.00	-27.21	1.13 V	251	17.66	29.13
1	1602.00	43.98 AV	54.00	-10.02	1.13 V	251	14.85	29.13
2	2388.00	47.80 PK	74.00	-26.20	1.05 V	199	15.90	31.90
2	2388.00	38.65 AV	54.00	-15.35	1.05 V	199	6.75	31.90
3	*2402.00	92.48 PK			1.05 V	199	60.50	31.98
3	*2402.00	62.48 AV			1.05 V	199	30.50	31.98
4	4804.00	47.56 PK	74.00	-26.44	1.10 V	230	10.07	37.49
4	4804.00	17.56 AV	54.00	-36.44	1.10 V	230	-19.93	37.49

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	45.68 PK	74.00	-28.32	1.28 H	184	16.52	29.16
1	1628.00	39.83 AV	54.00	-14.17	1.28 H	184	10.67	29.16
2	*2441.00	94.35 PK			1.00 H	123	62.13	32.22
2	*2441.00	64.35 AV			1.00 H	123	32.13	32.22
3	4882.00	45.06 PK	74.00	-28.94	1.17 H	340	7.50	37.56
3	4882.00	15.06 AV	54.00	-38.94	1.17 H	340	-22.50	37.56

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 39	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1628.00	44.85 PK	74.00	-29.15	1.19 V	231	15.69	29.16
1	1628.00	39.63 AV	54.00	-14.37	1.19 V	231	10.47	29.16
2	*2441.00	92.38 PK			1.00 V	245	60.16	32.22
2	*2441.00	62.38 AV			1.00 V	245	30.16	32.22
3	4882.00	44.01 PK	74.00	-29.99	1.10 V	223	6.45	37.56
3	4882.00	14.01 AV	54.00	-39.99	1.10 V	223	-23.55	37.56

REMARKS:
1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1654.00	44.25 PK	74.00	-29.75	1.19 H	182	15.06	29.18
1	1654.00	39.79 AV	54.00	-14.21	1.19 H	182	10.60	29.18
2	*2480.00	94.50 PK			1.00 H	120	62.03	32.47
2	*2480.00	64.50 AV			1.00 H	120	32.03	32.47
3	2484.00	51.63 PK	74.00	-22.37	1.00 H	120	19.14	32.49
3	2484.00	42.38 AV	54.00	-11.62	1.00 H	120	9.89	32.49
4	4960.00	47.71 PK	74.00	-26.29	1.18 H	313	10.11	37.59
4	4960.00	17.71 AV	54.00	-36.29	1.18 H	313	-19.89	37.59

REMARKS:
1. Emission level BuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 78	**FREQUENCY RANGE**	1 ~ 25GHz
MODULATION TYPE	8DPSK	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
INPUT POWER (SYSTEM)	25deg. C, 65%RH, 991hPa	**INPUT POWER (SYSTEM)**	120Vac, 60 Hz
TESTED BY	Jay Hsu	**TEST MODE**	B

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1654.00	44.68 PK	74.00	-29.32	1.17 V	228	15.50	29.18
1	1654.00	40.25 AV	54.00	-13.75	1.17 V	228	11.07	29.18
2	*2480.00	92.64 PK			1.02 V	230	60.17	32.47
2	*2480.00	62.64 AV			1.02 V	230	30.17	32.47
3	2484.00	49.77 PK	74.00	-24.23	1.02 V	230	17.28	32.49
3	2484.00	40.63 AV	54.00	-13.37	1.02 V	230	8.14	32.49
4	4960.00	47.23 PK	74.00	-26.77	1.09 V	221	9.64	37.59
4	4960.00	17.23 AV	54.00	-36.77	1.09 V	221	-20.36	37.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle be equal to: 20log(3.125/100)= -30 dB.
6. Average value = peak reading –20log(duty cycle).

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

MODE A FOR GFSK





MODE B FOR 8DPSK





4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.4.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation.

4.4.5 TEST SETUP

4.4.6 TEST RESULTS

MODE A FOR TEST GFSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	51 (times / 5 sec) *6.32=322.32 times	0.490	157.937	400
DH3	25 (times / 5 sec) *6.32=158.00 times	1.738	274.604	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.008	323.180	400

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.

DH1


RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 5 s
1 PK
VIEW
A
20
-10
0
-10
-20
-30
-40
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
0.12 dB
Ref 20 dBm
*Att 30 dB
SWT 3 ms
490.000000 µs
Marker 1 [T1]
-60.97 dBm
980.000000 µs
1 AP
VIEW
A
20
-10
0
-10
-20
-30
-40
-50
-70
-80
Center 2.402 GHz
300 µs/

DH3


RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 5 s
1 PK
MAXH
A
SGL
20
-10
0
-10
-20
-30
-40
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
0.80 dB
Ref 20 dBm
*Att 30 dB
SWT 3 ms
1.738000 ms
Marker 1 [T1]
-53.45 dBm
-16.000000 µs
1 PK
VIEW
A
20
-10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
300 µs/

DH5


RBW 100 kHz
*VBW 100 kHz
SWT 5 s
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
*VBW 100 kHz
SWT 5 ms
Delta 2 [T1]
-1.42 dB
3.008000 ms
Marker 1 [T1]
-53.23 dBm
-26.000000 µs
Ref 20 dBm
*Att 30 dB
1 PK
VIEW
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 µs/

MODE B FOR 8DPSK

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) *6.32=316.00 times	0.498	157.368	400
DH3	25 (times / 5 sec) *6.32=158.00 times	1.758	277.764	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.008	323.180	400

NOTE: Test plots of the transmitting time slot are shown on next 3 pages.

DH1


RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 5 s
1 PK
MAXH
A
SGL
20
-10
-10
-20
-30
-40
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
1.02 dB
Ref 20 dBm
*Att 30 dB
SWT 3 ms
498.000000 µs
Marker 1 [T1]
-54.90 dBm
-22.000000 µs
1 PK
VIEW
A
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
300 µs/

DH3


RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 5 s
1 PK
MAXH
A
SGL
20
-10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
-2.12 dB
Ref 20 dBm
*Att 30 dB
SWT 3 ms
1.758000 ms
Marker 1 [T1]
-52.41 dBm
-16.000000 µs
1 PK
VIEW
A
20
-10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
300 µs/

DH5


RBW 100 kHz
*VBW 100 kHz
Ref 20 dBm
*Att 30 dB
SWT 5 s
1 PK
MAXH
A
SGL
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 ms/


RBW 100 kHz
Delta 2 [T1]
*VBW 100 kHz
-1.01 dB
Ref 20 dBm
*Att 30 dB
SWT 5 ms
3.008000 ms
Marker 1 [T1]
-54.69 dBm
-16.000000 µs
1 PK
VIEW
A
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
500 µs/

4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.5.3 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation.

4.5.5 TEST SETUP

4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

MODE A FOR GFSK

MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	0.849
39	2441	0.843
78	2480	0.837

CH 0


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
0.90 dB
849.000000000 kHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-16.41 dBm
2.401586000 GHz
1 PK
MAXH
D1 4.46 dBm
D2 -15.54 dBm
F1
F2
Center 2.402 GHz
150 kHz/
Span 1.5 MHz

CH 39


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
0.00 dB
843.000000000 kHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-15.98 dBm
2.440592000 GHz
1 PK
VIEW
D1 4.22 dBm
D2 -15.78 dBm
F1
F2
Center 2.441 GHz
150 kHz/
Span 1.5 MHz

CH 78


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
0.29 dB
837.000000000 kHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-17.30 dBm
2.479595000 GHz
1 PK
VIEW
D1 2.96 dBm
D2 -17.04 dBm
F1
F2
Center 2.48 GHz
150 kHz/
Span 1.5 MHz

MODE B FOR 8DPSK

MODULATION TYPE	8DPSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.266
39	2441	1.266
78	2480	1.263

CH 0


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.32 dB
1.266000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-15.53 dBm
2.401388000 GHz
1 PK VIEW
D1 4.39 dBm
D2 -15.61 dBm
F1
F2
Center 2.402 GHz
150 kHz/
Span 1.5 MHz

CH 39


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.04 dB
1.266000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-15.83 dBm
2.440388000 GHz
1 PK VIEW
D1 4.11 dBm
D2 -15.89 dBm
F1
F2
Center 2.441 GHz
150 kHz/
Span 1.5 MHz

CH 78


*RBW 30 kHz
*VBW 300 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.50 dB
1.263000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
-16.38 dBm
2.479391000 GHz
1 PK
VIEW
D1 3.12 dBm
D2 -16.88 dBm
Center 2.48 GHz
150 kHz/
Span 1.5 MHz

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation.

4.6.5 TEST SETUP

4.6.6 TEST RESULTS

MODE A FOR GFSK

MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.000	0.849	0.566	PASS
39	2441	1.000	0.843	0.562	PASS
78	2480	1.000	0.837	0.558	PASS

NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to next two pages.

CH 0


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
0.18 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
3.96 dBm
2.402040000 GHz
1 PK
MAXH
A
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.4025 GHz
250 kHz/
Span 2.5 MHz

CH 39


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.00 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
3.73 dBm
2.441045000 GHz
1 PK
MAXH
A
20
-10
-0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.44155 GHz
250 kHz/
Span 2.5 MHz

CH 78


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
-0.04 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
2.81 dBm
2.479045000 GHz
1 PK
MAXH
A
20
-10
-0
--10
--20
--30
--40
--50
--60
--70
-80
Center 2.4793 GHz
250 kHz/
Span 2.5 MHz

MODE B FOR 8DPSK

MODULATION TYPE	8DPSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.000	1.266	0.844	PASS
39	2441	1.000	1.266	0.844	PASS
78	2480	1.000	1.263	0.842	PASS

NOTE: The minimum limit is two-third 20dB bandwidth. Test results please refer to next two pages.

CH 0


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T3]
-0.01 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
4.39 dBm
2.402040000 GHz
1 PK
VIEW
3 PK
MAXH
Center 2.402575 GHz
250 kHz/
Span 2.5 MHz

CH 39


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T3]
-0.01 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T1]
4.04 dBm
2.441045000 GHz
1 PK
VIEW
3 PK
MAXH
Center 2.441575 GHz
250 kHz/
Span 2.5 MHz

CH 78


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 ms
Delta 2 [T1]
0.08 dB
1.000000000 MHz
Ref 20 dBm
*Att 30 dB
Marker 1 [T3]
3.02 dBm
2.479040000 GHz
1 PK
VIEW
3 PK
VIEW
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.4794 GHz
250 kHz/
Span 2.5 MHz

4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.7.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYEER	FSEK30	100049	Aug. 14, 2006

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.7.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP

For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

MODE A FOR GFSK

MODULATION TYPE	GFSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	2.838	4.53	125	PASS
39	2441	2.661	4.25	125	PASS
78	2480	2.123	3.27	125	PASS

CH 0


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
4.53 dBm
2.401680000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
4 MHz/
Span 40 MHz

CH 39


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
4.25 dBm
2.440840000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.441 GHz
4 MHz/
Span 40 MHz

CH 78


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
3.27 dBm
2.479760000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.48 GHz
4 MHz/
Span 40 MHz

MODE B FOR 8DPSK

MODULATION TYPE	8DPSK	**ENVIRONMENTAL CONDITIONS**	23deg. C, 54%RH, 991hPa
INPUT POWER (SYSTEM)	120Vac, 60 Hz	**TESTED BY**	Morgan Chen

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (mW)	PASS/FAIL
0	2402	2.735	4.37	125	PASS
39	2441	2.553	4.07	125	PASS
78	2480	2.143	3.31	125	PASS

CH 0


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
4.37 dBm
2.402000000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.402 GHz
4 MHz/
Span 40 MHz

CH 39


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
4.07 dBm
2.441000000 GHz
Ref 20 dBm
*Att 30 dB
1 PK
MAXH
A
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Center 2.441 GHz
4 MHz/
Span 40 MHz

CH 78


*RBW 3 MHz
*VBW 10 MHz
SWT 2.5 ms
Marker 1 [T1]
3.31 dBm
2.479840000 GHz
Ref 20 dBm
*Att 30 dB
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
A
Center 2.48 GHz
4 MHz/
Span 40 MHz

4.8 BAND EDGES MEASUREMENT

4.8.1 LIMITS OF BAND EDGES MEASUREMENT

Below –20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
SPECTRUM ANALYZER	FSEK30	100049	Aug. 14, 2006

NOTES: The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to NML/ROC and NIST/USA.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following 4 images. D1 line indicates the highest level, D2 line indicates the 20dB offset below D1. It shows compliance with the requirement in part 15.247(d).

MODE A FOR GFSK

NOTE 1:
The band edge emission plot on the next page shows 53.61dBc between carrier maximum power and local maximum emission in restrict band (2.3598GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 95.58dBuV/m (Peak), so the maximum field strength in restrict band is 95.58 – 53.61 = 41.97dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on the next page shows 53.61dBc between carrier maximum power and local maximum emission in restrict band (2.3598GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 65.58dBuV/m (Average), so the maximum field strength in restrict band is 65.58 – 53.61 = 11.97dBuV/m, which is under 54 dBuV/m limit.

NOTE 2:
The band edge emission plot on the next second page shows 47.12dBc between carrier maximum power and local maximum emission in restrict band (2.4845GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 95.22dBuV/m (Peak), so the maximum field strength in restrict band is 95.22 – 47.12 = 48.10dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on the next second page shows 47.12dBc between carrier maximum power and local maximum emission in restrict band (2.4845GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 65.22dBuV/m (Average), so the maximum field strength in restrict band is 65.22 – 47.12 = 18.10dBuV/m, which is under 54 dBuV/m limit.


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
4.36 dBm
2.402200000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-49.55 dBm
2.399400000 GHz
Marker 3 [T1]
-50.60 dBm
2.390000000 GHz
Marker 4 [T1]
-49.25 dBm
2.359800000 GHz
1 PK
VIEW
D1 4.36 dBm
D2 -15.64 dBm
F2
F1
Center 2.357 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
0.41 dBm
2.377180000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-44.11 dBm
20.255700000 GHz
1 PK
VIEW
D1 4.36 dBm
D2 -15.64 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
2.74 dBm
2.480000000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-45.61 dBm
2.483500000 GHz
Marker 3 [T1]
-44.38 dBm
2.484520000 GHz
Marker 4 [T1]
-50.57 dBm
2.500000000 GHz
1 PK
VIEW
D1 2.74 dBm
D2 -17.26 dBm
F1
F2
Center 2.5268 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-0.57 dBm
2.477060000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-44.20 dBm
20.305640000 GHz
1 PK
VIEW
D1 2.74 dBm
D2 -17.26 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

MODE B FOR 8DPSK

NOTE 1:

The band edge emission plot on the next page shows 51.52dBc between carrier maximum power and local maximum emission in restrict band (2.3196GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 94.81dBuV/m (Peak), so the maximum field strength in restrict band is 94.81 – 51.52 = 43.29dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on the next page shows 51.52dBc between carrier maximum power and local maximum emission in restrict band (2.3196GHz). The emission of carrier strength list in the test result of channel 0 at the item 4.2.7 is 64.81dBuV/m (Average), so the maximum field strength in restrict band is 64.81 –51.52 = 13.29dBuV/m, which is under 54 dBuV/m limit.

NOTE 2:

The band edge emission plot on the next second page shows 44.37dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 94.50dBuV/m (Peak), so the maximum field strength in restrict band is 94.50 –44.37 = 50.13dBuV/m, which is under 74 dBuV/m limit.

The band edge emission plot on the next second page shows 44.37dBc between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 78 at the item 4.2.7 is 64.50dBuV/m (Average), so the maximum field strength in restrict band is 64.50 –44.37 = 20.13dBuV/m, which is under 54 dBuV/m limit.


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
4.49 dBm
2.402400000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-41.82 dBm
2.400000000 GHz
Marker 3 [T1]
-51.77 dBm
2.390000000 GHz
Marker 4 [T1]
-47.03 dBm
2.319600000 GHz
1 PK
VIEW
D1 4.49 dBm
D2 -15.51 dBm
F2
F1
Center 2.357 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
0.96 dBm
2.377180000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-44.10 dBm
22.003600000 GHz
1 PK
VIEW
D1 4.49 dBm
D2 -15.51 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz


*RBW 100 kHz
*VBW 100 kHz
SWT 10 ms
Marker 1 [T1]
3.24 dBm
2.480000000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-41.13 dBm
2.483500000 GHz
Marker 3 [T1]
-41.13 dBm
2.483500000 GHz
Marker 4 [T1]
-49.47 dBm
2.500000000 GHz
1 PK VIEW
D1 3.24 dBm
D2 -16.76 dBm
F1
F2
Center 2.5266 GHz
10 MHz/
Span 100 MHz


*RBW 100 kHz
*VBW 100 kHz
SWT 2.5 s
Marker 1 [T1]
-1.79 dBm
2.477060000 GHz
Ref 20 dBm
*Att 30 dB
Marker 2 [T1]
-44.19 dBm
24.051140000 GHz
1 PK VIEW
D1 3.24 dBm
D2 -16.76 dBm
Start 30 MHz
2.497 GHz/
Stop 25 GHz

4.9 ANTENNA REQUIREMENT

4.9.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.9.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Chip antenna without antenna connector. The maximum gain of this antenna is 2dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

RADIATED EMISSION TEST





6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:
Tel: 886-3-3183232
Fax: 886-3-3185050

Linko RF Lab.
Tel: 886-3-3270910
Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

APPENDIX-A

MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.