

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-------------------------------	----------------

RF Exposure Evaluation

1. RF EXPOSURE EVALUATION METHOD

According to KDB 447498 D01 General RF Exposure Guidance v06, unless specifically required by the *published RF exposure KDB procedures*, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding *SAR Test Exclusion Threshold* condition(s), listed below, is (are) satisfied.

For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

≤ 3.0 for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

EUT	Tablet PC
Frequency band (Operating)	☒ WLAN: 2.412GHz ~ 2.462GHz ☒ WLAN: 5.150GHz ~ 5.250GHz ☒ WLAN: 5.725GHz ~ 5.850GHz ☒ Others BT&BLE(1M&2M):2402-2480MHz,
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW}/\text{cm}^2$) ☒ General Population/Uncontrolled exposure($S=1\text{mW}/\text{cm}^2$)
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	BT(BR+EDR) : 7.38dBm (0.005471W) BLE(1M&2M) : 1.58dBm (0.001439W) 2.4G Wi-Fi : 5.21dBm (0.003319W) 5.2G Wi-Fi : 3.45dBm (0.002214W) 5.8G Wi-Fi : 5.81dBm (0.003811W)
Antenna gain (Max)	2.4G: 0dBi; 5.2G: -0.94dBi; 5.8G: -0.81dBi
Evaluation applied	☐ MPE Evaluation ☒ SAR Evaluation

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-----------------------------------	----------------

2. SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$$f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-------------------------------	----------------

3. Conducted Power Result

Maximum measured transmitter power:

BT(BR+EDR)						
Mode	Frequency	Measured Conducted output power		Target power	Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)	(dBi)	(Linear)
GFSK	2402	6.18	4.15	6 ± 1	0	1.0000
	2441	7.38	5.47	7 ± 1	0	1.0000
	2480	6.16	4.13	6 ± 1	0	1.0000
$\pi/4$ -DQPSK	2402	5.15	3.27	5 ± 1	0	1.0000
	2441	6.04	4.02	6 ± 1	0	1.0000
	2480	4.04	2.54	4 ± 1	0	1.0000
8-DPSK	2402	5.66	3.68	5 ± 1	0	1.0000
	2441	6.56	4.53	6 ± 1	0	1.0000
	2480	4.54	2.84	4 ± 1	0	1.0000

BLE (1M&2M)						
Mode	Frequency	Measured Conducted output power		Target power	Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)	(dBi)	(Linear)
GFSK 1M	2402	0.39	1.09	0 ± 1	0	1.0000
	2441	1.58	1.44	1 ± 1	0	1.0000
	2480	-0.39	0.91	0 ± 1	0	1.0000
GFSK 2M	2402	0.28	1.07	0 ± 1	0	1.0000
	2441	1.43	1.39	1 ± 1	0	1.0000
	2480	-0.57	0.88	0 ± 1	0	1.0000

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-------------------------------	----------------

2.4G WIFI						
Mode	Frequency	Measured Conducted output power		Target power	Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)	(dBi)	(Linear)
IEEE 802.11b	2412	4.87	3.07	4 ± 1	0	1.0000
	2437	4.84	3.05	4 ± 1	0	1.0000
	2462	4.18	2.62	4 ± 1	0	1.0000
IEEE 802.11g	2412	4.13	2.59	4 ± 1	0	1.0000
	2437	4.07	2.55	4 ± 1	0	1.0000
	2462	3.62	2.30	3 ± 1	0	1.0000
IEEE 802.11n HT20	2412	4.41	2.76	4 ± 1	0	1.0000
	2437	4.33	2.71	4 ± 1	0	1.0000
	2462	3.90	2.45	3 ± 1	0	1.0000
IEEE 802.11n HT40	2422	5.21	3.32	5 + 1	0	1.0000
	2437	4.17	2.61	4 ± 1	0	1.0000
	2452	3.54	2.26	3 ± 1	0	1.0000

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-----------------------------------	----------------

5.2G WIFI						
Mode	Frequency	Measured Conducted output power		Target power	Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)	(dBi)	(Linear)
IEEE 802.11a U-NII-1	5180	3.31	2.14	3 ± 1	-0.94	0.8054
	5220	2.14	1.64	2 ± 1	-0.94	0.8054
	5240	3.14	2.06	3 ± 1	-0.94	0.8054
IEEE 802.11n HT20 U-NII-1	5180	3.37	2.17	3 ± 1	-0.94	0.8054
	5220	2.17	1.65	2 ± 1	-0.94	0.8054
	5240	3.44	2.21	3 ± 1	-0.94	0.8054
IEEE 802.11n HT40 U-NII-1	5190	2.74	1.88	2 ± 1	-0.94	0.8054
	5230	2.53	1.79	2 ± 1	-0.94	0.8054
IEEE 802.11ac VHT20 U-NII-1	5180	3.33	2.15	3 ± 1	-0.94	0.8054
	5220	2.25	1.68	2 ± 1	-0.94	0.8054
	5240	3.45	2.21	3 ± 1	-0.94	0.8054
IEEE 802.11ac VHT40 U-NII-1	5190	2.52	1.79	2 ± 1	-0.94	0.8054
	5230	2.49	1.77	2 ± 1	-0.94	0.8054
IEEE 802.11ac VHT80 U-NII-1	5210	1.94	1.56	1 ± 1	-0.94	0.8054

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-----------------------------------	----------------

5.8G WIFI						
Mode	Frequency	Measured Conducted output power		Target power	Antenna gain	
	(MHz)	(dBm)	(mW)	(dBm)	(dBi)	(Linear)
IEEE 802.11a U-NII-3	5745	1.75	1.50	1 ± 1	-0.81	0.8299
	5785	-0.44	0.90	0 ± 1	-0.81	0.8299
	5825	0.32	1.08	0 ± 1	-0.81	0.8299
IEEE 802.11n HT20 U-NII-3	5745	2.09	1.62	2 ± 1	-0.81	0.8299
	5785	-0.12	0.97	0 ± 1	-0.81	0.8299
	5825	0.79	1.20	0 ± 1	-0.81	0.8299
IEEE 802.11n HT40 U-NII-3	5755	1.61	1.45	1 ± 1	-0.81	0.8299
	5795	0.71	1.18	0 ± 1	-0.81	0.8299
IEEE 802.11ac VHT20 U-NII-3	5745	5.81	3.81	5 ± 1	-0.81	0.8299
	5785	-0.10	0.98	0 ± 1	-0.81	0.8299
	5825	0.64	1.16	0 ± 1	-0.81	0.8299
IEEE 802.11ac VHT40 U-NII-3	5755	3.08	2.03	3 ± 1	-0.81	0.8299
	5795	5.27	3.37	5 ± 1	-0.81	0.8299
IEEE 802.11ac VHT80 U-NII-3	5775	1.91	1.55	1 ± 1	-0.81	0.8299

	RF Exposure Evaluation	FCC ID:RIJAF12
--	-------------------------------	----------------

4.Calculated Result and Limit

Mode	Frequency	Max Tune-up Power	Max Tune-up Power	min. test separation distance	[√f(GHz)]	Result	Limit
	(MHz)	(dBm)	(mW)	(mm)		(mW)	(mW)
BT(BR+EDR)	2441	8	6.3096	5	1.562	1.9716	10.0
BLE (1M&2M)	2441	2	1.5849	5	1.562	0.4952	10.0
2.4G WIFI	2422	6	3.9811	5	1.556	1.2391	10.0
5.2G WIFI	5240	4	2.5119	5	2.289	1.1500	7.0
5.8G WIFI	5795	6	3.9811	5	2.407	1.9167	6.0

Note: BT and WLAN can be active at the same time, but only with interleaving of packages switched on board level. That means that they cannot transmit at the same time.

Remark:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \times [\sqrt{f(\text{GHz})}]$$

The test Result is less than 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Conclusion: So, SAR test is not required

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01v06

-----End of RF Exposure Evaluation -----