FCC TEST REPORT

REPORT NO.: RF141024E02

MODEL NO.: 190541

FCC ID: RJE190541

RECEIVED: Oct. 24, 2014

TESTED: Nov. 24 to 27, 2014

ISSUED: Jan. 28, 2015

APPLICANT: Monster, LLC

ADDRESS: 7251 West Lake Mead Blvd. Las Vegas, NV89128-8381, USA

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch Hsin Chu Laboratory

LAB ADDRESS: No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, R.O.C.

TEST LOCATION (1): No. 81-1, Lu Liao Keng, 9th Ling,Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.

TEST LOCATION (2): No.49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan, Taiwan, R.O.C.

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4
1 CERTIFICATION 5
2 SUMMARY OF TEST RESULTS 6
2.1 MEASUREMENT UNCERTAINTY 7
3 GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 DESCRIPTION OF TEST MODES 9
3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL: 10
3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 12
3.5 DESCRIPTION OF SUPPORT UNITS 13
3.6 CONFIGURATION OF SYSTEM UNDER TEST 13
4 TEST PROCEDURES AND RESULTS 14
4.1 CONDUCTED EMISSION MEASUREMENT 14
4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 14
4.1.2 TEST INSTRUMENTS 14
4.1.3 TEST PROCEDURES 15
4.1.4 DEVIATION FROM TEST STANDARD 15
4.1.5 TEST SETUP 15
4.1.6 EUT OPERATING CONDITIONS 16
4.1.7 TEST RESULTS 17
4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT 19
4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 19
4.2.2 TEST INSTRUMENTS 20
4.2.3 TEST PROCEDURES 21
4.2.4 DEVIATION FROM TEST STANDARD 21
4.2.5 TEST SETUP 22
4.2.6 EUT OPERATING CONDITIONS 22
4.2.7 TEST RESULTS 23
4.3 NUMBER OF HOPPING FREQUENCY USED 30
4.3.1 LIMIT OF HOPPING FREQUENCY USED 30
4.3.2 TEST INSTRUMENTS 30
4.3.3 TEST PROCEDURES 30
4.3.4 DEVIATION FROM TEST STANDARD 30
4.3.5 TEST SETUP 31
4.3.6 TEST RESULTS 31
4.4 DWELL TIME ON EACH CHANNEL 32
4.4.1 LIMIT OF DWELL TIME USED 32
4.4.2 TEST INSTRUMENTS 32
4.4.3 TEST PROCEDURES 32
4.4.4 DEVIATION FROM TEST STANDARD 33
4.4.5 TEST SETUP 33
4.4.6 TEST RESULTS 34
4.5 CHANNEL BANDWIDTH 38

4.5.1 LIMITS OF CHANNEL BANDWIDTH 38
4.5.2 TEST INSTRUMENTS 38
4.5.3 TEST PROCEDURE 38
4.5.4 DEVIATION FROM TEST STANDARD 38
4.5.5 TEST SETUP 39
4.5.6 EUT OPERATING CONDITION 39
4.5.7 TEST RESULTS 40
4.6 HOPPING CHANNEL SEPARATION 41
4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION 41
4.6.2 TEST INSTRUMENTS 41
4.6.3 TEST PROCEDURES 41
4.6.4 DEVIATION FROM TEST STANDARD 41
4.6.5 TEST SETUP 41
4.6.6 TEST RESULTS 42
4.7 MAXIMUM PEAK OUTPUT POWER 43
4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT 43
4.7.2 INSTRUMENTS 43
4.7.3 TEST PROCEDURES 43
4.7.4 DEVIATION FROM TEST STANDARD 43
4.7.5 TEST SETUP 44
4.7.6 EUT OPERATING CONDITION 44
4.7.7 TEST RESULTS 45
4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT 46
4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT 46
4.8.2 TEST INSTRUMENTS 46
4.8.3 TEST PROCEDURE 46
4.8.4 DEVIATION FROM TEST STANDARD 46
4.8.5 TEST SETUP 46
4.8.6 EUT OPERATING CONDITION 46
4.8.7 TEST RESULTS 47
5 PHOTOGRAPHS OF THE TEST CONFIGURATION 50
6 INFORMATION ON THE TESTING LABORATORIES 51
7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB 52

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF141024E02	Original release	Jan. 28, 2015

1 CERTIFICATION

PRODUCT :	Bluetooth Noise Cancellation headphone
BRAND NAME :	CHANEL
MODEL NO. :	190541
TEST SAMPLE :	ENGINEERING SAMPLE
APPLICANT :	Monster, LLC
TESTED :	Nov. 24 to 27, 2014
STANDARDS :	FCC Part 15, Subpart C (Section 15.247) ANSI C63.10-2009

The above equipment (Model: 190541) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared By : _____ , **Date:** Jan. 28, 2015
(Midoli Peng, Specialist)

Approved By : _____ , **Date:** Jan. 28, 2015
(May Chen, Manager)

2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**REMARK**
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -6.60dB at 0.59141MHz.
15.247(a)(1) (iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1) (iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)	Transmitter Radiated Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -3.7dB at 539.98MHz
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

NOTE: Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions	2.86 dB
Radiated emissions (30MHz-1GHz)	5.37 dB
Radiated emissions (1GHz -6GHz)	3.65 dB
Radiated emissions (6GHz -18GHz)	3.88 dB
Radiated emissions (18GHz -40GHz)	4.11 dB

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Bluetooth Noise Cancellation headphone
MODEL NO.	190541
POWER SUPPLY	DC 5V from USB interface or DC 3.7V from battery
MODULATION TYPE	GFSK, π/4-DQPSK, 8DPSK
MODULATION TECHNOLOGY	FHSS
DATE RATE	Up to 3Mbps
FREQUENCY RANGE	2402MHz ~ 2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	3.304 mW
ANTENNA TYPE	PCB antenna (Gain: -5.76 dBi)
DATA CABLE	USB cable (Unshielded, 1.2m) x 1 Audio cable (Unshielded, 1.2m) x 1
I/O PORTS	Refer to user's manual
ASSOCIATED DEVICES	NA

Note:

1. The EUT could be supplied with battery, please refer to the following table:

Brand Name	Model	Rating
SHENZHEN NEW LIGHT ENERGY CO LTD	XHP383847	3.7V 750mAh

2. The EUT was pre-tested under following test modes:

Pre-test Mode	Description
Mode A	**Power from USB interface**
Mode B	Power from Battery

From the above modes, the worst radiated emission was found in **Mode A**. Therefore only the test data of the modes were recorded in this report individually.

3. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 DESCRIPTION OF TEST MODES

79 channels are provided for BT-EDR mode

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

3.3 TEST MODE APPLICABLITY AND TESTED CHANNEL DETAIL:

EUT CONFIGURE MODE	APPLICABLE TO					DESCRIPTION
	PLC	RE < 1G	RE ≥ 1G	APCM	OB	
-	√	√	√	√	√	-

Where **PLC:** Power Line Conducted Emission **RE < 1G:** Radiated Emission below 1GHz

RE ≥ 1G: Radiated Emission above 1GHz **APCM:** Antenna Port Conducted Measurement

OB: Conducted Out-Band Emission Measurement

NOTE: 1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane.**

POWER LINE CONDUCTED EMISSION:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	GFSK	DH5

RADIATED EMISSION TEST (BELOW 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	78	FHSS	GFSK	DH5

RADIATED EMISSION TEST (ABOVE 1 GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

CONDUCTED OUT-BAND EMISSION MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
0 to 78	0, 78	FHSS	GFSK	DH5
0 to 78	0, 78	FHSS	8DPSK	3DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
PLC	25deg. C,71%RH	120Vac, 60Hz	Wythe Lin
RE<1G	23deg. C, 67%RH	120Vac, 60Hz	Robert Cheng
RE≥1G	24deg. C, 69%RH	120Vac, 60Hz	Tim Ho
APCM	25deg. C, 60%RH	120Vac, 60Hz	Andy Ho
OB	25deg. C, 60%RH	120Vac, 60Hz	Andy Ho

3.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)
ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.

Note: The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID	Remark
A	iPod shuffle	Apple	MD778TA/A	CC4JMCMXF4T1	NA	Provided by Lab
B	TEST TOOL	CHANEL	NA	NA	NA	Supplied by client
C	ADAPTER	NICELINK	US-T12B(W)	NA	NA	Provided by Lab

NOTE:

1. All power cords of the above support units are non-shielded (1.8 m).

No.	Cable	Qty.	Length (m)	Shielded (Yes/ No)	Cores (Number)	Remark
1.	USB	1	1.2	No	0	Supplied by client
2.	Audio	1	1.2	No	0	Supplied by client
3.	Cable	5	0.1	No	0	Supplied by client

3.6 CONFIGURATION OF SYSTEM UNDER TEST



4 TEST PROCEDURES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS 30	100375	Apr. 29, 2014	Apr. 28, 2015
Line-Impedance Stabilization Network (for EUT) SCHWARZBECK	NSLK-8127	8127-522	Sep. 15, 2014	Sep. 14, 2015
Line-Impedance Stabilization Network (for Peripheral) ROHDE & SCHWARZ	ENV216	100071	Nov. 10, 2014	Nov. 09, 2015
RF Cable (JYEBAO)	5DFB	COCCAB-001	Mar. 10 , 2014	Mar. 09, 2015
50 ohms Terminator	N/A	EMC-03	Sep. 22, 2014	Sep. 21, 2015
50 ohms Terminator	N/A	EMC-02	Sep. 30, 2014	Sep. 29, 2015
Software ADT	BV ADT_Cond_V7.3.7.3	NA	NA	NA

Note:
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3 The VCCI Con C Registration No. is C-3611.
4 Tested Date: Nov. 27, 2014

4.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN.
b. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
c. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
d. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit – 20dB) were not recorded.

NOTE: The resolution bandwidth of test receiver is 9kHz for Quasi-peak detection (QP) & Average detection (AV).

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

1. Placed the EUT on testing table.
2. Controlling software “BlueTest3_2_5_8_667.exe” has been activated to set the EUT under transmission/receiving condition continuously.

4.1.7 TEST RESULTS

PHASE	Line (L)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

	Freq.	Corr.	Reading Value		Emission Level		Limit		Margin	
No		Factor	[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
	[MHz]	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.23594	0.07	28.82	21.22	28.89	21.29	62.24	52.24	-33.34	-30.94
2	**0.59141**	**0.10**	**49.27**	**39.30**	**49.37**	**39.40**	**56.00**	**46.00**	**-6.63**	**-6.60**
3	1.18266	0.14	42.64	32.73	42.78	32.87	56.00	46.00	-13.22	-13.13
4	2.96875	0.21	28.06	21.05	28.27	21.26	56.00	46.00	-27.73	-24.74
5	7.60156	0.37	34.72	28.20	35.09	28.57	60.00	50.00	-24.91	-21.43
6	20.79688	0.72	26.96	13.40	27.68	14.12	60.00	50.00	-32.32	-35.88

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



PHASE	Neutral (N)	DETECTOR FUNCTION	Quasi-Peak (QP) / Average (AV)

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)] Q.P.	Reading Value [dB (uV)] AV.	Emission Level [dB (uV)] Q.P.	Emission Level [dB (uV)] AV.	Limit [dB (uV)] Q.P.	Limit [dB (uV)] AV.	Margin (dB) Q.P.	Margin (dB) AV.
1	0.49766	0.10	32.84	27.22	32.94	27.32	56.04	46.04	-23.10	-18.72
2	0.59141	0.10	43.62	38.01	43.72	38.11	56.00	46.00	-12.28	-7.89
3	1.17188	0.14	36.16	24.78	36.30	24.92	56.00	46.00	-19.70	-21.08
4	2.61719	0.20	28.97	17.65	29.17	17.85	56.00	46.00	-26.83	-28.15
5	7.66797	0.38	26.32	19.55	26.70	19.93	60.00	50.00	-33.30	-30.07
6	20.80469	0.76	27.75	14.42	28.51	15.18	60.00	50.00	-31.49	-34.82

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission Level – Limit value
4. Correction Factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value



4.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
MXE EMI Receiver Agilent	N9038A	MY51210105	July 21, 2014	July 20, 2015
Pre-Amplifier Mini-Circuits	ZFL-1000VH2 B	AMP-ZFL-03	Nov. 12, 2014	Nov. 11, 2015
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-360	Feb. 26, 2014	Feb. 25, 2015
RF Cable	NA	CHGCAB_001	Oct. 04, 2014	Oct. 03, 2015
Horn_Antenna AISI	AIH.8018	0000320091110	Aug. 27, 2014	Aug. 26, 2015
Pre-Amplifier Agilent	8449B	3008A02578	June 24, 2014	June 23, 2015
RF Cable	NA	131205 131214 SNMY23684/4	Jan. 17, 2014	Jan. 16, 2015
Spectrum Analyzer R&S	FSV40	100964	July 05, 2014	July 04, 2015
Pre-Amplifier EMCI	EMC184045	980143	Jan. 17, 2014	Jan. 16, 2015
Horn_Antenna SCHWARZBECK	BBHA 9170	9170-424	Aug. 26, 2014	Aug. 25, 2015
RF Cable	NA	RF104-121 RF104-204	Dec. 12, 2013	Dec. 11, 2014
Antenna Tower & Turn Table CT	NA	NA	NA	NA

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
5 The VCCI Site Registration No. is G-137.
6 The CANADA Site Registration No. is IC 7450H-2.
7 Tested Date: Nov. 24 to 25, 2014

4.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

f. The test-receiver system was set to peak detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 1MHz for Peak detection at frequency above 1GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

BT_GFSK

CHANNEL	TX Channel 78	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	Below 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	112.01	30.1 QP	43.5	-13.4	1.50 H	265	45.89	-15.75
2	392.00	36.0 QP	46.0	-10.0	1.00 H	54	45.35	-9.39
3	468.00	38.9 QP	46.0	-7.1	1.50 H	223	46.26	-7.34
4	499.97	40.3 QP	46.0	-5.7	1.50 H	119	47.02	-6.75
5	**539.98**	**42.3 QP**	**46.0**	**-3.7**	**1.50 H**	**225**	**48.19**	**-5.92**
6	568.01	39.1 QP	46.0	-6.9	1.50 H	323	44.49	-5.39
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	**FREQ. (MHz)**	**EMISSION LEVEL (dBuV/m)**	**LIMIT (dBuV/m)**	**MARGIN (dB)**	**ANTENNA HEIGHT (m)**	**TABLE ANGLE (Degree)**	**RAW VALUE (dBuV)**	**CORRECTION FACTOR (dB/m)**
1	33.78	36.2 QP	40.0	-3.8	1.00 V	228	50.24	-14.06
2	107.12	30.0 QP	43.5	-13.5	1.50 V	325	46.32	-16.30
3	459.95	35.4 QP	46.0	-10.7	1.50 V	179	42.85	-7.50
4	492.11	38.4 QP	46.0	-7.6	1.00 V	360	45.32	-6.88
5	560.06	38.3 QP	46.0	-7.7	1.00 V	67	43.77	-5.49
6	579.99	38.2 QP	46.0	-7.8	1.00 V	78	43.12	-4.93

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.9 PK	74.0	-29.1	1.09 H	205	47.37	-2.47
2	2390.00	14.8 AV	54.0	-39.2	1.09 H	205	17.27	-2.47
3	*2402.00	88.0 PK			1.09 H	205	90.41	-2.41
4	*2402.00	57.9 AV			1.09 H	205	60.31	-2.41
5	4804.00	56.6 PK	74.0	-17.4	1.39 H	268	50.98	5.62
6	4804.00	26.5 AV	54.0	-27.5	1.39 H	268	20.88	5.62
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	43.2 PK	74.0	-30.8	1.20 V	318	45.67	-2.47
2	2390.00	13.1 AV	54.0	-40.9	1.20 V	318	15.57	-2.47
3	*2402.00	85.5 PK			1.20 V	318	87.91	-2.41
4	*2402.00	55.4 AV			1.20 V	318	57.81	-2.41
5	4804.00	51.2 PK	74.0	-22.8	1.00 V	341	45.58	5.62
6	4804.00	21.1 AV	54.0	-32.9	1.00 V	341	15.48	5.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	91.4 PK			1.11 H	198	93.64	-2.24
2	*2441.00	61.3 AV			1.11 H	198	63.54	-2.24
3	4882.00	56.7 PK	74.0	-17.3	1.49 H	248	50.76	5.94
4	4882.00	26.6 AV	54.0	-27.4	1.49 H	248	20.66	5.94
5	7323.00	54.2 PK	74.0	-19.8	1.00 H	79	41.02	13.18
6	7323.00	24.1 AV	54.0	-29.9	1.00 H	79	10.92	13.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	88.9 PK			1.15 V	303	91.14	-2.24
2	*2441.00	58.8 AV			1.15 V	303	61.04	-2.24
3	4882.00	50.5 PK	74.0	-23.5	1.03 V	343	44.56	5.94
4	4882.00	20.4 AV	54.0	-33.6	1.03 V	343	14.46	5.94
5	7323.00	55.0 PK	74.0	-19.0	1.00 V	338	41.82	13.18
6	7323.00	24.9 AV	54.0	-29.1	1.00 V	338	11.72	13.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	94.1 PK			1.14 H	190	96.16	-2.06
2	*2480.00	64.0 AV			1.14 H	190	66.06	-2.06
3	2483.50	46.8 PK	74.0	-27.2	1.14 H	190	48.83	-2.03
4	2483.50	16.7 AV	54.0	-37.3	1.14 H	190	18.73	-2.03
5	4960.00	56.4 PK	74.0	-17.6	1.43 H	254	50.14	6.26
6	4960.00	26.3 AV	54.0	-27.7	1.43 H	254	20.04	6.26
7	7440.00	54.7 PK	74.0	-19.3	1.00 H	85	41.57	13.13
8	7440.00	24.6 AV	54.0	-29.4	1.00 H	85	11.47	13.13
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	91.6 PK			1.18 V	303	93.66	-2.06
2	*2480.00	61.5 AV			1.18 V	303	63.56	-2.06
3	2483.50	45.4 PK	74.0	-28.6	1.18 V	303	47.43	-2.03
4	2483.50	15.3 AV	54.0	-38.7	1.18 V	303	17.33	-2.03
5	4960.00	51.0 PK	74.0	-23.0	1.00 V	342	44.74	6.26
6	4960.00	20.9 AV	54.0	-33.1	1.00 V	342	14.64	6.26
7	7440.00	54.5 PK	74.0	-19.5	1.00 V	352	41.37	13.13
8	7440.00	24.4 AV	54.0	-29.6	1.00 V	352	11.27	13.13

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.3 PK	74.0	-29.7	1.13 H	210	46.77	-2.47
2	2390.00	14.2 AV	54.0	-39.8	1.13 H	210	16.67	-2.47
3	*2402.00	87.0 PK			1.13 H	210	89.41	-2.41
4	*2402.00	56.9 AV			1.13 H	210	59.31	-2.41
5	4804.00	56.6 PK	74.0	-17.4	1.41 H	259	50.98	5.62
6	4804.00	26.5 AV	54.0	-27.5	1.41 H	259	20.88	5.62
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	43.2 PK	74.0	-30.8	1.20 V	327	45.67	-2.47
2	2390.00	13.1 AV	54.0	-40.9	1.20 V	327	15.57	-2.47
3	*2402.00	84.6 PK			1.20 V	327	87.01	-2.41
4	*2402.00	54.5 AV			1.20 V	327	56.91	-2.41
5	4804.00	51.4 PK	74.0	-22.6	1.02 V	341	45.78	5.62
6	4804.00	21.3 AV	54.0	-32.7	1.02 V	341	15.68	5.62

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	90.4 PK			1.13 H	218	92.64	-2.24
2	*2441.00	60.3 AV			1.13 H	218	62.54	-2.24
3	4882.00	56.7 PK	74.0	-17.3	1.44 H	240	50.76	5.94
4	4882.00	26.6 AV	54.0	-27.4	1.44 H	240	20.66	5.94
5	7323.00	54.7 PK	74.0	-19.3	1.00 H	69	41.52	13.18
6	7323.00	24.6 AV	54.0	-29.4	1.00 H	69	11.42	13.18
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	87.9 PK			1.18 V	339	90.14	-2.24
2	*2441.00	57.8 AV			1.18 V	339	60.04	-2.24
3	4882.00	51.1 PK	74.0	-22.9	1.00 V	350	45.16	5.94
4	4882.00	21.0 AV	54.0	-33.0	1.00 V	350	15.06	5.94
5	7323.00	54.3 PK	74.0	-19.7	1.00 V	341	41.12	13.18
6	7323.00	24.2 AV	54.0	-29.8	1.00 V	341	11.02	13.18

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.6 PK			1.10 H	200	94.66	-2.06
2	*2480.00	62.5 AV			1.10 H	200	64.56	-2.06
3	2483.50	46.5 PK	74.0	-27.5	1.10 H	200	48.53	-2.03
4	2483.50	16.4 AV	54.0	-37.6	1.10 H	200	18.43	-2.03
5	4960.00	56.4 PK	74.0	-17.6	1.43 H	261	50.14	6.26
6	4960.00	26.3 AV	54.0	-27.7	1.43 H	261	20.04	6.26
7	7440.00	54.5 PK	74.0	-19.5	1.00 H	91	41.37	13.13
8	7440.00	24.4 AV	54.0	-29.6	1.00 H	91	11.27	13.13

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	90.1 PK			1.25 V	320	92.16	-2.06
2	*2480.00	60.0 AV			1.25 V	320	62.06	-2.06
3	2483.50	45.2 PK	74.0	-28.8	1.25 V	320	47.23	-2.03
4	2483.50	15.1 AV	54.0	-38.9	1.25 V	320	17.13	-2.03
5	4960.00	50.9 PK	74.0	-23.1	1.02 V	350	44.64	6.26
6	4960.00	20.8 AV	54.0	-33.2	1.02 V	350	14.54	6.26
7	7440.00	55.1 PK	74.0	-18.9	1.00 V	356	41.97	13.13
8	7440.00	25.0 AV	54.0	-29.0	1.00 V	356	11.87	13.13

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: 20log(3.125 / 100)= -30.1 dB
7. Average value = peak reading + 20log(duty cycle).

4.3 NUMBER OF HOPPING FREQUENCY USED

4.3.1 LIMIT OF HOPPING FREQUENCY USED

At least 15 hopping frequencies, and should be equally spaced.

4.3.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.3.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.

d. Set the SA on View mode and then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 TEST RESULTS

There are 79 hopping frequencies in the hopping mode. Please refer the test result. On the plots, it shows that the hopping frequencies are equally spaced.

GFSK



8DPSK



4.4 DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.4.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.

c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.

d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.

e. Repeat above procedures until all different time-slot modes have been completed.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 TEST RESULTS

For GFSK:

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
DH1	50 (times / 5 sec) *6.32=316 times	0.465	146.94	400
DH3	25 (times / 5 sec) *6.32=158 times	1.711	270.34	400
DH5	17 (times / 5 sec) *6.32=107.44 times	3.026	325.11	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1


RBW 100 kHz
VBW 100 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dU
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 100 kHz
SWT 3 ms
[T1] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dU
Marker 1 [T1]
-70.08 dBm
1.248000 ms
Delta 2 [T1]
1.70 dB
465.000000 us
Center 2.441 GHz
300 us/

DH3


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dU
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dU
Marker 1 [T1]
-66.97 dBm
1.630000 ms
Delta 2 [T1]
6.34 dB
1.711000 ms
Center 2.441 GHz
500 us/

DH5


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dU
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 0 ms
[T1] MP VIEW
Ref 21 dBm
Att 20 dB
Offset 11 dU
Marker 1 [T1]
-69.03 dBm
2.458000 ms
Delta 2 [T1]
2.25 dB
3.026000 ms
Center 2.441 GHz
800 us/

For 8DPSK:

Mode	Number of transmission in a 31.6 (79Hopping*0.4)	Length of transmission time (msec)	Result (msec)	Limit (msec)
3DH1	50 (times / 5 sec) *6.32=316 times	0.487	153.89	400
3DH3	25 (times / 5 sec) *6.32=158 times	1.747	276.03	400
3DH5	17 (times / 5 sec) *6.32=107.44 times	3.003	322.64	400

NOTE: Test plots of the transmitting time slot are shown on next page.

DH1


RBW 100 kHz
VBW 100 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 100 kHz
SWT 3 ms
[T1] MP VIEW
Marker 1 [T1]
-74.10 dBm
1.239000 ms
Delta 2 [T1]
9.75 dB
487.000000 us
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
300 us/

DH3


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 5 ms
[T1] MP VIEW
Marker 1 [T1]
-68.83 dBm
1.594000 ms
Delta 2 [T1]
3.52 dB
1.747000 ms
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
600 us/

DH5


RBW 100 kHz
VBW 300 kHz
SWT 5 s
[T1] MP CLRWR
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
500 ms/


RBW 100 kHz
VBW 300 kHz
SWT 8 ms
[T1] MP VIEW
Marker 1 [T1]
-71.27 dBm
2.458000 ms
Delta 2 [T1]
2.55 dB
3.003000 ms
Ref 21 dBm
Att 20 dB
Offset 11 dB
Center 2.441 GHz
800 us/

4.5 CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.5.3 TEST PROCEDURE

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.

d. Repeat above procedures until all frequencies measured were complete.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.5.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	20dB BANDWIDTH (MHz)	
		GFSK	8DPSK
0	2402	0.87	1.31
39	2441	0.88	1.33
78	2480	0.88	1.28

SPECTRUM PLOT OF WORST VALUE	
GFSK / CH78	8DPSK / CH39
	

4.6 HOPPING CHANNEL SEPARATION

4.6.1 LIMIT OF HOPPING CHANNEL SEPARATION

At least 25 kHz or two-thirds of 20dB hopping channel bandwidth (whichever is greater).

4.6.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.6.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.

c. By using the MaxHold function record the separation of two adjacent channels.

d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.

e. Repeat above procedures until all frequencies measured were complete.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 TEST SETUP



4.6.6 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)		20dB BANDWIDTH (MHz)		MINIMUM LIMIT (MHz)		PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	0.87	1.31	0.58	0.88	PASS
39	2441	1.01	1.00	0.88	1.33	0.59	0.89	PASS
78	2480	1.01	1.01	0.88	1.28	0.59	0.86	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

SPECTRUM PLOT OF WORST VALUE	
GFSK / CH39	8DPSK / CH78
	

4.7 MAXIMUM PEAK OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Limit is 125mW.

4.7.2 INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.7.3 TEST PROCEDURES

a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.

b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.

c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.

d. Measure the captured power within the band and recording the plot.

e. Repeat above procedures until all frequencies required were complete.

4.7.4 DEVIATION FROM TEST STANDARD

No deviation

4.7.5 TEST SETUP



For the actual test configuration, please refer to the related Item – Photographs of the Test Configuration.

4.7.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.7.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	OUTPUT POWER (mW)		OUTPUT POWER (dBm)		POWER LIMIT (mW)	PASS / FAIL
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	1.047	0.944	0.20	-0.25	125	PASS
39	2441	2.239	2.032	3.50	3.08	125	PASS
78	2480	3.304	2.312	5.19	3.64	125	PASS

SPECTRUM PLOT OF WORST VALUE	
GFSK / CH78	8DPSK / CH78
	

4.8 CONDUCTED OUT-BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF CONDUCTED OUT-BAND EMISSION MEASUREMENT

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.8.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
SPECTRUM ANALYZER R&S	FSP 40	100060	May 08, 2014	May 07, 2015

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. Tested date : Nov. 24, 2014

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set RBW a of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation

4.8.5 TEST SETUP



4.8.6 EUT OPERATING CONDITION

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.8.7 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.

GFSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





8DPSK

Hopping disabled_ Low Channel





Hopping disabled_ High Channel





Hopping enabled_ Low Channel





Hopping enabled_ High Channel





5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).

6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC/RF/Telecom Lab:
Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab:
Tel: 886-3-3183232
Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

7 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No modifications were made to the EUT by the lab during the test.

--- END ---