FCC Test Report

Part 15 subpart C

Client Information:

Applicant: Monster, LLC

Applicant add.: 3837 Bay Lake Trail, Suite 103, North Las Vegas, NV 89030 USA

Product Information:

Product Name: Bluetooth Speaker

Model No.: 191304

Derivative model No.: N/A

Brand Name: MONSTER

FCC ID: RJE191304

Standards:

CFR 47 FCC PART 15 SUBPART C:2017 section 15.247

Prepared By:

Dongguan Yaxu (AiT) Technology Limited

Add. : No.22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan, Guangdong, China

Date of Receipt:	Feb. 25, 2017	Date of Test:	Feb. 05~Mar. 03, 2017
Date of Issue:	Mar. 04, 2017	Test Result:	Pass

This device described above has been tested by Dongguan Yaxu(AiT) Technology Limited, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

Reviewed by: Seal-Chen **Approved by:**

1 Contents

Page

COVER PAGE

1 CONTENTS 2

2 TEST SUMMARY 4

2.1 COMPLIANCE WITH FCC PART 15 SUBPART C 4
2.2 TEST LOCATION 4
2.3 MEASUREMENT UNCERTAINTY 5

3 TEST FACILITY 6

3.1 DEVIATION FROM STANDARD 6
3.2 ABNORMALITIES FROM STANDARD CONDITIONS 6

4 GENERAL INFORMATION 7

4.1 GENERAL DESCRIPTION OF EUT 7
4.2 DESCRIPTION OF TEST CONDITIONS 9
4.3 TEST PERIPHERAL LIST 10
4.4 EUT PERIPHERAL LIST 10

5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11

6 TEST RESULT 12

6.1 ANTENNA REQUIREMENT 12
6.1.1 Standard requirement 12
6.1.2 EUT Antenna 12
6.2 CONDUCTION EMISSIONS MEASUREMENT 13
6.2.1 Applied procedures / Limit 13
6.2.2 Test procedure 13
6.2.3 Test setup 13
6.2.4 Test results 14
6.3 RADIATED EMISSIONS MEASUREMENT 16
6.3.1 Applied procedures / Limit 16
6.3.2 Test setup 17
6.3.3 Test procedure 19
6.3.4 Test Result 20
6.3.5 TEST RESULTS (Restricted Bands Requirements) 35
6.4 BANDWIDTH TEST 36
6.4.1 Applied procedures / Limit 36
6.4.2 Test procedure 36
6.4.3 Deviation from standard 36
6.4.4 Test setup 36
6.4.5 Test results 37
6.5 CARRIER FREQUENCIES SEPARATED 43

6.5.1 Applied procedures / Limit 43
6.5.2 Test procedure 43
6.5.3 Deviation from standard 43
6.5.4 Test setup 43
6.5.5 Test results 44
6.6 HOPPING CHANNEL NUMBER 48
6.6.1 Applied procedures / Limit 48
6.6.2 Test procedure 48
6.6.3 Deviation from standard 48
6.6.4 Test setup 48
6.6.5 Test result 49
6.7 DWELL TIME 51
6.7.1 Applied procedures / Limit 51
6.7.2 Test procedure 51
6.7.3 Deviation from standard 51
6.7.4 Test setup 51
6.7.5 Test result 52
6.8 MAXIMUM PEAK OUTPUT POWER 56
6.8.1 Applied procedures / Limit 56
6.8.2 Test procedure 56
6.8.3 Deviation from standard 56
6.8.4 Test setup 56
6.8.5 Test results 57
6.9 BAND EDGE 63
6.9.1 Applied procedures / Limit 63
6.9.2 Test procedure 63
6.9.3 Deviation from standard 63
6.9.4 Test setup 63
6.9.5 Test results 64
6.10 CONDUCTED SPURIOUS EMISSIONS 68
6.10.1 Applied procedures / Limit 68
6.10.2 Test procedure 68
6.10.3 Deviation from standard 68
6.10.4 Test setup 68
6.10.5 Test results 69
6.11 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 81
6.11.1 Standard requirement 81
6.11.2 Other requirements Frequency Hopping Spread Spectrum System 82

7 PHOTOGRAPHS 84

7.1 RADIATED EMISSION TEST SETUP 84
7.2 CONDUCTED EMISSIONS TEST SETUP 85
7.3 EUT CONSTRUCTIONAL DETAILS 86

2 Test Summary

2.1 Compliance with FCC Part 15 subpart C

Test	Test Requirement	Standard Paragraph	Result
Antenna Requirement	FCC Part 15 C:2017	Section 15.247(c)	**PASS**
Conduction Emissions	FCC Part 15 C:2017	Section 15.207(a)	**PASS**
Radiated Emissions	FCC Part 15 C:2017	Section 15.247(d)	**PASS**
Carrier Frequencies Separated	FCC Part 15 C:2017	Section 15.247(a)(1)	**PASS**
Hopping Channel Number	FCC Part 15 C:2017	Section 15.247(a)(1) (iii)	**PASS**
Dwell Time	FCC Part 15 C:2017	Section 15.247(a)(1) (iii)	**PASS**
Maximum Peak Output Power	FCC Part 15 C:2017	Section 15.247(b)	**PASS**
Band edge	FCC Part 15 C:2017	Section 15.247(d)	**PASS**
Conducted Spurious Emissions	FCC Part 15 C:2017	Section 15.247(d)	**PASS**
Pseudorandom Frequency Hopping Sequence	FCC Part 15 C:2017	Section 15.247(g), (h)	**PASS**
Note:			
	(1) Reference to the ANSI C63.10:2013.		

2.2 Test Location

All tests were performed at:

Dongguan Yaxu (AiT) Technology Limited
No.22, Jinqianling Third Street, Jitigang, Huangjiang,Dongguan, Guangdong, China
Tel.: +86.769.82020499 Fax.: +86.769.82020495

2.3 Measurement Uncertainty

All measurements involve certain levels of uncertainties, the maximum value of the uncertainty as below:

No.	Item	Uncertainty
1	Conducted Emission Test	1.20dB
2	Radiated Emission Test	3.30dB
3	RF power,conducted	0.16dB
4	RF power density,conducted	0.24dB
5	Spurious emissions,conducted	0.21dB
6	All emissions,radiated(<1G)	4.68dB
7	All emissions,radiated(>1G)	4.89dB

3 Test Facility

The test facility is recognized, certified or accredited by the following organizations:

.CNAS- Registration No: L6177

Dongguan Yaxu (AiT) technology Limited is accredited to ISO/IEC 17025:2005 general Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the competence of testing and calibration laboratories) on Apr. 18, 2013

.FCC- Registration No: 248337

The 3m Semi-Anechoic Chamber, 3m/10m Open Area Test Site and Shielding Room of Dongguan Yaxu (AiT) Technology Limited have been registered by Federal Communications Commission (FCC) on Aug.29, 2014.

.Industry Canada(IC)-Registration No: IC6819A-1

The 3m Semi-Anechoic Chamber and 3m/10m Open Area Test Site of Dongguan Yaxu (AiT) Technology Limited have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing on Oct. 12, 2014.

3.1 Deviation from standard

None

3.2 Abnormalities from standard conditions

None

4 General Information

4.1 General Description of EUT

Manufacturer:	Monster, LLC
Manufacturer Address:	3837 Bay Lake Trail, Suite 103, North Las Vegas, NV 89030 USA
EUT Name:	Bluetooth Speaker
Model No:	191304
Brand Name:	MONSTER
Serial No:	N/A
Operation frequency:	2402 MHz to 2480 MHz
NUMBER OF CHANNEL:	79
Modulation Technology:	GFSK, π/4-DQPSK, 8DPSK(1/2/3Mbps)
Bluetooth version:	4.2+EDR (without BLE)
H/W No.:	V0.1
S/W No.:	V1.0
Antenna Type:	PCB antenna
Antenna Gain:	Maximum 0 dBi
Power Supply Range:	DC 5V from micro-USB or DC 3.7V from battery
Power Supply:	The same as above.
Power Cord:	0.6 m x 2 wires unscreened USB cable
Output power（max）:	1Mbps：5.07dBm
	3Mbps：3.96dBm
Note:	
1.	For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

Description of Channel:					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

4.2 Description of Test conditions

(1) EUT was tested in normal configuration (Please See following Block diagram)

1. Block diagram of EUT configuration(TX Mode)

Note:
1. The EUT was programmed to be in continuously transmitting mode with fully-charged battery and the transmit duty cycle is not less than 98%.
2. Using the notebook and the transform board to control the fixed transmitting frequency and other test mode. After finishing the test setting, the notebook and the transform board will be removed during measurements.

(2) E.U.T. test conditions:

15.31(e): For intentional radiators, measurements of the variation of the input power or the adiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

(3) Test frequencies:

According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and. If required reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

(4) Frequency range of radiated measurements:

According to the 15.33, the test range will be up to the tenth harmonic of the highest fundamental frequency.

(5) Pre-test the EUT in all transmitting mode at the lowest (2402 MHz), middle (2441 MHz) and highest (2480 MHz) channel with different data packet and conducted to determine the worst-case mode, only the worst-case results(1Mbps/3Mbps) are recorded in this report.

4.3 Test Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	Remark
1	Notebook	ASUS	N/A	X401A	X16-96072	N/A	N/A
2	USB line	N/A	N/A	N/A	N/A	0.3m/unshielded /detachable	N/A
3	Transform board	N/A	N/A	N/A	N/A	N/A	N/A
4	Adapter	N/A	N/A	Adapter1	N/A	1.0m/unshielded /detachable(USB)	Supply by lab

4.4 EUT Peripheral List

No.	Equipment	Manufacturer	EMC Compliance	Model No.	Serial No.	Power cord	Remark
1	USB cable	N/A	N/A	N/A	N/A	0.6m/shielded /detachable	N/A

5 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	SIGNAL ANALYZER	R&S	FSV40	101470	2016.06.29	2017.06.28
2	EMI Measuring Receiver	R&S	ESR	101660	2016.06.29	2017.06.28
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2016.06.29	2017.06.28
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2016.06.29	2017.06.28
5	TRILOG Super Broadband test Antenna	SCHWARZBECK	VULB9160	9160-3206	2016.06.29	2017.06.28
6	Broadband Horn Antenna	SCHWARZBECK	BBHA9120D	452	2016.06.29	2017.06.28
7	SHF-EHF Horn	SCHWARZBECK	BBHA9170	BBHA9170367	2016.06.29	2017.06.28
8	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2016.06.29	2017.06.28
9	EMI Test Receiver	R&S	ESCI	100124	2016.06.29	2017.06.28
10	LISN	Kyoritsu	KNW-242	8-837-4	2016.06.29	2017.06.28
11	LISN	Kyoritsu	KNW-407	8-1789-3	2016.06.29	2017.06.28
12	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2016.06.29	2017.06.28
13	Loop Antenna	ETS	6512	00165355	2016.06.29	2017.06.28
14	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2016.06.29	2017.06.28
15	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2016.06.29	2017.06.28
16	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2016.06.29	2017.06.28
17	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A
Note: The SMA antenna connector is soldered on the PCB board in order to perform conducted tests and this SMA antenna connector is listed in the equipment list.						

6 Test Result

6.1 Antenna Requirement

6.1.1 Standard requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

6.1.2 EUT Antenna

The antenna is PCB antenna and no consideration of replacement. Antenna gain is Max. 0 dBi from 2.4GHz to 2.5GHz.

Antenna RF Port


6.2 Conduction Emissions Measurement

6.2.1 Applied procedures / Limit

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

Note: Decreases with the logarithm of the frequency.

6.2.2 Test procedure

EUT was placed upon a wooden test table 0.1m above the horizontal metal reference plane and 0.4m from the vertical ground plane, and it was connected to an AMN. The closest distance between the boundary of the EUT and the surface of the AMN is 0.8m. All peripherals were connected to another AMN, and placed at a distance of 10cm from each other. A spectrum and receiver was connected to the RF output port of the AMN. Both average and quasi-peak value were detected.

6.2.3 Test setup



6.2.4 Test results

EUT:	Bluetooth Speaker	Model Name. :	191304
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Test Date :	2017-02-28
Test Mode:	TX (1Mbps) CH00 (worst case)	Phase :	Line
Test Voltage :	DC 5.0V from adapter, AC 120V/60Hz for adapter		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.3379	33.30	10.18	43.48	59.25	-15.77	QP
2		0.3460	24.20	10.17	34.37	49.06	-14.69	AVG
3	*	2.5100	40.00	10.01	50.01	56.00	-5.99	QP
4		2.5100	26.22	10.01	36.23	46.00	-9.77	AVG
5		10.4580	39.62	10.26	49.88	60.00	-10.12	QP
6		10.4580	26.73	10.26	36.99	50.00	-13.01	AVG

EUT:	Bluetooth Speaker	Model Name. :	191304
Temperature:	26 ℃	Relative Humidity:	54%
Pressure:	1010hPa	Test Date :	2017-02-28
Test Mode:	TX (1Mbps) CH00 (worst case)	Phase :	Neutral
Test Voltage :	DC 5.0V from adapter, AC 120V/60Hz for adapter		



Remark: Factor = LISN factor + Cable Loss + Pulse limiter factor.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector
1		0.1660	41.79	11.61	53.40	65.15	-11.75	QP
2		0.1660	27.97	11.61	39.58	55.15	-15.57	AVG
3		2.5260	28.20	10.01	38.21	46.00	-7.79	AVG
4		2.5380	40.00	10.01	50.01	56.00	-5.99	QP
5		15.8900	40.94	1.51	42.45	50.00	-7.55	AVG
6	*	16.3779	53.09	1.58	54.67	60.00	-5.33	QP

6.3 Radiated Emissions Measurement

6.3.1 Applied procedures / Limit

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Frequency of Emission (MHz)	Field Strength		Measurement Distance (meters)
	μV/m	dBμV/m	
0.009-0.49	2400/F(kHz)		300
0.49-1.705	24000/F(kHz)		30
1.705-30	30		30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

6.3.2 Test setup

Test Configuration:

1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:



3) 1 GHz to 25 GHz emissions:



6.3.3 Test procedure

a. The EUT was placed on the top of a wooden table 0.8 meters (for measurement at frequency below 1GHz) and a wooden table 1.5 meters (for measurement at frequency above 1GHz) above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter, for the test frequency of above 1GHz, horn antenna opening in the test would have been facing the EUT when rise or fall) and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. The resolution bandwidth and video bandwidth of the test receiver was 1MHz and 1MHz for Peak detection at frequency above 1GHz.
g. Test the EUT in the lowest channel (2402MHz), the middle channel (2440MHz), the Highest channel (2480MHz)
h. Repeat above procedures until all frequencies measured was complete.

For measurement at frequency above 1GHz
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

In 18GHz to 25GHz, The EUT was checked by Horn ANT. But the test result at least have 20dB margin.The EUT was tested in Chamber Site.

6.3.4 Test Result

Radiated Emissions Test Data Below 30MHz

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	25 ℃	Test Data	2017-02-28
Pressure：	1005 hPa	Relative Humidity：	60%
Test Mode ：	TX	Test Voltage ：	DC 5.0V from adapter, AC 120V/60Hz for adapter
Measurement Distance	3 m	Frenqucy Range	9KHz to 30MHz
RBW/VBW	9KHz~150KHz/RB 200Hz for QP, 150KHz~30MHz/RB 9KHz for QP		

No emission found between lowest internal used/generated frequencies to 30MHz.

Radiated Emissions Test Data Below 1GHz

EUT:	Bluetooth Speaker	Model Name :	191304
Temperature:	25 ℃	Test Data	2017-02-28
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX (1Mbps) CH00 (worst case)	Test Voltage :	DC 5.0V from adapter, AC 120V/60Hz for adapter
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

Vertical



Measurement Level = Reading Level + Factor, Factor=Ant Factor + Cable Loss– Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		37.8121	31.56	-16.68	14.88	40.00	-25.12	QP
2	*	121.9754	47.36	-15.00	32.36	43.50	-11.14	QP
3		295.1469	33.28	-10.27	23.01	46.00	-22.99	QP
4		531.9634	35.17	-4.51	30.66	46.00	-15.34	QP
5		724.2611	35.24	-0.46	34.78	46.00	-11.22	QP
6		965.5421	31.13	4.28	35.41	54.00	-18.59	QP

Horizontal



Measurement Level = Reading Level + Factor, Factor=Ant Factor + Cable Loss– Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector
1		88.0329	39.40	-17.19	22.21	43.50	-21.29	QP
2		122.4040	50.40	-15.02	35.38	43.50	-8.12	QP
3		182.5592	38.52	-11.36	27.16	43.50	-16.34	QP
4	*	393.4723	45.75	-7.18	38.57	46.00	-7.43	QP
5		526.3967	41.34	-4.74	36.60	46.00	-9.40	QP
6		979.1804	31.46	4.15	35.61	54.00	-18.39	QP

Note:

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Radiated Emissions Test Data Above 1GHz

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	25 ℃	Test Data	2017-02-28
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	1Mbps	Test Voltage ：	DC 3.7V from battery
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	1MHz/1MHz for Peak, 1MHz/10Hz for Average.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	45.96	5.06	51.02	74.00	-22.98	PEAK
4804.000	23.98	5.06	29.04	54.00	-24.96	AVERAGE
7206.000	50.56	7.03	57.59	74.00	-16.41	PEAK
7206.000	22.07	7.03	29.10	54.00	-24.90	AVERAGE
9608.000	37.75	10.63	48.38	74.00	-25.62	PEAK
9608.000	20.08	10.63	30.71	54.00	-23.29	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	46.81	5.06	51.87	74.00	-22.13	PEAK
4804.000	22.74	5.06	27.80	54.00	-26.20	AVERAGE
7206.000	49.37	7.00	56.37	74.00	-17.63	PEAK
7206.000	24.67	7.00	31.67	54.00	-22.33	AVERAGE
9608.000	40.39	10.63	51.02	74.00	-22.98	PEAK
9608.000	23.36	10.63	33.99	54.00	-20.01	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Lowest channel: 2402 MHz

Data rate: 1Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4882.000	51.97	5.14	57.11	74.00	-16.89	PEAK
4882.000	21.93	5.14	27.07	54.00	-26.93	AVERAGE
7323.000	52.61	7.54	60.15	74.00	-13.85	PEAK
7323.000	24.58	7.54	32.12	54.00	-21.88	AVERAGE
9764.000	41.65	11.39	53.04	74.00	-20.96	PEAK
9764.000	17.02	11.39	28.41	54.00	-25.59	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4882.000	44.22	5.14	49.36	74.00	-24.64	PEAK
4882.000	22.10	5.14	27.24	54.00	-26.76	AVERAGE
7323.000	54.83	7.54	62.37	74.00	-11.63	PEAK
7323.000	25.99	7.54	33.53	54.00	-20.47	AVERAGE
9764.000	33.20	11.39	44.59	74.00	-29.41	PEAK
9764.000	16.87	11.39	28.26	54.00	-25.74	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Middle Channel: 2441 MHz

Data rate: 1Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	50.77	5.22	55.99	74.00	-18.01	PEAK
4960.000	23.38	5.22	28.60	54.00	-25.40	AVERAGE
7440.000	49.28	8.06	57.34	74.00	-16.66	PEAK
7440.000	17.01	8.06	25.07	54.00	-28.93	AVERAGE
9920.000	35.17	12.10	47.27	74.00	-26.73	PEAK
9920.000	17.29	12.10	29.39	54.00	-24.61	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	43.57	5.22	48.79	74.00	-25.21	PEAK
4960.000	22.83	5.22	28.05	54.00	-25.95	AVERAGE
7440.000	52.58	8.06	60.64	74.00	-13.36	PEAK
7440.000	16.76	8.06	24.82	54.00	-29.18	AVERAGE
9920.000	30.44	12.10	42.54	74.00	-31.46	PEAK
9920.000	15.98	12.10	28.08	54.00	-25.92	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Highest Channel: 2480 MHz

Data rate: 1Mbps

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	25 ℃	Test Data	2017-02-28
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	3Mbps	Test Voltage ：	DC 3.7V from battery
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	1MHz/1MHz for Peak, 1MHz/10Hz for Average.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	40.26	5.06	45.32	74.00	-28.68	PEAK
4804.000	23.07	5.06	28.13	54.00	-25.87	AVERAGE
7206.000	46.13	7.03	53.16	74.00	-20.84	PEAK
7206.000	20.09	7.03	27.12	54.00	-26.88	AVERAGE
9608.000	35.00	10.63	45.63	74.00	-28.37	PEAK
9608.000	22.94	10.63	33.57	54.00	-20.43	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4804.000	36.95	5.06	42.01	74.00	-31.99	PEAK
4804.000	21.20	5.06	26.26	54.00	-27.74	AVERAGE
7206.000	41.79	7.03	48.82	74.00	-25.18	PEAK
7206.000	20.72	7.03	27.75	54.00	-26.25	AVERAGE
9608.000	31.60	10.63	42.23	74.00	-31.77	PEAK
9608.000	18.22	10.63	28.85	54.00	-25.15	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Lowest Channel: 2402 MHz

Data rate: 3Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4882.000	47.95	5.14	53.09	74.00	-20.91	PEAK
4882.000	22.09	5.14	27.23	54.00	-26.77	AVERAGE
7323.000	42.99	7.54	50.53	74.00	-23.47	PEAK
7323.000	19.96	7.54	27.50	54.00	-26.50	AVERAGE
9764.000	32.65	11.39	44.04	74.00	-29.96	PEAK
9764.000	17.16	11.39	28.55	54.00	-25.45	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4882.000	37.50	5.14	42.64	74.00	-31.36	PEAK
4882.000	20.66	5.14	25.80	54.00	-28.20	AVERAGE
7323.000	47.98	7.54	55.52	74.00	-18.48	PEAK
7323.000	22.14	7.54	29.68	54.00	-24.32	AVERAGE
9764.000	30.67	11.39	42.06	74.00	-31.94	PEAK
9764.000	17.04	11.39	28.43	54.00	-25.57	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Middle Channel: 2441 MHz

Data rate: 3Mbps

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	41.15	5.22	46.37	74.00	-27.63	PEAK
4960.000	23.07	5.22	28.29	54.00	-25.71	AVERAGE
7440.000	46.80	8.06	54.86	74.00	-19.14	PEAK
7440.000	16.94	8.06	25.00	54.00	-29.00	AVERAGE
9920.000	31.28	12.10	43.38	74.00	-30.62	PEAK
9920.000	19.21	12.10	31.31	54.00	-22.69	AVERAGE



(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4960.000	40.16	5.22	45.38	74.00	-28.62	PEAK
4960.000	21.14	5.22	26.36	54.00	-27.64	AVERAGE
7440.000	44.61	8.06	52.67	74.00	-21.33	PEAK
7440.000	16.94	8.06	25.00	54.00	-29.00	AVERAGE
9920.000	31.80	12.10	43.90	74.00	-30.10	PEAK
9920.000	17.13	12.10	29.23	54.00	-24.77	AVERAGE



Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier

Highest channel: 2480 MHz

Data rate: 3Mbps

6.3.5 TEST RESULTS (Restricted Bands Requirements)

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	25 ℃	Test Data	2017-02-28
Pressure：	1010 hPa	Relative Humidity：	60%
Test Mode ：	TX 1Mbps/3Mbps	Test Voltage ：	DC 3.7V from battery
Note：	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		

Test Mode	Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
			Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
Data rate 1Mbps	V	2390.00	42.77	31.79	-5.79	36.98	26.00	74.00	54.00
	H	2390.00	43.31	32.58	-5.79	37.52	26.79	74.00	54.00
	V	2483.50	42.82	31.48	-4.98	37.84	26.50	74.00	54.00
	H	2483.50	41.45	32.48	-4.98	36.47	27.50	74.00	54.00
Data rate 3Mbps	V	2390.00	42.55	31.27	-5.79	36.76	25.48	74.00	54.00
	H	2390.00	41.15	32.29	-5.79	35.36	26.50	74.00	54.00
	V	2483.50	42.41	31.77	-4.98	37.43	26.79	74.00	54.00
	H	2483.50	43.25	31.34	-4.98	38.27	26.36	74.00	54.00

Remark：

(1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode.

(2) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna

(3) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

6.4 BANDWIDTH TEST

6.4.1 Applied procedures / Limit

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dBbandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

6.4.2 Test procedure

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW, Sweep = auto, Detector function = peak
Trace = max hold

6.4.3 Deviation from standard

No deviation.

6.4.4 Test setup



6.4.5 Test results

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	26 ℃	Relative Humidity：	53%
Pressure：	1010 hPa	Test Power ：	DC 3.7V from battery
Test Mode ：	TX 1Mbps/ 3Mbps		

Channel		Channel frenqucy (MHz)	20dB bandwidth (KHz)	Limit (KHz)	Conclusion
1Mbps	Low	2402	1099.2	N/A	Pass
	Middle	2441	1094.4	N/A	Pass
	High	2480	1095.9	N/A	Pass
2Mbps	Low	2402	1348.5	N/A	Pass
	Middle	2441	1364.4	N/A	Pass
	High	2480	1363.8	N/A	Pass
3Mbps	Low	2402	1344.3	N/A	Pass
	Middle	2441	1344.3	N/A	Pass
	High	2480	1349.4	N/A	Pass

CH00-1Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40199085 GHz	1.88 dBm	ndB down	1.0992 MHz
T1		1	2.40144605 GHz	-18.12 dBm	ndB	20.00 dB
T2		1	2.40254525 GHz	-18.12 dBm	Q factor	2185.2

CH 39-1Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44082495 GHz	4.04 dBm	ndB down	1.0944 MHz
T1		1	2.44043855 GHz	-15.97 dBm	ndB	20.00 dB
T2		1	2.44153295 GHz	-15.96 dBm	Q factor	2230.3

CH 78-1Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47982315 GHz	4.87 dBm	ndB down	1.0959 MHz
T1		1	2.47943915 GHz	-15.14 dBm	ndB	20.00 dB
T2		1	2.48053505 GHz	-15.13 dBm	Q factor	2262.8

CH 00-2Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40199025 GHz	-1.00 dBm	ndB down	1.3485 MHz
T1		1	2.40130145 GHz	-20.99 dBm	ndB	20.00 dB
T2		1	2.40264995 GHz	-21.00 dBm	Q factor	1781.2

CH 39-2Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44099055 GHz	2.07 dBm	ndB down	1.3644 MHz
T1		1	2.44029755 GHz	-17.94 dBm	ndB	20.00 dB
T2		1	2.44166195 GHz	-17.92 dBm	Q factor	1789.1

CH 78-2Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47998875 GHz	3.16 dBm	ndB down	1.3638 MHz
T1		1	2.47929905 GHz	-16.83 dBm	ndB	20.00 dB
T2		1	2.48066285 GHz	-16.83 dBm	Q factor	1818.4

CH 00-3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.40182435 GHz	-0.93 dBm	ndB down	1.3443 MHz
T1		1	2.40131615 GHz	-20.90 dBm	ndB	20.00 dB
T2		1	2.40266045 GHz	-20.93 dBm	Q factor	1786.7

CH 39-3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44082465 GHz	2.13 dBm	ndB down	1.3443 MHz
T1		1	2.44031705 GHz	-17.89 dBm	ndB	20.00 dB
T2		1	2.44166135 GHz	-17.86 dBm	Q factor	1815.7

CH 78-3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47982735 GHz	3.19 dBm	ndB down	1.3494 MHz
T1		1	2.47931525 GHz	-16.81 dBm	ndB	20.00 dB
T2		1	2.48066465 GHz	-16.80 dBm	Q factor	1837.7

6.5 Carrier Frequencies Separated

6.5.1 Applied procedures / Limit

15.247(a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

6.5.2 Test procedure

(1) Connected the antenna port to the Spectrum Analyzer, set the Spectrum Analyzer as
Span = wide enough to capture the peaks of two adjacent channels, Resolution (or IF) Bandwidth (RBW) ≥ 1% of the span, Video (or Average) Bandwidth (VBW) ≥ RBW
Sweep = auto, Detector function = peak, Trace = max hold

(2) The EUT should be transmitting at its maximum data rate. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

(3) The above procedure shall be repeated at the lowest, the middle, and the highest frequency of the stated frequency range with modulated mode. also shall be performed at different modes of operation.

6.5.3 Deviation from standard

No deviation.

6.5.4 Test setup



6.5.5 Test results

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	26 ℃	Relative Humidity：	53%
Pressure：	1010 hPa	Test Power ：	DC 3.7V from battery
Test Mode ：	TX 1Mbps/ 3Mbps		

Channel		Channel frenqucy (MHz)	Channel Separation (MHz)	Conclusion
1Mbps	Low	2402	1.0008	Pass
	Middle	2441	1.0008	Pass
	Highest	2480	0.9993	Pass
3Mbps	Low	2402	0.9996	Pass
	Middle	2441	1.0005	Pass
	Highest	2480	1.0020	Pass

Ch. Separation >2/3(20dB bandwidth)

CH 00-1Mbps



CH 39-1Mbps



CH 78-1Mbps



CH 00-3Mbps



CH 39-3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.44082485 GHz	2.02 dBm		
D2	M1	1	1.0005 MHz	0.01 dB		

CH 78-3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.47982355 GHz	3.04 dBm		
D2	M1	1	-1.002 MHz	-0.03 dB		

6.6 Hopping Channel Number

6.6.1 Applied procedures / Limit

15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

6.6.2 Test procedure

(1) Connected the antenna port to the Spectrum Analyzer , set the Spectrum Analyzer as Span = the frequency band of operation, RBW ≥ 1% of the span, VBW ≥ RBW Sweep = auto Detector function = peak, Trace = max hold

(2) The EUT should be have its hopping function enabled. Maxhold and record hopping channels It may prove necessary to break the span up to sections, in order to clearly show all of the hopping frequencies.

6.6.3 Deviation from standard

No deviation.

6.6.4 Test setup

6.6.5 Test result

Hopping Channel Number result		
Operating Mode: 1Mbps/ 3Mbps Mode	Test date:2017-02-28	
Result	Limit	Conclusion
79	15	Pass

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	26 ℃	Relative Humidity：	53%
Pressure：	1010 hPa	Test Power ：	DC 3.7V from battery
Test Mode ：	TX 1Mbps/ 3Mbps		

1Mbps



3Mbps



6.7 Dwell time

6.7.1 Applied procedures / Limit

15.247(a) (1) (iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

6.7.2 Test procedure

(1) Place the EUT on the table in the chamber or connect the antenna port of the EUT to spectrum analyzer and set it in transmitting mode.
(2) Set RBW of spectrum analyzer to 1MHz, VBW ≥ RBW
(3) Use a video trigger with the trigger level set to enable triggering only on full pulses.
(4) Sweep Time is more than once pulse time.
(5) Set the center frequency on any frequency would be measure and set the frequency span to zero span.
(6) Measure the maximum time duration of one single pulse.
(7) Set the EUT for DH5, DH3 and DH1 packet transmitting.
(8) Measure the maximum time duration of one single pulse.
(9) A Period Time = 79*0.4=31.6 S
DH1 Time Slot: Reading * (1600/2)*31.6/79
DH3 Time Slot: Reading * (1600/4)*31.6/79
DH5 Time Slot: Reading * (1600/6)*31.6/79

6.7.3 Deviation from standard

No deviation.

6.7.4 Test setup

6.7.5 Test result

EUT:	Bluetooth Speaker	Model Name :	191304
Temperature:	26 ℃	Relative Humidity:	53%
Pressure:	1010 hPa	Test Power :	DC 3.7V from battery
Test Mode :	CH00-DH1/DH3/DH5 (1Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (ms)	Limits (s)
DH1	2402 MHz	0.4316	138.1120	0.4000
DH3	2402 MHz	1.6850	269.6000	0.4000
DH5	2402 MHz	2.9335	312.9065	0.4000

CH 00- DH1



CH 00- DH3



CH 00- DH5



EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	26 ℃	Relative Humidity：	53%
Pressure：	1010 hPa	Test Power ：	DC 3.7V from battery
Test Mode ：	CH00-3DH1/3DH3/3DH5 (3Mbps Mode)		

Data Packet	Frequency	Pulse Duration (ms)	Dwell Time (ms)	Limits (s)
3DH1	2402 MHz	0.4412	141.1840	0.4000
3DH3	2402 MHz	1.6878	270.0480	0.4000
3DH5	2402 MHz	2.9391	313.5038	0.4000

CH 00- DH1



CH 00- DH3



CH 00- DH5



6.8 Maximum Peak Output Power

6.8.1 Applied procedures / Limit

15.247(a) (1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

15.247(b) (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

6.8.2 Test procedure

(1) Connected the antenna port to the Spectrum Analyzer, set the Spectrum Analyzer as
(2) Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel
(3) RBW > the 20 dB bandwidth of the emission being measured, VBW ≥ RBW, Sweep = auto
(4) Detector function = peak, Trace = max hold
(5) The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.
(6) The above procedure shall be repeated at the lowest, the middle, and the highest frequency of the stated frequency range with modulated mode. Also shall be performed at different modes of operation.

6.8.3 Deviation from standard

No deviation.

6.8.4 Test setup



6.8.5 Test results

EUT：	Bluetooth Speaker	Model Name ：	191304
Temperature：	26 ℃	Relative Humidity：	60%
Pressure：	1010 hPa	Test Voltage ：	DC 3.7V from battery
Test Mode ：	TX		
Note: All the data rates have be tested and the worst-case as the table below.			

Test Mode	Frequency	Peak Output Power (dBm)	Limit (dBm)	Result
Data rate 1Mbps	2402 MHz	2.13	21	Pass
	2441 MHz	4.16	21	Pass
	2480 MHz	5.07	21	Pass
Data rate 2Mbps	2402 MHz	-0.04	21	Pass
	2441 MHz	2.88	21	Pass
	2480 MHz	3.95	21	Pass
Data rate 3Mbps	2402 MHz	-0.12	21	Pass
	2441 MHz	2.83	21	Pass
	2480 MHz	3.96	21	Pass
Cable loss = 0.5 dBm				

CH 00-1Mbps



CH 39-1Mbps



CH 78-1Mbps



CH 00-2Mbps



CH 39-2Mbps



CH 78-2Mbps



CH 00-3Mbps



CH 39-3Mbps



CH 78-3Mbps


Spectrum
Ref Level 20.00 dBm Offset 0.50 dB RBW 3 MHz
Att 30 dB SWT 2.6 µs VBW 3 MHz Mode Auto FFT
1Pk Max
M1[1] 3.96 dBm
2.47951700 GHz
M1
10 dBm
0 dBm
-10 dBm
-20 dBm
-30 dBm
-40 dBm
-50 dBm
-60 dBm
-70 dBm
CF 2.48 GHz
10000 pts
Span 20.0 MHz
Marker
Type Ref Trc X-value Y-value Function Function Result
M1 1 2.479517 GHz 3.96 dBm

6.9 Band edge

6.9.1 Applied procedures / Limit

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.9.2 Test procedure

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Span = wide enough to capture the peak level of the emission operating on the channel closest to the bandedge, as well as any modulation products which fall outside of the authorized band of operation, RBW ≥ 1% of the span, VBW ≥ RBW, Sweep = auto,
Detector function = peak, Trace = max hold

6.9.3 Deviation from standard

No deviation.

6.9.4 Test setup



6.9.5 Test results

CH00 (Lower) Data rate 1Mbps



CH 78 (Upper) Data rate 1Mbps



CH00 (Lower) Data rate 3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.401825 GHz	-1.04 dBm		
M2		1	2.4 GHz	-41.51 dBm		

CH 78 (Upper) Data rate 3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.479985 GHz	3.02 dBm		
M2		1	2.4835 GHz	-57.18 dBm		

CH00 (Lower) Data rate 1Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.407825 GHz	2.70 dBm		
M2		1	2.4 GHz	-53.52 dBm		

CH 78 (Upper) Data rate 1Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.478825 GHz	4.63 dBm		
M2		1	2.4835 GHz	-57.94 dBm		

CH00 (Lower) Data rate 3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.408995 GHz	0.41 dBm		
M2		1	2.4 GHz	-42.64 dBm		

CH 78 (Upper) Data rate 3Mbps



Marker

Type	Ref	Trc	X-value	Y-value	Function	Function Result
M1		1	2.476825 GHz	2.84 dBm		
M2		1	2.4835 GHz	-56.58 dBm		

6.10 Conducted Spurious Emissions

6.10.1 Applied procedures / Limit

15.247(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.10.2 Test procedure

a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
b. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span. RBW = 100 kHz
VBW ≥ RBW, Sweep = auto, Detector function = peak, Trace = max hold
sweep points ≥ investigated frequency range/RBW.

6.10.3 Deviation from standard

No deviation.

6.10.4 Test setup



6.10.5Test results

CH00 Data rate 1Mbps





CH00 Data rate 1Mbps





CH39 Data rate 1Mbps





CH39 Data rate 1Mbps





CH78 Data rate 1Mbps





CH78 Data rate 1Mbps





CH00 Data rate 3Mbps





CH00 Data rate 3Mbps





CH39 Data rate 3Mbps





CH39 Data rate 3Mbps





CH78 Data rate 3Mbps





CH78 Data rate 3Mbps





6.11 Pseudorandom Frequency Hopping Sequence

6.11.1 Standard requirement

15.247(a)(1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

6.11.2 Other requirements Frequency Hopping Spread Spectrum System

Test Requirement:	47 CFR Part 15**C Section 15.247 (a)(1), (h) requirement:**

The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

Compliance for section 15.247(a)(1)

According to Bluetooth Core Specification, the pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage
outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

• Number of shift register stages: 9
• Length of pseudo-random sequence: 2^9 -1 = 511 bits
• Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

According to Bluetooth Core Specification, Bluetooth receivers are designed to have input and IF bandwidths that match the hopping channel bandwidths of any Bluetooth transmitters and shift frequencies in synchronization with the transmitted signals.

Compliance for section 15.247(g)

According to Bluetooth Core Specification, the Bluetooth system transmits the packet with the pseudorandom hopping frequency with a continuous data and the short burst transmission from the Bluetooth system is also transmitted under the frequency hopping system with the pseudorandom hopping frequency system.

Compliance for section 15.247(h)

According to Bluetooth Core specification, the Bluetooth system incorporates with an adaptive system to detect other user within the spectrum band so that it individually and independently to avoid hopping on the occupied channels.

According to the Bluetooth Core specification, the Bluetooth system is designed not have the ability to coordinated with other FHSS System in an effort to avoid the simultaneous occupancy of individual hopping frequencies by multiple transmitter.

7 Photographs

7.1 Radiated Emission Test Setup

Below 1G

Above 1G



7.2 Conducted Emissions Test Setup



7.3 EUT Constructional Details

ADVENTURER





LINE IN




0.5 mm
1
2
3
4
0.5 mm
1
2
3
4
5
6


0.5 mm
1 2 3 4 5 6








4R7
2R2






0.5 mm
1 2 3 4 5 6
mm


0.5 mm
1 2 3 4 5 6 7
mm


0.5 mm
1 2 3 4 5 6 7 8 9
mm





End of the report