



11. Radio Frequency Exposure

11.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)
KDB 447498

11.2 EUT Specification

Frequency band (Operating)	☒ WLAN: 2412MHz ~ 2462MHz ☐ WLAN: 5150MHz ~ 5250MHz ☐ WLAN: 5250MHz ~ 5350MHz ☐ WLAN: 5470MHz ~ 5725MHz ☐ WLAN: 5725MHz ~ 5850MHz ☐ Bluetooth: 2402MHz ~ 2480MHz
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation)
Exposure classification	☐ Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) ☒ General Population/Uncontrolled exposure ($S=1\text{mW/cm}^2$)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☒ Tx/Rx diversity
Max. output power	Band: 2412MHz ~ 2462MHz 802.11b: 22.94dBm (196.79mW) 802.11g: 25.10dBm (323.36mW) 802.11n HT20: 27.38dBm (547.22mW) 802.11n HT40: 23.57dBm (227.67mW)
Antenna gain (Max)	2412-2462MHz: ANT 1: 2.8dBi; ANT 2: 3dBi 5150MHz-5250MHz: ANT 1: 3dBi; ANT 2: 3dBi 5725MHz -5850MHz: ANT 1: 2.9dBi; ANT 2: 2.8dBi
Evaluation applied	☒ MPE Evaluation* ☐ SAR Evaluation ☐ N/A
Remark: - The maximum output power is <u>27.38dBm (547.22mW)</u> at <u>2437MHz</u> (with <u>numeric 3.78 antenna gain.</u>) - DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance. - For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm^2 even if the calculation indicates that the power density would be larger.	



11.3 Test Results

No non-compliance noted.

Calculation

$$\text{Given } E = \frac{\sqrt{30 \times P \times G}}{d} \quad \& \quad S = \frac{E^2}{3770}$$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d (m) / 100

Yields

$$S = \frac{30 \times (P / 1000) \times G}{3770 \times (d / 100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

11.4 Maximum Permissible Exposure

Modulation Mode	Frequency band (MHz)	Max. Conducted output power(dBm)	Antenna gain (dBi)	Distance (cm)	Power density (mW/cm2)	Limit (mW/cm2)
802.11b	2412-2462	22.94	3.78	20	0.0935	1
802.11g	2412-2462	25.10	3.78	20	0.1536	1
802.11n HT20	2412-2462	27.38	3.78	20	0.2600	1
802.11n HT40	2412-2462	23.57	3.78	20	0.1082	1