Prüfbericht-Nr.: *Test Report No.*:	**10055433 001**	**Auftrags-Nr.:** *Order No.*:	114039975	Seite 1 von 32 *Page 1 of 32*
Kunden-Referenz-Nr.: *Client Reference No.*:	N/A	**Auftragsdatum:** *Order date*:	26-Aug-2015	
Auftraggeber: *Client*:	SHUN HU Technology Co.,Ltd., No.21, Zhonggong Rd.,TW-514 Xihu Township, Changhua County Taiwan,R.O.C.			
Prüfgegenstand: *Test item*:	Wireless module			
Bezeichnung / Typ-Nr.: *Identification / Type No.*:	RF-434LNA-915			
Auftrags-Inhalt: *Order content*:	FCC Part 15C Test report			
Prüfgrundlage: *Test specification*:	FCC 47CFR Part 15: Subpart C Section 15.247			

Wareneingangsdatum: *Date of receipt*:	18-Jan-2016
Prüfmuster-Nr.: *Test sample No.*:	A000318631-002
Prüfzeitraum: *Testing period*:	25-Jan-2016 - 11-Mar-2016
Ort der Prüfung: *Place of testing*:	EMC/RF Laboratory Taipei
Prüflaboratorium: *Testing laboratory*:	TUV Rheinland Taiwan Ltd.
Prüfergebnis*: *Test result**:	Pass



geprüft von / *tested by*:			**kontrolliert von /** *reviewed by*:		
2016-04-21	Ryan W. T. Chen / Project Manager		2016-04-21	Arvin Ho/Department Manager	
Datum *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*

Sonstiges / *Other*:

Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt
Condition of the test item at delivery: *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.
This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

v04

TEST SUMMARY

5.1.1 ANTENNA REQUIREMENT
RESULT: Passed

5.1.2 PEAK OUTPUT POWER
RESULT: Passed

5.1.3 6DB BANDWIDTH
RESULT: Passed

5.1.4 POWER DENSITY
RESULT: Passed

5.1.5 CONDUCTED SPURIOUS EMISSIONS AND FREQUENCY BAND EDGE MEASURED IN 100KHZ BANDWIDTH
RESULT: Passed

5.1.6 SPURIOUS EMISSION
RESULT: Passed

6.1.1 ELECTROMAGNETIC FIELDS
RESULT: Passed

Contents

1. GENERAL REMARKS 4
1.1 COMPLEMENTARY MATERIALS 4
2. TEST SITES 5
2.1 TEST LABORATORY 5
2.2 TEST FACILITY 5
2.3 LIST OF TEST AND MEASUREMENT INSTRUMENTS 6
2.4 TRACEABILITY 7
2.5 CALIBRATION 7
2.6 MEASUREMENT UNCERTAINTY 7
3. GENERAL PRODUCT INFORMATION 8
3.1 PRODUCT FUNCTION AND INTENDED USE 8
3.2 SYSTEM DETAILS AND RATINGS 8
3.3 INDEPENDENT OPERATION MODES 9
3.4 NOISE GENERATING AND NOISE SUPPRESSING PARTS 9
3.5 SUBMITTED DOCUMENTS 9
4. TEST SET-UP AND OPERATION MODES 10
4.1 PRINCIPLE OF CONFIGURATION SELECTION 10
4.2 TEST OPERATION AND TEST SOFTWARE 10
4.3 SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT 10
4.4 COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE 11
4.5 TEST SETUP DIAGRAM 11
5. TEST RESULTS 13
5.1 TRANSMITTER REQUIREMENT & TEST SUITES 13
5.1.1 Antenna Requirement 13
5.1.2 Peak Output Power 14
5.1.3 6dB Bandwidth 17
5.1.4 Power Density 20
5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth 23
5.1.6 Spurious Emission 27
6. SAFETY HUMAN EXPOSURE 28
6.1 RADIO FREQUENCY EXPOSURE COMPLIANCE 28
6.1.1 Electromagnetic Fields 28
7. PHOTOGRAPHS OF THE TEST SET-UP 29

8. LIST OF TABLES 32

9. LIST OF PHOTOGRAPHS..... 32

1. General Remarks

1.1 Complementary Materials

These attachments are integral parts of this test report:

Appendix P: Photo Documentation internal view
(File Name: 10055433APPENDIX P)

Appendix D: Test Result of Radiated Emissions
(File Name: 10055433APPENDIX D)

Test Specifications

The following standards were applied.

Table 1: Applied Standard and Test Levels

Radio
FCC CFR47 Part 15: Subpart C Section 15.247 ANSI C63.10:2013 KDB558074 D01 DTS Meas Guidance v03r04

2. Test Sites

2.1 Test Laboratory

TUV Rheinland Taiwan Ltd.
Taichung Branch Office

No.9, Lane 36, Minsheng Rd., Sec. 3, Daya District,
Taichung City 428
Taiwan (R.O.C.)

2.2 Test Facility

TUV Rheinland Taiwan Ltd.
Taipei Office

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.
Taipei City 105
Taiwan (R.O.C.)

FCC RegistrationNo.: 799772
IC Canada Registration No.: 9465A-1
TAF Accredited NCC Test Lab. No.:0759
TAF ISO17025 Certification effective periods: 2013-Jul-1st to 2016-Jun-30th

TAF
Testing Laboratory
0759

2.3 List of Test and Measurement Instruments

Table 2: List of Test and Measurement Equipment

Kind of Equipment	Manufacturer	Type	S/N	Last Calibration	Next Calibration
EMI Test Receiver	R&S	ESR7	101062	10-Sep-15	19-Sep-16
Bilog Antenna	TESEQ	CBL6111D	29802	4-Jul-14	3-Jul-16
Spectrum Analyzer	R&S	FSV 40	100921	21-Dec-15	21-Dec-16
Spectrum Analyzer	Agilent	N9010A	MY53470241	1-Apr-15	30-Mar-16
Horn Antenna	ETS-Lindgren	3117	138160	12-Jan-15	11-Jan-17
Horn Antenna (18GHz~40GHz)	COM-POWER	AH840	101031	22-Oct-15	21-Oct-17
Preamplifier (30MHz -1GHz)	HP	8447F	2805A03335	31-Aug-15	31-Aug-16
Preamplifier (18 GHz -40 GHz)	COM-POWER	PAM-840	461257	26-Aug-14	26-Aug-16
Pre-Amplifier (1GHz~18GHz)	EM Electronics	EM30180	60558	4-Nov-15	3-Nov-16
Loop Antenna	Schwarzbeck	FMZB 1513	1513-076	21-Oct-14	20-Oct-16
EMI Test Receiver	R&S	ESCI7	100797	28-Dec-15	27-Dec-16
Spectrum Analyzer	R&S	FSL3	101943	7-Sep-15	7-Sep-16
Temp. & Humid. Chamber	Giant Force	GCT-099-40-S	MAF0103-007	13-Jul-15	12-Jul-16
LISN (1 phase)	R&S	ENV216	101243	1-Jun-15	31-May-16
LISN	R&S	ENV216	101262	16-Jun-15	15-Jun-16

2.4 Traceability

All measurement equipment calibrations are traceable to NML(Taiwan)/NIST(USA) or where calibration is performed outside Taiwan, to equivalent nationally recognized standards organizations.

2.5 Calibration

Equipment requiring calibration is calibrated periodically in a suitably accredited Calibration Lab. Additionally all equipment is verified for proper performance on a regular schedule using in house standards or comparisons.

2.6 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements .

Table 3: Emission Measurement Uncertainty

Parameter	Uncertainty
Radio Frequency	± 1 x 10^{-7}
RF power, conducted	± 1.5 dB
RF power density, conducted	± 3 dB
spurious emissions, conducted	± 3 dB
all emissions, radiated	± 6 dB
Temperature	± 1 ºC
Humidity	± 5 %
DC and low frequency voltages	±3 %

3. General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless module It contains a 902-928MHz compatible module enabling the user to communicate data through a Wireless interface.
For details refer to the User Guide, Data Sheet and Circuit Diagram.

3.2 System Details and Ratings

Table 4: Basic Information of EUT

Item	EUT information
Kind of Equipment	Wireless module
Type Designation	RF-434LNA-915
FCC ID	RN489896162JK915

Table 5: Technical Specification of EUT

Technical Specification	Value
Operating Frequencies	902.5~927.5MHz
Channel Spacing	500kHz
Channel number	51
Operation Voltage	2~3.6V dc
Modulation	2GFSK
Antenna Gain	Internal : SHUN HU, 00K8M0040,0 dBi , External: MAGOYA ,NA-915-3: 2dBi and MAGOYA ,UT-915 :2.5dBi

3.3 Independent Operation Modes

Basic operation modes are:

A. Transmitting
   1. Low channel
   2. Middle channel
   3. High channel
B. Receiving
C. Standby
D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to the Circuit Diagram.

3.5 Submitted Documents

- Circuit Diagram
- Instruction Manual
- Rating Label
- Technical Description

4. Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

The equipment under test (EUT) was configured to measure its maximum power level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Setup for testing: Test samples are provided with a USB interface which makes it possible to control them through a test software installed on a notebook computer.

This software was running on the laptop computer connected to the EUT. It was used to enable the operation modes listed in section 3.3 as appropriate.

The samples were used as follows:
Conducted: A000318631-002
Radiation: A000318631-002

Full test was applied on all test modes, but only worst case was shown

4.3 Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

Description	Manufacturer	Model No.	Serial No.
Notebook(EMC-06)	Lenovo	TP00048A	PB-0F8B2

4.4 Countermeasures to achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Constructional Data Form or the Technical Construction File. No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m
And absorbers placed on the ground plane.

Diagram of Measurement Equipment Configuration for Conducted Transmitter Measurement



5. Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT: **Passed**

Test standard	:	LP0002(2011): 2.2, 3.10.1, (3) FCC Part 15.247(b)(4), Part 15.203 and RSS-Gen 8.3
Requirement	:	use of approved antennas only with directional gains that do not exceed 6 dBi

According to the manufacturer declaration, the EUT has an antenna with a directional gain of 0dBi / 2 dBi / 2.5 dBi. The antenna is a Monopole Antenna soldered to the PCB and External Monopole Antenna with reverse male SMA connector with no possibility of replacement with a non-approved antenna by the end-user. Therefore, the EUT is considered to comply with this provision.

Due to External antenna of model NA-915-3 and UT-915 are same type of antenna,thus,the worst case of antenna is UT-915 has been performed.

Refer to EUT photo for details.

5.1.2 Peak Output Power

RESULT: **Passed**

Test standard	:	LP0002(2011): 3.10.1, (2) FCC Part 15.247(b)(3), RSS-247 5.4(4)
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	1 Watt
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	20-24 °C
Relative humidity	:	50-65 %
Atmospheric pressure	:	100-103 kPa

Table 6: Test result of Peak Output Power

Channel	Channel Frequency (MHz)	Output Power		Limit
		(dBm)	(W)	(W)
Low Channel	902.5	11.67	0.0147	1
Middle Channel	915	11.33	0.0136	1
High Channel	927	11.06	0.0128	1

Pmax: 14.6994 mW

Test Plot of Output Power

Low Channel



Middle Channel



High Channel



5.1.3 6dB Bandwidth

RESULT: **Passed**

Test standard	:	LP0002(2011): 3.10.1, (5) FCC Part 15.247(a)(2), RSS-247 5.2(1)
Basic standard	:	ANSI C63.10:2013, KDB558074
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A

Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 7: Test result of 6dB Bandwidth

Channel	Channel Frequency (MHz)	6dB Bandwidth (kHz)	Limit (kHz)	Result
Low Channel	902.5	513	>500	Pass
Mid Channel	915	511.1	>500	Pass
High Channel	927	506.7	>500	Pass

Test Plot of 6dB Bandwidth

Low Channel



Middle Channel



High Channel



5.1.4 Power Density

RESULT: **Passed**

Test standard	:	LP0002(2011): 3.10.1, (6.2.2) FCC Part 15.247(e) , RSS-247 5.2(2)
Basic standard	:	ANSI C63.10:2013, KDB558074
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ Middle/ High
Operation Mode	:	A
Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

Table 8: Test result of Power Density

Channel	Channel Frequency (MHz)	Power Density	Limit
		(dBm)	(dBm)
Low Channel	902.5	3.373	8
Middle Channel	915	2.983	8
High Channel	927	2.869	8

Test Plot of Power Density

Low Channel



Middle Channel



High Channel



5.1.5 Conducted spurious emissions and Frequency Band Edge measured in 100kHz Bandwidth

RESULT: **Passed**

Test standard	:	LP0002(2011): 3.10.1, (5) FCC part 15.247(d), RSS-247 5.5
Basic standard	:	ANSI C63.10:2013, KDB558074
Limit	:	20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power)
Kind of test site	:	Shielded room

Test setup

Test Channel	:	Low/ High
Operation mode	:	A
Ambient temperature	:	20-24°C
Relative humidity	:	50-65%
Atmospheric pressure	:	100-103 kPa

All emissions are more than 20dB below fundamental, details refer to following test plot, and compliance is achieved as well.
Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

Test Plot 100kHz Conducted Emissions

Low Channel



Middle Channel



High Channel



Test Plot 100kHz RBW of Band Edge

Low Channel



High Channel



5.1.6 Spurious Emission

RESULT: **Passed**

Test standard	:	FCC part 15.247(d), FCC 15.205, FCC 15.209, RSS-210 2.2, RSS-247 5.5 and RSS-Gen 8.9 LP0002(2011): 3.10.1, (5)
Basic standard	:	ANSI C63.10:2013
Limits	:	Radiated emissions which fall in the restricted bands, as defined in FCC 15.205(a) and RSS-Gen i4, 8.9 (Table 6), must comply with the radiated emission limits specified in FCC 15.209(a) and RSS-Gen i4, 8.9 (Table 4 and 5). Radiated emissions which fall in the restricted bands, as defined in LP0002(2011): 2.7 , must comply with the radiated emission limits specified in LP0002(2011): 2.8 Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in FCC 15.209(a) and FCC 15.247(d), RSS-Gen i4, 8.9 (Table 4 and 5) and RSS-210 A2.9(a). Emission radiated outside the specified frequency bands must comply with the radiated emission limits specified in LP0002(2011): 2.8
Kind of test site	:	3m Semi-Anechoic Chamber

Test setup

Test Channel	:	Low/ Middle/ High
Operation mode	:	A, B

Remark: Testing was carried out within frequency range 30MHz to the tenth harmonic.

Due to has two same type of external antennas,thus,the worst of antenna gain 2.5 dBi has been tested.

For details refer to Appendix D.

Testing was carried out within frequency range 30MHz to the tenth harmonic. For details refer to Appendix D. The Radiated Emissions testing was performed in the X, Y and Z axis orientation. The worst-case Axis orientation is recorded in this test report. Due to the small size of the product and that there are no inductive components of significant size, 9kHz to 30MHz frequency range is not tested based on technical judgment.

6. Safety Human exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT: **Passed**

Test standard : FCC KDB Publication 447498 D01 v06

The maximum peak output power of the transmitter is 14.6994 mW. <16mW.

Hence the EUT is excluded from SAR evaluation.
Please also refer to FCC KDB publication 447498 D01 v06: Mobile Portable RF Exposure

7. Photographs of the Test Set-Up

Photograph 1: Set-up for Spurious Emissions (Front View)



Photograph 2: Set-up for Spurious Emissions (Back View 1) (Built-in Antenna)



Photograph 3: Set-up for Spurious Emissions (Back View 1) (External Antenna)



Photograph 4: Set-up for Spurious Emissions (Back View 2)



Photograph 5: Set-up for Conducted testing

8. List of Tables

Table 1: Applied Standard and Test Levels 4
Table 2: List of Test and Measurement Equipment 6
Table 3: Emission Measurement Uncertainty....7
Table 4: Basic Information of EUT 8
Table 5: Technical Specification of EUT 8
Table 6: Test result of Peak Output Power 14
Table 7: Test result of 6dB Bandwidth 17
Table 8: Test result of Power Density 20

9. List of Photographs

Photograph 1: Set-up for Spurious Emissions (Front View)....29
Photograph 2: Set-up for Spurious Emissions (Back View 1) (Built-in Antenna) 30
Photograph 2: Set-up for Spurious Emissions (Back View 1) (External Antenna)....30
Photograph 3: Set-up for Spurious Emissions (Back View 2) 31
Photograph 4: Set-up for Conducted testing 31