

RADIO TEST REPORT – 446890APFWL

Type of assessment:

MPE Calculation report

Applicant:

Blinq Wireless, Inc

Product:

Base station

Model:

FW6-B48-46-NA

FCC ID:

ROR0011


Specifications:

- ◆ FCC 47 CFR Part 1 Subpart I, §§1.1307, 1.1310
- ◆ FCC 47 CFR Part 2 Subpart J, §2.1091
- ◆ FCC KDB 447498 D01 General RF Exposure Guidance v06

Date of issue: January 7, 2022

Andrey Adelberg, Senior EMC/RF Specialist

Prepared by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.
The tests included in this report are within the scope of this accreditation.
The SCC Accreditation Symbol is an official symbol of the Standards Council of Canada, used under licence.

SCC File Number: 15064 (Ottawa/Almonte); 151100 (Montreal); 151097 (Cambridge)

Lab locations

Company name	Nemko Canada Inc.			
Facilities	<i>Ottawa site:</i>	<i>Montréal site:</i>	<i>Cambridge site:</i>	<i>Almonte site:</i>
	303 River Road	292 Labrosse Avenue	1-130 Saltsman Drive	1500 Peter Robinson Road
	Ottawa, Ontario	Pointe-Claire, Québec	Cambridge, Ontario	West Carleton, Ontario
	Canada K1V 1H2	Canada H9R 5L8	Canada N3E 0B2	Canada K0A 1L0
	Tel: +1 613 737 9680	Tel: +1 514 694 2684	Tel: +1 519 650 4811	Tel: +1 613 256-9117
	Fax: +1 613 737 9691	Fax: +1 514 694 3528		
Test site identifier	Organization	Ottawa/Almonte	Montreal	Cambridge
	FCC:	CA2040	CA2041	CA0101
	ISED:	2040A-4	2040G-5	24676
Website	www.nemko.com			

Limits of responsibility

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

Copyright notification

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.
© Nemko Canada Inc.

Table of Contents

Table of Contents	3
Section 1 Evaluation summary	4
1.1 MPE calculation for standalone transmission	4

Section 1 Evaluation summary

1.1 MPE calculation for standalone transmission

1.1.1 References, definitions and limits

FCC §2.1091(d)

- (2) (2) For operations within the frequency range of 300 kHz and 6 GHz (inclusive), the limits for maximum permissible exposure (MPE), derived from whole-body SAR limits and listed in Table 1 in paragraph (e)(1) of this section, may be used instead of whole-body SAR limits as set forth in paragraphs (a) through (c) of this section to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b) of this part, except for portable devices as defined in §2.1093 of this chapter as these evaluations shall be performed according to the SAR provisions in §2.1093.

Table 1.1-1: Table 1 to §1.1310(e)(1)—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3–3.0	614	1.63	*(100)	≤6
3.0–30	1842 / f	4.89 / f	*(900 / f ²)	<6
30–300	61.4	0.163	1.0	<6
300–1500			f / 300	<6
1500–100000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	<30
1.34–30	824 / f	2.19 / f	*(180 / f ²)	<30
30–300	27.5	0.073	0.2	<30
300–1500			f / 1500	<30
1500–100000			1.0	<30

Notes: f = frequency in MHz. * = Plane-wave equivalent power density.

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

where: S = power density (mW/cm² or W/m²)
P = power input to the antenna (mW or W)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator
R = distance to the center of radiation of the antenna (cm or m)

1.1.2 EUT technical information

	Transmitter 1 (CBRS)	Transmitter 2 (UNII-1)	Transmitter 3 (UNII-3)
Prediction frequency	3.57 GHz	5.2 GHz	5.8 GHz
Antenna type	Sector antenna	Dual slant sector antenna	Dual slant sector antenna
Antenna gain	24.5 dBi	19 dBi	19 dBi
Maximum transmitter conducted power	28.91 dBm	18.16 dBm	18.95 dBm
Prediction distance	160 cm	160 cm	160 cm

1.1.3 MPE calculation

	CBRS	UNII-1	UNII-3
Fundamental transmit (prediction) frequency:	3570 MHz	5200 MHz	5800 MHz
Maximum measured conducted peak output power:	28.91 dBm	18.16 dBm	18.95 dBm
Cable and/or jumper loss:	1.5 dB	0 dB	0 dB
Maximum peak power at antenna input terminal:	27.41 dBm	18.16 dBm	18.95 dBm
Tx On time:	1.000 ms	1.000 ms	1.000 ms
Tx period time:	1.000 ms	1.000 ms	1.000 ms
Average factor:	100 %	100 %	100 %
Maximum calculated average power at antenna input terminal:	550.808 mW	65.4636 mW	78.5236 mW
Single Antenna gain (typical):	24.5 dBi	19 dBi	19 dBi
Number of antennae:	2	1	1
Total system gain:	27.51 dBi	19.00 dBi	19.00 dBi
MPE limit for uncontrolled exposure at prediction frequency:	1.000000 mW/cm ²	1.000000 mW/cm ²	1.000000 mW/cm ²
	10.00000 W/m ²	10.00000 W/m ²	10.00000 W/m ²
Minimum calculated prediction distance for compliance:	157 cm	20 cm	22 cm
Typical (declared) distance:	160 cm	160 cm	160 cm
Average power density at prediction frequency:	0.965117 mW/cm ²	0.016164 mW/cm ²	0.019389 mW/cm ²
	9.651174 W/m ²	0.161640 W/m ²	0.193888 W/m ²
Combined MPE compliance:			
Margin of Compliance:	0.15 dB	17.91 dB	17.12 dB
Maximum allowable antenna gain:	27.66 dBi	36.91 dBi	36.12 dBi

1.1.4 Verdict

The calculation is below the limit; therefore, the product is passing the RF Exposure requirements for the declared distance.

End of the test report