



SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V06

Report Template Revision Date: 2026-01-30



中国认可
国际互认
检测
TESTING
CNAS L5785

TEST REPORT

Report No.: CQASZ20260501025E
Applicant: Shenzhen KTC Technology Co., Ltd.
Address of Applicant: Northern Wuhe Road, Gangtou, Buji, Longgang, Shenzhen, China
Equipment Under Test (EUT):
Product: Baby Monitor
Model No.: CB05-A1
Test Model No.: CB05-A1
Brand Name: N/A
FCC ID: ROU-CB05A1PU
Standards: 47 CFR Part 15, Subpart C
KDB558074 D01 15.247 Meas Guidance v05r02
ANSI C63.10:2020
Date of Receipt: 2026-05-21
Date of Test: 2026-05-21 to 2026-07-07
Date of Issue: 2026-7-14
Test Result : **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Tested By:

Lewis Zhou

(Lewis Zhou)

Reviewed By:

Timo Lei

(Timo Lei)

Approved By:

Jack Ai

(Jack Ai)



The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20260501025E	Rev.01	Initial report	2026-7-14

2 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15.203	N/A	PASS
AC Power Line Conducted Emission	47 CFR Part 15.207	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
Conducted Peak & Average Output Power	47 CFR Part 15.247	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
6dB Occupied Bandwidth	47 CFR Part 15.247	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
Power Spectral Density	47 CFR Part 15.247	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15.247	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
RF Conducted Spurious Emissions	47 CFR Part 15.247	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
Radiated Spurious Emissions	47 CFR Part 15.209	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15.205/15.209	ANSI C63.10- 2020+Cor. 1- 2023+C63.10a-2024 + Errata to C63.10a- 2024	PASS

Remark:

The tested sample(s) and the sample information are provided by the client.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radiated Frequency.

CH: In this whole report CH means channel.

Volt: In this whole report Volt means Voltage.

Temp: In this whole report Temp means Temperature.

Humid: In this whole report Humid means humidity.

Press: In this whole report Press means Pressure.

N/A: In this whole report not application

3 Contents

	Page
1 VERSION	2
2 TEST SUMMARY	3
3 CONTENTS	5
4 GENERAL INFORMATION	6
4.1 CLIENT INFORMATION	6
4.2 GENERAL DESCRIPTION OF EUT	6
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD	6
4.4 TEST ENVIRONMENT AND MODE	9
4.5 DESCRIPTION OF SUPPORT UNITS	10
4.6 TEST LOCATION	10
4.7 TEST FACILITY	10
4.8 TEST CONFIGURATION	10
4.9 STATEMENT OF THE MEASUREMENT UNCERTAINTY	11
4.10 DEVIATION FROM STANDARDS	11
4.11 ABNORMALITIES FROM STANDARD CONDITIONS	11
4.12 OTHER INFORMATION REQUESTED BY THE CUSTOMER	11
4.13 EQUIPMENT LIST	12
5 TEST RESULTS AND MEASUREMENT DATA	13
5.1 ANTENNA REQUIREMENT	13
5.2 CONDUCTED EMISSIONS	14
5.3 CONDUCTED PEAK & AVERAGE OUTPUT POWER	20
5.4 99% OCCUPIED BANDWIDTH	22
5.5 6dB OCCUPIED BANDWIDTH	23
5.6 POWER SPECTRAL DENSITY	24
5.7 BAND-EDGE FOR RF CONDUCTED EMISSIONS	25
5.8 RF CONDUCTED SPURIOUS EMISSIONS	26
5.9 RADIATED SPURIOUS EMISSIONS	27
5.9.1 Radiated emission below 1GHz	30
5.9.2 Transmitter emission above 1GHz	34
5.10 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY	40
6 PHOTOGRAPHS - EUT TEST SETUP	45
7 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	46

4 General Information

4.1 Client Information

Applicant:	Shenzhen KTC Technology Co., Ltd.
Address of Applicant:	Northern Wuhe Road, Gangtou,Buji,Longgang, Shenzhen, China
Manufacturer:	Shenzhen KTC Technology Co., Ltd.
Address of Manufacturer:	Northern Wuhe Road, Gangtou,Buji,Longgang, Shenzhen, China
Factory:	Dong Guan Kan Tsang Electroacoustic Technology Co.,Ltd.
Address of Factory:	Room 402, Unit 1, No. 8, Lu Yi 1st Road, Tangxia Town, Dongguan, Guangdong, China

4.2 General Description of EUT

Product Name:	Baby Monitor
Model No.:	CB05-A1
Test Model No.:	CB05-A1
Trade Mark:	N/A
Software Version:	V1.0
Hardware Version:	V1.0
Power Supply:	MODEL:YC-R02051000UU INPUT:100-240V~ 50/60Hz 0.2A OUTPUT:5V= 1.0A
	MODEL:YWK-AD050100-US INPUT:100-240V~ 50/60Hz 0.2A OUTPUT:5V= 1.0A
EUT Supports Radios application:	2.4GHz: Wi-Fi: 802.11b/g/n(HT20): 2412MHz~2462MHz;
Simultaneous Transmission	☐ Simultaneous TX is supported and evaluated in this report. ☒ Simultaneous TX is not supported.

4.3 Product Specification subjective to this standard

Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n HT20: 11 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE for 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE for 802.11g : OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE for 802.11n(HT20) : OFDM (64QAM, 16QAM, QPSK, BPSK)
Transfer Rate:	IEEE for 802.11b: 1Mbps/2Mbps/5.5Mbps/11Mbps IEEE for 802.11g : 6Mbps/9Mbps/12Mbps/18Mbps/24Mbps/36Mbps/48Mbps/54Mbps IEEE for 802.11n(HT20) : 6.5Mbps/13Mbps/19.5Mbps/26Mbps/39Mbps/52Mbps/58.5Mbps/65Mbps
Product Type:	☐ Mobile ☒ Portable ☐ Fix Location
Test Software of EUT:	SecureCRT

Antenna Type:	Copper tube antenna
Antenna Gain:	2.68dBi

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:


For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

Note:

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.4 Test Environment and Mode

Operating Environment:	
Radiated Emissions:	
Temperature:	25.3 °C
Humidity:	55 % RH
Atmospheric Pressure:	1009 mbar
Conducted Emissions:	
Temperature:	25.6 °C
Humidity:	60 % RH
Atmospheric Pressure:	1009 mbar
Radio conducted item test (RF Conducted test room):	
Temperature:	25.5 °C
Humidity:	52 % RH
Atmospheric Pressure:	1009 mbar
Test mode:	
Transmitting mode:	EUT is set in RF test mode in all supported modulation types, bandwidth and data rate, etc.
EUT Power level:	Class0
Run Software:	
	

4.5 Description of Support Units

The EUT has been tested with associated equipment below.

1) Support equipment

Description	Manufacturer	Model No.	Certification	Supplied by
/	/	/	/	/

2) Cable

Cable No.	Description	Manufacturer	Cable Type/Length	Supplied by
/	/	/	/	/

4.6 Test Location

All tests were performed at:

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD

102A, 102B, Building 2, Shanghenglang New Industrial Zone, Shanghenglang Community, Dalang Street, Longhua District, Shenzhen, Guangdong, People's Republic of China, 518000

4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• **A2LA (Certificate No. 4742.01)**


SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory is accredited by the

American Association for Laboratory Accreditation(A2LA). Certificate No. 4742.01.

• **FCC Registration No.: 522263**

SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD, Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.:522263

4.8 Test configuration



4.9 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate.

The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities.

The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the **SHENZHEN HUAXIA TESTING TECHNOLOGY CO., LTD** quality system acc. to DIN EN ISO/IEC 17025.

Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CQA laboratory is reported:

No.	Item	Uncertainty	Notes
1	Radiated Emission (Below 1GHz)	5.12dB	(1)
2	Radiated Emission (Above 1GHz)	4.60dB	(1)
3	Conducted Disturbance (0.15~30MHz)	3.34dB	(1)
4	Radio Frequency	3×10^{-8}	(1)
5	Duty cycle	0.6 %.	(1)
6	Occupied Bandwidth	1.1%	(1)
7	RF conducted power	0.86dB	(1)
8	RF power density	0.74	(1)
9	Conducted Spurious emissions	0.86dB	(1)
10	Temperature test	0.8℃	(1)
11	Humidity test	2.0%	(1)
12	Supply voltages	0.5 %.	(1)
13	Frequency Error	5.5 Hz	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

4.10 Deviation from Standards

None.

4.11 Abnormalities from Standard Conditions

None.

4.12 Other Information Requested by the Customer

None.

4.13 Equipment List

Test Equipment	Manufacturer	Model No.	Instrument No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU26	CQA-038	2025/9/1	2026/8/31
Spectrum analyzer	R&S	FSU40	CQA-075	2025/9/1	2026/8/31
Preamplifier	MITEQ	AFS4-00010300-18-10P-4	CQA-035	2025/9/1	2026/8/31
Preamplifier	MITEQ	AMF-6D-02001800-29-20P	CQA-036	2025/9/1	2026/8/31
Preamplifier	EMCI	EMC184055SE	CQA-089	2025/9/1	2026/8/31
Loop antenna	Schwarzbeck	FMZB1516	CQA-060	2023/9/8	2026/9/7
Bilog Antenna	R&S	HL562	CQA-011	2023/11/01	2026/10/31
Horn Antenna	R&S	HF906	CQA-012	2023/11/01	2026/10/31
Horn Antenna	Schwarzbeck	BBHA 9170	CQA-088	2023/9/7	2026/9/6
Coaxial Cable (Above 1GHz)	CQA	N/A	C007	2025/9/1	2026/8/31
Coaxial Cable (Below 1GHz)	CQA	N/A	C013	2025/9/1	2026/8/31
Antenna Connector	CQA	RFC-01	CQA-080	2025/9/1	2026/8/31
RF cable(9KHz~40GHz)	CQA	RF-01	CQA-079	2025/9/1	2026/8/31
Power meter	R&S	NRVD	CQA-029	2025/9/1	2026/8/31
Power divider	MIDWEST	PWD-2533-02-SMA-79	CQA-067	2025/9/1	2026/8/31
EMI Test Receiver	R&S	ESR7	CQA-005	2025/9/1	2026/8/31
LISN	R&S	ENV216	CQA-003	2025/9/1	2026/8/31
Coaxial cable	CQA	N/A	CQA-C009	2025/9/1	2026/8/31
DC power	KEYSIGHT	E3631A	CQA-028	2025/9/1	2026/8/31
Band Reject Filter	Wainwright instrument gmbh	WRCG2400/2483-2390/2493-35/10SS	CQA-037	2025/9/1	2026/8/31

Test software:


	Manufacturer	Software brand	Software version
Radiated Emissions test software	Tonscend	JS1120-3	Version:8
Conducted Emissions test software	Audix	e3	Version:9
RF Conducted test software	Audix	e3	V3.5.39

Note:

The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

5 Test results and Measurement Data

5.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.	
EUT Antenna:	
The antenna is Tubular Copper Antenna. The connection/connection type between the antenna to the EUT's antenna port is: permanently attachment. This is either permanently attachment or a unique coupling that satisfies the requirement.	

5.2 Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	* Decreases with the logarithm of the frequency.		
Test Procedure:	1) The mains terminal disturbance voltage test was conducted in a shielded room. 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded. 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2. 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2020 on conducted measurement.		
Test Setup:	Shielding Room AC Mains LISN1 EUT AE LISN2 AC Mains Test Receiver 80cm 80cm Ground Reference Plane		

Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate of 802.11b at middle channel is the worst case. Only the worst case is recorded in the report.
Test Voltage:	AC120V/60Hz
Test Results:	Pass

YC-R02051000UU:

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	24.43	9.49	33.92	55.46	-21.54	Average	Line
2	0.160	38.85	9.49	48.34	65.46	-17.12	QP	Line
3	0.170	20.42	9.49	29.91	54.96	-25.05	Average	Line
4	0.170	35.59	9.49	45.08	64.96	-19.88	QP	Line
5	0.195	26.51	9.49	36.00	53.82	-17.82	Average	Line
6 PP	0.195	41.58	9.49	51.07	63.82	-12.75	QP	Line
7	0.205	23.24	9.49	32.73	53.41	-20.68	Average	Line
8	0.205	37.06	9.49	46.55	63.41	-16.86	QP	Line
9	0.235	20.80	9.49	30.29	52.27	-21.98	Average	Line
10	0.235	34.94	9.49	44.43	62.27	-17.84	QP	Line
11 AV	0.595	20.32	9.70	30.02	46.00	-15.98	Average	Line
12	0.595	32.01	9.70	41.71	56.00	-14.29	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.190	23.30	9.62	32.92	54.04	-21.12	Average	Neutral
2	0.190	36.05	9.62	45.67	64.04	-18.37	QP	Neutral
3	0.240	17.22	9.55	26.77	52.10	-25.33	Average	Neutral
4	0.240	30.84	9.55	40.39	62.10	-21.71	QP	Neutral
5	0.285	14.51	9.50	24.01	50.67	-26.66	Average	Neutral
6	0.285	26.40	9.50	35.90	60.67	-24.77	QP	Neutral
7 AV	0.540	23.01	9.74	32.75	46.00	-13.25	Average	Neutral
8 PP	0.540	34.89	9.74	44.63	56.00	-11.37	QP	Neutral
9	0.590	17.39	9.79	27.18	46.00	-18.82	Average	Neutral
10	0.590	29.47	9.79	39.26	56.00	-16.74	QP	Neutral
11	14.430	19.16	9.75	28.91	50.00	-21.09	Average	Neutral
12	14.430	38.11	9.75	47.86	60.00	-12.14	QP	Neutral


Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

YWK-AD050100-US:

Measurement Data

Live Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.190	23.93	9.63	33.56	54.04	-20.48	Average	Line
2	0.190	35.46	9.63	45.09	64.04	-18.95	QP	Line
3	0.505	26.07	9.71	35.78	46.00	-10.22	Average	Line
4	0.505	35.97	9.71	45.68	56.00	-10.32	QP	Line
5	2.550	26.57	11.13	37.70	46.00	-8.30	Average	Line
6 PP	2.550	40.96	11.13	52.09	56.00	-3.91	QP	Line
7 AV	2.590	27.45	11.10	38.55	46.00	-7.45	Average	Line
8	2.590	40.87	11.10	51.97	56.00	-4.03	QP	Line
9	2.640	26.93	11.06	37.99	46.00	-8.01	Average	Line
10	2.640	39.95	11.06	51.01	56.00	-4.99	QP	Line
11	2.700	27.42	11.02	38.44	46.00	-7.56	Average	Line
12	2.700	39.04	11.02	50.06	56.00	-5.94	QP	Line

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

Neutral Line:




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB	dBuV	dBuV	dB		
1	0.160	23.49	9.68	33.17	55.46	-22.29	Average	Neutral
2	0.160	36.74	9.68	46.42	65.46	-19.04	QP	Neutral
3	0.540	24.03	9.74	33.77	46.00	-12.23	Average	Neutral
4	0.540	31.81	9.74	41.55	56.00	-14.45	QP	Neutral
5	0.585	23.87	9.79	33.66	46.00	-12.34	Average	Neutral
6	0.585	29.88	9.79	39.67	56.00	-16.33	QP	Neutral
7	2.560	25.54	9.76	35.30	46.00	-10.70	Average	Neutral
8	2.560	37.72	9.76	47.48	56.00	-8.52	QP	Neutral
9	2.645	27.51	9.76	37.27	46.00	-8.73	Average	Neutral
10 PP	2.645	38.99	9.76	48.75	56.00	-7.25	QP	Neutral
11 AV	2.835	27.59	9.76	37.35	46.00	-8.65	Average	Neutral
12	2.835	34.23	9.76	43.99	56.00	-12.01	QP	Neutral

Remark:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.
3. If the Peak value under Average limit, the Average value is not recorded in the report.

5.3 Conducted Peak & Average Output Power


Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	<i>Setup for Power meter measurement method</i>  <i>Setup for Spectrum analyser measurement method</i> 
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	30dBm
Test Results:	Pass

Measurement Data

Please Refer to Appendix for Details

.


5.4 99% Occupied Bandwidth

Test Requirement:	47 CFR Part 15C
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 $\text{Offset} = \text{cable loss} + \text{attenuation factor}$
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

Measurement Data

Please Refer to Appendix for Details


5.5 6dB Occupied Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	≥ 500 kHz
Test Results:	Pass

Measurement Data

Please Refer to Appendix for Details


5.6 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	$\leq 8.00\text{dBm}/3\text{kHz}$
Test Results:	Pass

Measurement Data

Please Refer to Appendix for Details


5.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Measurement Data


Please Refer to Appendix for Details

5.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 Offset=cable loss+ attenuation factor
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

Note:

The cable losses used in the testing system have already been included in the test data.



Measurement Data

Please Refer to Appendix for Details

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.


	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

5.9.1 Radiated emission below 1GHz

YC-R02051000UU:

30MHz~1GHz

Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	53.88	13.58	12.77	26.35	40.00	-13.65	Peak	VERTICAL
2	106.76	14.28	11.86	26.14	43.50	-17.36	Peak	VERTICAL
3	520.89	15.92	21.22	37.14	46.00	-8.86	Peak	VERTICAL
4 pp	649.66	19.59	22.82	42.41	46.00	-3.59	QP	VERTICAL
5 pk	878.32	10.00	28.94	38.94	46.00	-7.06	Peak	VERTICAL
6	996.50	10.71	28.28	38.99	54.00	-15.01	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal




	Read Freq	Level	Factor	Limit Level	Over Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	440.20	14.34	19.21	33.55	46.00	-12.45	Peak	HORIZONTAL
2	501.18	12.64	20.94	33.58	46.00	-12.42	Peak	HORIZONTAL
3	556.77	15.87	21.78	37.65	46.00	-8.35	Peak	HORIZONTAL
4 pp	645.12	17.06	22.77	39.83	46.00	-6.17	Peak	HORIZONTAL
5	866.09	10.72	28.73	39.45	46.00	-6.55	Peak	HORIZONTAL
6	968.93	11.06	28.10	39.16	54.00	-14.84	Peak	HORIZONTAL

YWK-AD050100-US:

30MHz~1GHz

Vertical



	Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	53.88-512.77		12.77-500.00	40.00-540.00	Peak		VERTICAL
2	53.88	14.58	12.77	27.35	40.00	-12.65	Peak VERTICAL
3	106.76	14.28	11.86	26.14	43.50	-17.36	Peak VERTICAL
4	242.53	10.90	15.42	26.32	46.00	-19.68	Peak VERTICAL
5	520.89	14.92	21.22	36.14	46.00	-9.86	Peak VERTICAL
6 pp	649.66	19.59	22.82	42.41	46.00	-3.59	Peak VERTICAL
7	932.27	10.60	27.92	38.52	46.00	-7.48	Peak VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



	Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	52.21	13.29	12.68	25.97	40.00	-14.03	Peak
2	106.01	11.28	11.86	23.14	43.50	-20.36	Peak
3	239.99	12.86	15.24	28.10	46.00	-17.90	Peak
4	556.77	15.87	21.78	37.65	46.00	-8.35	Peak
5	645.12	17.06	22.77	39.83	46.00	-6.17	Peak
6 pp	866.09	11.72	28.73	40.45	46.00	-5.55	Peak

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.9.2 Transmitter emission above 1GHz

Test mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.84	-4.26	48.58	74	-25.42	peak	H	1.5	283
4824.000	36.65	-4.26	32.39	54	-21.61	AVG	H	1.5	152
7236.000	51.97	1.18	53.15	74	-20.85	peak	H	1.5	270
7236.000	37.72	1.18	38.90	54	-15.10	AVG	H	1.5	317
4824.000	54.34	-4.26	50.08	74	-23.92	peak	V	1.5	69
4824.000	38.91	-4.26	34.65	54	-19.35	AVG	V	1.5	345
7236.000	52.23	1.18	53.41	74	-20.59	peak	V	1.5	135
7236.000	36.74	1.18	37.92	54	-16.08	AVG	V	1.5	222

Test mode:		802.11b(1Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	51.72	-4.12	47.60	74	-26.40	peak	H	1.5	311
4874.000	36.27	-4.12	32.15	54	-21.85	AVG	H	1.5	146
7311.000	48.44	1.46	49.90	74	-24.10	peak	H	1.5	334
7311.000	35.36	1.46	36.82	54	-17.18	AVG	H	1.5	121
4874.000	53.59	-4.12	49.47	74	-24.53	peak	V	1.5	268
4874.000	36.70	-4.12	32.58	54	-21.42	AVG	V	1.5	270
7311.000	48.37	1.46	49.83	74	-24.17	peak	V	1.5	303
7311.000	36.10	1.46	37.56	54	-16.44	AVG	V	1.5	266

Test mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	53.03	-4.03	49.00	74	-25.00	peak	H	1.5	307
4924.000	37.43	-4.03	33.40	54	-20.60	AVG	H	1.5	83
7386.000	49.90	1.66	51.56	74	-22.44	peak	H	1.5	305
7386.000	36.93	1.66	38.59	54	-15.41	AVG	H	1.5	211
4924.000	54.21	-4.03	50.18	74	-23.82	peak	V	1.5	269
4924.000	37.28	-4.03	33.25	54	-20.75	AVG	V	1.5	281
7386.000	50.38	1.66	52.04	74	-21.96	peak	V	1.5	89
7386.000	36.49	1.66	38.15	54	-15.85	AVG	V	1.5	200

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.59	-4.26	48.33	74	-25.67	peak	H	1.5	332
4824.000	37.90	-4.26	33.64	54	-20.36	AVG	H	1.5	279
7236.000	52.19	1.18	53.37	74	-20.63	peak	H	1.5	162
7236.000	37.41	1.18	38.59	54	-15.41	AVG	H	1.5	216
4824.000	56.14	-4.26	51.88	74	-22.12	peak	V	1.5	239
4824.000	39.91	-4.26	35.65	54	-18.35	AVG	V	1.5	183
7236.000	51.58	1.18	52.76	74	-21.24	peak	V	1.5	301
7236.000	36.07	1.18	37.25	54	-16.75	AVG	V	1.5	169

Test mode:		802.11g(6Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	52.70	-4.12	48.58	74	-25.42	peak	H	1.5	293
4874.000	37.15	-4.12	33.03	54	-20.97	AVG	H	1.5	299
7311.000	49.87	1.46	51.33	74	-22.67	peak	H	1.5	166
7311.000	36.27	1.46	37.73	54	-16.27	AVG	H	1.5	143
4874.000	52.57	-4.12	48.45	74	-25.55	peak	V	1.5	197
4874.000	37.67	-4.12	33.55	54	-20.45	AVG	V	1.5	253
7311.000	48.53	1.46	49.99	74	-24.01	peak	V	1.5	252
7311.000	34.99	1.46	36.45	54	-17.55	AVG	V	1.5	318

Test mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)				
4924.000	52.17	-4.03	48.14	74	-25.86	peak	H	1.5	182
4924.000	38.73	-4.03	34.70	54	-19.30	AVG	H	1.5	22
7386.000	51.03	1.66	52.69	74	-21.31	peak	H	1.5	292
7386.000	36.31	1.66	37.97	54	-16.03	AVG	H	1.5	173
4924.000	53.76	-4.03	49.73	74	-24.27	peak	V	1.5	12
4924.000	38.18	-4.03	34.15	54	-19.85	AVG	V	1.5	56
7386.000	51.03	1.66	52.69	74	-21.31	peak	V	1.5	214
7386.000	36.14	1.66	37.80	54	-16.20	AVG	V	1.5	267

Remark:

- 1) The 6Mbps of rate of 802.11g is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11n20(6.5Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.59	-4.26	48.33	74	-25.67	peak	H	1.5	37
4824.000	36.19	-4.26	31.93	54	-22.07	AVG	H	1.5	247
7236.000	50.94	1.18	52.12	74	-21.88	peak	H	1.5	257
7236.000	38.50	1.18	39.68	54	-14.32	AVG	H	1.5	295
4824.000	56.02	-4.26	51.76	74	-22.24	peak	V	1.5	153
4824.000	38.34	-4.26	34.08	54	-19.92	AVG	V	1.5	299
7236.000	50.87	1.18	52.05	74	-21.95	peak	V	1.5	359
7236.000	35.41	1.18	36.59	54	-17.41	AVG	V	1.5	52

Test mode:		802.11n20(6.5Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	52.69	-4.12	48.57	74	-25.43	peak	H	1.5	288
4874.000	36.66	-4.12	32.54	54	-21.46	AVG	H	1.5	178
7311.000	49.64	1.46	51.10	74	-22.90	peak	H	1.5	326
7311.000	36.79	1.46	38.25	54	-15.75	AVG	H	1.5	273
4874.000	52.63	-4.12	48.51	74	-25.49	peak	V	1.5	320
4874.000	37.42	-4.12	33.30	54	-20.70	AVG	V	1.5	112
7311.000	49.36	1.46	50.82	74	-23.18	peak	V	1.5	242
7311.000	35.91	1.46	37.37	54	-16.63	AVG	V	1.5	33

Test mode:		802.11n20(6.5Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.08	-4.03	48.05	74	-25.95	peak	H	1.5	179
4924.000	37.58	-4.03	33.55	54	-20.45	AVG	H	1.5	133
7386.000	51.02	1.66	52.68	74	-21.32	peak	H	1.5	82
7386.000	37.41	1.66	39.07	54	-14.93	AVG	H	1.5	92
4924.000	53.75	-4.03	49.72	74	-24.28	peak	V	1.5	315
4924.000	37.86	-4.03	33.83	54	-20.17	AVG	V	1.5	310
7386.000	50.24	1.66	51.90	74	-22.10	peak	V	1.5	356
7386.000	37.57	1.66	39.23	54	-14.77	AVG	V	1.5	15

Remark:

- 1) The MCS0 of rate of 802.11n20 is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2020		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - For each suspected emission, the EUT was arranged to its worst case and

	then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20). Only the worst case is recorded in the report.
Test Results:	Pass

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2390.000	58.77	-9.2	49.57	74	-24.43	peak	H	1.5	54
2390.000	44.34	-9.2	35.14	54	-18.86	AVG	H	1.5	285
2400.000	59.95	-9.39	50.56	74	-23.44	peak	H	1.5	98
2400.000	46.78	-9.39	37.39	54	-16.61	AVG	H	1.5	84
2390.000	58.88	-9.2	49.68	74	-24.32	peak	V	1.5	17
2390.000	44.70	-9.2	35.50	54	-18.50	AVG	V	1.5	180
2400.000	59.51	-9.39	50.12	74	-23.88	peak	V	1.5	294
2400.000	46.52	-9.39	37.13	54	-16.87	AVG	V	1.5	66

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2483.500	58.24	-9.29	48.95	74	-25.05	peak	H	1.5	126
2483.500	43.90	-9.29	34.61	54	-19.39	AVG	H	1.5	49
2483.500	57.69	-9.29	48.40	74	-25.60	peak	V	1.5	59
2483.500	46.30	-9.29	37.01	54	-16.99	AVG	V	1.5	183

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2390.000	58.87	-9.2	49.67	74	-24.33	peak	H	1.5	112
2390.000	44.83	-9.2	35.63	54	-18.37	AVG	H	1.5	105
2400.000	59.26	-9.39	49.87	74	-24.13	peak	H	1.5	88
2400.000	46.27	-9.39	36.88	54	-17.12	AVG	H	1.5	355
2390.000	58.68	-9.2	49.48	74	-24.52	peak	V	1.5	86
2390.000	44.00	-9.2	34.80	54	-19.20	AVG	V	1.5	1
2400.000	59.70	-9.39	50.31	74	-23.69	peak	V	1.5	351
2400.000	46.24	-9.39	36.85	54	-17.15	AVG	V	1.5	297

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2483.500	57.68	-9.29	48.39	74	-25.61	peak	H	1.5	124
2483.500	44.03	-9.29	34.74	54	-19.26	AVG	H	1.5	105
2483.500	57.67	-9.29	48.38	74	-25.62	peak	V	1.5	249
2483.500	46.26	-9.29	36.97	54	-17.03	AVG	V	1.5	260

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2390.000	58.50	-9.2	49.30	74	-24.70	peak	H	1.5	333
2390.000	44.34	-9.2	35.14	54	-18.86	AVG	H	1.5	74
2400.000	60.12	-9.39	50.73	74	-23.27	peak	H	1.5	72
2400.000	46.68	-9.39	37.29	54	-16.71	AVG	H	1.5	25
2390.000	58.66	-9.2	49.46	74	-24.54	peak	V	1.5	107
2390.000	44.65	-9.2	35.45	54	-18.55	AVG	V	1.5	195
2400.000	59.82	-9.39	50.43	74	-23.57	peak	V	1.5	131
2400.000	46.53	-9.39	37.14	54	-16.86	AVG	V	1.5	37

Worse case mode:		802.11n(HT20)(6.5Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2483.500	58.34	-9.29	49.05	74	-24.95	peak	H	1.5	81
2483.500	44.23	-9.29	34.94	54	-19.06	AVG	H	1.5	227
2483.500	58.35	-9.29	49.06	74	-24.94	peak	V	1.5	97
2483.500	45.95	-9.29	36.66	54	-17.34	AVG	V	1.5	62

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

6 Photographs - EUT Test Setup

Detailed information is given in Appendix A

7 Photographs - EUT Constructional Details

Detailed information is given in Appendix B and Appendix C

*** END OF REPORT ***