FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

ASIA VITAL COMPONENTS CO., LTD.

Bluekite

Model: TH600

Trade Name: AVC

Prepared for

ASIA VITAL COMPONENTS CO., LTD.
7F-3,No.24,Wu-Chuan 2RD.,Hsin Chuang City,
Taipei, Taiwan, R.O.C.

Prepared by

Compliance Certification Services Inc.
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,
Taoyuan Hsien, (338) Taiwan, R.O.C.
TEL: 886-3-324-0332
FAX: 886-3-324-5235

0363
ILAC MRA

Note: *This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document*

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION 3

2. EUT DESCRIPTION 4

3. TEST METHODOLOGY 5

3.1 EUT CONFIGURATION 5
3.2 EUT EXERCISE 5
3.3 GENERAL TEST PROCEDURES 5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS 6
3.5 DESCRIPTION OF TEST MODES 6

4. INSTRUMENT CALIBRATION 7

5. FACILITIES AND ACCREDITATIONS 8

5.1 FACILITIES 8
5.2 EQUIPMENT 8
5.3 LABORATORY ACCREDITATIONS AND LISTING 8
5.4 TABLE OF ACCREDITATIONS AND LISTINGS 9

6. SETUP OF EQUIPMENT UNDER TEST 10

6.1 SUPPORT EQUIPMENT 10

7. FCC PART 15.247 REQUIREMENTS 11

7.1 PEAK POWER 11
7.2 PEAK POWER SPECTRAL DENSITY 12
7.3 BAND EDGES MEASUREMENT 15
7.4 FREQUENCY SEPARATION 20
7.5 NUMBER OF HOPPING FREQUENCY 22
7.6 TIME OF OCCUPANCY (DWELL TIME) 24
7.7 RADIO FREQUENCY EXPOSURE 32
7.8 RADIATED EMISSIONS 33
7.9 POWERLINE CONDUCTED EMISSIONS 45

1. TEST RESULT CERTIFICATION

Applicant: ASIA VITAL COMPONENTS CO., LTD.
7F-3,No.24, Wu-Chuan 2RD., Hsin Chuang City,
Taipei, Taiwan, R.O.C.

Equipment Under Test: Bluekite

Trade Name: AVC

Model: TH600

Model Difference N/A

Report Number: B31121408-RP

Date of Test: December 4, 2003 ~ January 6, 2004

APPLICABLE STANDARDS	
STANDARD	**TEST RESULT**
FCC Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2001) and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

Jonson Lee
Director of Linkou Laboratory
Compliance Certification Services Inc.

Reviewed by:

Eric Wong
Section Manager
Compliance Certification Services Inc.

2. EUT DESCRIPTION

Product	Bluekite
Trade Name	AVC
Model Number	TH600
Model Discrepancy	N/A
Power Supply	Powered by the host USB port
Frequency Range	2402 ~ 2480 MHz
Transmit Power	2.92 dBm
Modulation Technique	FHSS
Number of Channels	79 Channels
Antenna Specification	Multilayer Ceramic Antenna Gain: 2.66 dBi (max)
Temperature Range	0 ~ +55°C

Note: *This submittal(s) (test report) is intended for FCC ID: ROXTH600 filing to comply with Section 15.247 of the FCC Part 15, Subpart C Rules. The composite system (digital device), if any, is compliance with Subpart B is authorized under a DoC procedure.*

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4. Radiated testing was performed at an antenna to EUT distance 3 meters.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT (Bluekite) was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.247 under the FCC Rules Part 15 Subpart C. The composite system (Digital device) is compliance with the Subpart B is authorized under the DoC procedure.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4-2001.Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4-2001.

3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	([2])
13.36 - 13.41	322 - 335.4		

[1] Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

[2] Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.5 DESCRIPTION OF TEST MODES

The EUT (Bluekite) has been tested under operating condition.

Test program used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Channel Low (2402MHz)、Mid (2441MHz) and High (2480MHz) with highest data rate (worst case) are chosen for full testing.

4. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☒ No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.

☐ No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, “Radio Interference Measuring Apparatus and Measurement Methods.”

5.3 LABORATORY ACCREDITATIONS AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200600-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (registration no: 93105 and 90471).

5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP*	EN 55011, EN 55014-1, AS/NZS 1044, CNS 13783-1, EN 55022, CNS 13438, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, FCC OST/MP-5, AS/NZS 3548IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	NVLAP 200600-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	FC 93105, 90471
Japan	VCCI	4 3/10 meter Open Area Test Sites to perform conducted/radiated measurements	VCCI R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328-2, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	N ELA 124a ELA 124b ELA 124c
Taiwan	CNLA	EN 300 328-1, EN 300 328-2, EN 300 220-1, EN 300 220-2, EN 300 220-3, 47 CFR FCC Part 15 Subpart C, EN 61000-3-2, EN 61000-3-3, CNS 13439, CNS 13783-1, CNS 14115, CNS 13438, AS/NZS 3548, CNS 13022-1, IEC 1000-4-3/4/5/6/8/11, CNS 13022-2/3	CNLA 0363 ILAC MRA
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	商檢 SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	Canada IC 3991-3 IC 3991-4

** No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.*

6. SETUP OF EQUIPMENT UNDER TEST

6.1 SUPPORT EQUIPMENT



Support Equipment

Device Type	Brand	Model	FCC ID	Series No.	Data Cable	Power Cord
Notebook PC	IBM	2659	ANODS1WLIV	N/A	N/A	Unshielded, 1.8m
USB Mouse	HP	MO19UCA	FCC DoC	020440941	Shielded, 1.8m	N/A

Notes:

1. *All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
2. *Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*

7. FCC PART 15.247 REQUIREMENTS

7.1 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
RF Power Meter	BOONTON	4531	130601	01/09/2004
RF Power Sensor	BOONTON	56218	2240	01/09/2004
Spectrum Analyzer	Agilent	E4446A	US42510252	04/27/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the RF Power Meter. The RF Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Reading Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2402	2.12	0.80	2.92	0.001959	1.00	PASS
Mid	2441	1.57	0.80	2.37	0.001726		PASS
High	2480	-0.18	0.80	0.62	0.001153		PASS

7.2 PEAK POWER SPECTRAL DENSITY

LIMIT

1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/28/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
4. Record the max. reading.
5. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted

Test Data

Channel	Frequency (MHz)	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
Low	2402	-9.10	1.20	-7.90	8.00	PASS
Mid	2441	-9.06	1.20	-7.86		PASS
High	2480	-11.78	1.20	-10.58		PASS

Test Plot

PPSD (CH Low)



Date: 4.DEC.2003 13:44:32

PPSD (CH Mid)



Date: 4.DEC.2003 13:41:39

PPSD (CH High)



Date: 4.DEC.2003 13:46:58

7.3 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in15.209(a).

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/27/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004
Horn Antenna	EMCO	3115	N/A	02/24/2004

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
   (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
   (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.

Band Edges Test Data (CH-Low)

Detector mode: Peak **Polarity: Vertical**



Date: 29.DEC.2003 13:37:55

Detector mode: Average **Polarity: Vertical**



Date: 29.DEC.2003 13:42:12

Detector mode: Peak **Polarity: Horizontal**



Date: 29.DEC.2003 13:33:40

Detector mode: Average **Polarity: Horizontal**



Date: 29.DEC.2003 13:35:33

Band Edges Test Data (CH-High)

Detector mode: Peak Polarity: Vertical



Date: 29.DEC.2003 13:17:41

Detector mode: Average Polarity: Vertical



Date: 29.DEC.2003 13:27:02

Detector mode: Peak **Polarity: Horizontal**



Date: 29.DEC.2003 13:29:13

Detector mode: Average **Polarity: Horizontal**



Date: 29.DEC.2003 13:25:59

7.4 FREQUENCY SEPARATION

LIMIT

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/28/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = middle of hopping channel.
4. Set the spectrum analyzer as RBW, VBW=100kHz, Adjust Span to 5 MHz, Sweep = auto.
5. Max hold. Mark 3 Peaks of hopping channel and record the 3 peaks frequency.

TEST RESULTS

No non-compliance noted

Test Data

Channel Separation (MHz)	20dB Bandwith (kHz)	Limit (kHz)	Result
1.00	426.00	>25	Pass

Test Plot

Measurement of Channel Separation



Date: 4.DEC.2003 13:35:53

Measurement of 20dB Bandwidth



Date: 4.DEC.2003 13:

7.5 NUMBER OF HOPPING FREQUENCY

LIMIT

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands shall use at least 75 hopping frequencies.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/28/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set spectrum analyzer Start=2400MHz, Stop = 2441.5MHz, Sweep = 250s and Start=2441.5MHz, Stop = 2483.5MHz, Sweep = 250s.
4. Set the spectrum analyzer as RBW, VBW=100kHz,
5. Max hold, view and count how many channel in the band.

TEST RESULTS

No non-compliance noted

Test Data

Result (No. of CH)	Limit (No. of CH)	Result
79	>75	PASS

Test Plot

Channel Number

2.4 GHz – 2.441 GHz



Date: 4.DEC.2003 13:31:36

2.441 GHz – 2.4835 GHz



Date: 4.DEC.2003 13:33:06

7.6 TIME OF OCCUPANCY (DWELL TIME)

LIMIT

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	04/28/2004
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set center frequency of spectrum analyzer = operating frequency.
4. Set the spectrum analyzer as RBW, VBW=10kHz, Span = 0Hz, Adjust Sweep = 100ms / RBW= 1MHz, VBW=3MHz, Span = 0Hz, Adjust Sweep = 2ms.
5. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

No non-compliance noted

Test Data

DH 1

CH Low: 0.42 * (1600/2)/79 * 30 = 127.59 (ms)
CH Mid: 0.42 * (1600/2)/79 * 30 = 127.59 (ms)
CH High: 0.42 * (1600/2)/79 * 30 = 127.59 (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	0.42	127.59	30.00	400.00	PASS
Mid	0.42	127.59	30.00		PASS
High	0.42	127.59	30.00		PASS

DH 3

CH Low: 1.68 * (1600/4)/79 * 30 = 255.19 (ms)
CH Mid: 1.68 * (1600/4)/79 * 30 = 255.19 (ms)
CH High: 1.68 * (1600/4)/79 * 30 = 255.19 (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	1.68	255.19	30.00	400.00	PASS
Mid	1.68	255.19	30.00		PASS
High	1.68	255.19	30.00		PASS

DH 5

CH Low: 2.92 * (1600/6)/79 * 30 = 295.7 (ms)
CH Mid: 2.92 * (1600/6)/79 * 30 = 295.7 (ms)
CH High: 2.92 * (1600/6)/79 * 30 = 295.7 (ms)

CH	Pulse Time (ms)	Total of Dwell (ms)	Period Time (s)	Limit (ms)	Result
Low	2.92	295.70	30.00	400.00	PASS
Mid	2.92	295.70	30.00		PASS
High	2.92	295.70	30.00		PASS

Test Plot

DH 1

(CH Low)



Date: 4.DEC.2003 14:23:12

(CH Mid)



Date: 4.DEC.2003 14:25:55

(CH High)



Date: 4.DEC.2003 14:27:37

DH 3

(CH Low)



Date: 4.DEC.2003 14:32:28

(CH Mid)



Date: 4.DEC.2003 14:30:56

(CH High)



Date: 4.DEC.2003 14:29:33

DH 5
(CH Low)



Date: 4.DEC.2003 14:36:20

(CH Mid)



Date: 4.DEC.2003 14:37:44

(CH High)



Date: 4.DEC.2003 14:42:21

7.7 RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	Bluekite
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☒ Others Bluetooth: 2402GHz ~ 2480GHz
Device category	☒ Portable (<20cm separation) ☐ Mobile (>20cm separation) ☐ Others _____
Exposure classification	☐ Occupational/Controlled exposure *(S = 5mW/cm^2)* ☒ General Population/Uncontrolled exposure *(S=1mW/cm^2)*
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	2.92dBm (1.96mW)
Antenna gain (Max)	2.66 dBi (Numeric gain:1.845)
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Note:

1. *The maximum output power is 2.92dBm (1.96mW) at 2402MHz (with 1.845 numeric antenna gain.)*
2. *DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.*
3. *For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.*

TEST RESULTS

No non-compliance noted.

(SAR evaluation is not required for the PORTABLE device while its maximum output power is lower than the general population low threshold: $60/f_{(GHz)}=60/2.441=24.58mW$)

MPE evaluation

Not applicable.

7.8 RADIATED EMISSIONS

LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

Note: *Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength (µV/m at 3-meter)	Field Strength (dBµV/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

MEASUREMENT EQUIPMENT USED

Open Area Test Site #3				
Name of Equipment	**Manufacturer**	**Model**	**Serial Number**	**Calibration Due**
Spectrum Analyzer	Agilent	E4446A	US42510252	04/27/2004
EMI Test Receiver	R&S	ESVS20	838804/004	01/08/2004
Pre-Amplifier	HP	8447D	2944A09173	03/02/2004
Bilog Antenna	SCHWAZBECK	VULB9163	145	07/05/2004
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R
RF Switch	ANRITSU	MP59B	M53867	N.C.R
Site NSA	C&C	N/A	N/A	09/06/2004
Horn Antenna	EMCO	3115	00022250	03/15/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration

Below 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

Conducted Spurious Emission Measurement Result

CH Low

30MHz – 2.9GHz



Date: 4.DEC.2003 14:14:50

2.9GHz – 26.5GHz



Date: 4.DEC.2003 14:16:02

CH Mid

30MHz – 2.9GHz



Date: 4.DEC.2003 14:12:04

2.9GHz – 26.5GHz



Date: 4.DEC.2003 14:13:32

CH High

30MHz – 2.9GHz



Date: 4.DEC.2003 14:06:52

2.9GHz – 26.5GHz



Date: 4.DEC.2003 14:07:47

Radiated Spurious Emission Measurement Result

Below 1 GHz

Operation Mode:	TX CH Low Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
132.60	V	Peak	18.53	11.13	29.66	43.50	-13.84
266.25	V	Peak	12.81	15.81	28.62	46.00	-17.38
344.33	V	Peak	16.92	17.88	34.80	46.00	-11.20
664.00	V	Peak	11.03	25.13	36.16	46.00	-9.84

246.00	H	Peak	12.29	16.15	28.44	46.00	-17.56
344.33	H	Peak	17.67	17.88	35.55	46.00	-10.45
479.67	H	Peak	11.62	21.56	33.18	46.00	-12.82
499.50	H	Peak	4.37	10.16	22.49	46.00	-23.51
562.50	H	Peak	8.44	24.55	32.99	46.00	-13.01

Notes:

1. *Measuring frequencies from 30 MHz to the 1GHz.*
2. *Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.*
3. *Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.*

Operation Mode:	TX CH Mid Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
133.05	V	Peak	18.85	16.15	35.00	43.50	-8.50
344.33	V	Peak	17.59	17.88	35.47	46.00	-10.53
499.50	V	Peak	8.82	22.49	31.31	46.00	-14.69
661.67	V	Peak	8.72	25.09	33.81	46.00	-12.19
930.00	V	Peak	2.96	28.58	31.54	46.00	-14.46

246.00	H	Peak	12.63	16.15	28.78	46.00	-17.22
344.33	H	Peak	20.59	17.88	38.47	46.00	-7.53
442.33	H	Peak	14.63	20.25	34.88	46.00	-11.12
499.50	H	Peak	12.16	22.49	34.65	46.00	-11.35
566.00	H	Peak	8.18	24.63	32.81	46.00	-13.19

Notes:

1. *Measuring frequencies from 30 MHz to the 1GHz.*
2. *Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.*
3. *Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.*

Operation Mode:	TX CH High Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
133.05	V	Peak	17.68	11.11	28.79	43.50	-14.71
266.25	V	Peak	21.81	15.92	37.73	46.00	-8.27
344.33	V	Peak	17.76	17.88	35.64	46.00	-10.36
498.33	V	Peak	10.52	22.43	32.95	46.00	-13.05
661.67	V	Peak	9.71	25.09	34.80	46.00	-11.20

266.25	H	Peak	11.96	16.15	28.11	46.00	-17.89
344.33	H	Peak	20.26	17.88	38.14	46.00	-7.86
480.83	H	Peak	12.58	21.61	34.19	46.00	-11.81
566.00	H	Peak	9.18	24.63	33.81	46.00	-12.19
960.33	H	Peak	5.90	29.05	34.95	54.00	-19.05

Notes:

1. *Measuring frequencies from 30 MHz to the 1GHz.*
2. *Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.*
3. *Data of measurement within this frequency range shown " - " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.*
4. *The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.*

Above 1 GHz

Operation Mode:	TX CH Low Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1440.00	V	47.34	---	-8.00	39.34	---	74.00	54.00	-14.66	Peak
1683.33	V	44.84	---	-6.34	38.50	---	74.00	54.00	-15.50	Peak
1983.33	V	43.00	---	-4.50	38.50	---	74.00	54.00	-15.50	Peak
4791.67	V	43.50	---	3.22	46.72	---	74.00	54.00	-7.28	Peak

1060.00	H	48.67	---	-10.01	38.66	---	74.00	54.00	-15.34	Peak
1070.00	H	48.50	---	-9.94	38.56	---	74.00	54.00	-15.44	Peak
1216.67	H	46.00	---	-8.95	37.05	---	74.00	54.00	-16.95	Peak
1440.00	H	50.00	---	-8.00	42.00	---	74.00	54.00	-12.00	Peak
4800.00	H	45.84	---	3.24	49.08	---	74.00	54.00	-4.92	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.

4. Spectrum setting:

a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.

b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode:	TX CH Mid Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1440.00	V	47.67	---	-8.00	39.67	---	74.00	54.00	-14.33	Peak
1726.67	V	46.50	---	-6.11	40.39	---	74.00	54.00	-13.61	Peak
4875.00	V	40.34	---	3.40	43.74	---	74.00	54.00	-10.26	Peak

1003.33	H	45.84	---	-10.44	35.40	---	74.00	54.00	-18.60	Peak
1440.00	H	49.84	---	-8.00	41.84	---	74.00	54.00	-12.16	Peak
4875.00	H	44.84	---	3.40	48.24	---	74.00	54.00	-5.76	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.

4. Spectrum setting:

a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.

b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

Operation Mode:	TX CH High Mode	**Test Date:**	January 6, 2003
Temperature:	20°C	**Tested by:**	Roy
Humidity:	70 % RH	**Polarity:**	Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1063.33	V	50.17	---	-9.99	40.18	---	74.00	54.00	-13.82	Peak
1440.00	V	46.50	---	-8.00	38.50	---	74.00	54.00	-15.50	Peak
1703.33	V	44.50	---	-6.23	38.27	---	74.00	54.00	-15.73	Peak
4950.00	V	43.67	---	3.56	47.23	---	74.00	54.00	-6.77	Peak

1063.33	H	48.50	---	-9.99	38.51	---	74.00	54.00	-15.49	Peak
1076.67	H	50.00	---	-9.89	40.11	---	74.00	54.00	-13.89	Peak
1440.00	H	48.50	---	-8.00	40.50	---	74.00	54.00	-13.50	Peak
2510.00	H	44.67	---	-2.83	41.84	---	74.00	54.00	-12.16	Peak
4950.00	H	45.67	---	3.56	49.23	---	74.00	54.00	-4.77	Peak

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.

2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.

3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.

4. Spectrum setting:

a. Peak Setting 1GHz - 26GHz, RBW = 1MHz, VBW = 1MHz, Sweep time = 200 ms.

b. AV Setting 1GH z- 26GHz, RBW = 1MHz, VBW = 10Hz, Sweep time = 200 ms.

7.9 POWERLINE CONDUCTED EMISSIONS

LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	847793/012	12/20/2004
LISN	R&S	ESH2-Z5	843285/010	12/15/2004
LISN	EMCO	3825/2	9003-1628	07/25/2004

Remark: *Each piece of equipment is scheduled for calibration once a year.*

Test Configuration

1. The conducted emission tests were performed in the test site, using the setup in accordance with the ANSI C63.4-2001.
2. The EUT was plug-in the host PC via USB port. The host PC system was placed on the center of the back edge on the test table. The peripherals like modem, monitor printer, K/B, and mouse were placed on the side of the host PC system. The rear of the EUT and peripherals were placed flushed with the rear of the tabletop.
3. The keyboard was placed directly in the front of the monitor, flushed with the front tabletop. The mouse was placed next to the Keyboard, flushed with the back of keyboard.
4. The spacing between the peripherals was 10 centimeters.
5. External I/O cables were draped along the edge of the test table and bundle when necessary.
6. The host PC system was connected with 110Vac/60Hz power source.

The EUT is set to transmit in a continuous mode.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Operation Mode:	TX + RX mode	**Test Date:**	December 29, 2003
Temperature:	22°C	**Humidity:**	67% RH
Tested by:	Roy		

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Note
0.150	58.80	44.40	66.00	56.00	-7.20	-11.60	L1
0.495	42.90	---	56.08	46.08	-13.18	---	L1
0.625	40.50	---	56.00	46.00	-15.50	---	L1
0.945	40.50	---	56.00	46.00	-15.50	---	L1
2.050	38.70	---	56.00	46.00	-17.30	---	L1
15.850	31.10	---	60.00	50.00	-28.90	---	L1
0.150	57.60	44.80	66.00	56.00	-8.40	-11.20	L2
0.460	42.80	---	56.69	46.69	-13.89	---	L2
0.700	41.30	---	56.00	46.00	-14.70	---	L2
0.930	40.80	---	56.00	46.00	-15.20	---	L2
2.700	38.80	---	56.00	46.00	-17.20	---	L2
3.750	35.80	---	56.00	46.00	-20.20	---	L2

Note:

1. *The measuring frequencies range between 0.15 MHz and 30 MHz.*
2. *The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.*
3. *"---" denotes the emission level was or more than 2dB below the Average limit, and no re-check was made.*
4. *The IF bandwidth of SPA between 0.15MHz and 30MHz was 10KHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9KHz.*
5. *L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)*

Test Data Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)